ALBEMARLE, NC

Orig-A, 02NOV23 (23306) (FAA) ELEV **609**

STANLY COUNTY (VUJ)

RADAR-1 128.325 307.8

	RWY	GP/TCH/RPI	CAT	DH/ MDA-VIS	HAT/ HAA	CEIL-VIS
PAR	22L	3.0°/40/887	ABCD	**916**-1	332	(400-1)

Rwy 22L helicopter visibility reduction below ¾ SM not authorized.
Procedure NA when control tower closed.

BEAUFORT, SC

Amdt 4, 17APR25 (25107) (FAA) ELEV **9**

BEAUFORT EXEC (ARW)

RADAR-1 125.125 292.125

	RWY	GP/TCH/RPI	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS
ASR	25		ABC	**380**-1	372	(400-1)	D	NA		
CIRCLING	ALL RWY		AB D	**480**-1 NA	471	(500-1)	C	**640**-1¾	631	(700-1¾)

When Beaufort Class D not in effect procedure NA.
VGSI and descent angles not coincident.

26 NOV 2026 to 24 DEC 2026

26 NOV 2026 to 24 DEC 2026

BEAUFORT MCAS (MERRITT FLD) (KNBC)

Beaufort, SC Amdt 8 25DEC25 (25359) (USN) ELEV **37**

RADAR - (E) 123.7x 298.875x 317.775x 323.275x 338.35x 372.0x 379.275x

	RWY	GP/TCH/RPI	CAT	DH/ MDA-VIS	HAT/ HATh/ HAA	CEIL-VIS
PAR[1]	5[2 3]	3.0°/38/778	ABCDE	**137**-¼	100	(100-¼)
	23[2 4]	3.0°/43/818	ABCDE	**116**-¼	100	(100-¼)
	14[5]	3.0°/40/766	ABCDE	**232**-¾	200	(200-¾)
	32[6]	3.0°/41/785	ABCDE	**225**-¾	200	(200-¾)
PAR W/O GS[1]	23[7]		ABCDE	**360**-⅝	344	(400-⅝)
	14		ABCDE	**400**-1⅛	368	(400-1⅛)
	5[8]		ABCDE	**440**-¾	363	(400-¾)
	32		ABCDE	**440**-1⅛	415	(500-1⅛)
ASR[1]	23[7]		AB	**360**-½	344	(400-½)
			CDE	**360**-⅝	344	(400-⅝)
	14		AB	**420**-1	388	(400-1)
			CDE	**420**-1⅛	388	(400-1⅛)
	5[9]		AB	**480**-¾	443	(500-¾)
			CDE	**480**-1	443	(500-1)
	32		AB	**500**-1	475	(500-1)
			CDE	**500**-1⅜	475	(500-1⅜)
CIR	5, 14, 23, 32		AB	**560**-1	523	(600-1)
			C	**580**-1½	543	(600-1½)
			D	**600**-2	563	(600-2)
			E	**740**-2½	703	(800-2½)

[1]No-NOTAM MP 1200-2000Z++ Sat.
[2]When ALS inop, increase vis to ½ mile.
[3]WCH for Group 3 is 18ft, Group 4 is 13ft.
[4]WCH for Group 4 is 18'.
[5]WCH for Group 4 is 15'.
[6]WCH for Group 4 is 16'.
[7]When ALS inop, increase vis to 1 mile.
[8]When ALS inop, increase vis to 1⅛ miles.
[9]When ALS inop, increase vis CAT AB to 1 mile, CAT CDE to 1⅜ miles.

CODED LOST COMMUNICATIONS
SCARLET
TACAN equipped aircraft: If no transmissions are received for one minute in the pattern or 5/15 seconds on final approach, attempt contact with Beaufort Tower on 342.875/119.05 and proceed VFR. If unable, climb and maintain two thousand six hundred, proceed direct COSAW, execute TACAN Rwy 23 approach.

GOLD
RNAV/GPS equipped aircraft: If no transmissions are received for one minute in the pattern or 5/15 seconds on final approach, attempt contact with Beaufort Tower on 342.875/119.05 and proceed VFR. If unable, climb and maintain two thousand eight hundred, proceed direct HOWEL and execute RNAV/GPS Rwy 23 approach.

CHERRY POINT MCAS (CUNNINGHAM FLD) (KNKT)

Cherry Point, NC Amdt 5 02NOV23 (23306) (USN) ELEV **29**

RADAR - (E) 118.35x 120.15x 275.6x 299.6x 305.2x 314.8x 320.4x 337.2x 348.0x

	RWY	GP/TCH/RPI	CAT	DA/ MDA-VIS	HAT/ HATh/ HAA	CEIL-VIS
PAR	32L[1 2]	3.0°/50/926	ABCDE	**125**-¼	100	(100-¼)
	5R[3]	3.0°/55/1022	ABCDE	**126**-½	100	(100-½)
	14L[4]	3.0°/55/1050	ABCDE	**126**-½	100	(100-½)
	23R[5]	3.0°/56/1066	ABCDE	**123**-½	100	(100-½)
ASR	23R[6]		AB	**400**-½	377	(400-½)
			CDE	**400**-⅝	377	(400-⅝)
	32L[2 6]		AB	**400**-½	375	(400-½)
			CDE	**400**-⅝	375	(400-⅝)
	5R[3]		AB	**500**-1	474	(500-1)
			CDE	**500**-1⅜	474	(500-1⅜)
	14L[4]		AB	**500**-1	474	(500-1)
			CDE	**500**-1⅜	474	(500-1⅜)
CIR	All Rwys		AB	**580**-1	551	(600-1)
			C	**580**-1½	551	(600-1½)
			D	**580**-2	551	(600-2)
			E	**700**-2½	671	(700-2½)

[1]When ALS inop, increase vis to ½ mile.
[2]VGSI and descent angle/PAR glidepath not coincident (VGSI Angle 3.00/TCH 78).
[3]VGSI and descent angle/PAR glidepath not coincident (VGSI Angle 3.00/TCH 73).
[4]VGSI and descent angle/PAR glidepath not coincident (VGSI Angle 3.00/TCH 71).
[5]CAUTION: PAR RPI and PAPI RRP not coincident.
[6]When ALS inop, increase vis to 1 mile.

26 NOV 2026 to 24 DEC 2026

NEW RIVER MCAS (MCCUTCHEON FLD) (KNCA)

Jacksonville, NC Amdt 5 01OCT26 (26274) (USN) ELEV **26**

RADAR - (U) 118.575 124.85 279.575 317.75 338.25 350.225 353.875 377.125

	RWY	GP/TCH/RPI	CAT	DH/ MDA-VIS	HAT/ HATh/ HAA	CEIL-VIS
PAR	1[1]	3.0°/46/879	ABCD	**124**-¼	100	(100-¼)
	5[2]	3.0°/37/808	ABCD	**126**-½	100	(100-½)
	19[3]	3.0°/41/759	ABCD	**123**-½	100	(100-½)
	23[2]	3.0°/37/672	ABCD	**124**-½	100	(100-½)
ASR	19[4]		AB	**460**-1	437	(500-1)
			CDE	**460**-1¼	437	(500-1¼)
	23[5]		AB	**460**-1	436	(500-1)
			CDE	**460**-1¼	436	(500-1¼)
	5[6]		AB	**480**-1	454	(500-1)
			CDE	**480**-1⅜	454	(500-1⅜)
CIR	All Rwys		AB	**540**-1	514	(600-1)
			C	**700**-2	674	(700-2)
			D	**700**-2¼	674	(700-2¼)
			E	**700**-2½	674	(700-2½)

[1]When ALS inop, increase vis to ½ mile.
[2]CAUTION: TCH (37') is less than the min TCH (45') for aircraft similar to B-767/777, KC-10, B-1, C-5, VC-25.
[3]CAUTION: TCH (41') is less than the min TCH (45') for aircraft similar to B-767/777, KC-10, B-1, C-5, VC-25.
[4]Step Down Fix 2 NM from thld, 640 min.
[5]Step Down Fix 2 NM from thld, 560 min.
[6]Step Down Fix 2 NM from thld, 600 min.

26 NOV 2026 to 24 DEC 2026