



U.S. Department of Transportation
Federal Aviation Administration
Washington, DC

Master Minimum Equipment List (MMEL)

Revision: 5
Date: XX/XX/XXXX

Dassault Aviation Falcon 2000EX

Approved by the Aircraft Evaluation Division
Federal Aviation Administration (FAA)
Air Carrier Branch
AFS-100
800 Independence Avenue, S.W.
Washington, DC 20591

AED Email: 9-AVS-AFS-100@faa.gov

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. I

AIRCRAFT:
Falcon 2000EX**TABLE OF CONTENTS AND CONTROL PAGE**

SYSTEM NO.	SYSTEM	PAGE NO.	REV NO.	DATE
--	Cover Page	--	5	XX/XX/XXXX
--	Table of Contents and Control Page	I	5	XX/XX/XXXX
--	Log of Revisions	II	5	XX/XX/XXXX
--	Highlights of Change	III thru VIII	5	XX/XX/XXXX
--	Preamble	IX	5	XX/XX/XXXX
--	Guidelines for (M) and (O) Procedures	X	5	XX/XX/XXXX
21	Air Conditioning	21-1 thru 9	5	XX/XX/XXXX
22	Autoflight	22-1 thru 3	5	XX/XX/XXXX
23	Communications	23-1 thru 9	5	XX/XX/XXXX
24	Electrical Power	24-1 thru 2	5	XX/XX/XXXX
25	Equipment/Furnishings	25-1 thru 15	5	XX/XX/XXXX
26	Fire Protection	26-1	5	XX/XX/XXXX
27	Flight Controls	27-1 thru 5	5	XX/XX/XXXX
28	Fuel	28-1 thru 8	5	XX/XX/XXXX
29	Hydraulic Power	29-1 thru 2	5	XX/XX/XXXX
30	Ice and Rain Protection	30-1 thru 5	5	XX/XX/XXXX
31	Indicating/Recording Systems	31-1 thru 3	5	XX/XX/XXXX
32	Landing Gear	32-1 thru 4	5	XX/XX/XXXX
33	Lights	33-1 thru 5	5	XX/XX/XXXX
34	Navigation	34-1 thru 17	5	XX/XX/XXXX
35	Oxygen	35-1 thru 3	5	XX/XX/XXXX
36	Pneumatic	36-1 thru 4	5	XX/XX/XXXX
38	Water/Waste	38-1 thru 2	5	XX/XX/XXXX
45	Central Maintenance System	45-1	5	XX/XX/XXXX
46	Information Systems	46-1 thru 2	5	XX/XX/XXXX
49	Airborne Auxiliary Power	49-1 thru 3	5	XX/XX/XXXX
52	Doors	52-1	5	XX/XX/XXXX
73	Engine Fuel and Control	73-1	5	XX/XX/XXXX
74	Ignition	74-1	5	XX/XX/XXXX
77	Engine Indicating	77-1	5	XX/XX/XXXX
78	Engine Exhaust	78-1	5	XX/XX/XXXX
79	Engine Oil	79-1	5	XX/XX/XXXX
80	Starting	80-1 thru 2	5	XX/XX/XXXX

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		MASTER MINIMUM EQUIPMENT LIST	
REVISION NO. 5 DATE: XX/XX/XXXX		PAGE NO. II	
AIRCRAFT: Falcon 2000EX		LOG OF REVISIONS	
REV NO.	DATE		
Original	09/26/2003		
1	03/18/2010		
2	11/18/2016		
3	07/05/2018		
4	06/24/2020		
5	XX/XX/XXXX		

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION	MASTER MINIMUM EQUIPMENT LIST
REVISION NO. 5 DATE: XX/XX/XXXX	PAGE NO. III
AIRCRAFT: Falcon 2000EX	HIGHLIGHTS OF CHANGE

The following changes are the Highlights of Changes for **Revision 5**. It is the result of a public Flight Operations Evaluation Board (FOEB) meeting held on 09/26/2024.

PAGE NO.	EXPLANATION OF CHANGE
General	Minor editorial corrections were made throughout the document that do not affect the relief but are indicated with change bars. These editorial corrections may be adopted in Minimum Equipment Lists (MEL) at the operator's discretion.
Definitions and Preamble	Updated to reference FAA Dynamic Regulatory System (DRS).
Guidelines for (M) and (O) Procedures	Added reference to Dassault Aviation procedures guide.
21-1	Item 21-30-05: Deleted dispatch case 21-30-05-A and modified remaining proviso.
21-2	Item 21-30-09-01-A: Added note. Item 21-30-09-01-B: Modified proviso. Item 21-30-09-02-B: Modified proviso. Item 21-30-09-03-B: Modified proviso.
21-3	Item 21-30-10: Modified proviso. Item 21-30-11: Modified proviso.
21-4	Item 21-32-00-B: Modified provisos.
21-7	Item 21-60-00-40: Modified provisos.
22-2	Item 22-10-01-A: Corrected typographical error.
23-2	Item 23-15-00-A: Modified sequence number. Item 23-15-00-B: Added dispatch case.
23-4	Item 23-20-11-B: Added dispatch case.
23-5	Item 23-50-00-30: Modified proviso.
23-6	Item 23-50-02: Modified applicability.
23-5 thru 7	Item 23-50-80: Modified relief IAW PL-058.

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		MASTER MINIMUM EQUIPMENT LIST
REVISION NO. 5 DATE: XX/XX/XXXX		PAGE NO. IV
AIRCRAFT: Falcon 2000EX		HIGHLIGHTS OF CHANGE
PAGE NO.	EXPLANATION OF CHANGE	
23-7	Item 23-50-80-10-C: Modified proviso. Item 23-50-80-10-D: Modified item name. Item 23-50-80-20-B: Deleted duplicate item name. Item 23-50-80-20-D: Added item.	
23-8	Item 23-50-80-30-A: Modified proviso. Item 23-50-80-30-B: Removed duplicate item name. Item 23-50-80-30-C: Modified proviso. Item 23-50-80-30-D: Removed duplicate item name.	
23-9	Item 23-50-95: Deleted dispatch case. Item 23-52-10: Added relief item IAW PL-09.	
25-3	Item 25-21-01: Added (O) procedure, modified proviso and note.	
25-4	Item 25-21-01-12-A: Modified provisos. Item 25-21-01-12-B: Modified provisos. Item 25-21-01-13: Modified provisos. Item 25-21-01-15-A: Modified provisos. Item 25-21-01-15-B: Modified provisos.	
25-5	Item 25-21-01-20-A: Divided item into two conditions, modified provisos. Item 25-21-01-20-B: Divided item into two conditions, modified provisos. Item 25-21-01-30: Modified proviso. Item 25-21-01-35: Modified item name. Item 25-21-01-35-A: Modified item name. Item 25-21-01-35-B: Modified item name.	

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		MASTER MINIMUM EQUIPMENT LIST
REVISION NO. 5 DATE: XX/XX/XXXX		PAGE NO. V
AIRCRAFT: Falcon 2000EX		HIGHLIGHTS OF CHANGE
PAGE NO.	EXPLANATION OF CHANGE	
25-6	Item 25-26-10: Added item. Item 25-26-10-01: Added item.	
25-8	Item 25-50-05-03: Modified proviso. Item 25-60-01-A: Modified proviso IAW PL-132. Item 25-60-01-B: Modified relief IAW PL-132. Item 25-60-01-10: Added item IAW PL-132.	
25-9	Item: 25-60-10-A: Modified proviso IAW PL-132. Item 25-60-10-B: Modified proviso IAW PL-132. Item 25-60-10-10: Added item IAW PL-132.	
25-10	Item 25-60-11-A: Modified proviso IAW PL-132. Item 25-60-11-B: Modified proviso IAW PL-132. Item 25-60-11-10: Added item IAW PL-132.	
25-11	Item 25-61-00-05-A: Modified proviso. Item 25-61-00-05-B: Modified proviso.	
25-12	Item 25-63-00: Modified item name.	
25-13	Item 25-64-13: Modified item name. Item 25-64-13-A: Modified provisos. Item 25-64-13-B: Added dispatch case. Item 25-64-17: Added item.	
25-14	Item 25-64-21-A: Added dispatch case, modified proviso IAW PL-132. Item 25-64-21-B: Added dispatch case, modified proviso IAW PL-132. Item 25-64-21-10: Added item IAW PL-132.	

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		MASTER MINIMUM EQUIPMENT LIST
REVISION NO. 5 DATE: XX/XX/XXXX		PAGE NO. VI
AIRCRAFT: Falcon 2000EX		HIGHLIGHTS OF CHANGE
PAGE NO.	EXPLANATION OF CHANGE	
26-1	Item 26-10-25: Modified proviso. Item 26-20-15: Modified item name and provisos IAW PL-132. Item 26-20-15-10: Added item IAW PL-132.	
27-2	Item 27-14-10: Modified provisos. Item 27-14-11: Modified proviso.	
27-3	Item 27-24-10: Modified provisos.	
27-4	Item 27-40-10: Modified provisos.	
27-5	Item 27-80-02: Deleted item.	
30-5	Item 30-80-00-A: Added dispatch case.	
31-1 thru 2	Item 31-31-32: Modified IAW PL-087.	
31-2	Item 31-32-00-A: Modified proviso. Item 31-32-00-B: Modified proviso.	
33-2	Item 33-20-02: Modified item name; modified proviso; added (O) procedure. Item 33-40-00-10-A: Modified proviso. Item 33-40-00-10-B: Modified repair category, number installed, and provisos. Item 33-40-00-20: Modified proviso.	
33-3	Item 33-40-01-10: Modified proviso.	
33-4	Item 33-40-70-A: Added dispatch case. Item 33-40-70-B: Modified sequence number.	
34-2	Item 34-15-03: Modified proviso.	
34-4	Item 34-25-00: Modified proviso.	
34-7 thru 9	Item 34-45-01: Modified to align with PL-054.	
34-9 thru 11	Item 34-45-02: Modified to align with PL-054.	

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		MASTER MINIMUM EQUIPMENT LIST
REVISION NO. 5 DATE: XX/XX/XXXX		PAGE NO. VII
AIRCRAFT: Falcon 2000EX		HIGHLIGHTS OF CHANGE
PAGE NO.	EXPLANATION OF CHANGE	
34-11	Item 34-45-03: Modified to align with PL-054.	
34-13	Item 34-55-00: Modified item name to align with PL-105. Item 34-55-00-A: Modified repair category and proviso IAW PL-105. Item 34-55-00-B: Modified repair category and proviso IAW PL-105. Item 34-55-00-C: Modified repair category and proviso IAW PL-105.	
34-14	Item 34-55-00-10: Modified item name IAW PL-105. Item 34-55-00-10-A: Modified repair category and proviso IAW PL-105. Item 34-55-00-10-B: Modified remarks IAW PL-105. Item 34-55-00-10-C: Added dispatch case IAW PL-105.	
34-15	Item 34-55-00-20: Modified item name IAW PL-105. Item 34-55-00-20-A: Modified repair category and proviso IAW PL-105. Item 34-55-00-20-B: Modified proviso IAW PL-105. Item 34-55-00-20-C: Added dispatch case IAW PL-105.	
34-16	Item 34-55-00-30: Modified item name IAW PL-105.	
35-2	Item 35-30-05: Modified item name and provisos; added notes IAW PL-132. Item 35-30-05-10: Added item IAW PL-132.	
35-3	Item 35-30-10: Added item IAW PL-132. Item 35-30-10-10: Added item IAW PL-132.	
36-1	Item 36-00-01-20: Modified proviso.	
38-1	Item 38-30-09-10-B: Modified proviso.	
38-2	Item 38-30-09-20-B: Modified proviso.	
45-1	Item 45-90-00-A: Modified repair category and proviso. Item 45-90-00-B: Added dispatch case.	

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		MASTER MINIMUM EQUIPMENT LIST
REVISION NO. 5 DATE: XX/XX/XXXX		PAGE NO. VIII
AIRCRAFT: Falcon 2000EX		HIGHLIGHTS OF CHANGE
PAGE NO.	EXPLANATION OF CHANGE	
46-1	Item 46-20-00-02: Deleted item IAW PL-121. Added note for clarity. Item 46-20-00-03-A: Modified sequence number, added (O) procedure, and modified proviso. Item 46-20-00-03-B: Added dispatch case IAW PL-121. Item 46-20-00-04-A: Modified sequence number and proviso. Item 46-20-00-04-B: Added dispatch case IAW PL-121.	
46-2	Item 46-20-00-05-A: Modified sequence number, and proviso. Item 46-20-00-05-B: Added dispatch case IAW PL-121.	
52-1	Item 52-30-00-01: Modified proviso.	
79-1	Item 79-30-02: Deleted item.	

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION	MASTER MINIMUM EQUIPMENT LIST
REVISION NO. 5 DATE: XX/XX/XXXX	PAGE NO. IX
AIRCRAFT: Falcon 2000EX	DEFINITIONS AND PREAMBLE

DEFINITIONS

Refer to the current FAA MMEL Policy Letter 25, MMEL and MEL Definitions, found on the FAA Dynamic Regulatory System (DRS) website at <https://drs.faa.gov>.

PREAMBLE

For operations under 14 CFR parts 91 subpart K (part 91K), 121, 125, 125 LODA, 129, and 135, refer to the current FAA MMEL Policy Letter PL-34, MMEL and MEL Preamble. For operations under 14 CFR part 91, refer to current FAA MMEL Policy Letter PL-36, 14 CFR Part 91 MEL Approval and Preamble. Both Policy Letters are found on the FAA Dynamic Regulatory System (DRS) website at <https://drs.faa.gov>.

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION	MASTER MINIMUM EQUIPMENT LIST
REVISION NO. 5 DATE: XX/XX/XXXX	PAGE NO. X
AIRCRAFT: Falcon 2000EX	GUIDELINES FOR (M) AND (O) PROCEDURES

Guidelines for (M) and (O) Procedures are based on Dassault Aviation (M) and (O) Procedures for Falcon 2000EX, published by the aircraft manufacturer.

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 21-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
21-20-05	Cockpit Gasper	C	2	0	One or more may be inoperative provided at least one Cockpit Gasper remains in open position.	
21-20-10	Cold Fan Pressure Control Valve	C	1	0	(O) May be inoperative provided EFIS Fans are verified operative.	
21-20-15 ***	Glare Shield Cold Air Manual Control (Aircraft with M1992)	C	1	0	May be inoperative.	
21-20-16	Air Conditioning Distribution Lever	C	2	0	One or more may be inoperative provided affected lever is set to windshield position.	
21-30-00	Cabin Temperature Indicator	C	1	0	May be inoperative.	
21-30-05	UP-DN Manual Controller	C	1	0	(O) May be inoperative provided flight is conducted in an unpressurized configuration.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 21-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
21-30-09	Triple Cabin Indication					
21-30-09-01	Cabin Altitude Indication					
21-30-09-01-A		C	1	0	(O) May be inoperative provided: a) Cabin Differential Pressure Indication is verified operative, and b) Cabin Pressure Controller (CPC) is verified operative.	
					NOTE: A chart to convert cabin differential pressure to cabin altitude is provided to the crew in the associated operating procedure.	
21-30-09-01-B		C	1	0	(O) May be inoperative provided flight is conducted in an unpressurized configuration.	
21-30-09-02	Cabin Differential Pressure Indication					
21-30-09-02-A		C	1	0	(O) May be inoperative provided the Cabin Altitude Indication is verified operative.	
21-30-09-02-B		C	1	0	(O) May be inoperative provided flight is conducted in an unpressurized configuration.	
21-30-09-03	Cabin Vertical Speed Indication					
21-30-09-03-A		C	1	0	(O) May be inoperative provided the Cabin Altitude Indication and Cabin Differential Pressure Indication are verified operative.	
21-30-09-03-B		C	1	0	(O) May be inoperative provided flight is conducted in an unpressurized configuration.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 21-3

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
21-30-10	CABIN Warning Light	C	1	0	(O) May be inoperative provided: a) "CABIN" Aural Warning is verified operative, b) Cabin Altitude Indication is operative, c) CPC is verified operative, and d) Cabin altitude is limited to 8,000 ft. or below.	
21-30-11	"CABIN" Aural Warning	C	1	0	(O) May be inoperative provided: a) CABIN Warning Light is verified operative, b) Cabin Altitude Indication is operative, c) CPC is verified operative, and d) Cabin altitude is limited to 8,000 ft. or below.	
21-30-12	CABIN Warning Light and Aural Warning Test System	C	1	0	(O) May be inoperative provided: a) CPC is verified operative, and b) CABIN Warning Light and Aural Warning are verified operative.	
21-31-09	Nose Cone Fan	C	1	0	(M)(O) May be inoperative provided: a) Duration of ground operations is limited, b) Nose Cone Pressurization System is verified operative, c) NOSE CONE OVHT Warning System is verified operative, and d) NOSE CONE OVHT Warning is not displayed.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 21-4

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
21-32-00	CPC (Cabin Pressure Controller)					
21-32-00-A		C	1	0	(O) May be inoperative provided: a) Flight level is limited to FL 250 or below, b) Departure and destination airfield elevations are below 8,000 ft., c) CABIN Warning Light and "CABIN" Aural Warning are verified operative, d) UP-DN Manual Controller and DUMP mode are verified operative before each departure, e) Cabin Altitude, Cabin Differential Pressure, and Cabin Vertical Speed Indications are verified operative, f) UP-DN Manual Controller is set to the RH part of the white arc for takeoff, and g) Cabin Altitude, Cabin Differential Pressure, and Cabin Vertical Speed Indications are closely monitored during flight.	
21-32-00-B		C	1	0	(O) May be inoperative provided flight is conducted in an unpressurized configuration.	
21-32-00-01	ARINC Input Data Bus Function	C	3	-	May be inoperative.	
21-32-00-02	Discrete Input Data Function	C	2	0	One or more may be inoperative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 21-5

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	---

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
21-32-10	Cabin Pressurization LOW Rate Control	C	1	0	May be inoperative provided it remains in off position.	
21-51-13	Cabin Air Recirculation Valve	C	1	0	(O) May be inoperative provided: a) RECIRC switch is set to ISOL, and b) Recirculation Valve is verified in closed position before each departure.	
21-51-15	RECIRC ISOL Caution Light	C	1	0	May be inoperative provided Cabin Air Recirculation Valve is considered inoperative (item 21-51-13).	
21-52-00	ECU (Environmental Control Unit)	C	1	0	(O) May be inoperative provided: a) Flight is conducted in an unpressurized configuration, b) MANUAL Mode of Air Conditioning Valves is verified operative, c) Hot air flow is verified blowing at crew air distribution outlets, and d) EFIS Fans are verified operative.	
21-52-10	ECU OVHT Caution Light	C	1	0	May be inoperative provided ECU is considered inoperative (item 21-52-00).	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 21-6

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
21-52-31	ECU Bypass Valve	C	1	0	May be inoperative.	
21-60-00	TCS (Temperature Control System)					
21-60-00-10	Alarm Light Command Function (Auto Cockpit, Auto Cabin, and Manual Mode)	A	3	0	One or more may be inoperative provided: a) TCS fault codes are considered before each departure, and b) Repairs are made within 3 consecutive calendar-days.	
21-60-00-20	Turbine Temperature Control Function (Auto and Manual Mode)	A	6	0	One or more may be inoperative provided repairs are made within 2 consecutive calendar-days.	
21-60-00-30	AUTO Mode	A	2	0	(O) One or more may be inoperative provided: a) MANUAL mode is verified operative, and b) Repairs are made within 3 consecutive calendar-days.	
(Continued)						

REVISION NO. 5

PAGE NO. 21-7

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
21-60-00	TCS (Temperature Control System) (Cont'd)					
21-60-00-31	Thrust Lever Position Function	A	2	1	One may be inoperative provided: a) Thrust Levers are operative, and b) Repairs are made within 3 consecutive calendar-days.	
21-60-00-32	Computer Dialog Function (Cockpit and Cabin)	A	2	1	One may be inoperative provided repairs are made within 3 consecutive calendar-days.	
21-60-00-33	Compressor Overheat Sensor Function (Cockpit and Cabin)	A	2	1	One may be inoperative provided repairs are made within 3 consecutive calendar-days.	
21-60-00-34	CREW and PAX Auto Temperature Potentiometer Function	A	2	0	One or more may be inoperative provided repairs are made within 3 consecutive calendar-days.	
21-60-00-35	Cockpit and Cabin Duct Temperature Sensor Function	A	2	1	One may be inoperative provided repairs are made within 2 consecutive calendar-days.	
21-60-00-40	MANUAL Mode	C	1	0	(O) May be inoperative provided flight is conducted in an unpressurized configuration.	
21-60-00-41	CREW and PAX Manual Temperature Potentiometer Function	A	2	1	One may be inoperative provided repairs are made within 3 consecutive calendar-days.	
21-60-05	Cabin Duct Temperature Indication	C	1	0	May be inoperative.	
21-60-06	CABIN DUCT Switch					
21-60-06-10	Light Bulb	D	4	0	One or more may be inoperative.	

REVISION NO. 5

PAGE NO. 21-8

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
21-61-05	CREW Amber Light (Overhead Panel)	C	1	0	May be inoperative provided TCS fault codes are considered before each departure.	
21-61-05-10	Light Bulb	B	2	1	One may be inoperative provided TCS is operative in both AUTO and MAN modes.	
21-61-10	PAX Amber Light (Overhead Panel)	C	1	0	May be inoperative provided TCS fault codes are considered before each departure.	
21-61-10-10	Light Bulb	B	2	1	One may be inoperative provided TCS is operative in both AUTO and MAN mode.	
21-64-00	Cabin Temperature Remote Control	C	1	0	May be inoperative.	
21-64-02	Hot Conditioning Valve	C	2	1	(M) One may be inoperative provided: a) Flight level is limited to FL 410 or below, b) Manual Air Conditioning Interconnect Valve is set in open position, and c) Affected Hot Conditioning Valve is secured in closed position.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 21-9

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
----------------------------	---

21. Air Conditioning

Sequence No.	Item	1	2	3	4	Change Bar
21-64-03	Cold Conditioning Valve					
21-64-03-A		C	2	1	(M) One may be inoperative provided: a) Flight level is limited to FL 410 or below, and b) Affected Cold Conditioning Valve is secured in closed position.	
21-64-03-B		C	2	0	(M)(O) Both may be inoperative provided: a) Flight is conducted in an unpressurized configuration, b) EFIS Fans are verified operative, and c) Both Cold Conditioning Valves are secured in closed position.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 22-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

22. Autoflight

Sequence No.	Item	1	2	3	4	Change Bar
22-10-00	AP (Autopilot) Computer					
22-10-00-10	AP Function	B	1	0	(O) May be inoperative provided: a) Enroute operations or approaches do not require its use, b) Number of flight legs and flight leg durations are acceptable to the flightcrew, and c) Flying Duration Limitations of the operating procedure are applied.	
22-10-00-20	FD (Flight Director) Function	C	2	0	One or more may be inoperative provided: a) AP Function is not used (item 22-10-00-10), and b) Flight envelope is limited to MI 0.80. NOTE: Yaw damper and mach trim are not available.	
22-10-00-30	YD (Yaw Damper) Function	C	1	0	(O) May be inoperative provided: a) "R" label on PFD is not displayed, and b) Rudder is verified centered before each departure. NOTE: AP can be used without YD.	
22-10-00-40	MT (Mach Trim) Function	C	1	0	May be inoperative provided flight envelope is limited to MI 0.80.	
22-10-00-50	AP (Autopilot) Warning Light	C	1	0	(O) May be inoperative provided annunciation on EFIS and aural warning are verified operative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 22-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

22. Autoflight

Sequence No.	Item	1	2	3	4	Change Bar
22-10-01	Flight Guidance Panel					
22-10-01-A		C	1	0	May be inoperative provided: a) Altitude Select (ASEL) and courses functions are verified operative before each departure, b) AP Function is not used (item 22-10-00-10), and c) FD Function is not used (item 22-10-00-20).	
22-10-01-B		C	1	0	(O) May be inoperative provided: a) ASEL and course functions are verified operative before each departure, b) ALT mode is operative, c) Approaches do not require its use, d) Number of flight legs and flight leg durations are acceptable to the flightcrew, and e) Flying Duration Limitations of the operating procedure are applied.	
22-10-02	AP Rudder Linear Actuator	C	1	0	(O) May be inoperative provided: a) Rudder is visually verified centered before each departure, b) YD Function is considered inoperative (item 22-10-00-30), and c) AP Function is not used (item 22-10-00-10).	
22-10-05	Servomotor (Pitch and Roll)	B	2	0	One or more may be inoperative provided AP Function is considered inoperative (item 22-10-00-10).	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 22-3

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

22. Autoflight

Sequence No.	Item	1	2	3	4	Change Bar
22-10-10	AP Quick Disconnect Pushbutton					
22-10-10-A		C	2	1	(O) One may be inoperative provided: a) AP is not used at or below 1,500 ft. AGL, and b) Approach minimums do not require the use of the autopilot.	
22-10-10-B		B	2	0	Both may be inoperative provided AP Function is not used (item 22-10-00-10).	
22-10-11	Go-Around Pushbutton					
22-10-11-A		C	2	1	One may be inoperative provided approaches are conducted on the non-affected side.	
22-10-11-B		C	2	0	One or more may be inoperative provided AP function and FD function are not used below 1,500 ft. AGL.	
22-10-12	TCS (Touch Control Steering) Pushbutton	C	2	0	One or more may be inoperative provided associated Autopilot Quick Disconnect Pushbutton is operative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 23-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
23-11-00	VHF/UHF (Very/Ultra High Frequency) Communication System	D	-	-	Any in excess of those required by 14 CFR may be inoperative provided: a) VHF #1 is operative, and b) Affected VHF is not powered by the emergency bus, battery bus, battery direct bus, or the DC transfer bus and not required for emergency procedures.	
23-11-10	RTU (Radio Tuning Unit)					
23-11-10-A		C	2	1	RH RTU may be inoperative provided: a) VHF #1 is operative, b) At least one flight management system (FMS) is operative, c) Tuning of the radios by the FMS is verified operative, and d) Radio volumes are adequate.	
23-11-10-B		C	2	1	(M) RH RTU may be inoperative provided: a) VHF #1 is operative, b) At least one flight management system (FMS) is operative, c) Tuning of the radios by the flight management system (FMS) is verified operative, and d) Radio volumes are verified adequate after resetting the LH RTU.	

REVISION NO. 5

PAGE NO. 23-2

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
23-12-00	HF (High Frequency) Communication System					
23-12-00-A		D	-	-	Any in excess of those required by 14 CFR may be inoperative.	
23-12-00-B		C	-	1	(O) May be inoperative while conducting operations that require two long-range communication system (LRCS) provided: a) Aircraft Satellite Voice (SATVOICE) system operates normally, b) SATVOICE services are available as an LRCS over the intended route of flight, c) The International Civil Aviation Organization (ICAO) Flight Plan is updated (as required) to notify air traffic control (ATC) of the communications equipment status of the aircraft, and d) Alternate procedures are established and used.	
23-15-00 ***	SATCOM (Satellite Communications)					
23-15-00-A		D	-	0	May be inoperative provided procedures do not require its use.	
23-15-00-B		C	-	0	(O) May be inoperative provided alternate procedures are established and used.	
23-15-15 ***	Flight Phone	D	-	0	May be inoperative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 23-3

AIRCRAFT:
Falcon 2000EX

TABLE KEY
1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
23-20-05	CVR (Cockpit Voice Recorder)					
23-20-05-A	With FDR (Flight Data Recorder) Installed	A	1	0	May be inoperative provided: a) FDR operates normally, and b) Repairs are made within 3 flight-days.	
23-20-05-B	Without FDR (Flight Data Recorder) Installed	A	1	0	May be inoperative provided repairs are made within 3 flight-days.	
23-20-05-C	For an Operator Other Than a Holder of an Air Carrier or Commercial Operator Certificate	A	1	0	May be inoperative provided repairs are made in accordance with applicable 14 CFRs.	
23-20-05-30 ***	Recorder Independent Power Supply (RIPS)	C	1	0	May be inoperative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 23-4

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
23-20-10 ***	SELCAL (Selective Call System)					
23-20-10-A		C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
23-20-10-B		D	1	0	May be inoperative provided procedures do not require its use.	
23-20-10-01	Channel					
23-20-10-01-A		C	-	0	(O) May be inoperative provided alternate procedures are established and used.	
23-20-10-01-B		D	-	0	May be inoperative provided procedures do not require its use.	
23-20-11 ***	ACARS (Aircraft Communication and Reporting System)					
23-20-11-A		C	-	0	(O) May be inoperative provided alternate procedures are established and used.	
23-20-11-B		D	1	0	May be inoperative provided procedures do not require its use.	
23-20-25 ***	AFIS (Airborne Flight Information System)	D	1	0	May be inoperative.	
23-21-00 ***	DTU (Data Transmission Unit) System (M3158)	D	1	0	(M) May be inoperative or removed provided: a) "DTU" C/B is pulled and collared, and b) Engine data download is performed as per the P&WC Engine Maintenance Manual.	

REVISION NO. 5

PAGE NO. 23-5

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
23-50-00	Audio Panel					
23-50-00-05	ST Pushbutton	C	-	0	May be inoperative.	
23-50-00-10	ADF (Automatic Direction Finder) Pushbutton					
23-50-00-10-A		C	-	1	Any in excess of one may be inoperative.	
23-50-00-10-B		C	-	0	May be inoperative provided the associated ADF is considered inoperative (item 34-53-00).	
23-50-00-20	MKR Pushbutton					
23-50-00-20-A		C	-	1	Any in excess of one may be inoperative.	
23-50-00-20-B		C	-	0	May be inoperative provided the Marker Beacon System is considered inoperative (item 34-51-40).	
23-50-00-30	FILT Pushbutton	C	-	1	Any in excess of one may be inoperative provided affected very high frequency omni-directional range (VOR)/instrument landing system (ILS) Function or distance measuring equipment (DME) or ADF is not used.	
23-50-00-40	SPK Pushbutton	C	-	0	May be inoperative provided associated Cockpit Speaker is considered inoperative (item 23-50-75).	
23-50-00-50	ISOL Pushbutton	C	-	0	May be inoperative.	
23-50-00-95	GRND Pushbutton	C	-	1	Any in excess of one may be inoperative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 23-6

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
23-50-02	Third Audio Panel					
23-50-02-A		A	1	0	May be inoperative provided: a) Forward Observer Seat is considered inoperative (item 25-11-20), and b) Repairs are made within 2 flight days.	
23-50-02-B		D	1	0	May be inoperative provided Forward Observer Seat is not required by 14 CFR	
23-50-75	Cockpit Speaker	C	2	0	One or more may be inoperative provided: a) Procedures do not require its use, and b) Associated Headset is installed and used.	
23-50-80	Flight Deck Headsets and Microphones					
23-50-80-10	Headset Boom Microphone					
23-50-80-10-A	Holder of an Air Carrier or Commercial Operator Certificate	A	-	0	May be inoperative provided: a) Associated hand microphone is installed and operates normally, and b) Repairs are made within 3 flight-days.	
23-50-80-10-B		D	-	-	Any in excess of those required by regulation may be inoperative.	
(Continued)						

REVISION NO. 5

PAGE NO. 23-7

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
23-50-80	Flight Deck Headsets and Microphones (Cont'd)					
23-50-80-10	Headset Boom Microphone (Cont'd)					
23-50-80-10-C	Operator Other Than a Holder of an Air Carrier or Commercial Certificate	A	-	0	May be inoperative provided: a) Associated hand microphone is installed and operates normally, and b) Repairs are made in accordance with applicable regulations.	
23-50-80-10-D		D	-	-	Any in excess of those required by regulation may be inoperative.	
23-50-80-20	Headset Earphones/Headphones					
23-50-80-20-A	Holder of an Air Carrier or Commercial Operator Certificate	C	-	1	May be inoperative provided associated Cockpit Speaker operates normally.	
23-50-80-20-B		D	-	-	Any in excess of those required by regulation may be inoperative.	
23-50-80-20-C	Operator Other Than a Holder of an Air Carrier or Commercial Certificate	C	-	1	May be inoperative provided associated Cockpit Speaker operates normally.	
23-50-80-20-D		D	-	-	Any in excess of those required by 14 CFR may be inoperative.	
(Continued)						

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 23-8

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	---

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
23-50-80	Flight Deck Headsets and Microphones (Cont'd)					
23-50-80-30	Hand Microphone					
23-50-80-30-A	Holder of an Air Carrier or Commercial Operator Certificate	C	-	0	May be inoperative provided associated boom microphone operates normally.	
23-50-80-30-B		D	-	0	Any in excess of those required by regulation may be inoperative.	
23-50-80-30-C	Operator Other Than a Holder of an Air Carrier or Commercial Certificate	C	-	0	May be inoperative provided associated boom microphone operates normally.	
23-50-80-30-D		D	-	0	Any in excess of those required by regulation may be inoperative.	

REVISION NO. 5

PAGE NO. 23-9

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

23. Communications

Sequence No.	Item	1	2	3	4	Change Bar
23-50-95	PA (Public Address) System					
23-50-95-A	Passenger Configuration	C	1	0	(O) May be inoperative provided alternate, normal, and emergency procedures and/or operating restrictions are established and used.	
					NOTE: Any station function(s) that operates normally may be used.	
23-50-95-B	Cargo Configuration	D	1	0	May be inoperative provided procedures do not require its use.	
23-52-10	Crewmember Interphone System					
23-52-10-A		C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
					NOTE: Any station function(s) that operate normally may be used.	
23-52-10-B		D	-	0	May be inoperative provided procedures do not require its use.	

REVISION NO. 5

PAGE NO. 24-1

DATE: XX/XX/XXXX

AIRCRAFT
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

24. Electrical Power

Sequence No.	Item	1	2	3	4	Change Bar
24-30-00	DC Voltmeter	C	2	1	RH Voltmeter may be inoperative provided RH BUS TIED, LH BUS ISOL, GEN 1, and GEN 2 Caution Lights are operative.	
24-31-10	GEN Caution Light					
24-31-10-01	GEN 1 Caution Light	B	1	0	(O) May be inoperative.	
24-31-10-02	GEN 2 Caution Light	C	1	0	(O) May be inoperative provided associated DC Voltmeter is operative.	
24-32-00	Battery Temperature Indication System (Aircraft without M1667)					
24-32-00-10	Temperature Indication	C	1	0	(O) May be inoperative provided: a) HOT BAT Warning Light is operative, b) Amber and Red Lights are operative, and c) Battery Fan is verified operative.	
24-32-00-20	Amber or Red Light	C	2	1	(O) One may be inoperative provided: a) Temperature Indication is operative, b) HOT BAT Warning Light and the remaining Amber or Red Light are operative, and c) Battery Fan is verified operative.	
24-32-05	Battery Fan					
24-32-05-A	(Aircraft without M1667)	C	1	0	(O) May be inoperative provided: a) HOT BAT Warning Light is operative, and b) Battery Temperature Indication System is operative.	

REVISION NO.5

PAGE NO. 24-2

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

24. Electrical Power

Sequence No.	Item	1	2	3	4	Change Bar
24-32-09 ***	AUX Battery System (Communication) (Aircraft with M0972)	D	-	0	May be inoperative provided associated switch is set to OFF.	
24-33-01	APU (Auxiliary Power Unit) Starter Generator	C	1	0	(O) Electrical Generator function may be inoperative.	
24-40-05	EXT PWR Switch					
24-40-05-10	Light Bulb	C	4	2	One or two may be inoperative.	
24-60-12	LH AV MASTER Switch					
24-60-12-10	LED	C	8	4	One or more may be inoperative.	
24-60-13	RH AV MASTER Switch					
24-60-13-10	LED	C	8	4	One or more may be inoperative.	
24-61-09	RH BUS TIED Caution Light	C	1	0	(O) May be inoperative provided RH/ESS Bus Tie Circuit and DC Voltmeters are verified operative.	
24-61-11	LH BUS ISOL Caution Light	C	1	0	(O) May be inoperative provided LH/ESS Bus Tie Circuit and DC Voltmeters are verified operative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 25-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-11-00	Crewmember Seat					
25-11-00-10	Vertical Adjustment	B	2	0	(M)(O) One or more may be inoperative provided: a) Seat is secured at the individual crewmember's requirements, and b) Associated CREW SEATS C/B is pulled and collared.	
25-11-00-15	Recline Adjustment	B	2	0	One or more may be inoperative provided: a) Seat is able to move full Fore and Aft on its track, and b) Seat is secured at a position acceptable to the affected crewmember.	
25-11-00-20	Armrest					
25-11-00-20-A		C	4	0	One or more may be inoperative provided: a) Affected Armrest is in the up position, and b) Seat is acceptable to the affected crewmember.	
25-11-00-20-B		C	4	0	(M) One or more may be inoperative provided: a) Affected Armrest is removed, and b) Seat is acceptable to the affected crewmember.	
25-11-00-30	Headrest	C	2	0	(O) One or more Headrests fairing only may be damaged provided: a) Seat is acceptable to the affected crewmember, and b) Headrest structure is verified adequate.	
25-11-10	Crewmember Inertial Reel	C	2	1	One may be jammed in locked position provided the tension of the harness is adequate.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 25-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-11-20 ***	Forward Observer Seat (Including Associated Equipment)					
25-11-20-A		A	1	0	May be inoperative provided: a) A passenger seat in the passenger cabin is made available to an FAA inspector for the performance of official duties, and b) Repairs are made within 2 flight days.	
25-11-20-B		A	1	0	May be inoperative provided: a) Required minimum safety equipment (oxygen and safety belt) is available, b) Seat is acceptable to the FAA inspector for performance of official duties, and c) Repairs are made within 2 flight days. NOTE 1: These provisos are intended to provide for occupancy of the seats by an FAA inspector when the minimum safety equipment (oxygen and safety belt) is functional, and the inspector determines the conditions to be acceptable. NOTE 2: The pilot-in-command will determine if the minimum safety equipment is functional for other persons authorized to occupy an observer seat.	
(Continued)						

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-11-20 ***	Forward Observer Seat (Including Associated Equipment) (Cont'd)					
25-11-20-C	Observer Seat Not Required by 14 CFR (Including Associated Equipment)	D	1	0	May be inoperative. NOTE: The pilot in command will determine if the minimum safety equipment is functional for other persons authorized to occupy an observer seat.	
25-13-31	Rudder Pedal Adjustment	C	2	0	One or more may be inoperative provided: a) Position of pedals permits normal full flight and brake control movement, and b) Adjustments are secured in a position that suits the individual pilot's requirements.	
25-21-01	Passenger Seat	D	-	-	(O) One or more may be inoperative provided: a) Seat does not block an emergency exit, b) Seat does not restrict any passenger from access to the main aircraft aisle, and c) Affected seat is blocked and placarded "DO NOT OCCUPY". NOTE: A seat with an inoperative seat belt or shoulder harness is considered inoperative.	
					(Continued)	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 25-4

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-21-01	Passenger Seat (Cont'd)					
25-21-01-12	Swivel Mechanism					
25-21-01-12-A		D	-	-	(M) One or more may be inoperative and the affected seat occupied provided: a) Affected seat is secured in taxi, takeoff, and landing (TTL) position, b) Affected seat does not block an emergency exit, and c) Affected seat does not restrict any passenger from access to the main aircraft aisle.	
25-21-01-12-B		C	-	-	One or more may be inoperative and the affected seat occupied provided the affected seat is immovable in taxi, takeoff, and landing (TTL) position.	
25-21-01-13	Forward/Aft Tracking Mechanism	C	-	-	May be inoperative and seat occupied provided: a) Associated seat does not block an emergency exit, b) Associated seat does not restrict any passenger from access to the main aircraft aisle, and c) Associated seat remains in taxi, takeoff, and landing (TTL) position for takeoff and landing.	
25-21-01-15	Recline Mechanism					
25-21-01-15-A		D	-	-	(M) One or more may be inoperative and affected seat occupied provided seat is secured in taxi, takeoff, and landing (TTL) position.	
25-21-01-15-B		C	-	-	One or more may be inoperative and affected seat occupied provided seat back is immovable in taxi, takeoff, and landing (TTL) position.	
(Continued)						

REVISION NO. 5

PAGE NO. 25-5

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX**TABLE KEY**

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-21-01	Passenger Seat (Cont'd)					
25-21-01-20	Armrest					
25-21-01-20-A	Armrest with Recline Mechanism	D	-	-	(M) May be inoperative or missing and seat occupied provided: a) Armrest does not block an emergency exit, b) Armrest does not restrict any passenger from access to the main aircraft aisle, and c) If Armrest is missing, seat is secured in the full upright position.	
25-21-01-20-B	Armrest without Recline Mechanism	D	-	-	May be inoperative or missing and seat occupied provided: a) Armrest does not block an emergency exit, and b) Armrest does not restrict any passenger from access to the main aircraft aisle.	
25-21-01-30	Headrest	C	-	-	May be inoperative and seat occupied provided the associated Passenger Seat and Headrest are in taxi, takeoff, and landing (TTL) position.	
25-21-01-35	Seat Belt Air Bag					
25-21-01-35-A	Required by 14 CFR/Regulation	D	-	-	May be inoperative provided affected seat is blocked and placarded "DO NOT OCCUPY."	
25-21-01-35-B ***	Not Required by 14 CFR/Regulation	D	-	-	(M) May be inoperative or disconnected provided seat belt operates normally.	
25-23-05	Keyed Lock	C	-	0	May be inoperative provided the associated door, compartment, or cap is verified secured prior to each departure.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 25-6

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-26-10 ***	Cabin Electrical Window Shade (A/C with M2189)	C	-	1	One or more may be inoperative provided the Electrical Window Shade on the Emergency Escape Door is operative.	
25-26-10-01 ***	Emergency Escape Door Electrical Window Shade	C	1	0	May be inoperative provided the window shade on the emergency escape door or one of the two immediate adjacent window shades stay in the full open position for all phases of flight.	
25-28-10	Aircraft Ladder					
25-28-10-01	Forward/Aft Service Compartment Ladder					
25-28-10-01-A		C	2	0	One or more may be inoperative in stowed position.	
25-28-10-01-B		C	2	0	(M) One or more may be removed.	
25-28-10-10	Portable Ladder	D	-	0	May be removed, or inoperative in the stowed position.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 25-7

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-40-05	Lavatory Door Ashtray					
25-40-05-A	Airplanes with Multiple Lavatory Doors with Ashtrays Installed	A	-	-	Up to and including 50 percent may be missing or inoperative for 10 days.	
25-40-05-B		A	-	-	More than 50 percent may be missing or inoperative for 3 days. NOTE: Crew lavatories are included in the total aircraft lavatory door ashtray count.	
25-40-05-C	Airplanes with Only One Lavatory Door with Ashtray Installed	A	1	0	May be missing or inoperative for 10 days.	
25-50-00	Baggage Compartment Restraint Nets and Anchors System					
25-50-00-A		D	-	-	May be inoperative or missing provided only the areas with operative restraint nets and anchors are used.	
25-50-00-B		C	-	-	(O) May be inoperative or missing provided baggage compartment remains empty.	
25-50-05	Baggage Compartment Shelf					
25-50-05-01	Shelf Stowage Strap	D	2	0	One or more may be inoperative or removed provided the shelves remain in the down position.	
25-50-05-02	Shelf Support Strap	D	4	0	One or more may be inoperative or removed provided the shelves remain in stowed (up) position and are not used.	
(Continued)						

REVISION NO. 5

PAGE NO. 25-8

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-50-05	Baggage Compartment Shelf (Cont'd)					
25-50-05-03	Shelf	D	2	0	One or more may be inoperative or removed provided the shelf remains in the stowed (up) position and is not used.	
25-60-01	Crewmember Flashlight Holder Assembly (Including Flashlight)					
25-60-01-A		C	-	-	May be inoperative or removed provided: a) Crewmember assigned to the affected position has an equivalent operative flashlight readily available, b) Inoperative flashlight remains in a certified location or is removed from the aircraft, and c) Location placarding is removed or obscured.	
25-60-01-B		D	-	-	Any in excess of those required by 14 CFR may be inoperative or removed provided: a) Inoperative flashlight remains in a certified location until removed from the aircraft at the next suitable maintenance facility, and b) Location placarding is removed or obscured.	
25-60-01-10 ***	Tamper Seals or Tags	C	-	-	(O) May be inoperative, damaged, or missing provided proper installation and servicing is verified at each preflight.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 25-9

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-60-10	AED (Automatic External Defibrillator) and/or Associated Equipment					
25-60-10-A		D	-	-	Any in excess of those required by 14 CFR may be incomplete, inoperative, or removed.	
25-60-10-B		A	-	0	(O) May be incomplete, inoperative, or removed provided: a) AED is labeled or placarded in a manner that will identify it as a unit that cannot be mistaken for a fully serviceable unit, b) Location placarding is removed or obscured, and c) Repairs or replacements are made within one flight.	
25-60-10-10 ***	Tamper Seals or Tags	C	-	-	(O) May be inoperative, damaged, or missing provided proper installation and servicing is verified at each preflight.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 25-10

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-60-11	EMK (Emergency Medical Kit) and/or Associated Equipment					
25-60-11-A		D	-	-	Any in excess of those required by 14 CFR may be incomplete or removed.	
25-60-11-B		A	-	-	(O) May be incomplete or removed provided: a) EMK is labeled or placarded in a manner that will identify it as a unit that cannot be mistaken for a fully serviceable unit, b) Location placarding is removed or obscured, and c) Repairs or replacements are made within one flight. NOTE: Medical equipment installed in the aircraft as part of an EMS operation is not considered part of the normal complement of equipment. No MMEL relief applies to that equipment and 14 CFR maintenance and inspection requirements do not apply.	
25-60-11-10 ***	Tamper Seals or Tags	C	-	-	(O) May be inoperative, damaged, or missing provided proper installation and servicing is verified at each preflight.	

REVISION NO. 5

PAGE NO. 25-11

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-61-00	ELT (Emergency Locator Transmitter)					
25-61-00-05 ***	Fixed ELT					
25-61-00-05-A		A	-	0	(M) May be inoperative provided: a) System is deactivated, and b) Repairs are made within 90 consecutive calendar-days.	
25-61-00-05-B		A	-	0	(M) May be missing provided: a) Placard stating "ELT not installed" is placed in view of the pilot, and b) Repairs are made within 90 consecutive calendar-days.	
25-61-00-05-C		D	-	-	(M) Any in excess of those required by 14 CFR may be inoperative provided system is deactivated.	
25-61-00-05-D		D	-	-	Any in excess of those required by 14 CFR may be missing.	
(Continued)						

REVISION NO. 5

PAGE NO. 25-12

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-61-00	ELT (Emergency Locator Transmitter) (Cont'd)					
25-61-00-10 ***	Survival Type ELTs	D	-	-	Any in excess of those required by 14 CFR may be inoperative or missing.	
25-61-00-15 ***	Remote ELT Switch	D	-	0	(M) May be inoperative provided: a) Remote ELT Switch is deactivated, and b) ELT Switch is placed in the ARMED mode.	
25-61-00-20 ***	ELT Indicator Light	D	-	0		
25-61-00-25 ***	ELT Aural Alarm	D	-	0		
25-63-00 ***	EVAS (Emergency Vision Assurance System) (STC #ST00892LA)	D	-	0	May be inoperative or missing.	
25-64-05	Lifeline (Overwater Operations Survival Equipment)	D	-	-	May be inoperative or missing provided overwater operations are not conducted.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 25-13

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-64-13	Life Raft					
25-64-13-A		D	-	-	(O) May be inoperative or missing provided: a) Extended overwater operations are not conducted, and b) Procedures are established and used to alert crew members of inoperative or missing equipment.	
25-64-13-B		C	-	-	(M)(O) Any in excess of those required may be inoperative or missing provided: a) Required distribution is maintained, b) Inoperative life raft and its installed location are placarded inoperative, c) When practical, the inoperative life raft is secured out of sight, and d) Procedures are established and used to alert crewmembers of inoperative or missing equipment.	
25-64-17	Lifejacket	D	-	-	(M)(O) Any in excess of those required by 14 CFR may be inoperative or missing provided: a) Required distribution is maintained, b) Inoperative lifejacket and its installed location are placarded inoperative, c) Inoperative lifejacket is secured out of sight, and d) Procedures are established and used to alert crew members of inoperative or missing equipment.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 25-14

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-64-21	FAK (First Aid Kit) and/or Associated Equipment					
25-64-21-A		D	-	-	Any in excess of those required by 14 CFR may be incomplete or removed.	
25-64-21-B		A	-	-	(O) If more than one is required by 14 CFR, only one of the required FAKs may be incomplete or removed provided: a) FAK is labeled or placarded in a manner that will identify it as a unit that cannot be mistaken for a fully serviceable unit, b) Location placarding is removed or obscured, and c) Repairs or replacements are made within one flight.	
					NOTE: Medical equipment installed in the aircraft as part of an EMS operation is not considered part of the normal complement of equipment. No MMEL relief applies to that equipment and 14 CFR maintenance and inspection requirements do not apply.	
25-64-21-10 ***	Tamper Seals or Tags	C	-	-	(O) May be inoperative, damaged, or missing provided proper installation and servicing is verified at each preflight.	

REVISION NO. 5

PAGE NO. 25-15

DATE: XX/XX/XXXX

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	---

25. Equipment/Furnishings

Sequence No.	Item	1	2	3	4	Change Bar
25-99-99 ***	NEF/NEF Items (Nonessential Equipment and Furnishings)	-	-	0	May be inoperative, damaged, or missing provided that the item(s) is deferred in accordance with the operator's NEF deferral program. The NEF program, procedures, and processes are outlined in the operator's (insert name) Manual. (M) and (O) procedures, if required, must be available to the flightcrew and included in the operator's appropriate document. NOTE: Exterior lavatory door ashtrays are not considered NEF items.	

26. Fire Protection

Sequence No.	Item	1	2	3	4	Change Bar
26-10-25 ***	Lavatory Smoke Detector (Aircraft with M1620)	D	-	0	One or more may be inoperative.	
26-20-15	Portable Fire Extinguisher	D	-	-	Any in excess of those required by 14 CFR may be inoperative or removed provided: a) Inoperative fire extinguisher remains in a certified location until removed from the aircraft at the next suitable maintenance facility, b) Location placarding is removed or obscured, and c) Required distribution is maintained. NOTE: Inoperative fire extinguishers, removed from a certified location or removed from the aircraft, are subject to 49 CFR dangerous goods regulations.	
26-20-15-10	Tamper Seals or Tags	C	-	-	(O) May be inoperative, damaged, or missing provided proper installation and servicing is verified at each preflight.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 27-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

27. Flight Controls

Sequence No.	Item	1	2	3	4	Change Bar
27-00-05	Servo-Actuator Integrated Anti-Flutter Function	A	8	7	(M) One may be inoperative for three flights or 10 flying-hours, whichever occurs first, provided the associated servo-actuator is verified before each flight.	
27-00-08	Stall Test	A	2	1	One may be inoperative provided: a) Slats are extended with the manual control at airspeed below 180 KIAS, b) Slat Configuration Panel is operative, c) AUTO SLATS Caution Light is operative, and d) Repairs are made within 2 consecutive calendar-days.	
27-00-09	"STALL..." Aural Warning	C	2	1	(O) One may be inoperative provided: a) Slat Configuration Panel is operative, b) Both Automatic Slat Extension Systems are verified operative before each departure, and c) Automatic Ignition System is verified operative before each departure.	
27-00-10	T/O CONFIG Warning Light	C	1	0	(O) May be inoperative provided the Aural Warning is verified operative.	
27-14-01	Roll Trim Control System	C	1	0	(M)(O) May be inoperative provided: a) AIL ZERO Caution Light is operative and extinguished, b) Fuel Quantity Indications are operative, c) Roll Trim is verified in neutral position before each departure, d) Rudder Trim Control System is verified operative, e) TRIM AILERON C/B is pulled and collared, and f) Fuel imbalance is limited to 500 lbs. or less.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 27-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

27. Flight Controls

Sequence No.	Item	1	2	3	4	Change Bar
27-14-10	Roll Trim Position Indication	C	1	0	(O) May be inoperative provided: a) AIL ZERO Caution Light is operative and extinguished, b) Fuel Quantity Indications are operative, c) Roll Trim Control System is verified operative, d) Ailerons are verified in neutral position, and e) Fuel imbalance is limited to 500 lbs. or less.	
27-14-11	AIL ZERO Caution Light	B	1	0	(O) May be inoperative provided it is verified before each departure that ailerons are in neutral position when Roll Trim is set to zero.	
27-15-01	Roll Arthur Variable Bellcrank	C	1	0	(M)(O) May be inoperative provided: a) AFM procedure is applied, b) Roll Arthur Variable Bellcrank is secured in low-speed position, and c) AIL FEEL C/B is pulled and collared.	
27-15-10	AIL FEEL Caution Light	C	1	0	(O) May be inoperative provided: a) AFM procedure is applied, and b) Roll control forces are verified in low-speed configuration before each departure.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 27-3

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

27. Flight Controls

Sequence No.	Item	1	2	3	4	Change Bar
27-24-01	Rudder Trim Control System	A	1	0	(M)(O) May be inoperative provided: a) Fuel Quantity Indications are operative, b) Roll Trim Control System is verified operative, c) Rudder Trim is verified in neutral position before each departure, d) TRIM RUDDER C/B is pulled and collared, e) Fuel imbalance is limited to 500 lbs. or less, and f) Repairs are made within 2 consecutive calendar-days.	
27-24-10	Rudder Trim Position Indication	C	1	0	(O) May be inoperative provided: a) Rudder Trim Control System is verified operative, and b) Rudder is verified in neutral position with Yaw Damper off before each departure.	
27-35-01	Elevator Arthur Variable Bellcrank	B	1	0	(M)(O) May be inoperative provided: a) AFM procedure is applied, b) Horizontal Stabilizer is verified and adjusted between the two takeoff reference marks before each departure, c) Elevator Arthur Variable Bellcrank is verified in low-speed position before each departure, and d) PITCH FEEL C/B is pulled and collared.	
27-35-10	PITCH FEEL Caution Light	B	1	0	(M)(O) May be inoperative provided: a) AFM procedure is applied, and b) Elevator Arthur Variable Bellcrank is verified in low-speed position before each departure.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 27-4

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

27. Flight Controls

Sequence No.	Item	1	2	3	4	Change Bar
27-35-11	PITCH AFU (Artificial Feel Unit) Heating System	D	1	0	(M) May be inoperative provided it is secured.	
27-35-11-20	PITCH AFU HEAT TEST Light					
27-35-11-20-A		D	1	0	May be inoperative provided OVERHEAT Magnetic Indicator is not tripped red.	
27-35-11-20-B		D	1	0	May be inoperative provided PITCH AFU Heating System is considered inoperative (item 27-35-11).	
27-40-10	Horizontal Stabilizer Position Indication	C	1	0	(O) May be inoperative provided: a) Touch and Go training maneuvers are prohibited, b) Autopilot Function is not used (item 22-10-00-10), c) Horizontal Stabilizer Trim Aural Warning is operative, d) Horizontal Stabilizer is verified operative, e) Horizontal Stabilizer is verified and adjusted between the two takeoff reference marks before each departure, and f) T/O CONFIG Warning System is verified operative.	
27-40-11	Horizontal Stabilizer Trim Aural Warning	C	1	0	(O) May be inoperative provided: a) Autopilot Function is not used (refer to item 22-10-00-10), b) Horizontal Stabilizer Position Indication is operative, c) Horizontal Stabilizer is verified operative, and d) T/O CONFIG Warning System is verified operative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 27-5

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

27. Flight Controls

Sequence No.	Item	1	2	3	4	Change Bar
27-80-02	Emergency Slat Extension (EMER SLATS)				DELETED, Revision 5.	
27-80-10	Slat Configuration Panel					
27-80-10-10	Green Light	B	1	0	(O) May be inoperative provided: a) Wing Anti-Ice Indication Lights are operative, b) Amber Light (slats in transit) is operative, c) T/O CONFIG Warning System is verified operative, and d) Position of the Slats and the slat control are verified to be in agreement before each departure.	
27-80-10-20	Amber Light (Slats in Transit)	C	1	0	(O) May be inoperative provided AFM Limitations are applied.	
27-80-10-30	AIRBRAKE Amber Light	B	1	0	(O) May be inoperative provided: a) T/O CONFIG Warning System is verified operative, b) Stall Tests are operative, c) Airbrakes are verified operative, and d) Airbrakes are verified in the retracted position before each takeoff.	
27-80-11	AUTO SLATS Caution Light	C	1	0	(O) May be inoperative provided: a) AFM procedure is applied, and b) Slat Configuration Panel is operative.	
27-80-12	FLAP ASYM Caution Light	C	1	0	(M)(O) May be inoperative provided: a) Flap symmetry is verified adequate before each departure, and b) Flap Asymmetry Protection System is verified operative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 28-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

28. Fuel

Sequence No.	Item	1	2	3	4	Change Bar
28-20-10	FUEL TRANSFER Caution Light	C	1	0	(O) May be inoperative provided: a) Fuel Quantity Indications are operative, and b) Fuel Quantity Indications are monitored at least every 30 minutes in flight.	
28-21-01	Booster Pump	C	4	3	(M)(O) One may be inoperative provided: a) Normal Booster Pump 2 is operative, b) XBP Crossfeed Valves are verified operative, c) XTK Valve is verified operative, d) Associated Booster Pump C/B is pulled and collared, and e) Fuel Quantity Indications are closely monitored during flight.	
28-21-25	XBP Crossfeed Valve	A	2	0	(M) One or more may be inoperative in closed position provided: a) All Booster Pumps are operative, b) Affected XBP Crossfeed Valve is secured in closed position, and c) Repairs are made within 3 consecutive calendar-days.	
28-21-26	X-BP Amber Indicator					
28-21-26-10	Light Bulb	B	2	1	(O) One bulb may be inoperative provided fuel crossfeed monitoring is verified operative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 28-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

28. Fuel

Sequence No.	Item	1	2	3	4	Change Bar
28-21-29	Transfer Valve	B	3	0	(M)(O) One or more may be inoperative provided: a) Fuel quantity is limited to 6,000 lbs. in each wing tank, b) Forward and rear fuel tanks are verified empty before each departure, and c) TRANSFER C/B is pulled and collared.	
28-22-01	XTK Valve	C	1	0	(O) May be inoperative in closed position provided: a) All Booster Pumps are operative, b) XTK Light is operative and extinguished, and c) XBP Crossfeed Valves are verified operative.	
28-22-02	XTK Amber Indicator					
28-22-02-10	Light Bulb	B	2	1	(O) One bulb may be inoperative provided fuel crossfeed monitoring is verified operative.	
28-30-10 ***	Fuel Tank Sump Drain Valve (A/C with M3844)	A	-	-	(M)(O) One or more may be inoperative provided: a) Affected Fuel Tank Sump Drain Valve is in an authorized position in accordance with the MAINT 28-30-10-b procedure, b) Affected drain valve is sealed with an approved cap, and c) Repairs are made before the next fuel tank sump draining operation. NOTE: The fuel tank sump draining operation interval is provided by AMM 05-10-28 (Scheduled Maintenance – Aircraft Maintenance Operations – ATA View – Fuel) or Operator’s documentation.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 28-3

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

28. Fuel

Sequence No.	Item	1	2	3	4	Change Bar
28-40-10	Fuel Quantity Indication	C	2	1	(O) Fuel Quantity Indication for one group of tanks may be inoperative provided: a) FULL refueling mode is used when refueling to any fuel level, b) Fuel quantity is determined by other acceptable means, c) Fuel Flow (FF) and Fuel Used (FU) Indications are operative, and d) LO FUEL 1, LO FUEL 2 Caution Lights and LEVEL Amber Lights are verified operative.	
28-41-02	FQMC (Fuel Quantity Management Computer) Channel	A	2	1	(M)(O) One may be inoperative provided: a) Remaining FQMC Channel is verified operative, b) Associated C/B is pulled and collared, and c) Repairs are made within 3 consecutive calendar-days. NOTE: For failure of FQMC Engine OIL or APU indications, refer to dedicated items.	
28-41-02-03	ARINC Input Data Bus Function					
28-41-02-03-A		B	2	1	One may be inoperative.	
28-41-02-03-B		C	2	0	Both may be inoperative provided: a) Actual fuel quantity is considered 400 lbs. lower than the displayed quantity for range performance purposes, b) LEVEL Amber Lights are operative, and c) LO FUEL 1 and LO FUEL 2 Caution Lights are operative.	

28. Fuel

Sequence No.	Item	1	2	3	4	Change Bar
28-41-05	Fuel Gauging System					
28-41-05-01	LH/RH Wing Outer Tank Gauge	C	4	2	One per wing may be inoperative provided associated fuel tank quantity is considered 300 lbs. higher than the displayed fuel quantity for takeoff and landing performance purposes. NOTE: Refueling of FRONT and REAR tanks is not possible.	
28-41-05-02	LH/RH Wing Inner Fuel Tank Gauge	C	2	0	One or more may be inoperative provided: a) Associated tank is considered full for takeoff and landing performance purposes, and b) Associated Wing Center Fuel Tank Gauge is operative. NOTE 1: PARTIAL refueling may lead to wing asymmetry. NOTE 2: Refueling of FRONT and REAR tanks is not possible.	
28-41-05-03	LH/RH Wing Center Fuel Tank Gauge	C	2	0	One or more may be inoperative provided: a) Associated tank is considered full for takeoff and landing performance purposes, and b) Associated Wing Inner Fuel Tank Gauge is operative. NOTE 1: PARTIAL refueling may lead to wing asymmetry. NOTE 2: Refueling of FRONT and REAR tanks is not possible.	
					(Continued)	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 28-5

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

28. Fuel

Sequence No.	Item	1	2	3	4	Change Bar
28-41-05	Fuel Gauging System (Cont'd)					
28-41-05-21	Front Tank Fuel Gauge	C	2	1	One may be inoperative provided associated fuel tank quantity is considered 100 lbs. higher than the displayed fuel quantity for takeoff and landing performance purposes.	
28-41-05-22	Rear Tank Fuel Gauge	C	2	1	One may be inoperative provided associated fuel tank quantity is considered 100 lbs. higher than the displayed fuel quantity for takeoff and landing performance purposes.	
28-41-09	Fuel Density Compensation					
28-41-09-04	LH/RH Density Compensator Probe	C	2	1	One may be inoperative.	
28-41-10	Fuel Used (FU)	C	2	0	One or more may be inoperative provided Fuel Flow (FF) and the associated Fuel Quantity Indications are operative.	
28-41-12	LO FUEL Caution Light	B	2	1	(O) One may be inoperative provided: a) Fuel Quantity Indications are operative, and b) LEVEL Amber Lights are verified operative.	
28-41-15	Fuel Flow (FF)	B	2	1	One may be inoperative provided all other engine indications and the associated Fuel Quantity Indications are operative.	
28-42-05	LEVEL Amber Light	C	2	0	(O) One or more may be inoperative provided: a) Fuel Quantity Indications are operative, and b) LO FUEL 1 and LO FUEL 2 Caution Lights are verified operative.	

REVISION NO.5

PAGE NO. 28-6

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

28. Fuel

Sequence No.	Item	1	2	3	4	Change Bar
28-42-10	Fuel High Level Detection System	A	1	0	May be inoperative provided: a) FULL Pressure Refueling is not used, b) Cockpit Fuel Quantity Indications are verified operative and monitored during refueling operation, and c) Repairs are made within 3 consecutive calendar-days.	
28-43-01	Fuel Temperature (TEMP) Indication	C	1	0	May be inoperative provided: a) Airplane is not operated with outside temperature below ISA -20 °C, and b) Initial fuel tank temperature is above -30 °C.	
28-50-00	Pressure Refueling System	C	1	0	May be inoperative provided FUELING Caution Light is operative and extinguished.	
28-50-01	Refueling Control Panel					
28-50-01-01	FULL/PARTIAL Refueling Selection Channel					
28-50-01-01-A		B	2	1	One may be inoperative.	
28-50-01-01-B		B	2	0	Both may be inoperative provided Pressure Refueling is not used.	
28-50-01-02	TOTAL QTY Digital Display	B	1	0	May be inoperative provided: a) Cockpit Fuel Quantity Indications are operative, and b) Cockpit Fuel Quantity Indications are monitored during refueling operation.	
28-50-01-03	TOTAL QTY SELECTED Digital Display	B	1	0	May be inoperative provided PARTIAL Refueling is not used.	
(Continued)						

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 28-7

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

28. Fuel

Sequence No.	Item	1	2	3	4	Change Bar
28-50-01	Refueling Control Panel (Cont'd)					
28-50-01-04	INC/DEC Switch	B	1	0	May be inoperative provided PARTIAL Refueling is not used.	
28-50-01-05	LAMP TEST Pushbutton	B	1	0	May be inoperative provided the HIGH LEVEL TEST Pushbutton and STOP FUELING Red Light are operative.	
28-50-01-06	FULL Amber Light	B	2	0	One or more may be inoperative provided HIGH LEVEL TEST Pushbutton is operative.	
28-50-01-07	STOP FUELING Red Light	C	1	0	(O) May be inoperative provided: a) Pressure Refueling is not used, and b) Fuel tanks are verified unpressurized before gravity refueling operation.	
28-50-01-08	FAULT Amber Light	B	1	0	May be inoperative provided the HIGH LEVEL TEST Pushbutton and STOP FUELING Red Light are operative.	
28-50-01-09	HIGH LEVEL TEST Pushbutton	A	1	0	(O) May be inoperative provided: a) Pressure Refueling is not used, b) Fuel tanks are verified unpressurized before gravity refueling operation, and c) Repairs are made within 3 consecutive calendar-days.	
28-50-02	Pressure Refueling Gauging System	C	2	0	One or more may be inoperative provided: a) FULL refueling mode is used when refueling to any fuel level, and b) FULL Amber Lights are operative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 28-8

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

28. Fuel

Sequence No.	Item	1	2	3	4	Change Bar
28-50-05	FUELING Caution Light	C	1	0	(M)(O) May be inoperative provided: a) Both Fueling Panel Access Doors are verified closed, b) Fuel tank pressurization is verified adequate, c) Defueling switch on maintenance panel is set to OFF, and d) Defueling valve is verified closed.	
28-50-09	Refueling Valve	A	4	3	(M) One may be inoperative provided: a) Pressure Refueling is not used, b) Inoperative Refueling Valve is verified in closed position, and c) Repairs are made within 3 consecutive calendar-days.	
28-70-21	Vent Valve	C	3	0	(M) One or more may be inoperative provided: a) FUELING Caution Light is operative, b) Affected Vent Valve is manually operated before/after refueling, c) If STOP FUELING Red Light (fueling panel) remains lighted after opening of the vent valves, presence of airflow at each air outlet is verified during pressure refueling, and d) FUELING Caution Light is extinguished after closing sequence of Vent Valves.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 29-1

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	---

29. Hydraulic Power

Sequence No.	Item	1	2	3	4	Change Bar
29-11-10	PUMP.. HYDR#.. Caution Light	C	3	2	(O) One may be inoperative provided: a) Associated Hydraulic Pressure Indication is verified operative, b) ST BY PUMP and HYDR#2 ISOL Caution Lights are operative, c) Standby Pump is verified operative, and d) Associated System Pressure Indication is monitored every 30 minutes in flight.	
29-11-11	Hydraulic Pressure Indication (PRESS on Engine Indication Electronic Display (EIED))	C	2	1	(O) One may be inoperative provided: a) ST BY PUMP and HYDR#2 ISOL Caution Lights are operative, b) Associated Hydraulic System PUMP.. HYDR#.. Caution Light is verified operative, and c) Standby Pump is verified operative before engine start.	
29-13-09	Hydraulic Filter Clogging Indicator	A	9	8	(M) One may be tripped red provided: a) Associated PUMP..HYDR#.. Caution Light is operative and extinguished, b) Affected Clogging Indicator is reset once at the beginning of the repair interval and is verified to not be tripped red before each departure, and c) Repairs are made within 10 consecutive calendar-days.	
29-14-01	HYD 1 Tank Quantity Indication (QTY)	C	1	0	(O) May be inoperative provided the tank fluid level is verified before engine start.	

REVISION NO. 5

PAGE NO. 29-2

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

29. Hydraulic Power

Sequence No.	Item	1	2	3	4	Change Bar
29-14-02	HYDR # TK PRESS Caution Light	C	1	0	(O) May be inoperative provided: a) Both Hydraulic Pressure Indications are verified operative, b) Hydraulic System pressure is closely monitored in flight, and c) AFM Procedures are applied if pressure starts fluctuating.	
29-14-11	Main Hydraulic Accumulator	C	2	1	Hydraulic System No. 1 Accumulator may be inoperative.	
29-14-12	Thrust Reverser Hydraulic Accumulator	C	2	0	One or more may be inoperative provided Thrust Reverser System is not used (item 78-30-00).	
29-20-10	ST BY PUMP Caution Light	C	1	0	(O) May be inoperative provided: a) Standby Pump is verified operative before engine start, and b) Standby Pump Selector Handle is verified secured in IN FLIGHT position.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 30-1

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	---

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
30-00-10	ANTI-ICE Caution Light	C	1	0	(O) May be inoperative provided: a) Anti-Ice Lights (overhead panel) are verified operative, and b) Anti-Ice Lights (overhead panel) are monitored at least every 30 minutes in flight.	
30-12-00	Wing Anti-Icing System	C	1	0	(M)(O) May be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, and b) Wing Anti-Icing Valve is secured in closed position.	
30-12-15	Wing Anti-Ice Indication – Green Light	C	1	0	(O) May be inoperative provided: a) ANTI-ICE Caution Light is operative, and b) Wing Anti-Icing System is verified operative before each departure.	
30-20-01	Engine Anti-Ice Valve					
30-20-01-A		B	2	1	(O) One may be jammed in closed position provided: a) Airplane is not operated in known or forecast icing conditions, and b) Associated ANTI-ICE ENG switch is set to OFF for the entire flight.	
(Continued)						

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 30-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
30-20-01	Engine Anti-Ice Valve (Cont'd)					
30-20-01-B		B	2	1	(O) One may be leaking in closed position provided: a) Outside Air Temperature (OAT) at the departure airport is at or below -7° C (20° F), b) Performance data is applied, c) Both ANTI-ICE ENG Amber Indicator Light is verified operative, d) ANTI-ICE Caution Light is verified operative, and e) Associated ANTI-ICE ENG switch is set to AUTO for the entire flight.	
30-20-01-C		B	2	1	(O) One may be leaking in closed position provided: a) Affected Engine Anti-Ice Valve regulation function is verified operative, b) Outside Air Temperature (OAT) at the departure airport is at or below +10° C (50° F), c) Performance data is applied, d) Both ANTI-ICE ENG Amber Indicator Light are verified operative, e) ANTI-ICE Caution Light is verified operative, and f) Associated ANTI-ICE ENG switch is set to AUTO for the entire flight.	
30-20-15	Engine Anti-Ice Indication – Green Light	C	2	0	(O) One or more may be inoperative provided: a) ANTI-ICE Caution Light is operative, and b) Engine Anti-Icing System is verified operative before each departure.	

REVISION NO. 5

PAGE NO. 30-3

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
30-30-05	Normal Static Port Heating System	B	2	1	(O) One may be inoperative provided: a) Airplane is not operated into visible moisture or in known or forecast icing conditions, and b) Enroute operations do not require its use.	
30-30-10	Normal Pitot Probe Heating System	B	2	1	(O) One may be inoperative provided: a) Airplane is not operated into visible moisture or in known or forecast icing conditions, b) Enroute operations do not require its use, and c) Pilot flying is on the non-affected side.	
30-30-12	LH/RH Probes or ST BY Pitot Caution Light	B	3	2	(O) One may be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, and b) Associated Probe Heater is verified operative before each departure.	
30-30-15	AoA (Angle of Attack) Heating System	C	2	1	(O) One may be inoperative provided: a) Airplane is not operated into visible moisture or in known or forecast icing conditions, b) Pitot Probe Heating System is operative, c) Normal Static Port Heating System is operative, and d) Stall 1 and Stall 2 Tests are operative.	
30-30-20	TAT (Total Air Temperature) Probe Heating System	B	1	0	(O) May be inoperative provided the airplane is not operated in known or forecast icing conditions.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 30-4

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
30-41-00	Windshield Deicing System	C	2	1	(O) One side may be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, b) Remaining side is verified operative, and c) Windshield Demisting System is verified operative.	
30-41-04	Windshield – XFR Caution Light	C	1	0	(M)(O) May be inoperative provided: a) Temperature Controller, Controller Transfer System, and Heating Networks are verified operative, and b) Windshield Demisting System is verified operative.	
30-41-10	Side and Rear Window Heating	C	1	0	May be inoperative.	
30-42-00	Windshield Demisting System	C	2	0	One or more may be inoperative provided Windshield Deicing System is operative.	
30-43-00	Windshield Wiper					
30-43-00-A		C	2	0	(O) One or more may be inoperative in rest position or missing provided: a) Airplane is not operated in known or forecast precipitation within arrival and departure areas, and b) Approaches do not require its use.	
(Continued)						

REVISION NO. 5

PAGE NO. 30-5

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

30. Ice and Rain Protection

Sequence No.	Item	1	2	3	4	Change Bar
30-43-00	Windshield Wiper (Cont'd)					
30-43-00-B		B	2	1	(M)(O) One may be inoperative in non-rest position provided: a) Airplane is not operated in known or forecast precipitation within arrival and departure areas, b) Approaches do not require its use, c) Pilot flying is on the non-affected side, d) Flight envelope is limited to 215 KIAS, and e) Associated C/B is pulled and collared.	
30-43-00-01	FAST Mode	C	2	0	One or more may be inoperative provided the associated SLOW Mode is operative.	
30-43-00-02	SLOW Mode	C	2	0	One or more may be inoperative provided the associated FAST Mode is operative.	
30-80-00 ***	Ice Detection System (Aircraft with M1893)					
30-80-00-A		C	1	0	May be inoperative.	
30-80-00-B		D	1	0	(M) May be inoperative provided ICE DETECTOCR C/B is pulled and collared.	
30-90-01 ***	Brake Heating System (Aircraft with M1834)	D	1	0	(M) May be inoperative provided: a) Brake Heating System is not used, and b) Brake Heating Valves are secured in closed position.	

REVISION NO. 5

PAGE NO. 31-1

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
31-14-11	Hydraulic Magnetic Indicators (Minelco on Maintenance Panel)	B	8	-	One or more may be inoperative provided associated systems (PITCH, RUD, AIL) are operative.	
31-21-00	Clock	C	2	1	One may be inoperative.	
31-31-32	FDR (Flight Data Recorder) System					
	For a Holder of an Air Carrier or Commercial Operator Certificate					
31-31-32-A	FDR (Flight Data Recorder) System	C	-	-	Any in excess of those required by 14 CFR may be inoperative.	
31-31-32-B	Includes FDR Function of CVFDR (Combined Voice and Flight Data Recorder)	A	-	-	May be inoperative provided: a) Cockpit Voice Recorder (CVR) operates normally, b) Airplane is not dispatched from a designated airport as listed in the operator's MEL unless: 1) FDR failure occurs after pushback but prior to takeoff, or 2) FDR repair was attempted but not successful. c) In those cases where repair is attempted but not successful, the aircraft may be dispatched on a flight or series of flights until the next designated airport where repair must be accomplished prior to dispatch, and d) Repairs are made within 3 flight-days.	
(Continued)						

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 31-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
31-31-32	FDR (Flight Data Recorder) System (Cont'd)					
31-31-32-01	FDR Recording Parameters Required by 14 CFR	A	-	-	Up to three recording parameters may be inoperative provided: a) Cockpit Voice Recorder (CVR) operates normally, and b) Repairs are made within 20 consecutive calendar-days.	
31-31-32-02	FDR Recording Parameters Not Required by 14 CFR	A	-	-	May be inoperative provided repairs are made prior to the completion of the next heavy maintenance visit.	
31-31-32-03	For an Operator Other Than a Holder of an Air Carrier or Commercial Operator Certificate					
31-31-32-03-A		C	-	1	Any in excess of those required by 14 CFR may be inoperative.	
31-31-32-03-B		A	-	0	May be inoperative provided repairs are made in accordance with 14 CFR.	
31-32-00	QAR (Quick Access Recorder) (Aircraft with M1896)					
31-32-00-A		C	1	0	May be inoperative provided no FDR or FDAU (Flight Data Acquisition Unit) fault is reported on the FDEP (Flight Data Entry Panel).	
31-32-00-B		A	1	0	May be inoperative provided FDR is considered inoperative (item 31-31-32).	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 31-3

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	---

31. Indicating/Recording Systems

Sequence No.	Item	1	2	3	4	Change Bar
31-50-01	Master Warning/ Master Caution Light System	C	1	0	May be inoperative provided Aural Warning System is verified operative.	
31-60-00	EIED (Engine Indication Electronic Display)	B	3	2	(O) Lower EIED may be inoperative provided: a) No display parameter is failed, b) Manual reconfiguration of remaining EIED is verified operative, and c) Associated Caution Lights are verified operative.	
31-60-00-10	Display Link Function	C	6	-	One or more may be inoperative.	
31-60-02	Electronic Checklist System (M1049)	C	1	0	(O) May be inoperative provided alternate procedures are established and used.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 32-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

32. Landing Gear

Sequence No.	Item	1	2	3	4	Change Bar
32-00-05	Configuration Panel					
32-00-05-01	LH L/G Green Indicator Light Bulb	B	2	1	(O) One bulb may be inoperative provided "GEAR" Aural Warning is verified operative.	
32-00-05-02	RH L/G Green Indicator Light Bulb	B	2	1	(O) One bulb may be inoperative provided "GEAR" Aural Warning is verified operative.	
32-00-05-03	Nose L/G Green Indicator Light Bulb	B	2	1	(O) One bulb may be inoperative provided "GEAR" Aural Warning is verified operative.	
32-00-05-04	LH L/G Red Indicator Light Bulb	B	2	1	(O) One bulb may be inoperative provided L/G Handle Flashing Light is operative.	
32-00-05-05	RH L/G Red Indicator Light Bulb	B	2	1	(O) One bulb may be inoperative provided L/G Handle Flashing Light is operative.	
32-00-05-06	Nose L/G Red Indicator Light Bulb	B	2	1	(O) One bulb may be inoperative provided L/G Handle Flashing Light is operative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 32-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

32. Landing Gear

Sequence No.	Item	1	2	3	4	Change Bar
32-30-00	Landing Gear (L/G) Retraction System	A	1	0	(M)(O) May be inoperative provided: a) AFM Procedures, Limitations, and Performance are applied, b) Affected modes of the E-GPWS/GPWS are considered inoperative (item 34-45-00), c) No untimely steady green L/G information was reported before L/G Retraction System failure, d) L/G Control Lever was not jammed in down position during the flight where the failure occurred, e) No BSCU fault code was logged before the L/G Retraction System failure, f) No BSCU fault code is displayed, except 315, 415, or both 333 and 433, g) L/G information are verified operative with L/G downlocked, h) Main L/G Doors are verified closed, i) L/G Control Lever is secured in down position, and j) Repairs are made within three flights or 2 consecutive calendar-days, whichever occurs first.	
32-31-10	L/G Handle Flashing Light	C	1	0	(O) May be inoperative provided: a) L/G position indications are operative, and b) "GEAR" aural warning is verified operative.	
32-41-02	BSCU (Brake System Computer Unit)					
32-41-02-10	Gear Handle Function	C	2	1	One may be inoperative provided L/G Retraction System is operative.	

(Continued)

TABLE KEY	
1.	REPAIR CATEGORY
2.	NO. INSTALLED
3.	NO. REQUIRED FOR DISPATCH
4.	REMARKS OR EXCEPTIONS

32. Landing Gear

Sequence No.	Item	1	2	3	4	Change Bar
32-41-02	BSCU (Brake System Computer Unit) (Cont'd)					
32-41-02-11	Main Gear Contact Function	A	4	3	(O) One may be inoperative provided: a) Landing distance is increased by 10%, b) Nose Gear Contact Functions are operative, c) FADEC WOW signals are verified operative, and d) Repairs are made within 2 consecutive calendar-days.	
32-41-02-12	Nose Gear Contact Function	A	2	1	(O) One may be inoperative provided: a) Landing distance is increased by 10%, b) Thrust Reverser System is considered inoperative (item 78 30-00), c) Main Gear Contact Functions are operative, d) FADEC WOW signals are verified operative, and e) Repairs are made within 2 consecutive calendar-days.	
32-41-02-13	NWS (Nose Wheel Steering) Function	C	2	1	One may be inoperative.	
32-41-02-14	IRS Data Function	C	4	3	One may be inoperative provided landing distance is increased by 10 percent.	
32-41-02-15	Pressure Recorder Acquisition Function	C	4	0	One or more may be inoperative provided DFDR is considered inoperative (item 31-31-32).	
32-41-02-16	Auto Airbrakes Command Function	C	2	1	(O) One may be inoperative provided AFM takeoff distance is increased by 70 ft.	
(Continued)						

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 32-4

AIRCRAFT:
Falcon 2000EX

TABLE KEY
1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

32. Landing Gear

Sequence No.	Item	1	2	3	4	Change Bar
32-41-02	BSCU (Brake System Computer Unit) (Cont'd)					
32-41-02-17	Pin Programming Function	C	4	0	One or more may be inoperative.	
32-41-02-18	Computer Identification Function	C	2	0	One or more may be inoperative.	
32-41-10	BRAKE ACCU Caution Light	C	1	0	(M) May be inoperative provided: a) Park Brake Accumulator pressure is verified adequate once each flight-day, and b) Chocks are installed before engine shutdown.	
32-41-33	Brake Temperature Indication	D	4	0	(O) One or more may be inoperative provided minimum turnaround time is observed.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 33-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
33-10-01	Cockpit and Instrument Panel Light					
33-10-01-A		C	-	-	(O) Individual lights may be inoperative provided: a) Remaining lighting system lights are sufficient to clearly illuminate all required instruments, controls, and other devices for which they are provided, b) Remaining lighting system lights are positioned so that direct rays are shielded from flightcrew members' eyes, and c) Lighting configuration and intensity is acceptable to the flightcrew. NOTE: Individual button/switch lights and/or annunciations/indications are excluded from this relief.	
33-10-01-B		D	-	0	May be inoperative for other than night operations.	
33-10-20 ***	Chartholder Lighting (Aircraft with M1426)	D	2	0	One or more may be inoperative.	
33-20-00	Cabin Lighting					
33-20-00-A		C	-	0	One or more may be inoperative or missing provided: a) Cabin Lighting is sufficient for flightcrew to perform required duties, b) For night operations, inoperative lights do not exceed 50 percent of the total installed, and c) Flashlight is used, as required.	

(Continued)

REVISION NO. 5

PAGE NO. 33-2

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
33-20-00	Cabin Lighting (Cont'd)					
33-20-00-B		D	-	0	One or more may be inoperative provided passengers are not carried.	
33-20-02	Passenger Lighted Information Sign (NO SMOKING and FASTEN BELT)	C	-	0	(O) May be inoperative provided alternate procedures are established and used to notify cabin occupants.	
33-30-01	Servicing Compartment/ Nose Cone Light	C	3	0	One or more may be inoperative.	
33-30-02	Pressure Fueling Bay Light	C	2	0	One or more may be inoperative.	
33-30-10	Baggage Compartment Light	C	2	0	One or more may be inoperative.	
33-40-00	Anticollision Light					
33-40-00-10	Red ANTICOL Light					
33-40-00-10-A		C	2	1	One may be inoperative provided White ANTICOL Lights are operative.	
33-40-00-10-B		B	2	0	Both may be inoperative provided: a) Flight is conducted in other than night operations, and b) White ANTICOL Lights are operative.	
33-40-00-20	White ANTICOL Light	C	3	0	One or more may be inoperative provided all Red ANTICOL Lights are operative.	

REVISION NO. 5

PAGE NO. 33-3

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
33-40-01	Navigation Light					
33-40-01-10	RH/LH Navigation Light					
33-40-01-10-A		C	-	0	One or more may be inoperative sunrise to sunset.	
33-40-01-10-B	(Aircraft with M1401)	C	4	2	One may be inoperative on each side.	
33-40-01-20	Rear Navigation Light	C	1	0	May be inoperative sunrise to sunset.	
33-40-33 ***	Logo Light (Aircraft with M1129 or M1746)	D	2	0	One or more may be inoperative.	
33-40-34	Pylon Light	C	-	0	May be inoperative.	
33-40-37	Landing Light					
33-40-37-A		C	2	1	One may be inoperative provided TAXI Light is operative.	
33-40-37-B		C	2	0	One or more may be inoperative for other than night operations.	
33-40-37-01	Pulse Light System	C	1	0	May be inoperative.	
33-40-41	Taxi Light					
33-40-41-A		C	1	0	May be inoperative provided both Landing Lights are operative.	
33-40-41-B		C	1	0	May be inoperative for other than night operations.	

REVISION NO. 5

PAGE NO. 33-4

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
33-40-70	Wing Ice Detection Light					
33-40-70-A		C	2	1	One may be inoperative provided ground deicing procedures do not require its use.	
33-40-70-B		C	2	0	(O) Both may be inoperative provided: a) Aircraft is not operated in known or forecast icing conditions at night, and b) Ground deicing procedures do not require their use.	
33-50-10	Interior Emergency Lighting					
33-50-10-04	Passenger Door – Exit Sign	C	2	0	One or more may be inoperative provided no passengers are carried.	
33-50-10-05	Passenger Door – Opening Instruction Sign	C	1	0	May be inoperative provided no passengers are carried.	
33-50-10-06	Passenger Door – Spotlight					
33-50-10-06-A		C	2	1	One may be inoperative.	
33-50-10-06-B		C	2	0	Both may be inoperative provided no passengers are carried.	
33-50-10-07	Overwing Emergency Exit – Exit Sign	C	2	0	One or more may be inoperative provided no passengers are carried.	
33-50-10-08	Overwing Emergency Exit – Handle Light	C	1	0	May be inoperative provided no passengers are carried.	
33-50-10-09	Overwing Emergency Exit – Opening Instruction Sign	C	1	0	May be inoperative provided no passengers are carried.	
(Continued)						

REVISION NO. 5

PAGE NO. 33-5

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

33. Lights

Sequence No.	Item	1	2	3	4	Change Bar
33-50-10	Interior Emergency Lighting (Cont'd)					
33-50-10-10	Floor Emergency Escape Path Light					
33-50-10-10-A		A	-	0	(M) One may be inoperative provided: a) Emergency Escape Path Lights adjacent to Passenger Door and Overwing Emergency Exit are operative, b) All other Interior Emergency Lights are operative, c) Cabin Sliding Doors are secured in open position, and d) Repairs are made within 3 consecutive calendar-days.	
33-50-10-10-B		C	-	0	One or more may be inoperative provided no passengers are carried.	
33-50-10-20	Bulkhead Exit Sign	C	-	0	One or more may be inoperative provided no seat behind the bulkhead is occupied.	
33-50-10-30	Pilot and Copilot Emergency Dome Light Bulb	C	4	3	One bulb may be inoperative.	
33-50-10-40 ***	Passenger Dome Light (Aircraft with M3553)	D	2	0	One or more may be inoperative.	
33-50-11	Exterior Emergency Light	C	2	0	(O) One or more may be missing or inoperative provided: a) No passengers are carried other than those authorized by 14 CFR for non-passenger-carrying operations, and b) Alternate procedures are established and used.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 34-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-00-00	DCP (Display Controller Panel)	A	2	1	RH DCP may be inoperative provided: a) Associated RSP is operative, and b) Repairs are made within 3 consecutive calendar-days.	
34-00-01	RSP (Reversion Switch Panel)	B	2	0	(O) One or more may be inoperative provided: a) DCPs are operative, and b) No reversion is selected.	
34-00-03	Air Data Reference Panel	B	2	1	IAS/MACH Function on Pilot Not Flying side may be inoperative.	
34-01-00	EFIS (Electronic Flight Instrument System) (Including A/C with STC ST11047SC)	A	4	3	(O) RH MFD may be inoperative provided: a) Enroute operations do not require its use, b) For takeoff and landing, remaining RH EFIS is in PFD mode, c) For takeoff and landing, Pilot flying is on the LH side, d) DCPs are operative, e) Standby Magnetic Compass and Standby Horizon are operative, f) RSPs are verified operative, and g) Repairs are made within 3 consecutive calendar-days. NOTE: The failure of MFD #2 may affect the ability to display electronic charts and maps on aircraft with STC ST11047SC.	
34-01-00-10	EFIS Fan	C	4	3	(O) One may be inoperative provided it is verified that cold airflow is delivered to EFIS.	

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-03-00 ***	DDRMI (Digital Distance and Radio Magnetic Indicator) (Aircraft with M0012)	C	-	0	May be inoperative.	
34-15-02	Altitude Alerting System	A	1	0	(O) May be inoperative provided: a) Enroute operations (i.e., RVSM) do not require its use, b) Autopilot with altitude hold and altitude capture operates normally, c) Airplane does not depart from a designated airport (as listed in the operator's MEL) where repair or replacement can be made, and d) Repairs are made within 3 flight-days.	
34-15-02-01	Aural Alert	C	2	0	One or more may be inoperative provided: a) Visual Alert operates normally, and b) Autopilot with altitude hold and altitude capture operates normally.	
34-15-02-02	Visual Alert	C	2	0	One or more may be inoperative provided: a) Aural Alert operates normally, and b) Autopilot with altitude hold and altitude capture operates normally.	
34-15-03	VMO/MMO (Maximum Operating Limit Speed) Aural Warning (ADC Source)	C	2	1	One may be inoperative provided: a) Both Mach/Airspeed indications are operative and from independent ADC sources on each side, and b) Mach/Airspeed are monitored against VMO/MMO AFM Limitations.	

REVISION NO. 5

PAGE NO. 34-3

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-21-00	AHS (Attitude and Heading System)	D	-	2	Any in excess of the two required to independently power the Captain and First Officer's system may be inoperative.	
34-21-10 ***	Lasertrack (Aircraft with M0259)	D	1	0	May be inoperative provided IRS is initialized by FMS.	
34-23-01	SFDS (Secondary Flight Display System)					
34-23-01-03	ATT Flag	B	1	0	(O) One may be inoperative provided: a) Operations are conducted only in Visual Meteorological Conditions (VMC), b) Operations are not conducted at night, c) Airplane is not operated in known or forecast flight over the top condition, and d) Standby Magnetic Compass is verified operative.	
34-23-01-04	LOC Flag	C	1	0	May be displayed.	
34-23-01-05	LOC Flag with B/C Label	C	1	0	May be displayed.	
34-23-01-06	G/S Flag	C	1	0	May be displayed.	

REVISION NO. 5

PAGE NO. 34-4

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-25-00	Standby Magnetic Compass	B	1	0	May be inoperative provided:	
					a) Operations are conducted only in Visual Meteorological Conditions (VMC),	
					b) Operations are not conducted at night, and	
					c) Two independent navigation systems (IRS, Attitude and Heading Reference System (AHRS)) are operative.	
34-25-00-01	Compass Lighting					
34-25-00-01-A		B	1	0	May be inoperative provided the Standby Magnetic Compass is considered inoperative (item 34-25-00).	
34-25-00-01-B		C	1	0	May be inoperative for other than night operations.	
34-31-01 ***	HUD (Head-Up Display)	D	1	0	(O) May be inoperative provided:	
					a) Approaches do not require its use, and	
					b) The Combiner is stowed in rest position.	
34-41-00	WX (Weather Radar)	C	-	-	As required by 14 CFR.	
34-41-13	WX Control Panel					
34-41-13-A	(Aircraft without M0878 or M1174)	C	1	0	May be inoperative provided the Weather Radar is considered inoperative (item 34-41-00).	
34-41-13-B	(Aircraft with M0878 or M1174)	D	2	1	One may be inoperative.	
34-41-13-C	(Aircraft with M0878 or M1174)	C	2	0	One or more may be inoperative provided the Weather Radar is considered inoperative (item 34-41-00).	

REVISION NO. 5

PAGE NO. 34-5

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-42-00	RA (Radio Altimeter)					
34-42-00-A		A	-	0	(O) May be inoperative provided: a) Approaches do not require its use, b) GPWS (basic modes) is considered inoperative (item 34-45-00), c) Traffic Alert and Collision Avoidance System (TCAS) is considered inoperative (item 34-44-00), d) No radio altitude is displayed, and e) Repairs are made within six flights or 2 consecutive calendar-days, whichever occurs first.	
34-42-00-B		D	2	1	(O) One may be inoperative provided: a) No radio altitude is displayed on affected RA, and b) Approaches do not require its use.	
34-44-00	TCAS (Traffic Alert and Collision Avoidance System)					
34-44-00-A		B	-	0	(M) May be inoperative provided: a) System is deactivated and secured, and b) Enroute or approach procedures do not require its use.	
34-44-00-B		C	-	-	(M) May be inoperative provided: a) Not required by 14 CFR, b) System is deactivated and secured, and c) Enroute or approach procedures do not require its use.	
(Continued)						

REVISION NO. 5

PAGE NO. 34-6

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-44-00	TCAS (Traffic Alert and Collision Avoidance System) (Cont'd)					
34-44-00-10	Combined TA (Traffic Alert) and RA (Resolution Advisory) Dual Display	C	2	1	May be inoperative on the non-flying pilot side provided: a) TA and RA visual display is operative on the flying pilot side, and b) TA and RA audio function is operative on flying pilot side.	
34-44-00-20	RA (Resolution Advisory) Display System					
34-44-00-20-A		C	2	1	One may be inoperative on the Pilot Not Flying side.	
34-44-00-20-B		C	-	0	(O) May be inoperative provided: a) TA visual display and audio functions are operative, b) TA only mode is selected by the crew, and c) Enroute or approach procedures do not require its use.	
34-44-00-30	TA (Traffic Alert) Display System	C	-	0	(O) May be inoperative provided: a) RA visual display and audio functions are operative, and b) Enroute or approach procedures do not require its use.	
34-44-00-40	Audio Functions	B	1	0	May be inoperative provided enroute or approach procedures do not require use of TCAS.	
34-44-00-50 ***	Airspace Selection Function	C	-	0	May be inoperative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 34-7

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-45-00	E-GPWS/GPWS (Enhanced Ground Proximity Warning System)					
34-45-01	Class A TAWS (Terrain Awareness and Warning System) Equipment Required					
34-45-01-10	GPWS	A	1	0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Repairs are made within 2 flight-days.	
34-45-01-11	Modes 1 to 4	A	4	0	(O) One or more mode may be inoperative provided: a) Alternate procedures are established and used, and b) Repairs are made within 2 flight-days.	
34-45-01-12	Test Mode	A	1	0	May be inoperative provided: a) GPWS is considered inoperative, and b) Repairs are made within 2 flight-days.	
34-45-01-13	Glideslope Deviation (Mode 5)					
34-45-01-13-A		C	-	1	May be inoperative.	
34-45-01-13-B		B	-	0	One or more may be inoperative.	
(Continued)						

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 34-8

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-45-00	E-GPWS/GPWS (Enhanced Ground Proximity Warning System) (Cont'd)					
34-45-01	Class A TAWS (Terrain Awareness and Warning System) Equipment Required (Cont'd)					
34-45-01-14	Advisory Callouts					
34-45-01-14-A		B	-	0	(O) May be inoperative provided alternate procedures are established and used.	
34-45-01-14-B		C	-	0	(O) May be inoperative provided: a) Advisory callout not required by 14 CFR, and b) Alternate procedures are established and used.	
34-45-01-15 ***	Windshear Mode (Reactive)					
34-45-01-15-A		B	1	0	(O) May be inoperative provided Alternate procedures are established and used. NOTE: Operator's alternate procedures should include reviewing windshear avoidance and windshear recovery procedures.	
34-45-01-15-B		C	1	0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Windshear Detection and Avoidance System (Predictive) are operative.	
(Continued)						

REVISION NO. 5

PAGE NO. 34-9

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-45-00	E-GPWS/GPWS (Enhanced Ground Proximity Warning System) (Cont'd)					
34-45-01	Class A TAWS (Terrain Awareness and Warning System) Equipment Required (Cont'd)					
34-45-01-20	Terrain System – FLTA (Forward Looking Terrain Avoidance) and PDA (Premature Descent Alert) Functions	B	1	0	(O) May be inoperative provided alternate procedures are established and used.	
34-45-01-30	Terrain Displays					
34-45-01-30-A		C	-	1	May be inoperative.	
34-45-01-30-B		B	-	0	One or more may be inoperative.	
34-45-01-40 ***	RAAS (Runway Awareness and Advisory System)	C	1	0	May be inoperative.	
34-45-02	Class B TAWS Equipment Required					
34-45-02-10	GPWS	A	1	0	(O) May be inoperative provided: a) Alternate procedures are established and used, and b) Repairs are made within 2 flight-days.	
34-45-02-11	Modes 1 and 3	A	2	0	(O) One or more may be inoperative provided: a) Alternate procedures are established and used, and b) Repairs are made within 2 flight-days.	
(Continued)						

AIRCRAFT:
Falcon 2000EX

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

Sequence No.	Item	1	2	3	4	Change Bar
34-45-00	E-GPWS/GPWS (Enhanced Ground Proximity Warning System) (Cont'd)					
34-45-02	Class B TAWS Equipment Required (Cont'd)					
34-45-02-12	Test Mode	A	1	0	May be inoperative provided: a) GPWS is considered inoperative, and b) Repairs are made within 2 flight-days.	
34-45-02-13	Modes 2, 4, and 5	C	3	0	One or more may be inoperative.	
34-45-02-14	Advisory Callouts					
34-45-02-14-A		B	-	0	(O) May be inoperative provided alternate procedures are established and used.	
34-45-02-14-B		C	-	0	(O) May be inoperative provided: a) Advisory callout not required by 14 CFR, and b) Alternate procedures are established and used.	
34-45-02-15 ***	Windshear Mode (Reactive)	C	1	0	(O) May be inoperative provided alternate procedures are established and used.	
34-45-02-20	Terrain System – FLTA (Forward Looking Terrain) and PDA (Premature Descent Alert) Functions	B	1	0	May be inoperative.	
34-45-02-30 ***	Terrain Displays	C	-	1	May be inoperative.	
					(Continued)	

REVISION NO. 5

PAGE NO. 34-11

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-45-00	E-GPWS/GPWS (Enhanced Ground Proximity Warning System) (Cont'd)					
34-45-02	Class B TAWS Equipment Required (Cont'd)					
34-45-02-40 ***	RAAS (Runway Awareness and Advisory System)	C	1	0	May be inoperative.	
34-45-03	Class C TAWS Equipment					
34-45-03-10	TAWS/GPWS	C	1	0	(O) May be inoperative provided alternate procedures are established and used. NOTE: Any mode that is operative may be used.	
34-51-00	VOR/ILS Function	C	2	-	As required by 14 CFR.	
34-51-40	Marker Beacon System	C	2	-	May be inoperative provided approaches do not require its use.	
34-51-60 ***	GPS (Global Positioning System)	D	2	-	(O) As required by 14 CFR.	
34-52-00	DME (Distance Measuring Equipment)	D	-	-	Any in excess of those required by 14 CFR may be inoperative.	
34-53-00	ADF (Automatic Direction Finder)	D	2	-	Any in excess of those required by 14 CFR may be inoperative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 34-12

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-54-00	ATC Transponder Function					
34-54-00-10	ATC Transponders and Automatic Altitude Reporting Systems					
34-54-00-10-A		B	-	0	May be inoperative provided: a) Operations do not require its use, and b) Prior to flight, approval is obtained from ATC facilities having jurisdiction over the planned route of flight.	
34-54-00-10-B		D	-	1	Any in excess of those required by 14 CFR may be inoperative.	
34-54-00-20	Elementary and Enhanced Downlink Aircraft Reportable Parameters Not Required by 14 CFR	A	-	0	May be inoperative provided: a) Operations do not require its use, and b) Repairs are made prior to completion of the next heavy maintenance visit.	

AIRCRAFT: Falcon 2000EX	TABLE KEY
	1. REPAIR CATEGORY
	2. NO. INSTALLED
	3. NO. REQUIRED FOR DISPATCH
	4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-55-00 ***	ADS-B (Automatic Dependent Surveillance-Broadcast System) (In and Out)					
34-55-00-A ***		B	-	0	(O) May be inoperative provided prior to flight, authorization is obtained from ATC facilities having jurisdiction over the planned route of flight using an approved authorization process. NOTE: Any ADS-B function that operates normally may be used.	
34-55-00-B ***		C	-	1	One may be inoperative.	
34-55-00-C ***		D	-	0	May be inoperative provided: a) Enroute operations do not require its use, and b) It is not required by 14 CFR. NOTE: Any ADS-B function that operates normally may be used.	
					(Continued)	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 34-14

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-55-00 ***	ADS-B (Automatic Dependent Surveillance-Broadcast System) (Cont'd)					
34-55-00-10 ***	ADS-B Out Extended Squitter Transmissions					
34-55-00-10-A ***		B	-	0	(O) May be inoperative provided prior to flight, authorization is obtained from ATC facilities having jurisdiction over the planned route of flight using an approved authorization process.	
					NOTE: Any ADS-B function that operates normally may be used.	
34-55-00-10-B ***		C	-	1	One may be inoperative.	
34-55-00-10-C ***		D	-	0	May be inoperative provided: a) Enroute operations do not require its use, and b) It is not required by 14 CFR.	
					NOTE: Any ADS-B Out function that operates normally may be used.	
					(Continued)	

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-55-00 ***	ADS-B (Automatic Dependent Surveillance-Broadcast System) (Cont'd)					
34-55-00-20 ***	ADS-B Out UAT (Universal Access Transceiver)					
34-55-00-20-A ***		B	-	0	(O) May be inoperative provided prior to flight, authorization is obtained from ATC facilities having jurisdiction over the planned route of flight using an approved authorization process. NOTE: Any ADS-B Out function that operates normally may be used.	
34-55-00-20-B ***		C	-	1	One may be inoperative.	
34-55-00-20-C ***		D	-	0	May be inoperative provided: a) Enroute operations do not require its use, and b) It is not required by 14 CFR. NOTE: Any ADS-B Out function that operates normally may be used.	
					(Continued)	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 34-16

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	---

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-55-00 ***	ADS-B (Automatic Dependent Surveillance-Broadcast System) (Cont'd)					
34-55-00-30 ***	ADS-B In					
34-55-00-30-A ***		C	-	0	(O) May be inoperative provided alternate procedures are established and used. NOTE: Any ADS-B In function that operates normally may be used.	
34-55-00-30-B ***		D	-	0	May be inoperative provided operations do not require its use. NOTE: Any ADS-B function that operates normally may be used.	

REVISION NO. 5

PAGE NO. 34-17

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

34. Navigation

Sequence No.	Item	1	2	3	4	Change Bar
34-60-00	FMS (Flight Management System)					
34-60-00-A ***	(Aircraft with M2319)	D	3	2	One may be inoperative.	
34-60-00-B		C	-	0	(O) One or more may be inoperative provided: a) Enroute operations and approaches do not require its use, and b) Operative IRS can be initialized.	
34-60-20	Navigation Database	A	-	0	May be inoperative provided: a) Operations do not require its use, b) It is not used in a primary navigation system required by 14 CFR, c) Alternate procedures are developed and used, d) The ICAO Flight Plan is updated (as required) to notify ATC of the navigation equipment status of the aircraft, and e) Is repaired within 10 flight-days. NOTE: An out-of-currency or out-of-date navigation database is not authorized MMEL relief per 14 CFR.	
34-70-00	FANS 1/A+ (Future Air Navigation System) Function (A/C with STC ST03586NY)	D	1	0	May be inoperative provided enroute operations do not require its use.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 35-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

35. Oxygen

Sequence No.	Item	1	2	3	4	Change Bar
35-20-00	Passenger Oxygen System					
35-20-00-A		D	1	0	May be inoperative provided: a) Only the pilot and copilot are on board, b) Passenger OXYGEN Selector is set to CLOSED, and c) Forward Observer Seat is not occupied.	
35-20-00-B		C	1	0	May be inoperative provided the flight altitude is limited to 10,000 ft. or below.	
35-20-00-10	Mask Automatic Dropout Mode	C	1	0	(M)(O) May be inoperative provided: a) Flight level is limited to FL 250 or below, b) OVERRIDE and FIRST AID Oxygen Systems are verified operative, and c) CABIN Warning System (visual and aural) is verified operative.	
35-20-00-20	Mask Unit	C	-	-	(M)(O) One or more may be inoperative provided: a) Affected seat is secured to prevent occupancy, and b) Mask Unit is verified operative for all operative passenger seats, toilet compartments, and flight attendant locations.	
35-21-20	First Aid Oxygen	D	-	-	Any in excess of those required by 14 CFR may be inoperative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 35-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

35. Oxygen

Sequence No.	Item	1	2	3	4	Change Bar
35-30-05	Portable Oxygen Bottles or Units (Including Masks and Hoses)	D	-	-	Any in excess of those required by 14 CFR may be inoperative or removed provided: a) An inoperative or not properly serviced portable oxygen bottle/unit remains in a certified location until removed or serviced at the next suitable maintenance facility, b) Location placarding is removed or obscured, and c) Required distribution is maintained. NOTE 1: Inoperative portable oxygen bottles or units, removed from a certified location or removed from the aircraft, are subject to 49 CFR dangerous goods regulations. NOTE 2: Medical equipment installed in the aircraft as part of an EMS operation is not considered part of the normal complement of equipment. No MMEL relief applies to that equipment and 14 CFR maintenance and inspection requirements do not apply.	
35-30-05-10 ***	Tamper Seals or Tags	C	-	-	(O) May be inoperative, damaged, or missing provided proper installation and servicing is verified at each preflight.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 35-3

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	--

35. Oxygen

Sequence No.	Item	1	2	3	4	Change Bar
35-30-10	PBE (Portable Protective Breathing Equipment)	D	-	-	Any in excess of those required by 14 CFR may be inoperative or removed provided: a) Inoperative PBE remains in a certified location until removed from the aircraft at the next suitable maintenance facility, b) Location placarding is removed or obscured, and c) Required distribution is maintained. NOTE: Inoperative PBE units removed from a certified location, or removed from the aircraft, are subject to 49 CFR dangerous goods regulations.	
35-30-10-10 ***	Tamper Seals or Tags	C	-	-	(O) May be inoperative, damaged, or missing provided proper installation and servicing is verified at each preflight.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 36-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
36-00-01	BASC (Bleed Air System Computer)	B	1	0	(M)(O) May be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, b) Flight is conducted in an unpressurized configuration, c) APU is verified operative before each departure, and d) Both Engine Bleed Air Valves (HP) are secured in closed position.	
36-00-01-10	Anemometry Data Function	C	4	2	One or more may be inoperative provided only one ADC information side is affected.	
36-00-01-20	Computer Failure Warning Function	C	2	0	One or more may be inoperative provided BASC fault codes are considered before each departure.	
36-10-02	Engine Bleed Air Valve (HP)	B	2	1	(M)(O) One may be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, b) Anti-Ice Caution Light is operative, c) APU is verified operative before each departure, d) Associated HP switch is set to OFF, e) CROSSBLEED selector switch is set to OPEN, and f) Associated Engine Bleed Air Valve is secured in closed position. NOTE: APU can pressurize the aircraft up to 35,000 ft. but cannot anti-ice.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 36-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
36-10-03	PRV (Engine Pressure Regulating Valve)	B	2	1	(O) One may be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, b) Opposite Engine Bleed Air Valve (HP) is operative, c) Affected PRV is verified in closed position before each departure, d) APU is verified operative before each departure, e) Associated PRV switch is set to OFF, and f) CROSSBLEED selector switch is set to OPEN. NOTE: APU can pressurize the aircraft up to 35,000 ft. but cannot anti-ice.	
36-10-15	APU Bleed Air System					
36-10-15-A		C	1	0	(M)(O) May be inoperative and APU used for ground engine start provided: a) APU is not used in flight, b) APU is used on ground for electrical generation and engine start only, c) APU is shut down as soon as an engine runs, d) FADECs are operative, e) Landing Gear Retraction System is operative, f) APU Bleed Valve is manually operated for APU-assisted ground engine start, and g) APU Bleed Valve is verified closed before each departure.	
36-10-15-B		C	1	0	(M) May be inoperative provided: a) APU is considered inoperative (item 49-10-01), and b) APU Bleed Valve is verified closed before each departure.	

REVISION NO. 5

PAGE NO. 36-3

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
36-21-01	Cockpit Air Conditioning Temperature Sensor (Tcc)	C	1	0	May be inoperative provided both Bleed Air Temperature Sensors (T1 and T2) are operative.	
36-21-02	Wing Anti-Icing Temperature Sensor (Tv)	C	1	0	(O) May be inoperative provided airplane is not operated in known or forecast icing conditions.	
36-21-08	Cabin Air Conditioning Temperature Sensor (Tcp)	C	1	0	May be inoperative provided both Bleed Air Temperature Sensors (T1 and T2) are operative.	
36-21-09	Pressure Sensor (Pv and Pm)	B	2	0	(M)(O) One or more may be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, b) Flight is conducted in an unpressurized configuration, c) APU is verified operative before each departure, d) EFIS Fans are verified operative, e) PRVs are verified in closed position, f) Engine Bleed Air Valves (HP) are secured in closed position, and g) PRV Switches are set to OFF.	
36-21-10	PAX COND'G OVERPRESS Caution Light	C	1	0	(O) May be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, b) CREW COND'G OVERPRESS Caution Light is operative, c) HP1 and PRV1 Bleed Valve Switches are set to OFF, and d) CROSSBLEED selector switch is set to OPEN.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 36-4

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

36. Pneumatic

Sequence No.	Item	1	2	3	4	Change Bar
36-21-11	CREW COND'G OVERPRESS Caution Light	C	1	0	(O) May be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, b) PAX COND'G OVERPRESS Caution Light is operative, c) HP2 and PRV2 Bleed Valve Switches are set to OFF, and d) CROSSBLEED selector switch is set to OPEN.	
36-21-13	Bleed Air Temperature Sensor (T1 or T2)	B	2	1	(O) One may be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, b) All other Bleed Air Temperature Sensors are operative, c) APU is verified operative before each departure, d) Associated HP switch is set to OFF, and e) CROSSBLEED selector switch is set to OPEN. NOTE: APU can pressurize the aircraft up to 35,000 ft. but cannot anti-ice.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 38-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

38. Water/Waste

Sequence No.	Item	1	2	3	4	Change Bar
38-30-05	Lavatory Waste System	C	1	0	(M) Individual components may be inoperative provided: a) Associated components are deactivated or isolated, and b) Associated system components are verified not to have leaks. NOTE: Any portion of the system which is operative may be used.	
38-30-09	Toilet Drain Valve					
38-30-09-10 ***	Front Toilet Drain Valve					
38-30-09-10-A		A	1	0	May be inoperative in closed position provided repairs are made before next Toilet Drain pan-draining operation.	
38-30-09-10-B		A	1	0	(O) May be inoperative in open position provided: a) Flight is conducted in an unpressurized configuration, b) Front Toilet is not used, c) Draining port cap is verified in locked position, d) Toilet door is placarded "DO NOT USE TOILET", and e) Repairs are made within 3 consecutive calendar-days.	
(Continued)						

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 38-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

38. Water/Waste

Sequence No.	Item	1	2	3	4	Change Bar
38-30-09	Toilet Drain Valve (Cont'd)					
38-30-09-20	Rear Toilet Drain Valve					
38-30-09-20-A		A	1	0	May be inoperative in closed position provided repairs are made before next Toilet Drain pan-draining operation.	
38-30-09-20-B		A	1	0	(O) May be inoperative in open position provided: a) Flight is conducted in an unpressurized configuration, b) Rear Toilet is not used, c) Draining port cap is verified in locked position, d) Toilet door is placarded "DO NOT USE TOILET", and e) Repairs are made within 3 consecutive calendar-days.	
38-32-09-20-C		A	1	0	(M) May be inoperative provided: a) After manually closing the Rear Toilet Drain Valve, it is verified not to have leaks, and b) Repairs are made within 3 consecutive calendar-days.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 45-1

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	---

45. Central Maintenance System

Sequence No.	Item	1	2	3	4	Change Bar
45-10-02	MDC (Maintenance Diagnostic Computer)	D	1	0	May be inoperative provided procedures do not require its use.	
45-90-00	Navigation Database Loading System					
45-90-00-A		C	1	0	May be inoperative provided Navigation Databases are not out of currency.	
45-90-00-B		C	1	0	May be inoperative provided Navigation Databases (item 34-60-20) are considered inoperative.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 46-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

46. Information Systems

Sequence No.	Item	1	2	3	4	Change Bar
46-20-00 ***	EFB (Electronic Flight Bag) System					
46-20-00-02 ***	EFB Device				DELETED, Revision 5.	
					NOTE: Per FAA MMEL Policy Letter 121, a portable EFB is not installed equipment and therefore not required for dispatch. Consequently, portable EFB relief is not appropriate for this MMEL and has been removed from the MMEL.	
46-20-00-03 ***	Power Connection					
46-20-00-03-A ***		C	-	0	(O) May be inoperative provided alternate procedures are established and used.	
46-20-00-03-B ***		D	-	0	May be inoperative provided procedures do not require its use.	
46-20-00-04 ***	Mounting Device					
46-20-00-04-A ***		C	-	0	(M)(O) May be inoperative provided: a) Associated EFB and hardware is stowed, secured by an alternate means, or removed from the aircraft, and b) Alternate procedures are established and used.	
46-20-00-04-B ***		D	-	0	(M) May be inoperative provided: a) Associated EFB and hardware is stowed, secured by an alternate means, or removed from the aircraft, and b) Procedures do not require its use.	
(Continued)						

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 46-2

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	---

46. Information Systems

Sequence No.	Item	1	2	3	4	Change Bar
46-20-00 ***	EFB (Electronic Flight Bag) System (Cont'd)					
46-20-00-05 ***	Data Connectivity					
46-20-00-05-A ***		C	-	-	(O) May be inoperative provided alternate procedures are established and used.	
46-20-00-05-B ***		D	-	0	May be inoperative provided procedures do not require its use.	

REVISION NO. 5

PAGE NO. 49-1

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

49. Airborne Auxiliary Power

Sequence No.	Item	1	2	3	4	Change Bar
49-00-10	APU START/STOP Switch					
49-00-10-10	Light Bulb					
49-00-10-10-A		C	4	2	One or two may be inoperative.	
49-00-10-10-B		C	4	0	One or more may be inoperative provided APU is considered inoperative (item 49-10-01).	
49-00-11	APU MASTER Switch					
49-00-11-10	Light Bulb					
49-00-11-10-A		C	4	2	One or two may be inoperative.	
49-00-11-10-B		C	4	0	One or more may be inoperative provided APU is considered inoperative (item 49-10-01).	
49-10-01	APU (Auxiliary Power Unit)	C	1	0	(O) May be inoperative provided: a) Both FADECs are operative, b) Landing Gear Retraction System is operative, and c) MASTER APU is set to OFF.	
49-50-01	APU Inlet Door					
49-50-01-A		C	1	0	(M) May be inoperative closed provided: a) APU is considered inoperative (item 49-10-01), and b) APU Inlet Door is secured in closed position.	
49-50-01-B		C	1	0	(M)(O) May be jammed in other than closed position provided: a) APU is considered inoperative (item 49-10-01), b) AFM Limitations and Performance are applied, and c) APU Inlet Door is secured.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 49-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

49. Airborne Auxiliary Power

Sequence No.	Item	1	2	3	4	Change Bar
49-50-05	APU Door Indication System					
49-50-05-A		C	1	0	May be inoperative provided APU Inlet Door operations are visually verified operative by performing an APU on/off cycle before each departure.	
49-50-05-B		C	1	0	May be inoperative provided APU is considered inoperative (item 49-10-01).	
49-60-05	APU FAULT Caution Light	C	1	0	(O) May be inoperative provided: a) APU is considered inoperative (item 49-10-01), and b) APU Inlet Door is verified in closed position.	
49-70-00	APU Indications (N ₁ , EGT, OVSP, Oil)	C	4	0	(O) One or more may be inoperative provided: a) APU is only used for engine start, b) APU FAULT Caution Light is operative, c) APU is verified operative before each flight, and d) APU FAULT Caution Light is monitored during APU use.	
49-70-40	APU GEN Caution Light	A	1	0	(O) May be inoperative provided: a) APU is only used for engine start, b) APU GEN Switch is set to OFF, c) LH Ammeter is closely monitored during APU start, and d) Repairs are made within 2 consecutive calendar-days.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 49-3

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	---

49. Airborne Auxiliary Power

Sequence No.	Item	1	2	3	4 Change Bar
49-91-10	APU Oil Test and Level Indication				
49-91-10-A		C	1	0	May be inoperative provided APU is considered inoperative (item 49-10-01).
49-91-10-B		A	1	0	(M) May be inoperative provided: a) APU oil quantity is visually verified within the first three flights of the repair interval, and b) Repairs are made within 40 flight-hours.

REVISION NO. 5

PAGE NO. 52-1

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

52. Doors

Sequence No.	Item	1	2	3	4	Change Bar
52-00-10	DOORS Warning Light	C	1	0	(O) May be inoperative provided the doors are verified closed and locked before each departure.	
52-10-20	Passenger Door Electrical Maneuver System					
52-10-20-01	Electrical Lifting	B	1	0	(O) May be inoperative provided: a) The door is closed with an alternate procedure, and b) Door opening duration is verified adequate.	
52-10-20-02	DOOR LIFT Amber Light	B	1	0	(O) May be inoperative provided door opening duration is verified adequate.	
52-30-00	Baggage Compartment External Door					
52-30-00-01	Proximity Sensor	C	4	0	(O) One or more may be inoperative provided Baggage Compartment External Door is verified to be latched and locked before each departure.	
52-40-10 ***	Pocket Sliding Door (Galley to Cabin)	D	1	0	(M) May be inoperative provided the door is secured open.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 73-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

73. Engine Fuel and Control

Sequence No.	Item	1	2	3	4	Change Bar
73-20-01	FADEC (Full-Authority Digital Engine Control)					
73-20-01-03	Channel	A	4	-	All FADEC Channels must be operative; however, aircraft may be dispatched with FADEC fault provided repairs are made in accordance with times established by Short Time/Long Time Dispatch Fault items, or by PWC Type Certificate Data Sheet number E00065NE, note 13, whichever is more restrictive.	
73-20-01-10	Short Time Dispatch Fault	A	-	-	Only one engine may be affected provided repairs are made within 125 flight-hours.	
73-20-01-11	Long Time Dispatch Fault	A	-	-	Only one engine may be affected provided repairs are made within 350 flight-hours.	
73-40-01	APR Automatic Mode	A	1	0	(O) May be inoperative provided: a) APR O'RIDE operation is verified operative on both engines before departure, b) APR O'RIDE Button is pressed before takeoff and landing, and c) Repairs are made within 2 consecutive calendar-days.	
73-40-05	APR Caution Light	A	1	0	(O) May be inoperative provided: a) All EIED are operative, b) APR Label on EIED Engine Page is verified operative, c) APR O'RIDE Button is pressed before takeoff and landing, and d) Repairs are made within 2 consecutive calendar-days.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 74-1

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
------------------------------------	---

74. Ignition

Sequence No.	Item	1	2	3	4 Change Bar
74-10-10	Igniter Channel	B	4	3	(O) One may be inoperative provided: a) Both FADECs are operative, b) Only one engine has a detected ground start light-off fault, and c) AFM procedure for starting engine in IGNITION mode is complied with.

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 77-1

AIRCRAFT: Falcon 2000EX	TABLE KEY 1. REPAIR CATEGORY 2. NO. INSTALLED 3. NO. REQUIRED FOR DISPATCH 4. REMARKS OR EXCEPTIONS
----------------------------	--

77. Engine Indicating

Sequence No.	Item	1	2	3	4	Change Bar
77-30-01	Engine Vibration Indication	C	2	1	One may be inoperative.	
77-30-10	EVMC (Engine Vibration Monitor Computer) Channel	C	2	1	One may be inoperative.	

REVISION NO.5

PAGE NO. 78-1

DATE: XX/XX/XXXX

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

78. Engine Exhaust

Sequence No.	Item	1	2	3	4	Change Bar
78-30-00	Thrust Reverser System	A	2	0	(M) One or more may be inoperative provided: a) AFM takeoff distance is increased by 70 ft., b) Takeoff and landing are not conducted on an icy runway, c) Both Thrust Reversers have sustained no damage, d) Both Thrust Reversers are secured in stowed position, e) Airbrakes are manually extended in case of RTO below V_1 (Airbrake Handle on position 2), and f) Repairs are made within 100 consecutive calendar-days.	
78-30-05	TRANS Amber Light	A	2	0	One or more may be inoperative provided: a) Thrust Reverser System is considered inoperative (item 78-30-00), and b) Repairs are made within 100 consecutive calendar-days.	
78-30-07	DEPLOY Green Light	A	2	0	One or more may be inoperative provided: a) Thrust Reverser System is considered inoperative (item 78-30-00), and b) Repairs are made within 100 consecutive calendar-days.	
78-30-09	THRUST REVERSER 1/2 Caution Light	A	2	0	One or more may be inoperative provided: a) Thrust Reverser System is considered inoperative (item 78-30-00), and b) Repairs are made within 100 consecutive calendar-days.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 79-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

79. Engine Oil

Sequence No.	Item	1	2	3	4	Change Bar
79-30-00	Engine Oil Level Indication System	C	1	0	(M) May be inoperative provided oil tank level of affected engine is verified adequate before each departure.	
79-30-02	Engine Oil Pressure Indication				DELETED, Revision 5.	
79-30-03	Engine Oil Chip Detector System	C	2	0	(M) One or more may be displayed provided associated magnetic chip detector is verified free of metal particles before each flight.	
79-30-05	Engine Oil Filter Clogging Indication	C	2	0	(M) One or more may be displayed provided associated Engine Oil Filter is verified free of contamination before each departure.	
79-30-10	Engine Oil Low Pressure Warning System	A	2	1	One may be inoperative provided: a) Associated Oil Pressure and Oil Temperature Indications are operative, b) Associated Oil Pressure and Oil Temperature Indications are monitored at least every 30 minutes in flight, and c) Repairs are made within 2 consecutive calendar-days.	

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 80-1

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

80. Starting

Sequence No.	Item	1	2	3	4	Change Bar
80-10-13	Engine Starting Valve					
80-10-13-10	Left Engine Starting Valve	A	1	0	(M)(O) May be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, b) Right Engine Starting Valve is operative, c) RH BUS TIED Caution Light is operative, d) APU is verified operative before each departure, e) Bus Tie System is verified operative, f) Fuel Crossfeed System is verified operative, g) Wing tank pressurization is verified adequate, h) All Booster Pumps are verified operative, i) Affected valve is opened manually before engine start and secured in closed position after engine start, and j) Repairs are made within 2 consecutive calendar-days. NOTE: In flight, restart of associated engine is only possible using ENGINE-WINDMILLING AIRSTART procedure.	
(Continued)						

REVISION NO. 5
DATE: XX/XX/XXXX

PAGE NO. 80-2

AIRCRAFT:
Falcon 2000EX

TABLE KEY

1. REPAIR CATEGORY
2. NO. INSTALLED
3. NO. REQUIRED FOR DISPATCH
4. REMARKS OR EXCEPTIONS

80. Starting

Sequence No.	Item	1	2	3	4	Change Bar
80-10-13	Engine Starting Valve (Cont'd)					
80-10-13-20	Right Engine Starting Valve	A	1	0	(M)(O) May be inoperative provided: a) Airplane is not operated in known or forecast icing conditions, b) Left Engine Starting Valve is operative, c) RH BUS TIED Caution Light is operative, d) APU is verified operative before each departure, e) Bus Tie System is verified operative, f) Fuel Crossfeed System is verified operative, g) Wing tank pressurization is verified adequate, h) All Booster Pumps are verified operative, i) Affected valve is opened manually before engine start and secured in closed position after engine start, and j) Repairs are made within 2 consecutive calendar-days. NOTE: In flight, restart of associated engine is only possible using ENGINE-WINDMILLING AIRSTART procedure.	