

Airport Design 150/5300-13A → 150/5300-13B Crosswalk

-13A	-13A heading	-13B	-13B heading
Chapter 1	Introduction	Chapter 1	Introduction
101	Purpose	1.1 1.2 1.3	Policy Standards, Recommended Practices and Requirements Federal Regulations
102	Definitions.	1.5	Definitions
103.	Roles of Federal, State and Local governments.	1.9 1.10 1.11	Airport Improvement Program (AIP) State Role Local Government Role
104	Airport operator responsibilities.	Deleted	
105	Planning.	2.2 1.6	Airport Planning Relationship to Airport Design Categories and Codes
106	Airport Layout Plan (ALP).	1.7	Airport Layout Plan (ALP)
107	Collection, processing and publication of airport data.	1.8	Airport Data
108	Related Advisory Circulars (ACs), Orders, and Federal regulations.	1.12	Related Documents and Federal Regulations
Table 1-1	Aircraft Approach Category (AAC)	Table 1-1	Aircraft Approach Category (AAC)
Table 1-2	Airplane Design Group (ADG)	Table 1-2	Airplane Design Group (ADG)
Table 1-3	Visibility minimums	Table 1-3	Visibility Minimums
Figure 1-1	Taxiway Design Groups (TDGs)	Figure 1-1	Taxiway Design Groups (TDGs)
Chapter 2	Design Process	Chapter 2	Design Principles
201	General.	2.1	General
202	Design aircraft.	2.6.1	Critical Aircraft
203	Runway incursions.	2.7.1	Runway Incursions
204	Airport design standards and the environmental process.	2.6	Design Process
205	Planned visibility minimums for instrument procedures.	2.6.3 2.6.4	Considerations for Visibility Minimums Visibility Categories
206	Airport Traffic Control Tower (ATCT) siting.	Deleted	
207	Airport Reference Point (ARP).	Deleted	
208	Heliports/helipads.	2.10.1	Heliports/Helipads
209	Other aeronautical uses on airports.	2.10	Diverse Aeronautical Activities on Airports
210	Drainage considerations.	6.3	Airfield Drainage
211	Security of airports.	6.8	Security of Airports
212	Pavement strength and design.	Deleted	
213	Location of on-airfield facilities.	Deleted	
Table 2-1	Changes in airport design standards associated with an upgrade in the first two components (Aircraft Approach Category [AAC] and Airplane Design Group [ADG]) of the Runway Design Code (RDC)	Table M-1	Differences in Design Standards with Upgrade in Aircraft Approach Category (AAC) and Airplane Design Group (ADG)
Table 2-2	Changes in airport design standards associated with lowering the third component (approach visibility minimums) of the Runway Design Code (RDC)	Table M-2	Differences in Airport Design Standards with Lowering Approach Visibility Minimums
Table 2-3	Aircraft characteristics and design components	Table M-3	Relationship of Aircraft Characteristics to Design Components
Chapter 3	Runway Design	Chapter 3	Runway Design
301	Introduction.	3.1	General
302	Runway design concepts.	3.4	Runway Design Concepts and Considerations
303	Runway end siting requirements.	3.5	Runway End Siting Criteria
304	Runway geometry.	3.7	Runway Geometry

Airport Design 150/5300-13A → 150/5300-13B Crosswalk

-13A	-13A heading	-13B	-13B heading
305	Runway line of sight requirements.	3.8	Runway Line of Sight (LOS)
306	Object clearing.	I.5	Object Clearing
307	Runway Safety Area (RSA) / Engineered Materials Arresting Systems (EMAS).	3.10 3.10.2.3	Runway Safety Area (RSA) Engineered Materials Arresting Systems (EMAS)
307.a(1)	Historical Development	I.2.1	Historical Development
307.a(2)	Recent Changes	I.2.2	Incremental Improvements
308	Obstacle Free Zone (OFZ).	3.11	Obstacle Free Zone (OFZ)
308.a	Runway Obstacle Free Zone (ROFZ).	3.11.2	Runway Obstacle Free Zone (ROFZ)
308.b	Inner-approach OFZ.	3.11.3	Inner-approach OFZ (IA-OFZ)
308.c	Inner-transitional OFZ.	3.11.4	Inner-transitional OFZ (IT-OFZ)
308.d	Precision Obstacle Free Zone (POFZ).	3.11.5	Precision Obstacle Free Zone (POFZ)
309	Runway Object Free Area (ROFA).	3.12	Runway Object Free Area (ROFA)
310	Runway Protection Zone (RPZ).	3.13	Runway Protection Zone (RPZ)
310.a	RPZ Background.	I.3	Runway Protection Zone (RPZ) Background
311	Clearway standards.	3.14	Clearway
312	Stopway standards.	3.15	Stopway
313	Surface gradient.	3.16	Surface Gradient
314	Turf runways.	3.20	Turf Runways
315	Marking and lighting.	3.21	Markings/Lighting/Signs
316	Parallel runway separation requirements.	3.9	Parallel Runway Separation
317	Approach procedures.	Appendix K	Instrument Flight Procedures
318	Aircraft Rescue and Fire Fighting (ARFF) access.	6.5.3	Aircraft Rescue and Fire Fighting (ARFF) Access Roads
319	Jet blast.	5.17	Jet Blast and Propeller Wash on Aprons
320	Runway design requirements matrix.	Deleted	
321	On-airport farming.	Deleted	
322	Declared distances.	Appendix H	Declared Distances
323	Approach and Departure Reference Codes.	Appendix L	Approach and Departure Reference Codes
Table 3-1	Allowable crosswind component per Runway Design Code (RDC)	Table B-1	Allowable Crosswind Component per Runway Design Code (RDC)
Table 3-2	Approach/departure standards table	Table 3-2 Table 3-3 Table 3-4 Table 3-5	Visual Approach Surfaces Non-Precision and IFR Circling Approach Surfaces APV and PA Instrument Runway Approach Surfaces Instrument Departure Surface
Table 3-3	Transverse grades	Table 3-6 Table 3-7	Transverse Grades Based on AAC Transverse Grades Based on ADG
Table 3-4	Standards for Instrument Approach Procedures	Table K-1	Criteria to Support Instrument Flight Procedure Development
Table 3-5	Runway design standards matrix	Online tool Table 3-1	Runway Design Standards Matrix Runway Design Standards
Table 3-6	Runway to taxiway separation for reverse turns from a high-speed exit based on Taxiway Design Group (TDG)	Table 4-5	Runway to Taxiway Separation for Reverse Turns from a High-Speed Exit Based on TDG
Table 3-7	Approach Reference Code (APRC)	Table L-1	Approach Reference Code (APRC)
Table 3-8	Departure Reference Code (DPRC)	Table L-2	Departure Reference Code (DPRC)
Figure 3-1	Runway ends	Figure 3-2	Runway Ends
Figure 3-2.a	Threshold siting based on approach slope	Figure 3-3	Standard Approach Surface
Figure 3-2.b	Threshold siting based on approach slope	Figure 3-4	Displaced Threshold
Figure 3-3	Approach slopes – with offset approach course	Figure 3-8	Offset Approach Plane
Figure 3-4	Departure surface for instrument runways (40:1)	Figure 3-9	Instrument Departure Surface
Figure 3-5	Runway Safety Area (RSA)	Figure 3-19	Runway Safety Area (RSA)

Airport Design 150/5300-13A → 150/5300-13B Crosswalk

-13A	-13A heading	-13B	-13B heading
Figure 3-6	Intersecting runways	Figure 3-13	Intersecting Runways
Figure 3-7	Runway visibility zone	Figure 3-14	Runway Visibility Zone – Perpendicular Intersection Runways
		Figure 3-15	Runway Visibility Zone – Non-Perpendicular Intersecting Runways – X Less Than 750 Feet (229 m)
		Figure 3-16	Runway Visibility Zone – Non-Perpendicular Intersecting Runways – X Distance Equal to or Greater Than 750 Feet (229 m)
Figure 3-8	Percent of aircraft overrun versus distance beyond the runway end	Figure I-1	Percent of Aircraft Overrun Versus Distance Beyond the Runway End
Figure 3-9	Obstacle Free Zone (OFZ) for visual runways and runways with not lower than 3/4 statute mile (1.2 km) approach visibility minimums	Figure 3-20	Obstacle Free Zone (OFZ) for Visual Runways and Runways with Not Lower Than 3/4 Statute Mile (1.2 km) Approach Visibility Minimums
Figure 3-10	OFZ for operations on runways by small aircraft with lower than 3/4 statute mile (1.2 km) approach visibility minimums	Figure 3-21	OFZ for Operations on Runways by Small Aircraft with Lower Than 3/4 Statute Mile (1.2 km) Approach Visibility Minimums
Figure 3-11	OFZ for operations on runways by large aircraft with lower than 3/4 statute mile (1.2 km) approach visibility minimums	Figure 3-22	OFZ for Operations on Runways by Large Aircraft with Lower Than 3/4 Statute Mile (1.2 km) Approach Visibility Minimums
Figure 3-12	OFZ for operations on runways by large aircraft with lower than 3/4 statute mile (1.2 km) approach visibility minimums and displaced threshold	Figure 3-23	OFZ for Operations on Runways by Large Aircraft with Lower Than 3/4 Statute Mile (1.2 km) Approach Visibility Minimums and Displaced Threshold
Figure 3-13	Sectional views of the OFZ	Figures 3-20, 3-21, 3-22	Incorporated into Figures 3-20 thru 3-22
Figure 3-14	Precision Obstacle Free Zone (POFZ) – no displaced threshold	Figure 3-24	Precision Obstacle Free Zone (POFZ) – No Displaced Threshold
Figure 3-15	POFZ – displaced threshold	Figure 3-25	POFZ – Displaced Threshold
Figure 3-16	Runway Protection Zone (RPZ), Runway Object Free Area (ROFA) and Runway Safety Area (RSA)	Figure 3-26	Runway Protection Zone (RPZ), Runway Object Free Area (ROFA), and Runway Safety Area (RSA)
Figure 3-17	Runway with all declared distances equal to the runway length	Figure 3-27	Runway with All Declared Distances Equal to the Runway Length
Figure 3-18	Approach and departure RPZs where the Takeoff Run Available (TORA) is less than the Takeoff Distance Available (TODA)	Figure 3-28	Approach and Departure RPZs Where the Takeoff Run Available (TORA) is Less Than the Takeoff Distance Available (TODA)
Figure 3-19	Clearway	Figure 3-29	Clearway
Figure 3-20	Stopway	Figure 3-30	Stopway
Figure 3-21	Longitudinal grade limitations for aircraft approach categories A and B	Figure 3-32	Longitudinal Grade Limitations for Aircraft Approach Categories A and B
Figure 3-22	Longitudinal grade limitations for aircraft approach categories C, D, and E	Figure 3-33	Longitudinal Grade Limitations for Aircraft Approach Categories C, D, and E
Figure 3-23	Transverse grade limitations	Figure 3-34	Transverse Grade Limitations
Figure 3-24	RSA grade limitations beyond 200 feet (61 m) from the runway end	Figure 3-35	RSA Grade Limitations Beyond 200 feet (61 m) from the Runway End
Figure 3-25	Parallel runway separation, simultaneous radar controlled approach – staggered threshold	Figure 3-18	Parallel Runway Separation – Simultaneous Radar-Controlled Approach Mixed Operations with Staggered Threshold
Figure 3-26	Typical airport layout	Figure 3-1	Airport Layout Example
Figure 3-27	Location of start of Accelerate-Stop Distance Available (ASDA), TODA, and TORA	Figure H-1	Typical Starting Point for ASDA, TODA, and TORA
Figure 3-28	Normal location of departure end of TORA	Figure H-2	Typical Location for Departure End of TORA

Airport Design 150/5300-13A → 150/5300-13B Crosswalk

-13A	-13A heading	-13B	-13B heading
Figure 3-29	Departure end of TORA based on departure RPZ located to mitigate unacceptable incompatible land use	Figure H-3	Modified Departure End of TORA due to Incompatible Land Use Within RPZ
Figure 3-30	TODA shortened to mitigate penetration to the departure surface resulting in shortened TORA	Figure H-4	Modified TODA and TORA due to Object Penetration of 40:1 Surface
Figure 3-31	TODA extended by use of a clearway, shortened TORA	Figure H-5	Extended TODA with Clearway – Shortened TORA
Figure 3-32	Normal location of departure end of TODA (no clearway)	Figure H-6	Typical Location of TODA Departure End of Runway (DER) – No Clearway
Figure 3-33	TODA extended by use of a clearway, normal TORA	Figure H-7	Extended TODA with Clearway – Typical TORA
Figure 3-34	Normal location of stop end of ASDA and Landing Distance Available (LDA)	Figure H-8	Typical Location of Departure End of ASDA and LDA
Figure 3-35	Stop end of ASDA and LDA located to provide additional RSA	Figure H-9	Adjusted ASDA and LDA Departure End for the RSA
Figure 3-36	Stop end of ASDA and LDA located to provide additional Runway Object Free Area (ROFA)	Figure H-10	Adjusted ASDA and LDA Departure End for ROFA
Figure 3-37	Stop end of ASDA located based on use of a stopway	Figure H-11	Departure End of ASDA with Stopway
Figure 3-38	Normal start of LDA	Figure H-12	Typical Start of LDA
Figure 3-39	Start of LDA at displaced threshold based on Threshold Siting Surface (TSS)	Figure H-13	LDA Starting Point – Displaced Threshold for Approach and Departure Surface
Figure 3-40	Start of LDA at displaced threshold based on approach RPZ located to mitigate unacceptable incompatible land use	Figure H-14	LDA Starting Point – Displaced Threshold for Adjusted RPZ
Figure 3-41	Start of LDA at displaced threshold located to provide additional RSA	Figure H-15	LDA Starting Point – Displaced Threshold for Adjusted RSA
Figure 3-42	Start of LDA at displaced threshold located to provide additional ROFA	Figure H-16	LDA Starting Point – Displaced Threshold for Adjusted ROFA
Chapter 4	Taxiway and Taxilane Design	Chapter 4	Taxiway and Taxilane Design
401	General.	4.1	General
402	Taxiway definitions.	Deleted	
403	Taxiway/taxilane width.	4.4	Straight Segment Taxiway/Taxilane Width
404	Taxiway/taxilane clearance requirements.	4.5	Taxiway/Taxilane Clearance
405	Parallel taxiways.	4.6	Parallel Taxiways
406	Curves and intersections.	4.7 4.3.3	Taxiway Fillet Design Three-Path Concept
407	Runway/taxiway intersections.	4.8	Runway/Taxiway Intersections
408	Entrance taxiways.	4.8.2	Entrance Taxiways
409	Exit taxiways.	4.8.4 4.8.5	Exit Taxiways High-Speed Exit Taxiways
410	Bypass taxiways.	4.8.3	Bypass Taxiways
411	Crossover taxiways.	4.8.6	Crossover Taxiways
412	Holding bays for runway ends.	4.9	Holding Bays for Runway Ends
413	Taxiway turnarounds.	4.10	Taxiway Turnarounds
414	Apron taxiways and taxilanes.	4.11	Apron Taxiways and Taxilanes
415	End-Around Taxiways (EAT).	4.12	End-Around Taxiways (EAT)
416	Aligned taxiways prohibited.	J.5.15	Aligned Taxiways
417	Taxiway shoulders.	4.13	Taxiway and Taxilane Shoulders
418	Surface gradient and Line Of Sight (LOS).	4.14	Surface Gradient for Taxiways, Taxilanes, and TSAs
419	Markings/lighting/signs.	4.16	Markings/Lighting/Signs
420	Islands.	Deleted	

Airport Design 150/5300-13A → 150/5300-13B Crosswalk

-13A	-13A heading	-13B	-13B heading
421	Taxiway bridges.	Deleted	
422	Jet blast.	Deleted	
Table 4-1	Design standards based on Airplane Design Group (ADG)	Table 4-1	Design Standards Based on Airplane Design Group (ADG)
Table 4-2	Design standards based on Taxiway Design Group (TDG)	Table 4-2	Design Standards Based on Taxiway Design Group (TDG)
Tables 4-3 thru 4-9	Standard intersection details for TDGs 1A, 1B, 2, 3, 4, 5, 6	Tables J-1 thru J-8	Standard intersection details for TDGs 1A, 1B, 2A, 2B, 3, 4, 5, 6
Table 4-10	Standard intersection details for TDG 7	Deleted	
Table 4-11	MGW-CMG combinations	Deleted	
Table 4-12	Dimensions for runway entrance/exit taxiways (where the two 90-degree turns are nonstandard)	Table 4-3 Table 4-4	Dimensions for Runway Entrance/Exit Taxiways with TDG 1A, 1B, 2A, or 2B (Where the Two 90-Degree Turns are Nonstandard) Dimensions for Runway Entrance/Exit Taxiways with TDG 3, 4, 5, or 6 (Where the Two 90-Degree Turns are Nonstandard)
Table 4-13	Exit taxiway cumulative utilization percentages	Deleted	
Table 4-14	Crossover taxiways with direction reversal between taxiways based on TDG	Table 4-6	Crossover Taxiways with Direction Reversal Between Taxiways Based on TDG
Table 4-15	Crossover taxiways with direction reversal between taxiways based on ADG	Table 4-7	Crossover Taxiways with Direction Reversal Between Taxiways Based on ADG
Figure 4-1	Three-node taxiway intersection	Figure 4-1	Three-Path Concept Taxiway Intersection
Figure 4-2	Not recommended taxiway design	Deleted	
Figure 4-3	Proper taxiway design	Deleted	
Figure 4-4.a	Taxiway designs that are not recommended (examples a, b, c, d)	Figure J-22	High-Speed Exit Collocated with Connecting Taxiway
Figure 4-4.b	Taxiway designs that are not recommended (examples a, b, c, d)	Figure J-24	Parallel Taxiway Adjacent to Apron Pavement
Figure 4-4.c	Taxiway designs that are not recommended (examples a, b, c, d)	Figure J-16	Complex Taxiway Intersection Not Meeting the “Three-Path Concept”
Figure 4-4.d	Taxiway designs that are not recommended (examples a, b, c, d)	Figure J-18	Taxiway Intersection that Coincides with Multiple Runways
Figure 4-5.e	Taxiway designs that are not recommended (examples e, f, g)	Deleted	
Figure 4-5.f	Taxiway designs that are not recommended (examples e, f, g)	Figure J-13	Extra-Wide Pavement Area at Runway Entrance
Figure 4-5.g	Taxiway designs that are not recommended (examples e, f, g)	Figure J-19	Y-Shaped Taxiway Crossing a Runway
Figure 4-6	Taxiway Edge Safety Margin (TESM) on straight segment	Figure 4-4	Taxiway Edge Safety Margin (TESM) - Straight Segment
Figure 4-7	Wingtip clearance - parallel taxiways	Figure 4-5	Wingtip Clearance - Parallel Taxiways/Taxilanes
Figure 4-8	Wingtip clearance from taxiway	Figure 4-6	Wingtip Clearance from Taxiway
Figure 4-9	Wingtip clearance from taxilane	Figure 4-7	Taxilane Separations and Clearances
Figure 4-10	Wingtip clearance from apron taxiway	Figure 4-8	Wingtip Clearance from Apron Taxilane
Figure 4-11	TSA and TOFA at taxiway intersections	Figure 4-9	TSA and TOFA at Taxiway Intersections
Figure 4-12	Parallel taxiways	Figure 4-10	Parallel Taxiways
Figure 4-13	Taxiway turn - 90 degree delta	Figure 4-12	Taxiway Turn – 90 Degree Delta
Figure 4-14	Taxiway turn - less than 90 degree delta	Figure 4-13	Taxiway Turn - Less Than 90 Degree Delta
Figure 4-15	Taxiway turn - greater than 90 degree delta	Figure 4-14	Taxiway Turn - Greater Than 90 Degree Delta
Figure 4-16	Key MGW-CMG combinations for modeling aircraft movements	Deleted	
Figure 4-17	Entrance taxiway	Figure 4-15	Entrance Taxiway
Figure 4-18	High speed exit for TDG-5	Figure 4-18	High-Speed Exit – TDG-5
Figure 4-19	Right-angled exit taxiway	Figure 4-20	Right-Angled Exit Taxiway

Airport Design 150/5300-13A → 150/5300-13B Crosswalk

-13A	-13A heading	-13B	-13B heading
Figure 4-20	Poor design of high speed exits	Figure J-28	Co-located High-Speed Runway Exit Taxiways
Figure 4-21	Proper design of high speed exits	Figure 4-21	High-Speed Exit Separation
Figure 4-22	Bypass taxiway	Figure 4-16	Bypass Taxiway Bay Configuration
Figure 4-23	Crossover taxiway where direction reversal is needed based on TDG	Figure 4-22	Crossover Taxiway where Direction Reversal is Needed Based on TDG
Figure 4-24	Crossover taxiway where direction reversal is necessary based on ADG	Figure 4-23	Crossover Taxiway where Direction Reversal is Necessary Based on ADG
Figure 4-25	Crossover taxiway without direction reversal between taxiways	Figure 4-24	Crossover Taxiway Without Direction Reversal Between Taxiways
Figure 4-26	Typical holding bay configuration	Figure 4-25	Holding Bay Configuration
Figure 4-27	Holding bay – not recommended design	Figure J-26	Poor Holding Bay – Moderate Risk Configuration
Figure 4-28	Poor holding bay design	Figure J-27	Poor Holding Bay – Elevated Risk Configuration
Figure 4-29	Taxiway turnaround	Figure 4-27	Taxiway Turnaround
Figure 4-30	End-Around Taxiway (EAT) – ADG-II	Figure 4-28	End-Around Taxiway (EAT)
Figure 4-31	EAT – ADG-III	Deleted	
Figure 4-32	Aligned taxiway	Figure J-30	Aligned Taxiway and Corrected Design
Figure 4-33	Taxiway transverse gradients	Figure 4-29	Taxiway and Taxilane Transverse Gradients
Chapter 5	Aprons	Chapter 5	Aprons
501	Background.	5.1	General
502	Apron types.	5.2	Apron Types
503	Apron layout and runway incursion prevention.	5.3	Apron Design Concepts and Considerations
504	Apron design.	5.4	Apron Location
505	Fueling.	5.8	Fueling on Aprons
506	Object Clearance.	Deleted	
507	Deicing facilities.	5.2.6	Deicing Apron (Pads)
508	Surface gradients.	5.9	Apron Surface Gradients
509	Drainage.	5.10	Apron Drainage
510	Marking and lighting.	5.12 5.13 5.14	Apron Markings Apron Signage and Edge Lighting Area Lighting on Aprons
511	Pavement design.	5.16	Apron Pavement Design
512	Jet blast.	Deleted	
513	Airport Traffic Control Tower (ATCT) visibility / Line Of Sight (LOS).	5.18	Airport Traffic Control Tower (ATCT) Visibility/ Line of Sight (LOS) on Aprons
514	Apron service roads.	5.19	Apron Vehicle Service Road
Chapter 6	Navigation Aids (NAVAIDs) and On-airport Air Traffic Control Facilities (ATC-F)	Chapter 6	Airfield Systems and Facilities
601	Background.	3.4.10	Navigation Aids (NAVAIDs)
602	Introduction and purpose.	6.1	General
603	Federally owned and non-federally owned NAVAIDs.	Deleted	
604	Siting criteria/land requirements.	6.11.4	General Facility Criteria
605	NAVAIDs as obstacles.	6.11.6	Facilities and Equipment near Runways
606	Physical security.	Deleted	
607	Maintenance access.	Deleted	
608	Electrical power.	Deleted	
609	Cable protection.	Deleted	
610	Cable loop system.	6.10.3.3	Cable Loop Systems
611	Communication and power cable trenches.	Deleted	
612	Facilities.	6.11	Communications, Navigation, Surveillance and Weather (CNSW) and Air Traffic Control (ATC) Facilities and Equipment.
613	Towers and elevated structures.	Deleted	

Airport Design 150/5300-13A → 150/5300-13B Crosswalk

-13A	-13A heading	-13B	-13B heading
614	Air Traffic Organization (ATO) – Orders and Notices.	Deleted	
615	Decommissioned facilities.	Deleted	
616	Airport Traffic Control Tower (ATCT).	6.11.7	Airport Traffic Control Tower (ATCT)
617	Remote Transmitter/Receiver (RTR) and Remote Communications Outlet (RCO).	6.11.8	Remote Transmitter/Receiver (RTR) and Remote Communications Outlet (RCO)
618	Airport Surveillance Radar (ASR).	6.11.9	Airport Surveillance Radar (ASR)
619	Precision Runway Monitor (PRM).	Deleted	
620	Airport Surface Detection Equipment (ASDE).	6.11.10	Airport Surface Surveillance Capability (ASSC)/Airport Surface Detection Equipment Model X (ASDE-X)
621	Approach Lighting System (ALS).	6.11.11	Approach Lighting System (ALS)
622	Approach Lead-In Lighting System (LDIN).	6.11.11.8	Approach Lead-In Lighting System (LDIN)
623	Runway End Identifier Lighting (REIL).	6.11.12	Runway End Identifier Lighting (REIL)
624	Airport rotating beacons.	6.11.13	Airport Rotating Beacons
625	Precision Approach Path Indicator (PAPI).	6.11.14	Precision Approach Path Indicator (PAPI)
626	Instrument Landing System (ILS).	6.11.15	Instrument Landing System (ILS)
627	Distance Measuring Equipment (DME).	6.11.18	Distance Measuring Equipment (DME)
628	Runway Visual Range (RVR).	6.11.19	Runway Visual Range (RVR)
629	Very High Frequency Omnidirectional Range (VOR).	6.11.20	Very High Frequency Omnidirectional Range (VOR)
630	Non-Directional Beacon (NDB).	6.11.21	Non-Directional Beacon (NDB)
631	Segmented circles and wind cones.	6.11.22	Segmented Circles and Wind Cones
632	Automated Surface Observing System (ASOS) and Automated Weather Observing System (AWOS).	6.11.23	Automated Surface Observing System (ASOS) and Automated Weather Observing System (AWOS)
633	Weather Camera (WCAM).	6.11.24	Weather Camera (WCAM)
634	Wind Equipment F-400 (WEF).	6.11.25	Wind Equipment F-400 (WEF)/Wind Measuring Equipment (WME)
635	Low Level Windshear Alert System (LLWAS).	6.11.26	Low Level Windshear Alert System (LLWAS)
636	Runway Status Lights (RWSL).	6.11.27	Runway Status Lights (RWSL)
Table 6-1	Fixed-by-function designation for NAVAID and Air Traffic Control (ATC) facilities for Runway Safety Area (RSA) and Runway Object Free Area (ROFA)	Table 6-1	Fixed-by-Function Designation for CNSW Equipment
Table 6-2	List of NAVAID facility type	Deleted	
Table 6-3	Surveillance facility type	Deleted	
Table 6-4	Communications facility type	Deleted	
Table 6-5	Weather detection facility type	Deleted	
Figure 6-1	Typical Communications, Navigation, Surveillance and Weather (CNSW)	Figure 6-3	Typical Communications, Navigation, Surveillance and Weather (CNSW)
Figure 6-2	Two frangible connections	Figure 6-4	Two Frangible Connections
Figure 6-3	Airport Traffic Control Tower (ATCT) facility	Deleted	
Figure 6-4	Remote Transmitter/Receiver (RTR) communication facility	Figure 6-5	Remote Transmitter/Receiver (RTR) Communication Facility
Figure 6-5	Airport Surveillance Radar (ASR) steel tower (17 feet [5 m] high)	Figure 6-6	Airport Surveillance Radar (ASR) Steel Tower (17 feet (5.2 m) high)
Figure 6-6	Precision Runway Monitor (PRM) facility	Deleted	
Figure 6-7	Approach Lighting System (ALS) with Sequenced Flashers II (ALSF-2)	Figure 6-7	Approach Lighting System (ALS) with Sequenced Flashers
Figure 6-8	Simplified Short Approach Light System with Runway Alignment (SSALR)	Deleted	

Airport Design 150/5300-13A → 150/5300-13B Crosswalk

-13A	-13A heading	-13B	-13B heading
Figure 6-9	Medium Intensity Approach Lighting System (MALS) with Runway Alignment Indicator Lights (MALSR)	Figure 6-8	Medium Intensity Approach Lighting System with Runway Alignment Indicator Lights (MALSR)
Figure 6-10	MALSR facility	Deleted	
Figure 6-11	MALS	Figure 6-9	MALS
Figure 6-12	MALS with Sequenced Flashers (MALSF)	Figure 6-10	MALS with Sequenced Flashers (MALSF)
Figure 6-13	Omnidirectional Airport Lighting System (ODALS)	Figure 6-11	Omnidirectional Airport Lighting System (ODALS)
Figure 6-14	Lead-in Lighting System (LDIN)	Deleted	
Figure 6-15	Approach LDIN facility	Deleted	
Figure 6-16	Runway End Identifier Lighting (REIL)	Figure 6-13	Runway End Identifier Lighting (REIL)
Figure 6-17	REIL	Deleted	
Figure 6-18	Precision Approach Path Indicator (PAPI)	Figure 6-14	4-Unit Precision Approach Path Indicator (PAPI)
Figure 6-19	PAPI light boxes	Deleted	
Figure 6-20	Instrument Landing System (ILS) Localizer (LOC) siting and critical area	Figure 6-15	Instrument Landing System (ILS) Localizer (LOC) Siting and Critical Area
Figure 6-21	LOC 8-antenna array	Figure 6-16	LOC 8-Antenna Array
Figure 6-22	LOC 14-antenna array	Deleted	
Figure 6-23	Glideslope (GS) siting and critical area	Figure 6-17	Glideslope (GS) Siting and Critical Area
Figure 6-24	GS antenna and equipment shelter	Figure 6-18	GS Antenna and Equipment Shelter
Figure 6-25	Distance Measuring Equipment (DME) antenna	Figure 6-19	Distance Measuring Equipment (DME) Antenna
Figure 6-26	Touchdown Runway Visual Range (RVR)	Figure 6-20	Runway Visual Range (RVR)
Figure 6-27	Enroute VHF Omnidirectional Range (VOR) facility	Figure 6-21	Enroute VHF Omnidirectional Range (VOR) Facility
Figure 6-28	Terminal VOR (TVOR) facility	Deleted	
Figure 6-29	TVOR installation	Figure 6-22	Terminal Very High Frequency Omnidirectional Range (TVOR) Facility
Figure 6-30	TVOR clearances	Deleted	
Figure 6-31	Non-Directional Beacon (NDB) facility	Figure 6-23	Non-Directional Beacon (NDB) Facility
Figure 6-32	Segmented circle and wind cone	Figure 6-24	Segmented Circle and Wind Cone
Figure 6-33	Automated Surface Observing System (ASOS) weather sensors suite	Figure 6-25	Automated Surface Observing System (ASOS) Weather Sensors Suite
Figure 6-34	Weather Camera (WCAM) pole	Figure 6-26	Weather Camera (WCAM) Pole
Figure 6-35	Weather equipment sensor pole	Figure 6-27	Weather Equipment Sensor Pole
Figure 6-36	Low Level Windshear Alert System (LLWAS) sensor pole	Figure 6-28	Low Level Windshear Alert System (LLWAS) Sensor Pole
Chapter 7	Airfield Bridges and Tunnels	6.2	Airfield Bridges and Tunnels
701	General.	6.2.1	General
702	Siting guidelines.	6.2.2	Bridge Siting
703	Dimensional criteria.	6.2.3	Bridge Structure Dimensions
704	Load considerations.	6.2.4	Bridge Load Considerations
705	Marking and lighting.	6.2.5	Airfield Marking and Lighting for Bridges and Tunnels
706	Other considerations.	Deleted	
707	Storm water structures.	Deleted	
Figure 7-1	Tunnel under a runway and parallel taxiway	Deleted	
Figure 7-2	Cross-section of a tunnel under a runway and taxiway	Deleted	
Figure 7-3	Airfield bridge	Deleted	
Figure 7-4	Shoulder markings for taxiway bridges	Figure 6-1	Shoulder Markings for Taxiway Bridges
Figure 7-5	Example of a structural deck with lighted depressed roadway	Deleted	
Appendix 1	Aircraft Characteristics	Appendix A	Aircraft Characteristics

Airport Design 150/5300-13A → 150/5300-13B Crosswalk

-13A	-13A heading	-13B	-13B heading
A1-1	Basic aircraft characteristics.	A.1	Basic Aircraft Characteristics
A1-2	Background.	A.2	Background
A1-3	Aircraft arranged by aircraft manufacturer, and Runway Design Code (RDC).	A.3	Aircraft Arranged by Aircraft Manufacturer, and Runway Design Code (RDC)
Table A1-1	Aircraft characteristics database – sorted by aircraft manufacturer/model	A.3.1	Aircraft Characteristics Database (table removed; online reference)
Figure A1-1	Typical dimensions of large aircraft	Figure A-1.	Key Dimensions – Large Aircraft
Figure A1-2	Typical dimensions of small aircraft	Figure A-2.	Key Dimensions – Small Aircraft
Appendix 2	Wind Analysis	Appendix B	Wind Analysis
A2-1	Objective.	B.1	Objective
A2-2	Crosswinds.	B.3.1	Crosswind Components
A2-3	Allowable crosswind components.	B.3	Allowable Crosswind Components.
A2-4	Coverage and orientation of runways.	B.2	Coverage and Orientation of Runways
A2-5	Assembling wind data.	B.4	Wind Data Sources
A2-6	Data source.	B.4.1	National Climatic Data Center (NCDC)
A2-6.a	Data Not Available	B.4.2	Data Not Available
A2-7	Analyzing wind data.	B.5	Analyzing Wind Data
A2-8	Conclusions.	Deleted	
A2-9	Assumptions.	Deleted	
A2-10	Automated wind analysis tools.	B.5.1	Standard Wind Analysis Tool
Table A2-1	Standard wind analysis results for ALL WEATHER	Table B-2.	Standard Wind Analysis Results for ALL WEATHER
Figure A2-1	Wind vector diagram	Figure B-1	Wind Vector Diagram
Figure A2-2	Blank windrose showing direction and divisions	Figure B-2	Blank Windrose Graphic Showing Direction and Divisions
Figure A2-3	Completed windrose using Figure A2 1 data	Figure B-3	Completed Windrose Graphic Using Table B-2 Data
Figure A2-4	Windrose analysis	Figure B-4	Windrose Analysis
Appendix 3	The Effects and Treatment of Jet Blast	Appendix C	Jet Blast and Propeller Wash
A3-1	Introduction.	C.1	Introduction
A3-2	Jet blast effects.	C.2	Aircraft Generated Air Currents
A3-3	Jet engine exhaust velocity and temperature.	C.4.2	Jet Engine Exhaust Velocity and Temperature
A3-4	Blast fences.	6.6	Blast Fences
A3-5	Shoulders and blast pads.	Deleted	
A3-6	Aircraft parking layout and jet blast effect(s).	Deleted	
Appendix 4	End-Around Taxiway (EAT) Screens	Appendix D	End-Around Taxiway (EAT) Visual Screens
A4-1	Screen sizing.	D.1	Screen Sizing
A4-2	Screen construction.	D.2	Screen Construction
Table A4-1	Aircraft characteristics	Table D-1	Aircraft Characteristics
Table A4-2	International Committee of Illumination (CIE) chromaticity coordinate limits	Table D-5	Daytime Color (x, y, Y) Specification Limits
Table A4-3	Minimum coefficient of retroreflection candelas/foot candle/square foot/candelas/lux/square meter	Table D-6	Minimum Coefficient of Retroreflection Candelas/Foot Candle/Square Foot/Candelas/Lux/Square Meter
Table A4-4	Visual screen panel wind loads	Table D-7	Visual Screen Panel Wind Loads
Figure A4-1	End-Around Taxiway (EAT) screen horizontal geometry	Figure D-1	End-Around Taxiway (EAT) Screen Sizing and Location
Figure A4-2	Visual screen width calculation		
Figure A4-3	EAT screen vertical dimension calculation	D.1.3	Visual Screen Vertical Dimension Calculation
Figure A4-4	Stop end of the runway/EAT elevation difference	D.1.4	Visual Screen and Vertical Elevation Difference
Figure A4-5	Examples of mounting screen to vertical column	Figure D-2	Example Visual Screen Structure

Airport Design 150/5300-13A → 150/5300-13B Crosswalk

-13A	-13A heading	-13B	-13B heading
Figure A4-6	Examples of panel layout for 13-foot (4 m) high screen	Figure D-3	Example Panel Layout for 13-foot (4 m) High Screen
Figure A4-7	Diagonal stripe orientation	Figure D-4	Visual Screen Stripe Orientation
Appendix 5	General Aviation Aprons and Hangars	Appendix E	General Aviation (GA) Facilities
A5-1	Background.	E.1	Background
A5-2	General aviation apron.	E.2	General Aviation Apron
A5-3	Wash pads.	E.5.3	Wash Racks
A5-4	Fueling.	E.5.1	Fuel Facilities
A5-5	Object clearance.	Deleted	
A5-6	Surface gradients.	Deleted	
A5-7	Drainage.	Deleted	
A5-8	Marking and lighting.	Deleted	
A5-9	Hangars.	E.3	Hangars
Figure A5-1	Tiedown layouts (a)	Figure E-3	Nested Tiedowns
Figure A5-1	Tiedown layouts (b)	Figure E-2	Tiedown Spacing
Figure A5-1	Tiedown layouts (c)	Figure E-1	Tiedown Layout
Appendix 6	Compass Calibration Pad	6.9	Compass Calibration Pad
A6-1	Purpose.	Deleted	
A6-2	Background.	Deleted	
A6-3	Design of compass calibration pad.	6.9.2	Compass Calibration Pad Size
A6-4	Location of compass calibration pad	6.9.1	Compass Calibration Pad Location
A6-5	Construction of compass calibration pad, paragraph d	F.1	Survey of the Compass Calibration Pad
Figure A6-1	Compass calibration pad marking layout	Deleted	
Figure A6-2	Typical compass calibration pad	Figure 6-2	Compass Calibration Pad
Appendix 7	Runway Design Standards Matrix (12 tables)	Appendix G	Runway Design Standards Tables (12 tables)
Appendix 8	Taxiway Fillet Design	Appendix J J.2	Taxiway Additional Information Taxiway Fillet and Turn Design
A8-1	Description.	J.2.1	Development of Taxiway Design Groups (TDGs)
A8-2	Dimensions.	J.2.6	Fillet Design Rationale
A8-3	Transitions.	J.2.7	Taper Transitions
Figure A8-1	Fillet design example	Figure J-1	Fillet Design Example
Figure A8-2	Angle of intersection (delta)	Figure J-2	Angle of Intersection (Delta)
Figure A8-3	Steering angle of no more than 50 degrees	Figure J-3	Steering Angle of No More Than 50 Degrees
Figure A8-4	Track of the main gear is modeled, offset by the TESM	Figure J-4	Track of the Main Gear is Modeled, Offset by the Taxiway Edge Safety Margin (TESM)
Figure A8-5	Minimize excess pavement while providing the required TESM	Figure J-5	Minimize Excess Pavement While Providing the Standard TESM
Figure A8-6	Pavement edge (main gear track + TESM) offset by 6 inches (15 cm)	Figure J-6	Pavement Edge (Main Gear Track + TESM) Offset by 6 inches (152 mm)
Figure A8-7	Detail of Figure A8-6	Figure J-7	Detail of Figure J-6
Figure A8-8	Tapers selected to minimize excess pavement while considering constructability	Figure J-8	Tapers Selection to Minimize Excess Pavement with Consideration for Constructability
Figure A8-9	Radius of outer pavement edge determined based on the minimum CMG and maximum MGW in the TDG	Figure J-9	Establishing Radius of Outer Taxiway Pavement Edge Based on the Centerline Radius and Taxiway Width for Each TDG
Figure A8-10	Dimensions applied to the design	Figure J-10	Dimensioning the Fillet Design
Appendix 9	Acronyms	Appendix N	Acronyms
Appendix 10	Index	Appendix O	Index