AC NO: 20- 74 DATE: 29 July 1971

ADVISORY CIRCULAR



AIRCRAFT POSITION AND ANTICOLLISION LIGHT MEASUREMENTS

DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION

Initiated by: FS-130

FOREWORD

- 1. <u>PURPOSE</u>. This advisory circular contains useful information concerning measurements for intensity, covering and color of sircraft position and anticollision lights.
- <u>REFERENCES</u>. Federal Aviation Regulations FAR 23.1385 through 23.1397 and 23.1401. FAR 25.1385 through 25.1397 and 25.1401. FAR 27.1385 through 27.1397 and 27.1401. FAR 29.1385 through 29.1397 and 29.1401. Advisory Circular AC 20-30A.
- 3. BACKGROUND.
 - a. This advisory circular has been developed as a reference for those concerned with data on measurements of aircraft position and anticollision lights. Light measurement is quite complex, and users of this advisory circular will have various degrees of experience and training. For these reasons, chapter one contains educational and reference material on the properties of light. It includes a description of light and discusses the general parameters.
 - b. <u>Chapter two includes information</u> on types of measurements and descriptions of the equipment used to make them.
 - c. <u>Chapter three is devoted to discussions</u> on measurement data. First, the Federal Aviation Regulations are shown by pictorial representations. Following this, measurement data considerations are given including the precautions which should be observed when making measurements.
 - d. <u>The appendices include a glossary</u> of terms, a conversion table, a bibliography and a discussion of tristimulus colorimetry as applied to aircraft position and anticollision light measurements.

Acting Director, Flight Standards Service

TABLE OF CONTENTS

			Page
LIST OF	ILLUSTRATIONS		iii
LIST OF	TABLES		v
CHAPTER	1. PROPERTIES OF LIGHT		1
1.	General		2
2.	Intensity		2
3.	Color		6
CHAPTER	2. MEASUREMENT CONSIDERATIONS		13
4.	General		13
5.	Inte-sity	•	13
6.	Color		16
7.	Temperature Effects		19
CHAPTER	3. MEASUREMENT DATA		21
8.	General		21
9.	Position Light Data		21
10.	Anticollision Light Data		24
APPENDIX	1. GLOSSARY OF TERMS	(2 pages)	1
APPENDIX	2. PHOTOMETRIC TERMS	(1 page)	1
APPENDIX	3. TRISTIMULUS COLORIMETRY AND AVIATION LIGHTS	(2 pages)	1
APPENDIX	4. BIBLIOGRAPHY	(2 pages)	1

Page 1(and 11)

.

LIST OF ILLUSTRATIONS

÷ •,

TITLE	FIGURE		PAGE
The Visible Spectrum	1.1		. 1
Standard-Observer Luminous-Efficiency Curve (C.I.E.)	1.2		3
Intensity and Illumination	1.3		5
Spectral Tristimulus Values According to the 1931 C.I.E. Standard Observer	1.4	v	7
C.I.E. Chromaticity Diagram	1.5		10
Strip Recording of Flash	2.1		15
Position Lights, Minimum Intensity in the Horizontal Plane	3.1		27
Position Lights, Minimum Intensities in Vertical Planes	3.2		28
Anticollision Lights, Minimum Intensity in Vertical Plane	3.3		29
Typical Horizontal Candlepower Distribution-Position Light	3.4		30
Typical Vertical (andlepower Distribution-Position Light	3.5		31
Vertical Distribution of Rotating Beacon	3.6		32
Time vs. Intensity curves 0° and 5° for Rotating Beacon	3.7		33
Time vs. Intensity - 20° for Rotating Beacon	3.8		34
Typical Flashtube Measurement Data Sheet	3.9		35

Page iii(and iv)

LIST OF TABLES

TITLE	TABLE	PAGE
Spectral Luminous Efficiency, $V(\lambda)$	1.1	4
Spectral Tristimulus Values	1.2	8
Computation Form	2.1	17

••

Page v(and vi)

CHAPTER 1

PROPERTIES OF LIGHT

1. <u>GENERAL</u>. Light is visually evaluated radiant energy. Like other forms of radiant energy, light travels through space at a constant velocity of 300,000,000 meters per second. Light energy may be considered as having a sinusoidal wave form, stimulating vision only over a narrow band of wavelengths (Fig. 1.1). Within this band, the amplitude affects the visual sensation of brightness and the wavelength, the visual sensation of hue. The longest waves produce a sensation of red, and the shortest a sensation of violet. By definition, white occurs when all visible wavelengths are combined in equal amounts. The appearance of white, however, may be produced when certain critical ones are combined. If the light covers a narrow band of wavelengths, a certain hue is seen. Black is usually treated as the absence of stimulation. The wavelength of light may be expressed in micrometers (μ m), equal to 10^{-6} meters, in nanometers (nm), equal to 10^{-9} meters, or in angstroms (A°), equal to



THE VISIBLE SPECTRUM



Chap 1 Par 1

29 July 1971

The sensitivity of the eye, however, varies within this visible spectrum. Radiant energy at different wavelengths produces varying sensations of brightness even though the amount of energy received is the same at each wavelength. Figure 1.2 and Table 1.1 show that the eye is twice as sensitive to a yellow-green of 555 nanometers, as it is to a green of 510 nm. This curve is referred to as "spectral sensitivity of the human eye" or "luminous efficiency". When the intensity of colored lights is measured, this variable sensitivity of the eye must be taken into consideration. In other words, a red light must be much higher in power to appear equally as bright as a green light. The detecting device, therefore, must be corrected for the response of the standard observer if the reading is to indicate luminous (visual) output. The numbers associated with Figure 1.2 and Table 1.1 are referred to as "spectral luminous efficiencies". It should be remembered that lumens and candelas are associated with visible light, and as the sensitivity of the eye decreases, so does the amount of lumens for the same radiant power. This is evidenced in the conversion from watts to lumens: luminous flux in lumens = 680 V(λ) times the radiant flux in watts.

2. INTENSITY. The luminous flux being emitted from a point source, if the light is emitted equally in all directions, may be represented by a sphere. Light flux is rate of flow of visible energy. The basic unit of flux is the lumen which by definition is equal to $1/4\pi$ times the total flux emitted by a uniform point source of one candela. The flux emitted by a point source per unit solid angle (steradian) is called intensity. A steradian is defined as that solid angle originating at the center of a sphere and subtending an area on the sphere surface equal to the square of the sphere radius. Intensity is measured in lumens per steradian, and a uniform point source equal to one candela has an intensity in every direction of one lumen per steradian. Intensity in a given direction is usually expressed in candelas and is often called candlepower.

The luminous flux density received on a surface (illuminance) varies with the intensity of the source, and inversely as the square of the distance from the source to the surface. Illuminance is expressed in lumens per unit area or footcandles. Figure 1.3 shows that as the distance from a source increases, one lumen is spread over increasing areas, and the illuminance decreases. The relation of illuminance to distance from the source is referred to as the "inverse square law". The illuminance from a given source varies inversely as the square of the distance from that source. Doubling the distance causes the illuminance to decrease to one fourth. As measurements of a light source are usually done with instruments which measure illuminance, the distance must be known before the intensity of the source can be determined. In other words, footcandles times the distance squared gives candelas. For example, if a footcandle reading of 10 is measured at 10 feet from the source, the intensity is 1000 candelas.

> Chap 1 Par 1



STANDARD-OBSERVER LUMINOUS EFFICIENCY CURVE (C.I.E.)

Figure 1.2

Chap 1 Par 2

WAVELENGTH NANOMETERS	SPECTRAL LUMINOUS EFFICIENCY, V(X)	WAVELENGTH NANOMETERS	SPECTRAL LUMINOUS EFFICIENCY, V(λ)	
380	0.0000	580	0.8700	
390	0.0001	590	0.7570	
400	0.0004	600	0.6310	
410	0.0012	610	0.5030	
420	0.0040	620	0.3810	
430	0.1116	630	0.2650	
440	0.0230	640	0.1750	
450	0.0380	650	0.1070	
460	0.0600	660	0.0610	
470	0.0910	670	0.0320	
480	0.1390	680	0.0170	
490	0.2080	690	0.0082	
500	0.3230	700	0.0041	
510	0.5030	710	0.0021	
520	0.7100	720	0.0010	
530	0.8620	730	0.0005	
540	0.9540	740	0.0003	
550	0.9950	750	0.0001	
560	0.9950	760	0.0001	
570	0.9520	770	0.0000	

1931 C.I.E. STANDARD OBSERVER

ŧ

SPECTRAL LUMINOUS EFFICIENCY, V(N)

Table 1.1

Page 4

Chap 1 Par 2

t en in

29 July 1971



INTENSITY AND ILLUMINATION

Figure 1.3

Flashing lights are used extensively as signals and warnings because of their superiority in attracting attention. Because of this characteristic, flashing beacons were established as the required lighting for anticollision lights. These beacons are of several types: rotating, flashing incandescent, oscillating and gas discharge (strobe).

When a light signal consists of separate flashes, the maximum intensity during the flash must be greater than the intensity of a steady light to have the same apparent intensity. It is convenient to evaluate flashing lights in terms of their EFFECTIVE INTENSITY, Ie or EFI, the intensity of a steady light which will appear equally bright when viewed at threshold, and is expressed in candelas.

Chap 1 Par 2

Current airworthiness requirements for aircraft anticollision lights specify the following equation (known as the Blondel Rey equation) for the computation of effective intensity:

$$l_{4} = \frac{\int_{t_{1}}^{t_{2}I(t)dt} t_{1}}{0.2 + (t_{2} - t_{1})};$$

where: I_{ρ} = effective intensity

I(t) = instantaneous intensity as a function of time

 $t_2 - t_1 =$ flash time interval (seconds)

The maximum computed value of effective intensity is obtained when t_2 and t_1 are chosen so that the effective intensity is equal to the instantaneous intensity at t_2 and t_1 . For short time flashes, $t_2 - t_1$ becomes insignificant compared to 0.2 seconds, and the total flash is integrated.

Short-duration flashtube lights have been used primarily as supplementary lights. Since flashtubes in general produce relatively small proportions of red light, about 90 percent of the light is lost in passing it through a red filter. Therefore, in order to use this source for an anti-collision light, it is necessary to operate them at higher energy levels than has been common in the small supplementary lights.

3. <u>COLOR</u>. The sensation of color is closely related to the wavelength of light and varies with the individual and the conditions of viewing. Usually a color is said to have three psychological components: <u>hue</u> (red, blue, orange, etc.), <u>brightness</u>, and <u>saturation</u> (the amount a color differs from a grey of the same brightness). A measure of hue, sufficiently reliable for signal-color specification, is the wavelength of the part of the spectrum required to be mixed with the equal-energy (white) source to produce the color; this wavelength is called the <u>dominant</u> wavelength of the color. Saturation is satisfactorily specified by the ratio of the distance on the CIE chromaticity diagram (See Figure 1.5) from the equal-energy point to the color point, to the distance from equal-energy point, in the same direction, to the spectrum locus. This ratio is called <u>purity</u>.

Chap 1 Par 3

It can be shown that any color can be matched by combining three properly chosen colors called primary colors. : If a colored sample is placed in one half of a photometric field, a mixture of three primary colors such as red, green, and blue, in the other half of the field can be made to match the colored sample to the satisfaction of the eye. This is done by varying the relative brightness of the three primary colors. A problem with this method is that the matching judgment of one observer cannot be taken as representative of the average person. Only when a large number of observers are used in each experiment can consistent values be obtained for the relative brightness of primary colors required to match any given color. In order to avoid this difficulty, the tristimulus method was revised and standardized. Three primary colors were agreed upon; then, by experiments with a number of normal observers, standard values for the relative amounts of each primary color were established to match each wavelength in the visible spectrum. These numbers were associated with a "standard observer". With these values made available in 1931 by the Commission Internationale de L'Eclairage (CIE), a more objective and economical technique is available to specify color. Figure 1.4 is a graphical presentation of the relative amounts of each primary color required to match any wavelength. Standard notation for these functions is: $\bar{\mathbf{x}}$ for the red primary, $\bar{\mathbf{y}}$ for the green primary, and $\bar{\mathbf{z}}$ for the blue primary. It should be noted that the \vec{y} function has been adjusted to correspond to the luminous-efficiency function (Figure 1.2). Table 1.2 shows the values of these functions in tabular form.



SPECTRAL TRISTIMULUS VALUES ACCORDING TO THE 1931 CIE STANDARD OBSERVER

Figure 1.4

Chap 1 Par 3

Wave- length,	Spectral tristimulus values of equal-energy spectrum			Wave-	Spectral tristimulus values of equal-energy spectrum		
D 20		7	7	200	7	Ţ	7
380	0.0014	0.0000	0.0065	580	0.9163	0.8700	0.0017
885	.0022	.0001	.0105	585	.9786	.8103	.0014
890	.0042	.0001	.0201	590	1.0263	.7570	.0011
895	.0076	.0002	.0862	595	1.0567	.6949	.0010
400	.0143	.0004	.0679	600	1.0622	.6310	.0008
405	.0232	.0008	.1102	605	1.0456	.5668	.0006
410	.0435	.0012	.2074	610	1.0026	.5030	.0003
415	.0776	.0022	.3713	615	0.9384	.4412	.0002
420	.1344	.0040	.6456	620	.8544	.3810	.0002
425	.2148	.0073	1.0891	625	.7514	.8210	.0001
430	.2839	.0116	1.8856	630	.6424	.2650	.0000
485	.8285	.0168	1.6230	635	.5419	.2170	.0000
440	.3483	.0250	1.7471	640	.4479	.1750	.0000
445	.3483	.0295	1.7826	645	.3608	.1382	.0000
450	.8362	.0380	1.7721	650	.2835	.1070	.0000.
455	.8187	.0480	1.7441	655	.2187	.0816	0000.
460	.2908	.0600	1.6692	660	.1649	.0610	0000.
465	.2511	.0739	1.5281	665	.1212	.0446	0000.
470	.1954	.0910	1.2876	670	.0874	.0320	0000.
475	.1421	.1126	1.0419	675	.0636	.0232	0000.
480	.0956	.1390	0.8180	680	.0468	.0170	0000.
485	.0580	.1693	.6162	685	.0829	.0119	0000.
490	.0320	.2080	.4652	690	.0227	.0082	0000.
495	.0147	.2586	.8583	695	.0158	.0057	0000.
500 505 510 515 520	.0049 .0024 .0093 .0291 .0633	* .8230 .4073 .5030 .6082 .7100	.2720 .2123 .1582 .1117 .0782	700 705 710 715 720	.0114 .0081 .0058 .0041 .0029	.0041 .0029 .0021 .0015 .0010	0000. 0000. 0000. 0000.
525	.1096	.7932	.0573	725	.0020	.0007	0000.
530	.1655	.8620	.0422	780	.0014	.0005	0000.
535	.2257	.9149	.0298	785	.0010	.0004	0000.
540	.2904	.9540	.0203	740	.0007	.0003	0000.
645	.3597	.9803	.0134	745	.0005	.0002	0000.
550 555 560 565 570	.4334 .5121 .5945 .6784 .7821	.9950 1.0002 0.9950 .9780 .9520	.0087 .0057 .0039 .0027 .0021	750 755 760 765 770	.0003 .0002 .0002 .0001 .0001	.0001 .0001 .0001 .0000 .0000	0000. 0000. 0000. 0000.
575	.8425	.9154	.0018	775	.0000	.0000	.0000
580	.9163	.8700	.0017	780	.0000	.0000	
				Totals	21.8713	21.3714	21.8715

The 1931 CIE standard observer

SPECTRAL TRISTIMULUS VALUES

Table 1.2

Page 8

Chap 1 Par 3

29 July 1971

Capital letters X, Y, and Z have been assigned as notation for the amounts of the three primaries required to visually match a color containing multiple wavelengths. These values can be plotted graphically if the following transformations are made:

$$x = \frac{X}{X + Y + Z}$$
 (2) $y = \frac{Y}{X + Y + Z}$ (3) $z = \frac{Z}{X + Y + Z}$ (4)

where X. Y, and Z are the amounts of the three primaries and x, y, and z are the "chromaticity coordinates" in the CIE system. The horizontal of the graph becomes x and the vertical becomes y; z may be obtained from the relationship x + y + z = 1. Such a graph, shown in Figure 1.5, is called a chromaticity diagram. Any color may be located on the diagram by specifying its chromaticity coordinates. The colors used for lighting of aircraft are shown with the limits as established by the airworthiness regulations. On this diagram, there is a central white point marked H, where X = Y = Z corresponding to the color of a source having an equalenergy spectrum. As x + y + z = 1, this white point appears graphically at x = .333; y = .333 and represents a position of zero purity. The outer periphery of this diagram is a locus of points of 100% purity for visible wavelengths. A line drawn from any point on this periphery to the point of equal energy (\mathbf{x}) represents all purities between 100% and 0 for that dominant wavelength. For example, a line is shown for a light of dominant wavelength 0.5 micrometers with the 0%, 50%, and 100% purity points indicated. An aviation green light of this dominant wavelength would have to have a purity of only 32% to meet the regulatory requirements. Aviation red, however, would require a purity of nearly 100%.

The temperature scale along the bottom of the diagram, showing a range from 1000 K to infinity, contains calibrations for source color temperatures. Note that each temperature has a calibration mark on the curved line above. The curved line is called the "Planckian locus," and represents the chromaticities of blackbodies at different temperatures. In practical applications, it is accepted as representing the chromaticities of incandescent bodies such as lamp filaments. The numbers along this curve on the CIE diagram indicate the color temperature in Kelvins. CIE illuminant "A" can be represented on this curve at the 2854 K point, illuminant "B" at about 5000 K and "C" at about 6800 K. Illuminant A represents the spectral distribution of typical tungsten-filament incandescent lamps, illuminant B represents the spectral distribution of average noon sunlight, and illuminant C represents the spectral distribution of average daylight.

Chap 1 Par 3

443-453 0 - 71 - 8



THE PRIOR TO HAUGUST 1871 Figure 1.5

Chap 1 Par 3

29 July 1971

The color of an object depends on the spectral characteristics of the illuminant as well as the nature of the object. For example, fabrics change color when moved from the light of ordinary tungstenfilament bulbs to fluorescent light. Any accurate system of color specification must account for this fact by relating the color to a specified light source. In specifying a color that is going to be used under known conditions of illumination, the tristimulus values for the standard illuminant conforming most closely to those conditions should be used. For example, in coloring an aviation red light cover, the color temperature of the light-source must be considered.

Some red glass filters change color as their temperatures change. As the temperature increases, the light passing through some red filters becomes more red (longer wavelength) and <u>less</u> intense. For this reason, red filters are generally designed to be near the yellow limit (shortest wavelength) at room temperature. Then, if the operating glass temperature is consistently higher than room temperature, aviation red light will be produced under all operating conditions. By designing to this yellow limit, the maximum intensity will also be obtained. Glass of other colors changes slightly with temperature, but not enough to be a problem.

Chap 1 Par 3

Page 11(and 12)

CHAPTER 2

MEASUREMENT CONSIDERATIONS

4. GENERAL. The measurement of visible radiated energy is called photometry. Instruments for measurement of the amount of a light, regardless of their calibration, measure only flux, and care must be taken when converting to various photometric units. An additional precaution is necessary because photosensitive devices, unless properly filtered, do not have the same characteristics as the human eye.

There are four general types of light measurements:

- a. <u>Luminous Intensity</u> The luminous flux emitted per unit solid angle in a given direction (candelas).
- b. <u>Illuminance</u> The luminous flux incident per unit area on a surface at some distance from the source (footcandles).
- c. <u>Luminance</u> Luminous intensity per init projected area of surface (candelas per square foot).
- d. <u>Chromaticity</u> The color quality of light determined by its chromaticity coordinates.

In addition to the above light measurements, the efficiency of light covers is sometimes measured. There are two terms associated with such efficiency measurements; spectral transmittance (τ) which refers to the ratio of transmitted to incident power at one wavelength or a very narrow band of wavelengths, and luminous transmittance (T) which is the ratio of transmitted to incident total light power. The transmittance of a light cover indicates the decrease in light due to material and color, and can be used to adjust luminous intensity values measured without the cover. The filtered light may be measured directly provided the photometer is equipped with filters which accurately match the luminous-efficiency function.

- 5. <u>INTENSITY</u>. The instrument used to measure the luminous intensity of lights is called a photometer. Photometers can be placed in two general classes; "visual" and "direct-reading photoelectric".
 - a. <u>Visual Photometers</u>. Before the invention of photoelectric cells, most instruments for measuring intensity employed the principle of balancing two adjacent fields visually. With these photometers, a test light and a standard light of known intensity were viewed

Chap 2 Par 4

simultaneously. By adjusting the relative distances from the viewing point, a balance was obtained, and by applying the inverse square law, the intensity of the test light could be determined. Although visual photometers have generally been superseded by direct-reading photoelectric type instruments, many are still being used.

- b. <u>Direct-Reading Photoelectric Photometers</u>. Photoelectric devices are now being used to detect and convert light energy to electrical energy for measurement. A photometric system for precisely measuring the magnitude and coverage of aircraft lights usually consists of the following:
 - (1) <u>Goniometer</u>. This device includes an attachment position for the light unit which can be moved around two axes of freedom. The vertical and horizontal positions are calibrated, and in some cases the information is remoted to recorders so that a plot of intensity vs. direction can be made directly. A goniometer of this type is installed in the photometric laboratory of the National Bureau of Standards in Washington, D. C.
 - (2) <u>Tunnel and Track.</u> A dark tunnel, including baffles to eliminate stray light, is located in line with the goniometer. A photodetector is placed on a carrier which can be moved on a track to vary the distance between the goniometer and the photodetector. Position information is usually remoted to a recorder.
 - (3) Photodetector. Photodetectors are of several types, and read-out in units such as milliwatts, microamperes, etc. By conversion factors, footcandles (illuminance) can be computed from the read-out. Then, by means of the distance information, a calculation of intensity can be made. For steady lights, measurements are concerned with rate of flow of light entering the eye, analogous to gallons per minute into a container. For flashing lights, however, the measurements are concerned with the quantity of light per flash entering the eye, analogous to gallons. The quantities are proportional to footcandles and footcandle-seconds respectively. Since the instantaneous illuminance varies during exposure to flashing lights, integration is necessary to determine the footcandle-seconds. As discussed in paragraph 2 of Chapter 1, the computation of effective intensity requires a candela-second measurement. Candela-seconds

Chap 2 Par 5

can be computed from footcandle seconds by multiplying by the distance (in feet) squared. Care must be taken not to overload a photodetector by too much light as it can saturate and its response become non linear.

Integrating photometers are available which electronically perform the integration and read out the total exposure in microcoulombs. These photometers are used only on short duration strobes where the entire flash is integrated. A microcoulomb is a microampere-second, and a calibration factor is used to convert a microcoulomb reading to footcandle-seconds. Then, multiplying by the distance squared gives candela-seconds corresponding to the numerator of the equation for effective intensity.

Strip recorders or recording oscilloscopes are generally used for longer duration flashes, such as rotating beacons, and mechanical integration is then performed.



Figure 2.1 shows an example of a recording made by a strip recorder. The paper is moved horizontally at a linear rate so that each division represents approximately .05 seconds. The recorder is calibrated so that each vertical division represents 100 candolas. After the flash is recorded, a machanical integrator (planimeter) is used to trace the recording and obtain the area, in candela-seconds, between the limits of t_2 and t_1 . This area divided by $0.2 + t_2 - t_1$ gives the effective intensity. The values of t_2 and t_1 are determined by experimentation, and are selected to maximize the computed effective intensity. In the

Chap 2 Par 2

example of figure 2.1 the flash has an area between t_2 and t_1 of approximately 51 candela-seconds. When divided by 0.3 seconds (0.2 + 0.1) the effective intensity is 170 candelas. The peak intensity of 850 candelas, therefore, has an effective intensity of only 170 candelas. A method for selecting t_2 and t_1 is given in Chapter 3.

When measuring colored flashing lights, the photodetector cannot always be relied upon to give accurate results, even with luminous-efficiency-correction filters. The alternative is to measure the effective intensity with a clear cover, and then with a spectrophotometer, determine the relative luminous transmittances of the two covers. The effective intensity value measured through the clear cover is then reduced by this luminous transmittance factor. Spectrophotometers are discussed in paragraph 3., <u>Color</u>.

- 3. <u>COLOR</u>. Color can be evaluated with a visual photometer by comparing a sample against a filter of known color. In such comparisons, the same, correct color temperature should be used for both sources. However, there has been increasing interest in the use of photoelectric instruments for the measurement of chromaticity of colored lights. The following is a discussion of some of these instruments:
 - a. <u>Spectrophotometer</u>. Spectrophotometers break up a self-contained light source into a spectrum by prisms or gratings, so that narrow bands within the visible spectrum can be individually applied to a test ware (such as a light cover). Although these are not single wavelengths, they are very narrow bands approximately five nanometers wide. Determining either luminous transmittance (T), or chromaticity coordinates (x, y, and z) with a spectrophotometer involves the measurement of 40 transmittances (t), spaced 10 nanometers apart, throughout the visible spectrum. Mathematically, these transmittances are used as follows:

 $X = \Sigma_{380}^{770} \bar{x} E \tau \Delta \lambda$ (5) $Y = \Sigma_{380}^{770} \bar{y} E \tau \Delta \lambda$ (6) $Z = \Sigma_{380}^{770} \bar{z} E \tau \Delta \lambda$ (7)

The values for \bar{x} , \bar{y} , and \bar{z} are found in Table 1.2, and represent the relative amounts of primaries required at each wavelength. The E in the equations represents the spectral distribution of the light source, and is published for certain illuminants such as C.I.E. Source A. Tables are available which list the products $\bar{x}E$, $\bar{y}E$, and $\bar{z}E$ for certain illuminants (NBS Monograph 104). These numbers are sometimes found on a computation form as shown in table 2.1. If the light is not a standard source, a table must be developed from measurements of the energy distribution. When each of the 40 lines have measured values for τ logged, the remainder of the sheet can be filled out with data computed by hand, calculating machine, or computer. For example, assume a measured value for τ at 380 nanometers of 0.078. Then $\bar{x}E\tau$ would be 0.078, $\bar{y}E\tau$ would be 0.000, and $zE\tau$ would be 0.468.

Chap 2 Par 5

1.4.2

Sample____

Guide for C	omputation of x, y, z, and T
Observer:	C.I.E. Standard 1931
Basic Stimu	lus: Equal Energy
Illuminant:	Planck 2856 K
	(C.I.E. Standard A)

wave Length								
Nanometers	т	хe	νe	ŽE	ž	Ξτ	ν VEτ	Z
380	0.	1	0	6				
390	0.	5	0	23				
400	0.	19	1	93				
410	0.	71	2	340				
420	0.	262	8	1256		<u> </u>	······	
430	0.	649	27	3167				
440	0.	926	61	4647				
450	0.	1031	117	5435				
460	0.	1019	210	5851				
470	0.	776	362	5116				
480	0.	428	622	3636				
490	0.	160	1039	2324				
500	0.	27	1792	1509				
510	0.	57	3080	969				
520	0.	425	4771	525				
530	0.	1214	6322	309				
540	0.	2313	7600	162				
550	0.	3732	8568	75				
560	0.	5510	9222	36				
570	0.	7571	9457	21		-		
580	0.	9719	9228	18				
590	0.	11579	8540	12				
600	0.	12704	7547	10				
610	0.	12669	6356	4		-		
620	0.	11373	5071	3				
630	0.	8980	3704					
640	0.	6558	2562					
650	0.	4336	1637	-				
660	0.	2628	972					
670	0.	1448	530					
680	0.	804	292					
690	0.	404	146					
700	0.	209	75					
710	0.	110	40					
720	0.	57	19					
730	0.	28	10					
740	0.	14	6					
750	0.	- 6	2					
760	0.	4	2					
770	0.	2						
SUMS		109828	100000	35547 X=		¥=	Z=-	
					X	Y		Z
				X=	ATITL	y = 1+1+	<u> </u>	7176

	x,	У,	8	nd	Z
COMPUT/	TI	ON	FO	RM	

Table 2.1

Chap 2 Par 6

29 July 1971

Summing the column for xEr would yield X which is the relative amount of red primary required for the match. Y and Z can be found with the other two columns. Then, the chromaticity coordinates for representing the sample on a chromaticity diagram, or evaluation against regulatory requirements is found as follows:

 $x = \frac{X}{X + Y + Z}$ $y = \frac{Y}{X + Y + Z}$ $z = \frac{Z}{X + Y + Z}$

The luminous transmittance T of the ware can be found from the same computation sheet as follows: The sum of the \overline{y} Et column (Y) is divided by the sum of the \overline{y} E column. This is possible because \overline{y} and V(λ) values (luminous-efficiencies) are identical. For example, if the sum of the \overline{y} Et column is 24407, dividing by 100,000 gives .24407 or 24.4%. The values given in this table have been adjusted so that the sum of the \overline{y} E column is a power of ten to simplify computations. This means that only 24.4% of the light incident on the ware is being transmitted through it. A more detailed explanation is given in the Appendix as "Tristimulus Colorimetry and Aviation Lights."

- b. <u>Spectroradiometer</u>. Spectroradiometers are similar to spectrophotometers, but can be used to measure the spectral distribution of external sources over a wider range of wavelengths than just the visible spectrum.
- c. Brightness Meters. When evaluating the color of ware with these instruments, a standard filter is used for comparison. The results are not chromaticity coordinates (x, y, and z), but are in or out of tolerance indications. Such procedures, due to filter limitations, are used only on highly saturated red glass (sharp cut-off).

One method of determining whether a color meets a specific requirement, by using a brightness meter and a NBS filter, is given in MLL-L-25467C. The filter specified in this procedure has a yellow limit corresponding to instrument and panel lighting red (National Bureau of Standards Filter No. 3215). However, the procedure has been used with an aviation red filter (NBS Filter No. 3647A). The procedure is a Go/No-Go measurement with the NBS filter used as a measurement standard. A brightness reading is taken of a colored aviation light at 10 ft. distance. A second reading is taken after a NBS filter is added in the light path. The ratio of these 2 readings must approximate a similar ratio obtained using a white light source in place of the colored aviation light. In the second case, a first reading is made with

Page 18

Chap 2 Par 6

one NBS filter and the second reading is made with two NBS filters. In this way, the aviation light color is compared to the NBS filter color. The two ratios must not differ over 3% (in the yellow direction) to qualify the test light color.

- d. Tristimulus Colorimeters. If the response of three photocells could be adjusted by glass filters, so their responses follow the curves of the C.I.E. Standard Observer, \bar{x} , \bar{y} , and \bar{z} (see Figure 1.4), they could be made to yield direct measurements of tristimulus values X, Y, and Z. Complete success of these colorimeters depends on the ability to duplicate the C.I.E. Standard Observer System. Acceptable instruments could simplify the measurements and reduce the required data processing. Presently, such instruments have more application to production line measurements than for showing initial compliance.
- 7. <u>TEMPERATURE EFFECTS</u>. All glass filtering elements have their color and transmittance affected in varying degrees by increased temperature. The change is more pronouncëd for red than for other colors. One manufacturer of glass has published data such that different red glasses are identified by their percent transmittance at room temperature. For example, red glasses are identified as 12.6%, 25.3%, etc., at 78° F. For each number, the color and transmittance at any temperature up to 500° F is charted and plotted. Most red glass colors are reversible up to the softening temperature (over 800°F). Reversibility means that after heating, when the temperature is returned to 78° F, the original color will return. Glasses that have transmittances of 25% or more at 78° F have transmittance vs temperature curves which are essentially linear up to 300° F, and transmittances change approximately 0.5% for each 10° F change in temperature.

In application of these filters, proper evaluation of their color characteristic at elevated temperatures requires knowing the following:

- a. The initial glass temperature, color and transmission.
- b. The range of glass temperatures found in operation.
- c. The type glass used in the filter and its characteristics. Generally, an increase in red glass temperature makes its color more red and decreases its transmission. The amount of such changes is determined by the temperature range of the glass in operation and the characteristics of the glass.

Chap 2 Par 6

Page 19(and 20)

CHAPTER 3

MEASUREMENT DATA

- 8. <u>GENERAL</u>. Aircraft exterior lights, on which measurements are required, include position and anticollision lights. Measurements include intensity (coverage and overlap) and color.
 - a. <u>Position Lights</u>. The airworthiness requirements for aircraft position lights are given in FAR 23.1385 through 23.1397, FAR 25.1385 through 25.1397, FAR 27.1385 through 27.1397 and FAR 29.1385 through 29.1397.
 - (1) Intensities.
 - (a) <u>Horizontal Coverage</u>. Figure 3.1 shows the minimum intensity requirements for the horizontal plane at 0° vertical. Overlap limits are not shown as they vary when intensities exceed 100 candelas.
 - (b) <u>Vertical Coverage</u>. Figure 3.2 shows the minimum intensities for any vertical plane. The value of "I" indicates the maximum required candelas for a given horizontal position.
 - (2) <u>Color</u>. A graphical presentation of the chromaticity coordinate limits for aviation red (left), aviation green (right), and aviation white (rear), is shown in figure 1.5.
 - b. <u>Anticollision Lights</u>. The airworthiness requirements for aircraft anticollision lights are given in FARs 23.1401, 25.1401, 27.1401 and 29.1401.
 - (1) Intensity & Coverage: Figure 3.3.
 - (2) <u>Color:</u> Each anticollision light must be either aviation red or aviation white.
- 9. POSITION LIGHT DATA.
 - a. Intensity. Measurement of position light intensity requires photometric equipment such as that described in Chapter 2, paragraph 2. Figure 3.4 and 3.5 show typical recordings as made in a photometric laboratory. The data should include enough distribution plots to adequately substantiate coverage. The following data should be sufficient:

Forward Red and Green Position Lights. A horizontal distribution curve in the zero degree vertical plane from directly forward outboard through 110 degrees (figure 3.4). Vertical distribution curves from 90 degrees up to 90 degrees down at 0, 10, 20, and 110 degree horizontal points (figure 3.5). In addition to these distribution

Chap 3 Par 8

curves, a visual inspection through the entire area should be made to determine whether or not there are any noticeable shadows or areas where visual observation would indicate questionable conformance. If any such questionable areas are noted, further measurements should be made in those areas to demonstrate satisfactory coverage.

Rear <u>White Position Light</u>. A horizontal distribution from 70 degrees right to 70 degrees left of directly to the rear. Three vertical distribution curves from 90 degrees up to 90 degrees down through the following horizontal points: directly astern, 70 degrees left of directly to the rear, and 70 degrees right of directly to the rear. Laboratory reports of such measurements should also include at least the following:

- (1) A list of the test equipment and calibration dates for light standards which should show calibration against the lab working standard within the past 30 days, and the working standard against the lab primary standard within the last 180 days. The laboratory primary standard should be traceable to the National Bureau of Standards.
- (2) If a luminous-efficiency-correction filter is included, data adjustment for filter errors should be shown and substantiated.
- (3) If transmittance measurements are used, the data should show adjustment for the comparison in transmittance between any clear filter used during the intensity measurements and the transmittance of the colored filter. If a clear cover is used, it should have the identical shape as the colored cover. Transmittance data should be shown on a computation sheet such as shown in Table 2.1. Also, if a spectrophotometer is used it should be substantiated that the sample used in the measurements is representative of the actual light cover.
- (4) When red glass is used, the data should show the temperature of light covers during measurements and data on the transmittance characteristics relative to temperature. Measured intensity values should be adjusted as follows:
 - (a) For measurements made with the red cover in place, adjust the intensity values to those corresponding to an ambient temperature of 100°F. If no actual measurement is made with an ambient temperature of 100°F, extrapolation should be supported by data.
 - (b) When transmittance data is used, values should be adjusted to correspond to a glass temperature equivalent to that of the outside surface of the light cover. Glass temperature measurements should be made after the glass has stabilized with an ambient temperature of at least 100°F. Optionally, a temperature of 130°F should be allowed in lieu of measured temperature. Chap 3

Par 2

trans and

- (5) A description of the procedure used to obtain intensity and transmittance data, including the calculations. A diagram of the test set-up is desirable. This description and diagram should show:
 - (a) Intensity measurements made from a distance sufficient to give accurate results with the linear operating range of the photocell of prime consideration. The distance should always be at least 10 times the diameter of the light source and preferably greater. (See IES Lighting Handbook, 4th Edition, page 4-18)
 - (b) Voltage measurements made as near the light source as possible, using a suitable meter when considering accuracy and loading. Current readings should also be recorded and data supplied to show where the lamp falls with respect to the manufacturing tolerance limits.
- b. <u>Color</u>. Position light color measurements require equipment such as described in Chapter 2, paragraph 3. Aviation green conformance should be shown with data in chromaticity-coordinate form (x, y, and z). Aviation red conformance should be shown by the same type data, or by the optional brightness meter and filter method. When spectrophotometric procedures are used, the data should include a computation sheet such as shown in Table 2.1. Laboratory reports which accompany the data should include at least the following:
 - (1) A list of the test equipment with, when applicable, calibration dates.
 - (2) When red glass is used, the data should include the temperature of light covers during color measurements, and data on the color characteristics relative to temperature. Red glass data should also include the following:
 - (a) For measurements made with the red cover in place, substantiating data to show that the color will be within limits when the outside temperature of the glass is 78°F.
 - (b) If chromaticity-coordinate measurements are made, measured values should be adjusted to those corresponding to an outside cover glass temperature of 78°F.
 - (3) A description of the procedure used to obtain the color data. A diagram of the test set-up is desirable.

Chap 3 Par 9

3. ANTICOLLISION LIGHT DATA.

a. <u>Intensity</u>. Measurements for "effective intensity" require techniques as described in Chapter 2, paragraph 2.b.(3). The light may be measured as a white light, and the intensity values adjusted according to the transmittance of the red cover. The computation sheet used to determine the chromaticity-coordinates contains the data for determining the luminous transmittance of the red cover. If a clear cover is used in the intensity measurements, the ratio of the transmittances of the two covers must be used to correct the data.

To show field of coverage, a combination of vertical and horizontal measurements is necessary. Figure 3.6 is a typical presentation of vertical effective intensity distribution and is shown with the FAA minimum intensity requirements. Such curves are constructed from points representing separate effective intensity measurements. To assure sufficient points to accurately draw the vertical distribution curve, measurements are usually made at vertical angles of +30°, $\pm 20^{\circ}$, $\pm 10^{\circ}$, $\pm 5^{\circ}$ and 0. Three of nine such points are shown in Figure 3.6. To obtain the values for the three points, individual intensity vs time curves are recorded and processed. The processing for long duration type lights can be done from a paper recording, using a planimeter for area measurements. Horizontal coverage must also be substantiated. As the curve of Figure 3.6 represents a single horizontal direction, there should be enough measurements to assure complete field of coverage. In other words, it should be substantiated that any variations in vertical patterns around the light will not result in an out of tolerance condition at any horizontal position.

When using the Blondel-Rey equation, the maximum value of effective intensity is obtained when t₂ and t, are chosen so that the effective intensity is equal to the instantaneous intensity at t2 and t1. To compute the highest possible effective intensity value for a given curve, estimates should be made until the proper values for t2 and t1 have been determined. When the instantaneous intensity at the t2 and t₁ points approximate the effective intensity value computed from the Blondel-Rey equation, the maximum computed value has been found. Figures-3.7 and 3.8 have examples of data and include the mechanics for determining maximum computable intensity for points A, B, and C of Figure 3.6. The heat correction factors used in Figures 3.7 and 3.8 are used because the light cover is at a higher temperature in the laboratory than in actual operation. For rotating beacon measurements, the motor is stopped and the light is concentrated on a particular area of the glass. As mentioned before, red glass decreases in transmittance with heat.

Page 24

Chap 3 Par 10

 $\{ j_{i}, j_{i} \}$

For short time flashes such as those produced by flashtube units, an integrating type photometer is generally used. These instruments integrate the whole flash rather than between specific limits. If an integrating photometer is used, the manufacturers' calibration and operation procedures should be followed. For typical flashtube measurements, the value of $t_2 - t_1$ is negligible compared to 0.2 seconds. Computed effective intensity for these lights is therefore maximum when the entire flash is included. Effective intensity for short time flashes can be found by the following relation:

Footcandle-seconds (meter reading) x distance squared + 0.2 seconds

To improve the accuracy, several flashes are integrated and an average is taken. Figure 3.9 is an example of typical flashtube measurement data. Information furnished usually includes the charge voltage, flash capacity, electrical energy stored (watt-sec), flash rate, and the plane of measurement. In the example, the 15.6 watt-seconds results from the equation:

Energy = $1/2 E^2 C = 1/2 (420)^2 (177 \times 10^{-6})$

The 15.6 watt-seconds of electrical energy is partially converted to light energy. If reflectors and gas conversion efficiency are considered, the watt-second number can be used to estimate possible candelas. The test distance is given so that the meter reading is convertible to candelas. The multiplier (125) in the example results from $D^2/0.2$. In the tabled data, therefore, the single flash footcandle-second reading times 125 gives effective intensity.

Laboratory reports of such measurements should include at least the following:

- A list of test equipment and calibration dates as discussed in paragraph 2.a.(1).
- (2) Luminous-efficiency-correction filter data as discussed in paragraph 2.a.(2).
- (3) Transmittance data as discussed in paragraph 2.a.(3).
- (4) Temperature corrections as discussed in paragraph 2.a.(4). If a heat correction factor is used, it should be substantiated by data.
- (5) Procedure information as discussed in paragraph 2.a.(5). For anticollision lights, this information should also include the method used to determine "effective intensity."

Chap 3 Par 10

443-453 0 + 71 - 3

- (6) For strobe sources, the spectral distribution data used in transmittance computations should be substantiated by data showing spectroradiometer measurements, or published data which can be shown to be applicable.
- b. <u>Color</u>. The measurement for color of an anticollision light red cover is usually made with a spectrophotometer. In this measurement, the computation sheet (Table 2.1) should contain values for spectral distribution which are representative of the light source being used. Pre-computed values for $E\bar{x}$, $E\bar{y}$, and $E\bar{z}$ are available for many type sources and are identified by color temperature. NBS Monograph 104 has several \pm camples. The color temperature and the values for $E\bar{x}$, $E\bar{y}$, and $E\bar{z}$ must be accurately known if the results are to be dependable.

Laboratory reports which accompany the data should show at least the following:

- (1) A list of the test equipment with, when applicable, calibration dates.
- (2) Temperature data as discussed in paragraph 2.b.(2).
- (3) Procedure information as discussed in paragraph 2.b.(3).

Read to



POSITION LIGHTS, MINIMUM INTENSITY IN THE HORIZONTAL PLANE

Figure 3.1

Chap 3 Par 10



POSITION LIGHTS, MINUMUM INTENSITIES IN VERTICAL PLANES

Figure 3.2

Chap 3 Par 10

t de la



ANTICOLLISION LIGHTS, MINIMUM INTENSITY IN VERTICAL PLANE

Figure 3.3

Date	of T.	C. Application:	I
Prior	to	8/11/71	100
On or	after	8/11/71	400

Chap 3 Par 10



Page 30

Chap 3 Par 10

1.20

29 July 1971

AC 20-74







Chap 3 Par 10



Chap 3 Par 10

EXAMPLES OF TYPICAL TIME-INTENSITY CURVES SHOWING EFFECTIVE INTENSITY CALCULATIONS SECONDS PER INCH = .0666 CANDELAS PER INCH = 200



29 July 1971

Page 33

AC 20-74

AC 20-74

29 July 1971





TYPICAL FLASHTUBE MEASUREMENT DATA SHEET

Input Voltage - 14.0, Flash Capacitor 177 MFD. Charge Voltage - 420 V., 15.6 Watt-Seconds Flash Rate - 1 per second. Vertical Angle - 0°

Test Distance - 5.0 ft. EFI = Single flash reading x D^2 x 5, (Multiplier = 125)

Horizontal Distribution Data

HOR.	METER	NO. OF FLASHES	AVG. READING	
DEG.	READING	INTEGRATED	FOR SINGLE FLASH	EFI
0 ⁰	19.8	10	1.98	248.0
100	22.0	10	2.20	275.0
200	22.0	10	2.20	275.0
300	19.8	10	1.98	248.0
40 ⁰	20.4	10	2.04	255.0
50 ⁰	17.1	10	1.70	212.0
60 ⁰	13.7	10	1.37	171.0
70 ⁰	11.0	10	1.10	137.0
80 ⁰	11.0	10	1.10	137.0
900	11.5	10	1.15	144.0
1000	12.1	10	1.20	150.0
1100	11.5	10	1,15	144.0
1200	11.0	10	1.10	137.0
130 ⁰	8.8	10	.88	110.0

TYPICAL FLASHTUBE MEASUREMENT DATA SHEET

Figure 3.9

Chap 3 Par 10

Page 35(and 36)

٩.

APPENDIX 1

GLOSSARY OF TERMS

- <u>CANDELA</u> Unit of intensity. Produces one lumen per unit solid angle (steradian). At a distance of one foot, one candela produces an illuminance of one footcandle.
- 2. <u>CHROMATICITY</u> The color quality of light determined by its chromaticity coordinates.
- 3. <u>COLORIMETRY</u> A method for measuring colors and specifying them in numerical or definite symbolic terms.
- 4. <u>COLOR TEMPERATURE</u> The temperature at which a blackbody must be operated to give the same color as the source, usually expressed in Kelvins (K).
- 5. DOMINANT WAVELENGTH That wavelength of spectrum light which, when combined with neutral light in suitable proportions, matches the color. Neutral light is light for which the chromaticity coordinates are x = .333 and y = .333.
- 6. <u>EXPOSURE</u> The product of the illuminance and the time during which the material is exposed to this illuminance, or E = it. The unit of measure is the footcandle-second, which represents an exposure of l second to a source having a light intensity of l candela at a distance of l foot.
- 7. <u>HUE</u> The attribute of color determined primarily by the wavelength of light entering the eye.
- 8. <u>ILLUMINANCE</u> The areal density of luminous flux incident on a surface, in lumens per unit area or footcandles.
- 9. <u>INTENSITY</u> Flux per unit solid angle from a point source measured in lumens per steradian or in candelas; often called candlepower.
- 10. LIGHT Radiant energy that produces visual sensations.
- 11. <u>LUMEN</u> Unit of luminous (visible) flux. Luminous energy emitted per second by a uniform point source of one candela intensity through a solid angle of one steradian.
- 12. <u>LUMINANCE</u> Luminous intensity of a surface in a given direction per unit of projected area of the surface as viewed from that direction; measured in candelas per unit area.

Par 1

AC 20-74 Appendix 1

- 13. LUMINOUS FLUX The time rate of flow of light, sometimes called light power.
- 14. <u>PHOTOMETER-</u> An optical device that utilizes equations of brightness or flux to permit the measurement of a photometric quantity, such as intensity, illuminance or brightness.
- 15. <u>PHOTOMETRY</u> The measurement of visible radiation on the basis of its effect upon the eye under standard conditions. Visual photometry involves the adjustment of two parts of the visual field, in order to identify or to determine a minimal difference. Photoelectric photometry involves the measurement of the flux incident on a receiver from a test and a standard source at known distances.
- 16. <u>SATURATION</u> The extent to which a chromatic color differs from grey of the same brightness, measured on an arbitrary scale from 0% to 100% (where grey is 0%). Also called "purity".
- 17. SPECTROPHOTOMETER An instrument designed to measure the spectral transmittance or reflectance of objects. Used primarily for comparing, at each wavelength, the flux leaving the object with the flux incident upon it. It usually has a built-in light source.
- 18. <u>SPECTRORADIOMETER</u> An instrument used to measure the spectral distribution of radiant energy.
- 19. SPECTRAL LUMINOUS EFFICIENCY $V(\lambda)$ Quotient of the luminous flux at a given wavelength by the radiant flux at that wavelength normalized by dividing by the maximum value of that quotient, formally called luminosity factor.
- 20. <u>STERADIAN</u> The unit solid angle. That solid angle originating at the center of a sphere which subtends an area on the surface of that sphere equal to the square of its sphere radius. A sphere contains 4π steradians (see Figure 1.3).

SYMBOL	DESCRIPTION	UNIT	EQUIVALENT	CONVERSIONS
¢	Rate of Flow of Light	lumen		lumens = Watts x 680 x $V(\lambda)$
I	Point Source Light Power	candela	l lumen/steradian	candelas = footcandles x distance squared
L	Concentration of Intensity from Surface Source	footlambert	(1/m) candelas/ft ² 1/452 candélas/in ²	
	•	lambert	l lumen/cm ² 2.054 candelas/in ²	
E	Surface Received Light Density	foctcandle	l lumen/ft ²	footcandles = candelasAistance squared
λ	Distance Traveled During a Cycle	meter	Ratio of velocity co frequency of radiation	meter = 10^6 micrometers (m) = 10^9 nanometers (nm) = 10^{10} angstroms (A^*)
ω	Two Dimension Angles	steradian	Total Solid Angles/4m (Sphere)	steradians = surface area/ distance square:
W	Electrical Energy Rate	watt	joules/Sec	
۷(۸)	Eye Response to varying Wavelengths (Table 1.1)		ÿ	
	<u>SYMBOL</u>	SYMBOL DESCRIPTION Φ Rate of Flow of Light I Point Source Light Power L Concentration of Intensity from Surface Source E Surface Received Light Density λ Distance Traveled During a Cycle ω Two Dimension Angles W Electrical Energy Rate V(λ) Eye Response to Varying Wavelengths (Table 1.1)	SYMBOLDESCRIPTIONUNIT\$\$\phi\$Rate of Flow of LightlumenIPoint Source Light PowercandelaLConcentration of Intensity from Surface SourcefootlambertLConcentration of Intensity from Surface SourcefootlambertESurface Received Light Densityfootcandle\[\lambda]Distance Traveled During a Cyclemeter\[\u03c6]WElectrical Energy Ratewatt\[\u03c6]WElectrical Energy Ratewatt\[\u03c6]V(\u03c6)Eye Response to Varying Wavelengths (Table 1.1)watt	SYMBOL DESCRIPTION UNIT EQUIVALENT

PHOTOMETRIC TERHS

Page 1(and 2)

AC 20-74 Appendix **2**

APPENDIX 3

TRISTIMULUS COLORIMETRY AND AVIATION LIGHTS

Although the energy distribution of a colored light may extend throughout the visible spectrum, the characteristics of vision are such that a combination of three primary colors can match the light to the satisfaction of the eye. The apparent match of two colors of different spectral content is called "metamerism," and the two colors are called a "metameric pair." This method of matching or reproducing a color is the basis for tristimulus colorimetry. The tristimulus method is to measure the energy distribution and then to convert this information into the tristimulus values which form a metameric match. Figure 1.4 of this circular shows how to mix the three CIE primary colors in order to match any wavelength. If we have energy distribution throughout the visible spectrum, we simply multiply the relative power amplitude at each wavelength. Then, by adding up all the measurements a total amount for each of the primaries is found. Mixing these amounts of X (red), Y (green), and Z (blue), we accomplished a metameric match. Thus,

$X = \Sigma_{380}^{770} E \overline{X} \Delta \lambda$

where E is the power, and \bar{x} is the proportion of red primary required for that wavelength; Y and Z are found similarly.

In this way, we can determine the required amounts of primaries to match the color of a source or in the case of lights, the lamp. C.I.E. standard illuminant "A" (incandescent) has a published power distribution, as have several other sources, and tables of $E\bar{x}$, $E\bar{y}$, and $E\bar{z}$ are available. If the source is non-standard, the E values must be measured, and by computation, the tables developed. The significance of this information is that the color of the light transmitted by the filter depends not only on the filter but also on the spectral distribution of the light incident on it.

After tabled values for $E\bar{x}$, etc., are developed, they must be modified by the filter effect. Usually, this is done by measuring the filters' transmittances throughout the visible spectrum. This gives a new column labeled " τ ". Then, to obtain the X, Y, and Z required to form a match of the overall system, we must combine the data. Combining the source and filter data we solve the equations:

> - 770 $X = \Sigma 380 E \overline{X} \tau \Delta \lambda$ etc.

Mechanically this is done as follows:

443-453 () - 71 - 4

1. Measure the power distribution of the light source (E) in 10 nanometer steps from 380 to 770 nanometers (40 measurements).

AC 20-74 Appendix 3

- 2. For each step, combine (by multiplication) \bar{x} , \bar{y} , and \bar{z} information from tabled values to obtain $E\bar{x}$, $E\bar{y}$, and $E\bar{z}$ (40 values).
- 3. Measure the transmittance (τ) of the filter at these same 40 points. Combine these numbers with previously computed values to obtain 40 values for $E\bar{x}\tau$, $E\bar{y}\tau$, $E\bar{z}\tau$.
- 4. Add the 40 values for $E\bar{x}\tau$ to obtain X; the amount of red primary required for a match. Repeat for $E\bar{y}\tau$ and $E\bar{z}\tau$ to obtain Y and Z.
- 5. Compute $x = \frac{X}{X + Y + Z}$, $y = \frac{Y}{X + Y + Z}$, and $z = \frac{Z}{X + Y + Z}$. This gives the chromaticity coordinates which will form a metameric match of the light color.

The transmittance of a light filter is, by definition, the ratio of transmitted to incident light power. The transmittances (τ) measured at the 40 sample points do not consider eye response, nor the power distribution of the illuminant. Therefore, when we evaluate a filter for overall transmittance, we must combine the following data:

- 1. Power distribution of source E
- 2. Eye response luminous-efficiency function . . . \overline{y} [\overline{y} was adjusted to correspond to $V(\lambda)$]

3. Filter transmittance distribution $\ldots \ldots \tau$

These three variables were combined when developing Y as Σ_{380}^{770} Ey $\tau\Delta\lambda$. As this is also a measurement of visible transmitted light magnitude, dividing by the incident light will give the transmittance of the filter. The incident light is the same as the transmitted light if we omit the filter transmittances. Therefore, the incident light is Σ_{380}^{770} Ey $\Delta\lambda$ and the transmittance T = Σ_{380}^{770} Ey $\tau\Delta\lambda$.

Σ⁷⁷⁰ 380 Ey Δλ

APPENDIX 4

BIBLIOGRAPHY

- Vision in Military Aviation MADC Technical Report 58-399, ASTIA Document No. AD 207780.
- 2. Fundamentals of Light and Lighting General Electric Company, Large Lamp Department, Cleveland, Ohio.
- 3. Federal Standard No. J, with Amendment 1, March 21, 1951. Superintenden: of Documents, Washington, D. C. 20402.
- 4. Mil-C-25050A(ASG) December 2, 1963 Colors, Aeronautical Lights and Lighting Equipment, General Requirements For.
- 5. Color and Transmission Properties of Sharp Cut-Off Glass Filters at Elevated Temperatures - C. E. Leberknight and G. E. Stone, Kopp Glass, Inc., Swissvale, Pennsylvania, April 1955.
- Specification for Photometric Test Procedure, Specification CAA-110., June 10, 1957, Department of Commerce, Civil Aeronautics Administration, Office of the Air Navigation Facilities, Plant Engineering Division, Washington, D. C. 20402.
- 7. A Short Course in Photometry, Leo Levi, Consulting Physicist, New York, New York, Electronics Products, February 1965.
- 8. Collision Avoidance and Aircraft Lighting, Grimes Manufacturing Co., Urbana, Ohio, 1965.
- Measurement of the Effective Candlepower of Flashing Beacons Charles
 A. Steinberger and Marshal F. Rowland, Grimes Manufacturing Co., Urbana, Ohio, 1965.
- 10. Illuminating Engineering Society Lighting Handbook, Fourth Edition.
- 11. Illuminating Engineering Society Guide for Calculating the Effective Intensity of Flashing Lights, Illumination Engineering, <u>59</u> 747 (1964).
- Photometry of Colored Lights A. C. Wall, Illuminating Engineering, 1967.
- 13. MIL-L-25467C Lighting, Integral, Aircraft Instrument, General Specification For, (Dec. 1963).
- 14. Colors of Signal Lights, NBS Monograph 75, (1967). Superintendent of Documents, Washington, D. C. 20402.
- 15. U. S. Standard for Colors of Signal Lights, (1964).

AC 20-74 Appendix 4

- 16. 1968 NEREM Technical Publications. How to Measure Light P.B. Lape and D. V. Ryer, International Light, Inc., Newburyport, Mass.
- 17. Illumination Engineering Warren B. Boast, 1953.
- Colorimetry, NBS Monograph 104, 1968. Superintendent of Documents, Washington, D. C. 20402.
- 19. Light and Color Measurements of Small Light Sources, Boris Meric, General Electric Small Lamp Division, Nels Park, New York.
- 20. The Measurement of the Color of Light Emitted by Signal Devices, by Stewart Sease and Paul M. Fisher, Rohm and Haas Color Laboratory, Available as a reprint from "Color Engineering," Reprint Dept., 18 John Street, New York, New York 10038.
- The Application of a Color-Correction Factor in the Photometry of Colored Signal Lights by George K. C. Hardesty and T. O. Twist, Naval Ship Research and Development Laboratory, Annapolis, Maryland (Technical Note ELECLAB 125/58 of May 1968)
- 22. Maximum Luminous Efficiency Contour Charts for Colored Materials by George K. C. Hardesty, R. L. Booker, and J. T. McLane, Naval Ship Research and Development Laboratory, Annapolis, Maryland 21402 (Technical Note, ELECLAB 200/68 of October 1968).
- 23. Photometry, W. T. Walsh Constable, Third Edition, 1958.
- 24. The Role of Exterior Lights in Mid-Air Collision Prevention, T.H. Projector, Applied Psychology Corp., July 1962, ASTIA Document AD 602421.
- 25. Computation of the Effective Intensity of Flashing Lights, C. A. Douglas, Illumination Engineering, Vol. 52, page 641, December 1957.