

# NOTICE

U.S. DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION  
Air Traffic Organization Policy

N JO 7110.487

**Effective Date:**

August 11, 2008

**Cancellation Date:**

March 12, 2009

**SUBJ:** Takeoff Clearance

---

- 1. Purpose of This Notice.** This notice amends Federal Aviation Administration Order (FAAO) JO 7110.65, Air Traffic Control, Paragraph 3-9-9, Takeoff Clearance.
- 2. Audience.** This notice applies to the Terminal Services organization and all associated air traffic control facilities.
- 3. Where Can I Find This Notice?** The notice is available on the MYFAA employee Web site at [https://employees.faa.gov/tools\\_resources/orders\\_notices/](https://employees.faa.gov/tools_resources/orders_notices/) and on the air traffic publications Web site at [http://www.faa.gov/airports\\_airtraffic/air\\_traffic/publications](http://www.faa.gov/airports_airtraffic/air_traffic/publications).
- 4. Explanation of Policy Change.** This change now requires all runways to be crossed along the taxi route before the takeoff clearance can be issued.
- 5. Procedures.** Change FAAO JO 7110.65S, Paragraph 3-9-9, Takeoff Clearance, to read as follows:

## **3-9-9. TAKEOFF CLEARANCE**

- a. When issuing a clearance for takeoff, first state the runway number followed by the takeoff clearance.

### **PHRASEOLOGY-**

*RUNWAY (number), CLEARED FOR TAKEOFF.*

### **EXAMPLE-**

*"RUNWAY TWO SEVEN, CLEARED FOR TAKEOFF."*

### **NOTE-**

*Turbine-powered aircraft may be considered ready for takeoff when they reach the runway unless they advise otherwise.*

### **REFERENCE-**

*FAAO JO 7110.65, Para 4-3-1, Departure Terminology.*

- b. The controller must ensure all runways along the taxi route that lead to the departure runway are crossed before the takeoff clearance is issued, except in subpara c (below).
- c. At those airports where the airport configuration does not allow for an aircraft to completely cross one runway and hold short of the departure runway and/or where airports do not have runway hold markings between runways, state the runway to be crossed with the takeoff clearance if the aircraft is not able to complete a runway crossing before reaching its departure runway.

**REFERENCE-**

FAAO JO 7210.3, Para 10-3-9. Takeoff Clearance.  
Pilot/Controller Glossary Term - Clear of the Runway.

**PHRASEOLOGY-**

CROSS RUNWAY (number), RUNWAY (number), CLEARED FOR TAKEOFF.

**EXAMPLE-**

"CROSS RUNWAY TWO FOUR LEFT, RUNWAY TWO FOUR RIGHT, CLEARED FOR TAKEOFF.

- d. USA/USN. Issue surface wind and takeoff clearance to aircraft.

**PHRASEOLOGY-**

WIND (surface wind in direction and velocity).CLEARED FOR TAKEOFF.

**6. Distribution.** This notice is distributed to the following Air Traffic Organization service units: Terminal, Safety, and System Operations Services; the Air Traffic Safety Oversight Service; the Office of the Chief Counsel; the William J. Hughes Technical Center; and the Mike Monroney Aeronautical Center.

**7. Background.** The FAA Administrator's recent "Call to Action" workgroup made many recommendations to enhance runway safety. The Terminal Services Safety and Operations Support Office assembled a safety risk management panel to address some of the proposals from this workgroup. The panel did a safety assessment on takeoff procedures at FAA tower-controlled airports and found no high risks associated with this proposal.

**8. Implementation.** This notice shall be implemented on the effective date. The procedures will be incorporated into FAAO JO 7110.65S, change 2, effective March 12, 2009.



Nancy B. Kalinowski  
Vice President, System Operations Services  
Air Traffic Organization

7-10-08

Date Signed