



**U.S. DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION**

**ORDER
7930.2U**

National Policy

Effective Date:
June 9, 2025

SUBJ: Notice to Airmen (NOTAM)

This order prescribes direction used to format and distribute information regarding unanticipated or temporary changes to services, components of, or hazards in, the National Airspace System (NAS). Authorized personnel assigned to facilities that collect, originate, and/or disseminate NOTAMs must be familiar with the provisions of this order that pertain to their operational responsibilities. The Notice to Airmen (NOTAM) system does not advertise published or charted data and information.

CHRISTOPHER A WILBANKS
Digitally signed by
CHRISTOPHER A WILBANKS
Date: 2025.05.09 07:08:15
-04'00'

Christopher Wilbanks
Acting Vice President, Mission Support Services
Air Traffic Organization

Notice to Airmen (NOTAM)

Explanation of Changes

Effective: June 9, 2025

a. SUBJ: Notice to Airmen (NOTAM)

1-3-7. DEPARTMENT OF DEFENSE AIRFIELD MANAGEMENT

This changes the abbreviation NOTAM from Notice to Air Missions to Notice to Airmen and changes the subject of the order to Notice to Airmen (NOTAM). This change incorporates and cancels GENOT 25/02 N 7930.114, effective February 10, 2025.

b. 1-1-7. RECOMMENDATION FOR PROCEDURAL CHANGES

1-1-9. RELATED PUBLICATIONS

1-2-1. PURPOSE

1-3-1. AIR TRAFFIC ORGANIZATION (ATO)

1-4-6. DEFINITIONS

3-1-1. NOTAM RESPONSIBILITIES

3-1-4. PERMANENT (PERM) NOTAM PROCESS

3-1-5. PERMANENT (PERM) NOTAM PROCESS

3-2-3. NOTAM LOG

3-3-3. UNITS OF MEASUREMENT

3-3-5. RUNWAY IDENTIFICATION

4-1-1. U.S. NOTAM OFFICE RELATIONSHIPS

4-2-1. NOTAM COMPOSITION

4-3-3. CANCELLING PUBLISHED NOTAM DATA

5-1-3. MOVEMENT AREA INFORMATION

5-1-4. FIELD CONDITION (FICON) REPORTING

5-1-6. WORK IN PROGRESS

5-2-1. LIGHTING AIDS

5-2-2. OBSTACLES

5-3-7. NAVAID CONDITIONS

5-3-8. SATELLITE BASED SYSTEMS

5-4-3. COMMUNICATION OUTLET CONDITONS

5-5-1. GENERAL

5-5-2. CHANGES TO PUBLISHED SERVICES

5-5-3. HOURS OF OPERATION

5-5-4. WEATHER AND WEATHER REPORTING EQUIPMENT

6-1-1. AIRSPACE NOTAM FORMAT

6-1-2. SPECIAL ACTIVITY AIRSPACE (SAA)

6-1-3. AIRSPACE AND ALTITUDE RESERVATIONS

6-1-5. OTHER AIRSPACE NOTAMS

6-1-6. SURFACE AREA AIRSPACE

7-1-3. INSTRUMENT IFR FLIGHT PROCEDURES

7-1-4. HIGH BAROMETRIC PRESSURE WARNING

7-1-5. TEMPORARY FLIGHT RESTRICTIONS

7-1-8. LASER LIGHT ACTIVITY

8-1-1. INTERNATIONAL NOTAMs

8-1-2. INTERNATIONAL NOTAM DATA FORMAT

8-2-1. REQUEST FOR CANADIAN NOTAMs FROM THE CANADIAN NOTAM SYSTEM

The following change aligns the order with current Notice to Airmen (NOTAM) policies and processes. These changes include compliance with International Civil Aviation Organization (ICAO) standards and contractions.

Within definitions, added Not Available, in response to stakeholder request, Proposed NOTAM to replace Candidate NOTAM and redefined the Pointer NOTAM to limit its use and identify office responsible for issuance. Added Radio Navigation Aid limitations of ILS when Localizer or Glide Slope is out of service. Updated coordination responsibility and added ICAO language for the duration of a NOTAM. Edits were made within NOTAM composition to state clearer language on NOTAM schedule and validity. Amended the format of a commissioning of a movement area by adding location and option to add pavement classification rating. Modified language on use of Work in Progress (WIP) within a NOTAM. Updated lighting aid section and added approach lighting one-thousand (1000) foot bar. Corrected use of LGT U/S with wind turbines. Updated Navaid section for ILS and Communication section on language for ARTCC air to ground outlets. Added language to include Terminal Radar Service Areas, Updated Traffic Management Program Alerts. Updated all Airspace sections and included language on collection of contact information. Updated Temporary Flight Restriction section with clearer language and amended process for NOTAM on laser light activity.

c. Appendix A. 5-1-3. MOVEMENT AREA

Appendix A. 5-1-4. FIELD CONDITIONS REPORTING

Appendix A. 5-1-5. AERODROME FACILITIES

Appendix A. 5-2-1. LIGHTING AIDS

Appendix A. 5-2-2. OBSTACLES

Appendix A. 5-3-7. NAVAID CONDITIONS

Appendix A. 5-3-8. SATELLITE BASED SYSTEMS

Appendix A. 5-4-3. COMMUNICATION OUTLET CONDITIONS

Appendix A. 5-5-1. GENERAL

Appendix A. 5-5-2. CHANGES TO PUBLISHED SERVICES

Appendix A. 5-5-3. HOURS OF OPERATION

Appendix A. 5-5-4. WEATHER AND WEATHER REPORTING EQUIPMENT

Appendix A. 6-1-1. AIRSPACE NOTAM FORMAT

Appendix A. 6-1-2. SPECIAL ACTIVITY AIRSPACE

Appendix A. 6-1-3. AIRSPACE AND ALTITUDE RESERVATIONS

Appendix A. 6-1-4. SPECIAL AERIAL REFUELING

Appendix A. 6-1-5. OTHER AIRSPACE NOTAMS

Appendix A. 6-1-5. AIRSPACE NOTAM REQUIRING AUTHORIZATION/WAIVER

Appendix A. 6-1-6. SURFACE AREA AIRSPACE

Appendix A. 7-1-4. HIGH BAROMETRIC PRESSURE WARNING

Appendix A. 7-1-7. SPECIAL DATA

Appendix C. ICAO Difference for the United States

Appendix F. Radiosonde/Unmanned Free Balloon Flights

Appendix G. Technical Operations Reference Chart

This change updates example of commissioning of a movement area with addition of location and pavement classification rating (PCR). Added to NOT STD examples inclusion of remarks. Added example of 1000 foot bar, corrected Wind Turbine Farm example to condition of LGT U/S. within Navigational Aid, corrected Offset ILS example identifier, added LOC/DME example, corrected NOTE spelling out localizer directional aid. Updated service availability prediction tool (SAPT) NOTAM to add acronym and correct keyword for FDC NOTAM to AIRSPACE. Updated ARTCC communication NOTAM to align with FAA communication order and Aeronautical Information Manual to Remote Center A/G. Added example for local airport advisory service and NOTE. Added examples for changes of hours of operation for terminal radar service area. Updated examples for airspace, CARF NOTAM and aerial refueling. Updated high barometric pressure NOTAM, corrected keyword for special data example. Removed Appendix F and G due to current updated guidance and processes. Updated high barometric pressure warning example.

d. Editorial Changes

Editorial changes include correcting the paragraph numbering in Appendix D and a universal change replacing all prior references to the term Gulf of Mexico with the term Gulf of America in accordance with Executive Order 14172.

e. Entire Publication

Additional editorial/format changes were made where necessary. Revision bars were not used because of the insignificant nature of these changes.

CHANGE

**U.S. DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION**

**7930.2U
CHG 1**

National Policy

Effective Date:
August 10, 2025

SUBJ: Notice to Airmen (NOTAM)

- 1. Purpose of This Change.** This change transmits revised pages to Federal Aviation Administration Order 7930.2U, Notice to Airmen (NOTAM), and the Briefing Guide.
- 2. Audience.** Audience for this order is any office responsible for originating NOTAMs and those who use aeronautical information.
- 3. Where Can I Find This Change?** This change is available on the FAA website at http://faa.gov/air_traffic/publications and https://employees.faa.gov/tools_resources/orders_notices/.
- 4. Explanation of Policy Change.** See the Explanation of Changes attachment which has editorial corrections and changes submitted through normal procedures. The Briefing Guide lists only new or modified material, along with background.
- 5. Distribution.** This order is distributed to selected offices in Washington headquarters, service area offices, the William J. Hughes Technical Center, the Mike Monroney Aeronautical Center, and air traffic operations field offices and facilities.
- 6. Disposition of Transmittal.** Retain this transmittal until superseded by a new basic order.
- 7. Page Control Chart.** See the page control chart attachment.

**GREGORY
E SCHWAB** Digitally signed by
GREGORY E SCHWAB
Date: 2025.07.09
08:09:21 -04'00'

For: Christopher Wilbanks
Acting Vice President, Mission Support Services
Air Traffic Organization

Notice to Airmen (NOTAM)

Explanation of Changes

Change 1

Effective: August 10, 2025

- a. 1–4–6. DEFINITIONS**
- 2–1–3. PUBLICATION CRITERIA**
- 2–1–9. COMPUTER PRINTOUTS**
- 5–2–1. LIGHTING AIDS**
- 7–2–1. FDC NOTAM EXPIRATION/CANCELLATION**
- Appendix E. E–6. RETRIEVING FDC NOTAMS**

This change revises language in multiple paragraphs to be inclusive of all certificated part 139 airports to have access to the FAA NOTAM system. It also removed the requirement for a cancellation NOTAM to be issued upon the cancellation of original FDC NOTAM.

- b. 3–1–2. FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFRs**
- Appendix D. D–2. FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFRs**

This change addresses the procedure that was required for acknowledgment of identified FDC NOTAMs. With automation of coordination and external stakeholders providing flight planning and pilot informational briefings, the requirement for acknowledgement of certain FDC NOTAMs is not necessary. The procedures of processing the identified FDC NOTAMs for the watch supervisor, controller-in-charge (CIC), or designated lead specialist (DLS) responsibility were updated in this order until future update in FAA Order JO 7110.10, Flight Services. The requirement for USNOF to issue an FDC list has also been removed and is no longer part of the watch checklist.

- c. 7–1–1. GENERAL**
- 7–1–5. TEMPORARY FLIGHT RESTRICTIONS**
- Appendix A. 7–1–5. TEMPORARY FLIGHT RESTRICTIONS**

This change addresses the addition of Temporary Flight Restrictions (TFRs) for unmanned aircraft (49 U.S.C. section 44812) within Chapter 7 and Appendix A, updating Notice to Airmen (NOTAM) TFR examples. This change incorporates and cancels N 7930.115, effective August 7, 2025.

d. Editorial Changes

An editorial change to Appendix A, paragraph 7–1–4, updates the example to reference the correct regulation 14 CFR § 91.144 and includes the waiver language, ensuring that operators understand the need for compliance or special authorization.

e. Entire Publication

Additional editorial/format changes were made where necessary. Revision bars were not used because of the insignificant nature of these changes.

Comments/Corrections

Comments or corrections concerning this publication may be submitted on this form and submitted electronically to: 9-AJV-P-HQ-Correspondence@faa.gov

Notice to Editor

The following comments/corrections are submitted concerning the information contained in:

Paragraph number _____ Title _____

Page _____ Dated _____

Name _____

Street _____

City _____ State _____ Zip _____

Table of Contents

Chapter 1. General

Section 1. Introduction

Paragraph	Page
1-1-1. PURPOSE	1-1-1
1-1-2. AUDIENCE	1-1-1
1-1-3. WHERE TO FIND THIS ORDER	1-1-1
1-1-4. CANCELLATION	1-1-1
1-1-5. EXPLANATION OF CHANGES	1-1-1
1-1-6. DISTRIBUTION	1-1-1
1-1-7. RECOMMENDATION FOR PROCEDURAL CHANGES	1-1-1
1-1-8. EFFECTIVE DATE	1-1-2
1-1-9. RELATED PUBLICATIONS	1-1-2

Section 2. Scope

1-2-1. PURPOSE	1-2-1
1-2-2. PROCEDURAL APPLICATIONS	1-2-2
1-2-3. AVOIDANCE OF DUPLICATION	1-2-2

Section 3. Accountable Organizations

1-3-1. AIR TRAFFIC ORGANIZATION (ATO)	1-3-1
1-3-2. TECHNICAL OPERATIONS	1-3-2
1-3-3. FLIGHT STANDARDS SERVICE	1-3-3
1-3-4. OFFICE OF AIRPORT SAFETY AND STANDARDS	1-3-3
1-3-5. AIRPORT MANAGEMENT	1-3-3
1-3-6. NON-FEDERAL FACILITIES	1-3-3
1-3-7. DEPARTMENT OF DEFENSE AIRFIELD MANAGEMENT	1-3-4

Section 4. Terms of Reference

1-4-1. WORD USE IN THIS ORDER	1-4-1
1-4-2. NOTES	1-4-1
1-4-3. EXAMPLES	1-4-1
1-4-4. REFERENCES	1-4-1
1-4-5. MANUAL CHANGES	1-4-1
1-4-6. DEFINITIONS	1-4-1

Chapter 2. Aeronautical Information Services

Section 1. Aeronautical Information System

2-1-1. GENERAL	2-1-1
2-1-2. DISSEMINATION OF AIRMEN INFORMATION	2-1-1
2-1-3. PUBLICATION CRITERIA	2-1-1
2-1-4. DOMESTIC NOTICES AND INTERNATIONAL NOTICES	2-1-2
2-1-5. CHART/PUBLICATION ERRORS OR OMISSIONS	2-1-2
2-1-6. FORWARDING DATA	2-1-2

Paragraph	Page
2-1-7. ADDRESSING CORRESPONDENCE	2-1-3
2-1-8. THE NATIONAL FLIGHT DATA DIGEST (NFDD)	2-1-3
2-1-9. COMPUTER PRINTOUTS	2-1-3

Chapter 3. General Operating Procedures

Section 1. General

3-1-1. NOTAM RESPONSIBILITIES	3-1-1
3-1-2. FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFR	3-1-1
3-1-3. MILITARY NOTAMs	3-1-2
3-1-4. DURATION OF NOTAM	3-1-2
3-1-5. PERMANENT (PERM) NOTAM PROCESS	3-1-2

Section 2. Coordination

3-2-1. COORDINATION WITH OTHER FACILITIES	3-2-1
3-2-2. FILING NOTAM INFORMATION WITH FSSs	3-2-1
3-2-3. NOTAM LOG	3-2-1
3-2-4. PASSING NOTAM DATA BY PART-TIME FSS FACILITIES	3-2-1

Section 3. Use of Terms

3-3-1. USE OF CONTRACTIONS AND ABBREVIATIONS	3-3-1
3-3-2. EXPRESSION OF TIME IN THE NOTAM SYSTEM	3-3-1
3-3-3. UNITS OF MEASUREMENT	3-3-1
3-3-4. USE OF VIRGULE (/)	3-3-2
3-3-5. RUNWAY IDENTIFICATION	3-3-2
3-3-6. TAXIWAY IDENTIFICATION	3-3-2
3-3-7. APRON IDENTIFICATION	3-3-3
3-3-8. STANDARD NOTAM PHRASES	3-3-4
3-3-9. CARDINAL DIRECTIONS	3-3-4

Chapter 4. NOTAM D Procedures

Section 1. General

4-1-1. U.S. NOTAM OFFICE RELATIONSHIPS	4-1-1
--	-------

Section 2. Preparing NOTAMs for Dissemination

4-2-1. NOTAM COMPOSITION	4-2-1
4-2-2. NOTAM ACCOUNTABILITY	4-2-3

Section 3. Canceling/Extending NOTAMs

4-3-1. EXTENDING NOTAM VALIDITY	4-3-1
4-3-2. CANCELLATION OF NOTAMs	4-3-1
4-3-3. CANCELING PUBLISHED NOTAM DATA	4-3-1

Chapter 5. NOTAM Criteria

Section 1. Movement Area NOTAMs

Paragraph	Page
5-1-1. ORIGINATORS OF AERODROME NOTAMs	5-1-1
5-1-2. HANDLING REPORTED AERODROME CONDITIONS	5-1-1
5-1-3. MOVEMENT AREA INFORMATION	5-1-1
5-1-4. FIELD CONDITIONS (FICON) REPORTING	5-1-3
5-1-5. AERODROME FACILITIES	5-1-11
5-1-6. WORK IN PROGRESS	5-1-12

Section 2. Lighting Aid and Obstruction NOTAMs

5-2-1. LIGHTING AIDS	5-2-1
5-2-2. OBSTACLES	5-2-2

Section 3. NAVAID NOTAMs

5-3-1. GENERAL	5-3-1
5-3-2. REPORTING NAVAID MALFUNCTIONS	5-3-1
5-3-3. UNPROGRAMMED EXTENDED SHUTDOWNS	5-3-1
5-3-4. NAVAID MAINTENANCE SHUTDOWNS	5-3-1
5-3-5. UNMONITORED NAVAIDs	5-3-1
5-3-6. INSTRUMENT LANDING SYSTEM STATUS	5-3-1
5-3-7. NAVAID CONDITIONS	5-3-2
5-3-8. SATELLITE BASED SYSTEMS	5-3-7
5-3-9. HOURS OF OPERATION	5-3-8

Section 4. Communications NOTAMs

5-4-1. GENERAL	5-4-1
5-4-2. REPORTING COMMUNICATIONS OUTLET MALFUNCTIONS	5-4-1
5-4-3. COMMUNICATION NOTAM FORMAT	5-4-1

Section 5. Services NOTAMs

5-5-1. GENERAL	5-5-1
5-5-2. CHANGES TO PUBLISHED SERVICES	5-5-1
5-5-3. HOURS OF OPERATION	5-5-1
5-5-4. WEATHER AND WEATHER REPORTING EQUIPMENT	5-5-2
5-5-5. MICROBURST/WINDSHEAR DETECTION SYSTEM	5-5-3
5-5-6. RADAR SERVICES	5-5-3

Chapter 6. Airspace NOTAMs

Section 1. Airspace

6-1-1. AIRSPACE NOTAM FORMAT	6-1-1
6-1-2. SPECIAL ACTIVITY AIRSPACE (SAA)	6-1-1
6-1-3. AIRSPACE AND ALTITUDE RESERVATIONS	6-1-2

6-1-4. SPECIAL AERIAL REFUELING	6-1-2
6-1-5. AIRSPACE NOTAM REQUIRING AUTHORIZATION/WAIVER	6-1-3
6-1-6. SURFACE AREA AIRSPACE	6-1-4
6-1-7. AREA IMPACTED TABLES	6-1-4

Chapter 7. FDC NOTAMs

Section 1. Transmitting FDC NOTAM Data

7-1-1. GENERAL	7-1-1
7-1-2. TEMPORARY OR PERMANENT FDC NOTAMS	7-1-1
7-1-3. INSTRUMENT IFR FLIGHT PROCEDURES	7-1-2
7-1-4. HIGH BAROMETRIC PRESSURE WARNING	7-1-6
7-1-5. TEMPORARY FLIGHT RESTRICTIONS	7-1-6
7-1-6. AIR DEFENSE EMERGENCY	7-1-7
7-1-7. SPECIAL DATA	7-1-7
7-1-8. LASER LIGHT ACTIVITY	7-1-7
7-1-9. FDC NOTAM LIST	7-1-7
7-1-10. RETRIEVING FDC NOTAMs	7-1-8

Section 2. Cancellation/Expiration

7-2-1. FDC NOTAM EXPIRATION/CANCELLATION	7-2-1
--	-------

Chapter 8. International NOTAMs

Section 1. General Procedures

8-1-1. INTERNATIONAL NOTAMs	8-1-1
8-1-2. INTERNATIONAL NOTAM DATA FORMAT	8-1-1

Section 2. Procedures For Canadian NOTAMs

8-2-1. REQUEST FOR CANADIAN NOTAMs FROM THE CANADIAN NOTAM SYSTEM	8-2-1
---	-------

Appendices

Appendix A. Examples	Appendix A-1
Appendix B. International NOTAM (Q) Codes	Appendix B-1
Appendix C. ICAO Difference for the United States	Appendix C-1
Appendix D. Miscellaneous Functions	Appendix D-1
Appendix E. Computer Functions	Appendix E-1

Index

Paragraph	Page
Index	I-1

Chapter 1. General

Section 1. Introduction

1-1-1. PURPOSE

This order prescribes direction used to format and distribute information regarding unanticipated or temporary changes to services, components of, or hazards in, the National Airspace System (NAS). The NOTAM System does not advertise published or charted data and information. Originators of aeronautical information are expected to inform the Aeronautical Data Team in sufficient time before the effective dates of changes to permit publishing of aeronautical data on the various charts or in the appropriate publications. When time does not allow for publication of a change or an outage and if the subject matter meets NOTAM criteria, issue a NOTAM until published.

1-1-2. AUDIENCE

Audience for this order is any office responsible for originating NOTAMs and those who use aeronautical information.

1-1-3. WHERE TO FIND THIS ORDER

This order is available on the FAA's Air Traffic Plans and Publications website at http://faa.gov/air_traffic/publications and Orders & Notices website at https://www.faa.gov/regulations_policies/orders_notices/.

1-1-4. CANCELLATION

FAA Order 7930.2T, Notice to Air Missions (NOTAM), dated December 14, 2023, is canceled. ■

1-1-5. EXPLANATION OF CHANGES

The significant changes to the basic order will be published and included in the Explanation of Change page(s). It is advisable to retain the page(s) throughout the duration of the basic order. If further information is desired, direct questions through the appropriate facility/service area staff to System Operations Services, Flight Services, U.S. NOTAM Governance and Operations Group.

1-1-6. DISTRIBUTION

This order is distributed electronically to all who subscribe to receive email notifications through the FAA's website. All organizations are responsible for viewing, downloading, and subscribing to receive email notifications when changes occur to this order. Subscriptions to air traffic directives can be made through the Air Traffic Plans and Publications website at https://www.faa.gov/air_traffic/publications/ or directly via the following link: https://public.govdelivery.com/accounts/USAFAA/subscriber/new?topic_id=USAFAA_39.

1-1-7. RECOMMENDATION FOR PROCEDURAL CHANGES

a. The contents of this order will be periodically reviewed and updated, as required by National Airspace Data Interchange Network (NADIN) or NAS Messaging Replacement (NMR), General Notices (GENOTs), and order changes.

b. Any changes to this order must be submitted to the Policy Directorate Correspondence Mailbox at 9-AJV-P-HO-Correspondence@faa.gov.

1. Personnel should submit recommended changes in procedures to facility management.
2. Recommendations for changes or requests for waivers to policy from other sources should be submitted through appropriate FAA, military, or industry/user channels.

1-1-8. EFFECTIVE DATE

This order is effective June 9, 2025.

1-1-9. RELATED PUBLICATIONS

- Military units issue NOTAMs pertaining to their mission based on the guidelines set forth in Air Force Instruction Interservice Publication 11-208/AR 95-10/OPNAVINST 3721.20, DoD Notice to Airmen (NOTAM) System.
- FAA Order 5010.4, *Airport Data and Information Management*
- FAA Order JO 7110.10, *Flight Services*
- FAA Order JO 7210.3, *Facility Operation and Administration*
- FAA Order JO 7340.2, *Contractions*
- FAA Order JO 7350.9, *Location Identifiers*
- FAA Order JO 7400.2, *Procedures for Handling Airspace Matters*
- FAA Order JO 7400.10, *Special Use Airspace*
- FAA Order JO 7610.4, *Sensitive Procedures and Requirements for Special Operations*
- FAA Order JO 7610.14, *Non-Sensitive Procedures and Requirements for Special Operations*
- FAA Order 8260.19, *Flight Procedures and Airspace*
- FAA Order 8260.46, *Departure Procedure (DP) Program*
- FAA Order 8260.58, *United States Standard for Performance Based Navigation (PBN) Instrument Procedure Design*
- FAA Order 8400.13, *Procedures for the Evaluation and Approval of Facilities for Special Authorization Category I Operations and All Category II and III Operations*
- Technical Operations
 - FAA Order 6000.15, *General Maintenance Handbook for NAS Facilities*
 - FAA Order 8200.1, *U.S. Standard Flight Inspection Manual*
 - FAA Order 6750.24, *Instrument Landing System and Ancillary Electronic Component Configuration and Performance Requirements*
 - FAA Order JO 6500.28, *Radio Communications Requirements for Air Traffic Control Facilities*
 - FAA Order JO 6850.5, *Maintenance of Lighted Navigational Aids*
- 14 CFR Parts
 - 77, Safe, Efficient Use, and Preservation of the Navigable Airspace
 - 91, General Operating and Flight Rules
 - 139, Certification of Airports
 - 157, Notice of Construction, Alteration, Activation and Deactivation of Airports

– 171, Non-Federal Navigation Facilities

- Advisory Circular (AC) 99–1, *Emergency Security Control of Air Traffic (ESCAT)*
- Advisory Circular (AC) 150/5200–28, *Notice to Airmen (NOTAM) for Airport Operators*
- Advisory Circular (AC) 150/5200–30, *Airport Field Condition Assessments and Winter Operations Safety*
- Advisory Circular (AC) 150/5300–18B, *General Guidance and Specifications for Submission of Aeronautical Surveys to NGS: Field Data Collection and Geographic Information System (GIS) Standards*
- Advisory Circular (AC) 150/5300–13, *Airport Design*
- ICAO Annex 15, *Aeronautical Information Services*
- ICAO Doc 7383, *Aeronautical Information Services Provided by States*
- ICAO Doc 8400, *ICAO Abbreviations and Codes*
- ICAO Doc 8126, *Aeronautical Information Services Manual*
- ICAO Doc 10066, *Procedures for Air Navigation Services—Aeronautical Information Management*
- Pilot/Controller Glossary

Section 2. Scope

1-2-1. PURPOSE

Authorized personnel assigned to facilities that collect, originate, and/or disseminate NOTAMs must be familiar with the provisions of this order that pertain to their operational responsibilities.

a. The United States NOTAM Office (USNOF) is the final authority on NOTAM formatting. Proposed NOTAMs submitted through the NOTAM System (NS) must be in the proper format. To ensure NOTAMs are issued in accordance with NOTAM policy, NOTAM originators must comply with USNOF personnel directions.

b. All NOTAMs will be processed, stored, and distributed by the NS. In order to ensure that NOTAMs are processed and distributed properly, data for transmission must be coded as prescribed in this order.

c. The USNOF ensures the integrity of the NS by managing it for compliance 24/7.

d. NOTAMs must have one of the following keywords as the first part of the text. A keyword is used to make it easier to sort and locate the specific data needed: RWY, TWY, APRON, AD, OBST, NAV, COM, SVC, AIRSPACE, ODP, SID, STAR, CHART, DATA, DVA, IAP, VFP, ROUTE, SPECIAL or SECURITY.

NOTE-

Examples of keywords (RWY, TWY, APRON, AD, OBST, NAV, COM, SVC) are shown in Chapter 5; AIRSPACE in Chapter 6; (IAP, ODP, SID, STAR, DVA, ROUTE, and SPECIAL) relating to instrument flight procedures in Chapter 7.

1. RWY (Runway). Keyword used to describe a temporary change or hazard associated with landing and takeoff surfaces to include runway lighting, markings, signage, and other airport services or attributes associated with a specific runway.

2. TWY (Taxiway). Keyword used to describe a temporary change or hazard associated with a taxiway, taxiway lighting, markings, helipads, signage and other attributes associated with a specific taxiway.

3. APRON (Apron/Ramp). Keyword used to describe a temporary change or hazard associated with an apron, ramp, or taxilane, lighting, markings, helipad, signage and other attributes associated with a specific apron.

4. AD (Aerodrome). Keyword used to describe a temporary change or hazard or potential hazard on or within 5 statute miles of an airport, heliport, or maneuvering area that is not associated with a specific movement area surface. Such hazards may include, (but are not limited to), aerodrome closures, lighting not associated with a specific movement area surface, aerodrome services (fuel, customs, ARFF), helicopter platforms, meteorological equipment (wind indicators) or services, and wildlife hazards.

5. OBST (Obstructions). Keyword used to describe a temporary change or hazard. Such hazards may include, (but are not limited to), moored balloon, kite, tower, crane, stack, obstruction, wind turbine, obstruction lighting outage, obstruction status, or telecommunication tower light outage.

6. NAV (Navigation Aids). Keyword used to describe a temporary change or hazard caused by the changes in the status of ground-based radio navigational aids and Global Navigation Satellite Systems (GNSS) (except for area navigation (RNAV) approach anomalies).

7. COM (Communications). Keyword used to describe a temporary change or hazard caused by or related to communication outlets and air-to-ground frequencies due to commissioning, decommissioning, outage, or unavailability.

8. SVC (Services). Keyword used to describe a temporary change or hazard associated with change in service levels, such as operating hours, air traffic management services, or airport services. The ICAO contraction for service (SER) is an allowable contraction in the body of the NOTAM. "SVC" is only used as the keyword contraction for Service NOTAMs.

9. AIRSPACE (Airspace). Keyword used to describe an airspace restriction or activity warning which impacts, restricts, or precludes use of airspace. Such restrictions and activities may include, (but are not limited to), parachute jumping, unmanned aircraft, etc.

10. ODP (Obstacle Departure Procedure). Keyword used when a NOTAM applies to a textual or graphic obstacle departure procedure.

11. SID (Standard Instrument Departure). Keyword used when a NOTAM applies to a published standard instrument departure.

12. STAR (Standard Terminal Arrival). Keyword used when a NOTAM applies to a published standard terminal arrival.

13. CHART (Chart). Keyword used to describe a U.S. Government chart correction, followed by name of chart and word “CORRECT” that becomes effective before the next publication cycle.

14. DATA (Data). Keyword used to describe a temporary change or hazard associated with a data set change followed by the name of the data set to be changed; for example, U.S. DOD DAFIF, DACS, or NFD.

15. IAP (Instrument Approach Procedure). Keyword used when a NOTAM applies to a published instrument approach procedure.

16. VFP (Visual Flight Procedure). Keyword used when a NOTAM applies to visual flight procedures such as Charted Visual Flight Procedure and RNAV Visual Flight Procedure.

17. DVA (Diverse Vector Areas). Keyword used to describe a temporary change or hazard associated with a Diverse Vector Area.

18. ROUTE (Route). Keyword used to describe a temporary change or hazard or change associated with published Air Traffic Services (ATS) routes and related information.

19. SPECIAL (Special). Keyword used when a NOTAM applies to a special instrument flight procedure.

20. SECURITY (Security). Keyword used for Department of State advisories, Special Federal Aviation Regulations (SFARs), advisories of national emergency, national security actions, special security instructions, Air Defense Identification Zone (ADIZ) procedures.

NOTE–

Keyword SECURITY is not used for NOTAMs that describe a defined restricted area or TFR. Such NOTAMs would use keyword AIRSPACE.

e. (U) – Unverified. (U) is used preceding a keyword as described in paragraph 5–1–2.

f. The United States Department of Defense (DOD) will append the keywords IAP, SPECIAL, ODP, SID, and STAR with “U. S. DOD” to indicate that a published procedure is for military use only (not for civil use). For example, STAR U. S. DOD, SID U. S. DOD, IAP U. S. DOD.

1–2–2. PROCEDURAL APPLICATIONS

Apply the procedures in this order except when other procedures are contained in a Letter of Agreement or other appropriate FAA documents, provided they only supplement this order and that any standards they specify are not less than those in this order. FAA Order JO 7210.3, Facility Operation and Administration, contains administrative procedures for developing and executing those letters and documents.

1–2–3. AVOIDANCE OF DUPLICATION

Before issuing a NOTAM on any NOTAM criteria data, check all appropriate charts and publications to assure the information does not duplicate the published data. Do not issue a NOTAM on information that duplicates published data unless a NOTAM is required by a Certificate of Waiver or Authorization from Title 14, Code of Federal Regulations (CFR) issued by the FAA.

Section 3. Accountable Organizations

1-3-1. AIR TRAFFIC ORGANIZATION (ATO)

a. All air traffic organization, Federal Contract Tower (FCT), and Federal Contract Flight Service Station (FCFSS) employees, regardless of position, must immediately report any situation or condition considered hazardous to flight to an air traffic facility for appropriate action.

NOTE-

Situations that present an immediate hazard should be reported to the air traffic control (ATC) facility most concerned. Other situations should be reported on a first priority basis to the flight service station or appropriate accountable organization.

b. Air traffic organization, FCT, and FCFSS personnel must accept all aeronautical information regardless of source or subject matter, provided the occurrence is no more than seven days in the future. Obtain the name, title (if appropriate), address, and telephone number of the person furnishing the information and forward all data to the appropriate FSS for NOTAM issuance, if appropriate.

NOTE-

Forwarding the NOTAM data to the tie-in FSS does not relieve the forwarding facility from the responsibility of coordinating the information with other affected ATC facilities.

c. The party that originates the NOTAM on behalf of the accountable organization is responsible for the accuracy, origination, and cancellation of the NOTAM. FSS personnel receiving NOTAM information that requires action by another FSS must forward the information to that FSS for appropriate action.

d. The certified source is responsible for the correct classification and format of the NOTAM and for ensuring that facilities affected by the NOTAM are aware of the new NOTAM.

e. FSS specialists are responsible for issuing NOTAMs that are not covered in any example in FAA Order 7930.2. If, after consulting with your management, a format cannot be determined, have management contact USNOF for assistance.

f. The Flight Service Directorate has the responsibility to ensure that NOTAM data submitted or approved by FSSs complies with the policies, criteria, and formats contained in this order.

g. Service Areas originate NOTAMs for certain FDC criteria, including Laser activities and Temporary Flight Restrictions that are issued by the USNOF through NS.

h. Mission Support Services, Aeronautical Information Services (AIS) is responsible for originating Flight Data Center (FDC) NOTAMs for revisions to standard instrument approach procedures (SIAP), air traffic service (ATS) routes, textual and graphic departure procedures (both ODPs and SIDs), charting (CHART) corrections, and special instrument flight procedures. AIS may originate NOTAMs regarding navigational aid (NAVAID) restrictions in accordance with FAA Order 8200.1, United States Standard Flight Inspection Manual. AIS is responsible for:

1. Formulating Instrument Flight Procedures (IFP) and ATS route NOTAMs for procedures for which they have responsibility.

2. Formulating FDC PERM NOTAMs used to correct aeronautical chart printing and compilation errors related to all U.S. Government aeronautical charting products.

3. Designating an office to develop specific internal guidance for NOTAM preparation, quality control, transmittal, cancellation, and follow-up actions for FDC NOTAMs issued by AIS. This guidance must be developed in concert with the Aeronautical Data Team and the USNOF. As a minimum, the guidance must include the following:

(a) Procedures to ensure that the airport manager at the affected location is notified whenever possible.

(b) Procedures to ensure all NOTAMs are reviewed for accuracy, completeness, content, etc. prior to submission.

(c) Procedures to ensure the Aeronautical Data Team is provided information copy of all NOTAMs and cancellations.

(d) Procedures to ensure non-FAA service providers are provided an information copy of all NOTAMs and cancellations at those locations non-FAA service providers are allowed. This will ensure non-FAA service providers are aware of the condition requiring the NOTAM.

4. The Aeronautical Data Team is responsible for ensuring a hard/electronic copy of each PERM NOTAM is stored with the current amendment and maintained in the procedures archive file.

i. Mission Support Services is responsible for the development of policy guidance regarding standard terminal arrival routes (STAR). STAR NOTAMs are initiated by the Air Route Traffic Control Center (ARTCC) in the airspace where the STAR originates.

j. System Operations Services, System Operations Security (AJR-2) will provide a list of long-term, security related Temporary Flight Restrictions (TFRs) to be charted on VFR Sectional and Terminal Area Charts. These will include select Title 14 Code of Federal Regulations (CFR) part 99.7 (Special Security Instructions), part 91.141 (Flight Restrictions in the Proximity of the Presidential and Other Parties), and part 91.139 (Emergency Air Traffic Rules) security related TFRs of extended duration with fixed and unchanging boundaries. System Operations Security will provide Aeronautical Information Services with updates and revisions to these charted long-term, security related TFRs, as needed, to ensure the data published on the charts is current.

k. The U.S. NOTAM Governance Team is the FAA's authoritative source for US NOTAM Policy, responsible for the maintenance, update, and publication of this order, which establishes national policy for the National Airspace System (NAS) NOTAM operations. Additionally, the team is comprised of NOTAM Subject Matter Experts for domestic and international NOTAMs. This ensures global harmonization with ICAO Annexes, Standards and Recommended Practices, and other documents. The team also provides policy guidance, oversight, and interpretations for consistent application of US NOTAM standards.

l. USNOF executes the operational compliance function. When operational personnel of the USNOF determine that NOTAM information submitted is not in compliance with the criteria or procedures as prescribed, they must call this to the attention of the transmitting party. The USNOF forwards NOTAM policy questions to the U.S. NOTAM Governance Team for decision-making in consultation with other interested program offices. The USNOF is responsible for operating the NOTAM system. USNOF originates NOTAMs, as needed. (*See paragraph 4-1-1, National NOTAM Office Relationships for more detail*)

NOTE-

NOTAM office phone numbers: (888) 876-6826; (540) 422-4262.

1-3-2. TECHNICAL OPERATIONS

a. Operations Control Center (OCC) and Service Operations Center (SOC).

The Technical Operations Services, Operations Center manager, or representative, is responsible for:

1. Originating and canceling NOTAM information for shutdown, restoration, or any condition that affects the operations of NAVAIDs, frequencies, or other electronic aids that affect safety of flight. This includes forwarding data of programmed changes in the NAS, such as frequency changes, commissioning/decommissioning, etc.

2. Coordinating with appropriate air traffic facilities prior to shutdown or changes that affect safety of flight.

3. When possible, approval should be obtained sufficiently in advance of the proposed shutdown time to allow dissemination of a NOTAM at least 5 hours before a shutdown will occur. A routine maintenance shutdown request must not be denied because of an inability to issue a NOTAM 5 hours in advance of the shutdown.

b. Aircraft Operations Group, Flight Inspection Team

Flight Inspection Services under FAA Order 8200.1, United States Standard Flight Inspection Manual, initiate NOTAMs regarding radio and lighting NAVAID restrictions. Facility classification based on flight inspection results is the responsibility of the flight inspector.

REFERENCE-

FAA Order 5010.4, Airport Safety Data Program, and 14 CFR parts 139 and 157.

1-3-3. FLIGHT STANDARDS SERVICE

a. Flight Technologies and Procedures Division, AFS-400, is responsible for development of policy guidance and procedures for the origination, tracking, and cancellation of NOTAMs relating to instrument flight procedures. This policy applies to the following: SIAPs, ATS routes, textual and graphic ODPs, SIDs, and special instrument flight procedures (*see paragraph 1-3-1 for procedures addressing STAR NOTAMs*). AFS-400 is responsible for oversight of non-FAA service providers authorized to maintain SIAP and/or special instrument flight procedures. Maintenance includes issuance of FDC NOTAMs.

b. AFS-400 is responsible for coordinating non-FAA service provider NOTAM authority and access to the FAA NOTAM system with ATO Mission Support Services, Aeronautical Information Services. The division is also responsible for ensuring that specific guidance for NOTAM preparation, quality control, transmittal, cancellation, and follow-up actions are developed for NOTAMs applicable to public and Special IFPs developed by non-FAA service provider and not under the purview of AIS. As a minimum, the guidance must ensure the non-FAA service provider NOTAM originators include the following:

1. Procedures to ensure that all affected ARTCC facilities are provided notification of NOTAMs at the time of submission. The NOTAM issuing authority must also attempt to notify the airport manager at the affected location whenever possible.

2. Procedures to ensure all NOTAMs are reviewed for accuracy, completeness, content, etc. prior to submission.

3. Procedures to ensure the Aeronautical Data Team is provided an information copy of all NOTAMs and cancellations.

4. Procedures to ensure that AIS is aware of those locations where non-FAA service provider procedure development is allowed.

5. Procedures to ensure that AIS is provided an information copy of all NOTAMs and cancellations issued by other non-FAA service providers. This will ensure FAA procedure developers are aware of the condition requiring the NOTAM.

c. AFS-400 serves as the approval authority for requests that temporary NOTAMs be allowed to extend beyond the 224-day time frame.

1-3-4. OFFICE OF AIRPORT SAFETY AND STANDARDS

Though not an accountable organization, the Office of Airport Safety and Standards is responsible for enforcing the airport management responsibilities as outlined in the Code of Federal Regulations (CFR).

1-3-5. AIRPORT MANAGEMENT

Specific airport management responsibilities are outlined in 14 CFR Parts 139 and 157. Airport managers are required to abide by applicable provisions of these and pertinent regulations regardless of application of any procedure in this order.

1-3-6. NON-FEDERAL FACILITIES

a. NOTAMs on non-Federal facilities covered by FAA Order 6700.20, *Non-Federal Navigation Aids, Air Traffic Control Facilities, and Automated Weather Systems* are distributed through the FAA NOTAM system.

REFERENCE-

14 CFR part 171 outlines owner/operation responsibilities.

b. NOTAMs on non-Federal facilities that are not part of the NAS are not distributed in the FAA NOTAM system. FSSs receiving data on these facilities must notify Aeronautical Information Services.

1-3-7. DEPARTMENT OF DEFENSE AIRFIELD MANAGEMENT

Specific military airport management responsibilities are outlined in Air Force Instruction Interservice
■ Publication 11-208/AR 95-10/OPNAVINST 3721.20, DoD Notice to Airmen (NOTAM) System.

Section 4. Terms of Reference

1-4-1. WORD USE IN THIS ORDER

As used in this order:

- a. “Must” means a procedure is mandatory.
- b. “Should” means a procedure is recommended.
- c. “May” or “need not” means a procedure is optional.
- d. “Must not” means a procedure is prohibited.
- e. Singular words include the plural.
- f. Plural words include the singular.
- g. Miles means nautical miles unless otherwise stated.
- h. Feet means mean sea level unless otherwise stated.

1-4-2. NOTES

Statements of fact of an introductory or explanatory nature and relating to the use of directive material have been identified and worded as NOTE.

1-4-3. EXAMPLES

An illustration which serves to explain subject material is identified as an EXAMPLE which represents the format discussed in each section and is used as an aid to support policy. Not all components of the NAS will be illustrated with an example. The examples throughout Appendix A contain the keyword and the subject of the NOTAM. All other data is assumed from the NOTAM sentence structure and is eliminated from examples.

1-4-4. REFERENCES

When another paragraph of this order is referenced in the text, the referenced paragraph number will be printed out in full. When a paragraph is referenced in a Reference subparagraph, the referenced paragraph’s title, followed by its number, will be printed in regular type. When other documents and directives are referenced in a Reference subparagraph, the document/directive and the paragraph number will be printed in regular type. All references to other FAA orders reflect the current edition of the order.

1-4-5. MANUAL CHANGES

When revised, reprinted, or additional pages are issued, they will be marked as follows:

- a. Each revised or additional page will show the change number and effective date of the change.
- b. Vertical lines in the margin of the text will mark the location of substantive procedural, operational, or policy changes; that is, when material which affects the performance of duty is added, revised, or deleted.

1-4-6. DEFINITIONS

The terms below as used in this order are defined in this section.

a. **Accountable Organization.** The accountable organization is responsible for accurately reporting the condition considered to be a hazard or potential hazard to flight operations. Reporting the condition must be

accomplished by ensuring that procedures are developed to establish NOTAM origination and coordination responsibilities.

b. Accountability Location. This is the location identifier of the location in the NOTAM computer that keeps track of the NOTAM numbering.

c. Aeronautical Fixed Telecommunication Network (AFTN). This interface will be used to support the exchange of Aeronautical Fixed Telecommunications Network (AFTN) formatted messages between NADIN and a common set of external TCP/IP users utilizing the Communications, Flight Service and Weather Engineering Group's (CFWG) Common Message Handling Protocol (CMHP).

d. Aeronautical Information. Any information concerning the establishment, condition, or change in any component (facility, service, or procedure of, or hazard) of the NAS. This information is published and/or disseminated by means of aeronautical charts, publications, and/or NOTAMs.

e. Airport Operating Certificate. A certificate issued by the FAA, pursuant to 14 CFR part 139, to airports serving or expected to serve scheduled and unscheduled air carrier operations in aircraft with a seating capacity as determined under 14 CFR part 139. These airports are maintained and operated in accordance with an Airport Certification Manual (ACM) prepared by airport management and approved by the FAA.

f. Automatic Data Processing (ADP) Code. A computer code within the Aeronautical Fixed Telecommunication Network (AFTN) used to identify the start of a new NOTAM. The ADP equipment is programmed to accept and begin processing a NOTAM upon receipt of the ADP code, which is an exclamation point (!).

g. Certificated Airport. An airport certificated under 14 CFR Part 139. These airports are identified in the Chart Supplement.

h. Certified Source/NOTAM Originator. The party (e.g., airport, Tech Ops AIS/Service provider, FSS, etc.) who enters/submits a NOTAM to the NOTAM System (NS) on behalf of the accountable organization using an approved direct entry tool or interface.

i. Chart Supplement. A series of civil/military flight information publications issued by FAA every 56 days consisting of the Chart Supplement Alaska, Chart Supplement Pacific and Chart Supplement U.S.

1. Chart Supplement Alaska. A flight information publication designed for use with appropriate IFR or VFR charts which contains data on all airports, seaplane bases, and heliports open to the public including communications data, navigational facilities, airport diagrams, certain special notices, and non-regulatory procedures. Also included in this publication are selected entries needed to support the unique geographical operational conditions of Alaska. This publication is issued in one volume for the state of Alaska.

2. Chart Supplement Pacific. A flight information publication designed for use with appropriate IFR or VFR charts which contains data on all airports, seaplane bases, and heliports open to the public including communications data, navigational facilities, airport diagrams, certain special notices, and non-regulatory procedures. Also included in this are publication Instrument Approach Procedures (IAP), Departure Procedures (DP), and Standard Terminal Arrival (STAR) charts along with selected entries needed to support the unique geographical operational conditions of the Pacific Oceanic region. This publication is issued in one volume for the Hawaiian Islands and other selected Pacific Islands.

3. Chart Supplement U.S. A flight information publication designed for use with appropriate IFR or VFR charts that contains data on all airports, seaplane bases, and heliports open to the public including communications data, navigational facilities, airport diagrams, certain special notices, and non-regulatory procedures. This publication is issued for the conterminous U.S., Puerto Rico, and the Virgin Islands in seven volumes according to geographical area.

j. Distribution. Forwarding of NOTAM information from the NS to NADIN.

k. Fix/Radial/Distance (F/R/D). Is a VOR identifier followed by 3-digit degrees magnetic and minimum of a 3-digit distance in nautical miles with no spaces between characters (AML360020.1 would be 360-degree radial, 20.1 NM from AML VOR/DME).

l. Flight Data Center (FDC) NOTAM. The classification of NOTAMs containing flight information that is normally regulatory in nature including, but not limited to, changes to IFR charts, procedures, and airspace usage. FDC NOTAM numbers are assigned consecutively by the NS, beginning with 0001 each year. The year of issuance and the serial number are separated by a forward slash; for example, Y/1323.

m. International NOTAM. The classification of NOTAMs received from other countries and stored in the NS. These NOTAMs are numbered consecutively by accountability, location, and series beginning with S0001 each year, where S stands for a generic series a country may have. The NOTAM number and year of issuance are separated by a forward slash; for example, S0211/YY, S0002/YY.

n. Location Identifier. Used to designate an affected airport, air route traffic control center (ARTCC), or facility.

o. Military NOTAM. The classification of NOTAMs issued by the U.S. Air Force, Army, Marine Corps, Navy, and Coast Guard against navigational aids and airports. Military units issue NOTAMs pertaining to their bases and airspace based on the guidelines set forth in Air Force Instruction Interservice Publication 11–208/AR 95–10/OPNAVINST 3721.20, DoD Notice to Airmen (NOTAM) System. These NOTAMs are numbered consecutively by accountability, location, and series beginning with S0001 each year, where S stands for a generic series the military may have. The NOTAM number and year of issuance are separated by a forward slash; for example, S0211/15, S0002/15.

p. Movement Area. The term Movement Area as used for the purpose of NOTAMs, include Runways, Taxiways, Ramps, Aprons, helipads, heliports and maneuvering areas.

q. NADIN. The National Airspace Data Interchange Network (NADIN), also referred to as NMR (NAS Messaging Replacement), Message Switch Network (MSN) receives, processes, and distributes domestic and international flight planning, flight movement, weather observation/forecast, NOTAM, and search and rescue messages between the NAS, commercial/general aviation, U.S. Government agencies, aviation information service providers, and international Civil Aviation Authorities.

r. NAVAID. Any visual or electronic device airborne or on the surface which provides point-to-point guidance information or position data to aircraft in flight.

s. NMR. NAS Messaging Replacement also known as NADIN.

t. NOTAM D. The classification of NOTAMs containing information concerning the establishment, condition, or change in any aeronautical facility, en route navigational aids, services, procedures, hazards, certificated part 139 airports, and civil public-use airports listed in the Chart Supplement. NOTAM Ds are numbered consecutively each month by the NS starting with 001 for each accountability, for example: DAY 01/001 would be the first NOTAM in the month of January for Dayton Accountable Location.

u. NOTAM System. A safety-critical system that collects, maintains and distributes NOTAMs for the aviation community.

v. Not Available (NOT AVBL). Defined within the NAS when a facility, equipment, or service is not accessible or is not being provided as published within normal operation.

w. Pointer NOTAM. NOTAM D issued to point to additional aeronautical information. Pointer NOTAM use is limited to pointing to traffic management program alerts (see subparagraph 5–5–3d), TFRs, and temporary special use airspace (SUA). Pointer NOTAMs should not duplicate information already available through wide area dissemination (for example, NOTAM D with affected location of an ARTCC publicizing an ATC closure is available to all airports within ARTCC). Flight Service is the responsible party for issuance of Pointer NOTAMs on behalf of the accountable organization. A pointer NOTAM should only be originated at aerodromes directly impacted by the referenced activity. When pointing to another NOTAM, the keyword in the pointer NOTAM must match the keyword in the original NOTAM followed by the phrase “SEE” Include the affected location identifier, NOTAM number, and the NOTAM subject of the original NOTAM within the text of the Pointer NOTAM.

x. Prior Permission Required (PPR) means prior permission required to have full operational use of a runway, taxiway, apron, or airport facility/service. Means of communication to the airport can be telephone and/or radio. If PPR and another exception are used in same NOTAM, the PPR should come first.

y. Proposed NOTAM. A drafted NOTAM that has been submitted by an individual, office, or entity for consideration for publication within the NS to be numbered (previously called a Candidate NOTAM).

z. Radio Navigation Aid. As used in this policy, the word “Radio” is added to further describe navigation aids such as ILS, LOC, VOR or other NAVAIDs that are used in assisting the pilot with approaches, departures, and en route operations.

aa. Supervisory Authority. The supervisory authority is the organization responsible for managing the regulatory standards for the particular hazard being advertised in a NOTAM. The supervisory authority establishes organizational responsibilities to include particular or potential hazards, time parameters for origination, cancellation, and/or duration of NOTAMs, and particularly, exceptions to the policies and procedures provided in this document. Each supervisory authority must ensure that the authoritative provider is notified of all offices to which accountable and certified source authority has been granted. The supervisory authority is responsible for ensuring compliance with this directive.

ab. Taxilanes (TXL). Designed for low speed and precise taxiing. Taxilanes usually provide access (to and from taxiways (usually an apron taxiway) to (and from) aircraft parking positions and other terminal areas.

ac. Tie-In Station. A flight service station designated to provide prescribed services for civil, military, national and international facilities; for example, NOTAM purposes and flight information messages.

ad. Unserviceable (U/S). When a piece of equipment, a NAVAID, a facility, or a service is not operational, certified (if required), and immediately “available” for air traffic or public use.

ae. Unusable. The NAVAID is not available for operational use because it may provide potentially unsafe or erroneous signals, or signals of unknown quality.

af. Virgule (/). For US NOTAM purposes – a diagonal symbol used to separate similar alternatives.

ag. Visual Navigation Aid. As used in this policy, the word visual is added to further describe those navigation aids such as PAPI, ALS, VASI, etc., or any other lighting aid that is used in assisting the pilot with approaches or departures.

ah. WMSCR. Weather Message Switching Center Replacement is one of the FAA’s gateway for the receipt and distribution of weather within the National Airspace System (NAS).

Chapter 2. Aeronautical Information Services

Section 1. Aeronautical Information System

2-1-1. GENERAL

The system for disseminating aeronautical information is made up of two subsystems, the Aeronautical Information System (AIS) and the NOTAM System. The AIS consists of charts and publications. The NOTAM system is discussed in later paragraphs.

2-1-2. DISSEMINATION OF AIRMEN INFORMATION

Airmen information is disseminated by the following methods:

a. Aeronautical charts depicting permanent baseline data:

1. IFR Charts:

- (a) Enroute High Altitude Conterminous U.S.
- (b) Enroute Low Altitude Conterminous U.S.
- (c) Alaska Charts
- (d) Pacific Charts

2. U.S. Terminal Procedures:

- (a) Departure Procedures
- (b) Standard Terminal Arrivals (STARs)
- (c) Standard Instrument Approach Procedures (SIAPs)

3. VFR Charts:

- (a) Sectional Aeronautical Charts
- (b) Terminal Area Charts
- (c) Helicopter Route Charts
- (d) Caribbean Charts
- (e) Wall Planning Charts

b. Flight information publications outlining baseline data:

- 1.** Domestic Notices and International Notices
- 2.** U.S. Chart Supplement (formally Airport/Facility Directory)
- 3.** Pacific Chart Supplement
- 4.** Alaska Supplement
- 5.** Aeronautical Information Manual (AIM)

2-1-3. PUBLICATION CRITERIA

The following conditions or categories of information should be forwarded to the Aeronautical Data Team for inclusion in the flight information publications and charts. Time critical delays, corrections, or changes to

previously published data that cannot be republished before occurrence must be issued as a NOTAM, providing they meet the criteria set forth in this order.

a. NAVAIDs. Commissioning, decommissioning, shutdown, restrictions, frequency changes, changes in monitoring status and monitoring facility used in the National Airspace System (NAS). NAVAID outage NOTAMs must remain active until the NAVAID is returned to service or, if being decommissioned, published as shut down or removed from all applicable publications.

b. Commissioning, decommissioning, changes in hours of operation of FAA air traffic control facilities.

c. Surface areas/airspace. Changes in hours of operations.

d. Remote Communication Outlets and Remote Communication Air Ground. Commissioning, decommissioning, changes in voice control or monitoring facility.

e. Weather reporting stations. Commissioning, decommissioning, failure, nonavailability or unreliable operations.

f. Certificated part 139 and civil public-use airports. Commissioning, decommissioning, openings, closings, and abandonment.

g. Airport Rescue Fire Fighting (ARFF) capability. Restrictions to air carrier operations.

h. Changes to runway identifiers, dimensions, threshold placements, and surface compositions.

i. NAS lighting systems. Commissioning, decommissioning, outages, change in classification or operation.

2-1-4. DOMESTIC NOTICES AND INTERNATIONAL NOTICES

Domestic Notices and International Notices are published by Mission Support Services, Policy, Publications and Administration. See Appendix D for further information.

2-1-5. CHART/PUBLICATION ERRORS OR OMISSIONS

a. Managers must review each edition of the Domestic Notices and International Notices, Chart Supplement, and other publications and charts to ensure that all required data is included and correct. Inform the Aeronautical Data Team promptly of errors or omissions in any publication or chart. Notification of errors in the Domestic Notices and International Notices should be sent to Mission Support Services, Policy, Publications and Administration via 9-ATOR-HQ-PubGrp@faa.gov.

b. Managers must review all current NOTAMs issued by their facility on a quarterly basis for currency.

c. When NOTAMs are published, or more than 30 days old, contact the accountable organization for possible cancellation.

2-1-6. FORWARDING DATA

a. When notice is received of a temporary condition which is expected to be corrected before information can be published, issue a NOTAM if it meets criteria.

b. NOTAM or aeronautical information concerning an extended (more than 30 days) shutdown or closure affecting components of the NAS must be forwarded in advance of the occurrence to the Aeronautical Data Team. The Aeronautical Data Team must publish data received in accordance with existing policies, criteria, and publication cutoff deadlines. The schedule of publication cutoff dates is contained in the Chart Supplement.

c. Information received by the Aeronautical Data Team for publication that meets publication criteria and will be current on the effective date of the next available Chart Supplement publication or aeronautical chart will be published.

d. Refer questions and data changes to https://www.faa.gov/air_traffic/flight_info/aeronav/aero_data/.

2-1-7. ADDRESSING CORRESPONDENCE

Federal Aviation Administration
Aeronautical Information Services address:
Aeronautical Information Services
1305 East-West Highway
SSMC4, Suite 4531
Silver Spring, MD 20910-3281

2-1-8. THE NATIONAL FLIGHT DATA DIGEST (NFDD)

The NFDD is used to transmit data from the Aeronautical Data Team to chart and publication producers. It may be used to update records. However, it must not be used as a basis to cancel NOTAMs.

2-1-9. COMPUTER PRINTOUTS

Computer printouts listing all navigational aids, certificated part 139 landing areas, and civil public-use landing areas by flight plan area may be obtained from Aeronautical Information Services. ■

Chapter 3. General Operating Procedures

Section 1. General

3-1-1. NOTAM RESPONSIBILITIES

a. The certified source (NOTAM originator) that enters the NOTAM data is responsible for classifying, formatting, cancelling, and informing the controlling facility and other facilities/offices affected by the aid, service, or hazard contained in the new NOTAM.

NOTE-

1. In the contiguous United States (CONUS), Hawaii, Puerto Rico, and Guam, ARTCC Flight Data Units perform required NOTAM coordination. In Alaska, Flight Service performs the required NOTAM coordination.

2. During contingency events or for scheduled outages, Flight Service may be directed to perform manual NOTAM coordination for ATC facilities in the CONUS, Hawaii, Puerto Rico and Guam as needed.

b. Any certified source that receives information is responsible for the accuracy, currency, and validity of the NOTAM. When a certified source receives information that is outside their area of responsibility, they will inform the accountable organization.

c. FSSs must accept all aeronautical information. Information obtained from other than authorized personnel must be confirmed before issuance. NOTAM data received from state inspectors or state contracted inspectors must be confirmed by airport managers or appropriate authority before issuance of NOTAMs except in case of data that presents an immediate hazard to aircraft operations. If a NOTAM is issued without confirmation, advise the airport manager as soon as possible. In case of conflict between airport management and the named state airport inspector, contact FAA regional airports personnel for resolution. Conditions requiring a NOTAM should be coordinated with the appropriate air traffic facilities.

REFERENCE-

FAA Order 7930.2, Para 5-1-2, Handling Reported Aerodrome Conditions.

d. Tie-in Stations. The Flight Service Directorate must designate an FSS as tie-in point for NOTAM purposes for all facilities in the NAS. The facilities assigned should normally be within the confines of the FSS's flight plan area. Letters of agreement between facilities or other agencies and the FSS should be executed to assure proper handling of NOTAMs:

e. Inform the controlling facility of all Obstruction Light Outage NOTAMs that meet one of the following criteria:

1. The obstruction is located 6 NM or less from an airport.

2. The obstruction is more than 400 feet AGL.

3. Identified by the terminal facility as one not meeting the criteria stated in e1 or e2 above; however, has been deemed necessary for the safety of operations (for example, depicted on the radar video map).

f. A Domestic NOTAM will auto-reject if it is over 20 lines. Ensure the NOTAM meets AFTN capability prior to originating NOTAM.

g. When a NOTAM is rejected, it is not distributed. It will not be stored in the NOTAM master file, and it will not be available by request-reply. Error messages are not stored in the master file.

h. ARTCCs are responsible for forwarding FDC and special activity airspace (SAA) NOTAM information to the affected terminal facilities.

3-1-2. FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFR

See Appendix D for further information.

The NS must send NOTAMs referencing Title 14 CFR, part 91, section 91.139, Emergency air traffic rules; section 91.141, Flight restrictions in the proximity of the Presidential and other parties; part 99, section 99.7, Special security instructions; and any revisions, modifications, or cancellations, directly to all flight service stations via NADIN (NMR) using the flight service group address of “KXXXXAFSS.”

3-1-3. MILITARY NOTAMs

- a. See Appendix D for further information regarding military NOTAMs/functions/facilities.
- b. See Appendix E for further information with regard to retrieving military NOTAMs and service messages.

3-1-4. DURATION OF NOTAM

NOTAM must only address the time that the activity or condition is taking place. Temporary changes anticipated to last less than three months are considered to be information of short duration, which is distributed by NOTAM. When a temporary change, condition or activity is expected to exceed three months in advance of NOTAM issuance, it is considered to be information of long duration. Consideration should be given for publication of the long duration temporary change of condition until the subject of the NOTAM is returned to normal operation.

3-1-5. PERMANENT (PERM) NOTAM PROCESS

a. When a NOTAM is originated for a permanent change to published aeronautical information, “PERM” must be inserted in lieu of a 10-figure date-time group end of validity time. Prior to issuance of a PERM NOTAM, the accountable organization must demonstrate that the publication process has been initiated. The originator is required to enter a temporary NOTAM until they are able to confirm the initiation of the publication process.

b. To submit aeronautical data for publication, go to:

https://www.faa.gov/air_traffic/flight_info/aeronav/aero_data/Submitting_Data/

Section 2. Coordination

3-2-1. COORDINATION WITH OTHER FACILITIES

When a shutdown or an outage/closure of a component of the NAS will affect another facility's operation, the facility serving as the approval/controlling authority must coordinate with other facilities concerned.

3-2-2. FILING NOTAM INFORMATION WITH FSSs

NOTAM information should not be filed with an FSS (1-877-4-US-NTMS or 1-877-487-6867) prior to 7 days before the expected condition is to occur. A NOTAM must be transmitted as soon as practical but not more than 7 days before the expected condition is to occur.

3-2-3. NOTAM LOG

FSS air traffic managers must ensure that NOTAMs originated by their facility and FDC NOTAMs received must be accounted for as follows:

a. Log all NOTAMs on a locally approved form containing at least the same data for each accountability (NOTAM file) location. Information to include on the form: month, facility, NOTAM number, condition description, transmitted by/date-time group (DTG), and canceled by/DTG.

b. Incoming FDC NOTAMs and cancellations must be logged on a locally approved form, containing at least the same data. Information to include on the form: FDC NOTAM receipt log, NOTAM number, sending facility, affected facility, number canceled by, and remarks. The remarks section should contain enough information to identify the location and NAS component affected.

c. Electronic NOTAM logs are acceptable and can replace any paper log.

d. When an FDC NOTAM is received and the previous number(s) have not been received, obtain the NOTAM on request-reply.

REFERENCE-

FAA Order 7930.2, Appendix E, Para 7-2-3, Retrieving FDC NOTAMs.

3-2-4. PASSING NOTAM DATA BY PART-TIME FSS FACILITIES

a. Before closing, part-time facilities must give any known NOTAMs that will require dissemination during the hours the facility is closed to the FSS responsible for handling their NOTAMs during the period the facility is closed.

b. Immediately upon resuming the daily operation, part-time facilities must obtain all current NOTAMs, as well as pertinent FDC NOTAMs issued.

Section 3. Use of Terms

3-3-1. USE OF CONTRACTIONS AND ABBREVIATIONS

- a. Contractions and abbreviations designated for ICAO usage as specified in FAA Order JO 7340.2, Contractions, and ICAO Document 8400, *ICAO Abbreviations and Codes*, must be used in the NOTAM system. When an ICAO-usage contraction is not available, plain text is required, except for the list of differences in Appendix C.
- b. For indicating abbreviated days of the week, use a hyphen to indicate successive days or each day can be specified individually separated by a single space; for example, MON-FRI means Monday through Friday, whereas MON WED FRI means Monday, Wednesday, and Friday.
- c. Use the Pilot/Controller Glossary to define terms in the NOTAM system.
- d. Location identifiers used in the NOTAM system are those contained in FAA Order JO 7350.9, Location Identifiers.
- e. Use applicable contractions and abbreviations published on instrument flight procedure charts in the text of FDC NOTAMs relating to approach and departure procedures.
- f. Contractions written in the singular form decode to mean both the singular and plural.
- g. Contractions written in the past tense decode into both the past and present tense.

3-3-2. EXPRESSION OF TIME IN THE NOTAM SYSTEM

- a. The day begins at 0000 and ends at 2359.
- b. Times used in the NOTAM system are Coordinated Universal Time (UTC/Zulu) unless otherwise stated, as in the body of Temporary Flight Restrictions, and must be stated in 10 digits for the year, month, day, hour, and minute (YYMMDDHHMM).
- c. When describing a daily schedule, Sunrise-Sunset (SR-SS) may follow the day(s) or "DLY".

EXAMPLES-

MON-FRI SR-SS
 DLY SS-SR
 DLY SR-1800
 TUE 2300-SR

3-3-3. UNITS OF MEASUREMENT

Specify the unit of measurement in distance, height, altitude, or weight. When using an abbreviation, do not add a space between the measurement and the unit of measurement. At a minimum, latitude must be 6 digits and longitude must be 7 digits.

EXAMPLES-

500FT
 FL320
 12500LB
 5NM
 6.2NM
 20MIN
 1HR
 330DEG
 305DME
 402646N0795856W
 402646.25N0795856.95W

3-3-4. USE OF VIRGULE (/)

The use of virgules should be limited to separate runway pairs (RWY 03/21), combining positions and affected frequencies (LOCAL CTL/CD), and equipment, affected components and frequencies (ILS GP/OM/MM, VOR/DME 111.0/CH77).

3-3-5. RUNWAY IDENTIFICATION

- a. Specify the runway identification as it is published, including the leading zero (0).
- b. List the runway identifications in clockwise order beginning from 010 degrees.
- c. Use runway pair when applicable.
- d. Indicated runways should be in feet for sections, closure of a movement area, or portion thereof. Partial runway closures must be indicated by feet, for example, E 500FT.
- e. Identify runways with the prefix RWY followed by magnetic bearing indicator.

EXAMPLES-

RWY 03/21

RWY 03

RWY 21

- f. Differentiate parallel runways by using the runway designators followed by L (left), R (right), and C (center). Use L, R, and C with runway designators only.

EXAMPLES-

RWY 03L

RWY 03C

RWY 03R

- g. Where the magnetic bearing indicator has not been established, identify the runway to the nearest eight points of the compass.

EXAMPLE-

...RWY NE/SW...

3-3-6. TAXIWAY IDENTIFICATION

- a. Identify taxiways with the prefix TWY followed with the taxiway designator letter or letter/number as assigned.

1. Describe a taxiway that does not have an assigned designator as adjacent to a runway or direction from runway.

EXAMPLES-

...TWY PARL TWY ADJ RWY 09/27...

...TWY PARL TWY...

...TWY EAST/WEST TWY CLSD...

2. When a cardinal direction is used to describe a taxiway condition, the word describing the direction must be spelled out in full to ensure that the cardinal direction is not mistaken for a taxiway designator; for example, "EAST," "WEST," "SOUTHWEST."

3. Describe a helipad located on a taxiway as:

...TWY HELIPAD 3...

4. Describe a runup pad located on a taxiway as:

...TWY A RUNUP PAD...

...TWY C RUNUP PAD FOR RWY 27...

- b. Keyword TWY may be followed by designator "ALL" to indicate every taxiway at an airport, even if there is only one taxiway as: (Can be used as "TWY ALL EXC TWY X" if needed.)

...TWY ALL...

c. For multiple taxiways, use a comma between each designator. Do not add “TWY” prior to each individual taxiway identifier.

EXAMPLE-

...TWY B3, C...

1. Taxiway segments may be identified using geographic points, cardinal directions or by feet.

(a) Geographic. Identify geographic segments using “BTN” and “AND”.

EXAMPLE-

...TWY A BTN TWY B AND RWY 01/19...

(b) Cardinal Direction. Identify directional segments using a cardinal direction.

EXAMPLE-

...TWY C NORTH OF RWY 09/27...

(c) Dimension. Identify the amount of a taxiway affected by feet.

EXAMPLES-

...TWY DD NORTHEAST 500FT...

...TWY A BTN TWY L AND 300FT WEST OF TWY L...

(d) Multiple taxiways. Indicate a series of taxiways using a hyphen between the first and last descriptors.

EXAMPLE-

...TWY A1-A6...

NOTE-

The example includes taxiways A1, A2, A3, A4, A5 and A6.

(e) Multiple segments. Indicate all taxiway segments by starting with the contraction “TWY”, and then add the segment description separated by commas.

EXAMPLES-

...TWY A BTN TWY C AND TWY G, TWY B NORTH 100FT, TWY ALL NORTH OF RWY 09/27...

...TWY A BTN RWY 01L/19R AND RWY 01R/19L, TWY B BTN RWY 01L/19R AND RWY 01R/19L, TWY C BTN RWY 01L/19R AND RWY 01R/19L CLSD...

(f) Multiple segments (Single Taxiway). Indicate multiple segments of a single taxiway with each portion beginning with TWY.

EXAMPLE-

...TWY A EAST OF RWY 01L/19R, TWY A WEST 100FT...

2. Full taxiways and taxiway segments separated by commas share the same condition for example: CLSD, NOT MARKED, WIP SN REMOVAL, etc.

NOTE-

Snow removal must only be issued when snow removal is actually occurring.

EXAMPLES-

...TWY B1, B2, F, TWY B BTN TWY B10 AND TWY B8 WIP SN REMOVAL...

...TWY C BTN APCH END RWY 04R AND APCH END RWY 04L CLSD...

NOTE-

The originator may always issue multiple NOTAMs to ensure clarity.

3-3-7. APRON IDENTIFICATION

a. Identify aprons with the keyword APRON followed with the apron designator. There is no requirement for RAMP or APRON to be part of the name of the surface. Keyword may be followed by designator “ALL” to indicate every APRON at an airport, even if there is only one APRON as: (“APRON ALL” or “APRON ALL EXC WEST APN” if needed.)

EXAMPLES-

- ...APRON TERMINAL APN... (Where the name is Terminal Apron)
- ...APRON MAIN TXL C... (Where the name is Main)
- ...APRON ALL...
- ...APRON J RUNUP PAD...
- ...APRON HELIPAD A1...

NOTE-

This example describes a helipad (A1) that resides on a ramp. Only this helipad (A1) has an abnormal condition.

b. SPOTS, GATES, HARDSTANDS, etc., can be used as geographical reference points to delineate a section on aprons or taxiways, but do not meet NOTAM criteria as its own “attribute”.

EXAMPLE-

...APRON TERMINAL RAMP BTN GATE 3 AND SPOT 4...

3-3-8. STANDARD NOTAM PHRASES

The following are a listing (not inclusive) of standard terms used in NOTAMs.

TBL 3-3-1
NOTAM Phrases

UNL (unlimited)	TO POINT OF ORIGIN	OBSC (obscured)	UNREL (unreliable)
AVBL or NOT AVBL	CENTERED AT	UNUSABLE	CLSD
IRREGULAR SFC (lips, dips, bumps, holes, ruts, breaks, etc.)	NOW (temporary)	CHANGED TO (permanent)	UNSAFE
TO	EXC	NEAR	BTN and AND
PLUS SEE...	NOT STD	NOT LGTD	FLAGGED
FOR/AT (RWY)	WI AN AREA DEFINED AS	LGTD	USABLE (Used in conjunction with a restriction; not by itself)
U/S (Out of Service/Unser- viceable)	FLAGGED AND LGTD	ADJ (adjacent)	NONMOVEMENT AREA
BARRICADED (means any type of barricade)	LGTD AND BARRICADED	OPN or CLSD	MARKED or NOT MARKED

3-3-9. CARDINAL DIRECTIONS

Cardinal directions (excluding TAXIWAY usage) is in abbreviation format. This includes N, NNE, NE, ENE, E, ESE, SE, SSE, S, SSW, SW, WSW, W, WNW, NW, and NNW. Also included are directions for high altitude balloons – northbound – NB; northeast bound – NEB; eastbound – EB; southeast bound – SEB; southbound – SB; southwest bound – SWB; westbound – WB; northwest bound – NWB.

Chapter 4. NOTAM D Procedures

Section 1. General

4-1-1. U.S. NOTAM OFFICE RELATIONSHIPS

a. The USNOF is charged with monitoring the NS. The USNOF must monitor the NS for compliance with the criteria and procedures set forth in this order. When questions arise on NOTAM dissemination, formats, contractions, or other aspects of the distribution system, the USNOF should be consulted. The authority for NOTAM formats is the USNOF, who will ensure that issued NOTAMs are consistent with FAA policy. NOTAM originators and certified sources must comply with USNOF personnel guidance. Discrepancies in procedures or format must be recorded, and Aeronautical Information Services must forward a list of the discrepancies to offices and facilities providing origination or management of NOTAMs.

b. Editing:

1. The USNOF may edit any NOTAM (except FDC NOTAMs relating to instrument flight procedures) that does not conform to the formats and/or examples contained in this order. The contents of a NOTAM must not be changed without notifying the originating facility.

NOTE-

FDC NOTAMS relating to instrument approach and departure procedures are originated by the Mission Support Services – Aeronautical Information Services under the Flight Standards Service policy. ARTCCs must ensure the origination of NOTAMs pertaining to a Standard Terminal Arrival (STAR).

2. Should the USNOF edit a NOTAM and change the intent, the NOTAM must be canceled by the issuing facility and reissued as a new NOTAM, after consultation with the USNOF.


Section 2. Preparing NOTAMs for Dissemination

4-2-1. NOTAM COMPOSITION

NOTE-

For FDC NOTAM examples, see Appendix A.

FIG 4-2-1
NOTAM Diagram



Where the solid lines indicate mandatory and the dashed lines indicate as needed or optional.

a. The purpose of the NOTAM diagram is to provide a basic outline of what constitutes a NOTAM. Not all NOTAMs will contain all of the elements. For detailed explanation, consult the applicable paragraph sections for further NOTAM composition assistance.

b. NOTAMs may contain these elements from left to right in the following order:

1. An ADP code/exclamation point (!).
2. Accountability (the identifier of the accountability location; for example, JFK, FDC, CARF).
3. Location identifier {the affected facility or location, for example, (airport, NAVAID, or ARTCC) appears AFTER the NOTAM number}. Approach controls or airspace located within multiple ARTCC must have a separate NOTAM for each ARTCC.

(a) The nearest public use airport when the full activity is completely within a 5 NM Radius of the airport.

(b) The nearest VOR when any of the activity is more than 5 NM from the nearest public use airport but completely within 25 NM Radius of a VOR

(c) When the activity doesn't fall within either (a) or (b), use the ARTCC.

4. Keyword.
5. Attribute, activity, or surface designator(s) (when needed).

NOTE-

A surface designator is required with keywords RWY, TWY, and APRON. For example, a surface designator is RWY 14/32, TWY A, APRON FedEx Ramp.

6. Surface segment (when needed).

7. Facility, feature, service, system, and/or components thereof (when needed). Spell out facility names when used in the body of the NOTAM.

8. Location description (when needed).

9. Lower limit then upper limit, or height, (when needed). Limits must be specified, as:

(a) For SFC, or 1 to 17,999 feet, include the unit of measurement (FT) (for example, 50FT, 1275FT AGL, 10500FT).

(b) For 18,000 feet and above, express in flight levels (FL), (for example, FL180, FL550, FL850, or UNL altitudes greater than 99,900 feet).

(c) Feet means mean sea level (MSL) unless otherwise stated, and therefore the reference indication label MSL must not be included after the stated altitude in the NOTAM (for example, 1200FT). When referencing heights above ground level (AGL), include the reference indication label AGL after the stated altitude in the NOTAM (for example, 800FT AGL). Include heights AGL when required (obstacle NOTAM) or when MSL is not known, for example, SFC-450FT AGL

(d) The term UNKNOWN may be used in lieu of the MSL or AGL altitudes if not known; however, one altitude must be identified.

10. Condition. The changed condition or status being reported, when needed. When the conditions include a limitation or an exception, follow the condition with "TO" or "EXC"; such as, "CLSD EXC SKI" or "CLSD TO TRANSIENT" or "CLSD EXC TAX BTN APCH END RWY 10 AND TWY C."

11. Reason (when needed).

12. Remarks (when needed). Other information considered important; for instance, a frequency (134.72), or an expected altitude for unmanned free balloons (NEB TO 150000FT)

13. Schedule, (when needed). A NOTAM may be originated for a scheduled condition/activity that will occur during the period. Specify the schedule between the condition/activity and the valid time string. The days of the week must be specified before the scheduled time. The term "DLY" (daily) indicates the event will occur each day at the same time during the stated time period. The start time of the schedule must correspond to the start of activity time. The end of the last schedule must correspond to the end of validity time. If the active time of a NOTAM corresponds to sunrise or sunset, the actual times of sunrise on the first day of validity and of sunset on the last day of validity must be used.

EXAMPLES-

- DLY 1200-2000 YYMMDD1200-YYMMDD2000*
- MON WED 0900-1300 YYMMDD0900-YYMMDD1300*
- TUE THU 0900-2000 YYMMDD0900-YYMMDD2000*
- MON 2130-1800 TUE 2330-2000*
- YYMMDD2130-YYMMDD2000*

**FIG 4-2-2
NOTAM Schedule**





FIG 4-2-3
NOTAM Validity



14. Start of Activity/End of Validity. This is a 10-digit date-time group (YYMMDDHHMM) used to indicate the time at which the NOTAM condition or activity begins and the time at which the NOTAM condition or activity ends (the expected return to service or return to normal status). These times must be separated by a hyphen “-.” For example, ...RWY 15 CLSD YY12031400-YY12051359... indicates that runway 15 will close at 1400UTC on December 3rd. It is expected to reopen at 1359 UTC on December 5th.

(a) If the NOTAM duration is expected to return to service prior to the End of Validity time, express the time by using a date-time group followed immediately by “EST” (estimate). Any NOTAM that includes an “EST” must be canceled or replaced before the NOTAM reaches its End of Validity time. If the NOTAM is not canceled or replaced, it will expire at the end of validity time regardless of EST. FDC NOTAMs relating to instrument flight procedures must not be canceled and reissued.

(b) The accountable organization is responsible for validating that any NOTAM that is coming to its End of Validity time can auto-expire. If the condition is still valid, the NOTAM must be canceled and reissued with a new Start/Stop time, PRIOR to the NOTAM reaching its End of Validity time.

(c) When a NOTAM is originated to advertise a permanent condition that will be published in a publication, chart or database “PERM” should be inserted as the expiration date in lieu of a 10-digit date-time group. PERM is also used as the end of validity for certain NOTAMs that 1) pertain to or support national security, law enforcement, and aviation security requirements, and 2) contain flight prohibitions for U.S. operators and U.S. airmen regarding operations in particular areas of non-U.S. controlled airspace due to weapons related hazards or other hostile threats to civil aviation. The NOTAM originator is responsible for canceling the NOTAM upon publication, as PERM will not auto-expire.

(d) All NOTAMs will auto-cancel at their End of Validity time, except PERM.

(e) For an uncontrolled airport, when a NOTAM originator submits a proposed NOTAM to the NOTAM System to advertise an airport or runway condition with a Start of Activity less than 60 minutes before the beginning of an activity that impacts/closes a runway or an airport, the activity must be reported to the Air Traffic Control (ATC) facility that has control jurisdiction.

c. NOTAMs issued when the condition of a number of facilities, NAVAIDs, services, or landing areas/runways are related to the same event (for example, date/time, facility closing, part-timing, runway closures, etc.) must be issued as separate NOTAMs.

d. Each NOTAM concerning a specific aid, service, or hazard must be a complete report including all deviations unless reference is made to other restrictions already published.

e. If information is published elsewhere and is still valid, when a NOTAM is issued with additional condition data, reference must be made to that publication with the statement, "PLUS SEE (publication)." A NOTAM issued not stating "PLUS SEE (publication)" indicates the NOTAM replaces previously published similar data (for example, VOR radials).

f. NOTAMs must state the abnormal status of a component of the NAS and not the normal status. Exception: If the temporary restriction is published in the chart supplement and the situation has been resolved, return to normal operations. For example, a VOR was out of service for more than three months, published in the chart supplement, and then returned to service, issue NOTAM stating the VOR is returned to service (RTS).

4-2-2. NOTAM ACCOUNTABILITY

Maintain separate accountability (NOTAM file) for each location whose weather report is disseminated via WMSCR and for the location of the tie-in FSS.

a. Issue NOTAMs for an FAA-monitored weather reporting location whose report is disseminated via WMSCR under the location identifier of the weather report.

b. Issue all other NOTAMs under the location identifier of the tie-in FSS. This includes NOTAMs for weather reporting locations whose report is not disseminated via WMSCR.

REFERENCE-

FAA Order 7930.2, Chapter 2, Aeronautical Information Services.

c. Make NOTAM accountability changes by mail, email or other electronic means when known sufficiently in advance. Issue all subsequent NOTAMs under the corrected accountability. If there are any current NOTAMs for the location, cancel and reissue those NOTAMs under the new accountability after the NS tables have been changed. Notify Aeronautical Information Services of any NOTAM accountability changes.

Section 3. Canceling/Extending NOTAMs

4-3-1. EXTENDING NOTAM VALIDITY

When there is a need to extend an existing NOTAM time validity, cancel the original NOTAM, and reissue the data as a new NOTAM with the new time.

4-3-2. CANCELLATION OF NOTAMs

a. Stations canceling NOTAMs must check the NOTAM data to ensure the NOTAM's deletion. Retransmit cancellations where no action was taken.

b. Cancel NOTAMs containing erroneous information, and reissue. Originate a new NOTAM when data is received amending a current NOTAM, and cancel the previous NOTAM.

4-3-3. CANCELING PUBLISHED NOTAM DATA

a. When data appearing in a NOTAM is printed correctly in a publication or on a chart, cancel the NOTAM.

b. NOTAMs must remain active until correctly published in all applicable publications/charts, except NAVAID NOTAMs, which must remain in effect until the NAVAID is returned to service, published as shutdown, or decommissioned. Review all publications listed below:

1. Chart Supplement
2. Enroute low altitude charts
3. Enroute high altitude charts
4. Terminal procedures publications

NOTE-

FDC NOTAMs relating to instrument approach and obstacle departure procedures and airways must remain current until published in the Terminal Procedures Publication or applicable enroute chart.

5. VFR Charts:

- (a) Sectional charts
- (b) Terminal area charts

c. NOTAMs concerning Army airfield operations, in addition to the above listed sources, must be researched in the Army Aviation Flight Information Bulletin, if applicable.

Chapter 5. NOTAM Criteria

Section 1. Movement Area NOTAMs

5-1-1. ORIGINATORS OF AERODROME NOTAMs

a. Airport management is responsible for observing and reporting the condition of the aerodrome services, facilities, and movement area. The FSS air traffic managers must coordinate with appropriate airport managers to obtain a list of airport employees who are authorized to originate NOTAMs.

b. At public airports without an airport manager, the FSS air traffic manager must coordinate with the appropriate operating authority to obtain a list of persons delegated to provide NOTAM information.

NOTE-

Letters of agreement should be executed between airport management and ATC facilities outlining procedures to be used for originating NOTAMs.

5-1-2. HANDLING REPORTED AERODROME CONDITIONS

a. Copy any information received verbally, and record the name, title (if appropriate), address, and telephone number of the person submitting the information. Information obtained from other than an authorized airport or FAA employee must be confirmed before issuance. If you are informed of or observe a condition that affects the safe use of a movement area, relay the information to the airport management for action.

NOTE-


This includes data received from airport inspectors.

b. If unable to contact airport management, classify and issue a NOTAM publicizing the unsafe condition always stating the condition and including the word “UNSAFE;” for example, RWY number or TWY letter or letter/number “UNSAFE DISABLED ACFT.” Inform airport management of the action taken as soon thereafter as practical.

c. (U) – Unverified aeronautical information (for use only where authorized by letters of agreement). Movement area or other information received that meets NOTAM criteria and has not been confirmed by the airport manager or designee. If Flight Service is unable to contact airport management, Flight Service must forward (U) NOTAM information to the NS. Subsequent to NS distribution of a (U) NOTAM, Flight Service will inform airport management of the action taken as soon as practical. Any such NOTAM will preface the keyword with “(U)” and must include the condition and cause.

5-1-3. MOVEMENT AREA INFORMATION

FIG 5-1-1
Movement Area Diagram



...AD AP CLSD EXC PPR MON-FRI 0330-1430 YYMMDD0330-YYMMDD1430

See Appendix A for examples.

Originate a NOTAM D for:

a. Aerodrome conditions. Use the keyword “AD” immediately followed by the facility: “AP”, “HLP”, or “SEAPLANE BASE”, followed by the condition. When the condition includes a limitation, follow the condition with “TO” or “EXC;” for example, “CLSD EXC SKI” or “CLSD TO TRANSIENT.”

b. Commissioning of a movement area or portions thereof as follows

1. Surface designator.
2. Condition “COMMISSIONED”.
3. Location of movement area in reference to existing airport surfaces using phrases (PARL, ADJ, BTN, cardinal direction and distance).

4. Length and width of movement area, (for example, 5000FT X 150FT).
5. Type of surface (for example, CONC, ASPH, GRVL, GRASS, WTR, ICE).
6. Lighting status (LGTD, NOT LGTD).
7. Pavement Classification Rating (PCR), if provided (for example, PCR 760/R/B/W/T).
8. Runway declared distances, required for only runway commissioning, if provided.

c. Closure of a movement area or portion thereof. Partial runway closures must be indicated by feet, for example, E 500FT.

1. Permanent closure (decommissioning). State the surface description and the condition “CLSD” with expiration time “PERM.”

2. Temporary Nonmovement Area. Use this feature when a taxiway is temporarily designated as Non Movement in a NOTAM.

d. Operational limitations on the use of any portion of a runway, a taxiway, a ramp, an apron or a waterway.

1. Weight bearing capacity of a runway can be changed only by authorization of the Manager, Airports Division (appropriate region).

(a) Include reference to ACFT when describing limitations associated – wing, weight, tail, engine, taxi speed, etc.


(b) Do not refer to the Airplane Design Group in the NOTAM.

2. NOTAMs must not be used to impose restrictions on airport access for the purpose of controlling or managing noise or to advertise data already published or charted.

3. If an airport must restrict touch and go landings (TGL), then issue the NOTAM only during operational necessity. Do not issue a PERM NOTAM, unless the publication process has been initiated.

e. Changes to usable runway length and declared distances.

FIG 5-1-2
Sentence Structure



1. When a runway condition restricts or precludes the use of any portion of a runway resulting in a change to the declared distances, include the published take-off run available (TORA), take-off distance available (TODA), accelerate-stop distance available (ASDA), and landing distance available (LDA) in the NOTAM. Ensure that a second NOTAM is originated for the reciprocal runway with all declared distances if any value has changed. Declared distances can only be authorized by the FAA Office of Airport Safety and Standards, Airport Design Division, AAS-100.

2. In the event the published TORA, TODA, ASDA, and LDA need to be reported without reference to the runway condition that caused the change, report declared distances or changes to published declared distances. For example, when the published runway length is changed, report the declared distances, or erroneous declared distances that were published and need to be corrected.

f. Change of runway identification.

g. Change of traffic pattern.

h. Runway Visual Range (RVR). When originating a NOTAM on RVR, RVR touchdown (RVRT), RVR midpoint (RVRM), and RVR rollout (RVRR), specify the single runway affected. When all the RVRs are unserviceable, issue a NOTAM using the keyword AD.

i. Surface Markings and Signage. Follow 4-2-1b1-3, including:

1. Keyword. Specify the keyword for the type of surface on which the sign/marking is located.

2. Surface designator. Specify the designator of the surface on which the sign/marking is located.

3. Geographical Relationship of surface from relevant intersection/point of reference, (N OF, E OF), if needed.

4. Name of sign/surface marking. Signs follow runway identification guidance.

5. Sign/ marking location from users' perspective (LEFT/RIGHT SIDE; FOR RWY; AT RWY), when needed.

6. Condition. For example, NOT STD, LGT U/S, OBSC, MISSING, NOT MARKED.

7. When using NOT STD the originator must include in remarks the reason for the subject of the NOTAM not meeting standards.

8. Follow 4-2-1b11-14 to complete the NOTAM.

j. Other reportable conditions. The airport operator must ensure that a NOTAM is submitted for conditions considered to be hazardous or potentially hazardous to the aircraft operator. Permanent changes in surface conditions must be coordinated for publication in accordance with paragraph 2-1-3, Publication Criteria.

1. When SNOWBANKS, BERMS, DRIFTS, and SN PILES are not on the movement areas, issue them without the FICON descriptor.

2. When it is determined that no surface condition reports will be taken and no current observation exists, issue a single NOTAM (Keyword AD) for the entire time-period. Use the phrase "SFC COND NOT REP", as this differs from Conditions Not Monitored.

3. Wildlife.

(a) Wildlife NOTAMs are to be issued for abnormal events, not as general information, and must specify the type of wildlife event.


(b) If wildlife events are expected on a regular basis, submit this information for publication in the Chart Supplement.

(c) Wildlife NOTAMs must not be issued as PERM, unless the publication process has been initiated per paragraph 3-1-4, Permanent (PERM) NOTAM Process.

- (d) Once published, do not submit information as a NOTAM.

5-1-4. FIELD CONDITIONS (FICON) REPORTING

FIG 5-1-3
FICON



...RWY 33 FICON 4/4/4 100 PRCT COMPACTED SN PLOWED 100FT WID 24IN BERMS...

See Appendix A for examples.

- a. Report surface conditions on runways, taxiways, and aprons using the FICON NOTAMs. The keyword AD must not be used with descriptor FICON, except for heliport.

EXAMPLES-

...AD HLP FICON 4IN DRY SN...

...AD HLP FICON 2IN DRY SN PLOWED 50FT WID 4FT SNOWBANKS...

- 1. Runway.** Takeoff and Landing Performance Assessment (TALPA) FICONs are reported in thirds of the landing runway. Runways are described using the RWY keyword followed by a single runway direction designator, FICON and condition, except when reporting Slippery When Wet use the dual runway designator. Airport condition reports (FICON) must not be issued for a closed runway.

EXAMPLES-

...RWY 04/22 FICON 3/3/3 SLIPPERY WHEN WET...

...RWY 04 FICON...

- 2. Taxiway.** Taxiways are described using the TWY keyword followed by a surface name/designator, FICON and condition. Depth is required and a width is optional.

EXAMPLES-

...TWY A FICON 1/2IN WET SN...

...TWY A FICON 1/2IN WET SN 50FT WID REMAINDER COMPACTED SN...

- 3. Apron.** Aprons are described using the APRON keyword followed by a surface name/designator, FICON and condition. Depth is required and a width is optional.

EXAMPLE-

...APRON MAIN RAMP BTN RWY 13/31 AND TWY C FICON 1IN DRY SN...

- 4. Heliport.** Heliports are described using TWY or APRON keywords followed by HELIPAD (surface designator) FICON and condition.

EXAMPLES-

...APRON HELIPAD H1 FICON 2IN DRY SN...

...TWY HELIPAD C FICON DRY PLOWED 50FT WID REMAINDER COMPACTED SN...

- b. When there is a significant change in conditions, issue an updated FICON NOTAM.

- c. Airport operators use the Runway Condition Assessment Matrix (RCAM – See TBL 5-1-4) to create the Runway Condition Code (RwyCC) for Paved Surfaces, which include asphalt, asphalt-concrete, concrete, and

porous friction course. Non-paved surface NOTAMs do not include the RwyCC. The NS generates the RwyCC based on airport operator input of the contaminants present. Per AC 150/5200-30, *Airport Field Condition Assessments and Winter Operations Safety*, airport operators have the capability, in accordance with specific action and protocols, to downgrade or upgrade the runway condition code.

d. Each field of the NOTAM is described below. Follow the NOTAM composition in 4-2-1 a 1-4 to include:

1. **Surface Designator** (RWY 04)

2. **FICON**. Insert “FICON” after the surface designator and before the field condition.

3. **RwyCC**. When generated, it will be illustrated as values between 0 and 6 and look similar to this for runway thirds (3/4/2). The RwyCC will only be provided for paved runways when the percentage coverage of the full runway that is contaminated is greater than 25 percent. Report RwyCCs based on the direction of the assessment. Report only one set of RwyCCs per runway surface. For example, do not report two runway condition reports (one from each end) for a runway.

4. **Condition**. Report the contaminants per TBL 5-1-2, including the percentage of coverage for runways, in thirds. For taxiways and aprons, do not express the condition in terms of percentage of coverage. Use the word “PATCHY” to describe a contaminant that covers 25 percent or less of the reported portion of the surface of a taxiway, apron, heliport or airport.

TBL 5-1-1
Reportable Depth Measurements

Use Value	To Report
1/8IN	1/8 inch or less
1/4IN	>1/8 inch to and including 1/4 inch
1/2IN	>1/4 inch to and including 1/2 inch
3/4IN	>1/2 inch to and including 3/4 inch
1IN	>3/4 inch to and including 1 inch

TBL 5-1-2
Reportable Contaminants

Wet (includes damp and 1/8 inch depth or less of water)	Compacted snow
Water* (greater than 1/8 inch depth)	Water* over compacted snow
Frost	Wet snow* over compacted snow
Slush*	Dry snow* over compacted snow
Ice	Slush* over Ice
Wet ice	Slippery When Wet
Wet snow*	Ash
Wet snow* over ice	Rubber (taxiways only)
Dry snow*	Oil
Dry snow* over ice	Sand
	Mud* (See AC 150/5200-30)

TBL 5-1-3
Percent Coverage of a Contaminant

10	10% or less
20	11% - 20%

25	21% – 25%
30	26% – 30%
40	31% – 40%
50	41% – 50%
60	51% – 60%
70	61% – 70%
75	71% – 75%
80	76% – 80%
90	81% – 90%
100	91% – 100%

(a) Runways, including ski strip and waterlane.

(1) RWY: Each third (touchdown, midpoint, and rollout) will include percentage, depth (when required), and type of contaminant. Up to two separate contaminants can be reported per runway third.

(2) A runway is dry when it is neither wet, nor contaminated. A FICON NOTAM must not be originated for the sole purpose of reporting all thirds of a runway are dry. A dry surface must be reported only when there is need to report conditions on the remainder of the surface. When describing a dry surface, it is considered the full length and width of the runway third. DRY can be reported in two thirds and the remaining third have a different contaminant.

EXAMPLE-

...RWY 04 FICON 10 PCT 1IN WET SN, 10 PCT 1/8IN DRY SN OVER ICE AND 10 PCT 1/8IN DRY SN, DRY...

(3) A runway is wet when there is any visible dampness or water that is 1/8 inch or less in depth. When describing a wet surface, include the percentage.

(4) If all three thirds are identical percentage, depth (when required) and type of contaminant, it is shown in the NOTAM once.

EXAMPLE-

...RWY 03 FICON 4/4/4 75 PCT COMPACTED SN...

(b) Taxiways and Aprons. The condition includes depth and type of contaminant.

NOTE-

Free-form is an acceptable means of entering FICONS for TWY and APRONS.

(c) Reportable values

(1) Report depths in measurement of fractions as indicated in TBL 5-1-1 above. When 1 inch is reached, report values in multiples of 1 inch and discontinue the use of fractions. When a snow depth of 35 inches is reached, report values in multiples of feet only. Round depths greater than 1 inch to the next higher reportable depth.


(2) Report the highest depth of the contaminant along the reported portion of the surface.

(3) The only reportable contaminants and contaminant combinations authorized for use are found in TBL 5-1-2 above. These contaminants marked by an “*” must be accompanied by a depth for all Part 139/Federally obligated airports. For all other airports, the depths on taxiways and aprons is optional.

5. Action. Action taken to treat the contaminated surface.

(a) Includes the treatment method (Up to three treatments permitted for full length of runway/taxiway/apron.) Treatment includes plowed, swept, sanded, deiced liquid, deiced solid, scarified (for runways, each third must be contaminated with only ice and the total surface coverage must be >25%). A treatment width of 50FT is considered 25ft on each side of the centerline.

FIG 5-1-4
Cleared and Remaining Width




(b) Includes width of PLOWED or SWEPT treatment if not the full width. The treatment is omitted when the entire surface has been plowed or swept.

(c) Includes SANDED when a surface has been treated with sand.

(d) Includes DEICED LIQUID or DEICED SOLID or both to report the presence of liquid or solid deicing material, as this can have operational significance to the pilot.

(e) Includes ridges (when applicable) to describe the accumulation at the edge of the movement area or of the treated area when the surface has been plowed/swept. Ridges include SNOWBANKS, BERMS (containing earth/gravel), WINDROWS (ridge of snow created by mechanical means), and DRIFTS (deposit of snow sculpted by wind action into a mound). Use the term "DRIFTS" after any treatments (when applicable) to describe one or more drifts. When the drifts are variable in depth, report the greater depth.

FIG 5-1-5
Distance of Snow Bank from Runway Edge



EXAMPLE-

...FICON 5IN DRIFTS...

(f) Includes “Remainder” (see example above that refers to cleared and remaining width) to describe the non-treated depth and type of contaminant for full length of runway/taxiway/apron to provide additional information about the surface condition. For example, a runway has been treated, resulting in differing field conditions on the untreated parts of the surface.

EXAMPLES-

...FICON 4/4/4 50 PCT COMPACTED SN PLOWED 75FT WID REMAINDER 1/2IN DRY SN...

...FICON 25 PCT COMPACTED SN AND 10 PCT ICE, 25 PCT 2IN DRY SN, DRY PLOWED 75FT WID REMAINDER 1/2IN DRY SN...

6. Braking Action (BA). (APRONS, TWYs and Non-Paved RWYs). Report braking action on movement areas as good to medium; medium; medium to poor; poor; or nil, as received from airport management. The worst runway braking action is shown by contaminant type and RwyCC.

(a) Reporting of a “NIL” braking condition is not permissible by Federally Obligated Airports or those airports certificated under 14 CFR part 139. A “NIL” braking condition at these airports must be mitigated by closure of the affected surface.

NOTE-

A “NIL” braking action NOTAM can be issued at airports not receiving federal money and non-part 139 airports on taxiway or apron surfaces only. No aerodrome can issue a runway NIL braking action.

(b) Paved surfaced runways cannot have a stand-alone BA NOTAM.

(c) Non-Paved surfaced runways can have BA, but as a stand-alone NOTAM described using both runway ends.

(d) TWY/Apron can have BA as stand-alone or appended to field condition NOTAM.

NOTE-

A braking action report from a landing aircraft should be processed as a PIREP.

7. Observation Time. The time airport management observed the conditions.

8. Conditions Not Monitored (when applicable). When an airport operator cannot monitor the condition of the movement area or airfield surface, this information is issued as a NOTAM. Usually necessitated due to staffing, operating hours or other mitigating factors associated with airport operations. When the field conditions

will not be monitored, follow the most recent observation with the words “COND NOT MNT (date/time) (date/time).” The time parameters specified must fall within the start of activity/end of validity times.

9. Start of Activity/End of Validity. FICON NOTAMs are considered temporary, therefore the End of Validity time for FICON NOTAMs must not exceed 24 hours from the Start of Activity time, except:

- (a) When the reported contaminant is ASH, MUD, OIL, RUBBER (taxiway only), or SAND.
 - (b) When appended with remarks “COND NOT MNT.”
- e. Rubber as a contaminant/Slippery When Wet.
- 1. Rubber is used on Taxiways only to describe the accumulation of rubber.

EXAMPLE-

...TWYA FICON RUBBER...

2. Slippery When Wet is a stand-alone NOTAM, used only on runways, where a friction survey (conducted for pavement maintenance) indicates the averaged Mu value at 40 mph on the wet pavement surface failed to meet the minimum friction level classification. Slippery When Wet FICON NOTAMs are described using both runway ends.

REFERENCE-

AC 150/5200-30, Airport Field Condition Assessments and Winter Operations Safety.

EXAMPLE-

...RWY 02/20 FICON 3/3/3 SLIPPERY WHEN WET...

NOTE-


May be downgraded to 2/2/2 or 1/1/1 with all numbers matching.

TBL 5-1-4
Runway Condition Assessment Matrix

Runway Condition Assessment Matrix (RCAM)				
Assessment Criteria		Downgrade Assessment Criteria		
Runway Condition Description	Code	Mu (μ)	Deceleration Or Directional Control Observation	Pilot Reported Braking Action
<ul style="list-style-type: none"> Dry 	6	40 or Higher	---	---
<ul style="list-style-type: none"> Frost Wet (Includes Damp and 1/8" depth or less of Water) <p>1/8" (3 mm) depth or less of:</p> <ul style="list-style-type: none"> Slush Dry Snow Wet Snow 	5		Braking deceleration is normal for the wheel braking effort applied AND directional control is normal.	Good
<p>5° F (-15°C) and Colder outside air temperature:</p> <ul style="list-style-type: none"> Compacted Snow 	4	39 to 30	Braking deceleration OR directional control is between Good and Medium.	Good to Medium
<ul style="list-style-type: none"> Slippery When Wet (wet runway) Dry Snow or Wet Snow (Any depth) over Compacted Snow <p>Greater than 1/8" (3 mm) depth of:</p> <ul style="list-style-type: none"> Dry Snow Wet Snow <p>Warmer than 5° F (-15°C) outside air temperature:</p> <ul style="list-style-type: none"> Compacted Snow 	3		Braking deceleration is noticeably reduced for the wheel braking effort applied OR directional control is noticeably reduced.	Medium
<p>Greater than 1/8" (3 mm) depth of:</p> <ul style="list-style-type: none"> Water Slush 	2	29 to 21	Braking deceleration OR directional control is between Medium and Poor.	Medium to Poor
<ul style="list-style-type: none"> Ice 	1		Braking deceleration is significantly reduced for the wheel braking effort applied OR directional control is significantly reduced.	Poor
<ul style="list-style-type: none"> Wet Ice Slush over Ice Water on top of Compacted Snow Dry Snow or Wet Snow over Ice 	0	20 or Lower	Braking deceleration is minimal to non-existent for the wheel braking effort applied OR directional control is uncertain.	Nil

5-1-5. AERODROME FACILITIES

FIG 5-1-6
Aerodrome Facilities



...AD AP CLSD EXC PPR MON-FRI 0330-1430 YYMMDD0330 - YYMMDD1430

See Appendix A for examples.

Issue a NOTAM if any aerodrome service availability has changed from that which is published.

a. Certified Aircraft Rescue and Fire Fighting (ARFF).

1. Issue a NOTAM D on airports (not runways) certificated under 14 CFR Part 139, when notified by airport management that required ARFF equipment is inoperative/unavailable and replacement equipment is not available. Except as indicated in paragraph 5-1-5a 3, airport management has 48 hours to replace or substitute equipment before the index changes. Air carriers and others must be notified that ARFF equipment is unserviceable. Each NOTAM must have an expiration time as obtained from airport management. If unable to obtain an expiration time, add 48 hours to the time of receipt and advise airport management.

NOTE-

The ARFF Index for each certificated airport is published in the U.S. Chart Supplement, which lists indices and ARFF equipment requirements.

2. At certificated airports listed in the U.S. Chart Supplement, the certificate holder (airport management) is required to notify air carriers by NOTAM when required ARFF equipment is inoperative/unavailable and replacement equipment is not available immediately. If the required Index level of capability is not restored within 48 hours, airport management is required to limit air carrier operations.

REFERENCE-
Title 14 CFR Part 139

3. If the ARFF vehicle is still unserviceable after 48 hours, the airport manager must notify the FSS of a temporary index change and approximate duration time.

4. If the ARFF Index is listed in the U.S. Chart Supplement, as A and the ARFF vehicle is unserviceable, the NOTAMs must indicate that index A is not available and the airport is closed to air carrier operations.

b. Fuel Services.

c. Custom Services.

d. Aerodrome Beacon (ABN). Describe the beacon status as accurately as possible. For example, ABN NOT ROTATING; ABN NOT STD GREEN ONLY


e. Wind direction equipment, including wind cones, wind direction indicator, wind sock, etc.

f. Airplane Design Group. For those airports capable of permitting Group VI (A-380, B747-8) aircraft but have a limit on the capacity, issue a NOTAM when the capacity is reached so other aircraft won't attempt to land. Do not refer to the Airplane Design Group in the NOTAM.

REFERENCE-
AC 150/5300-13, Airport Design

5-1-6. WORK IN PROGRESS

FIG 5-1-7
Work in Progress



...TWY C WIP TRENCHING ADJ EAST SIDE...

a. Work in Progress (WIP) describes any work being done on the airport surface, including construction, mowing, snow/ice removal, etc. WIP must not close or restrict a movement area. If the terms CLSD, PPR, or BARRICADED are used, the movement area is considered to be restricted and a closure NOTAM for the movement area must be issued. For example, if WIP for snow removal requires a 15-minute PPR, a NOTAM must be issued for the closure of that surface with an exception for 15-minute PPR. If a movement area is closed, do not issue an additional WIP NOTAM for the closed area.

b. WIP (reason) is mandatory for describing construction and snow/ice removal NOTAMs. Other WIP reasons are optional.

c. Any NOTAM associated with work in progress on or adjacent to a runway, taxiway, apron/ramp, or aerodrome must be formatted as follows 4-2-1 b 1-3, including:

1. Keyword. RWY, TWY, APRON, or AD.

2. Surface name/designator. Specify the name/ designator of the surface on which the work is being conducted.

3. Surface segment description must be specified in feet or from a specific point to point; for example, TWY A SOUTH 76FT or TWY A BTN TWY B AND TWY C.

NOTE-

A surface segment differs from the optional plain language description of the work areas in that the surface segment description can be captured and depicted graphically in a digital environment. The optional plain language comments will be delivered in text form only.

4. Condition or activity; “WIP.”

NOTE-

Airport operators must ensure this NOTAM remains active only when actual snow and ice removal operations are taking place.

5. Reason or purpose.


6. Remarks. The work area may be described in plain language text after the reason by specifying the area by cardinal direction in relationship to the work area, by an intersection, or distance from an intersection.

7. Follow 4-2-1 b 13 and 14 to complete the NOTAM.

Section 2. Lighting Aid and Obstruction NOTAMs

5-2-1. LIGHTING AIDS

FIG 5-2-1
Lighting Aids



...RWY 27 RTHL U/S...

Originate NOTAMs on operational status of lighting aids for certificated part 139 and civil public-use landing areas listed in the U.S. Chart Supplement. Each type of lighting requires separate NOTAMs. Technical Operations must be made aware of any runway approach lighting outages, as this is the office that maintains the equipment. When describing restrictions, use Runway Centerline (RCL) with visual navigational aids. NOTAMs regarding lighting aids are originated as follows:

a. Commissioning

1. Approach lighting systems (ALS).

(a) Only use the runway direction for which the equipment pertains.

(b) When commissioning approach light systems, indicate the exact type of system (MALSR, MALSF, etc.). Once commissioned and published, approach light systems need only be shown as ALS.

2. Runway edge lights (REDL). When commissioning runway edge light systems, indicate the exact type of system (LIRL, MIRL, HIRL, etc.). Once commissioned and published, runway edge lights must only be shown as REDL.

b. Lead-in lights. Runway lead-in light system (RLLS).

c. Approach light systems (ALS).

1. ALS Outage

(a) Complete loss or dual mode with loss or unavailability of both ALS and SSALR capability.

(b) Dual mode with loss or unavailability of ALS capability only.

(c) When the ALS has been changed to the simplified, short ALS with runway alignment lights, issue the condition as temporarily changed (“NOW”). Do not use unserviceable (U/S).

2. Sequence flashing light (SEQUENCED FLG LGT).

3. One-thousand-foot bar (1000-FOOT BAR).

4. Runway alignment indicator light (RAI LGT).

5. Runway threshold light (RTHL).

NOTE-

Technical Operations issues RTHL, when associated with approach lighting systems (ALS).

d. Visual approach lighting.

1. Visual approach slope indicator (VASI).
2. Precision approach path indicator (PAPI).
- e. Runway lighting.
 1. Runway status light system (RWY STATUS LGT SYSTEM).
 - (a) Take-off hold light (TKOF HOLD LGT).
 - (b) Runway entrance light (RWY ENTRANCE LGT).

NOTE—

NOTAM issued using keyword TWY.

2. Runway end identifier light (RWY END ID LGT).
3. Runway touchdown zone lights (RTZL).
4. Runway centerline light (RCLL).
5. Runway edge light. (REDL).
6. Runway end light (RENL).
- f. Taxiway lighting.
 1. Taxiway centerline light.
 2. Taxiway edge light.
 3. Runway guard lights.
 4. Stop bar lights.

NOTE—


NOTAMs for guard lights and stop bar lights issued using keyword TWY.

- g. Lead off /lead on lights. NOTAMs issued using keyword RWY. Lead off and lead on light will be the standardized verbiage for lead off/on lights, which are also referred to as turnoff lights.
- h. Pilot – controlled lighting (PCL) frequency when it controls approach lights or runway lights.
- i. Airport lighting total power failure.
- j. Lights obscured due to snow and ice.
 1. Only issue a NOTAM when lighting is completely obscured (OBSC), do not report partial obscuration.
 2. Do not report reason for obscuration.

NOTE—

OBSC can be used to describe physical state of airport infrastructure, including signs and markings.

FIG 5-2-2


Obscured or Partially Obscured Runway Edge Lights

NOTE–

Lights that are partially obscured are not reported as a NOTAM.

5–2–2. OBSTACLES

FIG 5–2–3
Obstacles



...OBST CRANE (ASN 20YY–ACE–5–NRA) 345140N0804506W (1.44NM SW N52) 580FT (195FT AGL) NOT LGTD...

See Appendix A for examples.

a. Obstructions to include telecommunications antenna tower lights, cranes, stacks, wind turbines, non–FCC towers, power lines, moored balloon, kites, natural growth/terrain, etc.

b. Any failure or malfunction which affects a top light or flashing obstacle light regardless of its position is a condition for a NOTAM.

c. Commercial tower light operators must report the operating status of tower lights and ensure that a NOTAM is originated via a direct entry tool or contacting FSS.

d. The NOTAM text for obstructions to air navigation must be formatted as follows 4–2–1 b 1–2, including:

1. Location Identifier: For wind turbine farms, use the ARTCC under which the farm falls.

2. Keyword “OBST.”

3. Specify the attribute; for example, “TOWER LGT”, “CRANE,” “STACK,” “ACFT TAIL,” “BLDG,” “MOORED BALLOON”, “KITE” etc.

4. Assigned obstruction identifier.

(a) For FCC Towers, the Antenna Structure Registration (ASR), if known, in parentheses. If the ASR is not known, indicate by (ASR UNKNOWN) in the NOTAM.

(b) For Cranes, Stacks, etc., the Aeronautical Study Number (ASN), if known, in parentheses. If the ASN is not known, indicate by (ASN UNKNOWN) in the NOTAM. Do not include the ASN for wind turbine farm NOTAMs, see examples.

(c) For Moored Balloon, which requires a waiver to 14 CFR Part 101, the assigned obstruction identifier is not required.

5. For FCC Tower Obstructions, enter the location by latitude and longitude to the nearest one hundredth of a second. For wind turbine farms, if using latitude and longitude, provide the coordinates for the center point of the wind farm, or the coordinates for one of the turbines closest to the center. If the latitude and longitude is not known, use “UNKNOWN”. For all other obstacles, use the latitude and longitude to the nearest second, or fix/radial/distance, or a nautical mile radius of a NAVAID.

6. Plain language location in parentheses.

(a) When the obstacle is within 5SM of an airport, describe the plain language location in feet or nautical miles using 16 points of compass from a specified location on the airport; for example, (.5NM E APCH END RWY 18) (2000FT SSE DEP END RWY 20) (2NM SSW ACY).

(b) When the obstacle is within 500 feet either side of the centerline of a charted helicopter route, or 5SM or more from an airport and more than 200 feet AGL, describe the plain language location by using the bearing, distance, and aerodrome designator of the nearest public-use airport; for example, (12NM SSW SPA).

7. Specify the altitude MSL with the unit of measurement (FT), if known. Otherwise state UNKNOWN. For wind turbine farms, use the tallest height of a turbine within the farm.

8. In parentheses, specify the height with the unit of measurement (FT) and reference indication label (AGL).

NOTE-

Report the height of obstruction lights on terrain (hills) in MSL only, as the terrain is the obstacle, not the light on the terrain.

9. Specify the condition:

(a) “U/S” for FCC obstructions. A light condition of unserviceable refers to a top light or flashing obstruction light is not operating, regardless of its position.

(b) “NOT LGTD,” “LGTD,” “FLAGGED” for non-FCC obstructions, for example, cranes.

NOTE-

For wind turbine farms, use “LGT U/S”.

10. Start of Activity/End of Validity.

(a) FCC receives notification only upon ASR NOTAM issuance.

(b) Cranes. Schedule (when needed).

NOTE-

See paragraph 4-2-1, NOTAM Composition, for more details on NOTAM schedule formatting.

11. OBST NOTAMs must not be issued as PERM, unless initiated by those associated with the obstacle publication process. To initiate the publication process of obstacles, contact the FAA Obstacle Data Team at 9-ajv-532-obstdata-req@faa.gov.

Section 3. NAVAID NOTAMs

5-3-1. GENERAL

Technical Operations personnel must ensure the origination of NOTAM Ds concerning NAVAIDs for which they are responsible.

5-3-2. REPORTING NAVAID MALFUNCTIONS

Known or reported malfunctions of a navigational aid must be reported to Technical Operations or appropriate personnel.

5-3-3. UNPROGRAMMED EXTENDED SHUTDOWNS

Unprogrammed, extended facility shutdowns or other unanticipated outages that are expected to last more than 30 days must be promptly reported to the Aeronautical Data Team. When possible, the expected duration of the shutdown is to be included in the message. Except for emergency shutdowns, technical operations personnel are expected to give at least 1 hour notice.

5-3-4. NAVAID MAINTENANCE SHUTDOWNS

Information concerning maintenance shutdown of NAVAIDs that are part of the NAS must be handled as follows:

- a. Routine maintenance shutdown. When possible, approval should be obtained sufficiently in advance of the proposed shutdown time to allow dissemination of a NOTAM at least 5 hours before a shutdown will occur. A routine maintenance shutdown request must not be denied because of an inability to issue a NOTAM 5 hours in advance of the shutdown.
- b. Emergency shutdown. When possible, obtain at least 1-hour advance notice so that appropriate dissemination may be made before shutdown.
- c. Extended maintenance shutdown. Notify the Aeronautical Data Team sufficiently in advance to permit publication of the information prior to the shutdown date. When this is not possible, disseminate a NOTAM no more than 7 days before the shutdown.

5-3-5. UNMONITORED NAVAIDs

- a. All VOR, VORTAC, and ILS equipment in the NAS have automatic monitoring and shutdown features in the event of malfunction.
- b. When a navigational aid's operational status cannot be monitored at the controlling or monitoring facility, but all indications or reports are the facility is operating normally, Technical Operations personnel must ensure the origination of a NOTAM placing the aid in an unmonitored status.
- c. When issuing a NOTAM describing a facility as unmonitored, do not use the category of monitor, only the phrase "NOT MNT."
- d. Do not issue a NOTAM for a standalone DME that is not monitored.
- e. If the NAVAID is reported as being unserviceable, the unmonitored NOTAM must be canceled.

5-3-6. INSTRUMENT LANDING SYSTEM STATUS

a. Technical Operations issue NOTAMs related to outages or restrictions for all ILS equipment and components that they own/maintain/certify, regardless of duration. AIS 24/7 NOTAM Center is responsible for

issuing any procedural NOTAMs, such as flight data center (FDC) NOTAMs. Consult FAA Order 6750.24 to determine if any additional NOTAM Ds should be issued. Ideally, a NOTAM will allow authorized operators to continue, while notifying unauthorized operators that the specified approach procedure is not available. It is critical that required NOTAMs alert users of an inoperative facility or system. In some situations, an all-encompassing cancellation of specific minima (e.g., “CAT II/III Not Authorized”) may not be necessary.

b. Category II and/or III approaches may not be authorized due to the failure of additional equipment, as specified in FAA Order 6750.24. The Technical Operations Control Center specialist in accordance with the guidance contained in FAA Order 6750.24 will make the determination of impact to Category II/III ILS operations, and a separate NOTAM request for loss of ILS category will be made if the equipment failures warrant this action.

c. When Technical Operations personnel issue a NOTAM suspending CAT II/III minimums, AIS must be notified. If the suspension will exist longer than 224-days or is permanent, AIS must submit a full or abbreviated procedure amendment prior to the 224-day suspense.

d. Special Authorization CAT I/II approaches. These Part 97 CAT I/II approaches are identified as “ILS RWY XX (SA CAT I) or ILS RWY XX (SA CAT II)” and by an additional chart note saying “Reduced Lighting: Requires specific OpSpec, MSpec, or LOA approval.”

1. The aircraft operator is authorized to conduct CAT I/II IAP on certain ILS facilities that do not meet the equipment requirements of a U.S. Standard or ICAO Standard, for example when TDZ lighting or RCL become inoperative. These procedures have been specifically approved in accordance with FAA Order 8400.13, Procedures for the Evaluation and Approval of Facilities for Special Authorization Category I Operations and All Category II and III Operations.

2. When TDZ and/or CL lighting become inoperative on a standard CAT II instrument approach, the certificate holder is authorized to conduct SA CAT II operations.

5-3-7. NAVAID CONDITIONS

...NAV VOR 090-180 BEYOND 25NM SFC-5000FT, 270-300 BEYOND 25NM SFC-5000FT, 301-360 BEYOND 35NM SFC-4000FT UNUSABLE...

a. Introduction. Facility status classification and NOTAM(s) will indicate restriction(s) to the expected use of these facilities. The NOTAM advises the user of any restriction to facility usage.

1. If the NAVAID is out of service, the VOICE is automatically out of service and no VOICE NOTAM is required.

2. If the VOR is unmonitored and there is an associated VOR VOICE service, issue both an unmonitored and COM VOR VOICE NOTAM.

b. Facility Status Classification.

Operational Status. The legal facility status of Usable or Unusable is broken down as follows:

1. Usable. The facility is available for operational use and is either.

(a) Unrestricted. Providing safe, accurate signals-in-space conforming to established standards within the coverage area of the facility.

(b) Restricted. Providing signals-in-space not conforming to established standards in all respects or in all sectors of the coverage area, but safe for use excluding the restrictions defined.

2. Unusable. The facility is not available for operational use because it may provide potentially unsafe or erroneous signals, or signals of unknown quality. When describing visual aids, this term is used only by Flight Inspection.

c. NOTAM(s).

1. General. Originate a NOTAM D for commissioning, decommissioning, outages, or unmonitored status of radio navigation aids (60 minutes or more) that are part of the NAS. The NOTAM must be cancelled by the originator. An exception is that Technical Operations will originate a NOTAM for all Instrument Landing System Equipment and components for all associated outages regardless of duration. When a flight inspection necessitates NOTAM action, the flight inspector is responsible for initiating the NOTAM(s). The flight inspector must verify within 24 hours that the appropriate NOTAM(s) were issued, amended, or cancelled. The inspector must verify that NOTAM(s) are published in the appropriate agency publication.

2. Facility NOTAM D. The inspector must immediately initiate NOTAM action whenever a facility restriction is found or revised.

3. Initiating FDC NOTAM(s). FDC NOTAM(s) must be issued if a restriction affects instrument flight procedures, approach minimums, or category (CAT) II or III authorizations. Internal processes are in place between the Oklahoma City Service Center (OKC SC), the National Operations Control Center (NOCC), and Aeronautical Information Services (AIS) to ensure FDC NOTAM(s) resulting from reported facility outages, flight inspection results, or restriction changes are issued. The NOCC automatically notifies the AIS when there is a facility outage or restoration. The OKC SC will notify AIS when a flight inspection results in a new or canceled facility restriction.

4. Expanded Service Volume (ESV). When a facility no longer supports a particular ESV, an FDC NOTAM must be issued for each published instrument flight procedure that requires that ESV.

5. Preparation of NOTAM(s).

(a) NOTAM(s) must include facility name, type, component, and the unusable area/altitude. The absence of a specific altitude or distance denotes all altitudes and distances. It is important to include specific information to avoid confusion. The reason for the restriction (e.g., lack of signal, frequency interference, course structure, alignment, unlocks) serves no useful purpose and must not be included in the text of the NOTAM.

(b) Restrictions to VORTAC and TACAN facilities are issued via NOTAM D, including TACAN azimuth restrictions. The NOTAM preparation for the TACAN azimuth component of a VORTAC is identical to the VOR.

6. Facility Restrictions. Restrictions to NAVAIDs are normally published by segment: for example, 020–055 degree radials. To correct a given segment, cancel the original NOTAM and issue a completely new NOTAM. Every effort should be made to restrict rather than remove from service a facility, or instrument procedure, when out of tolerance conditions are found. Describe lateral restrictions in a clock-wise (CW) direction. The following illustrate the most common applications for Flight Inspection.

FIG 5-3-1
NAVAIDs



(a) General. When defining altitude restrictions, use the format, “SFC – XXXXFT,” where “SFC” stands for surface and XXXXFT is the top of the restriction in MSL altitude. Altitude restrictions recorded on data sheets, Flight Inspection reports, Airport/NAVAID (AIRNAV) database, and in the Chart Supplement, will use the standard flight inspection format of, “unusable below (altitude), or “unusable above (altitude),” as appropriate. The listed altitude is the usable MSL altitude. Only NOTAM(s) will use the “SFC–XXXXFT” format. For example: a VOR found unusable below 3000FT MSL would result in a NOTAM that lists the restriction as unusable “SFC–2900FT.” Use a 100FT increment from the “usable” altitude to describe the first “unusable” altitude.

(b) Excessive snow and ice accumulation near the glide slope antennas may affect facility performance to the extent that it is inoperative. When this occurs, Technical Operations personnel at the glide slope location

are required to initiate appropriate NOTAM D action. Technical operations personnel must monitor snow conditions to determine when conditions permit use of the glide slope and initiate action to cancel the NOTAM. Technical Operations and Aeronautical Information Services NOTAM Office make the determination when to issue an FDC NOTAM or NOTAM D, based on FAA JO 6750.49, *Maintenance of Instrument Landing System (ILS) Facilities*. Tech Ops issues the NOTAM D and AIS 24/7 NOTAM Center issues the FDC.

(c) VOR/ TACAN/DME/ VOT/ NDB/ DF. Describe radial/ bearing from the station in a clockwise direction, altitude in terms of above or below an MSL altitude, and distance in terms of beyond or within a nautical mile distance. When defining a restriction adjacent to another in azimuth, the same radial should not be contained in both restrictions. For example: don't state "020–090 and 090–110", but rather state either, "020–090 and 091–110", or "020–089 and 090–110."

(1) When describing restrictions to these kind of facilities:

- [a] Describe the radials or bearings that are unusable.
- [b] Describe the mileage point beyond which the facility is unusable.
- [c] Describe any altitude restriction using the NOTAM format.

(2) Follow this guidance for identifying specific components:

[a] VOR/DME. Reference "VOR/DME" when the restriction simultaneously applies to both the VOR and DME performance. Just use "VOR" if the restriction only applies to the VOR component, and "DME" if it only applies to the DME component.

[b] VORTAC. Reference "VORTAC" when all components (VOR, TACAN AZM, and DME) are being restricted together. Reference the individual component if the restriction only applies to that component.

NOTE–

When the DME portion of a VORTAC fails or is removed from service, the entire TACAN automatically becomes inoperative. However, the TACAN AZM can be unserviceable with the VOR and DME operational.

[c] VOT (VOR Test Facility).

[d] VOR Receiver Checkpoint. There are airborne receiver checkpoints (VOR AIRBORNE REC CHECKPOINT) and ground receiver checkpoints (VOR GND REC CHECKPOINT).

NOTE–

If there is more than one ground checkpoint, describe the location also.

[e] TVOR (Terminal Class VOR).

[1] TVORs serving one airport, and not associated with airway structure, must have NOTAMs issued using the associated airport identifier as the affected facility.

[2] TVORs serving more than one airport, or associated with airway structure, must have NOTAMs issued using the TVOR identifier as the affected facility.

[f] NDB outages:

[1] Terminal NDBs. Those NDBs located on or serving only that airport must have NOTAMs issued using the associated airport as the affected facility.

[2] If an NDB serves more than one airport, or associated with an airway route structure, issue a NOTAM using the identifier of the NDB as the affected facility.

[g] LOM outages.

[1] LOM serving one airport must be issued with the three-letter identifier of the airport as the location identifier.

[2] LOM serving more than one airport must be issued under the three-letter identifier of each airport that it serves. This procedure may require coordination with other facilities.

[h] NAVAID identification change. (See example in Appendix A).

(d) Visual Glide Slope Indicator. Describe in terms of nautical miles from threshold and/or degrees left and right of runway centerline any areas of coverage where the facility is unusable.

(e) A DME can be a separate facility, or a facility associated with an ILS, LOC, LOC Type Directional Aid, Simplified Direction Finder, NDB and VOR. When a DME is a separate system (a DME-only facility), the only condition is unserviceable. Restrictions are not published for DME-only facilities.

(f) Instrument Landing Systems (ILS).

FIG 5-3-2
ILS



...NAV ILS RWY 12 LOC UNUSABLE BEYOND 4DEG RIGHT OF COURSE...

(1) An ILS is a precision approach. Distinguish components of an ILS from non-precision approach NAVAIDs by preceding the component with “ILS” followed by “RWY” and the runway number (including single ILS airports). Use the term “COURSE” when describing radio navigation aid restrictions. Coupled approach restrictions (for ILS CAT I) are issued via FDC NOTAM.

EXAMPLE-

...NAV ILS RWY 14 LOC U/S...

NOTE-

Restrictions on instrument flight procedures caused by outages to a localizer backcourse will be issued separately as FDC NOTAMs.

(2) NOTAMS on a localizer backcourse (BC) may be issued for both outages and restrictions. A backcourse facility may be completely separate from front course operations.

EXAMPLES-

...NAV LOC RWY 16 BC UNUSABLE BEYOND 6DEG RIGHT OF COURSE...

...NAV LOC RWY 05 BC U/S...

NOTE-

1. Restrictions on instrument flight procedures caused by outages to a localizer backcourse will be issued separately as FDC NOTAMs.

2. When describing the back course, the runway designator is for the back course approach runway.

(3) Glide Slope Elevation. Describe in terms of degrees left or right of inbound course and nautical miles from threshold; Describe unusable altitudes in terms of surface to the lowest usable MSL altitude or as unusable above a highest usable MSL altitude. Ensure the restriction correctly reflects the service volume origin. Additional reference to DME distances may be used if the DME is part of the approach procedure.

(g) Localizer/LOC Directional Aid/Simplified Directional Facility Azimuth. There are runways equipped with a localizer facility without a glide slope, and are not designated an ILS.

EXAMPLES-

...NAV LOC RWY 08 U/S...

...NAV LOC RWY 08 UNUSABLE BEYOND 6DEG RIGHT OF COURSE...

(1) Lateral Restriction: Lateral restrictions are measured in degrees left or right of inbound course.

(2) Remaining Distance Restriction: Restriction occurs in the remaining distance to the runway, expressed in nautical miles from the runway threshold. For example, the localizer is unusable within 0.3 NM of the threshold.

(3) Usable Distance Restriction: Restrictions affecting the usable distance of the facility are measured in nautical miles from the antenna. For example, the localizer is unusable beyond 15 NM.

NOTE-

Additional reference to DME distances may be used for ease of correlating the restriction distance to the approach procedure, for those approach procedures with DME. However, DME distance will not be used to replace the distance from threshold/antenna.

7. Modifying an existing facility NOTAM. When a new facility restriction modifies an existing restriction, add “PLUS SEE (*publication*)” when other valid restrictions to the NAVAID are published. The absence of this statement from the NOTAM indicates that all other restrictions have been canceled.

Flight Inspection Work Flow Process:

(a) Given a VOR/DME with the published (not NOTAMs) restrictions of:

VOR Unusable: 005–040 BEYOND 27NM SFC–13000FT

VOR Unusable: 325–040 BEYOND 20NM SFC–10500FT

(b) And during a subsequent flight inspection it is determined that the previous restriction of 005–040 BEYOND 27NM SFC–13000FT must be moved in and raised so it now reads 005–040 BEYOND 25NM SFC–14000FT. First, cancel the existing restriction:

[CANCEL:] VOR 005–040 BEYOND 27NM SFC–12900FT UNUSABLE.

(c) Next, issue the NOTAM with the new restriction with the addition of “PLUS SEE”:

...VOR 005–040 BEYOND 25NM SFC–13900FT UNUSABLE PLUS SEE CHART SUPPLEMENT...

8. **NOTAM Scenarios.** The following are illustrations of conditions and prescribed NOTAM(s):

(a) All components of a VORTAC are unusable in a specific sector. For example, beyond 25NM and below 3500FT MSL due to out-of-tolerance VOR and TACAN course structure and unusable DME.

NOTAM: *...NAV VORTAC 025–075 BEYOND 25NM SFC–3400FT UNUSABLE...*

(b) The VOR and TACAN azimuth signals of a VORTAC are unusable in a specific sector. For example, beyond 25 NM and below 3500FT MSL due to out-of-tolerance conditions, and the DME is unaffected. Issue separate NOTAMs for each component.

NOTAM: *...NAV VOR 025–075 BEYOND 25NM SFC–3400FT UNUSABLE...*

NOTAM: *...NAV TACAN AZM 025–075 BEYOND 25NM SFC–3400FT UNUSABLE...*

(c) A VOR does not provide adequate signal within the standard service volume at the required altitudes in various areas sectors. For example, the VOR is unusable 080° CW to 100° beyond 18 NM below 3500FT MSL, and is unusable from 101° CW to 200° beyond 30 NM below 4500FT MSL.

NOTAM: *...NAV VOR 080–100 BEYOND 18NM SFC–3400FT, 101–200 BEYOND 30NM SFC–4400FT UNUSABLE...*

(d) A VOR is unusable in various areas below one altitude, and the DME is unusable in one sector. For example, the VOR is unusable below 1,700FT MSL in the following areas: 250° CW 265° beyond 17 NM; 266° CW 280° beyond 10 NM; and 281° CW 290° beyond 17 NM. DME unusable 225° CW 275° in the following areas: Beyond 15 NM below 2,400FT MSL and beyond 30 NM below 5,000FT MSL.

NOTAM: *...NAV VOR 250–265 BEYOND 17NM, 266–280 BEYOND 10NM, 281–290 BEYOND 17NM SFC–1600FT UNUSABLE...*

NOTAM: *...NAV DME 225–275 BEYOND 15NM SFC–2300FT UNUSABLE...*

NOTAM: *...NAV DME 225–275 BEYOND 30NM SFC–4900FT UNUSABLE...*

(e) A Nondirectional radio beacon is not usable at all altitudes beyond a certain distance in a sector. For example, the signal is unusable in the SE quadrant beyond 15 NM.

NOTAM: *...NAV NDB 090–180 BEYOND 15NM UNUSABLE...*

(f) Glide slope tolerances are exceeded at a specific point on the glidepath. Describe the restriction from the surface to the altitude specified in the flight inspection report. For example, an ILS glide slope is found unusable below 2900FT MSL.

NOTE-

Do not subtract 100 feet, rather use the altitude specified by flight inspection.

NOTAM: ...NAV ILS RWY 35 GP UNUSABLE SFC-2900FT...

(g) An ILS localizer exceeds tolerances at a point prior to the runway. For example, the localizer is unusable from 0.5 NM inbound.

NOTAM: ...NAV ILS RWY 25 LOC UNUSABLE WI .5NM...

NOTE-

(WI = within)

(h) An ILS localizer is restricted in usable distance. For example, the localizer is restricted beyond 12 NM from the facility.

NOTAM: ...NAV ILS RWY 33 LOC UNUSABLE BEYOND 12NM...

(i) A Cat II ILS ceases to meet CAT II criteria. Flight Inspection will coordinate with AIS to issue an FDC NOTAM to show “CAT II NA” for the associated ILS approach procedure.

(j) A CAT III ILS localizer exceeds CAT III tolerances in Zone 4. Flight Inspection will coordinate with AIS to issue an FDC NOTAM to show “CAT III NA” for the associated ILS approach procedure.

(k) A CAT II ILS localizer exceeds tolerances in Zone 4, (Zone 4 is not required for CAT II performance level II/T). A facility NOTAM (NOTAM D) is issued.

NOTAM: ...NAV ILS RWY 28 UNUSABLE INSIDE RWY THR...

(l) A CAT III ILS localizer exceeds tolerances in Zone 5, (Zone 5 is not required for CAT III performance level III/D). A facility NOTAM (NOTAM D) is issued.

NOTAM: ...NAV ILS RWY 10 UNUSABLE FOR ROLLOUT GUIDANCE...

(m) Glide slope does not meet change/reversal tolerances below a point on the glide path. For example, flight inspection determines the glide slope is not suitable for autopilot use below 1574FT MSL. Flight Inspection will coordinate with AIS to issue an FDC NOTAM with the following: AUTOPILOT COUPLED APPROACH NA BELOW 1574FT.

NOTE-

The facility is not considered restricted.

(n) Localizer does not meet tolerances in the vertical plane.

NOTAM: ...NAV ILS RWY 22 LOC UNUSABLE BEYOND OM ABOVE 3500FT, AND AT THR ABOVE 500FT...

(o) An out-of-tolerance condition is determined for an ILS glide slope left or right of the localizer centerline. For example, flight inspection finds that beyond 5° left of LOC course, there are no glide slope clearances above path, and a glide path is not provided.

NOTAM: ...NAV ILS RWY 30 GP UNUSABLE BEYOND 5DEG LEFT OF COURSE...

(p) VGSI systems can have different conditions.

(1) A PAPI could be off the air for any reason and the NOTAM would read: U/S. But, if it was found Unsatisfactory by flight inspection, the NOTAM term “UNUSABLE” is more appropriate.

(2) When a PAPI is not visible out to the standard 10-degree lateral azimuth due to baffling or optical performance, the NOTAM should describe the unusable area referenced to the runway centerline.

For example, the PAPI is not visible beyond 6 degrees left of centerline.

NOTAM: ...RWY 18 PAPI BEYOND 6DEG LEFT OF RCL UNUSABLE...

(3) VGSI may also be restricted in usable distance for obstacle clearance.

For example, the obstacle clearance plane is penetrated at some distance.

NOTAM: ...RWY 32 PAPI BEYOND 2.8NM UNUSABLE...

5-3-8. SATELLITE BASED SYSTEMS

a. Global Positioning System (GPS). Proposed global positioning system pseudo-random noise (PRN) GPS satellite outage NOTAMs will be submitted via an approved direct entry tool or interface by the DoD

NOTAM Office per request from the Air Force Space Command (AFSPACECOM) monitoring facility. PRN GPS NOTAMs must be issued under the accountability “GPS” with a location of “GPS.” When these NOTAMs get distributed internationally, the NOTAM System changes the designator “KNMH.” GPS testing NOTAMs must be issued under the accountability “GPS” with a location identifier of the affected ARTCC(s).

NOTE–

GPS operations are included in the Aeronautical Information Manual.

b. Wide Area Augmentation System (WAAS). WAAS area-wide NOTAMs are originated when WAAS assets are out of service and impact the service area. The term “MAY NOT BE AVBL” indicates that due to ionospheric conditions, lateral guidance may still be available when vertical guidance is unavailable. Under certain conditions, both lateral and vertical guidance may be unavailable. The USNOF distributes these as FDC NOTAMs when a WAAS asset failure affects a large area. USNOF utilizes templates provided by Technical Operations, WAAS Operations. All events must reflect an effective time and expiration time.

1. Unscheduled loss of signal or service.
2. Ionosphere storm conditions.
3. Scheduled loss of signal or service.
4. Operating under a single GEO
5. Extreme storm detector trips
6. Test
7. Emergency

c. Automatic Dependent Surveillance–Broadcast (ADS–B) and Wide–Area Multilateration (WAM). ADS–B and WAM NOTAMs are originated when assets are out of service and impact the service area. USNOF distributes these as FDC NOTAMs and utilizes templates provided by Technical Operations. All events must reflect an effective time and expiration time, whether scheduled or unscheduled loss of signal or service.

1. ADS–B. Distributed as FDC NOTAMs.
2. WAM. Issued as NOTAM D, with the impacted airport as the affected location.

d. Service Availability Prediction Tool (SAPT). If SAPT is out of service, then operators are entitled to relief from the preflight check requirements and will not be penalized. Otherwise, operators may use the FAA–provided preflight SAPT to determine predicted navigation or surveillance availability before a flight. SAPT predictions are based on:

1. The time, route, and airspace of the planned flight;
2. The announced status of the Global Positioning System (GPS) satellite constellation; and
3. ADS–B related avionics on the subject aircraft.

NOTE–

Under 14 CFR § 91.103, pilots and operators must use all available information in planning their flight to ensure that they will meet the performance requirements for the duration of the flight.

e. Ground Based Augmentation System (GBAS) and GBAS Landing System (GLS). Originate NOTAMs when the GBAS is unserviceable, is predicted to be unserviceable, or the usability of the GLS is restricted. GBAS facilities are operated by non–federal service providers.

1. Unscheduled loss of signal or service.
2. Predicted loss of signal or service.
3. Restricted usability of GLS.

5–3–9. HOURS OF OPERATION

Changes in the hours of operation of a NAVAID due to other than seasonal daylight time changes.

Section 4. Communications NOTAMs


5-4-1. GENERAL

Technical Operations personnel must ensure the origination of NOTAM D concerning communication outlets for which they are responsible.

5-4-2. REPORTING COMMUNICATIONS OUTLET MALFUNCTIONS

Known or reported malfunctions of a communication outlet must be reported to Technical Operations or appropriate personnel.

5-4-3. COMMUNICATION NOTAM FORMAT



...COM REMOTE TRANS/REC 126.25, 131.25 U/S...

Originate a NOTAM for conditions pertaining to the operation of communications outlets that are part of the NAS when an outage occurs or when a scheduled shutdown (60 minutes or more) is expected as follows:

a. Affected location.

1. Communication outlets associated with an airport or NAVAID, issue with the affected location as the airport or NAVAID.

2. Communications outlets not associated with an airport or NAVAID, issue with the affected location as the ARTCC.

NOTE-

Communication (COM) NOTAMs for the Approach Control frequencies which are located within the TRACON facility and all Remote Center Air-to-Ground facilities, will be issued with the ARTCC as the affected location with which the frequency provides coverage within. The full name of the facility will be spelled out after the keyword and before the type of A/G communication facility. For example, NORTHERN CALIFORNIA APP, DUTCH HARBOR REMOTE CENTER A/G.

b. Communication facilities.

1. Remote Center Air-to-Ground (REMOTE CENTER A/G).

(a) Air Route Traffic Control Centers (ARTCC).

(b) Combined Center Radar Approach Control (CERAP).

2. Remote Transmitter Receiver (REMOTE TRANS/REC).

(a) Air Traffic Control Towers (ATCT).

(b) Terminal Radar Approach Control (TRACON).

3. Remote Communication Outlet (REMOTE COM OUTLET).

- (a) Flight Service Station (FSS).**
- (b) Emergency Frequencies.**

4. Other Identified Communications.

- (a) Controller Pilot Data Link Communication (CPDLC).**
- (b) Ground Control (GND CTL).**
- (c) Local Control (LOCAL CTL).**
- (d) Clearance Delivery (CLR DELIVERY).**
- (e) Local Airport Advisory (LOCAL AP ADVISORY).**
- (f) Ground Communication Outlet (GND COM Outlet).**
- (g) Common Traffic Advisory Frequency (CTAF).**
- (h) Universal Communications (UNICOM).**

c. NOTAM conditions.

1. Commissioning and decommissioning. When decommissioning frequency, unserviceable (U/S) must be stated as the condition with a PERM validity end date.

2. An outage or (un)availability of communications outlets when an outage occurs or, when a scheduled shutdown (60 minutes or more) is expected. All published ATC frequencies and all communication frequencies will be issued with the affected frequency when unserviceable.


3. Communication outlet or facility frequency change.

- (a) Temporary frequency change,** issue with condition of NOW and new frequency to be used.
- (b) Permanent frequency change,** issue with condition CHANGED TO, new frequency to be used, and validity end date of PERM.

Section 5. Services NOTAMs

5-5-1. GENERAL

FIG 5-5-1
Services



...SVC XXX TWR CLSD TWR XXX.XX NOW CTAF CTC XXXXXXXX FOR CLR DELIVERY AT XXX-XXX-XXXX...

- a. Technical Operations personnel must ensure the origination of NOTAM D concerning the malfunction or degradation of FAA maintained systems and/or equipment.
- b. When notified, Technical Operations and Air Traffic personnel must ensure the origination of NOTAM D concerning changes to air traffic services and capabilities, for which they are responsible, for example, Tower visual signal–light gun.
- c. Services provided by air traffic control (such as surveillance approaches, practice instrument approaches, practice low approaches) do not meet NOTAM criteria as a standalone condition.

5-5-2. CHANGES TO PUBLISHED SERVICES

- a. The party that issues the NOTAM is responsible for formatting the information correctly.
- b. Originate a NOTAM for conditions pertaining to the following conditions:
 1. Commissioning, decommissioning, or outage of TWRs, APPs, RAPCONs, FSSs, and ARTCCs that are part of the NAS.
 2. Automatic Terminal Information Service (ATIS).
 3. Automatic Flight Information Service.
 4. Local Airport Advisory Service.
 5. Automated Universal Communication (AUNICOM). AUNICOMs have portions that are automatically broadcast along with the voice recordings. When these functions are unserviceable or not available, issue a NOTAM.

5-5-3. HOURS OF OPERATION

Any change of published hours of operation to ATC facilities, including contingency situations, must be submitted as an SVC NOTAM, ensuring not to duplicate published or charted data. When submitting NOTAMs, ARTCCs and approach controls must use the associated ARTCC as the location identifier. Approach controls located within multiple ARTCCs must have a separate NOTAM for each ARTCC. Air traffic control towers must use the airport as the location identifier. Satellite FSS must use the airport as the affected location. Hub FSS and FCFSS must use the ARTCC as the affected location. Flight plan areas located within multiple ARTCC airspace must have a separate NOTAM for each ARTCC. Spell out facility names when used in the body of the NOTAM.

Disseminate the following conditions as a NOTAM:

a. Change in the hours of operation of an air traffic control facility or published service. Closed (CLSD) is the appropriate term for events when an air traffic facility is unstaffed but does not result in a total failure of the facility (pandemic events, closing early, shortage of staffing, etc.). Unserviceable (U/S) is the appropriate term for complete system outages/total failure of a facility. Provide a NOTAM as stated in the following, ensuring not to duplicate published or charted data:

1. Air Route Traffic Control Center (ARTCC).

(a) Originate NOTAM D with a condition of CLSD or U/S.

(b) As necessary, provide additional information within an FDC NOTAM with the ARTCC as the affected location.

2. Approach control.

(a) Originate NOTAM D with a condition of CLSD or U/S.

(b) Provide which air traffic control services are or are not available, and whom to contact.

(c) Include language that identifies the air traffic control facility overlying the Class B or Class C airspace that will provide communications and separation services to aircraft.

(d) If an approach control contains two or more of either Class B, Class C, or Terminal Radar Service Area airspace, two or more NOTAMs must be issued, one for each category of airspace.

NOTE–

This includes approach controls with multiple airports that have the same class of airspace. For example, Northern California Approach has five airports with Class C Airspace (MRY, OAK, RNO, SJC and SMF), a NOTAM is required for each individual Class C.

3. Air traffic control tower.

(a) Originate NOTAM D with a condition of CLSD or U/S.

(b) Include language that provides common traffic advisory frequency (CTAF).

(c) Provide contact for clearance delivery if other than published.

(d) Include language that identifies the air traffic control facility overlying the Class B or Class C surface airspace that will provide communications and separation services to aircraft.

(e) Issue two NOTAMs, one for the ATCT closure and one for the approach closure, during an event closure with a combined, full-time ATCT/TRACON that the overlying ARTCC is unable to provide Class B or Class C services.

4. Flight service station. Originate NOTAM D with a condition of CLSD or U/S.

b. Establishment of a temporary air traffic control tower. Specify the frequency(ies) to be used and, if necessary, the control position associated with each frequency (e.g., local, ground). A temporary control tower does not change classification of airspace unless done through rulemaking.

c. At times, air traffic facilities temporarily extend their hours/availability of operation outside of published times. When this occurs, substitute “OPN” as the condition and include, if requested, the control position (e.g., local, ground) and the associated frequency(ies), for example, if published ATCT hours are 1130–0330 and the ATCT open hours are extending until 0530, then NOTAM would read SVC TWR OPN PLUS SEE CHART SUPPLEMENT YYMMDD0330–YYMMDD0530.

NOTE–

“PLUS SEE CHART SUPPLEMENT” only used when extending hours/availability outside of published times.

d. Traffic Management Program Alerts.

1. When requested by the associated arrival ARTCC TMU, FSS will issue a pointer NOTAM for each airport where an arrival/departure reservation is required. NOTAMs must be in self-canceling format.

2. When a flow control message for ground stops is received from the Air Traffic Control System Command Center (ATCSCC), FSS must issue a NOTAM(s) for the affected airport(s) in self-canceling format.

5-5-4. WEATHER AND WEATHER REPORTING EQUIPMENT

a. Technical Operations personnel, responsible for system monitoring, must ensure the origination of NOTAMs on the Federal Automated Weather Observation System (AWOS) as follows:

1. When malfunctions or discrepancies are identified, they must be verified by any of the following methods:

(a) A certified weather observer, airport manager, or fixed base operator at the observation site.

(b) Reports regarding a given observation by two pilots within 2 miles of the airport prior to the observation.

(c) Technical operations personnel.

NOTE-

For non-federal automated weather systems, see paragraph 1-3-6, Non-Federal Facilities.

2. When verified, issue a NOTAM and notify the responsible technical operations office of the discrepancy, unless they reported the outage. If notified of system failure or other irregularity by other than a technical operations office that cannot be verified by the methods given above, forward the information to technical operations office for resolution. Accept NOTAM cancellation information only from the responsible technical operations office.

b. Accept NOTAM information on Automated Surface Observing System (ASOS) only from the NWS Weather Forecast Office. Either the person on duty, Meteorologist in Charge, or Lead Forecaster, at the NWS Weather Forecast Office is responsible for requesting NOTAMs to be issued and canceled regarding ASOS system malfunctions and return to service. When malfunctions or discrepancies of an ASOS system are reported to a facility, they are reported to the NWS Weather Forecast Office.

c. Disseminate only the following conditions as NOTAMs for AWOS and ASOS:

1. Total system failure (which includes date-time code failures).

2. The entire ASOS or AWOS observation is missing and no backup observation is available for long-line dissemination.

3. The altimeter setting is missing and is not backed-up.

4. The date/time group is erroneous and has not been corrected.

5. Unreliable (intermittent) or inaccurate (erroneous) elements.

NOTE-

Unreliable or inaccurate visibility, temperature, and dew point will affect present weather information type and intensity reporting (i.e., rain, snow) within the system and must be included in the NOTAM.

6. Commissioning or decommissioning of weather reporting. When commissioning an automated system that has a frequency/telephone number, include that information in the NOTAM. When decommissioning an automated system, unserviceable (U/S) with a PERM validity end date must be stated as the condition.

7. The broadcast frequency of the automated weather system is inoperative, or has returned to service.

NOTE-

When reporting a failure or unavailability of weather reporting, do not specify the system nomenclature.

d. Juneau Airport Wind Service is a wind warning system which provides turbulence alerts based on real-time wind information from anemometers and wind profilers around hazardous terrain.

5-5-5. MICROBURST/WINDSHEAR DETECTION SYSTEM

Technical Operations personnel must ensure the origination of NOTAM D concerning microburst/windshear detection systems, such as low-level windshear alert system, Terminal Doppler Weather Radar and weather system processor.

5-5-6. RADAR SERVICES

The Technical Operations personnel must ensure the origination of NOTAM D concerning radar outages of 30 minutes or more. List the service restrictions with reference to the nearest NAVAID.

a. Radar services for terminal facilities are described using the following terminology. Location identifiers used for the issuance of NOTAMs for terminal facilities must be the airport identifier.

TBL 5-5-1
Types of Radar

SSR (secondary surveillance radar)	SMR (surface movement radar)	TAR (terminal area surveillance radar)
GCA (ground control approach)	PAR (precision approach radar)	PRECISION RWY MNT No contraction


b. The contraction phrase “RADAR SER” must not be used. When describing the radar service, do not use the model number.

Chapter 6. Airspace NOTAMs

Section 1. Airspace

6-1-1. AIRSPACE NOTAM FORMAT

FIG 6-1-1
Airspace



...AIRSPACE CRYPT NORTH MOA AND REVELLE MOA ACT 5000FT-16000FT...

- a. NOTAMs originated for Airspace items will be formatted following 4-2-1 b 1-2, including:
 1. Location identifier.
 - (a) Use nearest public use airport when the full activity is completely within a 5 NM radius of the airport.
 - (b) Use nearest VOR when any of the activity is more than 5 NM from the nearest public use airport but completely within 25 NM radius of a VOR.
 - (c) Use the ARTCC when the activity doesn't fall within either (a) or (b).
 2. Keyword "AIRSPACE."
 3. Description of activity, if needed.
 4. Description of area impacted; for example, the name of a published area, an airport, a nautical mile radius of a latitude/longitude, NAVAID or fix-radial-distance from a VOR-type NAVAID, or an area defined by latitude/longitude or NAVAID. When applicable, preface the description with this standard phrase: "WI AN AREA DEFINED AS..."
 5. Plain Language location, when using all latitude/longitude, except Central Altitude Reservation Function (CARF) and surveillance broadcast systems (SBS)-type NOTAMs. In parentheses, specify using nautical miles...direction...airport (5NM E IAD), or F/R/D from the nearest NAVAID.
 6. Condition.
 7. Lower limit/upper limit; for example, 5000FT-16000FT (as specified in 4-2-1).
 8. Remarks (when needed). Other operational information.
 - (a) When identifying the expected height of a balloon trajectory, express it in FT, 150000FT.
 - (b) Identifying the frequency transmitting on is an acceptable remark.
 - (c) Certificate of Authority, when requested by the proponent.

- 9. Follow 4-2-1 b 13-14 to complete the NOTAM.
- b. If the area impacts more than one ARTCC, originate a NOTAM for each ARTCC.

**TBL 6-1-1
Types of Activity**

AIRSHOW ACFT	AEROBATIC AREA	PJE (Parachute Jumping)
DEMONSTRATION ACFT	HOT AIR BALLOON	UNMANNED FREE BALLOON
UNMANNED ROCKET	UAS (Unmanned Aircraft System)	GLD (Glider)
HANG GLD	LGT OUT TRG (Lights-Out Training)	BALLOON LDG (Landing)
PYROTECHNIC DEMONSTRATION (fireworks)	BLASTING	CONTROLLED BURN
AEROBATIC ACFT	SPACE LAUNCH	SPACE REENTRY

NOTE-

Airspace activities that will require airspace management such as Temporary Flight Restrictions will require the issuance of an FDC NOTAM.

6-1-2. SPECIAL ACTIVITY AIRSPACE (SAA)

A NOTAM must be entered through Special Use Airspace Management System to activate permanent or temporary special use airspace if activated by NOTAM only or at other than published times for those SAA that contain a NOTAM provision in their legal description, under the appropriate ARTCC(s):

- a. SAA, for the purpose of this manual, includes Special Use Airspace (SUA) (restricted area, military operations area (MOA), warning area, and alert area airspace), instrument and visual military training routes, aerial refueling tracks and anchors.

NOTE-

Controlled Firing Area (CFA) does not require a NOTAM as the activity is suspended immediately when a nonparticipating aircraft approaches the area.

REFERENCE-

FAA Order JO 7400.2, Procedures for Handling Airspace Matters.

1. A NOTAM must be in effect to activate SAA at other than published or charted times for those areas that contain a NOTAM provision (“BY NOTAM,” “INTERMITTENT BY NOTAM,” or “OTHER TIMES BY NOTAM”) in their times of use legal description per FAA Order JO 7400.10, Special Use Airspace, Flight Information Publications, and related Government charting products, or if that SAA can only be activated by NOTAM. A NOTAM must not be used to make other changes to the charted lateral dimensions or which would exceed the lower or upper published altitude limits.

2. NOTAMs for SAA activation and cancellation for uncharted and unpublished times must be originated by the appropriate controlling agency, with the overlying ARTCC as the location identifier, using the appropriate accountability of SUA, SUAC and SUAW, corresponding to the FAA service areas, east, central and west, respectively.

- b. Issue the NOTAM in the format described in 6-1-1 above using the following items:

- 1. Accountability = SUA (E, C, W)

2. Location Identifier = ARTCC

3. Condition = ACT (active)

c. Lights Out/Night Vision Goggle Operations in MOAs. Upon notification of a lights out/ Night Vision Goggle operation in an authorized MOA (as listed in FAA exemption 7960 and FAA exemption 3946), issue a NOTAM containing the description of activity information.

d. SUA NOTAMs are originated by the controlling agency, utilizing the SUA Management System. The type of activity included does not restrict movement into or out of the airspace. TFRs restrict movement. This is an advisory about unusual activity within the airspace. Do not use this to report increased flight movement.

6-1-3. AIRSPACE AND ALTITUDE RESERVATIONS

a. Central Altitude Reservation Function (CARF) airspace and altitude reservation NOTAMs must be transmitted by the USNOF, after receipt of the proposed NOTAM from the CARF office or ARTCC. The information will be stored in the NS database and available for request/reply. If the altitude reservation affects international airspace, it will be sent and stored as an international NOTAM.

NOTE-

Commercial space operations are examples of activity permitted in ALTRVs within oceanic and offshore airspace

b. Issue the NOTAM in the format described in 6-1-1 above using the following items:

1. Accountability = CARF Location identifier

2. Location Identifier = ARTCC

3. Description of Activity = STNR ALT RESERVATION

c. Airspace and Altitude reservation involving a single ARTCC.

d. Missile firing and offshore airspace reservations. ARTCCs must issue as a NOTAM missile firing exercises and offshore airspace reservations. These NOTAMs must be transmitted as an international NOTAM to the USNOF.

e. Weather Reconnaissance Area (WRA). A WRA is established to support weather reconnaissance/research flights. ARTCCs must use the CARF accountability location identifier when issuing NOTAMs for a WRA.

6-1-4. SPECIAL AERIAL REFUELING

a. Where published tracks/anchors are inadequate for special mission/sortie, special track/anchor may be established. Special tracks/anchors must not be published in the DOD Flight Information Publications (FLIP) Planning document but may be described in Letters of Agreement.

b. NOTAM Ds will be used for special refueling tracks/anchors outside Class A airspace so as to define the refueling area as specifically as mission security will allow.

c. Issue the NOTAM in the format described in 6-1-1a above with:

1. Description of Activity = SPECIAL AERIAL REFUELING TRACK/ANCHOR

2. Condition = "ACT"

REFERENCE-

FAA Order JO 7610.14, Para 5-6-6, Special Exercises.

FAA Order JO 7610.14, Para 5-6-7, Issue NOTAM.

6-1-5. AIRSPACE NOTAM REQUIRING AUTHORIZATION/WAIVER

a. When required, originate an airspace activity NOTAM only for the time period the activity is taking place. When the activity is expected to be temporary but of long duration (more than three months) or permanent, the

information must be published in the appropriate chart/publication. Once the information is published, the NOTAM must be canceled unless required by a Certificate of Waiver or Authorization from Title 14, Code of Federal Regulations (CFR) issued by the FAA.

b. FAA Authorization will consist of an approved waiver/authorization to 14 CFR. Upon receipt of appropriate notification/authorization, but not more than 7 days prior to the event, originate an AIRSPACE NOTAM using the format described in 6–1–1a above, ensuring not to advertise published or charted data and information.

c. Ensure the NOTAM originator is aware that authorizations, waivers, and/or air traffic notifications may be required by the proponent, and the proponent's information is not released in the NOTAM but must be made available immediately upon request to ATO and other entities responsible for airspace deconfliction for the following activities:

1. Airshows, aerial demonstrations, aerobatic areas, hot air balloon events, flight test areas, light out training, banner towing.

(a) FAA authorization will consist of a waiver to 14 CFR part 91.

(b) Obtain the following information from the requestor:

(1) Name, address, and telephone number of the person giving notice.

(2) Identification and type of the aircraft to be used.

2. Moored balloons, kites, amateur rockets, unmanned free balloons.

(a) FAA authorization will consist of a waiver to 14 CFR part 101.

(b) Obtain the following information from the requestor: Name, address, and telephone number of the person requesting authorization or giving notice.

NOTE–

Unmanned rocket activities that will require airspace management such as Temporary Flight Restrictions will require the issuance of an FDC NOTAM.

3. Parachute Jumping/Sky Diving

(a) FAA authorization/air traffic notification will be required under 14 CFR part 105.

(b) Obtain the following information from the requestor

(1) Name, address, and telephone number of the person requesting authorization or giving notice.

(2) Identification of the aircraft to be used

4. Unmanned Aircraft Operations

(a) FAA authorization will consist of a Certificate of Authorization, Certificate of Waiver or an Airspace Authorization documented on an FAA Form 7711–1–Certificate of Waiver or Authorization.

(b) NOTAM is not required for UAS operations, unless specifically stated on the FAA Form 7711–1 – Certificate of Waiver or Authorization, Special Airworthiness, or similar document.

(c) In general, a NOTAM is not required for UAS operations in Class A airspace.

(d) In general, a NOTAM is not required for UAS operating as follows:

(1) at or below 400' above ground level (AGL), in Class G airspace, or at or below the established UAS facility map altitudes in Class B, C, D and E surface area, and

(2) UAS weighs less than 55 lbs., and

(3) remaining within visual line of sight, and

(4) have a maximum airspeed of 100 mph (87 knots) or less.

6-1-6. SURFACE AREA AIRSPACE

Originate an AIRSPACE NOTAM using the format described in 6-1-1a above.

a. A NOTAM D may be originated for permanent changes to part time surface area hours of operation only, under the following conditions:

1. The change in the surface area hours of operation is due to other than seasonal daylight time changes.
2. Only those surface areas identified as part time in the airspace section of the U.S. Chart Supplement as part time are subject to change by NOTAM. A continuous surface area "hours of operation" is changed only through rulemaking action.
3. The change in the surface area hours of operation will thereafter be continuously published in the U.S. flight information publication, Chart Supplement Alaska, Chart Supplement Pacific, or the Chart Supplement U.S.

NOTE-

NOTAM specifying or changing the dates and times of a designated part time surface area must coincide with issuance of a corresponding Hours of Operation Services NOTAM and may be issued by the appropriate facility only after coordination with the regional/service area office.


b. For temporary changes to published part time surface area hours of operation, issue a Services NOTAM (SVC) in accordance with paragraph 5-5-3, Hours of Operation. Do not issue an Airspace NOTAM.

6-1-7. AREA IMPACTED TABLES

The graphs below depict the commonly used airspace areas.


a. Polygon. Points defining lateral limits of an area must be enumerated in clockwise order. The last and the first points of the list must be the same (TO POINT OF ORIGIN). Latitude/longitude must be followed by plain language location between parentheses.

FIG 6-1-2
Polygon




b. Circle. Define a circular shape as “*WI AN AREA DEFINED AS XNM RADIUS*” followed by the location of the center of the circle

FIG 6-1-3
Circle



c. Corridor. A corridor is a type of polygon defined by a line between points and a lateral distance on either side of the line. The lateral limits are at the end points connected by arcs of circle.

FIG 6-1-4
Corridor



Chapter 7. FDC NOTAMs

Section 1. Transmitting FDC NOTAM Data

7-1-1. GENERAL

FDC NOTAMs refer to information that is normally regulatory in nature and includes, but is not limited to, the following:

a. Interim IFR flight procedures.

1. Air traffic service route changes.

2. Instrument flight procedure changes to include special instrument flight procedures, Standard Instrument Approach Procedures (SIAP), textual and graphic Obstacle Departure Procedures (ODP), Standard Instrument Departures (SID), and Standard Terminal Arrivals (STAR). Refer to FAA Order 8260.19, Flight Procedures and Airspace, for policy guidance and procedures for the issuance, tracking, and cancellation of FDC NOTAMs relating to instrument flight procedures.

3. Airspace changes in general. For FDC NOTAMs that are generated due to unforeseen events, use keyword/title "AIRSPACE...NOTICE".

b. Temporary flight restrictions.

1. Unmanned aircraft over large public gatherings.

2. Disaster/hazard areas.

3. Hijacking.

4. Aerial demonstrations.

5. Space flight operations.

6. Flight restrictions in the proximity of the President and other parties.

NOTE-

Presidential aircraft includes the aircraft and the entourage of the President, the Vice President, or other public figures designated by the White House.

REFERENCE-

FAA Order JO 7210.3, Chapter 5, Section 1, Presidential Aircraft.

c. 14 CFR Part 139 certificated airport condition changes.

d. Air defense emergencies.

e. Emergency flight rules

f. Substitute airway routes.

g. Special data.

h. U.S. Government charting corrections

i. Laser activity.

7-1-2. TEMPORARY OR PERMANENT FDC NOTAMs

a. Instrument flight procedure FDC NOTAMs may, at the direction of the Aeronautical Information Services and Flight Inspection Services Group personnel, be used for either temporary or permanent conditions.

b. NOTAMS for temporary conditions must be identified by the addition of “EST” following the expiration date/time group. NOTAMS for permanent conditions must be identified by inserting “PERM” in lieu of an expiration date/time group.

c. FDC NOTAMS of a permanent nature, relating to instrument approach and obstacle departure procedures and airways, must remain current until published in the Terminal Procedures Publication or applicable en route chart.

7-1-3. INSTRUMENT IFR FLIGHT PROCEDURES

a. Instrument Flight Procedure (IFP) NOTAM. Changes to IFPs that have been charted and distributed, are processed as FDC NOTAMS and issued through the NS. Procedural NOTAMS are originated by FAA Flight Operations and FAA Flight Inspection and Procedures personnel. When these revisions cannot be published in advance of their effective date, the NOTAM is transmitted as an FDC NOTAM. The applicable keyword (ODP, SID, STAR, CHART, DATA, IAP, VFP, ROUTE, or SPECIAL) will be included immediately following the location identifier designator.

NOTE-

The USNOF is responsible for Quality Control on Interim IFR Flight Procedure NOTAMS.

1. Procedural minimums must not be lowered by NOTAM unless fully justified as a safety of flight issue or after returning the minimums to their previously published level at the end of the NOTAM.

2. Both temporary and permanent conditions may be promulgated via an FDC NOTAM at the direction of AIS.

b. Temporary conditions. NOTAMS for temporary conditions whose expiration time is uncertain and approximate, must be identified by the addition of “EST” following the NOTAM date/time group. The “EST” suffix may be used with all IFP temporary NOTAMS.

1. When it is known that the condition requiring a PERM NOTAM will be effective for more than four chart cycles (224 days), a procedure amendment [revised 8260-series form] or PERM NOTAM must be submitted as soon as possible to allow publication of the change within the 224-day timeframe.

2. When the timeframe for temporary conditions requiring NOTAM action is unknown or cannot be determined and the condition is beyond the control of the NOTAM issuing authority; e.g., airport construction, NAVAID restrictions, temporary obstructions, etc., the NOTAM issuing authority will ensure the line of business (LOB) approving the temporary condition is advised (copy the Flight Technologies and Procedures Division, AFS-400) of the procedural impact and the necessity of reconciling the condition as soon as possible so the temporary NOTAM can be canceled within the 224-day timeframe.

3. If the condition cannot be corrected within 224 days, the NOTAM issuing authority must obtain Flight Standards approval from AFS-400 for the NOTAM to remain in effect beyond the 224-day limitation. *It is important that NOTAMS not be allowed to remain active for excessive periods of time; therefore, an FDC IFP NOTAM must not be canceled and re-issued without Flight Standards approval.*

NOTE-

Requests for Flight Standards approval must be coordinated with AFS-400 as soon as the requirement is known. For example, it is known that a temporary crane affecting an IFP(s) will be in place for 10 months as soon as it is erected; therefore, forward the approval request for extension immediately.

c. Permanent conditions. When the condition requiring NOTAM action is known to be permanent or is expected to be effective for more than four charting cycles (224 days), a permanent NOTAM is used to promulgate amended SIAPs and textual ODPs as well as correction information for U.S. Government aeronautical charts.

1. Identify permanent NOTAMS by inserting “PERM,” meaning the condition is permanent, instead of an actual date/time group. Procedural amendments may be charted from the permanent NOTAM information and may also be used as a substitute for the abbreviated amendment process within the limitations specified in Order 8260.19.

2. IFP permanent NOTAMs contain information that is complete for charting purposes and are promulgated in the bi-weekly Transmittal Letter (TL) with a specified procedure amendment date that is coincidental with an international Aeronautical Information Regulation and Control (AIRAC) charting date.

3. Permanent NOTAMs may only be used for SIAPs, textual ODPs, and to correct U.S. Government charting printing and compilation errors. Permanent NOTAMs must *not* be used for changes to Special IFPs, ATS routes, graphic ODPs, SIDs, and STARs.

4. Permanent NOTAMs may be used to amend procedures without a complete review of the procedure. The amendment will be indicated by an alphanumeric identifier; e.g., Orig-A, Amdt 3B, Amdt 4C, etc.

5. Only one procedure may be addressed per PERM NOTAM except that a single PERM NOTAM may be used for ILS CAT I/II/III and SA CAT I/II procedures to the same runway. A single PERM NOTAM may also address multiple procedures at a single location when correcting a common printing error on U.S. Government charts.

6. A hard/electronic copy of each PERM NOTAM must be stored with the current amendment and maintained with the procedure filed by AIS specialists.

7. PERM NOTAMs must not be used for RNAV/database driven procedures when the change(s) will affect waypoint coordinates, course (track), distances, or bearings.

8. The PERM NOTAM originator must coordinate a procedure amendment date with AIS for inclusion in the Transmittal Letter. This will ensure that all charting agencies publish the amended procedure on the same AIRAC chart cycle and with the same procedure amendment date.

9. Each AIRAC cycle is limited to no more than 150 PERM NOTAMs, except for Flight Standards directed safety initiatives or national implementation processes. Whenever the 150 PERM NOTAM limit must be exceeded, AIS is responsible for coordinating with other charting agencies (for example, Jeppesen, LIDO) to ensure they can accommodate the necessary changes on the required AIRAC date.

10. PERM NOTAMs must be canceled when the applicable procedural change has been published.

11. When a PERM NOTAM is originated to permanently amend a SIAP or textual ODP, “PERM” must be inserted as the expiration date in lieu of a 10-digit date-time group. The NOTAM originator is responsible for canceling the NOTAM upon publication.

12. A NOTAM will auto-expire at the expiration DTG unless “PERM” is used.

d. NOTAM Procedures:

The applicable keyword (ODP, SID, STAR, CHART, DATA, IAP, VFP, ROUTE, DVA, or SPECIAL) will be included immediately following the location identifier designator.

1. Standard instrument approach procedure and special instrument flight procedure format:

(a) For SIDs and STARs serving multiple airports, a separate FDC NOTAM must be prepared for each airport affected by the procedure. Permanent NOTAMs must not be used as a source to effect charting changes for these procedures. Procedural NOTAMs are originated by FAA Flight Operations and FAA Flight Inspection and Procedures personnel and are transmitted to the NS. When these revisions cannot be published in advance of their effective date, the NOTAM is transmitted as an FDC NOTAM.

(b) Permanent procedural changes to graphic ODPs and SIDs must be made via a new or amended 8260-15 series form [see 8260-17 series forms for STARs] within 224 days of the issuance of the associated NOTAM.

2. Form 8260-17.1, Standard Terminal Arrival [and Form 8260-17.2, STAR (Data Record) for PBN STARs] must be submitted for permanent charting changes. NOTAM on STARs must not exceed 224 days.

e. Instrument Flight Procedure NOTAMs. A complete review and a new amendment are the preferred methodology for permanent procedure changes, particularly when applying new or revised Order 8260.3 criteria.

However, it is recognized that this may not always be possible due to time constraints, workload, staffing level, etc. Abbreviated 8260-series forms and/or PERM NOTAMs have proven to be an effective means of updating aeronautical charts and amending instrument flight procedures within the following guidelines:

1. Whenever the need for a NOTAM to a procedure arises, AIS, or the non-FAA service provider must review the procedure and ascertain that there is no other safety of flight changes required. If a PERM NOTAM is required to amend a SIAP or textual ODP for safety reasons, other items may be included in the NOTAM to simultaneously update procedure charts.

2. Procedural minimums must not be lowered by NOTAM except when returning minimums to their previously published level at the end of a temporary condition. Refer to Order 8260.19, *Flight Procedures and Airspace*, chapter 8, for conditions pertaining to IFP NOTAMs when amending an instrument flight procedure.

3. Exercise caution in initiating or adding a NOTAM to a procedure when there is already a current NOTAM in effect for the procedure. In many cases close follow-up action, including canceling and reissuing NOTAMs, will be necessary to ensure there is no confusion for pilots and chart producers. All FDC NOTAMs must be issued against the *currently published* procedure.

4. When a NOTAM D is issued closing an airport permanently, an FDC NOTAM need not be issued denying use of an IFP. A routine procedure cancellation should be processed.

5. When a NOTAM D is issued to shut down a facility permanently, only routine cancellations of procedures predicated on that facility are required. FDC NOTAMs may be required for other procedures supported by the affected facility.

6. When a NOTAM D is issued closing a runway, an FDC NOTAM need not be issued denying approach or departure minimums to that runway. If the closing is permanent, routine procedure cancellations, including takeoff/departure procedures, must be processed immediately.

7. When a NOTAM D is issued for a facility shutdown or outage, an FDC NOTAM denying IFP use is not required for those IFPs using only that facility. However, other IFPs in the vicinity must be reviewed to determine if that facility supports courses or fixes; in such cases, those IFPs require an FDC NOTAM. Particular attention must be given to fixes supporting stepdown minimums and missed approach procedures, which are predicated on the out of service facility. It is not necessary to issue NOTAMs for fixes and terminal route segments that are related to unusable airway segments from the subject facility. Do not issue "Radar Required" NOTAMs on unusable or restricted ATS route segments. Also, see Order 8260.19, paragraph 4-3-3, for ILS CAT II/III NOTAM restrictions.

8. When a NOTAM D removes a localizer from service, the ILS approach is unusable. If the glide slope (GS) is out, the precision approach is unusable. If other ILS components are out, the inoperative table applies. In these instances, an FDC NOTAM for the ILS approach is not required.

9. When Final Approach Segment (FAS) data problems are reported and LPV minimums must be restricted, also restrict use of the WAAS VNAV. The NOTAM must read: "LPV MINIMUMS AND WAAS VNAV NA."

NOTE-

Some avionics use the LPV FAS data information to establish the glideslope for the LNAV/VNAV. Baro VNAV is not affected.

f. Chart correction NOTAMs. FDC NOTAMs to correct U.S. Government chart printing or compilation errors are issued by AIS. If the NOTAM is used to correct an IFP, specify the location identifier of the airport affected by the procedure, the full procedure title and amendment number (if applicable). If the NOTAM is used to correct a chart; e.g., VFR sectional chart, IFR enroute chart, etc., use "FDC" as the location identifier. The first word in the NOTAM text should be "correct."

g. RNAV substitution. Properly equipped aircraft may substitute RNAV systems for inoperative ground NAVAIDs; however, RNAV systems must not be substituted for NAVAIDs providing final approach course guidance on instrument approach procedures.

1. When the use of an instrument approach procedure, departure procedure (SID or ODP), or STAR is restricted or prohibited by NOTAM because of a NAVAID (VOR, TACAN, NDB, compass locator, or DME)

outage, the NOTAM does not apply to aircraft equipped with suitable global positioning system (GPS) RNAV. For clarification, state the reason for the restriction in the text of the procedural FDC NOTAM.

2. In certain circumstances, AFS-400 may determine that the use of RNAV systems that utilize DME/DME/inertial reference unit (IRU) inputs should be allowed [see Order 8260.19, paragraph 4-6-9, for additional information/requirements]. In these instances, AFS-400 will advise AIS by e-mail or memorandum to insert the phrase “OR DME/DME/IRU” after “SUITABLE RNAV SYSTEM WITH GPS.” Include in the NOTAM any required DME facilities, as provided by AFS-400 to support DME/DME/IRU operations.

h. Air Traffic Service Route NOTAMs. Under 14 CFR part 71.13, the term “ATS route” refers to a variety of routes, including airways, jet routes, and PBN routes. When a restriction or a change to an ATS route requires a NOTAM, AIS must prepare and forward a temporary FDC NOTAM following the procedures in paragraph 7-1-3b.

1. ATS Route changes involving a single state and one or more ARTCCs must be issued with the ARTCC identifier followed by the two-letter state code. The two-letter state code must also follow all NAVAID and fix designators.

2. If the ATS Route NOTAM affects one, two, or three ARTCCs and multiple states, issue a separate NOTAM for each affected ARTCC. Do not include two-letter state codes if more than one state is involved.

3. If the NOTAM affects four or more ARTCCs, send one NOTAM using “FDC” as the facility identifier.

4. If the restriction will exceed the 224-day time limit, a procedure amendment (revised 8250-series form or PERM NOTAM) must be submitted as soon as possible to allow publication of the change within the 224-day timeframe.

i. FDC NOTAMs for Special Instrument Approach Procedures (Specials). A Temporary FDC NOTAM may also be used to promulgate safety of flight information relating to Specials provided the location has a valid landing area identifier and is serviced by the NS.

1. If the Special is maintained by AIS or a non-FAA service provider and the location is in the NS, then procedures for NOTAM processing will be similar to the procedures used for public, 14 CFR part 97 instrument approach procedures. When preparing the NOTAM for submission, include the keyword “Special” immediately following the three or four character location identifier. (!FDC PAJN SPECIAL)

2. AIS/non-FAA service providers will notify the Regional NextGen Branch (RNGB) as soon as practicable when a NOTAM has been issued.

NOTE-

For AIS maintained procedures, after duty hours, contact the stand-by AIS representative at (405) 954 8260.

3. If the Special procedure location is not in the NS, whoever is responsible for maintaining the procedure will notify the applicable RNGB of the change/outage. The RNGB must contact the user(s) of the procedure to disseminate appropriate action; (e.g., NA the procedure, raise applicable minimums, etc.)

4. Non-FAA service providers must notify Flight Inspection Services of the change/outage if flight inspection is responsible for conducting flight inspection/validation activities.

j. NOTAM content.

1. FDC SIAP and textual departure NOTAMs must identify the procedure being amended and the current amendment number. NOTAMs for graphic ODPs, SIDs, and STARs must reflect the current procedure identification, including number. The NOTAM must be as concise as possible.

2. The issuing authority must prepare the NOTAM using plain language text and those contractions found in Order JO 7340.2 and those contractions and abbreviations used on IFP charts. Specialists must keep in mind that the NOTAM is directed to the pilot, and should be worded so that the intended change will not be misinterpreted. Avoid the use of internal cartographic instructions that have no meaning to pilots. Spell out NAVAID names in clear text followed by the identifier. If it appears that the NOTAM length will exceed 20 lines, call the USNOF at (888)-876-6826 for assistance and guidance.

3. For temporary obstructions, include the type, elevation, distance, and direction from the airport or runway threshold, as appropriate, as the last line of the NOTAM text. Do not preface this information with “Chart”

4. Include a reason for the NOTAM following the NOTAM text. This information will not be transmitted as a part of the NOTAM text, but will inform the NFDC and the USNOF of the basis for the NOTAM. It will also ensure the data is retained in the NOTAM historical files.

7-1-4. HIGH BAROMETRIC PRESSURE WARNING

When requested by the affected area Air Route Traffic Control Center (ARTCC), the USNOF will ensure an FDC NOTAM is issued.

REFERENCE-

14 CFR § 91.144.

FAA Order JO 7110.10, Flight Services, Chapter 4.

7-1-5. TEMPORARY FLIGHT RESTRICTIONS

a. Through system interface, the NOTAM requestor must forward the NOTAM information directly to the USNOF for FDC NOTAM issuance. The NS disseminates the FDC NOTAM for coordination purposes, and to FSS and external providers of pilot informational briefings. The NOTAM must follow subparagraph 4-2-1b1-2, including:

1. ARTCC designator/location (mandatory) followed by the state(s) abbreviation; for example: ZDC VA.
2. Keyword “AIRSPACE.”
3. City/Location(s), State(s) for each area; for example: Detroit, MI Ann Arbor, MI.; Beale AFB, CA.; Libby AAF, AZ.; Hibbing, MN.; Fargo, ND.
4. Description of activity: “TEMPORARY FLIGHT RESTRICTIONS.”
5. Plain language effective date; for example, February 26, 2014 LOCAL (applicable to 14 CFR Sections 91.141 and 99.7 only).
6. The phrase beginning with, “PURSUANT TO...” for the following:
 - (a) For unmanned aircraft over large public gatherings. “PURSUANT TO 49 U.S.C. SECTION 44812 AS AMENDED BY SECTION 935 OF THE FAA REAUTHORIZATION ACT OF 2024 FOR PROTECTION OF LARGE PUBLIC GATHERINGS.”
 - (b) Include the phrase as required for 14 CFR sections 91.141 and 99.7: “PURSUANT TO 49 USC (section)...”.
 - (c) For 14 CFR sections 91.137, 91.141, 91.143, 91.145, and 99.7: “PURSUANT TO TITLE 14 CFR SECTION 9X.XXX...(the appropriate paragraph and subparagraph number) (plain language text, as needed).
7. Description of area or areas impacted; each area will contain:
 - (a) Stated as “WI AN AREA DEFINED AS...” and if appropriate “...TO POINT OF ORIGIN.” The area is defined as a nautical mile radius of a latitude/longitude. Include an alternate description as a fix/radial/distance in parentheses to help clarify the location. For example, ...285039N0800500W (MLB040053)...
 - (b) Lower limit then upper limit, or height, (when needed). Limits must be specified, as:
 - (1) For SFC, or 1 to 17,999 feet, include the unit of measurement (FT), for example 1275FT.
 - (2) For 18,000FT and above, express in flight levels (FL), FL180, FL250, FL850, or UNL (altitudes greater than 99,900).
 - (3) When referencing heights above ground level, include the reference indication label (AGL) after the stated altitude in the NOTAM (for example, 4000FT AGL).

(c) Schedule of individual area, if needed. For example, EFFECTIVE YY02271900 (1400 LOCAL 2/27/YY) UNTIL YY02280200 (2100 LOCAL 2/27/YY). If a daily (or MON WED FRI) time is required, DLY 1900–0200 (1400–2100 LOCAL).

NOTE–

Repeat 7 (a)–(c), as necessary, for each defined area.

8. Reason or purpose (when needed).

9. The FAA coordination facility and commercial telephone number.

10. Remarks (when needed). Include other information that is required or considered to be important to the pilot. Do not use the 1–800–WX–BRIEF telephone number for the flight service stations.

11. Start of Activity/End of Validity.

b. Flight restrictions in the proximity of the President or other parties (14 CFR Section 91.141) or Special Security Instructions (14 CFR Section 99.7) will be issued by System Operations Services, System Operations Security, and System Operations Support Center (SOSC). Operational requirements may necessitate a change in format to Presidential and Special Security Instructions TFRs at any time.

1. Multiple areas may be specified in one NOTAM when the areas are in the same ARTCC airspace.

2. The requirement for one effective period per NOTAM is waived for NOTAMs advertising flight restrictions in the proximity of the President or other parties. See paragraph 4–1–1.

7–1–6. AIR DEFENSE EMERGENCY

When an air defense emergency is declared and Emergency Security Control of Air Traffic (ESCAT) has been implemented, an FDC NOTAM will be issued in accordance with procedures in FAA Order JO 7610.4, Sensitive Procedures and Requirements for Special Operations, Chapter 6, Emergency Security Control of Air Traffic. NOTAMs advertising an air defense emergency must use accountability FDC, location identifier FDC, and be preceded by keyword “SECURITY.”

REFERENCE–

*FAA Order JO 7610.4, Chapter 6, Emergency Security Control of Air Traffic (ESCAT).
AC 99–1, Emergency Security Control of Air Traffic (ESCAT).*

7–1–7. SPECIAL DATA

When special data NOTAMs must be issued (for example, Department of State information and special air traffic programs for national security, aviation security, and law enforcement, etc.), an FDC NOTAM is issued by the USNOF using the keyword “SECURITY.” Issue the NOTAM with PERM instead of a cancellation date and cancel the NOTAM only at the request of the originating office, System Operations Security.

NOTE–

See information on use of the System Operations Security KICZ Accountability/Location Code for United States International Security NOTAMs in Chapter 8.

7–1–8. LASER LIGHT ACTIVITY

The service area office where the laser activity will occur must enter the NOTAM via an approved direct entry tool or interface within 7 days of a proposed activity. Additionally, service area offices, when coordinated with their respective ATC facilities, may delegate notification responsibility. The USNOF will transmit the appropriate FDC NOTAM. If the event is canceled prior to the scheduled ending date/time, the service area office or their designee must notify the USNOF to cancel the NOTAM.

REFERENCE–

FAA Order JO 7400.2, Procedures for Handling Airspace Matters.

Follow 4–2–1b1–2, including:

- a. ARTCC designator (mandatory) followed by the state abbreviation.
- b. Keyword “AIRSPACE.”
- c. City/state.
- d. Description of activity; for example, “LASER LGT ACT.”
- e. Description of area impacted; describe the area using radius and latitude/longitude.
- f. Alternate description. In parentheses, specify area impacted in reference to a fix/radial/DME.
- g. Altitudes impacted. Must include lower limit and upper limit.
- h. Follow 4-2-1b11-14 to complete the NOTAM.

7-1-9. FDC NOTAM LIST

a. The NS transmits a list of FDC NOTAM numbers issued during the previous 24 hours. The NS transmits the list between 1715 and 1745 UTC.

7-1-10. RETRIEVING FDC NOTAMs

Upon issuance, all FDC NOTAMs are given all circuit distribution and are stored in the NS. See Appendix E for further information.

Section 2. Cancellation/Expiration

7-2-1. FDC NOTAM EXPIRATION/CANCELLATION

a. The FDC NOTAM originator is responsible for canceling FDC NOTAM prior to end of validity; otherwise, the NOTAM cancellation is automatically processed.

b. When a new FDC NOTAM is issued to correct or in any way change a previously issued FDC NOTAM, a new NOTAM will be issued and the previous NOTAM will be canceled. ■

Chapter 8. International NOTAMs

Section 1. General Procedures

8-1-1. INTERNATIONAL NOTAMs

a. Appendix B, International NOTAM (Q) Codes, contains the NOTAM codes used for international NOTAMs.

b. International NOTAM offices that provide NOTAMs to the U.S. NOTAM office are listed in ICAO DOC 7383.

c. International NOTAMs transmitted and received by the U.S. NOTAM Office are stored in the NS, and while current, may be retrieved by both Aeronautical Fixed Telecommunication Network subscribers and FAA facilities via request/reply. All facilities must use their particular equipment's keyboard equivalent of the closed parenthesis or the equal symbol as appropriate.


d. The USNOF issues international NOTAMs concerning the GPS systems as well as certain special activity airspace for ARTCCs; that is, ARTCC and CARF altitude reservations (ALTRVs) and warning areas. Warning areas and ALTRVs are filed under the associated ARTCC ICAO location indicator (KZBW, KZHU, KZJX, KZLA, KZMA, KZNY, KZOA, KZSE, KZWY, KZAK, PAZN, PAZA, PHZH, or TJZS). Information concerning permanent, long-term general data and selected foreign advisories are stored under KFDC location indicator. GPS information is stored under KNMH.

e. United States International Security NOTAMs are issued under the accountability/location identifier of "KICZ" by the USNOF, using the keyword "SECURITY" in item E) of the international NOTAM based on need by the requesting office, System Operations Security. Issue the NOTAM with PERM instead of a cancellation date and cancel the NOTAM only at the request of the originating office, System Operations Security.

8-1-2. INTERNATIONAL NOTAM DATA FORMAT

a. The format of international NOTAMs is shown in TBL 8-1-1.

TBL 8-1-1
International NOTAM Format

**NOTE-**

NOTAMR (NOTAM replacement) and NOTAMC (NOTAM cancellation) are valid contractions and will be followed by another NOTAM number that is being replaced or canceled.

b. The following guidance relates to the body of the NOTAM. The NOTAM content is captured in an organized compilation of specific mandatory and optional fields. Each field has a specific place in the ICAO NOTAM format. The fields are:

1. Item Q) – Encoded specific information about the NOTAM.
2. Item A) – List of flight information regions or the aerodrome impacted by the NOTAM information.
3. Item B) – Effective date/time.
4. Item C) – Expiration date/time.
5. Item D) – Schedule (optional).
6. Item E) – Plain text description of the information.
7. Item F) – Lower altitude limit (used with Airspace NOTAMs).
8. Item G) – Upper altitude limit (used with Airspace NOTAMs).

Section 2. Procedures For Canadian NOTAMs

8-2-1. REQUEST FOR CANADIAN NOTAMs FROM THE CANADIAN NOTAM SYSTEM

a. The NS receives NOTAM data from Canada. The NS cannot confirm that they have all NOTAM data; therefore, you are urged to visit the Canadian Website for the most current and up-to-date NOTAM data. ■

NOTE-

Altitude reservations will be input by Canada utilizing FIR ACCOUNTABILITIES.

NOTE-

Refer to current Canadian charts and flight information publications for information within Canadian airspace. ■

TBL 8-2-1

FIRs

EDMONTON	CZEG	GANDER	CZQX
MONCTON	CZQM	MONTREAL	CZUL
TORONTO	CZYZ	VANCOUVER	CZVR
WINNIPEG	CZWG		

b. Canadian NOTAMs are available via the NADIN (NMR) system from the Canadian NOTAM System Computer for automated retrieval.

Appendix A. Examples

Not all components of the NAS will be illustrated with an example, which are aids to support policy. The examples throughout Appendix A contain the keyword and the subject of the NOTAM. All other data is assumed from the NOTAM sentence structure and is eliminated from examples. Refer to the specific chapter for policy.

5-1-2. HANDLING REPORTED AERODROME CONDITIONS

5-1-2 b.

EXAMPLE-

/CLE CLE TWYL UNSAFE BREAKS IN ASPH YYMMDDHHMM –YYMMDDHHMM

NOTE-

As this is the first example, all elements are shown. Subsequent examples will begin with keyword and end prior to the schedule, unless it is deemed helpful for clarity.

...RWY 16/34 UNSAFE DISABLED ACFT SE END...

NOTE-

Only airport management can close any portion of an airport.

REFERENCE-

14 CFR Part 139

5-1-2 c.

EXAMPLE-

...(U) RWY 07/25 UNSAFE ABANDONED VEHICLE...

5-1-3. MOVEMENT AREA

a. Aerodrome conditions

EXAMPLES-

...AD AP CLSD...

...AD AP CLSD TO TRANSIENT...

...AD AP CLSD EXC SKI...

...AD AP CLSD EXC 1HR PPR...

...AD AP CLSD EXC PPR MON-FRI 0330-1430 YYMMDD0330 – YYMMDD1430

...AD AP CLSD EXC HI-WING ACFT...

...AD HLP CLSD...

...AD SEAPLANE BASE CLSD...

...AD AP OPN...

NOTE-

OPN is only an acceptable condition when the airport is published as being closed.

...AD AP CHANGED TO PRIVATE...

NOTE-

This airport is now closed to the public and is no longer a public-use airport.

...AD AP NOT ATTENDED MAIN TERMINAL CLSD...

NOTE-

The terminal does not meet NOTAM criteria on its own but is allowed as a remark when the airport is not attended.

b. Commissioning

**TBL 5-1-1
Contractions**

Movement Area – Surface:	
ASPH	asphalt/tar/macadam
CONC	concrete
GRVL	gravel/cinders
Movement Area – Lighting:	
LGTD	lighted
NOT LGTD	unlighted

EXAMPLES-

...RWY 01L/19R COMMISSIONED E OF TWY A, 10301FT X 150FT CONC LGTD PCR: 760 R/B/W/T. DECLARED DIST: RWY 01L TORA 10301FT TODA 10301FT ASDA 10301FT LDA 10301FT. RWY 19R TORA 10301FT TODA 10301FT ASDA 10301FT LDA 10301FT. YMMDDHHMM-PERM
...TWY C1 COMMISSIONED WEST OF TWY A BTN TWY A3 AND TWY A4 500FT X 50FT ASPH LGTD PCR70 YMMDDHHMM-PERM

c. Closure of a movement area or portion thereof.

EXAMPLES-

...APRON ALL CLSD...
...APRON NORTH APN E 50FT CLSD...
...TWY A3, A4, A5, TWY A BTN TWY A2 AND TWY A3 CLSD...
...TWY ALL CLSD...
...TWY B, C, D, TWY P BTN TWY EL AND TWY B, TWY P BTN TWY A AND TWY ER, TWY ER BTN RWY 17C/35C AND TWY Q CLSD...
...TWY PARL TWY ADJ RWY 09/27 CLSD...
...TWY PARL TWY CLSD...

NOTE-

- 1. One unnamed parallel taxiway exists at this airport.
 ...RWY 36 CLSD...
 ...RWY 02 FST 1000FT CLSD EXC TAX...*
- 2. The first 1000 feet of runway 02 is closed, except it is available for taxiing aircraft. This is used for single runway only. If both runways were affected, the NOTAM would state 02/20 N 1000FT
 ...RWY 06/24 CLSD EXC 1HR PPR 134.5/303-627-3001...*
- 3. Runways 06 and 24 are closed except by 1-hour prior permission from that frequency/telephone number during the times stated.
 ...APRON NORTH APN CLSD RESURFACING...*

EXAMPLES-

...TWY C CLSD YMMDDHHMM-PERM
...RWY 17/35 CLSD YMMDDHHMM-PERM
...TWY Y BTN TWY Q AND RWY 10/28 NONMOVEMENT AREA...

d. Operational limitations

EXAMPLE-

...RWY 18/36 CLSD TO JET...

NOTE-

Runways 18 and 36 are closed to jet aircraft.

EXAMPLE-

...RWY 09/27 CLSD EXC ACFT MORE THAN 13500LB...

NOTE-

Runways 09 and 27 are closed to all aircraft weighing less than 13,500 pounds. Do not use class of aircraft when closing runways. Always use aircraft weight.

EXAMPLE-

...RWY 10/28 E 3800FT CLSD TO ACFT LESS THAN 12500LB...

NOTE-

Runways 10 and 28 east 3800 feet are closed to all aircraft weighing less than 12,500 pounds.

EXAMPLE-

...RWY 16/34 CLSD TO ACFT WINGSPAN MORE THAN 70FT AND TAIL HGT MORE THAN 49FT...

NOTE-

Runways 16 and 34 are closed to aircraft with a wingspan more than 70 feet and is also closed to aircraft with tail height more than 49 feet.

EXAMPLES-

...RWY 05 CLSD TO LDG...

...RWY 03 CLSD TO TKOF...

...RWY 08/26 CLSD TO TGL...

...RWY 01/19 CLSD EXC XNG...

e. Changes to usable runway length and declared distances**EXAMPLES-**

...RWY 19 THR DISPLACED 300FT MARKING NOT STD. DECLARED DIST: TORA 6827FT TODA 6827FT ASDA 6827FT LDA 6527FT.

...RWY 01 DECLARED DIST: TORA 6827FT TODA 6827FT ASDA 6527FT LDA 6527FT. ...

NOTE-

Runway 19 threshold is displaced 300 feet, therefore the Runway 19 landing LDA is shortened by 300 feet. The LDA and ASDA for Runway 1 are also shortened by 300 feet.

EXAMPLE-

...RWY 05/23 NE 500FT CLSD. DECLARED DIST: RWY 05 TORA 7002FT TODA 7002FT ASDA 7002FT LDA 7002FT. RWY 23 TORA 7002FT TODA 7002FT ASDA 7002FT LDA 7002FT. ...

NOTE-

Construction on Runway 05 requires 500 feet to be closed to protect a construction area thus changing declared distances to Runways 05 and 23.

EXAMPLE-

...RWY 08/26 CHANGED TO 10000FT X 150FT. DECLARED DIST: RWY 08 TORA 9000FT TODA 9500FT ADSA 9000FT LDA 9000FT. RWY 26 TORA 9000FT TODA 9000FT ASDA 9400FT LDA 10000FT....

f. Change of runway identification.**EXAMPLE-**

...RWY 13/31 CHANGED TO RWY 14/32...

NOTE-

Runway 13/31 is permanently changed to this new identify. If the change was temporary, NOW would have been used.

g. Change of traffic pattern.**EXAMPLE-**

...RWY 03L RIGHT TFC PATTERN...

h. Runway Visual Range (RVR).**EXAMPLES-**

...RWY 10 RVRT U/S ...

...AD AP RVR ALL U/S...

i. Surface Markings and Signage**EXAMPLES-**

...AD AP SIGNS OBSC...

...RWY 21 4000FT DIST REMAINING SIGN LGT U/S...

...TWY U7 HLDG PSN SIGN FOR RWY 01L/19R LGT U/S ...

...TWY ALL SFC PAINTED HLDG PSN SIGNS NOT STD (Include plain language description of why signs are not

standard)...

...RWY 01/19 CL MARKING NOT STD (Include plain language description of why marking is not standard)...

j. Other reportable conditions.

EXAMPLES–

...RWY 01/19 3FT SNOWBANKS ADJ...

...APRON MAIN RAMP 6FT SN PILES ADJ E SIDE...

...TWY A NORTH 500FT 3FT SNOWBANKS...

...AD AP SFC COND NOT REP...

...RWY 31C ENGINEERED MATERIAL ARST SYSTEM NOT STD...

...RWY 31C ENGINEERED MATERIAL ARST SYSTEM U/S...

...AD AP CARIBOU NEAR MOV AREAS S OF TERMINAL DLY SS–SR...

...AD AP BIRD ACT INCREASED NW SIDE...

...RWY 02R/20L S 2600FT FROST HEAVES...

...RWY 12/30 NUMEROUS 5IN CRACKS...

...RWY 01/19 SAFETY AREA BTN TWY C AND TWY B IRREGULAR SFC...

...RWY 01/19 SOFT...

NOTE–

1. Runway 01/19 is a turf runway that gets soft during the melting of snow or rainy seasons.

...RWY 06/24 W 1000FT IRREGULAR SFC 4IN DPT X 12IN WID X 24FT LEN...

2. In this example, the irregular surface affects the west 1000ft and is 4 inches deep, 12 inches wide and 24 feet long– within the surface itself. NOTAM format for temporary field conditions (FICON) caused by weather phenomena are covered in paragraph 5–1–4, Reporting of Field Conditions.

5–1–4. FIELD CONDITIONS REPORTING

EXAMPLE–

/LGA LGA RWY 13 FICON 1/1/1 100 PCT WET ICE OBS AT YYMMDDHHMM. COND NOT MNT YYMMDDHHMM – YYMMDDHHMM. YYMMDDHHMM – YYMMDDHHMM

NOTE–

1. Runway 13 is the landing runway and is 95% covered by wet ice but the Runway Condition Code(RwyCC) has been upgraded to a 1 for all of the runway thirds. The field conditions are not monitored from January 4, 2017 0300UTC January 6, 2017 1045UTC. The airport operator expects to have a new NOTAM submitted by January 6, 2017 1115UTC.

2. This will be the only example reflecting times. All FICON NOTAMs have “OBS AT” and start of activity/end of validity times but not all have “COND NOT MNT”.

3. The percentage of coverage described in the note after each example falls within the ranges found in TBL 5–1–4, Percent Coverage of a Contaminant.

EXAMPLE–

...RWY 31 FICON 25 PCT WET ICE...

NOTE–

Runway 31 is the landing runway and has 22% coverage of wet ice. The RwyCC is not displayed because there is $\leq 25\%$ total surface coverage by the contaminant.

EXAMPLE–

...RWY 10 FICON 1/1/1 100 PCT 1/4IN DRY SN AND ICE...

NOTE–

Runway 10 is the landing runway and is completely covered by one–quarter inch of dry snow and ice and the RwyCC was upgraded to one for each third.

EXAMPLE–

...TWY C, C1, C6, TWY D BTN RWY 13/31 AND TWY C FICON 1/2IN DRY SN OVER ICE...

NOTE–

A number of taxiways have one half inch of dry snow over ice. The depth of the contaminant on an apron/ramp is not required when reporting the conditions of airports that are non–part 39 or not federally obligated.

EXAMPLE-

...RWY 16 FICON 1/1/1 75 PCT ICE...

NOTE-

Runway 16 is the landing runway and is 71% covered in ice. The depth of the ice is not reported.

EXAMPLE-

...TWY A FICON PATCHY COMPACTED SN...

NOTE-

Taxiway A has 25% or less coverage of compacted snow. The depth of the compacted snow is not reported.

EXAMPLE-

...RWY 08 FICON 5/5/5 100 PCT 1/8IN WET SN...

NOTE-

Runway 08 is the landing runway and is 97% covered with one eighth inch (3mm) depth or less of wet snow.

EXAMPLE-

...RWY 28 FICON 3/3/3 100 PCT 2IN DRY SN OVER COMPACTED SN...

NOTE-

Runway 28 is the landing runway and is completely covered by two inches of dry snow over compacted snow. The depth of compacted snow is not reported.

EXAMPLE-

...APRON FEDEX FEEDER RAMP FICON 2IN DRY SN...

NOTE-

The FedEx Feeder ramp is covered by two inches of dry snow. The depth of the contaminant on an apron/ramp is not required when reporting the conditions of airports that are non-part 39 or not federally obligated.

EXAMPLE-

...APRON AIR CARGO APN FICON 1IN WET SN...

NOTE-

The Air Cargo apron has one inch of wet snow.

EXAMPLE-

...RWY 34 FICON 5/5/5 100 PCT WET PLOWED 50FT WID REMAINDER 4IN WET SN...

NOTE-

Runway 34 is the landing runway and is wider than fifty feet; the center fifty feet has been plowed leaving the plowed surface completely wet and the remaining surface outside of the plowed area is covered by 4 inches of wet snow.

EXAMPLE-

...RWY 01 FICON 4/4/3 25 PCT COMPACTED SN, 25 PCT COMPACTED SN, 100 PCT 8IN DRY SN SWEPT 75FT WID REMAINDER 8IN DRY SN...

NOTE-

Runway 01 is the landing runway and is one hundred feet wide, the center seventy five feet has been swept. The temperature is -15°C or colder. The first two thirds of the runway have 25% coverage of compacted snow. The final third of the runway is completely covered by eight inches of dry snow. The remaining area of the first two thirds of runway 01 is completely covered by eight inches of dry snow.

EXAMPLE-

...TWY ALL FICON DRY PLOWED 50FT WID REMAINDER 6IN DRY SN...

NOTE-

All taxiways are plowed 50 feet wide and are dry. The part that has not been plowed has 6 inches dry snow.

EXAMPLE-

...RWY 16 FICON 4/4/4 100 PCT COMPACTED SN PLOWED 75FT WID REMAINDER 1/2IN DRY SN OVER COMPACTED SN...

NOTE-

Runway 16 is the landing runway and is wider than seventy five feet; the center 75 feet has been plowed. The temperature is -15°C or colder. The plowed portion is 95% covered by compacted snow. The area that has not been plowed has one half inch dry snow over compacted snow. The depth is not reported for compacted snow.

Snowbanks, Berms**EXAMPLE-**

...RWY 16 FICON 3/3/3 100 PCT COMPACTED SN 12IN SNOWBANKS...

NOTE-

Runway 16 is the landing runway and has been plowed and swept in its entirety; therefore, neither "PLOWED" nor "SWEPT" is used. The temperature is warmer than -15°C. The runway is 100% covered with compacted snow and has 12- inch snowbanks.

EXAMPLE-

...RWY 33 FICON 4/4/4 100 PCT COMPACTED SN PLOWED 100FT WID 24IN BERMS...

NOTE-

Runway 33 is the landing runway and has been plowed 100 feet wide leaving 100% coverage of compacted snow on the runway. The temperature is -15°C or colder. The depth of the compacted snow is not reported, however 24-inch berms are also observed along the edges of the plowed area.

EXAMPLE-

...TWY ALL FICON WET 4FT SNOWBANKS...

NOTE-

All of the taxiways are wet with snowbanks reaching 4 feet in depth off the edge of the paved surface.

Ice Contaminants**EXAMPLE-**

...RWY 01 FICON 1/2/2 100 PCT ICE, 100 PCT 1IN SLUSH, 100 PCT 1IN SLUSH...

NOTE-

Runway 01 is the landing runway and the first third is 92% covered with ice. The remaining two thirds are 100% covered in one inch of slush.

EXAMPLE-

...APRON FEDEX FEEDER RAMP FICON ICE...

NOTE-

The FedEx Feeder Ramp is covered with ice. The depth of ice is not reported.

EXAMPLE-

...RWY 25 FICON 5/5/5 75 PCT WET AND 25 PCT ICE, 100 PCT WET, 100 PCT WET...

NOTE-

Runway 25 is the landing runway and the first third of the runway is 71% percent wet and 21% ice covered. The remaining two thirds of the runway are completely covered by visible moisture, described as "WET."

Wet**EXAMPLE-**

...RWY 10 FICON 5/5/5 100 PCT WET...

NOTE-

Runway 10 is the landing runway and is 100% covered by visible moisture with 1/8 inch (3mm) depth or less of water.

Frost**EXAMPLE-**

...TWY ALL FICON FROST...

NOTE-

Frost is observed completely covering all taxiways.

Slush Contaminants**EXAMPLE-**

...TWY ALL EXC TWY G FICON 3IN SLUSH...

NOTE-

All of the taxiways except taxiway G, are completely covered by three inches of slush. The depth of the contaminant is not required when reporting the conditions of airports that are non-part 139 or not federally obligated.

Drift**EXAMPLE-**

...RWY 03R FICON 3/3/3 100 PCT 4IN DRY SN 9IN DRIFTS...

NOTE-

Runway 03R is the landing runway and is 95% covered with 4 inches of dry snow and 9inch snow drifts.

EXAMPLE-

...RWY 04 FICON 5IN DRIFTS...

NOTE-

Runway 04 is the landing runway and is contaminant free; however, there are five-inch snow drifts on the surface. The term DRIFTS means one or more snow drifts and is not considered a contaminant.

Sanded, as treatment of the surface**EXAMPLE-**

...RWY 36 FICON 1/1/1 100 PCT ICE SANDED...

NOTE-

Runway 36 is the landing runway and is 100% covered by ice and has been treated full length and width with sand. The depth of ice is not reported.

EXAMPLE-

...RWY 11 FICON 5/5/5 100 PCT 1/8IN DRY SN SANDED 80FT WID...

NOTE-

Runway 11 is wider than eighty feet, is the landing runway and is 98% covered with 1/8 inch (3mm) depth or less of dry snow and also has been treated with sand eighty feet wide.

Deiced, as treatment of the surface**EXAMPLE-**

...RWY 30 FICON 5/5/5 100 PCT WET DEICED LIQUID...

NOTE-

Runway 30 is the landing runway and is 91% wet and has also been treated with a liquid deicing chemical.

Miscellaneous (ash, mud, rubber, sand)**EXAMPLE-**

...RWY 01R FICON 50 PCT 2IN MUD, DRY, DRY...

NOTE-

Runway 01R is the landing runway and the first third of the runway is 45% covered with 2 inches of mud. The remaining two thirds of the runway are contaminant free. When mud is listed as a contaminant there will be no RwyCC generated.

EXAMPLE-

...RWY 01L FICON 100 PCT ASH...

NOTE-

Runway 01L is the landing runway and is 100% covered with volcanic ash.

Slippery When Wet**EXAMPLE-**

...RWY 01/19 FICON 3/3/3 SLIPPERY WHEN WET...

NOTE-

The north 800 feet of runway 01/19 is covered by rubber. Although the rubber is only observed at the approach end of Runway 01, when rubber is on a runway surface, the entire surface is reported as slippery when wet. This is the only contaminant that is reported using both runway designators.

Braking Action**EXAMPLES-**

...TWY AA FICON BA GOOD TO MEDIUM...

...APRON MAIN APN FICON BA POOR...

...RWY 09/27 FICON BA MEDIUM TO POOR...

NOTE-

This runway is a non-paved surface.

5-1-5. AERODROME FACILITIES**a. Certified Aircraft Rescue and Fire Fighting (ARFF).****EXAMPLES-**

...AD AP ARFF VEHICLE U/S INDEX UNCHANGED...

...AD AP ARFF NOW INDEX A...

NOTE-

Even though the ARFF index is now A, four or less Index B aircraft may still operate into the airport.

EXAMPLE-

...AD AP ARFF INDEX A NOT AVBL AND AP CLSD TO AIR CARRIER OPS...

b. Fuel services**EXAMPLES-**

...AD AP 100LL FUEL NOT AVBL...

...AD AP MOBILE JET A FUEL NOT AVBL...

...AD AP HYDRANT MOGAS FUEL NOT AVBL...

...AD AP SELF SERVE 100LL FUEL NOT AVBL...

...AD AP FUEL NOT AVBL...

c. Custom Services**EXAMPLE-**

...AD AP CUST PROCESSING DLA DUE TO CAPACITY, INTL CARRIERS MAY EXPERIENCE SIGNIFICANT DLA IN CLEARING CUST, CTC AP MANAGEMENT AT XXX-XXX-XXXX...

d. Aerodrome beacon (ABN)**EXAMPLES-**

...AD AP ABN U/S...

...AD AP ABN NOT STD GREEN ONLY...

e. Wind direction equipment**EXAMPLES-**

...AD AP WDI UNREL...

...AD AP WINDCONE LGT U/S...

...AD AP WINDCONE OBST LGT U/S...

...AD AP WINDCONE FOR RWY 17L LEFT SIDE U/S...

f. Airplane Design Group**EXAMPLE-**

...AD AP CLSD TO ACFT WINGSPAN MORE THAN 214FT AND TAIL HGT MORE THAN 66FT...

5-1-6. WORK IN PROGRESS**EXAMPLES-**

...RWY 01L/19R WIP...

...TWY E BTN RWY 05/23 AND TWY B WIP RESURFACING...

...TWY B BTN RWY 14/32 AND TWY A WIP TRENCHING ADJ EAST SIDE...

...APRON FEDEX FEEDER RAMP W 1000FT WIP RESURFACING...

...RWY 03/21 NE 1000FT WIP LGT REPLACEMENT...

...RWY 01L/19R NE 500FT WIP MOWING ADJ...

...RWY 01L/19R SAFETY AREA WIP MAINT VEHICLES E SIDE...

...AD AP ALL SFC WIP SN REMOVAL...

...RWY 01L/19R WIP SN REMOVAL...

...TWY D4, D5, D6, TWY B BTN RWY 13/31 AND TWY D, TWY D WEST OF RWY 05/23 WIP SN REMOVAL...

5-2-1. LIGHTING AIDS

a. Commissioning approach lighting systems (ALS) and runway edge lights (REDL).

EXAMPLE-

...RWY 12 MALSR COMMISSIONED...
 ...RWY 12/30 HIRL COMMISSIONED...

b. Lead-in lights.

EXAMPLES-

...RWY 01C RLLS U/S...
 ...RWY 32 RLLS U/S EXC LOW INTST ON CONS...

c. Approach light system.

EXAMPLES-

...RWY 01 ALS U/S...
 ...RWY 19 ALS U/S EXC MEDIUM INTST ON CONS...
 ...RWY 06 ALSF-2 NOW SSALR...
 ...RWY 24 SEQUENCED FLG LGT U/S...
 ...RWY 11 1000-FOOT BAR U/S...
 ...RWY 16 RAI LGT U/S...
 ...RWY 34 RTHL U/S...

NOTE-

Technical Operations issue RTHL, when associated with approach lighting systems (ALS).

d. Visual approach lighting.

EXAMPLES-

...RWY 05 VASI U/S...
 ...RWY 04 VASI UNUSABLE...
 ...RWY 13 VASI BEYOND 5DEG LEFT OF RCL UNUSABLE
 ...RWY 02 VASI NOW 2 BOX (TIME-TIME)...For a temporary change
 ...RWY 02 VASI CHANGED TO 2 BOX (YYMMDDHHMM...PERM)
 ...RWY 34 VASI BEYOND 3.0NM UNUSABLE...
 ...RWY 01L PAPI U/S...
 ...RWY 01 PAPI UNUSABLE...
 ...RWY 10 PAPI BEYOND 5DEG LEFT OF RCL UNUSABLE...
 ...RWY 28 PAPI COMMISSIONED...
 ...RWY 30 PAPI COMMISSIONED GPA 3.15DEG...
 ...RWY 12 PAPI GPA CHANGED TO 3.2DEG...
 ...RWY 34 PAPI BEYOND 2.8NM UNUSABLE...

e. Runway lighting.

EXAMPLES-

...AD AP RWY STATUS LGT SYSTEM U/S...
 ...RWY 18L RWY STATUS LGT SYSTEM U/S...
 ...RWY 18L/36R RWY STATUS LGT SYSTEM U/S...
 ...TWY ALL RWY ENTRANCE LGT FOR RWY 09L SOUTH SIDE U/S...
 ...TWY K5, K6, T RWY ENTRANCE LGT FOR RWY 09L U/S...
 ...RWY 28 TKOF HOLD LGT U/S...
 ...RWY 18 RWY END ID LGT U/S...
 ...RWY 08R RTZL U/S...
 ...RWY 08R/26L RCLL U/S...
 ...RWY 13/31 REDL U/S...
 ...RWY 01/19 REDL U/S EXC MEDIUM INTST ON CONS...
 ...RWY 09 RENL U/S...

f. Taxiway lighting.**EXAMPLES-**

...TWY B CL LGT U/S
 ...TWY E CL LGT BTN TWY E1 AND RWY 15/33 U/S...
 ...TWY K, L EDGE LGT U/S...
 ...TWY ALL EDGE LGT WEST OF RWY 16L/34R U/S...
 ...TWY ALL EDGE LGT U/S...

NOTE-

ALL means every taxiway at an airport even if there is only a single taxiway.

...TWY ALL RWY GUARD LGT U/S...
 ...TWY A4 RWY GUARD LGT FOR RWY 01L/19R U/S...
 ...TWY C STOP BAR LGT FOR RWY 16R/34L U/S...

NOTE-

NOTAM for guard light and stop bar light issued using keyword TWY.

g. Lead off / lead on lights.**EXAMPLE-**

...RWY 01C LEAD OFF LGT FOR TWY Y4 U/S...

NOTE-

NOTAMs issued using keyword RWY. Lead off and lead on light will be the standardized verbiage for lead off/on lights, which are sometimes referred to as turnoff.

h. Pilot-controlled lighting.**EXAMPLES-**

...SVC PCL ALL U/S...
 ...SVC PCL RWY 18/36 REDL U/S
 ...SVC PCL RWY 18 ALS U/S...
 ...SVC PCL RWY 18/36 MEDIUM/HIGH INTST U/S...
 ...SVC PCL ALL UNUSABLE BEYOND 2NM...
 ...SVC PCL RWY 18/36 MEDIUM/HIGH INTST U/S...

NOTE-

All the PCL services for runway 18/36 only have low intensity operating.

...SVC PCL RWY 14/32 COMMISSIONED KEY FREQ 122.7 7 TIMES HIGH, 5 TIMES MEDIUM, 3 TIMES LOW
 INTST...

...SVC PCL RWY 01/19 NOT STD KEY FREQ 122.7 5 TIMES HIGH, 3 TIMES MEDIUM, 2 TIMES LOW
 INTST...

NOTE-

The PCL frequency transmissions is not standard, and the new information is provided until it is back to standard.

...SVC PCL FREQ CHANGED TO 122.8...

NOTE-

PCL frequency need not be an ATC frequency.

i. Airport lighting total power failure.**EXAMPLE-**

...AD AP LGT ALL U/S...

j. Lights obscured.**EXAMPLES-**

...RWY 15/33 REDL OBSC...
 ...RWY 01C LEAD ON LGT FOR TWY Y9 OBSC...
 ...TWY C EDGE LGT OBSC...
 ...TWY ALL LGT OBSC...

NOTE-

In this example all of the taxiways' lighting is fully obscured.

5-2-2. OBSTACLES**EXAMPLES-**

...OBST CRANE (ASN 2013-ACE-5-NRA) 345140N0804506W (1.44NM SW N52) 580FT (195FT AGL) FLAGGED, NOT LGTD...

!CLE ZOB OBST WIND TURBINE FARM WI AN AREA DEFINED AS 4NM RADIUS OF 411931N0822776W (17NM WLPR) 2820FT (410FT AGL) LGT U/S...

...OBST TOWER LGT (ASR UNKNOWN) 420651.07N0875406.27W (12NM N PWK) 1049FT (330FT AGL) U/S...

...OBST TOWER LGT (ASR 1234567)345313.12N0815744.34W (3NM SSW SPA) 1528FT (564FT AGL) U/S...

...OBST MOORED BALLOON WI AN AREA DEFINED AS 1NM RADIUS OF SJT 2430FT (510FT AGL) FLAGGED...

NOTE-

Moored balloons are not certified aircraft, nor operated by a certified pilot.

EXAMPLE-

...OBST KITE WI AN AREA DEFINED AS 1NM RADIUS OF ABQ020002 (10NM WSW ABQ) 5860FT (505FT AGL) FLAGGED...

5-3-6. INSTRUMENT LANDING SYSTEM (ILS) STATUS**EXAMPLES-**

...NAV ILS RWY 08L CAT II NA...

...NAV ILS RWY 08L CAT III NA...

...NAV ILS RWY 08L CAT II/III NA...

...NAV ILS RWY 22L REDUCED LGT SPECIAL AUTH CAT II AVBL...

5-3-7. NAVAID CONDITIONS**c. NOTAMs****1. General: Decommissioning of a NAVAID****EXAMPLE-**

...NAV ILS RWY 35L U/S YMMDDHHMM-PERM...

6. Facility Restrictions**(b) Excessive snow and ice accumulation****EXAMPLE-**

...NAV ILS RWY 18 GP U/S...

(c) VOR/ TACAN/ DME/ VOT/ NDB/ DF.**(2) [a] VOR/DME****EXAMPLES-**

...NAV VOR/DME 113.0/CH77 COMMISSIONED...

...NAV VOR/DME 020-140 BEYOND 28NM UNUSABLE...

...NAV VOR 045-060 SFC-2000FT UNUSABLE...

...NAV VOR 010-035 BEYOND 35NM SFC-2000FT UNUSABLE...

...NAV DME 010-035 BEYOND 30NM UNUSABLE...

...NAV DME 010-035 BEYOND 30NM SFC-17000FT UNUSABLE PLUS SEE CHART SUPPLEMENT...

...NAV VOR 090-180 BEYOND 25NM SFC-5000FT, 270-300 BEYOND 25NM SFC-5000FT, 300-360 BEYOND 35NM SFC-4000FT UNUSABLE...

...NAV VOR U/S...

NOTE-

Using "VOR U/S" means the VOR portion of the VOR/DME is out of service/unserviceable. The DME portion is still functioning.

EXAMPLE-

...NAV DME U/S...

NOTE-

A DME-only facility or the DME portion of the VOR/DME, or the DME of an NDB is unserviceable. The VOR or NDB portion is still functioning.

(2) [b] VORTAC**EXAMPLES-**

...NAV VORTAC 116.2/CH 109 COMMISSIONED...

...NAV VORTAC U/S...

...NAV VORTAC 010-035 BEYOND 30NM SFC-2800FT UNUSABLE ...

...NAV VOR U/S...

...NAV TACAN U/S...

NOTE-

When the DME portion of a VORTAC fails or is removed from service for maintenance, the TACAN and azimuth automatically becomes inoperative.

EXAMPLE-

...NAV TACAN AZM U/S...

(2) [c] VOT (VOR Test Facility).**EXAMPLE-**

...NAV VOT U/S...

(2) [d] VOT Receiver Checkpoint.**EXAMPLES-**

...NAV VOR AIRBORNE REC CHECKPOINT U/S...

...NAV VOR GND REC CHECKPOINT U/S...

...NAV VOR GND REC CHECKPOINT FOR TWY A U/S...

NOTE-

There are two separate Ground Receiver Checkpoints for this airport.

(2) [e] TVOR. (Terminal Class VOR).**EXAMPLES-**

!ILN ILN NAV MXQ VOR U/S

!DAY XUB NAV VOR U/S

NOTE-

For clarity, these examples show the accountability and location identifier.

(2) [f] NDB**EXAMPLES-**

!DCA DCA NAV GTN NDB U/S

!RKD SUH NAV NDB U/S

NOTE-

For clarity, these examples show the accountability and location identifier.

(2) [g] LOM**EXAMPLES-**

!SBY SBY NAV ILS RWY 32 COLBE LOM U/S...

!SUS SUS NAV ILS RWY 08R SNOOP LOM U/S...

NOTE-

1. In these examples, both the NDB and the marker beacon are unserviceable.

2. Except in Alaska, collocated LOMs are assigned five-letter names. All other NDBs are assigned three-letter identifiers.

EXAMPLE-

...JOSIE LOM NDB U/S

NOTE-

In this example, the NDB is not operational, but the marker beacon is operational.

EXAMPLE-

...JOSIE MKR BCN U/S

NOTE-

In this example, only the marker beacon is unserviceable; the NDB is operational.

EXAMPLES-

!MCI MCI NAV ILS RWY 09 HUGGY LOM U/S...

FLV FLV NAV HUGGY NDB U/S...

NOTE-

In the above examples, Huggy NDB serves as a LOM to runway 9 at Kansas City Intl (MCI). It also serves Fort Leavenworth/Sherman AAF (FLV), Kansas, as an NDB.

(2) [h] NAVAID identification change.**EXAMPLE-**

...NAV VORTAC ID CHANGED TO VHP...

(d) Visual Glide Slope Indicator.**EXAMPLES-**

...RWY 18 PAPI BEYOND 6DEG LEFT OF RCL UNUSABLE...

...RWY 32 PAPI BEYOND 2.8NM UNUSABLE...

(f) Instrument Landing Systems (ILS). Precision.**EXAMPLES-**

...NAV ILS RWY 35L U/S...

...NAV ILS RWY 32 110.3 COMMISSIONED...

...NAV ILS RWY 08R SNOOP LOM U/S...

...NAV ILS RWY 05 U/S... -PERM

...NAV ILS RWY 18 DME U/S...

...NAV ILS RWY 02 FAN MKR U/S...

...NAV ILS RWY 18 GP UNUSABLE SFC-768FT ...

...NAV ILS RWY 02 GP/OM/MM U/S...

...NAV ILS RWY 30 GP UNUSABLE BEYOND 5DEG LEFT OF COURSE ...

...NAV BZB ILS RWY 22R U/S...

NOTE-

Offset ILS are issued with the 3 letter ID (example BZB) for the localizer after the Keyword NAV.

EXAMPLE-

...NAV ILS RWY 30 FAC PER CLASSIFICATION CODE CHANGED TO CLASS IIIE...

NOTE-

For runway 30, the ILS facility performance classification code has been changed from the previously published data.

(g) Localizer/LOC Directional Aid/Simplified Directional Facility Azimuth.**EXAMPLES-**

...NAV ILS RWY 30 LOC RTS...

...NAV ILS RWY 35L U/S...

...NAV ILS RWY 12 LOC UNUSABLE BEYOND 4DEG RIGHT OF COURSE ...

...NAV ILS RWY 12 LOC UNUSABLE BEYOND RWY THR...

...NAV LOC RWY 27 U/S...

...NAV LOC RWY 33 LOC UNUSABLE WI .4NM ...

...NAV LOC RWY 16 BC UNUSABLE BEYOND 6DEG RIGHT OF COURSE...

...NAV LOC TYPE DIRECTIONAL AID U/S...

...NAV LOC RWY 14 LOC/DME U/S...

NOTE-

The LDA at the airport, not a particular runway, is unserviceable.

...NAV VHW LOC TYPE DIRECTIONAL AID RWY 18 LOC U/S...
 ...NAV SIMPLIFIED DIRECTIONAL FAC RWY 23 U/S...

5-3-8. SATELLITE BASED SYSTEMS

a. Global Positioning System (GPS).

EXAMPLES-

!GPS GPS NAV PRN 16 U/S...

!GPS ZAB NAV GPS (NAFC GPS 15-01 E1) (INCLUDING WAAS, GBAS, AND ADS-B) MAY NOT BE AVBL WI AN AREA DEFINED AS A 468NM RADIUS CENTERED AT 330702N1062540W (TCS103044) FL400-UNL, 425NM RADIUS AT FL250, 360NM RADIUS AT 10000FT, 354NM RADIUS AT 4000FT AGL, 327NM RADIUS AT 50FT AGL DLY 0400-1000 YMMDD0400-YMMDD1000

b. Wide Area Augmentation System (WAAS).

1. Unscheduled loss of signal or service.

EXAMPLES-

!FDC FDC NAV WAAS NOT AVBL...

!FDC ZAN NAV WAAS SIGNAL MAY NOT BE AVBL NORTH OF A LINE DEFINED AS XXXXXXNXXXXXXXXW TO XXXXXXNXXXXXXXXW. WAAS USERS SHOULD CONFIRM RAIM AVBL FOR IFR OPS IN THIS AREA. T-ROUTES IN THIS SECTOR NOT AVBL. ANY REQUIRED ALTN AP IN THIS AREA MUST HAVE AN APPROVED IAP OTHER THAN GPS THAT IS ANTICIPATED TO BE OPR AND AVBL AT THE EST TIME OF ARR AND WHICH THE ACFT IS EQUIPPED TO FLY...

2. Ionosphere storm conditions.

EXAMPLES-

...NAV WAAS VNAV/LPV/LP MINIMA MAY NOT BE AVBL...

...NAV WAAS VNAV/LPV MINIMA NOT AVBL, WAAS LP MINIMA MAY NOT BE AVBL...

3. Scheduled loss of signal or service.

EXAMPLES-

...NAV WAAS NOT AVBL...

!FDC ZAN NAV WAAS SIGNAL NORTH OF LINE DEFINED AS XXXXXXNXXXXXXXXW TO XXXXXXNXXXXXXXXW MAY NOT BE AVBL. WAAS USERS SHOULD CONFIRM RAIM AVBL FOR IFR OPS IN THIS AREA. T-ROUTES IN THIS SECTOR NOT AVBL. ANY REQUIRED ALTN AP IN THIS AREA MUST HAVE AN APPROVED IAP OTHER THAN GPS THAT IS ANTICIPATED TO BE OPR AND AVBL AT THE EST TIME OF ARR AND WHICH THE ACFT IS EQUIPPED TO FLY

c. Automatic Dependent Surveillance-Broadcast (ADS-B) and Wide Area Multilateration (WAM).

1. ADS-B

EXAMPLES-

!FDC x/xxxx ZHU AIRSPACE ADS-B, AUTO DEPENDENT SURVEILLANCE-REBROADCAST (ADS-R), TFC INFO SER BCST (TIS-B), FLT INFO SER BCST (FIS-B) SER MAY NOT BE AVBL WI AN AREA DEFINED AS 139NM RADIUS OF 261010N0892142W. AIRSPACE AFFECTED MAY INCLUDE GULF OF AMERICA AREAS OF GREEN CANYON, EWING BANK, MISSISSIPPI CANYON. SFC-UNL...

!FDC x/xxxx ZLA AIRSPACE ADS-B, AUTO DEPENDENT SURVEILLANCE REBROADCAST (ADS-R), TFC INFO SER BCST (TIS-B), FLT INFO SER BCST (FIS-B) SER MAY NOT BE AVBL WI AN AREA DEFINED AS 79NM RADIUS OF 333730N1183137W. AP AIRSPACE AFFECTED MAY INCLUDE LAX, BUR, ONT. SFC-UNL...

2. WAM

EXAMPLES-

!MTJ MTJ SVC WID AREA MULTILATERATION U/S...

d. Service Availability Prediction Tool (SAPT).**EXAMPLE-**

/FDC XX/XXX FDC AIRSPACE ADS-B SERVICE AVAILABILITY PREDICTION TOOL (SAPT) U/S SEE AC 90-114 FOR PREFLIGHT GUIDANCE YMMDDHHMM-YMMDDHHMM...

e. Ground Based Augmentation System (GBAS) and GBAS Landing System (GLS).**1. Unscheduled loss of signal or service.****EXAMPLE-**

...NAV GBAS U/S...

2. Predicted loss of signal or service.**EXAMPLE-**

...NAV GLS RWY 04R, RWY 04L, RWY 11, RWY 22R, RWY 22L U/S...

NOTE-

When one or multiple GLS approaches are predicted to not be available.

3. Restricted usability of GLS.**EXAMPLES-**

...NAV GBAS, RWY 4L GLS UNUSABLE BYD 28 DEG LEFT OF CL AND UNUSABLE BYD 15NM...

...NAV GBAS, RWY 22 GLS UNUSABLE BYD 15NM...

5-3-9. HOURS OF OPERATION (NAVAID)**EXAMPLE-**

...NAV ILS RWY 32 NOT MNT DLY 0200-0900...

5-4-3. COMMUNICATION NOTAM FORMAT**c. 1. Commissioning and decommissioning.****EXAMPLES-**

...COM CTAF 122.8 COMMISSIONED...-PERM

...COM LOCAL CTL 118.9, GND CTL 121.0 COMMISSIONED...-PERM

...COM REMOTE COM OUTLET 122.6 U/S...-PERM

...COM LOCAL CTL 118.9, GND CTL 121.0 COMMISSIONED...

c. 2. Outage, or (un)availability of communications outlets.**EXAMPLES-**

...COM REMOTE COM OUTLET 122.6 U/S...

...COM REMOTE TRANS/REC 126.25, 131.25 U/S...

...COM REMOTE COM OUTLET U/S...

...COM GRAND ISLE REMOTE COM OUTLET 122.4 U/S

...COM DUTCH HARBOR REMOTE CENTER A/G 268.7 U/S...

...COM VOR VOICE U/S...

...COM VOR 122.1 U/S...

...COM ARINC CPDLC NOT AVBL...

...COM CLR DELIVERY 121.7 U/S...

...COM GND COM OUTLET 135.075 U/S...

...COM LOCAL AP ADVISORY 121.3 U/S... ...COM UNICOM FREQ 122.8 U/S...

c. 3. Communication outlet or facility frequency change.**EXAMPLES-**

...COM CLR DELIVERY 121.7 NOW 124.125...

...CPDLC DEP CLR LOGON CHANGED TO KUSA...

...COM REMOTE COM OUTLET 122.6 CHANGED TO 122.2...

5-5-1. GENERAL**EXAMPLES-**

SVC TWR VISUAL SIGNAL NOT AVBL LIGHT GUN U/S...

5-5-2. CHANGES TO PUBLISHED SERVICES**EXAMPLES-**

...SVC TWR COMMISSIONED...

...SVC ATIS NOT AVBL...

NOTE-

When ATIS is not available for other than equipment malfunction, use NOT AVBL.

EXAMPLES-

...SVC ATIS 134.025 U/S...

...SVC ATIS 134.025 NOT AVBL...

NOTE-

ATIS service from 134.025 is not available; however, ATIS service is being provided from another frequency.

EXAMPLES-

...SVC AUTO FLT INFO U/S...

...SVC AUTO FLT INFO SER 134.95 U/S...

...SVC AUNICOM WX BCST NOT AVBL...

NOTE-

The Automated UNICOM weather broadcast is not available.

EXAMPLES-

...SVC LOCAL AP ADVISORY SER NOT AVBL...

NOTE-

The CTAF frequency at an airport is U/S, and the FSS providing local airport advisory services is not CLSD.

EXAMPLE-

...SVC AUNICOM U/S...

NOTE-

The Automated UNICOM is unserviceable.

5-5-3. HOURS OF OPERATION

- a. Changes in hours of operation.

NOTE-

Spell out facility names when used in the body of the NOTAM.

1. Air route traffic control center (ARTCC).

EXAMPLE-

...SVC XXXXXX ARTCC CLSD...

NOTE-

Closed (CLSD) is the appropriate term for events when an air traffic facility is unstaffed but not resulting in a total failure of the facility.

EXAMPLE-

...SVC XXXXXX ARTCC U/S...

NOTE-

Unserviceable (U/S) is used with complete system outages/total failure of a facility.

2. Approach control.

EXAMPLE-

...SVC XXXXXX APP CLSD CLASS C SER INVOLVING VFR ACFT NOT AVBL CTC XXXXXX ARTCC FOR CLASS C ARR COM ON XXX.XX, FOR CLR DELIVERY AT XXX-XXX-XXXX...

...SVC XXXXXX APP CLSD TERMINAL RADAR SERVICE AREA SER INVOLVING VFR ACFT NOT AVBL CTC XXXXXX ARTCC FOR TERMINAL RADAR SERVICE AREA ARR COM ON XXX.XX, FOR CLR DELIVERY AT XXX...XXX...XXXX...

NOTE-

For approach facilities with a terminal RADAR Service Area. The overlying ARTCC is unable to provide Terminal RADAR Service Area services.

3. Air traffic control tower.**EXAMPLE-**

...SVC TWR CLSD TWR XXX.XX NOW CTAF CLASS B SER AVBL CTC XXXXXX APP FOR CLASS B VFR DEP AND IFR CLR DELIVERY AT XXX-XXX-XXXX...

NOTE-

Class B stand-alone ATCT with operational overlying TRACON. Class B VFR separation services remain.

EXAMPLE-

...SVC TWR CLSD TWR XXX.XX NOW CTAF CLASS B SER AVBL CTC XXXXXX APP FOR CLASS B VFR DEP AND IFR CLR DELIVERY ON XXX.XX...

NOTE-

Class B combined ATCT/TRACON with operational overlying TRACON. Class B VFR separation services remain.

EXAMPLES-

...SVC TWR CLSD TWR XXX.XX NOW CTAF CLASS B VFR OPS NOT PERMITTED CTC XXXXXX ARTCC FOR CLASS B ARR ON XXX.XX, FOR CLR DELIVERY ON XXX.XX...

...SVC XXXXXX APP CLSD CLASS B VFR OPS NOT PERMITTED CTC XXXXXX ARTCC FOR CLASS B ARR ON XXX.XX, FOR CLR DELIVERY AT XXX-XXX-XXXX...

NOTE-

Combined ATCT/TRACON both with overlying ARTCC that is unable to provide Class B separation service. Two NOTAMs must be issued, one for the ATCT closure and one for the approach closure.

EXAMPLE-

...SVC TWR CLSD TWR XXX.XX NOW CTAF CLASS C SER AVBL CTC XXXXXX APP FOR CLASS C VFR DEP AND IFR CLR DELIVERY AT XXX-XXX-XXXX...

NOTE-

Stand-alone, full-time ATCT (no published CTAF) with operational overlying TRACON (Class C VFR separation services remain). No Class C arrival communication information necessary because frequency is published.

EXAMPLE-

...SVC TWR CLSD MNT CTAF XXX.XX CLASS C SER AVBL CTC XXXXXX APP FOR CLASS C VFR DEP AND IFR CLR DELIVERY AT XXX-XXX-XXXX...

NOTE-

Stand-alone, part-time ATCT (published CTAF) with operational overlying TRACON (Class C VFR separation services remain). No Class C arrival communication information necessary because frequency is published.

EXAMPLES-

...SVC TWR CLSD TWR XXX.XX NOW CTAF CLASS C SER INVOLVING VFR ACFT NOT AVBL CTC XXXXXX ARTCC FOR CLASS C ARR COM ON XXX.XX, FOR CLR DELIVERY AT XXX-XXX-XXXX...

...SVC XXXXXX APP CLSD CLASS C SER INVOLVING VFR ACFT NOT AVBL CTC XXXXXX ARTCC FOR CLASS C ARR COM ON XXX.XX, FOR CLR DELIVERY AT XXX-XXX-XXXX...

...SVC TWR CLSD MNT CTAF XXX.XX TERMINAL RADAR SERVICE AREA SER AVBL CTC XXXXXX APP FOR TERMINAL RADAR SERVICE AREA VFR DEP AND IFR CLR DELIVERY AT XXX-XXX-XXXX...

NOTE-

For stand-alone, part-time ATCT (published CTAF) with operational overlying Approach facility (Terminal RADAR Service Area VFR separation services remain), no Terminal RADAR Service Area arrival communication information necessary because frequency is published.

4. Flight Service Station.**EXAMPLES–**

...SVC XXXXXX FSS CLSD...
 ...SVC XXXXXX FSS U/S...
 ...SVC XXXXXX FSS CLSD LOCAL AP ADVISORY SER NOT AVBL...

b. Establishment of temporary air traffic control tower.**EXAMPLE–**

...TEMPO TWR LOCAL CTL 121.0, GND CTL 121.7...

NOTE–

Frequency 121.0 will be used to control arriving and departing aircraft from the designated runway(s), and 121.7 will be used for controlling taxiing aircraft.

c. Extended hours of operation.**EXAMPLE–**

...SVC TWR OPN PLUS SEE CHART SUPPLEMENT YMMDD0330–YMMDD0530

...SVC TWR OPN PLUS SEE CHART SUPPLEMENT DLY 0330–0530 YMMDD0330–YMMDD0530

d. Traffic Management Program Alerts.**EXAMPLES–**

...SVC TFC MANAGEMENT PROGRAM ALERT SEE DOMESTIC NOTICES RESERVATION REQUIRED...
 ...SVC TFC MANAGEMENT PROGRAM ALERT SEE ATCSCC MSG...

NOTE–

Details of each traffic management program are published in Domestic Notices or included in a special traffic management program advisory message

5–5–4. WEATHER AND WEATHER REPORTING EQUIPMENT**c.1. Total system failure.****EXAMPLE–**

...SVC AUTOMATED WX BCST SYSTEM U/S...

c.2. Entire observation missing.**NOTE–**

The non–automated weather reporting service provided by the FAA or the NWS is missing or not available as published.
 ...SVC AUTOMATED WX BCST SYSTEM NOT AVBL

NOTE–

The automated observation is missing and no backup observation is available.

c.3. Missing altimeter setting.**EXAMPLE–**

...SVC AUTOMATED WX BCST SYSTEM ALTIMETER SETTING NOT AVBL...

NOTE–

The AWOS–C altimeter setting is being reported as “missing” on the weather report.

c.4. Erroneous date/time group.**EXAMPLE–**

...SVC AUTOMATED WX BCST SYSTEM DTG UNREL...

c.5. Unreliable (intermittent) or inaccurate (erroneous) elements at locations without a certified weather observer to backup weather system.

EXAMPLES–

...SVC AUTOMATED WX BCST SYSTEM ALTIMETER SETTING UNREL...

...SVC AUTOMATED WX BCST SYSTEM CEILING UNREL...
 ...SVC AUTOMATED WX BCST SYSTEM WIND UNREL...
 ...SVC AUTOMATED WX BCST SYSTEM CEILING/WIND UNREL...

NOTE-

An element (for example, ceiling, visibility, wind, temperature, dew point, and altimeter setting) disseminated in the weather report as unreliable and/or inaccurate will be described in the NOTAM as UNREL. Multiple elements must be submitted as one NOTAM. Separate each element with a forward slash.

EXAMPLES-

...SVC AUTOMATED WX BCST SYSTEM VIS/PRESENT WX UNREL...
 ...SVC AUTOMATED WX BCST SYSTEM T/PRESENT WX UNREL...

NOTE-

Unreliable or inaccurate visibility, temperature, and dew point will affect present weather information type and intensity reporting (i.e., rain, snow) within the system and must be included in the NOTAM.

c.6. Commissioning or decommissioning of weather reporting.**EXAMPLES-**

...SVC AUTOMATED WX BCST SYSTEM COMMISSIONED...-PERM
 ...SVC AUTOMATED WX BCST SYSTEM U/S ...-PERM
 ...SVC WX REP U/S ...-PERM

c.7. Broadcast frequency**EXAMPLES-**

...SVC AUTOMATED WX BCST SYSTEM 120.3 U/S...,
 ...SVC AUTOMATED WX BCST SYSTEM 119.075 RTS...

d. Juneau Airport Wind Service**EXAMPLES-**

...SVC JUNEAU AP WIND SYSTEM NOT AVBL...
 ...SVC WIND SYSTEM EAGLECREST NOT AVBL...
 ...SVC WIND SYSTEM RWY 08 NOT AVBL...
 ...SVC WIND SYSTEM SOUTH DOUGLAS PROFILER NOT AVBL...

5-5-5. MICROBURST/WINDSHEAR DETECTION SYSTEM**EXAMPLES-**

...SVC MBST/WS DETECTION SYSTEM NOT AVBL...
 ...SVC MBST /WS DETECTION SYSTEM FOR RWY 10/28 NOT AVBL...
 ...SVC WX RADAR BEYOND 60NM RADIUS OF SJU VOR U/S...
 ...SVC WX RADAR U/S...

5-5-6. RADAR SERVICES**EXAMPLES-**

...SVC SMR U/S...
 ...SVC PRECISION RWY MNT U/S...
 !CLE ZOB SVC WX RADAR U/S. ENR WX ADVSIORIES MAY NOT BE AVBL IN SW PA NW OH...

6-1-1. AIRSPACE NOTAM FORMAT**EXAMPLES-**

!SUAW mm/nnn ZSE AIRSPACE OKANOGAN C MOA ACT 300FT-8999FT YMMDD1815- YMMDD2245

!CARF mm/nnn ZDC AIRSPACE DCC VIENNA STNR ALT RESERVATION WI AN AREA DEFINED AS 7NM RADIUS OF SBY312017 SFC-3500FT 2312021500-2312021930

...AIRSPACE UNMANNED ROCKET WI AN AREA DEFINED AS 1NM RADIUS OF 424238N0902332W (2.5NM E

PVB) SFC-4500FT YMMDD1400- YMMDD2300

... 9N1 AIRSPACE AEROBATIC ACFT WI AN AREA DEFINED AS 403200N0750842W (3.4NM NW 9N1) TO 403200N0750605W (3.1NM N 9N1)

TO 402959N0750605W (1NM N 9N1) TO 402959N0750842W (1.4NM W 9N1) TO POINT OF ORIGIN SFC-7500FT AGL...

AIRSPACE FLTCK ACFT OPS WI AN AREA DEFINED AS 5NM RADIUS OF (airport) SFC-3500FT AGL ACFT CS FLC77...

6-1-2. SPECIAL ACTIVITY AIRSPACE (SAA)

EXAMPLES-

!SUAW mm/nnn ZLC AIRSPACE SADDLE A MOA ACT 10000FT-17999FT YMMDD1515-YMMDD0530...

...(ARTCC) AIRSPACE (SUA) ACT 8000FT-FL235 YMMDD1900-YMMDD0500

...AIRSPACE DRUM MOA ACT 500FT AGL-4999FT...

SUAW mm/nnn ZLA AIRSPACE TEMPO RESTRICTED AREA R2509W ACT PLUS SEE DOMESTIC NOTICE YMMDD0424-YMMDD1200

NOTE-

Temporary SUA information must be described in the Domestic Notice. See FAA Order JO 7400.2, Procedures for Handling Airspace Matters, 21-1-15c.

!SUAW mm/nnn ZLC AIRSPACE LGT OUT/NIGHT VISION GOGGLE TRG SADDLE A MOA ACT 10000FT-17999FT YMMDD1515-YMMDD0530

NOTE-

NOTAMs for LIGHT OUT/NGT VISION GOGGLE operations are scheduled times only, identified 48 hours in advance.

6-1-3. AIRSPACE AND ALTITUDE RESERVATIONS

EXAMPLES-

!CARF mm/nnn ZDC AIRSPACE DCC BURGESS STNR ALT RESERVATION WI AN AREA DEFINED AS SBY265052 TO SBY251056 TO SBY242054 TO SBY236048 TO SBY244044 TO POINT OF ORIGIN SFC-3500FT YYDDMM2210-YYDDMM2320

...(ARTCC) AIRSPACE STNR ALT RESERVATION WI AN AREA DEFINED AS XXXXXXNXXXXXXXXXW TO XXXXXXNXXXXXXXXXW TO XXXXXXNXXXXXXXXXW TO XXXXXXNXXXXXXXXXW TO POINT OF ORIGIN SFC-UNL

6-1-4. SPECIAL AERIAL REFUELING

EXAMPLES-

...AIRSPACE SPECIAL AERIAL REFUELING TRACK/ANCHOR WI AN AREA DEFINED AS MCN TO SUG TO GRD090003 TO IRQ TO POINT OF ORIGIN ACT 12000FT-14000FT...

6-1-5. AIRSPACE NOTAM REQUIRING AUTHORIZATION/WAIVER

c.1. Airshows, Aerial Demonstrations, Aerobatic Areas, Hot Air Balloon Events, Flight Test Areas, Light Out Training, Banner Towing.

EXAMPLES-

AIRSPACE (Activity) WI AN AREA DEFINED AS 2NM RADIUS OF DJB320015 SFC-4000FT...

...HAR AIRSPACE AEROBATIC ACFT WI AN AREA DEFINED AS 2NM RADIUS OF HAR011009 SFC-5000FT SUN 1400-1800 YYYYMMDD1400-YYYYMMDD1800

... AIRSPACE LGT OUT TRG WI CLASS D SFC AREA FRI TUE WED THU 0615-0745 YYYYMMDD0615-YYYYMMDD 0745

c.2. Amateur rockets, Unmanned free balloons.

EXAMPLES-

...AIRSPACE UNMANNED ROCKET WI AN AREA DEFINED AS 4NM RADIUS OF ICT SFC-FL250
 ...AIRSPACE UNMANNED FREE BALLOON ABQ180020 SFC-UNL NEB TO 150000FT...
 ...AIRSPACE BALLOON LDG WI AN AREA DEFINED AS 100NM RADIUS OF ICT PAYLOAD FALLING FM 150000FT SFC-UNL...

c.3. Parachute Jumping/Sky Diving

EXAMPLE-

...AIRSPACE PJE WI AN AREA DEFINED AS 5NM RADIUS OF BVT080015...

c.4. Unmanned Aircraft Systems (UAS) Operations.

EXAMPLE-

...AIRSPACE UAS WI AN AREA DEFINED AS 13NM RADIUS OF SYR SFC-17999FT...

6-1-6. SURFACE AREA AIRSPACE

EXAMPLES-

...AIRSPACE CLASS D SFC AREA HR CHANGED TO ACT MON-FRI 0615-2100, SAT 0830-1700, SUN 1000-1900 YMMDDHHMM-PERM
 ...AIRSPACE CLASS E SFC AREA HR CHANGED TO ACT DLY 0430-0600 YMMDDHHMM-PERM

7-1-3. IFR FLIGHT PROCEDURES

f. Chart correction NOTAMs.

EXAMPLES-

!FDC x/xxxx VLL CHART TROY/OAKLAND, TROY, MI.
 VOR-A, ORIG...
 CORRECT FAF TO READ PERLS INT. VS PERSL INT. YMMDDHHMM-PERM

!FDC x/xxxx FDC CHART U.S. GOVERNMENT CHART
 NORTH ATLANTIC ROUTE CHART, EFFECTIVE 5 MAY 2011...
 CORRECT ROUTE IDENTIFIER A763 BETWEEN GRAND TURK ISLAND (GTK) VORTAC AND AGUADILLA (BQN) VORTAC TO READ R763. YMMDDHHMM-PERM

!FDC x/xxxx FDC CHART U.S. GOVERNMENT CHART
 IFR EN ROUTE LOW ALTITUDE CHART L-3, PANEL C, EFFECTIVE 23 SEPT 2010...
 CORRECT VICTOR AIRWAY V458 BTW JLI VORTAC (330825.651N/116 3509.365W) AND KUMBA INT (324543.180N/1160313.370W) MEA SHOULD READ 7700 VICE 7800. YMMDDHHMM-PERM

EXAMPLES-

A DME antenna is unserviceable:

!FDC x/xxxx PWK IAP CHICAGO EXECUTIVE, CHICAGO/PROSPECT HEIGHTS/WHEELING, IL. VOR RWY 16, ORIG-B...

DME MINIMUMS NA EXCEPT FOR AIRCRAFT EQUIPPED WITH SUITABLE RNAV SYSTEM WITH GPS, ORD DME U/S.

YMMDDHHMM - YMMDDHHMMEST

REASON: ORD DME U/S

A locator outer marker (LOM) used for procedure entry and/or missed approach clearance limit for an ILS approach is unserviceable:

!FDC x/xxxx ASH IAP NASHUA/BOIRE FIELDS, NH. ILS OR LOC RWY 14, AMDT 5B...
 PROCEDURE NA EXCEPT FOR AIRCRAFT EQUIPPED WITH SUITABLE RNAV SYSTEM WITH GPS, CHERN

LOM U/S. YMMDDHHMM – YMMDDHHMMEST REASON: CHERN LOM U/S.

A VOR is used in a departure procedure (ODP or SID) is unserviceable:

!FDC x/xxxx DUG ODP BISBEE–DOUGLAS INTL, DOUGLAS BISBEE, AZ. TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES... DEPARTURE PROCEDURE: NA EXCEPT FOR AIRCRAFT EQUIPPED WITH SUITABLE RNAV SYSTEM WITH GPS, DUG VOR U/S.

YMMDDHHMM – YMMDDHHMMEST

REASON: DUG VOR U/S.

EXAMPLES–

!FDC x/xxxx LAS SID HARRY REID INTL, LAS VEGAS, NV. HOOVER THREE DEPARTURE...

PROCEDURE NA EXCEPT FOR AIRCRAFT EQUIPPED WITH SUITABLE RNAV SYSTEM WITH GPS OR DME/DME/IRU, PGS VOR U/S. BLD AND DRK DME MUST BE OPERATIONAL FOR DME/DME/IRU ON PEACH SPRINGS TRANSITION. DRAKE TRANSITION NA FOR DME/DME/IRU.

YMMDDHHMM – YMMDDHHMMEST

REASON: PGS VOR U/S.

h. Air Traffic Service NOTAMs.

EXAMPLES–

!FDC x/xxxx ZFW OK ROUTE ZFW ZKC.

V140 SAYRE (SYO) VORTAC, OK TO TULSA (TUL) VORTAC, OK MEA 4300.

YMMDDHHMM – YMMDDHHMMEST

!FDC x/xxxx ZKC OK ROUTE ZFW ZKC.

V140 SAYRE (SYO) VORTAC, OK TO TULSA (TUL) VORTAC, OK MEA 4300.

YMMDDHHMM – YMMDDHHMMEST

REASON: TEMPORARY NEW TOWER, 20 YY –ASW–0123–OE.

EXAMPLES–

!FDC x/xxxx ZAB ROUTE ZAB ZKC.

V12–V280 PANHANDLE (PNH) VORTAC, TX TO GAGE (GAG) VORTAC, OK MOCA 5000. YMMDDHHMM – YMMDDHHMMEST

!FDC x/xxxx ZKC ROUTE ZAB ZKC.

V12–V280 PANHANDLE (PNH) VORTAC, TX TO GAGE (GAG) VORTAC, OK MOCA 5000. YMMDDHHMM – YMMDDHHMMEST

REASON: NEW CONTROLLING OBSTACLE: 352536.26N/1013119.72W, 389 AGL/3932 MSL. 20 YY –ASW–0369–OE.

EXAMPLES–

!FDC x/xxxx FDC ROUTE ZBW ZNY ZDC ZJX.

V1 HARTFORD (HFD) VORTAC, CT TO CRAIG (CRG) VORTAC, FL MEA 4000. YMMDDHHMM – YMMDDHHMMEST

REASON: REDESIGNATION OF CONTROLLED AIRSPACE.

i. DVA, IAP, ODP, SPECIAL, SID, and STAR FDC NOTAM EXAMPLES:

EXAMPLES–

!FDC x/xxxx ORD IAP CHICAGO O'HARE INTL, CHICAGO, IL.

VOR RWY 22R AMDT 8B...

MDA 1400/HAT 750, VIS 1–1/2 ALL CATS. TEMPORARY CRANE 1100 MSL

1.2-NM SE OF RWY 23 (Note: Specify distances less than 1 NM in feet.)(2013–AGL–0689–OE) YMMDDHHMM – YMMDDHHMMEST

REASON: TEMPORARY CRANE FOR 180 DAYS. 20 YY –AGL–0689–OE

!FDC x/xxxx MYF DVA MONTGOMERY FIELD, SAN DIEGO, CA. DIVERSE VECTOR AREA ORIG... RWY 5 REQUIRES MINIMUM CLIMB OF 338 FT PER NM TO 2200. ALL OTHER DATA REMAINS AS PUBLISHED.

YMMDDHHMM – YMMDDHHMMEST

REASON: TEMPORARY CRANE FOR 180 DAYS. 20 YY –AWP–1234–OE

*!FDC x/xxxx GPT IAP GULFPORT–BILOXI INTL, GULFPORT, MS
VOR RWY 31 AMDT 18...*

*S–31 MDA 720/HAT 693 ALL CATS. VIS CAT C 2, CAT D 2–1/2. CIRCLING MDA 720/HAA 692 ALL CATS. VIS
CAT C 2, CAT D 2–1/2. TEMPORARY CRANE 410 MSL 375 FT SE OF RWY 31.
THIS IS VOR RWY 31 AMDT 18A. (ASN 2013–ASO–5–NRA) YMMDDHHMM–PERM REASON: TEMPORARY
CRANE FOR 1 YEAR. ASN 20 YY –ASO–5–NRA*

*!FDC x/xxxx LAN IAP CAPITAL CITY, LANSING, MI.
ILS RWY 10R AMDT 8A...*

*CIRCLING MDA 1420/HAA 559 ALL CATS.
THIS IS ILS RWY 10R AMDT 8B. (2013–AGL–0123–OE) YMMDDHHMM–PERM
REASON: NEW BUILDING, 1115 MSL. 20 YY –AGL–0123–OE*

*!FDC x/xxxx AXH IAP HOUSTON–SOUTHWEST, HOUSTON, TX
NDB RWY 28 AMDT 4...*

*CHANGE ALL REFERENCE TO RWY 10–28 TO RWY 9–27. THIS IS NDB RWY 27 AMDT 4A. YMMDDHHMM
– YMMDDHHMMEST
REASON: RUNWAYS RENUMBERED FOR MAGNETIC VARIATION CHANGE.*

*!FDC x/xxxx HIE ODP MOUNT WASHINGTON REGIONAL, WHITEFIELD, NH
TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES...*

*TAKEOFF MINIMUMS: RWY 10, NA. RWY 28, 2700–3 WITH A MINIMUM CLIMB OF 340 FT PER NM TO
4400. DEPARTURE PROCEDURE: RWY 10, NA. RWY 28, CLIMB DIRECT GMA NDB, CLIMB IN HOLDING
PATTERN (W, RIGHT TURNS, 104 INBOUND) TO 5300 BEFORE PROCEEDING ON COURSE. ALL OTHER
DATA REMAINS AS PUBLISHED. YMMDDHHMM – YMMDDHHMMEST
REASON: PERIODIC REVIEW. PROCEDURE UPDATED TO MEET CURRENT POLICY/CRITERIA.*

!FDC x/xxxx BCE ODP BRYCE CANYON, BRYCE CANYON, UT.

*TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES.
BRYCE ONE DEPARTURE (RNAV): PROCEDURE NA. YMMDDHHMM – YMMDDHHMMEST
REASON: AWAITING CONTROLLED AIRSPACE RULEMAKING*

!FDC x/xxxx PAJN SPECIAL JUNEAU INTERNATIONAL, JUNEAU, AK.

*LDA X RWY 8 AMDT 9...
PROCEDURE TURN NA. YMMDDHHMM – YMMDDHHMMEST
REASON: PROCEDURE TURN (PT) STEPDOWN FIX GREATER THAN 4-NM FROM PT FIX.*

!FDC x/xxxx DFW SID DALLAS–FORT WORTH INTL, DALLAS–FORT WORTH, TX.

*PODDE THREE DEPARTURE...
CHANGE NOTES TO READ: RWYS 17C/R, 18L/R: DO NOT EXCEED 240KT UNTIL LARRN. RWYS 35L/C,
36L/R: DO NOT EXCEED 240KT UNTIL KMART.
YMMDDHHMM – YMMDDHHMMEST
REASON: TO SEPARATE SID FROM THE CEOLA DEPARTURE AND CHANGE 240L TO READ 240 KT.*

!FDC x/xxxx DCA STAR WASHINGTON/RONALD REGAN WASHINGTON NATIONAL, WASHINGTON, DC.

*WZRRD TWO ARRIVAL...
SHAAR TRANSITION: ROUTE FROM DRUZZ INT TO WZRRD INT NOT
AUTHORIZED. AFTER DRUZZ INT EXPECT RADAR VECTORS TO ARMEL (AML) VORTAC.
YMMDDHHMM– YMMDDHHMMEST
REASON: ATC ROUTING RESTRICTION.*

Snow Glideslope

EXAMPLE–

*!FDC x/xxxx DLH IAP DULUTH INTL, DULUTH, MN
ILS OR LOC RWY 27 AMDT 10...*

S-ILS 27 CAT D/E NA.
YYMMDDHHMM-YYMDHMMEST

7-1-4. HIGH BAROMETRIC PRESSURE WARNING

EXAMPLE-

(ARTCC) AIRSPACE HIGH BAROMETRIC PRESSURE ALTIMETER PROC ARE IN EFFECT PURSUANT 14 CFR SECTION 91.144 WI AN AREA DEFINED AS (ARTCC Name or see 6-1-1a4) BLW 18000FT. NO PERSON MAY OPR AN ACFT UNLESS ABLE TO COMPLY WITH AERONAUTICAL INFORMATION MANUAL (AIM) 7-2-3 AND AERONAUTICAL INFORMATION PUBLICATION (AIP) ENR 1.7 OR SPECIFICALLY WAIVED BY THE ADMINISTRATOR.

7-1-5. TEMPORARY FLIGHT RESTRICTIONS

a. 49 U.S.C. section 44812

EXAMPLE-

!FDC y/nnnn (ARTCC ID) (state code)..AIRSPACE (city/location, state)..TEMPORARY FLIGHT RESTRICTIONS PURSUANT TO 49 U.S.C. SECTION 44812 AS AMENDED BY SECTION 935 OF THE FAA REAUTHORIZATION ACT OF 2024 FOR PROTECTION OF LARGE PUBLIC GATHERINGS. UAS FLT OPS ARE PROHIBITED WI AN AREA DEFINED AS (XNM) RADIUS OF (Centerpoint L/L) (Fix/Radial/Distance) (altitude, ex, SFC-400FT) AGL. UAS OPS FOR OPERATIONAL, SAFETY, SECURITY, OR COMPLIANCE OVERSIGHT PURPOSES MUST APPLY FOR AUTH VIA EMAIL AT (SERVICE CENTER). (ATC Facility Name/ATC Facility ID/ATC Facility Type) TEL (XXX-XXX-XXXX) IS THE FAA CDN FAC. (schedule, if needed) (YYMMDDHHMM)-(YYMMDDHHMM)

b. 14 CFR section 91.137

EXAMPLE-

!FDC y/nnnn (ARTCC ID) (state code)..AIRSPACE (city/location, state)..TEMPORARY FLIGHT RESTRICTIONS PURSUANT TO TITLE 14 CFR SECTION 91.137(A)(1) WI AN AREA DEFINED AS 10NM RADIUS OF (Centerpoint L/L) (Fix/Radial/Distance) SFC -FL180 (schedule, if needed) (reason) ONLY RELIEF ACFT OPS UNDER DIRECTION OF (agency in charge) ARE AUTH IN THE AIRSPACE (Agency name and telephone number) OR (frequency) IS IN CHARGE OF THE OPS. (Agency name and telephone number) OR (frequency) IS IN CHARGE OF ON SCENE EMERG RESPONSE ACT. (ATC Facility Name/ATC Facility ID/ATC Facility Type) TEL (XXX-XXX-XXXX) IS THE FAA CDN FAC. (schedule, if needed) (YYMMDDHHMM)-(YYMMDDHHMM)

!FDC y/nnnn ZLC MT..AIRSPACE MISSOULA, MT..TEMPORARY FLIGHT RESTRICTIONS PURSUANT TO TITLE 14 CFR SECTION 91.137(A)(2) WI AN AREA DEFINED AS 3NM RADIUS OF 465422N1135521W (MSO076008.6) SFC -10000FT FIRE FIGHTING ACFT OPS. MONTANA DNRC MISSOULA DISPATCH TEL 406 -829 -7070 OR FREQ 133.20/WEST RIVERSIDE FIRE IS IN CHARGE OF THE OPS. SALT LAKE/ZLC/ARTCC TEL 801 -320 -2560 IS THE FAA CDN FAC...

!FDC y/nnnn (ARTCC id) (state code)..AIRSPACE (city/location, state)...TEMPORARY FLIGHT RESTRICTIONS PURSUANT TO TITLE 14 CFR SECTION 91.137(A)(3) WI AN AREA DEFINED AS 5NM RADIUS OF 464996N1140000W (Fix/Radial/Distance) SFC -(upper limit) DLY SR -SS (reason) (Agency and telephone number) OR (frequency) IS IN CHARGE OF THE OPS. (coordination facility)...

c. 14 CFR section 91.141 and section 99.7

EXAMPLE-

!FDC y/nnnn ZHU TX..AIRSPACE CORPUS CHRISTI, TX..TEMPORARY FLIGHT RESTRICTIONS APRIL 4 -5, 20YY LOCAL. PURSUANT TO 49 USC 40103(B) (3)...(remainder of the clause). PURSUANT TO TITLE 14 CFR SECTION 99.7 (plain language text) WI AN AREA DEFINED AS 273437N0970631W (NGP117011.9) TO...(remainder of the description) TO POINT OF ORIGIN 2500FT-17999FT EFFECTIVE YY04041800 (1300 LOCAL 4/4/YY) UNTIL YY04051000 (0500 LOCAL 4/5/YY). WI AN AREA DEFINED AS 15NM EITHER SIDE OF A LINE FM 274022N0971244W (NGP094004.5) TO...(remainder of the description) 1500FT -3500FT EFFECTIVE YY04041800 (1300 LOCAL 4/4/YY) UNTIL YY04051000 (0500 LOCAL 4/5/YY). WI A 4.3NM RADIUS OF 274134N0971725W (NGP025000.4) SFC -3000FT EFFECTIVE YY04041800 (1300 LOCAL 4/4/YY) UNTIL YY04051000 (0500 LOCAL 4/5/YY). HOUSTON/ZHU/ARTCC TEL 281 -230 -5560 IS THE FAA CDN FAC. EXC AS SPECIFIED BELOW

AND/OR UNLESS AUTH BY ATC: 1. ALL ACFT MUST BE ON AN ACTIVE IFR OR FILED VFR FLT PLAN WITH A DISCRETE CODE ASSIGNED BY AN ATC FAC. 2. ACFT MUST BE SQUAWKING THE DISCRETE CODE AT ALL TIMES WHILE IN THE TFR. 3. ALL ACFT ENTERING OR EXITING THE TFR MUST REMAIN IN TWO – WAY RADIO COMMUNICATIONS WITH ATC...

7-1-6. AIR DEFENSE EMERGENCY

EXAMPLE-

/FDC y/nnnn FDC SECURITY AIR DEFENSE EMERGENCY DECLARED THROUGHOUT THE UNITED STATES AND POSSESSIONS. THE EMERGENCY SECURITY CONTROL OF AIR TFC (ESCAT) HAS BEEN IMPLMENTED. UNTIL FURTHER ADZ, NO ACFT WILL BE ALLOWED TO OPR WI THE AIRSPACE OVERLYING THE FOLLOWING AREAS: THE PACIFIC COASTAL ADIZ, THE SOUTHERN BORDER DOMESTIC ADIZ, THE GULF OF AMERICA COASTAL ADIZ, THE ATLANTIC COASTAL ADIZ, THE ALASKAN DOMESTIC ADIZ, THE ALASKAN DEWIZ, THE GUAM COASTAL ADIZ, AND THE HAWAIIAN COASTAL ADIZ UNLESS THE ACFT PROPOSING TO OPR WI THE ABOVE AREAS HAVE A PRIORITY ASSIGNMENT OF “ONE” OR “TWO” IN ACCORDANCE WITH THE WARTIME AIR TFC PRIORITY LIST FOR MOV OF ACFT CONTAINED IN SECTION FIVE OF THE ESCAT PLAN. ALL PILOTS, REGARDLESS OF PRIORITY, CIVIL OR MIL, CHECK WITH THE NEAREST FAA OR MIL OPS FAC TO DETERMINE CURRENT RESTRICTIONS AND OBTAIN AN ATC CLR FROM FAA...

NOTE-

The example FDC NOTAM is for guidance purposes only. Although the information contained in this example could conceivably cover all facets of an emergency, it does not mean that the information contained covers all emergency actions that might be placed into effect by the military when the provisions of the ESCAT are implemented.

7-1-7. SPECIAL DATA

EXAMPLE-

/FDC X/XXXX FDC ... SECURITY ... PILOTS ARE REMINDED... -PERM...

7-1-8. LASER LIGHT ACTIVITY

EXAMPLES-

/FDC y/nnnn (ARTCC id) (state code)..AIRSPACE (city/state)..LASER LGT location identifier DEMONSTRATION WI AN AREA DEFINED AS (description of area) (alternate, if needed) SFC-5000FT (schedule, if needed) LASER LGT BEAM MAY BE INJURIOUS TO PILOT’S/PASSENGER’S EYES WI XXXFT VERTICALLY AND XXXFT LATERALLY OF THE LGT SOURCE. FLASH BLINDNESS OR COCKPIT ILLUMINATION MAY OCCUR BEYOND THESE DISTANCES. (Name of facility)/(id)(type of facility) (telephone number) IS THE FAA CDN FAC...

/FDC y/nnnn (ARTCC id) (state code)... AIRSPACE (city/state)..LASER RESEARCH WI AN AREA DEFINED AS (description of area) (alternate location identifier, if needed) SFC-8000FT (schedule if needed) AT AN ANGLE OF XXXDEG, FM THE SFC, PROJECTING UP TO XXXFT AVOID AIRBORNE HAZARD BY 5NM. THIS BEAM IS INJURIOUS TO PILOT’S/AIRCREW’S AND PASSENGER’S EYES. (Name of facility)/(id)(type of facility) (telephone number) IS THE FAA CDN FAC...

/FDC y/nnnn (ARTCC id) (state code)..AIRSPACE (city/state)..AIRBORNE TO GND LASER ACT WI AN AREA DEFINED AS (latitude/longitude or fix/radial/distance) TO (latitude/longitude or fix/radial/distance) SFC-7000FT AVOID AIRBORNE HAZARD BY 5NM. THIS BEAM IS INJURIOUS TO PILOT’S/AIRCREW’S AND PASSENGER’S EYES. (Name of facility)/(id)(type of facility) (telephone number) IS THE FAA CDN FAC (schedule, if needed)...

8-1-1. INTERNATIONAL NOTAMS

EXAMPLE-

*GG KSEAYFYX
041749 KDZZNAXX
) SVC RQ INT LOC=KZSE NT=A0007/YY
040105 KZSE (A0007/YY) NOTAMN
Q) KZSE/QRRCA/////*
A) KZSE

- B) XX01042100*
- C) XX01050100*
- E) AIRSPACE W460B ACT*
- F) SFC*
- G) 2000FT*

NOTE-

This is an example of the reply after Seattle FSS requested an international NOTAM from the U.S. NOTAM System computer. The request was for Seattle Air Route Traffic Control Center (ARTCC) International NOTAM A0007/YY and received the data from the computer. The NOTAM was issued on January 4 at 0105 UTC. The affected location was Seattle ARTCC (KZSE) with an effective time of January 4 at 2100UTC (B) and good through January 5 at 0100 UTC (C). The condition was that Warning Area W460B will be active during those times stated and for an altitude of surface (F) to 2000 feet MSL (G). There was only one NOTAM found.

Appendix B. International NOTAM (Q) Codes

This appendix is to be used to interpret the contents of coded international NOTAMs. A NOTAM code group contains five letters.

f. The first letter is always the letter “Q” to indicate a code abbreviation for use in the composition of NOTAMs.

g. The second and third letters identify the subject being reported. (See Second and Third Letter Decode Tables).

h. The fourth and fifth letters identify the status of operation of the subject being reported. (See Fourth and Fifth Letter Decode Tables).

Second and Third Letter Decode Tables

ATM Airspace Organization (A)		
Code	Signification	Uniform Abbreviated Phraseology
AA	Minimum altitude (specify en route/crossing/safe)	mnm alt
AC	Class B, C, D, or E Surface Area	ctr
AD	Air defense identification zone	adiz
AE	Control area	cta
AF	Flight information region	fir
AH	Upper control area	uta
AL	Minimum usable flight level	mnm usable fl
AN	Area navigation route	rnav rte
AO	Oceanic control area	oca
AP	Reporting point (specify name or coded designator)	rep
AR	ATS route (specify)	ats route
AT	Terminal control area	tma
AU	Upper flight information region	uir
AV	Upper advisory area	uda
AX	Significant point	sig
AZ	Aerodrome traffic zone	atz

CNS Communications and Surveillance Facilities (C)		
Code	Signification	Uniform Abbreviated Phraseology
CA	Air/ground facility (specify service and frequency)	a/g fac
CB	Automatic dependent surveillance — broadcast (details)	ads-b
CC	Automatic dependent surveillance — contract (details)	ads-c
CD	Controller-pilot data link communications (details)	cpdlc
CE	En route surveillance radar	rsr
CG	Ground controlled approach system (GCA)	gca
CL	Selective calling system (SELCAL)	selcal
CM	Surface movement radar	smr
CP	Precision approach radar (PAR) (specify runway)	par
CR	Surveillance radar element of precision approach radar system (specify wavelength)	sre
CS	Secondary surveillance radar (SSR)	ssr
CT	Terminal area surveillance radar (TAR)	tar

Second and Third Letter Decode Tables (continued)

AGA Facilities and Services (F)		
Code	Signification	Uniform Abbreviated Phraseology
FA	Aerodrome	ad
FB	Friction measuring device (specify type)	Friction measuring device
FC	Ceiling measurement equipment	ceiling measurement eqpt
FD	Docking system (specify AGNIS, BOLDS, etc.)	dckg system
FE	Oxygen (specify type)	oxygen
FF	Fire fighting and rescue	fire and rescue
FG	Ground movement control	gnd mov ctl
FH	Helicopter alighting area/platform	hel alighting area
FI	Aircraft de-icing (specify)	acft de-ice
FJ	Oils (specify type)	oil
FL	Landing direction indicator	ldi
FM	Meteorological service (specify type)	met
FO	Fog dispersal system	fog dispersal
FP	Heliport	heliport
FS	Snow removal equipment	snow removal eqpt
FT	Transmissometer (specify runway and, where applicable, designator(s) of transmissometer(s))	transmissometer
FU	Fuel availability	fuel avbl
FW	Wind direction indicator	wdi
FZ	Customs/immigration	Cust/immigration

CNS GNSS Services (G)		
Code	Signification	Uniform Abbreviated Phraseology
GA	GNSS airfield-specific operations (specify operation)	gnss airfield
GW	GNSS area-wide operations (specify operation)	gnss area

CNS Instrument and Microwave Landing System (I)		
Code	Signification	Uniform Abbreviated Phraseology
IC	Instrument landing system (specify runway)	ils
ID	DME associated with ILS	ils dme
IG	Glide path (ILS) (specify runway)	ils gp
II	Inner marker (ILS) (specify runway)	ils im
IL	Localizer (ILS) (specify runway)	ils loc
IM	Middle marker (ILS) (specify runway)	ils mm
IN	Localizer (not associated with ILS)	loc
IO	Outer marker (ILS) (specify runway)	ils om
IS	ILS Category I (specify runway)	ils cat I
IT	ILS Category II (specify runway)	ils cat II
IU	ILS Category III (specify runway)	ils cat III
IW	Microwave landing system (MLS) (specify runway)	mls
IX	Locator, outer (ILS) (specify runway)	ils lo
IY	Locator, middle (ILS) (specify runway)	ils lm

Second and Third Letter Decode Tables (continued)

AGA Lighting Facilities (L)		
Code	Signification	Uniform Abbreviated Phraseology
LA	Approach lighting system (specify runway and type)	als
LB	Aerodrome beacon	abn
LC	Runway centre line lights (specify runway)	rcll
LD	Landing direction indicator lights	ldi lgt
LE	Runway edge lights (specify runway)	redl
LF	Sequenced flashing lights (specify runway)	sequenced flg lgt
LG	Pilot-controlled lighting	pcl
LH	High intensity runway lights (specify runway)	high intst rwy lgt
LI	Runway end identifier lights (specify runway)	rwy end id lgt
LJ	Runway alignment indicator lights (specify runway)	rai lgt
LK	Category II components of approach lighting system (specify runway)	category II components als
LL	Low intensity runway lights (specify runway)	low intst rwy lgt
LM	Medium intensity runway lights (specify runway)	medium intst rwy lgt
LP	Precision approach path indicator (specify runway)	papi
LR	All landing area lighting facilities	ldg area lgt fac
LS	Stopway lights (specify runway)	stwl
LT	Threshold lights (specify runway)	thr lgt
LU	Helicopter approach path indicator	hapi
LV	Visual approach slope indicator system (specify type and runway)	vasis
LW	Heliport lighting	heliport lgt
LX	Taxiway centre line lights (specify taxiway)	twy cl lgt
LY	Taxiway edge lights (specify taxiway)	twy edge lgt
LZ	Runway touchdown zone lights (specify runway)	rtzl

AGA Movement and Landing Area (M)		
Code	Signification	Uniform Abbreviated Phraseology
MA	Movement area	mov area
MB	Bearing strength (specify part of landing area or movement area)	bearing strength
MC	Clearway (specify runway)	cwy
MD	Declared distances (specify runway)	declared dist
MG	Taxiing guidance system	tg
MH	Runway arresting gear (specify runway)	rag
MK	Parking area	prkg area
MM	Daylight markings (specify threshold, centre line, etc.)	day markings
MN	Apron	apron
MO	Stopbar (specify runway)	rag
MP	Aircraft stands (specify)	acft stand
MR	Runway (specify runway)	rwy
MS	Stopway (specify runway)	swy
MT	Threshold (specify runway)	thr
MU	Runway turning bay (specify runway)	rwy turning bay
MW	Strip/shoulder (specify runway)	Strip/shoulder
MX	Taxiway(s) (specify)	twy
MY	Rapid exit taxiway (specify)	Rapid exit twy

Second and Third Letter Decode Tables (continued)

COM Terminal and En Route Navigation Facilities (N)		
Code	Signification	Uniform Abbreviated Phraseology
NA	All radio navigation facilities (except...)	all rdo nav fac
NB	Nondirectional radio beacon	ndb
NC	DECCA	decca
ND	Distance measuring equipment (DME)	dme
NF	Fan marker	fan mkr
NL	Locator (specify identification)	l
NM	VOR/DME	vor/dme
NN	TACAN	tacan
NO	OMEGA	omega
NT	VORTAC	vortac
NV	VOR	vor

Other Information (O)		
Code	Signification	Uniform Abbreviated Phraseology
OA	Aeronautical information service	ais
OB	Obstacle (specify details)	obst
OE	Aircraft entry requirements	acft entry rqmnts
OL	Obstacle lights on ... (specify)	obst lgt
OR	Rescue coordination centre	rcc

ATM Air Traffic Procedures (P)		
Code	Signification	Uniform Abbreviated Phraseology
PA	Standard instrument arrival (specify route designator)	star
PB	Standard VFR arrival	stc vfr arr
PC	Contingency procedures	contingency proc
PD	Standard instrument departure (specify route designator)	sid
PE	Standard VFR departure	stf vfr dep
PF	Flow control procedure	flow ctl proc
PH	Holding procedure	hldg proc
PI	Instrument approach procedure (specify type and runway)	instr apch proc
PK	VFR approach procedure	vfr apch proc
PL	Flight plan processing (filing and related contingency)	fpl
PM	Aerodrome operating minima (specify procedure and amended minimum)	opr minima
PN	Noise operating restriction	noise opr restrictions
PO	Obstacle clearance altitude and height (specify procedure)	oca och
PR	Radio failure procedure	rdo failure proc
PT	Transition altitude or transition level (specify)	ta/trl
PU	Missed approach procedure (specify runway)	missed apch proc
PX	Minimum holding altitude (specify fix)	mnm hldg alt
PZ	ADIZ procedure	adiz proc

Second and Third Letter Decode Tables (continued)

Navigation Warnings: Airspace Restrictions (R)		
Code	Signification	Uniform Abbreviated Phraseology
RA	Airspace reservation (specify)	airspace reservation
RD	Danger area (specify)	..d..
RM	Military operating area	moa
RO	Overflying of ... (specify)	overflying
RP	Prohibited area (specify)	..p..
RR	Restricted area (specify)	..r..
RT	Temporary restricted area (specify area)	tempo restricted area

ATM Air Traffic and VOLMET Services (S)		
Code	Signification	Uniform Abbreviated Phraseology
SA	Automatic terminal information service	atis
SB	ATS reporting office	aro
SC	Area control centre	acc
SE	Flight information service	fis
SF	Aerodrome flight information service	afis
SL	Flow control centre	flow ctl centre
SO	Oceanic area control centre	oac
SP	Approach control service	app
SS	Flight service station	fss
ST	Aerodrome control tower	twr
SU	Upper area control centre	uac
SV	VOLMET broadcast	volmet
SY	Upper advisory service (specify)	upper advisory ser

Navigation Warnings: Warnings (W)		
Code	Signification	Uniform Abbreviated Phraseology
WA	Air display	air display
WB	Aerobatics	aerobatics
WC	Captive balloon or kite	captive balloon/kite
WD	Demolition of explosives	demolition of explosives
WE	Exercises (specify)	exer
WF	Air refueling	air refueling
WG	Glider flying	gld fly
WH	Blasting	blasting
WJ	Banner/target towing	banner/target towing
WL	Ascent of free balloon	ascent of free balloon
WM	Missile, gun or rocket firing	Missile/gun/rocket/frng
WP	Parachute jumping exercise, paragliding, or hang gliding	Pje/paragliding/hang gliding
WR	Radioactive materials or toxic chemicals (specify)	pje
WS	Burning or blowing gas	burning or blowing gas
WT	Mass movement of aircraft	mass mov of acft
WU	Unmanned aircraft	formation flt
WV	Formation flight	formation flt
WW	Significant volcanic activity	formation flt
WY	Aerial survey	model flying
WZ	Model flying	model flying

Fourth and Fifth Letter Decode Tables

Availability (A)		
Code	Signification	Uniform Abbreviated Phraseology
AC	Withdrawn for maintenance	withdrawn maint
AD	Available for daylight operation	avbl day ops
AF	Flight checked and found reliable	fltck okay
AG	Operating but ground checked only, awaiting flight check	opr but gnd ck only, awaiting fltck
AH	Hours of service are now...(specify)	hr ser
AK	Resumed normal operations	okay
AL	Operative (or reoperative) subject to previously published limitations/conditions	Opr subj previous cond
AM	Military operations only	mil ops only
AN	Available for night operation	avbl night ops
AO	Operational	opr
AP	Available, prior permission required	avbl, ppr
AR	Available on request	avbl o/r
AS	Unserviceable	u/s
AU	Not available (specify reason if appropriate)	not avbl
AW	Completely withdrawn	withdrawn
AX	Previously promulgated shutdown has been canceled	promulgated shutdown cnl

Changes (C)		
Code	Signification	Uniform Abbreviated Phraseology
CA	Activated	act
CC	Completed	cmpl
CD	Deactivated	deactivated
CE	Erected	erected
CF	Operating frequency(ies) changed to	opr freq changed to
CG	Downgraded to	downgraded to
CH	Changed	changed
CI	Identification or radio call sign changed to	Ident/rdo call sign changed to
CL	Realigned	realigned
CM	Displaced	displaced
CN	Canceled	cnl
CO	Operating	opr
CP	Operating on reduced power	opr reduced pwr
CR	Temporarily replaced by	tempo rplcd by
CS	Installed	instl
CT	On test, do not use	on test, do not use

Fourth and Fifth Letter Decode Tables (continued)

Hazard Conditions (H)		
Code	Signification	Uniform Abbreviated Phraseology
HA 1) Poor 2) Medium/Poor 3) Medium 4) Medium/Good 5) Good	Braking action is ...	ba is...
HB	Friction coefficient is ... (specify friction measurement device used)	friction coefficient is
HC	Covered by compacted snow to depth of	cov compacted snow depth
HD	Covered by dry snow to a depth of	cov dry snow depth
HE	Covered by water to a depth of	cov water depth
HF	Totally free of snow and ice	free of sn and ice
HG	Grass cutting in progress	grass cutting inpr
HH	Hazard due to (specify)	hazard due
HI	Covered by ice	cov ice
HJ	Launch planned ... (specify balloon flight identification or project code name, launch site, planned period of launch(es)–date/ time, expected climb direction, estimate time to pass 18 000 m (60 000 ft), or reaching cruise level if at or below 18 000 m (60 000 ft), together with estimated location)	launch plan
HK	Bird migration in progress	bird migration inpr
HL	Snow clearance completed	sn clr cml
HM	Marked by	marked by
HN	Covered by wet snow or slush to a depth of	cov wet sn/slush depth
HO	Obscured by snow	obscured by sn
HP	Snow clearance in progress	sn clr inpr
HQ	Operation canceled ... (specify balloon flight identification or project code name)	opr cnl
HR	Standing water	standing water
HS	Sanding in progress	sanding inpr
HT	Approach according to signal area only	apch according signal
HU	Launch in progress ... (specify balloon flight identification or project code name, launch site, date/time of launch(es), estimated time passing 18 000 m (60 000 ft), or reaching cruising level if at or below 18 000 m (60 000 ft), together with estimated location, estimated date/time of termination of the flight, and planned location of ground contact when applicable)	launch inpr
HV	Work completed	work cml
HW	Work in progress	wip
HX	Concentration of birds	bird concentration
HY	Snow banks exist (specify height)	sn banks hgt
HZ	Covered by frozen ruts and ridges	cov frozen ruts and ridges

Fourth and Fifth Letter Decode Tables (continued)

Limitations (L)		
Code	Signification	Uniform Abbreviated Phraseology
LA	Operating on auxiliary power supply	opr aux pwr
LB	Reserved for aircraft based therein	reserved for acft based therein
LC	Closed	clsd
LD	Unsafe	unsafe
LE	Operating without auxiliary power supply	opr wo aux pwr
LF	Interference from	interference fm
LG	Operating without identification	opr without ident
LH	Unserviceable for aircraft heavier than	u/s acft heavier than
LI	Closed to IFR operations	clsd ifr ops
LK	Operating as a fixed light	opr as f lgt
LL	Usable for length of...and width of...	usable len.../wid...
LN	Closed to all night operations	clsd to all ngt ops
LP	Prohibited to	prohibited to
LR	Aircraft restricted to runways and taxiways	acft restricted to rwy and twy
LS	Subject to interruption	subj intrp
LT	Limited to	ltd to
LV	Closed to VFR operations	clsd vfr ops
LW	Will take place	will take place
LX	Operating but caution advised due to	opr but ctn adz due to

Other (XX)		
Code	Signification	Uniform Abbreviated Phraseology
XX	Where 4th and 5th letter Code does not cover the situation, use XX and supplement by plain language	(plain language following the NOTAM Code)

Appendix C. ICAO Difference for the United States

Below is a listing (not all inclusive) of abbreviations that we use frequently in a domestic NOTAM, but are not recognized ICAO contractions.

ARFF – Airport Rescue and Fire Fighting

ARINC – A system name for CPDLC

ARTCC – Air Route Traffic Control Center

ATCSCC – Air Traffic Control System Command Center

AUNICOM – Automated UNICOM

BC – Back Course

CTAF – Common Traffic Advisory Frequency

FDC – Flight Data Center

FICON – Field Condition

HIRL – High Intensity Runway Light

INFO – Information

LB – Pounds

LIRL – Low Intensity Runway Light

LOM – Compass locator at ILS outer marker

MALSR – Medium-Intensity Approach Lighting System with Runway Alignment Indicator Lights

MIRL – Medium Intensity Runway Lights

MU – Friction value representing runway surface conditions

NA – Not Authorized

ORIG – Original

PRN – Pseudo Random Noise

RVRM – Runway Visual Range Midpoint

RVRR – Runway Visual Range Rollout

RVRT – Runway Visual Range Touchdown

SAA – Special Activity Airspace

SITA – A system name for CPDLC

SSALR – Short Approach Lighting System with Runway Alignment Indicator Lights

TFR – Temporary Flight Restrictions

VASI – Visual Approach Slope Indicator

VOR/DME – Navigational aid

UNICOM – Universal Communication

Appendix D. Miscellaneous Functions

D-1. DOMESTIC NOTICES AND INTERNATIONAL NOTICES

- a. The Domestic Notices are divided into the following:
 1. General Notices.
 2. Special Operations Notices.
 3. Airport and Facility Notices.
 4. Major Sporting and Entertainment Event Notices and other Notices.
 5. Airshow Notices.
- b. The International Notices are divided into two sections:
 1. Section 1: Flight Prohibitions, Potentially Hostile Situations, and Foreign Notices.
 2. Section 2: International Oceanic Airspace Notices.

NOTE-

Domestic Notices and International Notices are submitted to and processed through Mission Support Services, Policy, Publications and Administration via 9-ATOR-HQ-PubGrp@faa.gov. Cutoff dates and requirements for Domestic notices are found at https://www.faa.gov/air_traffic/publications/domesticnotices/. For International Notices refer to https://www.faa.gov/air_traffic/publications/internationalnotices/

D-2. FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFR

- a. Upon receipt of these messages, the watch supervisor, controller-in-charge (CIC), or designated lead specialist (DLS) at the designated flight service station must ensure that the NOTAM is received at each of the remaining facilities.
- b. The watch supervisor, CIC, or DLS of the designated flight service station must be responsible for:
 1. Logging the Presidential, Special Security Instructions, or Emergency Air Traffic Rules FDC NOTAM in the facility log.
 2. Notifying the specialists on duty that a Presidential, Special Security Instructions, or Emergency Air Traffic Rules FDC NOTAM has been issued.
 3. Posting the Presidential, Special security instructions, or Emergency air traffic rules FDC NOTAM in the facility status information area.
 4. As part of the FSS watch checklist, the watch supervisor, CIC, or DLS must check to ensure that every Presidential, Special security instructions, or Emergency air traffic rules FDC NOTAM has been received in the facility.

NOTE-

The purpose of this procedure is to ensure that all flight service specialists are aware of the Presidential, Special security instructions, or Emergency air traffic rules TFR so that pilots are briefed appropriately.

D-3. MILITARY NOTAMS

The NS transmits a list of FDC NOTAM numbers issued during the previous 24 hours. The NS transmits the list between 1715 and 1745 UTC.

- a. Military Functions

1. MILITARY FACILITIES

NOTAMs pertaining to U.S. Air Force, Army, and Navy navigational aids that are part of the NAS must be disseminated.

2. SUBMISSION OF MILITARY DATA FOR PUBLICATION

Military aeronautical data affecting FAA publications must be submitted to the FAA through the responsible military authority.

3. MILITARY NOTAMs

Department of Defense (DOD) NOTAMs are stored in the FAA NOTAM database. Most of these facilities are assigned to a tie-in FSS for NOTAM purposes.

NOTE-

Some Army airfields are not assigned to a tie-in FSS. Army aeronautical data and NOTAMs are not necessarily published in FAA publications. Publication of NOTAM data in the DOD FLIP is justification for NOTAM cancellation.

4. ALASKAN MILITARY NOTAMs

Select Alaskan military facility NOTAMs may be disseminated in the FAA NOTAM system via the tie-in FSS. The military base operations must transmit NOTAM data into the Department of Defense Aeronautical Information Portal (DAIP) and, at a minimum, coordinate with tie-in FSS.

5. MILITARY NOTAM AVAILABILITY

(a) All military NOTAMs are stored in the NS data base. While current, they may be retrieved by both AFTN subscribers and FAA facilities via request/reply.

(b) Refer to the DOD Flight Information Publication (EN Route), IFR, or VFR Supplements to determine whether NOTAM service is provided for a facility.

(c) Military NOTAMs are entered in the military system using the following NOTAM format:

EXAMPLE-

281131 KLTS
 NOTAMN M0719/ YY
 Q) ZFW/QMXLC/IV/NBO/A/000/999/3439N09916W005
 A) KLTS
 B) YY 08071256
 C) YY 10302359
 E) TWY C BTN TWY G AND TWY B CLSD

NOTE-

Refer to ICAO 8126 for international NOTAM (Q) codes. The DOD may supplement ICAO NOTAM (Q) codes based on military necessity.

D-4. SATELLITE BASED SYSTEMS

Use standard request/reply procedures to obtain all current GPS NOTAMs.

EXAMPLE-

GG KDZZNAXX
 DDHHMM KDCAYFYX
)SVC RQ DOM LOC (or ACC)=GPS
 OR
 GG KDZZNAXX
 DDHHMM KDCAYFYX
)SVC RQ INT LOC (or ACC)=KNMH

Appendix E. Computer Functions

Flight Services Computer Functions

E-1. CONFIRMING ACCEPTANCE BY THE NOTAM SYSTEM

- a. When a new NOTAM is accepted into the NOTAM file, a copy of the NOTAM with the NOTAM number will be returned back to the originating facility.
- b. If the NOTAM is rejected, an NS-generated service message will be relayed back to the facility of origin indicating the reason for rejection as shown in paragraph 4-5-2, NOTAM Service Messages.

E-2. TRANSMISSION BY ANOTHER FACILITY

When unable to transmit a NOTAM directly into the system due to equipment failure or other situation, relay the information to an FSS and request that the data be transmitted into the system.

E-3. CANCELLATION OF NOTAMS

To cancel a NOTAM, use the same NOTAM/serial number assigned to the original NOTAM by the NS computer, preceded by the letter "C." If the serial number of a NOTAM cancellation is invalid (number not in a master file), no action is taken within the NOTAM system. A cancellation must receive the same dissemination as the NOTAM it cancels. Do not carry the NOTAM text in the cancellation.

EXAMPLE-
!ABC C05/005

E-4. MONITORING

- a. All input transmissions from a facility are monitored by the NS computer for the presence of an ADP code. The validity of the station identifier, format, and times are also checked before the NS computer assigns a number and updates the NOTAM master file.
- b. Errors in the station identifier or the format will result in a computer-generated service message being sent to the facility of origin. (See paragraph 4-5-2 for examples). The service message will identify the NOTAM parameter which was in error. A rejection (R) requires corrective action as soon as possible.

E-5. NOTAM SERVICE MESSAGES

If data is entered incorrectly, it will be rejected. Each rejection will be preceded with a service message (SVC) explaining the cause for the rejection.

E-6. RETRIEVING FDC NOTAMS

- a. Upon issuance, all FDC NOTAMS are given all circuit distribution and are stored in the NS. FDC NOTAMS remain in the NS for the duration of their validity.
- b. FDC NOTAMS may be retrieved via request/reply. To minimize response delays, each FDC NOTAM should be requested individually.

1. To retrieve an individual FDC NOTAM by number:

- (a) When the location identifier and number are known:

EXAMPLE-
AIS:
GG KDZZNAXX

DDHHMM KFODYFYX
)SVC RQ FDC LOC=CID NT=Y/2735

(b) When only the number is known:

EXAMPLE-
 GG KDZZNAXX
 DDHHMM KFODYFYX
)SVC RQ FDC NT=Y/2735

2. To request all FDC NOTAMs for a given location:

EXAMPLE-
 GG KDZZNAXX DDHHMM KCOUYFYX
)SVC RQ FDC LOC=MCI

NOTE-
 All facilities must use their particular equipment's keyboard equivalent of the closed parenthesis or equal symbol as appropriate.

E-7. RETRIEVING MILITARY NOTAMS

Formats for retrieving military NOTAMS via NADIN are as follows:

a. A request for a single NOTAM for a given location:

EXAMPLE-
 SVC B:
 GG KDZZNAXX
 DDHHMM KDCAIFYX
)SVC RQ MIL ACC=KADW NT= M0134/YY

b. A request for all military NOTAMs for a given location:

EXAMPLE-
 SVC B:
 GG KDZZNAXX
 DDHHMM KSJTYFYX
)SVC RQ MIL LOC=KNGP

c. A request for all military NOTAMs for multiple locations (maximum of eight):

EXAMPLE-
 SVC B:
 GG KDZZNAXX
 DDHHMM KEKNYFYX
)SVC RQ MIL LOC= KADW,KDAA,KNGP,KNGU,KNUW,KHST,KHIF

NOTE-
 All facilities must use their particular equipment's keyboard equivalent of the closed parenthesis or equal symbol as appropriate.

d. To review all NOTAMs for a joint-use airport (for example, CHS), both civil (CHS) and military (KCHS) NOTAMs must be retrieved.

e. To request all NOTAMs for a given location from all files (domestic, FDC, international, and military) that meets the military NOTAM criteria:

EXAMPLE-
 SVC B:
 GG KDZZNAXX
 DDHHMM KEKNYFYX
)SVC RQ MIL LOC= KADW

E-8. SERVICE MESSAGES

a. Receipt of the NS generated service message “NOTAMS FOUND 0” indicates that there are no military NOTAMS on file for the number or location requested.

b. The following is an example of a receipt of the NS cancellation of a military NOTAM.

EXAMPLE-

SVC B:
GG KDZZNAXX
DDHHMM KADW
MYYYY/YY NOTAMC M0142/YY
B) KADW

c. Formats for retrieving international NOTAMS via NADIN are as follows:

1. A request for a single NOTAM for a given accountability identifier:

EXAMPLE-

SVC B:
GG KDZZNAXX
042100 KDCAYFYX
)SVC RQ INT ACC= MYNNYNYX NT=A0211/YY
Reply:
GG KDCAYFYX 042105 KDZZNAXX
)SVC RQ INT ACC= MYNNYNYX NT=A0211/YY
181906 MYNNYNYX
A0211/YY NOTAMN
Q) MYNA/QMRLC/IV/NBO/A/000/999/ 2502N07728W005
A) MYNN
B) YY 11181730
C) PERM
E) RWY 05 CLSD TO BOTH LDG AND DEP ACFT BUT MAY BE USED FOR TAX.

NOTE-

The Bahamas International NOTAM office issued a new NOTAM numbered A0211 and it was the 211th NOTAM issued for 2013. This NOTAM affected Nassau International Airport (MYNN) with a start time of November 18, 2013, at 1730 UTC and will be permanent. The condition is that Runway 5 is closed to both landing and departing aircraft but may be used for taxiing.

2. A request for all international NOTAMS for a given location:

EXAMPLE-

SVC B:
GG KDZZNAXX
DDHHMM KDCAYFYX
)SVC RQ INT LOC=CYUL

3. A request for a single international NOTAM issued in the KFDC series:

EXAMPLE-

SVC B:
GG KDZZNAXX
DDHHMM KDCAYFYX
)SVC RQ INT ACC=KFDC NT=A0174/YY

4. A request for a single oceanic airspace NOTAM for a given domestic ARTCC:

EXAMPLE-

SVC B:
GG KDZZNAXX
DDHHMM KDCAYFYX
)SVC RQ INT ACC=KZNY NT=A0135/YY

5. A request for all oceanic airspace NOTAMs for a given domestic ARTCC:

EXAMPLE-

SVC B:
GG KDZZNAXX
DDHHMM KDCAYFYX
)SVC RQ INT LOC=KZNY

6. A request for multiple international locations: (separated by a comma with no spaces)

EXAMPLE-

SVC B:
GG KDZZNAXX
DDHHMM KDCAYFYX
)SVC RQ INT LOC=EGGN,EDDF,LIIA,EGPX,SBRJ,MYNN,MKJ

E-9. NS-GENERATED SERVICE MESSAGES

a. Receipt of the message "NOTAMS FOUND 0" indicates that there are no international NOTAMs on file for the number or location requested.

- b. The following is an example of a receipt of the NS cancellation of an international NOTAM.

EXAMPLE-

SVC B:
GG KDZZNAXX
DDHHMM KDEN
FNNNN/YY NOTAMC ANNNN/YY
A) KDEN
B) YMMDDHHMM
C)
F) ILS RWY 34R U/S CANCELLED

E-10. REQUEST FOR CANADIAN NOTAMs FROM THE CANADIAN NOTAM SYSTEM

- a. The following is the format for the request/reply message to the Canadian system:

EXAMPLE-

Request:
GG CYZZQQNI
151245 KDCAYFYX NOTAMQ CYXS
Reply:
GG KDCAYFYX 151248 CYHQYNYN
RE NOTAMQ 151245 KDCAYFYX

- SUMMARY CYXS 01151248 -

000019 NOTAMN CYXS PRINCE GEORGE CYXS NDB X 260 U/S TIL YY01151845
000022 NOTAMN CYXS PRINCE GEORGE CYXS ILS U/S YY01182100 TIL YY01192100
000023 NOTAMN CYXS PRINCE GEORGE FUEL UNAVAILABLE
- END OF SUMMARY -

NOTE-

The maximum number of locations that may be requested is 4; for example, NOTAMQ CYUL CYXE CYYT CYYC.

INDEX

[References are to page numbers]

A

Accountable Organizations, 1-3-1
ADDRESSING CORRESPONDENCE, 2-1-3
AERODROME FACILITIES, 5-1-11, Appendix A-7
Aeronautical Information Services, 2-1-1
Aeronautical Information System, 2-1-1
AIR DEFENSE EMERGENCY, Appendix A-25
AIR TRAFFIC ORGANIZATION (ATO), 1-3-1
AIRPORT MANAGEMENT, 1-3-3
Airspace, 6-1-1
AIRSPACE AND ALTITUDE RESERVATIONS, 6-1-2, Appendix A-20
Airspace NOTAMs, 6-1-1
Airspace NOTAM Requiring Authorization/Waiver, 6-1-3, Appendix A-20
APRON IDENTIFICATION, 3-3-3
AREA IMPACTED TABLES, 6-1-4
AVOIDANCE OF DUPLICATION, 1-2-2

C

CANADIAN NOTAMs, REQUESTS, 8-2-1
Canceling/Extending NOTAMs, 4-3-1
CANCELATION OF NOTAMs, 4-3-1, Appendix E-1
Cancellation/Expiration, 7-2-1
CANCELING PUBLISHED NOTAM DATA, 4-3-1
CARDINAL DIRECTIONS, 3-3-4
CHANGES TO PUBLISHED SERVICES, 5-5-1, Appendix A-15
CHART/PUBLICATION ERRORS OR OMISSIONS, 2-1-2
COMMUNICATION NOTAM Format, 5-4-1, Appendix A-16
Communications NOTAMs, 5-4-1
Computer Functions, Appendix E-1
COMPUTER PRINTOUTS, 2-1-3
CONFIRMING ACCEPTANCE BY THE NOTAM SYSTEM, Appendix E-1
COORDINATION WITH OTHER FACILITIES, 3-2-1

D

DEFINITIONS, 1-4-1

[References are to page numbers]

DEPARTMENT OF DEFENSE AIRFIELD MANAGEMENT, 1-3-4
 DISSEMINATION OF AIRMEN INFORMATION, 2-1-1
 DOMESTIC NOTICES, 2-1-2, Appendix D-1
 Duration of NOTAM, 3-1-4

E

Examples, Appendix A-1
 EXPRESSION OF TIME IN THE NOTAM SYSTEM, 3-3-1
 EXTENDING NOTAM VALIDITY, 4-3-1

F

FDC NOTAM EXPIRATION/CANCELLATION, 7-2-1
 FDC NOTAMs, 7-1-1
 AIR DEFENSE EMERGENCY, 7-1-7
 FDC NOTAM LIST, 7-1-7
 GENERAL, 7-1-1
 HIGH BAROMETRIC PRESSURE WARNING, 7-1-6
 INSTRUMENT IFR FLIGHT PROCEDURES, 7-1-2
 LASER LIGHT ACTIVITY, 7-1-7
 RETRIEVING FDC NOTAMs, 7-1-8
 TEMPORARY FLIGHT RESTRICTIONS, 7-1-6
 TEMPORARY OR PERMANENT, 7-1-1
 FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFR,
 3-1-1, 3-1-2, Appendix D-1
 FIELD CONDITIONS (FICON) REPORTING, 5-1-4
 FIELD CONDITIONS REPORTING, Appendix A-4
 FILING NOTAM INFORMATION WITH FSSs, 3-2-1
 FLIGHT STANDARDS SERVICE, 1-3-3
 FORWARDING DATA, 2-1-2

G

General Operating Procedures, 3-1-1

H

HANDLING REPORTED AERODROME CONDITIONS, 5-1-1, Appendix A-1
 HIGH BAROMETRIC PRESSURE WARNING, Appendix A-24
 HOURS OF OPERATION, 5-3-8, 5-5-1, Appendix A-16
 HOURS OF OPERATION (NAVAID), Appendix A-16

I

ICAO Difference for the United States, Appendix C-1

[References are to page numbers]

IFR FLIGHT PROCEDURES, Appendix A-21
 INSTRUMENT LANDING SYSTEM (ILS) STATUS, Appendix A-12
 INSTRUMENT LANDING SYSTEM STATUS, 5-3-1
 International NOTAM (Q) Codes, Appendix B-1
 INTERNATIONAL NOTAMs, 8-1-1, Appendix A-25
 DATA FORMAT, 8-1-1
 INTERNATIONAL NOTICES, 2-1-2, Appendix D-1

L

LASER LIGHT ACTIVITY, Appendix A-25
 Lighting Aids, 5-2-1
 LIGHTING AIDS, 5-2-1, Appendix A-9

M

MANUAL CHANGES, 1-4-1
 MICROBURST/WINDSHEAR DETECTION SYSTEM, 5-5-3, Appendix A-19
 MILITARY NOTAMs, 3-1-2, Appendix D-2
 Miscellaneous Functions, Appendix D-1
 MONITORING, Appendix E-1
 MOVEMENT AREA, Appendix A-1
 MOVEMENT AREA INFORMATION, 5-1-1
 Movement Area NOTAMs, 5-1-1

N

NAVAID CONDITIONS, 5-3-2, Appendix A-11
 NAVAID MAINTENANCE SHUTDOWNS, 5-3-1
 NAVAID CONDITIONS, 5-3-2
 NON-FEDERAL FACILITIES, 1-3-3
 NOTAM ACCOUNTABILITY, 4-2-4
 NOTAM COMPOSITION, 4-2-1
 NOTAM Criteria, 5-1-1
 NOTAM D Procedures, 4-1-1
 NOTAM LOG, 3-2-1
 NOTAM RESPONSIBILITIES, 3-1-1
 NOTAM SERVICE MESSAGES, Appendix E-1
 NS-GENERATED SERVICE MESSAGES, Appendix E-4
 NWS RADIOSONDE BALLOON RELEASES, Appendix F-1

[References are to page numbers]**O**

OBSTACLES, 5-2-2, Appendix A-11
OFFICE OF AIRPORT SAFETY AND STANDARDS, 1-3-3
ORIGINATORS OF AERODROME NOTAMs, 5-1-1

P

PASSING NOTAM DATA BY PART-TIME FSS FACILITIES, 3-2-1
Preparing NOTAMs for Dissemination, 4-2-1
PROCEDURAL APPLICATIONS, 1-2-2
Procedures For Canadian NOTAMs, 8-2-1
PUBLICATION CRITERIA, 2-1-1
PURPOSE, 1-2-1

R

RADAR SERVICES, 5-5-3, Appendix A-19
Radiosonde/Unmanned Free Balloon Flights, Appendix F-1
REPORTING NAVAID MALFUNCTIONS, 5-3-1
REQUEST FOR CANADIAN NOTAMs FROM THE CANADIAN NOTAM SYSTEM, Appendix E-4
RETRIEVING FDC NOTAMs, Appendix E-1
RETRIEVING MILITARY NOTAMs, Appendix E-2
RNP. *See* Required Navigation Performance
RUNWAY IDENTIFICATION, 3-3-2

S

SATELLITE BASED SYSTEMS, 5-3-7, Appendix A-14, Appendix D-3
SERVICE MESSAGES, Appendix E-3
Services NOTAMs, 5-5-1
SPECIAL ACTIVITY AIRSPACE (SAA), 6-1-1, Appendix A-19
SPECIAL AERIAL REFUELING, 6-1-2, Appendix A-20
SPECIAL DATA, 7-1-7, Appendix A-25
STANDARD NOTAM PHRASES, 3-3-4
SURFACE AREA AIRSPACE, 6-1-4

T

TAXIWAY IDENTIFICATION, 3-3-2

[References are to page numbers]

TECHNICAL OPERATIONS, 1-3-2

Technical Operations Reference Chart, Appendix G-1

TEMPORARY FLIGHT RESTRICTIONS, Appendix A-24

Terms of Reference, 1-4-1

THE NATIONAL FLIGHT DATA DIGEST (NFDD), 2-1-3

TRANSMISSION BY ANOTHER FACILITY, Appendix E-1

Transmitting FDC NOTAM Data, 7-1-1

U

U.S. NOTAM OFFICE RELATIONSHIPS, 4-1-1

UNITS OF MEASUREMENT, 3-3-1

UNMONITORED NAVAIDS, 5-3-1

UNPROGRAMMED EXTENDED SHUTDOWNS, 5-3-1

USE OF CONTRACTIONS AND ABBREVIATIONS, 3-3-1

USE OF VIRGULE (/), 3-3-2

W

WEATHER AND WEATHER REPORTING EQUIPMENT, 5-5-2, Appendix A-18

WORK IN PROGRESS, 5-1-12, Appendix A-8

BRIEFING GUIDE



**U.S. DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION**

**Initiated By: AJV-0
Vice President, Mission Support Services**

Table of Contents

Paragraph Number	Title	Page
SUBJ	NOTICE TO AIRMEN (NOTAM)	BG-5
1-1-7	RECOMMENDATION FOR PROCEDURAL CHANGES	BG-5
1-1-9	RELATED PUBLICATIONS	BG-5
1-2-1	PURPOSE	BG-5
1-3-1	AIR TRAFFIC ORGANIZATION (ATO)	BG-5
1-3-3	FLIGHT STANDARDS SERVICE	BG-5
1-3-7	DEPARTMENT OF DEFENSE AIRFIELD MANAGEMENT	BG-5
1-4-6	DEFINITIONS	BG-5
3-1-1	NOTAM RESPONSIBILITIES	BG-5
3-1-4	DURATION OF NOTAM	BG-5
3-2-3	NOTAM LOG	BG-5
3-3-3	UNITS OF MEASUREMENT	BG-5
3-3-5	RUNWAY IDENTIFICATIONS	BG-5
4-1-1	NOTAM OFFICE RELATIONSHIPS	BG-5
4-2-1	NOTAM COMPOSITION	BG-5
4-3-3	CANCELLING PUBLISHED NOTAM DATA	BG-5
5-1-3	MOVEMENT AREA INFORMATION	BG-5
5-1-4	FIELD CONDITIONS (FICON) REPORTING	BG-5
5-1-6	WORK IN PROGRESS	BG-5
5-2-1	LIGHTING AIDS	BG-5
5-2-2	OBSTACLES	BG-5
5-3-6	INSTRUMENT LANDING SYSTEM STATUS	BG-5
5-3-7	NAVAID CONDITIONS	BG-5
5-3-8	SATELLITE BASED SYSTEMS	BG-5
5-4-3	COMMUNICATIONS NOTAM FORMAT	BG-5
5-5-2	CHANGES TO PUBLISHED SERVICES	BG-5
5-5-3	HOURS OF OPERATION	BG-5
5-5-4	WEATHER AND WEATHER REPORTING EQUIPMENT	BG-5
6-1-1	AIRSPACE NOTAM FORMAT	BG-5
6-1-2	SPECIAL ACTIVITY AIRSPACE	BG-5
6-1-3	AIRSPACE AND ALTITUDE RESERVATIONS	BG-5
6-1-5	AIRSPACE NOTAM REQUIRING AUTHORIZATION/WAIVER	BG-5
6-1-6	SURFACE AREA AIRSPACE	BG-5
7-1-3	INSTRUMENT FLIGHT PROCEDURES	BG-5
7-1-4	HIGH BAROMETRIC PRESSURE WARNING	BG-5

7-1-5	TEMPORARY FLIGHT RESTRICTIONS	BG-5
7-1-8	LASER LIGHT ACTIVITY	BG-5
8-1-1	INTERNATIONAL NOTAMs	BG-5
8-1-2	INTERNATIONAL NOTAM DATA FORMAT	BG-5
8-2-1	REQUEST FOR CANADIAN NOTAMs FROM THE CANADIAN NOTAM SYSTEM	BG-5
Appendix A. 5-1-3	MOVEMENT AREA	BG-42
Appendix A. 5-1-4	FIELD CONDITIONS REPORTING	BG-42
Appendix A. 5-1-5	AERODROME FACILITIES	BG-42
Appendix A. 5-2-1	LIGHTING AIDS	BG-42
Appendix A. 5-2-2	OBSTACLES	BG-42
Appendix A. 5-3-7	NAVAID CONDITIONS	BG-42
Appendix A. 5-3-8	SATELLITE BASED SYSTEMS	BG-42
Appendix A. 5-4-3	COMMUNICATION NOTAM FORMAT	BG-42
Appendix A. 5-5-1	GENERAL	BG-42
Appendix A. 5-5-2	CHANGES TO PUBLISHED SERVICES	BG-42
Appendix A. 5-5-3	HOURS OF OPERATION	BG-42
Appendix A. 5-5-4	WEATHER AND WEATHER REPORTING EQUIPMENT	BG-42
Appendix A. 6-1-1	AIRSPACE NOTAM FORMAT	BG-42
Appendix A. 6-1-2	SPECIAL ACTIVITY AIRSPACE	BG-42
Appendix A. 6-1-3	AIRSPACE AND ALTITUDE RESERVATIONS	BG-42
Appendix A. 6-1-4	SPECIAL AERIAL REFUELING	BG-42
Appendix A. 6-1-5	AIRSPACE NOTAMS REQUIRING AUTHORIZATION/WAIVER	BG-42
Appendix A. 6-1-6	SURFACE AREA AIRSPACE	BG-42
Appendix A. 7-1-4	HIGH BAROMETRIC PRESSURE WARNING	BG-42

Appendix A. 7-1-7	SPECIAL DATA	BG-42
Appendix C.	ICAO DIFFERENCES FOR THE UNITED STATES	BG-42
Appendix F.	RADIOSONDE/UNMANNED FREE BALLOON FLIGHTS	BG-42
Appendix G.	TECHNICAL OPERATIONS REFERENCE CHART	BG-42

1. PARAGRAPH NUMBER AND TITLE:

SUBJ: NOTICE TO AIR MISSIONS

1-3-7. DEPARTMENT OF DEFENSE AIRFIELD MANAGEMENT

2. BACKGROUND: Effective with GENOT 25/02 N 7930.114, the term Notice to Air Missions (NOTAM) was changed to Notice to Airmen (NOTAM), and the title of FAA Order JO 7930.2 was changed to “Notice to Airmen (NOTAM).”

OLDSUBJ: Notice to Air Missions (NOTAM)**OLD**

**1-3-7. DEPARTMENT OF DEFENSE
AIRFIELD MANAGEMENT**

Specific military airport management responsibilities are outlined in Air Force Instruction Interservice Publication 11-208/AR 95-10/OP-NAVINST 3721.20, DoD Notice to Air Missions (NOTAM) System.

NEWSUBJ: Notice to Airmen (NOTAM)**NEW**

**1-3-7. DEPARTMENT OF DEFENSE
AIRFIELD MANAGEMENT**

Specific military airport management responsibilities are outlined in Air Force Instruction Interservice Publication 11-208/AR 95-10/OP-NAVINST 3721.20, DoD Notice to Airmen (NOTAM) System.

1. PARAGRAPH NUMBER AND TITLE:

1-1-7. RECOMMENDATION FOR PROCEDURAL CHANGES

1-1-9. RELATED PUBLICATIONS

1-2-1. PURPOSE

1-3-1. AIR TRAFFIC ORGANIZATION (ATO)

1-3-3. FLIGHT STANDARDS SERVICE

1-4-6. DEFINITIONS

3-1-1. NOTAM RESPONSIBILITIES

3-1-4. DURATION OF NOTAM

3-1-4. PERMANENT (PERM) NOTAM PROCESS

3-2-3. NOTAM LOG

3-3-3. UNITS OF MEASUREMENT

3-3-5. RUNWAY IDENTIFICATION

4-1-1. U.S. NOTAM OFFICE RELATIONSHIPS

4-2-1. NOTAM COMPOSITION

4-3-3. CANCELLING PUBLISHED NOTAM DATA

5-1-3. MOVEMENT AREA INFORMATION

5-1-4. FIELD CONDITIONS (FICON) REPORTING

5-1-6. WORK IN PROGRESS

5-2-1. LIGHTING AIDS

5-2-2. OBSTACLES

5-3-6. INSTRUMENT LANDING SYSTEM STATUS

5-3-7. NAVAID CONDITIONS

5-3-8. SATELLITE BASED SYSTEMS

5-4-3. COMMUNICATION OUTLET CONDITION

- 5-5-2. CHANGES TO PUBLISHED SERVICES
- 5-5-3. HOURS OF OPERATION
- 5-5-4. WEATHER AND WEATHER REPORTING EQUIPMENT
- 6-1-1. AIRSPACE NOTAM FORMAT
- 6-1-2. SPECIAL ACTIVITY AIRSPACE (SAA)
- 6-1-3. AIRSPACE AND ALTITUDE RESERVATIONS
- 6-1-5. OTHER AIRSPACE NOTAMS
- 6-1-6. SURFACE AREA AIRSPACE
- 7-1-3. INSTRUMENT IFR FLIGHT PROCEDURES
- 7-1-4. HIGH BAROMETRIC PRESSURE WARNINGS
- 7-1-5. TEMPORARY FLIGHT RESTRICTIONS
- 7-1-8. LASER LIGHT ACTIVITY
- 8-1-1. INTERNATIONAL NOTAMS
- 8-1-2. INTERNATIONAL NOTAM DATA FORMAT
- 8-2-1. REQUEST FOR CANADIAN NOTAMS FROM THE CANADIAN NOTAM SYSTEM

2. BACKGROUND: This change is an extensive update to the order that includes multiple amendments and corrections. This change is necessary to better align the Notice to Airmen (NOTAM) order with the International Civil Aviation Organization (ICAO) Standards and Recommended Practices (SARP), including duration of a NOTAM and publication of information. This update starts to address Safety Risk Management Panel (SRMP) recommendations on NOTAM numbering rollover when the FAA implements ICAO NOTAM format. This change adds definitions to clarify use of NOTAM terms and limits use of a Pointer NOTAM, and identifies the office responsible for issuance. Amended the format of a commissioning of a movement area per stakeholders' request by adding location and option to add pavement classification rating. Organized presentation of policy for lighting aids, communication, and airspace. Updated policy on collection of information of accountable organization for airspace users to deconflict airspace for air traffic and U.S. Forestry Service.

3. CHANGE:

<u>OLD</u>	<u>NEW</u>
<p>1-1-7. RECOMMENDATION FOR PROCEDURAL CHANGES</p> <p style="text-align: center;">a through b1</p> <p>2. Recommendations from other sources should be submitted through appropriate FAA, military, or industry/user channels.</p>	<p>1-1-7. RECOMMENDATION FOR PROCEDURAL CHANGES</p> <p style="text-align: center;">No Change</p> <p>2. Recommendations <u>for changes or requests for waivers to policy</u> from other sources should be submitted through appropriate FAA, military, or industry/user channels.</p>
<p style="text-align: center;"><u>OLD</u></p> <p>1-1-9. RELATED PUBLICATIONS</p> <p style="text-align: center;">Title through FAA Order 8260.19, <i>Flight Procedures and Airspace</i></p> <p style="text-align: center;">Add</p> <p style="text-align: center;">Add</p>	<p style="text-align: center;"><u>NEW</u></p> <p>1-1-9. RELATED PUBLICATIONS</p> <p style="text-align: center;">No Change</p> <ul style="list-style-type: none"> • <u>FAA Order 8260.46, <i>Departure Procedure (DP) Program</i></u> • <u>FAA Order 8260.58, <i>United States Standard for Performance Based Navigation (PBN) Instrument Procedure Design</i></u>

FAA Order 8400.13 through FAA Order 6750.24

No Change

Add

- FAA Order JO 6500.28, Radio Communications Requirements for Air Traffic Control Facilities

Add

- FAA Order JO 6850.5, Maintenance of Lighted Navigational Aids

14 CFR Parts through Advisory Circular (AC) 99-1 Emergency Security Control of Air Traffic (ESCAT)

No Change

Advisory Circular (AC) 150/5200-28, Notices to Air Missions (NOTAMs) for Airport Operators

Advisory Circular (AC) 150/5200-28, Notice to Airmen (NOTAM) for Airport Operators

OLD

NEW

1-2-1. PURPOSE

1-2-1. PURPOSE

Authorized personnel assigned to facilities that collect, originate, and/or disseminate NOTAMs must be familiar with the provisions of this order that pertain to their operational responsibilities.

No Change

a. The United States NOTAM Office (USNOF) is the final authority on NOTAM formatting. Candidate NOTAMs submitted through the NOTAM System (NS) must be in the proper format. To ensure NOTAMs are issued in accordance with NOTAM policy, NOTAM originators must comply with USNOF personnel directions.

a. The United States NOTAM Office (USNOF) is the final authority on NOTAM formatting. **Proposed** NOTAMs submitted through the NOTAM System (NS) must be in the proper format. To ensure NOTAMs are issued in accordance with NOTAM policy, NOTAM originators must comply with USNOF personnel directions.

OLD

NEW

1-3-1. AIR TRAFFIC ORGANIZATION (ATO)

1-3-1. AIR TRAFFIC ORGANIZATION (ATO)

Title through d

No Change

e. FSS specialists are responsible for issuing NOTAMs that are not covered in any example in FAA Order JO 7930.2. If, after consulting with your management, a format cannot be determined, have management contact USNOF for assistance.

e. FSS specialists are responsible for issuing NOTAMs that are not covered in any example in FAA Order 7930.2. If, after consulting with your management, a format cannot be determined, have management contact USNOF for assistance.

f. System Operations Services, Flight Services, has the responsibility to ensure that data submitted complies with the policies, criteria, and formats contained in this order. This responsibility is delegated to the U.S. NOTAM Governance and Operations Group.

f. **The Flight Service Directorate** has the responsibility to ensure that **NOTAM data submitted or approved by FSSs** complies with the policies, criteria, and formats contained in this order.

OLD**1-4-6. DEFINITIONS****Title through l**

m. International NOTAM. The classification of NOTAMs received from other counties and stored in the NS. These NOTAMs are numbered consecutively by accountability, location, and series beginning with S0001 each year, where S stands for a generic series a country may have. The NOTAM number and year of issuance are separated by a forward slash; for example, S0211/YY, S0002/YY.

n through u

v. Out of Service/Unserviceable (U/S). When a piece of equipment, a NAVAID, a facility or a service is not operational, certified (if required) and immediately “available” for air traffic or public use.

w. Pointer NOTAM. NOTAM D issued to point to additional aeronautical information. When pointing to another NOTAM, use the affected facility/location of the original NOTAM. The keyword in the pointer NOTAM must match the keyword in the original NOTAM. If the NOTAM is pointing to a publication, choose the most appropriate keyword for the situation. For example, a pointer NOTAM at a specific airport is used to highlight or “point out” an FDC NOTAM, or additional aeronautical information from the Domestic Notices or Chart Supplement. At the request of an Air Traffic facility, a NOTAM originator, or as deemed necessary by FSS, issue Pointer NOTAMs to highlight events of significance. Pointer NOTAMs should be issued for, but are not limited to, TFRs, Airshows, Temporary SUA, major NAS system interruptions, etc.

x. Prior Permission Required (PPR) means prior permission required to have full operational use of a runway, taxiway, apron, or airport facility/service. Means of communication to the airport can be telephone and/or radio. If PPR and another exception are used in same NOTAM, the PPR should come first.

NEW**1-4-6. DEFINITIONS****No Change**

m. International NOTAM. The classification of NOTAMs received from other countries and stored in the NS. These NOTAMs are numbered consecutively by accountability, location, and series beginning with S0001 each year, where S stands for a generic series a country may have. The NOTAM number and year of issuance are separated by a forward slash; for example, S0211/YY, S0002/YY.

No Change

v. Not Available (NOT AVBL). Defined within the NAS when a facility, equipment, or service is not accessible or is not being provided as published within normal operation.

w. Pointer NOTAM. NOTAM D issued to point to additional aeronautical information. Pointer NOTAM use is limited to pointing to traffic management program alerts (see subparagraph 5-5-3d), TFRs, and temporary special use airspace (SUA). Pointer NOTAMs should not duplicate information already available through wide area dissemination (for example, NOTAM D with affected location of an ARTCC publicizing an ATC closure is available to all airports within ARTCC). Flight Service is the responsible party for issuance of Pointer NOTAMs on behalf of the accountable organization. A pointer NOTAM should only be originated at aerodromes directly impacted by the referenced activity. When pointing to another NOTAM, the keyword in the pointer NOTAM must match the keyword in the original NOTAM followed by the phrase “SEE”. Include the affected location identifier, NOTAM number, and the NOTAM subject of the original NOTAM within the text of the Pointer NOTAM.

No Change

y. Radio Navigation Aid. As used in this policy, the word radio is added further describe those navigation aids such as ILS, LOC, VOR or other NAVAID that is used in assisting the pilot with approaches, departures, and enroute operations.

Add

z through ab

Add

ac through af

OLD

3-1-1. NOTAM RESPONSIBILITIES

a. The certified source (NOTAM originator) that enters the NOTAM data is responsible for classifying, formatting, cancelling, and informing the controlling facility and other facilities/offices affected by the aid, service, or hazard contained in the new NOTAM. Flight Service Stations are exempt from the requirement to inform the controlling facility when an alternate means of coordination is approved by the Flight Service Safety and Operations Group, AJR-B1.

Add

Add

b through e2

3. Identified by the terminal facility as one not meeting the criteria stated in d1 or d2 above; however, has been deemed necessary for the safety of operations (for example, depicted on the radar video map).

y. Proposed NOTAM. A drafted NOTAM that has been submitted by an individual, office, or entity for consideration for publication within the NS to be numbered (previously called a Candidate NOTAM).

z. Radio Navigation Aid. As used in this policy, the word “Radio” is added to further describe navigation aids such as ILS, LOC, VOR or other NAVAIDs that are used in assisting the pilot with approaches, departures, and en route operations.

Re-letter **aa** through **ac**

ad. Unserviceable (U/S). When a piece of equipment, a NAVAID, a facility, or a service is not operational, not certified (if required), and immediately “available” for air traffic or public use.

Re-letter **ae** through **ah**

NEW

3-1-1. NOTAM RESPONSIBILITIES

a. The certified source (NOTAM originator) that enters the NOTAM data is responsible for classifying, formatting, canceling, and informing the controlling facility and other facilities/offices affected by the aid, service, or hazard contained in the new NOTAM.

NOTE-

1. In the contiguous United States (CONUS), Hawaii, Puerto Rico, and Guam, ARTCC Flight Data Units perform required NOTAM coordination. In Alaska, Flight Service performs the required NOTAM coordination.

2. During contingency events or for scheduled out-ages, Flight Service may be directed to perform manual NOTAM coordination for ATC facilities in the CONUS, Hawaii, Puerto Rico and Guam as needed.

No Change

3. Identified by the terminal facility as one not meeting the criteria stated in e1 or e2 above; however, has been deemed necessary for the safety of operations (for example, depicted on the radar video map).

OLD

3-1-4. PERMANENT (PERM) NOTAM PROCESS

a. When a NOTAM is originated for a permanent change to published aeronautical information, “PERM” must be inserted in lieu of a ten-figure date-time group end of validity time. Prior to issuance of a PERM NOTAM, the accountable organization must demonstrate that the publication process has been initiated. The originator is required to enter a temporary NOTAM until they are able to confirm the initiation of the publication process.

b. To submit aeronautical data for publication, go to:
https://www.faa.gov/air_traffic/flight_info/aeronav/aero_data/Submitting_Data/.

OLD

Add

Add

Add

OLD

3-2-3. NOTAM LOG

FSS air traffic managers must ensure that NOTAMs originated by their facility and FDC NOTAMs received must be accounted for as follows:

NEW

3-1-4. DURATION OF NOTAM

NOTAM must only address the time that the activity or condition is taking place. Temporary changes anticipated to last less than three months are considered to be information of short duration, which is distributed by NOTAM. When a temporary change, condition or activity is expected to exceed three months in advance of NOTAM issuance, it is considered to be information of long duration. Consideration should be given for publication of the long duration temporary change of condition until the subject of the NOTAM is returned to normal operation.

Delete

NEW

3-1-5. PERMANENT (PERM) NOTAM PROCESS

a. When a NOTAM is originated for a permanent change to published aeronautical information, “PERM” must be inserted in lieu of a 10-figure date-time group end of validity time. Prior to issuance of a PERM NOTAM, the accountable organization must demonstrate that the publication process has been initiated. The originator is required to enter a temporary NOTAM until they are able to confirm the initiation of the publication process.

**b. To submit aeronautical data for publication, go to:
https://www.faa.gov/air_traffic/flight_info/aeronav/aero_data/Submitting_Data/.**

NEW

3-2-3. NOTAM LOG

No Change

a. Log all NOTAMs on a locally approved form containing at least the same data for each accountability (NOTAM file) location. information to include on the form: month, facility, NOTAM number, condition description, transmitted by/day time group (DTG), and cancelled by/DTG.

b. Incoming FDC NOTAMs and cancellations must be logged on a locally approved form, containing at least the same data. Information to include on the form: FDC NOTAM receipt log, NOTAM number, sending facility, affected facility, number cancelled by, and remarks. The remarks section should contain enough information to identify the location and NAS component affected.

OLD

3-3-3. UNITS OF MEASUREMENT

Specify the unit of measurement in distance, height, altitude, or weight. When using an abbreviation, do not add a space between the measurement and the unit of measurement. At a minimum, latitude must be 6 digits and longitude must be 7 digits.

EXAMPLES-
 500FT
 12500LB
 5NM
 6.2NM
 20MIN
 1HR
 330DEG
 305DME
 402646N0795856W
 402646.25N0795856.95W

OLD

3-3-5. RUNWAY IDENTIFICATION

a. Specify the runway identification as it is published, including the leading zero (0).

b. List the runway identifications in clockwise order beginning from the 1 o'clock position.

a. Log all NOTAMs on a locally approved form containing at least the same data for each accountability (NOTAM file) location. Information to include on the form: month, facility, NOTAM number, condition description, transmitted by/date-time group (DTG), and canceled by/DTG.

b. Incoming FDC NOTAMs and cancellations must be logged on a locally approved form, containing at least the same data. Information to include on the form: FDC NOTAM receipt log, NOTAM number, sending facility, affected facility, number canceled by, and remarks. The remarks section should contain enough information to identify the location and NAS component affected.

NEW

3-3-3. UNITS OF MEASUREMENT

No Change

EXAMPLES-
 500FT
FL320
 12500LB
 5NM
 6.2NM
 20MIN
 1HR
 330DEG
 305DME
 402646N0795856W
 402646.25N0795856.95W

NEW

3-3-5. RUNWAY IDENTIFICATION

No Change

b. List the runway identifications in clockwise order beginning from 010 degrees.

OLD**4-1-1. U.S. NOTAM OFFICE RELATIONSHIPS**

a. The USNOF is charged with monitoring the NS. The USNOF must monitor the NS for compliance with the criteria and procedures set forth in this order. When questions arise on NOTAM dissemination, formats, contractions, or other aspects of the distribution system, the USNOF should be consulted. The USNOF is the authority for NOTAM criteria and formats and ensures that issued NOTAMs are consistent with FAA policy. NOTAM originators and certified sources must comply with USNOF personnel guidance. Discrepancies in procedures or format must be recorded, and Aeronautical Information Services must forward a list of the discrepancies to Flight Services, Safety and Operations Support, Operational Procedures, and the service area office.

OLD**4-2-1. NOTAM COMPOSITION****Title through b8**

9. Lower limit then upper limit, or height, (when needed). Limits must be specified, as:

(a) For SFC, or 1 to 17,999FT with the unit of measurement (AGL or MSL), 50FT, 1275FT AGL, 10500FT.

(b) For 18,000FT and above, express in flight levels (FL), FL180, FL550, FL850, or UNL (altitudes greater than 99,900FT).

(c) Include heights AGL when required (obstacle NOTAMs) or when MSL is not known, for example, SFC-450FT AGL.

b9(d) through b12

NEW**4-1-1. U.S. NOTAM OFFICE RELATIONSHIPS**

a. The USNOF is charged with monitoring the NS. The USNOF must monitor the NS for compliance with the criteria and procedures set forth in this order. When questions arise on NOTAM dissemination, formats, contractions, or other aspects of the distribution system, the USNOF should be consulted. The USNOF is the authority for NOTAM criteria and formats and ensures that issued NOTAMs are consistent with FAA policy. NOTAM originators and certified sources must comply with USNOF personnel guidance. Discrepancies in procedures or format must be recorded, and Aeronautical Information Services must forward a list of the discrepancies **to offices and facilities providing origination or management of NOTAMs.**

NEW**4-2-1. NOTAM COMPOSITION**

No Change

No Change

(a) For SFC, or 1 to 17,999 **feet, include** the unit of measurement (**FT**) (**for example, 50FT, 1275FT AGL, 10500FT**).

(b) For 18,000 **feet** and above, express in flight levels (FL), (**for example, FL180, FL550, FL850, or UNL altitudes greater than 99,900 feet**).

(c) **Feet means mean sea level (MSL) unless otherwise stated, and therefore the reference indication label MSL must not be included after the stated altitude in the NOTAM (for example, 1200FT). When referencing heights above ground level (AGL), include the reference indication label AGL after the stated altitude in the NOTAM (for example, 800FT AGL).** Include heights AGL when required (obstacle NOTAM) or when MSL is not known, for example, SFC-450FT AGL.

No Change

13. Schedule, (when needed). A NOTAM may be originated for a scheduled condition/activity that will occur during the period. Specify the schedule between the condition/activity and the valid time string. The days of the week must be specified before the scheduled time. The term “DLY” (daily) indicates the event will occur each day at the same time during the stated time period. The start time of the schedule must correspond to the start of activity time. The end of the last schedule must correspond to the end of validity time.

EXAMPLES–

DLY 1200–2000 YYMMDD1200–YYMMDD2000
MON WED 0900–1300 YYMMDD0900–YYM-
MDD1300
TUE THU 0900–2000 YYMMDD0900–YYMMDD2000

If the active time of a NOTAM corresponds to sunrise or sunset, the actual times of sunrise on the first day of validity and of sunset on the last day of validity must be used.

FIG 4–2–2

13. Schedule, (when needed). A NOTAM may be originated for a scheduled condition/activity that will occur during the period. Specify the schedule between the condition/activity and the valid time string. The days of the week must be specified before the scheduled time. The term “DLY” (daily) indicates the event will occur each day at the same time during the stated time period. The start time of the schedule must correspond to the start of activity time. The end of the last schedule must correspond to the end of validity time. **If the active time of a NOTAM corresponds to sunrise or sunset, the actual times of sunrise on the first day of validity and of sunset on the last day of validity must be used.**

EXAMPLES–

DLY 1200–2000 YYMMDD1200–YYMMDD2000
MON WED 0900–1300 YYMMDD0900–YYM-
MDD1300
TUE THU 0900–2000 YYMMDD0900–YYMMDD2000
MON 2130–1800 TUE 2330–2000
YYMMDD2130–YYMMDD2000

Delete

No Change


OLD

Add
Add

NEW

FIG 4-2-3

NOTAM Validity



!GNV 12/018 F95 AIRSPACE MIL ACT WI AN AREA DEFINED AS 3NM RADIUS OF F95 SFC-14000FT DLY 2200-0900 YY05142200 - YY05170900

Delete

This military activity occurs Sunday (May 14) between 2200UTC and 0900UTC, again on Monday and again on Tuesday at 2200UTC then ends on Wednesday (May 17) at 0900UTC.

Delete

14. Start of Activity/End of Validity. This is a 10-digit date-time group (YYMMDDHHMM) used to indicate the time at which the NOTAM comes into force (the date/time a condition will exist or begin) and the time at which the NOTAM ceases to be in force and becomes invalid (the expected return to service, return to normal status time, or the time the activity will end). These times must be separated by a hyphen “-.” For example, ...RWY 15 CLSD YY12031400-YY12051359...indicates that runway 15 will close at 1400UTC on December 3rd. It is expected to reopen at 1359 UTC on December 5th.

14. Start of Activity/End of Validity. This is a 10-digit date-time group (YYMMDDHHMM) used to indicate the time at which the NOTAM condition or activity begins and the time at which the NOTAM condition or activity ends (the expected return to service or return to normal status). These times must be separated by a hyphen “-.” For example, ...RWY 15 CLSD YY12031400-YY12051359...indicates that runway 15 will close at 1400UTC on December 3rd. It is expected to reopen at 1359 UTC on December 5th.

b14(a)

No Change

(b) The NOTAM Originator is responsible for validating that any NOTAM that is coming to its End of Validity time can auto-expire. If the condition is still valid, the NOTAM must be canceled and reissued with a new Start/Stop time, PRIOR to the NOTAM reaching its End of Validity time.

b14(c) through b14(d)

(e) For an uncontrolled airport, when a NOTAM originator submits a candidate NOTAM to the NOTAM System to advertise an Airport or Runway condition with a Start of Activity less than 60 minutes before the beginning of an activity that impacts/closes a runway or an airport, the activity must be reported to the Air Traffic Control (ATC) facility that has control jurisdiction.

c through d

e. If information is published elsewhere and is still valid, reference must be made to that publication with the statement, "PLUS SEE (publication)." A NOTAM issued not stating "PLUS SEE (publication)" indicates the NOTAM replaces previously published similar data.

f. NOTAMs must state the abnormal status of a component of the NAS and not the normal status. Exception – Temporarily extending hours of use beyond published times, for example: RWY 09/27 OPN.

OLD

4-3-3. CANCELLING PUBLISHED NOTAM DATA

OLD

5-1-3. MOVEMENT AREA INFORMATION

Title through a

b. Commissioning of a movement area or portions thereof. State the type of surface, length and width of the surface, lighting status, and declared distances.

(b) The **accountable organization** is responsible for validating that any NOTAM that is coming to its End of Validity time can auto-expire. If the condition is still valid, the NOTAM must be canceled and reissued with a new Start/Stop time, PRIOR to the NOTAM reaching its End of Validity time.

No Change

(e) For an uncontrolled airport, when a NOTAM originator submits a **proposed** NOTAM to the NOTAM System to advertise an **airport** or **runway** condition with a Start of Activity less than 60 minutes before the beginning of an activity that impacts/closes a runway or an airport, the activity must be reported to the Air Traffic Control (ATC) facility that has control jurisdiction.

No Change

e. If information is published elsewhere and is still valid, **when a NOTAM is issued with additional condition data**, reference must be made to that publication with the statement, "PLUS SEE (publication)." A NOTAM issued not stating "PLUS SEE (publication)" indicates the NOTAM replaces previously published similar data (**for example, VOR radials**).

f. NOTAMs must state the abnormal status of a component of the NAS and not the normal status. Exception: **If the temporary restriction is published in the chart supplement and the situation has been resolved, return to normal operations. For example, a VOR was out of service for more than three months, published in the chart supplement, and then returned to service, issue NOTAM stating the VOR is returned to service (RTS).**

NEW

4-3-3. CANCELING PUBLISHED NOTAM DATA

NEW

5-1-3. MOVEMENT AREA INFORMATION

No Change

b. Commissioning a movement area or portions thereof **as follows**.

1. Lighting status; for example, LGTD, NOT LGTD.

Delete

2. Length and declared distances required for only runway commissioning.

Delete

Add

1. Surface designator.

Add

2. Condition “COMMISSIONED”.

Add

3. Location of movement area in reference to existing airport surfaces using phrases (PARL, ADJ, BTN, cardinal direction and distance).

Add

4. Length and width of movement area, (for example, 5000FT X 150FT).

Add

5. Type of surface (for example, CONC, ASPH, GRVL, GRASS, WTR, ICE).

Add

6. Lighting status (LGTD, NOT LGTD).

Add

7. Pavement Classification Rating (PCR), if provided (for example, PCR 760/R/B/W/T).

Add

8. Runway declared distances, required for only runway commissioning, if provided.

c through c2

No Change

d. Operational limitations on the use of any portion of a runway, a taxiway, a ramp, an apron or a waterway. Weight bearing capacity of a runway can be changed only by authorization of the Manager, Airports Division (appropriate region). Include reference to ACFT when describing limitations associated – wing, weight, tail, engine, taxi speed, etc. Do not refer to the Airplane Design Group in the NOTAM.

d. Operational limitations on the use of any portion of a runway, a taxiway, a ramp, an apron, or a waterway.

Add

1. Weight bearing capacity of a runway can be changed only by authorization of the Manager, Airports Division (appropriate region).

Add

(a) Include reference to ACFT when describing limitations associated—wing, weight, tail, engine, taxi speed, etc.

Add

(b) Do not refer to the Airplane Design Group in the NOTAM.

Add

2. NOTAMs must not be used to impose restrictions on airport access for the purpose of controlling or managing noise or to advertise data already published or charted.

Add

e through i5

6. Condition. For example, NOT STD, NOT LGTD, OBSC, MISSING, NOT MARKED

7. Follow 4-2-1b11-14 to complete the NOTAM.

Add

OLD

5-1-4. FIELD CONDITION (FICON) REPORTING

Title through d6(b)

(c) Non-Paved surfaced runways can have BA, but as a stand-alone NOTAM.

(d) TWY/Apron can have BA as stand-alone or appended to field condition NOTAM.

NOTE-
A braking action report from a landing aircraft should be processed as a PIREP

EXAMPLES-
...TWY A FICON BA GOOD TO MEDIUM...
...TWY A FICON 1/8IN WET SN BA MEDIUM...

d7 through d9

(a) When the reported contaminant is ASH, MUD, OIL RUBBER (taxiway only), or SAND.

d9(b) through e1 Example

2. Slippery When Wet is a stand-alone NOTAM, used only on runways, where a friction survey (conducted for pavement maintenance) indicates the averaged Mu value at 40 mph on the wet pavement surface failed to meet the minimum friction level classification. This is the only FICON that is described using both runway ends.

REFERENCE-
AC 150/5200-30, Airport Field Condition Assessments and Winter Operations Safety.

3. If an airport must restrict touch and go landings (TGL), then issue the NOTAM only during operational necessity. Do not issue a PERM NOTAM, unless the publication process has been initiated.

No Change

6. Condition. For example, NOT STD, LGT U/S, OBSC, MISSING, NOT MARKED.

7. When using NOT STD the originator must include in remarks the reason for the subject of the NOTAM not meeting standards.

8. Follow 4-2-1b11-14 to complete the NOTAM.

NEW

5-1-4. FIELD CONDITION (FICON) REPORTING

No Change

(c) Non-Paved surfaced runways can have BA, but as a stand-alone NOTAM, **described using both runway ends.**

No Change

No Change

Delete

No Change

(a) When the reported contaminant is ASH, MUD, OIL, RUBBER (taxiway only), or SAND.

No Change

2. Slippery When Wet is a stand-alone NOTAM, used only on runways, where a friction survey (conducted for pavement maintenance) indicates the averaged Mu value at 40 mph on the wet pavement surface failed to meet the minimum friction level classification. **Slippery When Wet FICON NOTAMs are described using both runway ends.**

No Change

EXAMPLE-
...RWY 02/20 FICON 3/3/3 SLIPPERY WHEN WET...

No Change

NOTE-
May be downgraded to 2/2/2 or 1/1/1 with all numbers matching.

No Change

OLD

5-1-6. WORK IN PROGRESS

Title through **FIG 5-1-7**

...TWY C WIP TRENCHING ADJ EAST SIDE...

See Appendix A for examples.

a. Work in Progress (WIP) describes any work being done on the airport surface, including construction, mowing, snow/ice removal, etc. WIP does not close a movement area; therefore, if the movement area is restricted, another NOTAM identifying that restriction is needed. For example, a WIP with snow removal requires a closure NOTAM with 15-minute PPR in order to use the surface.

NEW

5-1-6. WORK IN PROGRESS

No Change

No Change

Delete

a. Work in Progress (WIP) describes any work being done on the airport surface, including construction, mowing, snow/ice removal, etc. WIP **must not close or restrict a movement area. If the terms CLSD, PPR, or BARRICADED are used, the movement area is considered to be restricted and a closure NOTAM for the movement area must be issued. For example, if WIP for snow removal requires a 15-minute PPR, a NOTAM must be issued for the closure of that surface with an exception for 15-minute PPR. If a movement area is closed, do not issue an additional WIP NOTAM for the closed area.**

OLD

5-2-1. LIGHTING AIDS

Title through subparagraph **FIG 5-2-1**

...RWY 27 RTHL U/S...

See Appendix A for examples.

Originate NOTAMs on operational status of lighting aids for public use civil landing areas listed in the U.S. Chart Supplement. Each type of lighting requires separate NOTAMs. Technical Operations must be made aware of any runway lighting outages, as this is the office that maintains the equipment. When describing restrictions, use Runway Centerline (RCL) with visual navigational aids. NOTAMs regarding lighting aids are originated as follows:

a. Approach light systems (ALS). Only use the runway direction for which the equipment pertains.

1. When commissioning approach light systems, indicate the exact type of system; for example, MALSR, MALSF, etc.

NEW

5-2-1. LIGHTING AIDS

No Change

No Change

Delete

Originate NOTAMs on operational status of lighting aids for public use civil landing areas listed in the U.S. Chart Supplement. Each type of lighting requires separate NOTAMs. Technical Operations must be made aware of any runway **approach** lighting outages, as this is the office that maintains the equipment. When describing restrictions, use Runway Centerline (RCL) with visual navigational aids. NOTAMs regarding lighting aids are originated as follows:

Delete

Delete

<u>2. Once commissioned and published, approach light systems need only be shown as ALS.</u>	Delete
<u>3. When the ALS has been changed to the simplified, short ALS with runway alignment lights, issue the condition as temporarily changed (“NOW”). Do not use out of service/unserviceable.</u>	Delete
<u>b. Lead off /lead on lights. NOTAMs issued using keyword RWY. Lead off and lead on light will be the standardized verbiage for lead off/on lights, which are also referred to as turnoff lights.</u>	Delete
<u>c. Runway status light system.</u>	Delete
<u>1. Runway entrance lights. NOTAMs issued using keyword TWY</u>	Delete
<u>2. Take-off hold lights.</u>	Delete
<u>d. Sequence flashing lights/runway alignment indicator lights.</u>	Delete
<u>e. Visual approach lighting.</u>	Delete
<u>1. Visual approach slope indicator (VASI).</u>	Delete
<u>2. Precision approach path indicator (PAPI).</u>	Delete
<u>3. Runway end identifier lights.</u>	Delete
<u>4. Threshold lights (RTHL).</u>	Delete
<u>NOTE-</u> <u>Technical Operations issued, when associated with Approach Lighting System (ALS).</u>	Delete
<u>f. Runway end lights (RENL).</u>	Delete
<u>NOTE-</u> <u>Airport Operations issued, not associated with Approach Lighting System (ALS).</u>	Delete
<u>g. Runway edge lights (REDL).</u>	Delete
<u>1. When commissioning runway edge light systems, indicate the exact type of system; for example, LIRL, MIRL, HIRL, etc.</u>	Delete
<u>2. Once commissioned and published, runway edge lights must only be shown as REDL</u>	Delete
<u>3. Runway lights obscured due to snow and ice.</u>	Delete
<u>h. Runway centerline light (RCLL).</u>	Delete
<u>i. Touchdown zone lights (RTZL).</u>	Delete
<u>j. Runway lead-in lighting system (RLLS).</u>	Delete
<u>k. Airport lighting total power failure.</u>	Delete
<u>l. Pilot-controlled lighting (PCL) frequency when it controls approach lights or runway lights.</u>	Delete
<u>m. Taxiway lighting.</u>	Delete

- 1. Taxiway edge lights. Delete
- 2. Taxiway centerline lights. Delete
- 3. Runway guard lights. NOTAM issued using keyword TWY. Delete
- 4. Stop bar lights. NOTAM issued using keyword TWY. Delete
- 5. Taxiway lights obscured due to snow and ice. Delete

Add

a. Commissioning

Add

1. Approach lighting systems (ALS).

Add

(a) Only use the runway direction for which the equipment pertains.

Add

(b) When commissioning approach light systems, indicate the exact type of system (MALSR, MALSF, etc.). Once commissioned and published, approach light systems need only be shown as ALS.

Add

2. Runway edge lights (REDL). When commissioning runway edge light systems, indicate the exact type of system (LIRL, MIRL, HIRL, etc.). Once commissioned and published, runway edge lights must only be shown as REDL.

Add

b. Lead-in lights. Runway lead-in light system (RLLS).

Add

c. Approach light systems (ALS).

Add

1. ALS Outage.

Add

(a) Complete loss or dual mode with loss or unavailability of both ALS and SSALR capability.

Add

(b) Dual mode with loss or unavailability of ALS capability only.

Add

(c) When the ALS has been changed to the simplified, short ALS with runway alignment lights, issue the condition as temporarily changed (“NOW”). Do not use unserviceable (U/S).

Add

2. Sequence flashing light (SEQUENCED FLG LGT).

Add

3. One-thousand-foot bar (1000-FOOT BAR).

Add

4. Runway alignment indicator light (RAI LGT).

Add

5. Runway threshold light (RTHL).

- Add NOTE-
Technical Operations issues RTHL, when associated with approach lighting systems (ALS).
- Add **d. Visual approach lighting.**
- Add **1. Visual approach slope indicator (VASI).**
- Add **2. Precision approach path indicator (PAPI).**
- Add **e. Runway lighting.**
- Add **1. Runway status light system (RWY STATUS LGT SYSTEM).**
- Add **(a) Take-off hold light (TKOF HOLD LGT).**
- Add **(b) Runway entrance light (RWY ENTRANCE LGT).**
- Add NOTE-
NOTAM issued using keyword TWY.
- Add **2. Runway end identifier light (RWY END ID LGT).**
- Add **3. Runway touchdown zone lights (RTZL).**
- Add **4. Runway centerline light (RCLL).**
- Add **5. Runway edge light. (REDL).**
- Add **6. Runway end light (RENL).**
- Add **f. Taxiway lighting.**
- Add **1. Taxiway centerline light.**
- Add **2. Taxiway edge light.**
- Add **3. Runway guard lights.**
- Add **4. Stop bar lights.**
- Add NOTE-
NOTAMs for guard lights and stop bar lights issued using keyword TWY.
- Add **5. Runway threshold light (RTHL).**
- Add **g. Lead off/lead on lights. NOTAMs issued using keyword RWY. Lead off and lead on light will be the standardized verbiage for lead off/on lights, which are also referred to as turnoff lights.**
- Add **h. Pilot-controlled lighting (PCL) frequency when it controls approach lights or runway lights.**
- Add **i. Airport lighting total power failure.**
- Add **j. Lights obscured due to snow and ice.**

Add

1. Only issue a NOTAM when lighting is completely obscured (OBSC), do not report partial obscuration.

Add

2. Do not report reason for obscuration.

Add

NOTE-
OBSC can be used to describe physical state of airport infrastructure, including signs and markings

OLD

NEW

5-2-2. OBSTACLES

5-2-2. OBSTACLES

Title through d7

No Change

8. In parentheses, specify the height with the unit of measurement (FT) and reference datum (AGL).

8. In parentheses, specify the height with the unit of measurement (FT) and reference **indication label** (AGL).

NOTE-

Report the height of obstruction lights on terrain (hills) in MSL only, as the terrain is the obstacle, not the light on the terrain

NOTE-

Report the height of obstruction lights on terrain (hills) in MSL only, as the terrain is the obstacle, not the light on the terrain.

9. Specify the condition:

No Change

(a) “U/S” for FCC obstructions. A light condition of unserviceable refers to a top light or flashing obstruction light is not operating, regardless of its position.

No Change

(b) “NOT LGTD,” “LGTD,” “FLAGGED” for non-FCC obstructions, for example. As used in a NOTAM, NOT LGTD refers to a facility (sign) that is installed, but the lights aren’t lit.

(b) “NOT LGTD,” “LGTD,” “FLAGGED” for non-FCC obstructions, for example, Cranes.

Add

NOTE-

For wind turbine farms, use “LGT U/S”.

10. Start of Activity/End of Validity. FCC receives notification upon ASR NOTAM issuance.

10. Start of Activity/End of Validity.

Add

(a) FCC receives notification only upon ASR NOTAM issuance.

Add

(b) Cranes. Schedule (when needed).

Add

NOTE-

See paragraph 4-2-1, NOTAM Composition, for more details on NOTAM schedule formatting.

OLD

NEW

5-3-7. NAVAID CONDITIONS

5-3-7. NAVAID CONDITIONS

**...NAV VOR 090-180 BEYOND 25NM
SFC-5000FT, 270-300 BEYOND 25NM
SFC-5000FT, 301-360 BEYOND 35NM
SFC-4000FT UNUSABLE...**

No Change

See Appendix A for examples.

Delete

a. Introduction. Facility status classification and NOTAM(s) will indicate restriction(s) to the expected use of these facilities. The NOTAM advises the user of any restriction to facility usage. If the NAVAID is out of service or unmonitored, the VOICE is automatically out of service.

Add

Add

b through FIG 5-3-2

...NAV ILS RWY 12 LOC UNUSABLE BEYOND 4DEG RIGHT OF COURSE...

(1) Distinguish components of an ILS from non-precision approach NAVAIDs by preceding the component with “ILS” followed by “RWY” and the runway number (including single ILS airports). Use the term “COURSE” when describing radio navigation aid restrictions. Coupled approach restrictions (for ILS CAT I) are issued via FDC NOTAM.

EXAMPLE-

...NAV ILS RWY 14 LOC U/S...

Add

OLD

5-3-8. SATELLITE BASED SYSTEMS

See Appendix A for examples.

a. Introduction. Facility status classification and NOTAM(s) will indicate restriction(s) to the expected use of these facilities. The NOTAM advises the user of any restriction to facility usage.

1. If the NAVAID is out of service, the VOICE is automatically out of service and no VOICE NOTAM is required.

2. If the VOR is unmonitored and there is an associated VOR VOICE service, issue both an unmonitored and COM VOR VOICE NOTAM.

No Change

No Change

(1) **An ILS is a precision approach.** Distinguish components of an ILS from non-precision approach NAVAIDs by preceding the component with “ILS” followed by “RWY” and the runway number (including single ILS airports). Use the term “COURSE” when describing radio navigation aid restrictions. Coupled approach restrictions (for ILS CAT I) are issued via FDC NOTAM.

No Change

NOTE-

Restrictions on instrument flight procedures caused by outages to a localizer backcourse will be issued separately as FDC NOTAMs.

NEW

5-3-8. SATELLITE BASED SYSTEMS

Delete

a. Global Positioning System (GPS). Candidate global positioning system pseudo-random noise (PRN) GPS satellite outages will be reported directly to the USNOF (must be properly formatted) by the Air Force Space Command (AFSPACECOM) monitoring facility. The USNOF will issue NOTAMs under the accountability “GPS” with a location of “GPS.” When these NOTAMs get distributed internationally, the NOTAM System changes the designator “KNMH.” (Refer to 1-2-1a.)

a. Global Positioning System (GPS). **Proposed global positioning system pseudo-random noise (PRN) GPS satellite outage NOTAMs will be submitted via an approved direct entry tool or interface by the DoD NOTAM Office per request from the Air Force Space Command (AFSPACECOM) monitoring facility. PRN GPS NOTAMs must be issued under the accountability “GPS” with a location of “GPS.”** When these NOTAMs get distributed internationally, the NOTAM System changes the designator “KNMH.” **GPS testing NOTAMs must be issued under the accountability “GPS” with a location identifier of the affected ARTCC(s).**

NOTE-

GPS operations are included in the Aeronautical Information Manual.

Candidate GPS testing NOTAMs must be properly formatted when received from Technical Operations ATC Spectrum Engineering Services, Spectrum Assignment and Engineering Services. The USNOF will issue NOTAMs under the accountability “GPS” with a location identifier of the associated center.

No Change

Delete

OLD

5-4-3. COMMUNICATION OUTLET CONDITIONS

Title through FIG 5-4-1

...COM REMOTE TRANS/REC 126.25, 131.25 U/S...

Originate a NOTAM for conditions pertaining to the operation of communications outlets that are part of the NAS when an outage occurs or when a scheduled shutdown (60 minutes or more) is expected as follows:

a. Use a comma to separate multiple frequencies.

b. Commissioning, decommissioning, outage, or (un)availability of communications outlets for the following:

1. All published ATC frequencies and all communication frequencies will be issued with the affected frequency when unserviceable.

(a) Remote Communication Outlets associated with an airport or NAVAID.

NEW

5-4-3. COMMUNICATION NOTAM FORMAT

No Change

No Change

No Change

Delete

Delete

Delete

Delete

(b) Remote Communication Outlets NOT associated with an airport or NAVAID.

Delete

2. If several frequencies are out, but one is still operating, issue the out-of-service frequencies in one NOTAM.

Delete

(a) Remote Communication Outlets associated with an airport or NAVAID.

Delete

(b) Remote Communication Outlets NOT associated with an airport or NAVAID.

Delete

Add

a. Affected location.

Add

1. Communication outlets associated with an airport or NAVAID, issue with the affected location as the airport or NAVAID.

Add

2. Communications outlets not associated with an airport or NAVAID, issue with the affected location as the ARTCC.

Add

**NOTE-
Communication (COM) NOTAMs for the Approach Control frequencies which are located within the TRACON facility and all Remote Center Air-to-Ground facilities, will be issued with the ARTCC as the affected location with which the frequency provides coverage within. The full name of the facility will be spelled out after the keyword and before the type of A/G communication facility. For example, NORTHERN CALIFORNIA APP, DUTCH HARBOR REMOTE CENTER A/G**

Add

b. Communication facilities.

Add

1. Remote Center Air-to-Ground (REMOTE CENTER A/G).

Add

(a) Air Route Traffic Control Centers (ARTCC).

Add

(b) Combined Center Radar Approach Control (CERAP).

Add

2. Remote Transmitter Receiver (REMOTE TRANS/REC).

Add

(a) Air Traffic Control Towers (ATCT).

Add

(b) Terminal Radar Approach Control (TRACON).

Add

3. Remote Communication Outlet (REMOTE COM OUTLET).

Add

(a) Flight Service Station (FSS).

Add

(b) Emergency Frequencies.

Add

4. Other Identified Communications

- Add (a) Controller Pilot Data Link Communication (CPDLC).
- Add (b) Ground Control (GND CTL).
- Add (c) Local Control (LOCAL CTL).
- Add (d) Clearance Delivery (CLR DELIVERY).
- Add (e) Local Airport Advisory (LOCAL AP ADVISORY).
- Add (f) Ground Communication Outlet (GND COM Outlet).
- Add (g) Common Traffic Advisory Frequency (CTAF).
- Add (h) Universal Communications (UNICOM).
- Add c. NOTAM conditions.
- Add 1. Commissioning and decommissioning. When decommissioning frequency, unserviceable (U/S) must be stated as the condition with a PERM validity end date.
- Add 2. An outage or (un)availability of communications outlets when an outage occurs or, when a scheduled shutdown (60 minutes or more) is expected. All published ATC frequencies and all communication frequencies will be issued with the affected frequency when unserviceable.
- Add 3. Communication outlet or facility frequency change.
- Add (a) Temporary frequency change, issue with condition of NOW and new frequency to be used.
- Add (b) Permanent frequency change, issue with condition CHANGED TO, new frequency to be used, and validity end date of PERM.

OLD

5-5-1. GENERAL

Title through a

b. When notified, Technical Operations and Air Traffic personnel must ensure the origination of NOTAM D concerning changes to air traffic services and capabilities, for which they are responsible.

NEW

5-5-1. GENERAL

No Change

b. When notified, Technical Operations and Air Traffic personnel must ensure the origination of NOTAM D concerning changes to air traffic services and capabilities, for which they are responsible, for example, Tower visual signal-light gun.

OLD

5-5-2. CHANGES TO PUBLISHED SERVICES

a through b3

Add

4. Automated Universal Communication (AUNICOM). AUNICOMs have portions that are automatically broadcast along with the voice recordings. When these functions are unserviceable or not available, issue a NOTAM.

OLD

5-5-3. HOURS OF OPERATION

Any change of published hours of operation to ATC facilities, including contingency situations, must be submitted as an SVC NOTAM, ensuring not to duplicate published or charted data. When submitting NOTAMs, ARTCCs and approach controls must use the associated ARTCC as the location identifier. Approach controls located within multiple ARTCCs must have a separate NOTAM for each ARTCC. Air traffic control towers must use the airport as the location identifier. FSS with a small flight plan area of 5 nautical miles or less must use the airport as the location identifier. FSS covering a large flight plan area must use the ARTCC as the location identifier. Flight plan areas located within multiple ARTCC airspace must have a separate NOTAM for each ARTCC. Spell out facility names when used in the body of the NOTAM.

Disseminate the following conditions as a NOTAM:

a through a2(c)

(d) If an approach control contains both Class B and Class C airspace, two NOTAMs must be issued, one for each class of airspace.

Add

a3 through b

NEW

5-5-2. CHANGES TO PUBLISHED SERVICES

No Change

4. Local Airport Advisory Service.

5. Automated Universal Communication (AUNICOM). AUNICOMs have portions that are automatically broadcast along with the voice recordings. When these functions are unserviceable or not available, issue a NOTAM.

NEW

5-5-3. HOURS OF OPERATION

Any change of published hours of operation to ATC facilities, including contingency situations, must be submitted as an SVC NOTAM, ensuring not to duplicate published or charted data. When submitting NOTAMs, ARTCCs and approach controls must use the associated ARTCC as the location identifier. Approach controls located within multiple ARTCCs must have a separate NOTAM for each ARTCC. Air traffic control towers must use the airport as the location identifier. **Satellite FSS must use the airport as the affected location. Hub FSS and FCFSS must use the ARTCC as the affected location.** Flight plan areas located within multiple ARTCC airspace must have a separate NOTAM for each ARTCC. Spell out facility names when used in the body of the NOTAM.

No Change

No Change

(d) If an approach control contains **two or more of either Class B, Class C, or Terminal Radar Service Area airspace, two or more** NOTAMs must be issued, one for each **category** of airspace.

NOTE-
This includes approach controls with multiple airports that have the same class of airspace. For example, Northern California Approach has five airports with Class C Airspace (MRY, OAK, RNO, SJC and SMF), a NOTAM is required for each individual Class C.

No Change

c. At times, air traffic facilities temporarily extend their hours of operation. When this occurs, substitute “OPN” as the condition and include, if requested, the control position (e.g., local, ground) and the associated frequency(ies).

c. At times, air traffic facilities temporarily extend their **hours/availability of operation outside of published times**. When this occurs, substitute “OPN” as the condition and include, if requested, the control position (e.g., local, ground) and the associated frequency(ies), **for example, if published ATCT hours are 1130–0330 and the ATCT open hours are extending until 0530, then NOTAM would read SVC TWR OPN PLUS SEE CHART SUPPLEMENT YYMMDD0330–YYMMDD0530.**

Add

*NOTE–
“PLUS SEE CHART SUPPLEMENT” only used when extending hours/availability outside of published times.*

d. Traffic Management Program Alerts

No Change

1. When requested by the associated arrival ARTCC TMU, issue an alerting NOTAM for each airport where an arrival/departure reservation is required. NOTAMs should be in the self-canceling format whenever possible.

1. When requested by the associated arrival ARTCC TMU, **FSS will issue a pointer** NOTAM for each airport where an arrival/departure reservation is required. NOTAMs **must** be in self-canceling format.

2. When a flow control message (for example, arrival delays, ground stops, ground delays, airborne holding, etc.) is received from the Air Traffic Control System Command Center (ATCSCC), the tie-in FSS for the affected airport(s) must issue a NOTAM(s) in the self-canceling format.

2. When a flow control message **for ground stops** is received from the Air Traffic Control System Command Center (ATCSCC), FSS **must issue a NOTAM(s) for the affected airport(s) in self-canceling format.**

OLD

NEW

5–5–4. WEATHER AND WEATHER REPORTING EQUIPMENT

5–5–4. WEATHER AND WEATHER REPORTING EQUIPMENT

Title through a1 Note

No Change

2. When verified, issue a NOTAM and notify the responsible technical operations office of the discrepancy, unless they reported the outage. If notified of system failure or other irregularity by other than a technical operations office that cannot be verified by the methods given above, forward the information to technical operations office for resolution. Accept NOTAM cancellation information only from the responsible technical operations office.

b. Accept NOTAM information on Automated Surface Observing System (ASOS) only from the NWS Weather Forecast Office. Either the person on duty, Meteorologist in Charge, or Lead Forecaster, at the NWS Weather Forecast Office is responsible for requesting NOTAMs to be issued and cancelled regarding ASOS system malfunctions and return to service. When malfunctions or discrepancies of an ASOS system are reported to a facility, they are reported to the NWS Weather Forecast Office.

OLD

6-1-1. AIRSPACE NOTAM FORMAT

FIG 6-1-1

Airspace

No Change


b. Accept NOTAM information on Automated Surface Observing System (ASOS) only from the NWS Weather Forecast Office. Either the person on duty, Meteorologist in Charge, or Lead Forecaster, at the NWS Weather Forecast Office is responsible for requesting NOTAMs to be issued and canceled regarding ASOS system malfunctions and return to service. When malfunctions or discrepancies of an ASOS system are reported to a facility, they are reported to the NWS Weather Forecast Office.

NEW


6-1-1. AIRSPACE NOTAM FORMAT

No Change

OLD



NEW



...AIRSPACE CRYPT NORTH MOA ACT
5000FT-16000FT...

No Change

a. NOTAMs originated for Airspace items will be formatted following 4-2-1 b1-2, including:

No Change

1. Location identifier – may be AP, NAVAID, or ARTCC depending on NOTAM.

1. Location identifier,

Add

(a) Use nearest public use airport when the full activity is completely within a 5 NM radius of the airport.

Add

(b) Use nearest VOR when any of the activity is more than 5 NM from the nearest public use airport but completely within 25 NM radius of a VOR.

Add

(c) Use the ARTCC when the activity doesn't fall within either (a) or (b).

a2 through b

No Change

OLD

Add

Add

NEW

TBL 6-1-1

Types of Activity

<u>AIRSHOW ACFT</u>	<u>AEROBATIC AREA</u>	<u>PJE</u> <u>(Parachute Jumping)</u>
<u>DEMONSTRATION ACFT</u>	<u>HOT AIR BALLOON</u>	<u>UNMANNED FREE BALLOON</u>
<u>UNMANNED ROCKET</u>	<u>UAS</u> <u>(Unmanned Aircraft System)</u>	<u>GLD</u>
<u>HANG GLD</u>	<u>LGT OUT TRG</u> <u>(Lights-Out Training)</u>	<u>BALLOON LDG</u> <u>(Landing)</u>
<u>PYROTECHNIC DEMONSTRATION</u> <u>(fireworks)</u>	<u>BLASTING</u>	<u>CONTROLLED BURN</u>
<u>AEROBATIC ACFT</u>	<u>SPACE LAUNCH</u>	<u>SPACE REENTRY</u>

Add

NOTE-

Airspace activities that will require airspace management such as Temporary Flight Restrictions will require the issuance of an FDC NOTAM.

OLD

6-1-2. SPECIAL ACTIVITY AIRSPACE (SAA)

A NOTAM must be entered through Special Use Airspace Management System to activate permanent or temporary special use airspace if activated by NOTAM only or at other than published times for those SAA that contain a NOTAM provision in their legal description, under the appropriate ARTCC(s):

- a.** SAA, for the purpose of this manual, includes Special Use Airspace (SUA) (restricted area, military operations area (MOA), warning area, and alert area airspace), instrument and visual military training routes, aerial refueling tracks and anchors.

Add

Add

NEW

6-1-2. SPECIAL ACTIVITY AIRSPACE (SAA)

No Change

No Change

NOTE-

Controlled Firing Area (CFA) does not require a NOTAM as the activity is suspended immediately when a nonparticipating aircraft approaches the area.

REFERENCE-

FAA Order JO 7400.2, Procedures for Handling Airspace Matters.

a through a2

No Change

b. Issue the NOTAM in the format described in 6-1-1 above using the following items:

No Change

Accountability = SUA (E, C, W) Location identifier = ARTCC Condition = "ACT" (active)

Delete

Add

1. Accountability = SUA (E, C, W)

Add

2. Location Identifier = ARTCC

Add

3. Condition = ACT (active)

OLD

NEW

6-1-3. AIRSPACE AND ALTITUDE RESERVATIONS

6-1-3. AIRSPACE AND ALTITUDE RESERVATIONS

a. Central Altitude Reservation Function (CARF) airspace and altitude reservation NOTAMs must be transmitted by the USNOF, after receipt of the candidate NOTAM from the CARF office. The information will be stored in the NS database and available for request/reply. If the altitude reservation affects international airspace, it will be sent and stored as an international NOTAM.

a. Central Altitude Reservation Function (CARF) airspace and altitude reservation NOTAMs must be transmitted by the USNOF, after receipt of the **proposed** NOTAM from the CARF office **or ARTCC**. The information will be stored in the NS database and available for request/reply. If the altitude reservation affects international airspace, it will be sent and stored as an international NOTAM.

NOTE-

Commercial space operations are examples of activity permitted in ALTRVs within oceanic and offshore airspace

No Change

b. Issue the NOTAM in the format described in 6-1-1 above using the following items:

No Change

1. Accountability = CARF Location identifier = ARTCC

1. Accountability = CARF Location identifier

Add

2. Location Identifier = ARTCC

2. Description of Activity = STNR ALT RESERVATION

3. Description of Activity = STNR ALT RESERVATION

c. Airspace and Altitude reservation involving a single ARTCC.

No Change

d. Missile firing and offshore airspace reservations. ARTCCs must issue as a NOTAM missile firing exercises and offshore airspace reservations. These NOTAMs must be transmitted as an international NOTAM to the USNOF.

No Change

e. Weather Reconnaissance Area (WRA). A WRA is established to support weather reconnaissance/research flights. ARTCCs must use the CARF location identifier when issuing NOTAMs for a WRA.

e. Weather Reconnaissance Area (WRA). A WRA is established to support weather reconnaissance/research flights. ARTCCs must use the CARF **accountability** location identifier when issuing NOTAMs for a WRA.

OLD

6-1-5. OTHER AIRSPACE NOTAMS

With the exception of hot air balloons and commercial space launches and reentries, FAA Authorization will consist of an approved waiver/ authorization to 14 CFR part 101.

NOTE-

14 CFR part 91 applies to hot air balloons

a. Upon receipt of appropriate notification/authorization, but not more than 7 days prior to the event, originate an AIRSPACE NOTAM using the format described in 6-1-1a above.

1. Location Identifier

(a) The nearest public use airport when the full activity is completely within a 5 NM Radius of the airport.

(b) The nearest VOR when any of the activity is more than 5 NM from the nearest public use airport but completely within 25 NM Radius of a VOR

(c) When the activity doesn't fall within either (a) or (b), use the ARTCC.

2. Description of activity = see TBL 6-1-1 for general types of activity.

NEW

6-1-5. AIRSPACE NOTAM REQUIRING AUTHORIZATION/WAIVER

Delete

Delete

Delete

Delete

Delete

Delete

Delete

Delete

OLD

TBL 6-1-1

Types of Activity

<u>AIRSHOW ACFT</u>	<u>AEROBATIC AREA</u>	<u>PJE</u> <u>(parachute jumping)</u>
<u>DEMONSTRATION ACFT</u>	<u>HOT AIR BALLOON</u>	<u>UNMANNED FREE</u> <u>BALLOON</u>
<u>UNMANNED ROCKET</u>	<u>UAS</u> <u>(unmanned aircraft system)</u>	<u>GLD</u>
<u>HANG GLD</u>	<u>LGT OUT TRG</u> <u>(lights-out training)</u>	<u>BALLOON LDG</u>
<u>PYROTECHNIC</u> <u>DEMONSTRATION</u> <u>(fireworks)</u>	<u>BLASTING</u>	<u>CONTROLLED BURN</u>
<u>AEROBATIC ACFT</u>	<u>SPACE LAUNCH</u>	<u>SPACE REENTRY</u>

NEW

Delete

Delete

NOTE-

Unmanned rocket activities that will require airspace management such as Temporary Flight Restrictions will require the issuance of an FDC NOTAM.

Delete

b. Controlled Firing Area (CFA) does not require a NOTAM as the activity is suspended immediately when a nonparticipating aircraft approaches the area.

Delete

REFERENCE-

FAA Order JO 7400.2, Procedures for Handling Airspace Matters.

Delete

c. For unmanned free balloons the forecasted trajectory and cruising altitude or UNL (unlimited). For operations above FL999/UNL, place expected altitude in remarks. Include a landing area NOTAM, if requested by proponent.

Delete

(Pointer NOTAM)

Delete

...SEE MTU 12/045 UNMANNED ROCKET...

d. Authorizations and/or Air Traffic notifications are required by the proponent for the following activities; ensure the NOTAM Originator is aware of this. The information is not released in the NOTAM.

Delete

1. Airshows, Demonstrations, Aerobatic Areas.

Delete

2. Unmanned Aircraft Operations.

Delete

3. Parachute Jumping/Sky Diving

Delete

Add

a. When required, originate an airspace activity NOTAM only for the time period the activity is taking place. When the activity is expected to be temporary but of long duration (more than three months) or permanent, the information must be published in the appropriate chart/publication. Once the information is published, the NOTAM must be canceled unless required by a Certificate of Waiver or Authorization from Title 14, Code of Federal Regulations (CFR) issued by the FAA.

Add

b. FAA Authorization will consist of an approved waiver/authorization to 14 CFR. Upon receipt of appropriate notification/authorization, but not more than 7 days prior to the event, originate an AIRSPACE NOTAM using the format described in 6-1-1a above, ensuring not to advertise published or charted data and information.

- Add **c. Ensure the NOTAM originator is aware that authorizations, waivers, and/or air traffic notifications may be required by the proponent, and the proponent's information is not released in the NOTAM but must be made available immediately upon request to ATC and other entities responsible for airspace deconfliction for the following activities:**
- Add **1. Airshows, aerial demonstrations, aerobatic areas, hot air balloon events, flight test areas, light out training, banner towing.**
- Add **(a) FAA authorization will consist of a waiver to 14 CFR part 91.**
- Add **(b) Obtain the following information from the requestor:**
- Add **(1) Name, address, and telephone number of the person giving notice.**
- Add **(2) Identification and type of the aircraft to be used.**
- Add **2. Moored balloons, kites, amateur rockets, unmanned free balloons.**
- Add **(a) FAA authorization will consist of a waiver to 14 CFR part 101.**
- Add **(b) Obtain the following information from the requestor: Name, address, and telephone number of the person requesting authorization or giving notice.**
- Add **NOTE-
Unmanned rocket activities that will require airspace management such as Temporary Flight Restrictions will require the issuance of an FDC NOTAM.**
- Add **3. Parachute Jumping/Sky Diving**
- Add **(a) FAA authorization/air traffic notification will be required under 14 CFR part 105.**
- Add **(b) Obtain the following information from the requestor:**
- Add **(1) Name, address, and telephone number of the person requesting authorization or giving notice.**
- Add **(2) Identification of the aircraft to be used.**
- Add **4. Unmanned Aircraft Operations.**

Add (a) FAA authorization will consist of a Certificate of Authorization, Certificate of Waiver or an Airspace Authorization documented on an FAA Form 7711-1 – Certificate of Waiver or Authorization.

Add (b) NOTAM is not required for UAS operations, unless specifically stated on the FAA Form 7711-1 – Certificate of Waiver or Authorization, Special Airworthiness, or similar document.

Add (c) In general, a NOTAM is not required for UAS operations in Class A airspace.

Add (d) In general, a NOTAM is not required for UAS operating as follows:

Add (1) at or below 400’ above ground level (AGL), in Class G airspace, or at or below the established UAS facility map altitudes in Class B, C, D and E surface area, and

Add (2) UAS weighs less than 55 lbs., and

Add (3) remaining within visual line of sight, and

Add (4) have a maximum airspeed of 100 mph (87 knots) or less.

OLD

6-1-6. SURFACE AREA AIRSPACE

Title through a2

3. The change in the surface area hours of operation will thereafter be continuously published in the U.S. Flight Information Publication U.S. Chart Supplement, Chart Supplement Alaska, or the Chart Supplement Pacific.

Add

NEW

6-1-6. SURFACE AREA AIRSPACE

No Change

3. The change in the surface area hours of operation will thereafter be continuously published in the U.S. flight information publication, Chart Supplement Alaska, Chart Supplement Pacific, or the Chart Supplement U.S.

NOTE-
NOTAM specifying or changing the dates and times of a designated part time surface area must coincide with issuance of a corresponding Hours of Operation Services NOTAM and may be issued by the appropriate facility only after coordination with the regional/service area office.

OLD**7-1-3. INSTRUMENT IFR FLIGHT PROCEDURES**

a. Instrument Flight Procedure (IFP) NOTAMs. Changes to IFPs that have been charted and distributed, are processed as FDC NOTAMs and issued through the NS. Procedural NOTAMs are originated by FAA Flight Operations and FAA Flight Inspection and Procedures personnel. When these revisions cannot be published in advance of their effective date, the NOTAM is transmitted as an FDC NOTAM. The applicable keyword (ODP, SID, STAR, CHART, DATA, IAP, VFP, ROUTE, or SPECIAL) will be included immediately following the location identifier designator.

NOTE-

The USNOF is responsible for Quality Control on Interim IFR Flight Procedure NOTAMs.

a1 through a2

b. Temporary conditions. NOTAMs for temporary conditions whose expiration time is uncertain and approximate, must be identified by the addition of “EST” following the NOTAM date/time group. The “EST” suffix may be used with all IFP T-NOTAMs.

b1 through c4

5. Only one procedure may be addressed per Permanent NOTAM except that a single P NOTAM may be used for ILS CAT I/II/III and SA CAT I /II procedures to the same runway. A single Permanent NOTAM may also address multiple procedures at a single location when correcting a common printing error on U.S. Government charts.

6. A hard/electronic copy of each Permanent NOTAM must be stored with the current amendment and maintained with the procedure filed by AIS specialists.

7. Permanent NOTAMs must not be used for RNAV/database driven procedures when the change(s) will affect waypoint coordinates, course (track), distances, or bearings.

8. The Permanent NOTAM originator must coordinate a procedure amendment date with AIS for inclusion in the Transmittal Letter. This will ensure that all charting agencies publish the amended procedure on the same AIRAC chart cycle and with the same procedure amendment date.

NEW**7-1-3. INSTRUMENT IFR FLIGHT PROCEDURES**

a. Instrument Flight Procedure (IFP) NOTAM. Changes to IFPs that have been charted and distributed, are processed as FDC NOTAMs and issued through the NS. Procedural NOTAMs are originated by FAA Flight Operations and FAA Flight Inspection and Procedures personnel. When these revisions cannot be published in advance of their effective date, the NOTAM is transmitted as an FDC NOTAM. The applicable keyword (ODP, SID, STAR, CHART, DATA, IAP, VFP, ROUTE, or SPECIAL) will be included immediately following the location identifier designator.

No Change

No Change

b. Temporary conditions. NOTAMs for temporary conditions whose expiration time is uncertain and approximate, must be identified by the addition of “EST” following the NOTAM date/time group. The “EST” suffix may be used with all IFP temporary NOTAMs.

No Change

5. Only one procedure may be addressed per PERM NOTAM except that a single PERM NOTAM may be used for ILS CAT I/II/III and SA CAT I /II procedures to the same runway. A single PERM NOTAM may also address multiple procedures at a single location when correcting a common printing error on U.S. Government charts.

6. A hard/electronic copy of each PERM NOTAM must be stored with the current amendment and maintained with the procedure filed by AIS specialists.

7. PERM NOTAMs must not be used for RNAV/database driven procedures when the change(s) will affect waypoint coordinates, course (track), distances, or bearings.

8. The PERM NOTAM originator must coordinate a procedure amendment date with AIS for inclusion in the Transmittal Letter. This will ensure that all charting agencies publish the amended procedure on the same AIRAC chart cycle and with the same procedure amendment date.

9. Each AIRAC cycle is limited to no more than 150 Permanent NOTAMs, except for Flight Standards directed safety initiatives or national implementation processes. Whenever the 150 P NOTAM limit must be exceeded, AIS is responsible for coordinating with other charting agencies; e.g., Jeppesen, LIDO, etc., to ensure they can accommodate the necessary changes on the required AIRAC date.

10. Permanent NOTAMs must be canceled when the applicable procedural change has been published.

11. When a Permanent NOTAM is originated to permanently amend a SIAP or textual ODP, “PERM” must be inserted as the expiration date in lieu of a 10–digit date–time group. The NOTAM originator is responsible for cancelling the NOTAM upon publication.

12. A NOTAM will auto–expire at the expiration DTG unless “PERM” is used.

d. NOTAM Procedures:

d1 through d1(b)

2. Form 8260–17.1, Standard Terminal Arrival [and Form 8260–17.2, STAR (Data Record) for RNAV STARs] must be submitted for permanent charting changes. NOTAMs on STARs must not exceed 224 days [see paragraph 2–6–3.a].

e. Instrument Flight Procedure NOTAMs. A complete review and a new amendment are the preferred methodology for permanent procedure changes, particularly when applying new or revised Order 8260.3 criteria. However, it is recognized that this may not always be possible due to time constraints, workload, staffing level, etc. Abbreviated 8260–series forms and/or Permanent NOTAMs have proven to be an effective means of updating aeronautical charts and amending instrument flight procedures within the following guidelines:

1. Whenever the need for a NOTAM to a procedure arises, AIS, or the non–FAA service provider must review the procedure and ascertain that there is no other safety of flight changes required. If a Permanent NOTAM is required to amend a SIAP or textual ODP for safety reasons, other items may be included in the NOTAM to simultaneously update procedure charts.

e2 through e9 Note

9. Each AIRAC cycle is limited to no more than 150 PERM NOTAMs, except for Flight Standards directed safety initiatives or national implementation processes. Whenever the 150 PERM NOTAM limit must be exceeded, AIS is responsible for coordinating with other charting agencies (for example, Jeppesen, LIDO) to ensure they can accommodate the necessary changes on the required AIRAC date.

10. PERM NOTAMs must be canceled when the applicable procedural change has been published.

11. When a PERM NOTAM is originated to permanently amend a SIAP or textual ODP, “PERM” must be inserted as the expiration date in lieu of a 10–digit date–time group. The NOTAM originator is responsible for canceling the NOTAM upon publication.

No Change

d. NOTAM Procedures:

No Change

2. Form 8260–17.1, Standard Terminal Arrival [and Form 8260–17.2, STAR (Data Record) for PBN STARs] must be submitted for permanent charting changes. NOTAM on STARs must not exceed 224 days.

e. Instrument Flight Procedure NOTAMs. A complete review and a new amendment are the preferred methodology for permanent procedure changes, particularly when applying new or revised Order 8260.3 criteria. However, it is recognized that this may not always be possible due to time constraints, workload, staffing level, etc. Abbreviated 8260–series forms and/or PERM NOTAMs have proven to be an effective means of updating aeronautical charts and amending instrument flight procedures within the following guidelines:

1. Whenever the need for a NOTAM to a procedure arises, AIS, or the non–FAA service provider must review the procedure and ascertain that there is no other safety of flight changes required. If a PERM NOTAM is required to amend a SIAP or textual ODP for safety reasons, other items may be included in the NOTAM to simultaneously update procedure charts.

No Change

f. Chart correction NOTAMs. FDC NOTAMs to correct U.S. Government chart printing or compilation errors are issued by AIS. If the NOTAM is used to correct an IFP, specify the location identifier of the airport affected by the procedure, the full procedure title and amendment number (if applicable). If the NOTAM is used to correct a chart; e.g., VFR sectional chart, IFR enroute chart, etc., use “FDC” as the location identifier. The first word in the NOTAM text should be “correct.”

g. RNAV substitution. Properly equipped aircraft may substitute RNAV systems for inoperative ground NAVAIDs; however, RNAV systems must not be substituted for NAVAIDs providing final approach course guidance on instrument approach procedures.

g1 and g2

h. Air Traffic Service Route NOTAMs. Under 14 CFR Part 71.13, the term “ATS route” refers to a variety of routes, including airways, jet routes, and RNAV routes. When a restriction or a change to an ATS route requires a NOTAM, AIS must prepare and forward an FDC T–NOTAM following the procedures in paragraph 7–1–3_b.

h1 through h4

i. FDC NOTAMs for Special Instrument Approach Procedures (Specials). FDC Temporary NOTAMs may also be used to promulgate safety of flight information relating to Specials provided the location has a valid landing area identifier and is serviced by the NS.

i1 through i4

j. NOTAM content.

OLD

7–1–4. HIGH BAROMETRIC PRESSURE WARNING

When requested by a Flight Standards District office, the USNOF will ensure an FDC NOTAM is issued.

*REFERENCE–
14 CFR Part 91.144 and FAA Order JO 7110.10, Flight Services, Chapter 3.*

f. Chart correction NOTAMs. FDC NOTAMs to correct U.S. Government chart printing or compilation errors are issued by AIS. If the NOTAM is used to correct an IFP, specify the location identifier of the airport affected by the procedure, the full procedure title and amendment number (if applicable). If the NOTAM is used to correct a chart; e.g., VFR sectional chart, IFR enroute chart, etc., use “FDC” as the location identifier. The first word in the NOTAM text should be “correct.”

g. RNAV substitution. Properly equipped aircraft may substitute RNAV systems for inoperative ground NAVAIDs; however, RNAV systems must not be substituted for NAVAIDs providing final approach course guidance on instrument approach procedures.

No Change

h. Air Traffic Service Route NOTAMs. Under 14 CFR **part** 71.13, the term “ATS route” refers to a variety of routes, including airways, jet routes, and **PBN** routes. When a restriction or a change to an ATS route requires a NOTAM, AIS must prepare and forward **a temporary FDC NOTAM** following the procedures in paragraph 7–1–**3b**.

No Change

i. FDC NOTAMs for Special Instrument Approach Procedures (Specials). **A Temporary FDC NOTAM** may also be used to promulgate safety of flight information relating to Specials provided the location has a valid landing area identifier and is serviced by the NS.

No Change

j. NOTAM content.

NEW

7–1–4. HIGH BAROMETRIC PRESSURE WARNING

When requested by **the affected area Air Route Traffic Control Center (ARTCC)**, the USNOF will ensure an FDC NOTAM is issued.

*REFERENCE–
14 CFR § 91.144.
FAA Order JO 7110.10, Flight Services, Chapter 4.*

OLD**7-1-5. TEMPORARY FLIGHT RESTRICTIONS****Title through a7**

(a) Stated as “WI AN AREA DEFINED AS...” and if appropriate “...TO POINT OF ORIGIN.” The area is defined as a nautical mile radius of a latitude/longitude, or an area defined by latitude/longitude or fixes. As necessary, include an alternate description as a fix/radial/distance in parentheses, to help clarify the location. For example, X (alt X) TO Y (alt Y) TO Z (alt Z).

(b) Lower limit then upper limit, or height, (when needed). Limits must be specified, as:

(1) For SFC, or 1 to 17,999FT with the unit of measurement (AGL or MSL). 1275FT AGL, 10500FT MSL.

(2) For 18,000FT and above, express in flight levels (FL), FL180, FL250, FL850, or UNL (altitudes greater than 99,900).

(3) Heights AGL may be added, for example, SFC-450FT AGL.

(c) Schedule of individual area, if needed. For example, EFFECTIVE YY02271900 UTC (1400 LOCAL 2/27/YY) UNTIL YY02280200 UTC (2100 LOCAL 2/27/YY). If a daily (or MON WED FRI) time is required, DLY 1900-0200 (1400-2100 LOCAL).

NOTE-

Repeat 7 (a)-(c), as necessary, for each defined area.

OLD**7-1-8. LASER LIGHT ACTIVITY**

The service area office where the laser activity will occur must notify the USNOF via telephone (888) 876-6826 or email (9-AWA-NOTAMS@FAA.-GOV) within 7 days of a proposed activity. Additionally, service area offices, when coordinated with their respective ATC facilities, may delegate notification responsibility. The USNOF will transmit the appropriate FDC NOTAM. If the event is canceled prior to the scheduled ending date/time, the service area office or their designee must notify the USNOF to cancel the NOTAM.

NEW**7-1-5. TEMPORARY FLIGHT RESTRICTIONS****No Change**

(a) Stated as “WI AN AREA DEFINED AS...” and if appropriate “...TO POINT OF ORIGIN.” The area is defined as a nautical mile radius of a latitude/longitude, or an area defined by latitude/longitude. Include an alternate description as a fix/radial/distance in parentheses to help clarify the location. For example, ...**285039N0800500W (MLB040053)**...

No Change

(1) For SFC, or 1 to 17,999 **feet, include** the unit of measurement (**FT**), **for example** 1275FT.

No Change

(3) **When referencing heights above ground level, include the reference indication label (AGL) after the stated altitude in the NOTAM (for example, 4000FT AGL).**

(c) Schedule of individual area, if needed. For example, EFFECTIVE YY02271900 (1400 LOCAL 2/27/YY) UNTIL YY02280200 (2100 LOCAL 2/27/YY). If a daily (or MON WED FRI) time is required, DLY 1900-0200 (1400-2100 LOCAL).

No Change**NEW****7-1-8. LASER LIGHT ACTIVITY**

The service area office where the laser activity will occur must **enter the NOTAM via an approved direct entry tool or interface** within 7 days of a proposed activity. Additionally, service area offices, when coordinated with their respective ATC facilities, may delegate notification responsibility. The USNOF will transmit the appropriate FDC NOTAM. If the event is canceled prior to the scheduled ending date/time, the service area office or their designee must notify the USNOF to cancel the NOTAM.

Add

Follow 4-2-1b1-2, including:

8-1-1. INTERNATIONAL NOTAMs

Title through c

d. The USNOF issues international NOTAMs concerning the GPS systems as well as certain special activity airspace for ARTCCs; that is, ARTCC and CARF altitude reservations (ALTRVs) and warning areas. Warning areas and ALTRVs are filed under the associated ARTCC ICAO location indicator (KZBW, KZHU, KZJX, KZLA, KZMA, KZNY, KZOA, KZSE, PAZA, PHZH, or TJZS). Information concerning permanent, long-term general data and selected foreign advisories are stored under KFDC location indicator. GPS information is stored under KNMH.

OLD

8-1-2. INTERNATIONAL NOTAM DATA FORMAT

Title through TBL 8-1-1

NOTE-
NOTAMR (NOTAM replacement) and NOTAMC (NOTAM cancellation) are valid contractions and will be followed by another NOTAM number that is being replaced or cancelled.

OLD

8-2-1. REQUEST FOR CANADIAN NOTAMs FROM THE CANADIAN NOTAM SYSTEM

a. The NS receives NOTAM data from Canada. The NS cannot confirm that they have all NOTAM data; therefore, you are urged to contact the Canadian Web_site for the most current and up-to-date NOTAM data.

<http://www.flightplanning.navcanada.ca>

NOTE-
Altitude reservations will be input by Canada utilizing FIR ACCOUNTABILITIES.

Add

REFERENCE-
FAA Order JO 7400.2, Procedures for Handling Airspace Matters.

No Change

8-1-1. INTERNATIONAL NOTAMs

No Change

d. The USNOF issues international NOTAMs concerning the GPS systems as well as certain special activity airspace for ARTCCs; that is, ARTCC and CARF altitude reservations (ALTRVs) and warning areas. Warning areas and ALTRVs are filed under the associated ARTCC ICAO location indicator (KZBW, KZHU, KZJX, KZLA, KZMA, KZNY, KZOA, KZSE, **KZWY, KZAK, PAZN**, PAZA, PHZH, or TJZS). Information concerning permanent, long-term general data and selected foreign advisories are stored under KFDC location indicator. GPS information is stored under KNMH.

NEW

8-1-2. INTERNATIONAL NOTAM DATA FORMAT

No Change

NOTE-
NOTAMR (NOTAM replacement) and NOTAMC (NOTAM cancellation) are valid contractions and will be followed by another NOTAM number that is being replaced or canceled.

NEW

8-2-1. REQUEST FOR CANADIAN NOTAMs FROM THE CANADIAN NOTAM SYSTEM

a. The NS receives NOTAM data from Canada. The NS cannot confirm that they have all NOTAM data; therefore, you are urged to visit the Canadian **Website** for the most current and up-to-date NOTAM data.

Delete

No Change

NOTE-
Refer to current Canadian charts and flight information publications for information within Canadian airspace.

1. PARAGRAPH NUMBER AND TITLE:

- Appendix A. 5-1-3. MOVEMENT AREA
- Appendix A. 5-1-4. FIELD CONDITIONS REPORTING
- Appendix A. 5-1-5. AERODROME FACILITIES
- Appendix A. 5-2-1. LIGHTING AIDS
- Appendix A. 5-2-2. OBSTACLES
- Appendix A. 5-3-7. NAVAID CONDITIONS
- Appendix A. 5-3-8. SATELLITE BASED SYSTEMS
- Appendix A. 5-4-3. COMMUNICATION NOTAM FORMAT
- Appendix A. 5-5-1. GENERAL
- Appendix A. 5-5-2. CHANGES TO PUBLISHED SERVICES
- Appendix A. 5-5-3. HOURS OF OPERATION
- Appendix A. 5-5-4. WEATHER AND WEATHER REPORTING EQUIPMENT
- Appendix A. 6-1-1. AIRSPACE NOTAM FORMAT
- Appendix A. 6-1-2. SPECIAL ACTIVITY AIRSPACE
- Appendix A. 6-1-3. AIRSPACE AND ALTITUDE RESERVATIONS
- Appendix A. 6-1-4. SPECIAL AERIAL REFUELING
- Appendix A. 6-1-5. AIRSPACE NOTAMS REQUIRING AUTHORIZATION/WAIVER
- Appendix A. 6-1-6. SURFACE AREA AIRSPACE
- Appendix A. 7-1-4. HIGH BAROMETRIC PRESSURE WARNING
- Appendix A. 7-1-7. SPECIAL DATA
- Appendix C. ICAO DIFFERENCE FOR THE UNITED STATES
- Appendix F. RADIOSONDE/UNMANNED FREE BALLOON FLIGHTS
- Appendix G. TECHNICAL OPERATIONS REFERENCE CHART

2. BACKGROUND: The changes within Appendix A are to update examples, correct and align references with policy, and to group and arrange for clearer referencing. Examples needed to align with other orders and documents, therefore numerous additions and corrections were made. Updates made to examples after coordination with FAA offices overseeing Technical Operations, ATC contingency, UAS policy and high barometric pressure.

3. CHANGE:

<u>OLD</u>	<u>NEW</u>
5-1-3. MOVEMENT AREA	5-1-3. MOVEMENT AREA
Title through <i>TBL 5-1-1</i>	No Change
<i>EXAMPLES-</i>	<i>EXAMPLES-</i>
<i>...RWY 01L/19R COMMISSIONED 10301FT X 150FT CONC LGTD. DECLARED DIST: RWY 01L TORA 10301FT TODA 10301FT ASDA 10301FT LDA 10301FT. RWY 19R TORA 10301FT TODA 10301FT ASDA 10301FT LDA 10301FT. ...</i>	<i>...RWY 01L/19R COMMISSIONED <u>E OF TWY A, 10301FT X 150FT CONC LGTD PCR: 760 R/B/W/T.</u> DECLARED DIST: RWY 01L TORA 10301FT TODA 10301FT ASDA 10301FT LDA 10301FT. RWY 19R TORA 10301FT TODA 10301FT ASDA 10301FT LDA 10301FT. <u>YMMDDHHMM-PERM</u></i>
<i>...TWY <u>M8 COMMISSIONED 500FT X 75FT CONC LGTD...</u></i>	<i>...TWY <u>C1 COMMISSIONED WEST OF TWY A BTN TWY A3 AND TWY A4 500FT X 50FT ASPH LGTD PCR70 YMMDDHHMM-PERM</u></i>
c through h Examples	No Change

i. Surface Markings and Signage

No Change

EXAMPLES-

...AD AP SIGNS OBSC...
...RWY 21 4000FT DIST REMAINING SIGN NOT LGTD
...TWY U7 HLDG PSN SIGN FOR RWY 01L/19R NOT LGTD
...TWY ALL SFC PAINTED HLDG PSN SIGNS NOT STD DUE TO REPAINTING...
...RWY 01/19 SFC MARKING NOT STD...

EXAMPLES-

...AD AP SIGNS OBSC...
...RWY 21 4000FT DIST REMAINING SIGN LGT U/S...
...TWY U7 HLDG PSN SIGN FOR RWY 01L/19R LGT U/S...
...TWY ALL SFC PAINTED HLDG PSN SIGNS NOT STD (Include plain language description of why signs are not standard)...
...RWY 01/19 CL MARKING NOT STD (Include plain language description of why marking is not standard)...

OLD

NEW

5-1-4. FIELD CONDITIONS REPORTING

5-1-4. FIELD CONDITIONS REPORTING

**Title through Slippery When Wet
Braking Action**

No Change
No Change

EXAMPLES-

...RWY 09/27 FICON BA MEDIUM TO POOR...
...TWY AA FICON BA GOOD TO MEDIUM...
...APRON MAIN APN FICON BA POOR...

EXAMPLES-

...TWY AA FICON BA GOOD TO MEDIUM...
...APRON MAIN APN FICON BA POOR...
...RWY 09/27 FICON BA MEDIUM TO POOR...

NOTE-

This runway is a non-paved surface.

No Change

OLD

NEW

5-1-5. AERODROME FACILITIES

5-1-5. AERODROME FACILITIES

f through j

Re-letter **a** through **e**

k. Airport Design Group

f. Airplane Design Group

EXAMPLE-

...AD AP CLSD TO ACFT WINGSPAN MORE THAN 214FT AND TAIL HGT MORE THAN 66FT...

No Change

OLD

NEW

5-2-1. LIGHTING AIDS

5-2-1. LIGHTING AIDS

a. Approach light systems (ALS). Only use the runway direction for which the equipment pertains.

Delete

1. When commissioning approach light systems, indicate the exact type of system; for example, MALSR, MALSF, etc.

Delete

EXAMPLE-

...RWY 12 MALSR COMMISSIONED...

Delete

2. Once commissioned and published, approach light systems need only be shown as ALS.

Delete

EXAMPLES-

...RWY 36 ALS U/S...
...RWY 18 ALS U/S...

Delete

NOTE- Delete
ALSF-1 is the type of approach lighting at that airport.

EXAMPLE- Delete
...RWY 22 ALS U/S EXC MEDIUM INTST ON
CONS...

3. When the ALS has been reduced to the Simplified, Short ALS with Runway Alignment Lights, issue the condition as temporarily changed (“NOW”) and not out of service/unserviceable. Delete

EXAMPLE- Delete
...RWY 22 ALSF-1 NOW SSLAR...

b. Lead off /lead on lights. NOTAMs issued using keyword RWY. Delete

NOTE- Delete
Lead off and lead on light will be the standardized verbiage for lead off/on lights, which are sometimes referred to as turnoff lights.

EXAMPLES- Delete
...RWY 01C LEAD OFF LGT FOR TWY Y4 U/S...
...RWY 01C LEAD ON LGT FOR TWY Y9 OBSC...

c. Runway status light system. Delete

EXAMPLES- Delete
...RWY 18L RWY STATUS LGT SYSTEM U/S...
...AD AP RWY STATUS LGT SYSTEM U/S...
...RWY 18L/36R RWY STATUS LGT SYSTEM U/S...

1. Runway entrance lights. Delete

EXAMPLES- Delete
...TWY ALL RWY ENTRANCE LGT FOR RWY 09L
SOUTH SIDE U/S...
...TWY K5, K6, T RWY ENTRANCE LGT FOR RWY
09L U/S...

2. Take-off hold lights. Delete

EXAMPLE- Delete
...RWY 28 TKOF HOLD LGT U/S...

d. Sequence flashing lights/runway alignment indicator lights. Delete

EXAMPLES- Delete
...RWY 18 SEQUENCED FLG LGT OBSC...
...RWY 18 RAILGTT U/S...

e. Visual approach lighting. Delete

1. Visual approach slope indicator (VASI). Delete

EXAMPLES-...RWY 01L PAPI U/S......RWY 01 PAPI UNUSABLE......RWY 10 PAPI BEYOND 5DEG LEFT OF RCL UNUSABLE......RWY 28 PAPI COMMISSIONED......RWY 30 PAPI COMMISSIONED GPA 3.15DEG......RWY 12 PAPI GPA CHANGED TO 3.2DEG......RWY 34 PAPI BEYOND 2.8NM UNUSABLE...**2. Precision approach path indicator (PAPI).****EXAMPLES-**...RWY 01L PAPI U/S......RWY 01 PAPI UNUSABLE......RWY 10 PAPI BEYOND 5DEG LEFT OF RCL UNUSABLE......RWY 28 PAPI COMMISSIONED......RWY 30 PAPI COMMISSIONED GPA 3.15DEG......RWY 12 PAPI GPA CHANGED TO 3.2DEG......RWY 34 PAPI BEYOND 2.8NM UNUSABLE...**3. Runway end identifier lights.****EXAMPLES-**...RWY 18 RWY END ID LGT U/S...**4. Threshold lights (RTHL).****EXAMPLE-**...RWY 27 RTHL U/S...**f. Runway end lights (RENL).****EXAMPLE-**...RWY 09 RENL U/S...**g. Runway edge lights (REDL).**

1. When commissioning runway edge light systems, indicate the exact type of system; for example, LIRL, MIRL, HIRL, etc.

EXAMPLE-...RWY 13/31 HIRL COMMISSIONED...

2. Once commissioned and published, runway edge lights must only be shown as REDL.

EXAMPLES-...RWY 13/31 REDL U/S......RWY 01/19 REDL U/S EXC MEDIUM INTST ON CONS...**3. Runway lights obscured due to snow and ice.****EXAMPLE-**...RWY 15/33 REDL OBSC...

Delete

NOTE-

Delete

1. All edge lights for runway 15/33 are completely obscured. The reason for the obscuration should not be reported.

2. Lights that are partially obscured should not be reported.

h. Runway centerline light (RCLL).

Delete

EXAMPLE-

Delete

...RWY 08R/26L RCLL U/S...

i. Touchdown zone lights (RTZL).

Delete

EXAMPLE-

Delete

...RWY 08R RTZL U/S...

j. Runway lead-in lighting system (RLLS).

Delete

EXAMPLE-

Delete

...AD APLGT ALL U/S...

k. Airport lighting total power failure.

Delete

EXAMPLE-

Delete

...RWY 08R RTZL U/S...

l. Pilot-controlled lighting (PCL) frequency when it controls approach lights or runway lights.

Delete

EXAMPLES-

Delete

...SVC PCL ALL U/S...

...SVC PCL RWY 18/36 REDL U/S...

...SVC PCL RWY 18 ALS U/S...

...SVC PCL RWY 18/36 MEDIUM/HIGH INTST U/S...

...SVC PCL ALL UNUSABLE BEYOND 2NM...

NOTE-

Delete

All the PCL services for runway 18/36 only have low intensity operating.

EXAMPLES-

Delete

...SVC PCL RWY 14/32 COMMISSIONED KEY
FREQ 122.7 7 TIMES HIGH, 5 TIMES MEDIUM, 3
TIMES LOW INTST...

...SVC PCL RWY 01/19 NOT STD KEY FREQ 122.7 5
TIMES HIGH, 3 TIMES MEDIUM, 2 TIMES LOW
INTST...

NOTE-

Delete

The PCL frequency transmissions is not standard, and the new information is provided until it is back to standard.

...SVC PCL FREQ CHANGED TO 122.8...

NOTE-

Delete

PCL frequency need not be an ATC frequency.

m. Taxiway lighting.

Delete

1. Taxiway edge lights.

Delete

EXAMPLES-

...TWY K, L EDGE LGT U/S...
...TWY ALL EDGE LGT WEST OF RWY 16L/34R
U/S...
...TWY ALL EDGE LGT U/S...

Delete

NOTE-

PCL frequency need not be an ATC frequency.

Delete

2. Taxiway centerline lights.

Delete

EXAMPLE-

...TWY E CL LGT BTN TWY E1 AND RWY 15/33
U/S...

Delete

3. Runway guard lights. NOTAM issued using keyword TWY.

Delete

EXAMPLES-

.....TWY ALL RWY GUARD LGT U/S...
...TWY A4 RWY GUARD LGT FOR RWY 01L/19R
U/S...

Delete

4. Stop bar lights. NOTAM issued using keyword TWY.

Delete

EXAMPLE-

...TWY C STOP BAR LGT FOR RWY 16R/34L U/S...

Delete

5. Taxiway lights obscured due to snow and ice.

Delete

EXAMPLES-

...TWY C EDGE LGT OBSC...
...TWY ALL LGT OBSC...

Delete

NOTE-

- 1. OBSC can be used to describe the physical state of airport infrastructure, including signs and markings.
- 2. All taxiway C edge lights are completely obscured. The reason for the obscuration should not be reported.
- 3. Lights that are partially obscured should not be reported.
- 4. In this example all of the taxiways have the two types of taxiway lighting obscured.

Delete

Add

a. Commissioning approach lighting systems (ALS) and runway edge lights (REDL).

Add

EXAMPLE-
...RWY 12 MALSR COMMISSIONED...
...RWY 12/30 HIRL COMMISSIONED...

Add

b. Lead-in lights.

Add

EXAMPLES-
...RWY 01C RLLS U/S...
...RWY 32 RLLS U/S EXC LOW INTST ON
CONS...

Add

c. Approach light system.

- Add **EXAMPLES-**
...RWY 01 ALS U/S...
...RWY 19 ALS U/S EXC MEDIUM INTST ON
CONS...
...RWY 06 ALSF-2 NOW SSALR...
...RWY 24 SEQUENCED FLG LGT U/S...
...RWY 11 1000-FOOT BAR U/S...
...RWY 16 RAI LGT U/S...
...RWY 34 RTHL U/S...
- Add **NOTE-**
Technical Operations issue RTHL, when associated
with approach lighting systems (ALS).
- Add **d. Visual approach lighting.**
- Add **EXAMPLES-**
...RWY 05 VASI U/S...
...RWY 04 VASI UNUSABLE...
...RWY 13 VASI BEYOND 5DEG LEFT OF RCL
UNUSABLE
...RWY 02 VASI NOW 2 BOX (TIME-TIME)...For
a temporary change
...RWY 02 VASI CHANGED TO 2 BOX
(YYMMDDHHMM-PERM)
...RWY 34 VASI BEYOND 3.0NM UNUSABLE...
...RWY 01L PAPI U/S...
...RWY 01 PAPI UNUSABLE...
...RWY 10 PAPI BEYOND 5DEG LEFT OF RCL
UNUSABLE...
...RWY 28 PAPI COMMISSIONED...
...RWY 30 PAPI COMMISSIONED GPA
3.15DEG...
...RWY 12 PAPI GPA CHANGED TO 3.2DEG...
...RWY 34 PAPI BEYOND 2.8NM UNUSABLE...
- Add **e. Runway lighting.**
- Add **EXAMPLES-**
...AD AP RWY STATUS LGT SYSTEM U/S...
...RWY 18L RWY STATUS LGT SYSTEM U/S...
...RWY 18L/36R RWY STATUS LGT SYSTEM
U/S...
...TWY ALL RWY ENTRANCE LGT FOR RWY 09L
SOUTH SIDE U/S...
...TWY K5, K6, T RWY ENTRANCE LGT FOR
RWY 09L U/S...
...RWY 28 TKOF HOLD LGT U/S...
...RWY 34 RTHL U/S...
- Add **NOTE-**
Airport Operations issue RTHL, when not associated
with approach lighting systems (ALS).

Add ...RWY 18 RWY END ID LGT U/S...
...RWY 08R RTZL U/S...
...RWY 08R/26L RCLL U/S...
...RWY 13/31 REDL U/S...
...RWY 01/19 REDL U/S EXC MEDIUM INTST
ON CONS...
...RWY 09 RENL U/S...

Add **f. Taxiway lighting.**

Add **EXAMPLES-**
...TWY B CL LGT U/S
...TWY E CL LGT BTN TWY E1 AND RWY 15/33
U/S...
...TWY K, L EDGE LGT U/S...
...TWY ALL EDGE LGT WEST OF RWY 16L/34R
U/S...
...TWY ALL EDGE LGT U/S...

Add **NOTE-**
ALL means every taxiway at an airport even if there is
only a single taxiway.

Add ...TWY ALL RWY GUARD LGT U/S...
...TWY A4 RWY GUARD LGT FOR RWY
01L/19R U/S...
...TWY C STOP BAR LGT FOR RWY 16R/34L
U/S...

Add **NOTE-**
NOTAM for guard light and stop bar light issued using
keyword TWY.

Add **g. Lead off / lead on lights.**

Add **EXAMPLE-**
...RWY 01C LEAD OFF LGT FOR TWY Y4 U/S...

Add **NOTE-**
NOTAMs issued using keyword RWY. Lead off and
lead on light will be the standardized verbiage for lead
off/on lights, which are sometimes referred to as
turnoff.

Add **h. Pilot-controlled lighting.**

Add **EXAMPLES-**
...SVC PCL ALL U/S...
...SVC PCL RWY 18/36 REDL U/S
...SVC PCL RWY 18 ALS U/S...
...SVC PCL RWY 18/36 MEDIUM/HIGH INTST
U/S...
...SVC PCL ALL UNUSABLE BEYOND 2NM...
...SVC PCL RWY 18/36 MEDIUM/HIGH INTST
U/S...

Add **NOTE-**
All the PCL services for runway 18/36 only have low
intensity operating.

- Add ...SVC PCL RWY 14/32 COMMISSIONED KEY
FREQ 122.7 7 TIMES HIGH, 5 TIMES MEDIUM, 3
TIMES LOW
INTST...
...SVC PCL RWY 01/19 NOT STD KEY FREQ 122.7
5 TIMES HIGH, 3 TIMES MEDIUM, 2 TIMES LOW
INTST...
- Add NOTE-
The PCL frequency transmissions is not standard, and
the new information is provided until it is back to
standard.
- Add ...SVC PCL FREQ CHANGED TO 122.8...
- Add NOTE-
PCL frequency need not be an ATC frequency.
- Add i. Airport lighting total power failure.
- Add EXAMPLE-
...AD AP LGT ALL U/S...
- Add j. Lights obscured.
- Add EXAMPLES-
...RWY 15/33 REDL OBSC...
...RWY 01C LEAD ON LGT FOR TWY Y9 OBSC...
...TWY C EDGE LGT OBSC...
...TWY ALL LGT OBSC...
- Add NOTE-
In this example all of the taxiways' lighting is fully
obscured.

OLD

5-2-2. OBSTACLES

EXAMPLES-

*...OBST CRANE (ASN 2013-ACE-5-NRA)
345140N0804506W (1.44NM SW N52) 580FT (195FT
AGL) NOT LGTD...
!CLE ZOB OBST WIND TURBINE FARM WI AN
AREA DEFINED AS 4NM RADIUS OF
411931N0822776W (17NM W LPR) 2820FT (410FT
AGL) NOT LGTD...*

NEW

5-2-2. OBSTACLES

EXAMPLES-

*OBST CRANE (ASN 2013-ACE-5-NRA)
345140N0804506W (1.44NM SW N52) 580FT (195FT
AGL) **FLAGGED**, NOT LGTD...
!CLE ZOB OBST WIND TURBINE FARM WI AN
AREA DEFINED AS 4NM RADIUS OF
411931N0822776W (17NM W LPR) 2820FT (410FT
AGL) **LGT U/S...***

OLD

5-3-7. NAVAID CONDITIONS

Title through c6(d) Examples

**(f) Instrument Landing Systems (ILS).
Precision.**

NEW

5-3-7. NAVAID CONDITIONS

No Change

**(f) Instrument Landing Systems (ILS).
Precision.**

EXAMPLES-

...NAV ILS RWY 35L U/S...
 ...NAV ILS RWY 32 110.3 COMMISSIONED...
 ...NAV ILS RWY 08R SNOOP LOM U/S...
 ...NAV ILS RWY 05 U/S...-PERM
 ...NAV ILS RWY 18 DME U/S...
 ...NAV ILS RWY 02 FAN MKR U/S...
 ...NAV ILS RWY 18 GP UNUSABLE SFC-768FT ...
 ...NAV ILS RWY 02 GP/OM/MM U/S...
 ...NAV ILS RWY 30 GP UNUSABLE BEYOND 5DEG
 LEFT OF COURSE ...
 ...NAV HJT ILS RWY 04L U/S...

NOTE-

Offset ILS are issued with the 3 letter ID (HJT) to the localizer after the Keyword NAV.

EXAMPLE-

...NAV ILS RWY 30 FAC PER CLASSIFICATION CODE CHANGED TO CLASS IIIE...

NOTE-

For runway 30, the ILS facility performance classification code has been changed from the previously published data.

(g) Localizer/LOC Directional Aid/Simplified Directional Facility Azimuth.

EXAMPLES-

...NAV ILS RWY 30 LOC RTS...
 ...NAV ILS RWY 35L U/S...
 ...NAV ILS RWY 12 LOC UNUSABLE BEYOND
 4DEG RIGHT OF COURSE ...
 ...NAV ILS RWY 12 LOC UNUSABLE BEYOND RWY
 THR...
 ...NAV LOC RWY 27 U/S...
 ...NAV LOC RWY 33 LOC UNUSABLE WI .4NM ...
 ...NAV LOC RWY 16 BC UNUSABLE BEYOND
 6DEG RIGHT OF COURSE...
 ...NAV LOC TYPE DIRECTIONAL AID U/S...

NOTE-

The LDA at the airport, not a particular runway, is unserviceable.

...NAV VHW LOC TYPE DIRECTIONAL AID RWY 18
 LOC U/S...
 ...NAV SIMPLIFIED DIRECTIONAL FAC RWY 23
 U/S...

OLD

5-3-8. SATELLITE BASED SYSTEMS

Title through c2

d. Service Availability Prediction Tool (SAPT).

EXAMPLES-

...NAV ILS RWY 35L U/S...
 ...NAV ILS RWY 32 110.3 COMMISSIONED...
 ...NAV ILS RWY 08R SNOOP LOM U/S...
 ...NAV ILS RWY 05 U/S...-PERM
 ...NAV ILS RWY 18 DME U/S...
 ...NAV ILS RWY 02 FAN MKR U/S...
 ...NAV ILS RWY 18 GP UNUSABLE SFC-768FT ...
 ...NAV ILS RWY 02 GP/OM/MM U/S...
 ...NAV ILS RWY 30 GP UNUSABLE BEYOND 5DEG
 LEFT OF COURSE ...
 ...NAV BZB ILS RWY 22R U/S...

NOTE-

Offset ILS are issued with the 3 letter ID (example BZB) for the localizer after the Keyword NAV.

No Change

No Change

(g) Localizer/LOC Directional Aid/Simplified Directional Facility Azimuth.

EXAMPLES-

...NAV ILS RWY 30 LOC RTS...
 ...NAV ILS RWY 35L U/S...
 ...NAV ILS RWY 12 LOC UNUSABLE BEYOND
 4DEG RIGHT OF COURSE ...
 ...NAV ILS RWY 12 LOC UNUSABLE BEYOND RWY
 THR...
 ...NAV LOC RWY 27 U/S...
 ...NAV LOC RWY 33 LOC UNUSABLE WI .4NM ...
 ...NAV LOC RWY 16 BC UNUSABLE BEYOND
 6DEG RIGHT OF COURSE...
 ...NAV LOC RWY 14 LOC/DME U/S...
 ...NAV LOC TYPE DIRECTIONAL AID U/S...

NOTE-

The Localizer Directional Aid at the airport, not a particular runway, is unserviceable.

No Change

NEW

5-3-8. SATELLITE BASED SYSTEMS

No Change

No Change

EXAMPLE-
 !FDC XX/XXX FDC SVC ADS-B SER AVBL
 PREDICTION TOOL U/S SEE AC 90-114 FOR
 PREFLIGHT GUIDANCE YMMDDHHMM-YM-
 MDDHHMM...

EXAMPLES-
 !FDC x/xxxx ZHU AIRSPACE ADS-B, AUTO
 DEPENDENT SURVEILLANCE-REBROADCAST
 (ADS-R), TFC INFO SER BCST (TIS-B), FLT INFO
 SER BCST (FIS-B) SER MAY NOT BE AVBL WI AN
 AREA DEFINED AS 139NM RADIUS OF
 261010N0892142W. AIRSPACE AFFECTED MAY
 INCLUDE GULF OF MEXICO AREAS OF GREEN
 CANYON, EWING BANK, MISSISSIPPI CANYON.
 SFC-UNL...

EXAMPLE-
 !FDC XX/XXX FDC AIRSPACE ADS-B SERVICE
AVAILABILITY PREDICTION TOOL (SAPT) U/S
 SEE AC 90-114 FOR PREFLIGHT GUIDANCE
 YMMDDHHMM-YMMDDHHMM...

EXAMPLES-
 !FDC x/xxxx ZHU AIRSPACE ADS-B, AUTO
 DEPENDENT SURVEILLANCE-REBROADCAST
 (ADS-R), TFC INFO SER BCST (TIS-B), FLT INFO
 SER BCST (FIS-B) SER MAY NOT BE AVBL WI AN
 AREA DEFINED AS 139NM RADIUS OF
 261010N0892142W. AIRSPACE AFFECTED MAY
 INCLUDE GULF OF AMERICA AREAS OF GREEN
 CANYON, EWING BANK, MISSISSIPPI CANYON.
 SFC-UNL...

OLD

**5-4-3. COMMUNICATION OUTLET
CONDITIONS**

**b. Commissioning, decommissioning, outage,
or (un)availability of communications outlets**

EXAMPLES-
...COM ARINC CPDLC NOT AVBL...
...COM CPDLC NOT AVBL...
...COM CTAF 122.8 COMMISSIONED...
...COM UNICOM FREQ 122.8 U/S...
...COM LOCAL CTL 118.9, GND CTL 121.0
COMMISSIONED...
...COM CLR DELIVERY 121.7 U/S...
...COM GND COM OUTLET 135.075 U/S...
...COM LOCAL AP ADVISORY 121.3 U/S...

NOTE-
Local Airport Advisory frequency unserviceable.

EXAMPLES-
...COM REMOTE AP ADVISORY 123.65 U/S...
...COM REMOTE COM OUTLET 122.6 U/S...

NOTE-
*The airport's other frequency 255.4 is still operating. If
 both were unserviceable, the NOTAM would be
 "...COM REMOTE COM OUTLET U/S..."*

EXAMPLES-
!JBR 1SH COM SOCIAL HILL REMOTE COM
OUTLET U/S...
...COM VOR VOICE U/S...
...COM REMOTE TRANS/REC 126.25, 131.25 U/S...
...COM REMOTE COM A/G U/S...
...COM REMOTE COM OUTLET 122.5 U/S...
!DCA 2D2 COM FALLS CHURCH REMOTE COM
OUTLET 122.6 U/S...

Add

NEW

**5-4-3. COMMUNICATION NOTAM
FORMAT**

Delete

Delete

Delete

Delete

Delete

Delete

c. 1. Commissioning and decommissioning.

Add **EXAMPLES-**
...COM CTAF 122.8 COMMISSIONED...-PERM
...COM LOCAL CTL 118.9, GND CTL 121.0
COMMISSIONED...-PERM
...COM REMOTE COM OUTLET 122.6
U/S...-PERM
...COM LOCAL CTL 118.9, GND CTL 121.0
COMMISSIONED...

Add **c. 2. Outage, or (un)availability of communications outlets.**

Add **EXAMPLES-**
...COM REMOTE COM OUTLET 122.6 U/S...
...COM REMOTE TRANS/REC 126.25, 131.25
U/S...
...COM REMOTE COM OUTLET U/S...
...COM GRAND ISLE REMOTE COM OUTLET
122.4 U/S
...COM DUTCH HARBOR REMOTE CENTER A/G
268.7 U/S...
...COM VOR VOICE U/S...
...COM VOR 122.1 U/S...
...COM ARINC CPDLC NOT AVBL...
...COM CLR DELIVERY 121.7 U/S...
...COM GND COM OUTLET 135.075 U/S...
...COM LOCAL AP ADVISORY 121.3 U/S...
...COM UNICOM FREQ 122.8 U/S...

Add **c. 3. Communication outlet or facility frequency change.**

Add **EXAMPLES-**
...COM CLR DELIVERY 121.7 NOW 124.125...
...CPDLC DEP CLR LOGON CHANGED TO
KUSA...
...COM REMOTE COM OUTLET 122.6
CHANGED TO 122.2...

OLD

NEW

Add

5-5-1. GENERAL

Add

EXAMPLES-
SVC TWR VISUAL SIGNAL NOT AVBL LIGHT
GUN U/S...

OLD

NEW

5-5-2. CHANGES TO PUBLISHED SERVICES

5-5-2. CHANGES TO PUBLISHED SERVICES

EXAMPLES-
...SVC TWR COMMISSIONED...
...SVC ATIS NOT AVBL...

No Change

NOTE-
When ATIS is not available for other than equipment malfunction, use NOT AVBL.

No Change

EXAMPLES-

...SVC ATIS 134.025 U/S...
...SVC ATIS 134.025 NOT AVBL...

No Change

NOTE-

The Automated UNICOM weather broadcast is not available.

No Change

Add

EXAMPLES-

...SVC LOCAL AP ADVISORY SER NOT AVBL...

Add

NOTE-

The CTAF frequency at an airport is U/S, and the FSS providing local airport advisory services is not CLSD.

EXAMPLE-

...SVC AUNICOM U/S...

No Change

NOTE-

The Automated UNICOM is unserviceable.

No Change

OLD

NEW

5-5-3. HOURS OF OPERATION

5-5-3. HOURS OF OPERATION

Title through a1 Note 2

No Change

2. Approach Control.

No Change

EXAMPLES-

...SVC XXXXXX APP CLSD CLASS C SER INVOLVING VFR ACFT NOT AVBL CTC XXXXXX ARTCC FOR CLASS C ARR COM ON XXX.XX, FOR CLR DELIVERY AT XXX-XXX-XXXX...

EXAMPLES-

...SVC XXXXXX APP CLSD CLASS C SER INVOLVING VFR ACFT NOT AVBL CTC XXXXXX ARTCC FOR CLASS C ARR COM ON XXX.XX, FOR CLR DELIVERY AT XXX-XXX-XXXX...

Add

...SVC XXXXXX APP CLSD TERMINAL RADAR SERVICE AREA SER INVOLVING VFR ACFT NOT AVBL CTC XXXXXX ARTCC FOR TERMINAL RADAR SERVICE AREA ARR COM ON XXX.XX, FOR CLR DELIVERY AT XXX-XXX-XXXX...

Add

NOTE-

For approach facilities with a Terminal RADAR Service Area, the overlying ARTCC is unable to provide Terminal RADAR Service Area services.

3. Air traffic control tower.

No Change

EXAMPLE-

...SVC TWR CLSD TWR XXX.XX NOW CTAF CLASS B SER AVBL CTC XXXXXX APP FOR CLASS B VFR DEP AND IFR CLR DELIVERY AT XXX-XXX-XXXX...

No Change

NOTE-

Class B stand-alone ATCT with operational overlying TRACON. Class B VFR separation services remain.

No Change

EXAMPLE-

...SVC TWR CLSD TWR XXX.XX NOW CTAF CLASS B SER AVBL CTC XXXXXX APP FOR CLASS B VFR DEP AND IFR CLR DELIVERY ON XXX.XX...

No Change

NOTE-

Class B combined ATCT/TRACON with operational overlying TRACON. Class B VFR separation services remain.

No Change

EXAMPLES-

...SVC TWR CLSD TWR XXX.XX NOW CTAF CLASS B VFR OPS NOT PERMITTED CTC XXXXXX ARTCC FOR CLASS B ARR ON XXX.XX, FOR CLR DELIVERY ON XXX.XX...

...SVC XXXXXX APP CLSD CLASS B VFR OPS NOT PERMITTED CTC XXXXXX ARTCC FOR CLASS B ARR ON XXX.XX, FOR CLR DELIVERY AT XXX-XXX-XXXX...

EXAMPLES-

...SVC TWR CLSD TWR XXX.XX NOW CTAF CLASS B VFR OPS NOT PERMITTED CTC XXXXXX ARTCC FOR CLASS B ARR ON XXX.XX, FOR CLR DELIVERY ON XXX.XX...

...SVC XXXXXX APP CLSD CLASS B VFR OPS NOT PERMITTED CTC XXXXXX ARTCC FOR CLASS B ARR ON XXX.XX, FOR CLR DELIVERY AT XXX-XXX-XXXX...

...SVC XXXXXX APP CLSD TERMINAL RADAR SERVICE AREA SER INVOLVING VFR ACFT NOT AVBL CTC XXXXXX ARTCC FOR TERMINAL RADAR SERVICE AREA ARR COM ON XXX.XX, FOR CLR DELIVERY AT XXX-XXX-XXXX...

Add

NOTE-

For stand-alone, part-time ATCT (published CTAF) with operational overlying Approach facility (Terminal RADAR Service Area VFR separation services remain), no Terminal RADAR Service Area arrival communication information necessary because frequency is published.

4. Flight Service Station.

No Change

EXAMPLES-

...SVC XXXXXX FSS CLSD...

...SVC XXXXXX FSS U/S...

...SVC XXXXXX FSS CLSD LOCAL AP ADVISORY SER NOT AVBL...

No Change

b through b Note

No Change

c. Extended hours of operation

No Change

EXAMPLE-

...SVC TWR OPN...

EXAMPLE-

...SVC TWR OPN PLUS SEE CHART SUPPLEMENT YMMDD0330-YMMDD0530
...SVC TWR OPN PLUS SEE CHART SUPPLEMENT DLY 0330-0530 YMMDD0330-YMMDD0530

d. Traffic Management Program Alerts.

No Change

EXAMPLES-

...SVC TFC MANAGEMENT PROGRAM ALERT SEE DOMESTIC NOTICES RESERVATION REQUIRED...

...SVC TFC MANAGEMENT PROGRAM ALERT SEE TFC MANAGEMENT MSG RESERVATION REQUIRED...

EXAMPLES-

...SVC TFC MANAGEMENT PROGRAM ALERT SEE DOMESTIC NOTICES RESERVATION REQUIRED...

NOTE-

Details of each traffic management program are published in Domestic Notices or included in a special traffic management program advisory message.

Delete

EXAMPLE-

...SVC TFC MANAGEMENT PROGRAM ALERT SEE ATCSCC MSG...

...SVC TFC MANAGEMENT PROGRAM ALERT SEE ATCSCC MSG...

OLD

5-5-4. WEATHER AND WEATHER REPORTING EQUIPMENT

Title through c3 Note

c4 Erroneous date/time group.

NEW

5-5-4. WEATHER AND WEATHER REPORTING EQUIPMENT

No Change

No Change

Delete

EXAMPLES-

...SVC WX REPORTING NOT AVBL...

EXAMPLE-

...SVC AUTOMATED WX BCST SYSTEM DTG UNREL...

NOTE-

...SVC AUTOMATED WX BCST SYSTEM DTG UNREL...

OLD

Add

Add

Add

Add

Add

Add

NEW

6-1-1. AIRSPACE NOTAM FORMAT

EXAMPLES-

!SUAW mm/nnn ZSE AIRSPACE OKANOGAN C MOA ACT 300FT-8999FT YYMMDD1815-YYMMDD2245

EXAMPLES-

!CARF mm/nnn ZDC AIRSPACE DCC VIENNA STNR ALT RESERVATION WIAN AREA DEFINED AS 7NM RADIUS OF SBY312017 SFC-3500FT 2312021500-2312021930

EXAMPLES-

... AIRSPACE UNMANNED ROCKET WIAN AREA DEFINED AS 1NM RADIUS OF 424238N0902332W (2.5NM E PVB) SFC-4500FT YYMMDD1400- YYMMDD2300

EXAMPLES-

...9N1 AIRSPACE AEROBATIC ACFT WIAN AREA DEFINED AS 403200N0750842W (3.4NM NW 9N1) TO 403200N0750605W (3.1NM N 9N1) TO 402959N0750605W (1NM N 9N1) TO 402959N0750842W (1.4NM W 9N1) TO POINT OF ORIGIN SFC-7500FT AGL...

EXAMPLES-

...AIRSPACE FLTK ACFT OPS WIAN AREA DEFINED AS 5NM RADIUS OF (airport) SFC-3500FT AGL ACFT CS FLC77...

OLD

6-1-2. SPECIAL ACTIVITY AIRSPACE

NEW

6-1-2. SPECIAL ACTIVITY AIRSPACE

EXAMPLE-

Delete

FDC y/nnn ZLA CA AIRSPACE..NOTICE
TWENTYNINE PALMS, CA. TEMPO RESTRICTED
AREA R-2509W WI AN AREA DEFINED AS
343503N1163610W (HEC19414.5) TO
342225N116310W (HEC17125.5) TO
342738N1164034W (HEC19322.8) TO
342759N1164251W (HECXXXX.X) TO
342944N1164251W (HECXXXX.X) TO POINT OF
ORIGIN. SFC-15000FT. LOS ANGELES CENTER
128.15 IS THE FAA COORDINATION FACILITY.
USMC RANGE CONTROL 760-830-3737 FOR
STATUS UPDATES. 1804070424-1805071200

Add

EXAMPLES-

!SUAW mm/nnn ZLC AIRSPACE SADDLE A MOA
ACT 10000FT-17999FT YMMDD1515-YM-
MDD0530
...(ARTCC) AIRSPACE (SUA) ACT 8000FT-FL235
YMMDD1900-YMMDD0500
...AIRSPACE DRUM MOA ACT 500FT
AGL-4999FT...
SUAW mm/nnn ZLA AIRSPACE TEMPO
RESTRICTED AREA R2509W ACT PLUS SEE
DOMESTIC NOTICE YMMDD0424-YM-
MDD1200

Add

NOTE-
Temporary SUA information must be described in the
Domestic Notice. See JO 7400.2, Procedures for
Handling Airspace Matters 21-1-15c.

Add

!SUAW mm/nnn ZLC AIRSPACE LGT OUT/NIGHT
VISION GOGGLE TRG SADDLE A MOA ACT
10000FT-17999FT YMMDD1515-YMMDD0530

Add

NOTE-
NOTAMs for LIGHT OUT/NGT VISION GOGGLE
operations are scheduled times only, identified 48
hours in advance.

OLD

NEW

**6-1-2. b. and c. SPECIAL ACTIVITY
AIRSPACE (SAA)**

Delete

EXAMPLES-

Delete

...AIRSPACE CRYPT NORTH MOA ACT
5000FT-16000FT...
...AIRSPACE LGT OUT/NGT VISION GOGGLE TRG
DESERT AND REVEILLE NORTH/SOUTH MOA
ACT SFC-9000FT AVOIDANCE ADZ...

NOTE-
NOTAMs for LIGHT OUT/NGT VISION GOGGLE operations are scheduled times only, identified 48 hours in advance.

Delete

EXAMPLE-
AIRSPACE DRUM MOA ACT 500FT AGL-4999FT...

Delete

OLD

NEW

6-1-3. AIRSPACE AND ALTITUDE RESERVATIONS

6-1-3. AIRSPACE AND ALTITUDE RESERVATIONS

EXAMPLES-
...AIRSPACE STNR ALT RESERVATION WI AN AREA DEFINED AS 100NM RADIUS OF FJC360020 5500FT-FL270...
...(ARTCC) AIRSPACE STNR ALT RESERVATION WI AN AREA DEFINED AS XXXXXXNXXXXXXXXW (Plain text) TO XXXXXXNXXXXXXXXW (Plain text) TO XXXXXXNXXXXXXXXW (Plain text) TO XXXXXXNXXXXXXXXW (Plain text) TO POINT OF ORIGIN SFC-UNL...

EXAMPLES-
!CARF mm/nnn ZDC AIRSPACE DCC BURGESS STNR ALT RESERVATION WI AN AREA DEFINED AS SBY265052 TO SBY251056 TO SBY242054 TO SBY236048 TO SBY244044 TO POINT OF ORIGIN SFC-3500FT YYDDMM2210-YYDDMM2320
...(ARTCC) AIRSPACE STNR ALT RESERVATION WI AN AREA DEFINED AS XXXXXXNXXXXXXXXW TO XXXXXXNXXXXXXXXW TO XXXXXXNXXXXXXXXW TO XXXXXXNXXXXXXXXW TO POINT OF ORIGIN SFC-UNL...

Delete

GG KDZZNAXX DDHHMM KZOAZRZX FNNNN/YY NOTAMN
Q) KZOA/QWMLM/IV/NBO E/000/999/3411N12456W
A) KZOA
B) EFFECTIVE TIME
C) EXPIRATION TIME
E) AIRSPACE WATER OPS WI AN AREA DEFINED AS XXXXXXNXXXXXXXXW (Plain text) TO XXXXXXNXXXXXXXXW (Plain text) TO XXXXXXNXXXXXXXXW (Plain text) TO POINT OF ORIGIN
NONPARTICIPATING PILOTS ARE STRONGLY ADZ TO AVOID THE ABOVE AREAS. IFR TFC UNDER ATC JURISDICTION SHOULD ANTICIPATE REROUTING IN VCY OF IMPACTS.
F) SFC
G) UNL

OLD

NEW

6-1-4. SPECIAL AERIAL REFUELING

6-1-4. SPECIAL AERIAL REFUELING

EXAMPLES-
...AIRSPACE SPECIAL AERIAL REFUELING TRACK/ANCHOR WI AN AREA DEFINED AS MCN TO IRQ TO GRD TO SUG TO MCN049050 TO POINT OF ORIGIN ACT 12000FT-14000FT... (Pointer NOTAMs for MCN, GRD)

EXAMPLES-
...AIRSPACE SPECIAL AERIAL REFUELING TRACK/ANCHOR WI AN AREA DEFINED AS MCN TO SUG TO GRD090003 TO IRQ TO POINT OF ORIGIN ACT 12000FT-14000FT...

...SEE ZTL XX/XXX AERIAL REFUELING TRACK/ANCHOR...

Delete

OLD

NEW

6-1-5. OTHER AIRSPACE NOTAMS

Delete

a. Airspace NOTAMs

Delete

EXAMPLES-

Delete

...AIRSPACE BALLOON LDG WI AN AREA
DEFINED AS 100NM RADIUS OF ICT PAYLOAD
FALLING FM
150000FT SFC-UNL...

...AIRSPACE HOT AIR BALLOON WI AN AREA
DEFINED AS 2NM RADIUS OF 13M SFC-1500FT...

...AIRSPACE UAS WI AN AREA DEFINED AS 10NM
RADIUS OF BGR130020 (6NM E BHB)
SFC-10000FT AGL FREQ XXX.XX...

...AIRSPACE HIGH INTST FOUR-BEAM SEARCH
LGT WI AN AREA DEFINED AS 2NM RADIUS OF
DJB320015 SFC-4000FT...

...AIRSPACE UNMANNED ROCKET WI AN AREA
DEFINED AS 4NM RADIUS OF ICT SFC-FL250...

...AIRSPACE PYROTECHNIC DEMONSTRATION
WI AN AREA DEFINED AS 2NM RADIUS OF
AML360001 SFC-1500FT...

...AIRSPACE LGT OUT TRG WI AN AREA DEFINED
AS DMN307017 TO DMN052030.6 TO DMN071029.9
TO DMN212016 TO POINT OF ORIGIN
5000FT-12000FT AVOIDANCE ADZ...

...AIRSPACE LGT OUT TRG WI CLASS D SFC
AREA...

NOTE-

Delete

Activities that will prohibit the use of airspace will
require the issuance of an FDC NOTAM by the USNOF.

NOTE-

Delete

NOTAMS specifying or changing the dates and times of
a designated part time surface area must coincide with
issuance of a corresponding Hours of Operation
Services NOTAM and may be issued by the appropriate
facility only after
coordination with the regional/service area office.

EXAMPLES-

Delete

...AIRSPACE CLASS D SFC AREA HR CHANGED
TO ACT MON-FRI 0615-2100, SAT 0830-1700, SUN
1000-1900 YYMMDDHHMM-PERM

...AIRSPACE CLASS E SFC AREA HR CHANGED
TO ACT DLY 0430-0600 YYMMDDHHMM-PERM...

b. Unmanned Free Balloon

Delete

EXAMPLES-

Delete

...AIRSPACE UNMANNED FREE BALLOON
DVV180030 (32NM S DEN) SFC-10000FT SB...

...AIRSPACE UNMANNED FREE BALLOON
ABQ180020 SFC-UNL NEB TO 150000FT...

c. Authorizations and/or Air Traffic notifications are required by the proponent for the following activities; ensure the NOTAM Originator is aware of this. The information is not released in the NOTAM.

Delete

1. Airshows, Demonstrations, Aerobatic Areas.

Delete

(a) FAA authorization will consist of a waiver to 14 CFR Part 91.8*

Delete

(b) Obtain the following information from the requestor:

Delete

(1) Name, address, and telephone number of the person giving notice.

Delete

(2) Identification and frequency to be used.

Delete

2. Unmanned Aircraft Operations.

Delete

(a) FAA authorization will consist of a Certificate of Authorization or Waiver, Special Airworthiness, or similar document. When requested, put the COA in remarks. A COA exists of the year – Service Center (3 centers and AHQ) – serial number – the word COA (20YY – CSA – 23 – COA)

Delete

(b) Obtain the following information from the requestor:

Delete

(1) Name, address, and telephone number of the person giving notice.

Delete

(2) Identification and frequency to be used.

Delete

3. Parachute Jumping/Sky Diving

Delete

(a) Obtain the following information from the requestor:

Delete

(1) Name address, and telephone number of the person requesting authorization or giving notice.

Delete

(2) Identification of the aircraft to be used.

Delete

OLD

NEW

Add

6-1-5. AIRSPACE NOTAM REQUIRING AUTHORIZATION/WAIVER

Add

c.1. Airshows, Aerial Demonstrations, Aerobatic Areas, Hot Air Balloon Events, Flight Test Areas, Light Out Training, Banner Towing.

Add *EXAMPLES-*
...AIRSPACE (Activity) WIAN AREA DEFINED AS 2NM RADIUS OF DJB320015 SFC-4000FT...
...HAR AIRSPACE AEROBATIC ACFT WIAN AREA DEFINED AS 2NM RADIUS OF HAR011009 SFC-5000FT SUN 1400-1800 YYMMDD1400-YYMMDD1800
... AIRSPACE LGT OUT TRG WI CLASS D SFC AREA FRI TUE WED THU 0615-0745 YYMMDD0615-YYMMDD 0745

Add **c.2. Amateur rockets, Unmanned free balloons.**

Add *EXAMPLES-*
AIRSPACE UNMANNED ROCKET WIAN AREA DEFINED AS 4NM RADIUS OF ICT SFC-FL250
...AIRSPACE UNMANNED FREE BALLOON ABQ180020 SFC-UNL NEB TO 150000FT...
...AIRSPACE BALLOON LDG WIAN AREA DEFINED AS 100NM RADIUS OF ICT PAYLOAD FALLING FM 150000FT SFC-UNL...

Add **c.3. Parachute Jumping/Sky Diving**

Add *EXAMPLE-*
...AIRSPACE PJE WIAN AREA DEFINED AS 5NM RADIUS OF BVT080015...

Add **c.4. Unmanned Aircraft Systems (UAS) Operations.**

Add *EXAMPLE-*
...AIRSPACE UAS WIAN AREA DEFINED AS 13NM RADIUS OF SYR SFC-17999FT...

OLD

NEW

Add **6-1-6. SURFACE AREA AIRSPACE**

Add *EXAMPLES-*
...AIRSPACE CLASS D SFC AREA HR CHANGED TO ACT MON-FRI 0615-2100, SAT 0830-1700, SUN 1000-1900 YYMMDDHHMM-PERM
...AIRSPACE CLASS E SFC AREA HR CHANGED TO ACT DLY 0430-0600 YYMMDDHHMM-PERM

OLD

NEW

7-1-4. HIGH BAROMETRIC PRESSURE WARNING

EXAMPLE-
 ...(ARTCC) AIRSPACE HIGH PRESSURE ALTIMETER SETTING PROC ARE IN EFFECT FOR THE MEMPHIS CENTER AREA. SEE AERONAUTICAL INFO MANUAL FOR PROC...

7-1-4. HIGH BAROMETRIC PRESSURE WARNING

EXAMPLE-
 ...(ARTCC) AIRSPACE HIGH **BAROMETRIC** PRESSURE ALTIMETER SETTING PROC FOR ALTIMETER GREATER THAN 31.00 HG BLW 18000FT ARE IN EFFECT FOR THE MEMPHIS CENTER AREA. SEE AERONAUTICAL INFORMATION MANUAL (AIM) FOR PROC...

OLD

7-1-7. SPECIAL DATA

EXAMPLE-

!FDC FDC ... NOTICE ... PILOTS ARE REMINDED...

NEW

7-1-7. SPECIAL DATA

EXAMPLE-

!FDC ~~X/XXXX~~ FDC ... SECURITY ... PILOTS ARE REMINDED...-PERM

OLD

Appendix C. ICAO Difference for the United States

SAPT – Service Availability Prediction Tool

TFR – Temporary Flight Restriction

USPS – United States Postal Service

NEW

Appendix C. ICAO Difference for the United States

Delete

TFR – Temporary Flight Restrictions

Delete

OLD

Appendix F. Radiosonde/Unmanned Free Balloon Flights

F-1. NWS RADIOSONDE/UNMANNED FREE BALLOON FLIGHTS

Use the procedures in this appendix for National Weather Service (NWS) radiosonde balloon releases.

F-2. NWS RADIOSONDE BALLOON RELEASES

a. Issue as Aeronautical Information at least 30 minutes prior to the release of a NWS radiosonde balloon under the following conditions:

1. Delayed Release. A radiosonde balloon that will be released later than the scheduled times of 1130 or 2330 UTC.

2. Special Observations. A release that will be made at times other than those specified for the scheduled observations (1130 or 2330 UTC).

b. The Aeronautical Information must contain the following information:

1. The balloon release time.

2. The time the balloon is expected to reach 10,000 MSL, using an average rate of climb of 800 feet per minute.

c. The locations of radiosonde balloon release points are listed in the Chart Supplements.

NEW

Delete

OLD**Appendix G. Technical Operations Reference Chart**

NOTE-

For “*”, see Chapter 5 and Appendix A.**NEW**

Delete

Delete

OLD

Facility Type	FSEP Name	NOTAM	NOTAM Examples Full outage (FL)	NOTAM Examples Reduced Equipment (RE)	NOTAM Examples Reduced Service (RS)
<u>ALS</u>	<u>APPROACH LIGHTING SYSTEM</u>	<u>YES</u>	<u>RWY 18 ALS U/S</u>	<u>RWY 18 SEQUENCED FLG LGT OTS</u>	<u>N/A</u>
-	-	-	-	<u>RWY 35 RTHL U/S</u>	-
-	-	-	-	<u>RWY 23 ALS U/S EXC MEDIUM INTST ON CONS</u>	-
<u>ASDE</u>	<u>AIRPORT SURFACE DETECTION EQUIPMENT</u>	<u>YES</u>	<u>SVC SMR U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>ASR</u>	<u>AIRPORT SURVEILLANCE RADAR</u>	<u>YES</u>	<u>SVC TAR U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>ATCBI</u>	<u>AIR TRAFFIC CONTROL BEACON INTERROGATOR</u>	<u>YES</u>	<u>SVC SSR U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>ATCRB</u>	<u>AIR TRAFFIC CONTROL RADAR BEACON</u>	<u>YES</u>	<u>SVC SSR U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>ATIS</u>	<u>AUTOMATIC TERMINAL INFORMATION SYSTEM</u>	<u>YES</u>	<u>SVC ATIS NOT AVBL</u>	<u>N/A</u>	<u>N/A</u>
<u>ATISS</u>	<u>AUTOMATIC TERMINAL INFORMATION SYSTEM SERVICE</u>	<u>YES</u>	<u>SVC ATIS NOT AVBL</u>	<u>N/A</u>	<u>SVC ATIS 257.7 U/S</u>
<u>AWOS</u>	<u>AUTOMATED WEATHER OBSERVING SYSTEM</u>	<u>YES</u>	<u>SVC AUTOMATED WX BCST SYSTEM U/S</u>	<u>SVC AUTOMATED WX BCST SYSTEM PRECIPITATION UNREL</u>	<u>N/A</u>
-	-	-	-	<u>SVC AUTOMATED WX BCST SYSTEM ALTIMETER SETTING NOT AVBL</u>	<u>N/A</u>
-	-	-	-	<u>SVC AUTOMATED WX BCST SYSTEM ALTIMETER SETTING UNREL</u>	<u>N/A</u>
-	-	-	-	<u>SVC AUTOMATED WX BCST SYSTEM CEILING UNREL</u>	<u>N/A</u>
-	-	-	-	<u>SVC AUTOMATED WX BCST SYSTEM WIND UNREL</u>	<u>N/A</u>
-	-	-	-	<u>SVC AUTOMATED WX BCST SYSTEM T UNREL</u>	<u>N/A</u>
<u>CPDLC</u>	<u>CONTROLLER PILOT DATA LINK COMMUNICATION SERVICE</u>	<u>YES</u>	<u>MSY COM CPDLC NOT AVLB</u>	<u>MSY COM SITA CPDLC NOT AVLB</u>	<u>MSY COM SITA CPDLC NOT AVLB</u>
<u>DME (ILS)</u>	<u>DISTANCE MEASURE EQUIPMENT</u>	<u>YES</u>	<u>NAV ILS RWY 18 DME U/S</u>	<u>NAV ILS RWY 05 DME NOT MNT</u>	<u>N/A *</u>
<u>DME (VOR)</u>	<u>DISTANCE MEASURE EQUIPMENT</u>	<u>YES</u>	<u>NAV DME U/S</u>	<u>NAV DME NOT MNT</u>	<u>N/A *</u>

<u>DMER</u>	<u>DISTANCE MEASURE EQUIPMENT REMAINING</u>	<u>YES</u>	<u>NAV DME U/S</u>	<u>NAV DME NOT MNT</u>	<u>N/A</u>
Facility Type	FSEP Name	NOTAM	NOTAM Examples Full outage (FL)	NOTAM Examples Reduced Equipment (RE)	NOTAM Examples Reduced Service (RS)
<u>ECOM</u>	<u>EN ROUTE COMMUNICATIONS SERVICE</u>	<u>YES</u>	<u>COM REMOTE COM A/G U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>FCOM</u>	<u>FLIGHT SERVICE STATIONS COMMUNICATIONS SERVICE</u>	<u>YES</u>	<u>COM REMOTE COM OUTLET 122.2 U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>FISB</u>	<u>FLIGHT INFORMATION SERVICE-BROADCAST</u>	<u>YES</u>	<u>ZNY AIRSPACE FLT INFO SERVICE BCST SERVICES NOT AVBL...</u>	<u>N/A</u>	<u>N/A</u>
-	-	-	<u>AIRSPACE TFC INFO SERVICE BCST MAY NOT BE AVBL WI AN AREA DEFINED AS</u>	<u>N/A</u>	<u>N/A</u>
-	-	-	<u>100 NM RADIUS OF 360728N0864041W SFC-UNL...</u>	<u>N/A</u>	<u>N/A</u>
<u>FM</u>	<u>FAN MARKER</u>	<u>YES</u>	<u>NAV ILS RWY 30 FAN MKR U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>GS</u>	<u>GLIDE SLOPE</u>	<u>YES</u>	<u>NAV ILS RWY 07R GP U/S</u>	<u>NAV ILS RWY 05 CAT III NA</u>	<u>N/A *</u>
-	-	-	-	<u>NAV ILS RWY 05 CAT II/III NA</u>	-
-	-	-	-	<u>NAV ILS RWY 05 GP NOT MNT</u>	<u>N/A</u>
<u>IM</u>	<u>INNER MARKER</u>	<u>YES</u>	<u>NAV ILS RWY 11 IM U/S</u>	<u>NAV ILS RWY 05 IM NOT MNT</u>	<u>N/A</u>
<u>LLWAS</u>	<u>LOW LEVEL WIND SHEAR ALERT SYSTEM</u>	<u>YES</u>	<u>SVC MBST/WS DETECTION SYSTEM NOT AVBL</u>	<u>N/A</u>	<u>N/A</u>
<u>LOC</u>	<u>LOCALIZER</u>	<u>YES</u>	<u>NAV ILS RWY 06 LOC U/S</u>	<u>NAV ILS RWY 05 CAT II/III NA</u>	<u>N/A *</u>
-	-	-	-	<u>NAV ILS RWY 05 LOC NOT MNT</u>	<u>N/A</u>
-	-	-	-	<u>NAV ILS RWY 05 CAT II NA</u>	<u>N/A</u>
-	-	-	-	<u>NAV ILS RWY 05 CAT III NA</u>	<u>N/A</u>
<u>LOM</u>	<u>LOCATOR OUTER MARKER</u>	<u>YES</u>	<u>NAV ILS RWY 31 GALEY LOM U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>MALS</u>	<u>MEDIUM INTENSITY APPROACH LIGHTING SYSTEM</u>	<u>YES</u>	<u>RWY 34 ALS U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>MALSF</u>	<u>MEDIUM INTENSITY APPROACH LIGHT SYSTEM WITH SFL's</u>	<u>YES</u>	<u>RWY 34 ALS U/S</u>	<u>RWY 30R RTHL U/S RWY 11 SEQUENCED FLG LGT U/S</u>	<u>N/A</u>
<u>MALSR</u>	<u>MEDIUM INTENSITY APPROACH LIGHT SYSTEM WITH RAIL</u>	<u>YES</u>	<u>RWY 34 ALS U/S</u>	<u>RWY 26L RAIL LGT U/S RWY 11 SEQUENCED FLG LGT U/S</u>	<u>N/A</u>
<u>MSEC</u>	<u>MODES SECONDARY RADAR SERVICE</u>	<u>YES</u>	<u>SVC SSR U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>MDAT</u>	<u>MODES RADAR SERVICE</u>	<u>YES</u>	<u>SVC SSR U/S</u>	<u>N/A</u>	<u>N/A</u>

MM	MIDDLE MARKER	YES	NAV ILS RWY 23R MM U/S	NAV ILS RWY 23 MM NOT MNT	N/A
Facility Type	FSEP Name	NOTAM	NOTAM Examples Full outage (FL)	NOTAM Examples Reduced Equipment (RE)	NOTAM Examples Reduced Service (RS)
NDB	NON DIRECTIONAL BEACON	YES	NAV LRT NDB U/S	NAV LRT NDB NOT MNT	N/A *
OM	OUTER MARKER	YES	NAV ILS RWY 03 OM U/S	NAV ILS RWY 03 OM NOT MNT	N/A
PAPI	PRECISION APPROACH PATH INDICATOR	YES	RWY 17R PAPI U/S	N/A	N/A *
PRM	PRECISION RUNWAY MONITOR	YES	SVC PRECISION RWY MNT U/S	N/A	N/A
RCAG	REMOTE COMMUNICATIONS AIR TO GROUND	YES	COM REMOTE COM A/G U/S	N/A	N/A
RCO	REMOTE COMMUNICATIONS OUTLET	YES	COM REMOTE COM OUTLET 122.2 U/S	N/A	N/A
-	-	-	COM VOR VOICE 122.1 U/S	-	-
REIL	RUNWAY END IDENTIFIER LIGHTS	YES	RWY 06 RWY END ID LGT U/S	N/A	N/A
RTR	REMOTE TRANSMITTER/RECEIVER	YES	COM REMOTE TRANS/REC 121.2 U/S	N/A	N/A
-	-	-	COM CL DELIVERY 121.7 U/S	N/A	N/A
-	-	-	COM COMMON TFC ADVISORY FREQ 122.8 U/S	N/A	N/A
-	-	-	COM REMOTE AP ADVISORY 123.65 U/S	N/A	N/A
RVR	RUNWAY VISUAL RANGE	YES	AD AP RVR ALL U/S	RWY 10L RVRM U/S	N/A
-	-	-	-	RWY 10LRVRT U/S	N/A
-	-	-	-	RWY 10R RVRU U/S	N/A
RWSL	RUNWAY STATUS LIGHT SYSTEM	YES	AD AP RWY STATUS LGT SYSTEM U/S	RWY 01R/19L RWY STATUS LGT SYSTEM U/S TWY K5, K6, T RWY ENTRANCE LGT FOR RWY 09L U/S RWY 28 TKOF HOLD LGT U/S	N/A
SSO	SELF SUSTAINING OUTLET	YES	COM MENTASTA REMOTE COM OUTLET 121.4 U/S	N/A	N/A
SSOI	SELF SUSTAINING OUTLET INTERMEDIATE	YES	COM LAKE CLARK PASS EAST REMOTE COM OUTLET 122.1 U/S	N/A	N/A
TACAN	TACTICAL AIR NAVIGATION	YES	NAV TACAN U/S	N/A	* NAV TACAN AZM U/S
TCOM	TERMINAL COMMUNICATION SERVICE	YES	COM REMOTE TRANS/REC 121.2 U/S COM CL DELIVERY 121.7 U/S	N/A	N/A

<u>Facility Type</u>	<u>FSEP Name</u>	<u>NOTAM</u>	<u>NOTAM Examples Full outage (FL)</u>	<u>NOTAM Examples Reduced Equipment (RE)</u>	<u>NOTAM Examples Reduced Service (RS)</u>
<u>TISB</u>	<u>TRAFFIC INFORMATION SERVICE-BROADCAST</u>	<u>YES</u>	<u>ISP ZNY AIRSPACE TFC INFO SERVICE BCST SERVICES NOT AVBL</u>	<u>N/A</u>	<u>N/A</u>
-	-	-	<u>AIRSPACE TFC INFO SERVICE BCST MAY NOT BE AVBL WI AN AREA DEFINED AS</u>	<u>N/A</u>	<u>N/A</u>
-	-	-	<u>100NM RADIUS OF 360728N0864041W SFC-UNL...</u>	<u>N/A</u>	<u>N/A</u>
<u>TRAD</u>	<u>TERMINAL RADAR SERVICE</u>	<u>YES</u>	<u>SVC TAR U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>TSEC</u>	<u>TERMINAL SECONDARY RADAR SERVICE</u>	<u>YES</u>	<u>SVC SSR U/S</u>	<u>N/A</u>	<u>N/A</u>
<u>TDWR</u>	<u>TERMINAL DOPPLER WEATHER RADAR</u>	<u>YES</u>	<u>SVC MBST/WS DETECTION SYSTEM NOT AVBL</u>	<u>N/A</u>	<u>N/A</u>
<u>VASI</u>	<u>VISUAL APPROACH SLOPE INDICATOR</u>	<u>YES</u>	<u>RWY 10L VASI U/S</u>	<u>RWY 28 VASI NOW 2 BOX</u>	<u>N/A *</u>
<u>VOR</u>	<u>VHF OMIDIRECTIONAL RANGE</u>	<u>YES</u>	<u>NAV VOR U/S</u>	<u>N/A</u>	<u>* NAV VOR NOT MNT</u>
<u>VOT</u>	<u>VHF OMIDIRECTIONAL RANGE TEST</u>	<u>YES</u>	<u>NAV VOT U/S</u>	<u>N/A</u>	<u>N/A</u>

NEW

Delete

BRIEFING GUIDE



**U.S. DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION**

**Initiated By: AJV-0
Vice President, Mission Support Services**

Table of Contents

Paragraph Number	Title	Page
1-4-6	DEFINITIONS	BG-3
2-1-3	PUBLICATION CRITERIA	BG-3
2-1-9	COMPUTER PRINTOUTS	BG-3
3-1-2	FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMER- GENCY AIR TRAFFIC RULES TFRs	BG-5
5-2-1	LIGHTING AIDS	BG-3
7-1-1	GENERAL	BG-7
7-1-5	TEMPORARY FLIGHT RESTRICTIONS	BG-7
7-2-1	FDC NOTAM EXPIRATION/CANCELLATION	BG-3
Appendix A. 7-1-5	TEMPORARY FLIGHT RESTRICTIONS	BG-7
Appendix D. D-2	FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMER- GENCY AIR TRAFFIC RULES TFR	BG-5
Appendix E. E-6	RETRIEVING FDC NOTAMS	BG-3

1. PARAGRAPH NUMBER AND TITLE:

1-4-6. DEFINITIONS

2-1-3. PUBLICATION CRITERIA

2-1-9. COMPUTER PRINTOUTS

5-2-1. LIGHTING AIDS

7-2-1. FDC NOTAM EXPIRATION/CANCELLATION

Appendix E. E-6. RETRIEVING FDC NOTAMS

2. BACKGROUND: 14 CFR section 139.339, states that certificate holders must provide for the collection and dissemination of airport condition information to air carriers using the Notice to Airmen (NOTAM) system. Previously, the NOTAM order only addressed civil public-use airports, including certificated part 139 airports, but it should be inclusive of all certified part 139 airports.

OLD**1-4-6. DEFINITIONS****Title through d**

e. Airport Operating Certificate. A certificate issued by the FAA, pursuant to 14 CFR Part 139, to airports serving or expected to serve scheduled air carrier operations in aircraft with a seating capacity of more than thirty passengers. These airports are maintained and operated in accordance with an Airport Certification Manual (ACM) prepared by airport management and approved by the FAA.

f through s

t. NOTAM D. The classification of NOTAMs containing information concerning the establishment, condition, or change in any aeronautical facility, en route navigational aids, services, procedures, hazards and civil public-use airports listed in the Chart Supplement. NOTAM Ds are numbered consecutively each month by the NS starting with 001 for each accountability, for example: DAY 01/001 would be the first NOTAM in the month of January for Dayton Accountable Location.

NEW**1-4-6. DEFINITIONS****No Change**

e. Airport Operating Certificate. A certificate issued by the FAA, pursuant to 14 CFR part 139, to airports serving or expected to serve scheduled **and unscheduled** air carrier operations in aircraft with a seating capacity **as determined under 14 CFR part 139.** These airports are maintained and operated in accordance with an Airport Certification Manual (ACM) prepared by airport management and approved by the FAA.

No Change

t. NOTAM D. The classification of NOTAMs containing information concerning the establishment, condition, or change in any aeronautical facility, en route navigational aids, services, procedures, hazards, **certificated part 139 airports,** and civil public-use airports listed in the Chart Supplement. NOTAM Ds are numbered consecutively each month by the NS starting with 001 for each accountability, for example: DAY 01/001 would be the first NOTAM in the month of January for Dayton Accountable Location.

OLD

2-1-3. PUBLICATION CRITERIA

Title through e

f. Public airports. Commissioning, decommissioning, openings, closings, and abandonment.

OLD

2-1-9. COMPUTER PRINTOUTS

Computer printouts listing all navigational aids and public use civil landing areas by flight plan area may be obtained from Aeronautical Information Services.

OLD

5-2-1. LIGHTING AIDS

Title through FIG 5-2-1

...RWY 27 RTHL U/S...

Originate NOTAMs on operational status of lighting aids for public use civil landing areas listed in the U.S. Chart Supplement. Each type of lighting requires separate NOTAMs. Technical Operations must be made aware of any runway lighting outages, as this is the office that maintains the equipment. When describing restrictions, use Runway Centerline (RCL) with visual navigational aids. NOTAMS regarding lighting aids are originated as follows:

OLD

7-2-1. FDC NOTAM EXPIRATION/CANCELLATION

a. The FDC NOTAM originator is responsible for canceling FDC NOTAM prior to end of validity; otherwise, the NOTAM cancellation is automatically processed.

b. When a new FDC NOTAM is issued to correct or in any way change a previously issued FDC NOTAM, a new NOTAM will be issued, and a separate cancellation NOTAM will be issued to cancel the old NOTAM.

NEW

2-1-3. PUBLICATION CRITERIA

No Change

f. Certificated part 139 and civil public-use airports. Commissioning, decommissioning, openings, closings, and abandonment.

NEW

2-1-9. COMPUTER PRINTOUTS

Computer printouts listing all navigational aids, certificated part 139 landing areas, and civil public-use landing areas by flight plan area may be obtained from Aeronautical Information Services.

NEW

5-2-1. LIGHTING AIDS

No Change

No Change

Originate NOTAMs on operational status of lighting aids for certificated part 139 and civil public-use landing areas listed in the U.S. Chart Supplement. Each type of lighting requires separate NOTAMs. Technical Operations must be made aware of any runway lighting outages, as this is the office that maintains the equipment. When describing restrictions, use Runway Centerline (RCL) with visual navigational aids. NOTAMS regarding lighting aids are originated as follows:

NEW

7-2-1. FDC NOTAM EXPIRATION/CANCELLATION

No Change

b. When a new FDC NOTAM is issued to correct or in any way change a previously issued FDC NOTAM, a new NOTAM will be issued and the previous NOTAM will be canceled.

OLD

E-6. RETRIEVING FDC NOTAMS

a. Upon issuance, all FDC NOTAMS are given all circuit distribution and are stored in the NS. FDC NOTAMS remain in the NS for the duration of their validity. FDC NOTAM cancellations remain in the NS for 72-hours after transmission.

b. FDC NOTAMS may be retrieved via request/reply. To minimize response delays, each FDC NOTAM and FDC NOTAM cancellation to be retrieved should be requested individually.

NEW

E-6. RETRIEVING FDC NOTAMS

a. Upon issuance, all FDC NOTAMS are given all circuit distribution and are stored in the NS. FDC NOTAMS remain in the NS for the duration of their validity.

b. FDC NOTAMS may be retrieved via request/reply. To minimize response delays, each FDC NOTAM should be requested individually.

1. PARAGRAPH NUMBER AND TITLE:

3-1-2. FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFR

Appendix D. D-2. FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFR

2. BACKGROUND: Past procedures for NOTAMS referencing Title 14 CFR, part 91, section 91.139, Emergency air traffic rules; section 91.141, Flight restrictions in the proximity of the Presidential and other parties; part 99, section 99.7, Special security instructions required, the United States NOTAM System (USNS) to request acknowledgment of receipt of the NOTAM from Flight Service air traffic facilities. Moving forward with USNS modernization, this requirement will no longer be necessary under the new system.

3. CHANGE:

OLD

3-1-2. FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFR_s

See Appendix D for further information.

a. The NS must send NOTAMS referencing Title 14 CFR, Part 91, Section 139, Emergency Air Traffic Rules; Section 141, Flight Restrictions in the Proximity of the Presidential and Other Parties; Part 99, Section 7, Security Instructions; and any revisions, modifications, or cancellations, directly to all flight service stations via NADIN (NMR) using the flight service group address of “KXXXXAFSS.”

NEW

3-1-2. FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFR

No Change

The NS must send NOTAMS referencing Title 14 CFR, part 91, section 91.139, Emergency air traffic rules; section 91.141, Flight restrictions in the proximity of the Presidential and other parties; part 99, section 99.7, Special security instructions; and any revisions, modifications, or cancellations, directly to all flight service stations via NADIN (NMR) using the flight service group address of “KXXXXAFSS.”

OLD

D-2. FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFR_s

b. Upon receipt of these messages, the watch supervisor at the designated flight service station must ensure that the NOTAM is received at each of the remaining facilities. The designated facility must send notification within 15 minutes by receipt message to “KDZZNAXX.” The receipt message must include:

- 1. R or RGR.**
- 2. The FDC number, including the letters FDC.**
- 3. The initials of the watch supervisor.**

NOTE-

Only the designated facility needs to acknowledge the NOTAM. For automation processing, the receipt message must adhere to the following format: R FDC Y/1234 XX

c. The USNOF must make a record of all receipt messages received.

d. If no receipt message is received by the USNOF within 90 minutes of issuance of the FDC Presidential, Special Security Instructions, or Emergency Air Traffic Rules NOTAM, the USNOF will follow-up with a phone call to the facility watch supervisor.

e. The watch supervisor of the designated flight service station must be responsible for:

1. Logging the Presidential, Special Security Instructions, or Emergency Air Traffic Rules FDC NOTAM in the facility log.

2. Notifying the specialists on duty that a Presidential, Special Security Instructions, or Emergency Air Traffic Rules FDC NOTAM has been issued.

3. Putting the Presidential, Special Security Instructions, or Emergency Air Traffic Rules FDC NOTAM in the facility status information area.

NEW

D-2. FDC PRESIDENTIAL, SPECIAL SECURITY INSTRUCTIONS, OR EMERGENCY AIR TRAFFIC RULES TFR

a. Upon receipt of these messages, the watch supervisor, **controller-in-charge (CIC), or designated lead specialist (DLS)** at the designated flight service station must ensure that the NOTAM is received at each of the remaining facilities.

Delete

Delete

Delete

Delete

Delete

Delete

b. The watch supervisor, **CIC, or DLS** of the designated flight service station must be responsible for:

No Change

No Change

3. Posting the Presidential, Special security instructions, or Emergency air traffic rules FDC NOTAM in the facility status information area.

4. As part of the watch checklist, the watch supervisor must check the FDC list that is issued by the USNOF to ensure that every Presidential, Special Security Instructions, or Emergency Air Traffic Rules FDC NOTAM has been received in the facility.

NOTE-

The purpose of this procedure is to ensure that:
1. All flight service specialists know about the Presidential, Special Security Instructions, or Emergency Air Traffic Rules TFRs so that pilots are briefed appropriately.
2. All affected air traffic facilities receive immediate notification when these TFRs are issued.

4. As part of the **FSS** watch checklist, the watch supervisor, **CIC, or DLS** must check to ensure that every Presidential, Special security instructions, or Emergency air traffic rules FDC NOTAM has been received in the facility.

NOTE-

*The purpose of this procedure is to ensure that all flight service specialists **are aware of** the Presidential, Special security instructions, or Emergency air traffic rules TFR so that pilots are briefed appropriately.*

1. PARAGRAPH NUMBER AND TITLE:

7-1-1. GENERAL

7-1-5. TEMPORARY FLIGHT RESTRICTIONS

Appendix A. 7-1-5. TEMPORARY FLIGHT RESTRICTIONS

2. BACKGROUND: Section 935 of the FAA Reauthorization Act of 2024 (Public Law 118-63) amended section 44812 of Title 49 United States Code (U.S.C). This amendment created a requirement for the FAA to temporarily restrict unmanned aircraft operations over large eligible public gatherings by issuing Temporary Flight Restrictions (TFRs). A TFR issued under this authorization would restrict unmanned aircraft operations over eligible large public gatherings when requested by credentialed law enforcement organizations.

3. CHANGE:

<u>OLD</u>	<u>NEW</u>
<p>7-1-1. GENERAL</p> <p style="padding-left: 40px;">Title through b</p> <p>1. <u>Disaster/hazard areas.</u></p> <p>2. <u>Aerial Demonstrations.</u></p> <p>3. Hijacking.</p> <p>4. <u>Flight restrictions in the proximity of the President and other parties.</u></p> <p>NOTE- <i>Presidential aircraft includes the aircraft and the entourage of the President, the Vice President, or other public figures designated by the White House.</i></p> <p>REFERENCE- <i>FAA Order JO 7210.3, Chapter 5, Section 1, Presidential Aircraft.</i></p> <p style="padding-left: 40px;">Add</p> <p style="padding-left: 40px;">Add</p>	<p>7-1-1. GENERAL</p> <p style="padding-left: 40px;">No Change</p> <p>1. <u>Unmanned aircraft over large public gatherings.</u></p> <p>2. <u>Disaster/hazard areas.</u></p> <p style="padding-left: 40px;">No Change</p> <p>4. <u>Aerial demonstrations.</u></p> <p style="padding-left: 40px;">Delete</p> <p style="padding-left: 40px;">Delete</p> <p>5. <u>Space flight operations.</u></p> <p>6. <u>Flight restrictions in the proximity of the President and other parties.</u></p>

Add

NOTE-
Presidential aircraft includes the aircraft and the entourage of the President, the Vice President, or other public figures designated by the White House.

Add

REFERENCE-
FAA Order JO 7210.3, Chapter 5, Section 1, Presidential Aircraft.

OLD

NEW

7-1-5. TEMPORARY FLIGHT RESTRICTIONS

7-1-5. TEMPORARY FLIGHT RESTRICTIONS

a. Through system interface, the NOTAM requestor must forward the NOTAM information directly to the USNOF for FDC NOTAM issuance and to the FSS nearest the incident site for coordination purposes. The NS disseminates FDC NOTAMs, and the FSS must act as “coordination facility” for preflight briefings for the ARTCC. The NOTAM must follow 4-2-1 b 1-2, including

a. Through system interface, the NOTAM requestor must forward the NOTAM information directly to the USNOF for FDC NOTAM issuance. The NS disseminates **the FDC NOTAM for coordination purposes, and to FSS and external providers of pilot informational briefings.** The NOTAM must follow **subparagraph 4-2-1b1-2**, including:

a1 through a5

No Change

6. The phrase “PURSUANT TO TITLE 14 CFR SECTION 9X.XXX...(the appropriate paragraph and sub-paragraph number) (plain language text, as needed). Include the phrase “PURSUANT TO 49 USC (section)...” as required for 14 CFR Sections 91.141 and 99.7 only.

6. The phrase **beginning with**, “PURSUANT TO...” **for the following:**

Add

(a) For unmanned aircraft over large public gatherings. “PURSUANT TO 49 U.S.C. SECTION 44812 AS AMENDED BY SECTION 935 OF THE FAA REAUTHORIZATION ACT OF 2024 FOR PROTECTION OF LARGE PUBLIC GATHERINGS.”

Add

(b) Include the phrase as required for 14 CFR sections 91.141 and 99.7: “PURSUANT TO 49 USC (section)...”.

Add

(c) For 14 CFR sections 91.137, 91.141, 91.143, 91.145, and 99.7: “PURSUANT TO TITLE 14 CFR SECTION 9X.XXX...(the appropriate paragraph and subparagraph number) (plain language text, as needed).

OLD

NEW

Appendix A. Examples

Appendix A. Examples

7-1-5. TEMPORARY FLIGHT RESTRICTIONS

7-1-5. TEMPORARY FLIGHT RESTRICTIONS

a. 14 CFR Section 91.137

a. 49 U.S.C. section 44812

EXAMPLES-

!FDC y/nnnn (ARTCC id) (state code)..AIRSPACE (city/location, state)..TEMPORARY FLIGHT RESTRICTIONS PURSUANT TO TITLE 14 CFR SECTION 91.137(A)(1) WIAN AREA DEFINED AS 10NM RADIUS OF 292000N0902000W (FIX/RADIAL/DISTANCE) SFC -FL180 (schedule, if needed) (reason) ONLY RELIEF ACFT OPS UNDER DIRECTION OF (agency in charge) ARE AUTH IN THE AIRSPACE (Agency name and telephone number) OR (frequency) IS IN CHARGE OF THE OPS. (Agency name and telephone number) OR (frequency) IS IN CHARGE OF ON SCENE EMERG RESPONSE ACT. (Coordination facility)...

!FDC y/nnnn ZLC MT..AIRSPACE MISSOULA, MT..TEMPORARY FLIGHT RESTRICTIONS PURSUANT TO TITLE 14 CFR SECTION 91.137(A)(2) WI AN AREA DEFINED AS 3NM RADIUS OF 465422N1135521W (MSO076008.6NM) SFC -10000FT FIRE FIGHTING ACFT OPS. MON-TANA DNRC MISSOULA DISPATCH TEL 406 -829 -7070 OR FREQ 133.20/WEST RIVERSIDE FIRE IS IN CHARGE OF THE OPS. SALT LAKE/ZLC/ARTCC TEL 801 -320 -2560 IS THE FAA CDN FAC...

!FDC y/nnnn (ARTCC id) (state code)..AIRSPACE (city/location, state)...TEMPORARY FLIGHT RESTRICTIONS PURSUANT TO TITLE 14 CFR SECTION 91.137(A)(3) WIAN AREA DEFINED AS 5NM RADIUS OF 464996N1140000W (F/R/D) SFC -(upper limit) DLY SR -SS (reason) (Agency and telephone number) OR (frequency) IS IN CHARGE OF THE OPS. (coordination facility)...

b. 14 CFR Section 91.141 and Section 99.7

EXAMPLE-

!FDC y/nnnn (ARTCC ID) (state code)..AIRSPACE (city/location, state)..TEMPORARY FLIGHT RESTRICTIONS PURSUANT TO 49 U.S.C. SECTION 44812 AS AMENDED BY SECTION 935 OF THE FAA REAUTHORIZATION ACT OF 2024 FOR PROTECTION OF LARGE PUBLIC GATHERINGS. UAS FLT OPS ARE PROHIBITED WIAN AREA DEFINED AS (XNM) RADIUS OF (Center-point L/L) (Fix/Radial/Distance) (altitude, ex, SFC-400FT) AGL. UAS OPS FOR OPERATIONAL, SAFETY, SECURITY, OR COMPLIANCE OVERSIGHT PURPOSES MUST APPLY FOR AUTH VIA EMAIL AT (SERVICE CENTER). (ATC Facility Name/ATC Facility ID/ATC Facility Type) TEL (XXX-XXX-XXXX) IS THE FAA CDN FAC. (schedule, if needed) (YYMMDDHHMM)-(YYM-MDDHHMM)

Delete

Delete

b. 14 CFR section 91.137

EXAMPLE-

!FDC y/nnnn ZHU TX..AIRSPACE CORPUS CHRISTI, TX..TEMPORARY FLIGHT RESTRICTIONS APRIL 4 – 5, 20YY LOCAL. PURSUANT TO 49 USC 40103(B) (3)...(remainder of the clause). PURSUANT TO TITLE 14 CFR SECTION 99.7 (plain language text) WIAN AREA DEFINED AS 273437N0970631W (NGP117011.9) TO...(remainder of the description) TO POINT OF ORIGIN 2500FT MSL – 17999FT MSL EFFECTIVE YY04041800 UTC (1300 LOCAL 4/4/YY) UNTIL YY04051000 UTC (0500 LOCAL 4/5/YY). WIAN AREA DEFINED AS 15NM EITHER SIDE OF A LINE FM 274022N0971244W (NGP094004.5) TO...(remainder of the description) 1500FT – 3500FT EFFECTIVE YY04041800 UTC (1300 LOCAL 4/4/YY) UNTIL YY04051000 UTC (0500 LOCAL 4/5/YY). WIA 4.3NM RADIUS OF 274134N0971725W (NGP025000.4) SFC – 3000FT EFFECTIVE YY04041800 UTC (1300 LOCAL 4/4/YY) UNTIL YY04051000 UTC (0500 LOCAL 4/5/YY). HOUSTON CENTER TEL 281 – 230 – 5560 IS THE FAA CDN FAC. EXC AS SPECIFIED BELOW AND/OR UNLESS AUTH BY ATC: 1. ALL ACFT MUST BE ON AN ACTIVE IFR OR FILED VFR FLT PLAN WITH A DISCRETE CODE ASSIGNED BY AN ATC FAC. 2. ACFT MUST BE SQUAWKING THE DISCRETE CODE AT ALL TIMES WHILE IN THE TFR. 3. ALL ACFT ENTERING OR EXITING THE TFR MUST REMAIN IN TWO – WAY RADIO COMMUNICATIONS WITH ATC.....

EXAMPLE-

!FDC y/nnnn (ARTCC ID) (state code)..AIRSPACE (city/location, state)..TEMPORARY FLIGHT RESTRICTIONS PURSUANT TO TITLE 14 CFR SECTION 91.137(A)(1) WIAN AREA DEFINED AS 10NM RADIUS OF (Centerpoint L/L) (Fix/Radial/Distance) SFC – FL180 (schedule, if needed) (reason) ONLY RELIEF ACFT OPS UNDER DIRECTION OF (agency in charge) ARE AUTH IN THE AIRSPACE (Agency name and telephone number) OR (frequency) IS IN CHARGE OF THE OPS. (Agency name and telephone number) OR (frequency) IS IN CHARGE OF ON SCENE EMERG RESPONSE ACT. (ATC Facility Name/ATC Facility ID/ATC Facility Type) TEL (XXX–XXX–XXXX) IS THE FAA CDN FAC. (schedule, if needed) (YYM–MDDHHMM)–(YYMMDDHHMM)

!FDC y/nnnn ZLC MT..AIRSPACE MISSOULA, MT..TEMPORARY FLIGHT RESTRICTIONS PURSUANT TO TITLE 14 CFR SECTION 91.137(A)(2) WIAN AREA DEFINED AS 3NM RADIUS OF 465422N1135521W (MSO076008.6) SFC – 10000FT FIRE FIGHTING ACFT OPS. MONTANA DNRC MISSOULA DISPATCH TEL 406 – 829 – 7070 OR FREQ 133.20/WEST RIVERSIDE FIRE IS IN CHARGE OF THE OPS. SALT LAKE/ZLC/ARTCC TEL 801 – 320 – 2560 IS THE FAA CDN FAC....

!FDC y/nnnn (ARTCC id) (state code)..AIRSPACE (city/location, state)...TEMPORARY FLIGHT RESTRICTIONS PURSUANT TO TITLE 14 CFR SECTION 91.137(A)(3) WIAN AREA DEFINED AS 5NM RADIUS OF 464996N1140000W (Fix/Radial/Distance) SFC – (upper limit) DLY SR – SS (reason) (Agency and telephone number) OR (frequency) IS IN CHARGE OF THE OPS. (coordination facility)....

Add

c. 14 CFR section 91.141 and section 99.7

Add

EXAMPLE-
/FDC y/nnnn ZHU TX..AIRSPACE CORPUS
CHRISTI, TX..TEMPORARY FLIGHT
RESTRICTIONS APRIL 4 –5, 20YY LOCAL.
PURSUANT TO 49 USC 40103(B) (3)...(remainder
of the clause). PURSUANT TO TITLE 14 CFR
SECTION 99.7 (plain language text) WIAN AREA
DEFINED AS 273437N0970631W (NGP117011.9)
TO...(remainder of the description) TO POINT OF
ORIGIN 2500FT–17999FT EFFECTIVE
YY04041800 (1300 LOCAL 4/4/YY) UNTIL
YY04051000 (0500 LOCAL 4/5/YY). WIAN AREA
DEFINED AS 15NM EITHER SIDE OF A LINE
FM 274022N0971244W (NGP094004.5)
TO...(remainder of the description)
1500FT –3500FT EFFECTIVE YY04041800 (1300
LOCAL 4/4/YY) UNTIL YY04051000 (0500 LOCAL
4/5/YY). WIA 4.3NM RADIUS OF
274134N0971725W (NGP025000.4) SFC –3000FT
EFFECTIVE YY04041800 (1300 LOCAL 4/4/YY)
UNTIL YY04051000 (0500 LOCAL 4/5/YY).
HOUSTON/ZHU/ARTCC TEL 281 –230 –5560 IS
THE FAA CDN FAC. EXC AS SPECIFIED BELOW
AND/OR UNLESS AUTH BY ATC: 1. ALL ACFT
MUST BE ON AN ACTIVE IFR OR FILED VFR
FLT PLAN WITH A DISCRETE CODE ASSIGNED
BY AN ATC FAC. 2. ACFT MUST BE SQUAWKING
THE DISCRETE CODE AT ALL TIMES WHILE
IN THE TFR. 3. ALL ACFT ENTERING OR
EXITING THE TFR MUST REMAIN IN
TWO –WAY RADIO COMMUNICATIONS WITH
ATC...
