



Federal Aviation Administration

September 25, 2015

Exemption No. 12997 Regulatory Docket No. FAA-2015-2743

Mr. Tom Raffelt Owner-Photographer New England Studio LLC 25 West Street Keene, NH 03434

Dear Mr. Raffelt:

This letter is to inform you that we have granted your request for exemption. It transmits our decision, explains its basis, and gives you the conditions and limitations of the exemption, including the date it ends.

By letter dated June 19, 2015, you petitioned the Federal Aviation Administration (FAA) on behalf of New England Studio LLC (hereinafter petitioner or operator) for an exemption. The petitioner requested to operate an unmanned aircraft system (UAS) to conduct aerial photography and video primarily of real estate and events.

See Appendix A for the petition submitted to the FAA describing the proposed operations and the regulations that the petitioner seeks an exemption.

The FAA has determined that good cause exists for not publishing a summary of the petition in the Federal Register because the requested exemption would not set a precedent, and any delay in acting on this petition would be detrimental to the petitioner.

#### **Airworthiness Certification**

The UAS proposed by the petitioner is a DJI Phantom 3 Professional.

The petitioner requested relief from 14 CFR part 21, Certification procedures for products and parts, Subpart H—Airworthiness Certificates. In accordance with the statutory criteria provided in Section 333 of Public Law 112–95 in reference to 49 U.S.C. § 44704, and in

consideration of the size, weight, speed, and limited operating area associated with the aircraft and its operation, the Secretary of Transportation has determined that this aircraft meets the conditions of Section 333. Therefore, the FAA finds that the requested relief from 14 CFR part 21, *Certification procedures for products and parts, Subpart H—Airworthiness Certificates*, and any associated noise certification and testing requirements of part 36, is not necessary.

#### The Basis for Our Decision

You have requested to use a UAS for aerial data collection<sup>1</sup>. The FAA has issued grants of exemption in circumstances similar in all material respects to those presented in your petition. In Grants of Exemption Nos. 11062 to Astraeus Aerial (*see* Docket No. FAA–2014–0352), 11109 to Clayco, Inc. (*see* Docket No. FAA–2014–0507), 11112 to VDOS Global, LLC (*see* Docket No. FAA–2014–0382), and 11213 to Aeryon Labs, Inc. (*see* Docket No. FAA–2014–0642), the FAA found that the enhanced safety achieved using an unmanned aircraft (UA) with the specifications described by the petitioner and carrying no passengers or crew, rather than a manned aircraft of significantly greater proportions, carrying crew in addition to flammable fuel, gives the FAA good cause to find that the UAS operation enabled by this exemption is in the public interest.

Having reviewed your reasons for requesting an exemption, I find that—

- They are similar in all material respects to relief previously requested in Grant of Exemption Nos. 11062, 11109, 11112, and 11213;
- The reasons stated by the FAA for granting Exemption Nos. 11062, 11109, 11112, and 11213 also apply to the situation you present; and
- A grant of exemption is in the public interest.

#### **Our Decision**

In consideration of the foregoing, I find that a grant of exemption is in the public interest. Therefore, pursuant to the authority contained in 49 U.S.C. 106(f), 40113, and 44701, delegated to me by the Administrator, New England Studio LLC is granted an exemption from 14 CFR §§ 61.23(a) and (c), 61.101(e)(4) and (5), 61.113(a), 61.315(a), 91.7(a), 91.119(c), 91.121, 91.151(a)(1), 91.405(a), 91.407(a)(1), 91.409(a)(1) and (2), and 91.417(a) and (b), to the extent necessary to allow the petitioner to operate a UAS to perform aerial data collection. This exemption is subject to the conditions and limitations listed below.

<sup>&</sup>lt;sup>1</sup> Aerial data collection includes any remote sensing and measuring by an instrument(s) aboard the UA. Examples include imagery (photography, video, infrared, etc.), electronic measurement (precision surveying, RF analysis, etc.), chemical measurement (particulate measurement, etc.), or any other gathering of data by instruments aboard the UA.

## **Conditions and Limitations**

In this grant of exemption, New England Studio LLC is hereafter referred to as the operator.

Failure to comply with any of the conditions and limitations of this grant of exemption will be grounds for the immediate suspension or rescission of this exemption.

- 1. Operations authorized by this grant of exemption are limited to the DJI Phantom 3 Professional when weighing less than 55 pounds including payload. Proposed operations of any other aircraft will require a new petition or a petition to amend this exemption.
- 2. Operations for the purpose of closed-set motion picture and television filming are not permitted.
- 3. The UA may not be operated at a speed exceeding 87 knots (100 miles per hour). The exemption holder may use either groundspeed or calibrated airspeed to determine compliance with the 87 knot speed restriction. In no case will the UA be operated at airspeeds greater than the maximum UA operating airspeed recommended by the aircraft manufacturer.
- 4. The UA must be operated at an altitude of no more than 400 feet above ground level (AGL). Altitude must be reported in feet AGL.
- 5. The UA must be operated within visual line of sight (VLOS) of the PIC at all times. This requires the PIC to be able to use human vision unaided by any device other than corrective lenses, as specified on the PIC's FAA-issued airman medical certificate or U.S. driver's license.
- 6. All operations must utilize a visual observer (VO). The UA must be operated within the visual line of sight (VLOS) of the PIC and VO at all times. The VO may be used to satisfy the VLOS requirement as long as the PIC always maintains VLOS capability. The VO and PIC must be able to communicate verbally at all times; electronic messaging or texting is not permitted during flight operations. The PIC must be designated before the flight and cannot transfer his or her designation for the duration of the flight. The PIC must ensure that the VO can perform the duties required of the VO.
- 7. This exemption and all documents needed to operate the UAS and conduct its operations in accordance with the conditions and limitations stated in this grant of exemption, are hereinafter referred to as the operating documents. The operating documents must be accessible during UAS operations and made available to the Administrator upon request. If a discrepancy exists between the conditions and limitations in this exemption and the procedures outlined in the operating documents,

the conditions and limitations herein take precedence and must be followed. Otherwise, the operator must follow the procedures as outlined in its operating documents. The operator may update or revise its operating documents. It is the operator's responsibility to track such revisions and present updated and revised documents to the Administrator or any law enforcement official upon request. The operator must also present updated and revised documents if it petitions for extension or amendment to this grant of exemption. If the operator determines that any update or revision would affect the basis upon which the FAA granted this exemption, then the operator must petition for an amendment to its grant of exemption. The FAA's UAS Integration Office (AFS–80) may be contacted if questions arise regarding updates or revisions to the operating documents.

- 8. Any UAS that has undergone maintenance or alterations that affect the UAS operation or flight characteristics, e.g., replacement of a flight critical component, must undergo a functional test flight prior to conducting further operations under this exemption. Functional test flights may only be conducted by a PIC with a VO and must remain at least 500 feet from other people. The functional test flight must be conducted in such a manner so as to not pose an undue hazard to persons and property.
- 9. The operator is responsible for maintaining and inspecting the UAS to ensure that it is in a condition for safe operation.
- 10. Prior to each flight, the PIC must conduct a pre-flight inspection and determine the UAS is in a condition for safe flight. The pre-flight inspection must account for all potential discrepancies, e.g., inoperable components, items, or equipment. If the inspection reveals a condition that affects the safe operation of the UAS, the aircraft is prohibited from operating until the necessary maintenance has been performed and the UAS is found to be in a condition for safe flight.
- 11. The operator must follow the UAS manufacturer's maintenance, overhaul, replacement, inspection, and life limit requirements for the aircraft and aircraft components.
- 12. Each UAS operated under this exemption must comply with all manufacturer safety bulletins.
- 13. Under this grant of exemption, a PIC must hold either an airline transport, commercial, private, recreational, or sport pilot certificate. The PIC must also hold a current FAA airman medical certificate or a valid U.S. driver's license issued by a state, the District of Columbia, Puerto Rico, a territory, a possession, or the Federal government. The PIC must also meet the flight review requirements specified in 14 CFR § 61.56 in an aircraft in which the PIC is rated on his or her pilot certificate.

- 14. The operator may not permit any PIC to operate unless the PIC demonstrates the ability to safely operate the UAS in a manner consistent with how the UAS will be operated under this exemption, including evasive and emergency maneuvers and maintaining appropriate distances from persons, vessels, vehicles and structures. PIC qualification flight hours and currency must be logged in a manner consistent with 14 CFR § 61.51(b). Flights for the purposes of training the operator's PICs and VOs (training, proficiency, and experience-building) and determining the PIC's ability to safely operate the UAS in a manner consistent with how the UAS will be operated under this exemption are permitted under the terms of this exemption. However, training operations may only be conducted during dedicated training sessions. During training, proficiency, and experience-building flights, all persons not essential for flight operations are considered nonparticipants, and the PIC must operate the UA with appropriate distance from nonparticipants in accordance with 14 CFR § 91.119.
- 15. UAS operations may not be conducted during night, as defined in 14 CFR § 1.1. All operations must be conducted under visual meteorological conditions (VMC). Flights under special visual flight rules (SVFR) are not authorized.
- 16. The UA may not operate within 5 nautical miles of an airport reference point (ARP) as denoted in the current FAA Airport/Facility Directory (AFD) or for airports not denoted with an ARP, the center of the airport symbol as denoted on the current FAA-published aeronautical chart, unless a letter of agreement with that airport's management is obtained or otherwise permitted by a COA issued to the exemption holder. The letter of agreement with the airport management must be made available to the Administrator or any law enforcement official upon request.
- 17. The UA may not be operated less than 500 feet below or less than 2,000 feet horizontally from a cloud or when visibility is less than 3 statute miles from the PIC.
- 18. If the UAS loses communications or loses its GPS signal, the UA must return to a pre-determined location within the private or controlled-access property.
- 19. The PIC must abort the flight in the event of unpredicted obstacles or emergencies.
- 20. The PIC is prohibited from beginning a flight unless (considering wind and forecast weather conditions) there is enough available power for the UA to conduct the intended operation and to operate after that for at least 5 minutes or with the reserve power recommended by the manufacturer if greater.
- 21. Air Traffic Organization (ATO) Certificate of Waiver or Authorization (COA). All operations shall be conducted in accordance with an ATO-issued COA. The exemption holder may apply for a new or amended COA if it intends to conduct operations that cannot be conducted under the terms of the enclosed COA.

- 22. All aircraft operated in accordance with this exemption must be identified by serial number, registered in accordance with 14 CFR part 47, and have identification (N–Number) markings in accordance with 14 CFR part 45, Subpart C. Markings must be as large as practicable.
- 23. Documents used by the operator to ensure the safe operation and flight of the UAS and any documents required under 14 CFR §§ 91.9 and 91.203 must be available to the PIC at the Ground Control Station of the UAS any time the aircraft is operating. These documents must be made available to the Administrator or any law enforcement official upon request.
- 24. The UA must remain clear and give way to all manned aviation operations and activities at all times.
- 25. The UAS may not be operated by the PIC from any moving device or vehicle.
- 26. All Flight operations must be conducted at least 500 feet from all nonparticipating persons, vessels, vehicles, and structures unless:
  - a. Barriers or structures are present that sufficiently protect nonparticipating persons from the UA and/or debris in the event of an accident. The operator must ensure that nonparticipating persons remain under such protection. If a situation arises where nonparticipating persons leave such protection and are within 500 feet of the UA, flight operations must cease immediately in a manner ensuring the safety of nonparticipating persons; and
  - b. The owner/controller of any vessels, vehicles or structures has granted permission for operating closer to those objects and the PIC has made a safety assessment of the risk of operating closer to those objects and determined that it does not present an undue hazard.
  - The PIC, VO, operator trainees or essential persons are not considered nonparticipating persons under this exemption.
- 27. All operations shall be conducted over private or controlled-access property with permission from the property owner/controller or authorized representative. Permission from property owner/controller or authorized representative will be obtained for each flight to be conducted.
- 28. Any incident, accident, or flight operation that transgresses the lateral or vertical boundaries of the operational area as defined by the applicable COA must be reported to the FAA's UAS Integration Office (AFS-80) within 24 hours. Accidents must be reported to the National Transportation Safety Board (NTSB) per instructions contained on the NTSB Web site: <a href="www.ntsb.gov">www.ntsb.gov</a>.

If this exemption permits operations for the purpose of closed-set motion picture and television filming and production, the following additional conditions and limitations apply.

- 29. The operator must have a motion picture and television operations manual (MPTOM) as documented in this grant of exemption.
- 30. At least 3 days before aerial filming, the operator of the UAS affected by this exemption must submit a written Plan of Activities to the local Flight Standards District Office (FSDO) with jurisdiction over the area of proposed filming. The 3-day notification may be waived with the concurrence of the FSDO. The plan of activities must include at least the following:
  - a. Dates and times for all flights;
  - b. Name and phone number of the operator for the UAS aerial filming conducted under this grant of exemption;
  - c. Name and phone number of the person responsible for the on-scene operation of the UAS:
  - d. Make, model, and serial or N-Number of UAS to be used;
  - e. Name and certificate number of UAS PICs involved in the aerial filming;
  - f. A statement that the operator has obtained permission from property owners and/or local officials to conduct the filming production event; the list of those who gave permission must be made available to the inspector upon request;
  - g. Signature of exemption holder or representative; and
  - h. A description of the flight activity, including maps or diagrams of any area, city, town, county, and/or state over which filming will be conducted and the altitudes essential to accomplish the operation.
- 31. Flight operations may be conducted closer than 500 feet from participating persons consenting to be involved and necessary for the filming production, as specified in the exemption holder's MPTOM.

Unless otherwise specified in this grant of exemption, the UAS, the UAS PIC, and the UAS operations must comply with all applicable parts of 14 CFR including, but not limited to, parts 45, 47, 61, and 91.

This exemption terminates on September 30, 2017, unless sooner superseded or rescinded.

Sincerely,

/s/

John S. Duncan Director, Flight Standards Service

Enclosures

June 19, 2015

U.S. Dept. of Transportation, Docket Operations West Building Ground Floor, Room w12-140 1200 New Jersey Avenue, SE., Washington, DC 20590

New England Studio LLC
25 West Street
Keene NH 03434
(603)355-1010
tom@newenglandstudio.com

Re: Exemption Request under Section 333 of the FAA Reform Act and Part 11 of the Federal Aviation Regulations

Dear Sir or Madam:

Pursuant to Section 333 of the FAA Modernization and Reform Act of 2012 (the "Reform Act") and 14 C.F.R. Part 11, New England Studio seeks an exemption from Federal Aviation Regulations ("FARs") detailed below for the following described Unmanned Aerial System called in this application the ME System, which includes an Unmanned Aircraft (UA) and ground station-based equipment and crew:

## THE UNMANNED AIRCRAFT (UA):

- A lightweight (2.8 lb gross weight with all on-board equipment), battery operated 4-motor rotorcraft in the form of a quadcopter that takes off and lands vertically, manufactured by DJI, Phantom 3 Professional that includes all the following equipment in flight:
- An on-board flight computer with GPS navigation and location ability that receives signals for flight controls from a ground-based transmitter/controller;
- An on-board camera capable of capturing imagery in the form of full color, high definition still photos and video;
- An on-board telemetry system that delivers flight data from the on-board flight computer to the
  on-board radio transmitter including altitude AGL, horizontal and vertical speed, compass
  direction of flight and direction back to its launch site;
- A 2.4GHz on-board radio transmitter that transmits live video from the on-board camera plus all the flight data from the telemetry system described above;

#### THE GROUD STATION -BASED PART OF THE SYSTEM:

- A Pilot in Command (PIC) in operational control of a flight operation from beginning to end and who controls the UA while in the air;
- A 2.4GHz radio transmitter/controller operated by the PIC to control the UA while in flight;
- A radio receiver receiving live video and flight data from the on-board camera and computer projects it all together onto a screen for the PIC to view during flight;
- A Visual Observer (VO) is a person who provides a second pair of eyes to visually track the UA while in flight.

The requested exemption would support an application for a commercial Certificate of Authorization to use the above described ME System to support aerial photography and video primarily of real estate property, wedding and wedding engagement session, high school senior sessions, youth sports.

The UA, powered by batteries, is smaller, lighter and more maneuverable than larger aircraft running on combustible fuel, it operates at lower altitudes with no people on board and will thereby reduce current risk levels and thereby enhance safety and diminish the likelihood of death or serious bodily injury. With a small payload and maximum flight time of only 22 minutes, this is offers little or no risk to national security.

Low level oblique photos and video from several angles are far more effective than ground-based imagery for displaying the characteristics of large, complex properties with several buildings and large trees. The alternative could be to charter a full-sized helicopter for this purpose, which has proven more costly than many potential clients are able to afford. The benefits of reduced cost and improved quality of presentation from the UA will be valuable to and benefit many buyers and sellers of real estate property.

The ME System will be operated in the field with both a PIC and a VO in accordance with FAA Policy N 8900.227 Section 14 "Operational Requirements for UAS" and with the following Restrictions:

- a) No flight will be made with a UA Gross weight exceeding 2.8 pounds;
- b) All operations must occur in FAA Class G airspace at no more than 400 ft AGL, at an airspeed of no more than 50 knots and no further than 3/4 NM from the PIC;
- c) All operations must utilize a visual observer (VO). The VO and PIC must be able to communicate by voice at all times during a flight operation;
- d) Operations will be restricted to flights over property with the permission of the property owner;
- e) The PIC must have accumulated and logged, a minimum of 100 flight cycles and 25 hours of total time as a UA rotorcraft pilot and at least ten hours logged as a UA pilot with a similar UA type;
- f) All required permits will be obtained from state and local government prior to operation;
- g) The ME System will not be operated over densely populated areas;
- h) The ME System will not be operated at air shows;
- i) The ME System will not be operated over any open-air assembly of people;
- j) The ME System will not be operated over heavily trafficked roads;
- k) The ME System will not be operated within 5 NM of an airport or heliport;
- 1) Operations will be restricted to day only and weather conditions equivalent to VFR;
- m) The PIC will brief the VO and property owner about the operation and risk before the first flight at each new location:
- n) No flight may be made without a Pre-Flight Inspection by the PIC before each operation to ascertain that the UA is in a condition safe for flight (see Appendix A).

The PIC and VO will meet the requirements outlined in FAA Policy N 8900.227 Section 16 personnel Qualifications. Additionally, the PIC and VO will perform maintenance on the system and will complete a course of maintenance instruction as part of their initial training.

We submit that the combination of the UA's light weight, flight performance and ability, fully qualified flight crew and strict operation under the guidelines established in 8900.227, and under all of the Restrictions (a) through (n) listed above, the FAA can have full confidence that the operation will have an equivalent or greater level of safety than manned aircraft performing the same mission.

The name and contact information of the applicant are:

New England Studio Attn: Tom Raffelt (603)355-1010 (603)499-1136 tom@newenglandstudio.com

The regulations from which the exemption is requested are listed below. Beside each regulation number is the page of the attached Addendum upon which each may be found together with our proposed equivalent level of safety for each regulation:

- 14 CFR Part 21	Addendum Page 1
- 14 CFR 91.203	Addendum Page 1
- 14 CFR 45.23, 45.29	Addendum Page 2
- 14 CFR 91.9	Addendum Page 2
- 14 CFR 61.113, 61.133	Addendum Page 2
- 14 CFR 91.109, 91.119, 91.121	Addendum Page 3
- 14 CFR 91.151	Addendum Page 3
- 14 CFR Subpart E (91.401 - 91.417)Addendum Page 3	
- FAA Policy 8900.227 Paragraph 16(c)(4) and Paragraph 16(e)(1) Addendum 1 Page 4	

We are prepared to modify or amend any part of this request to satisfy the need for an equivalent level of safety. Please contact us at any time if you require additional information or clarification. We look forward to working with your office.

Sincerely,

Tom Raffelt

Owner-Photographer

New England Studio LLC

Addendum containing Exemption Requests and Equivalent Level of Safety

Appendix A - Flight Manual

Appendix B – Owner's Manual for UA

# ADDENDUM EXEMPTION REQUESTS AND EQUIVALENT LEVEL OF SAFETY

Moonlight Engineering, requests an exemption from the following regulations as well as any additional regulations that may technically apply to the operation of the ME System:

## 14 CFR Part 21, Subpart H: Airworthiness Certificates

This part establishes the procedures for the issuance of an airworthiness certificate. While the FAA continues to work to develop airworthiness standards for Unmanned Aerial Systems, we request an experimental certificate be issued for the ME System under either or both of the following provisions: 21.191 Experimental certificates.

Experimental certificates are issued for the following purposes:

- (a) Research and development. Testing new aircraft design concepts, new aircraft equipment, new aircraft installations, new aircraft operating techniques, or new uses for aircraft.
- **(b)** Showing compliance with regulations. Conducting flight tests and other operations to show compliance with the airworthiness regulations including flights to show compliance for issuance of type and supplemental type certificates, flights to substantiate major design changes, and flights to show compliance with the function and reliability requirements of the regulations.

Since the experimental certificate can be used for commercial purposes such as market surveys, sales demonstrations, and customer crew training, we would expect that an experimental certificate would permit our commercial purpose as well.

The aircraft will not carry persons or property, will not carry fuel, and will only fly under strict operational requirements. Combined with the UA's light weight, being constructed primarily of carbon fiber and plastic, we propose that the UA will be at least as safe, if not safer, than a conventionally certificated aircraft performing the same mission.

If an experimental airworthiness certificate is not appropriate for this application, then we request an exemption of 14 CFR Part 21, Subpart H, and the requirement for an airworthiness certificate in general, citing the equivalent level of safety outlined in the previous paragraph.

## 14 CFR 91.203(a) & (b) Civil aircraft: Certifications required.

The regulation provides that an airworthiness certificate, with the registration number assigned to the aircraft and a registration certificate must be aboard the aircraft. Additionally, subparagraph (b) provides that the airworthiness certificate be "displayed at the cabin or cockpit entrance so that it is legible to passengers or crew."

At a maximum gross weight of 2.8 pounds, the UA is too small to carry documentation, does not have an entrance, and is not capable of carrying passengers or crew. To obtain an equivalent level of safety and meet the intent of 91.203, we propose that documents deemed appropriate for this aircraft by the FAA will be co-located with the crew at the ground control station and available for inspection upon request. In order to identify the aircraft, we propose that the information found on airworthiness and registration certificates be permanently affixed to the aircraft via placard containing the following information plus the word "EXPERIMENTAL" to satisfy the requirement of 14 CFR 45.23, which follows immediately after the proposed placard description below:

Manufacturer: DJI Innovations, Inc.

Address: 14th Floor, West Wing, Skyworth Semiconductor Design Building, No.18 Gaoxin South 4th Ave, Nanshan District, Shenzhen, China, 518057.

Purchased locally from B&H Photo & Video, 420 Ninth Ave, New York, NY 10001

If found please contact: Tom Raffelt (603)355-1010

## 14 CFR 45.23 Display of marks; general and 45.29 Size of marks.

These regulations provide that each aircraft must display "N" and the aircraft's registration number in letters at least 3 inches high. Additionally, the aircraft must display the word "EXPERIMENTAL" in letters at least 2 inches high near the entrance to the cabin, cockpit, or pilot station. The UA does not have an entrance in which the word "EXPERIMENTAL" can be placed, and may not have a registration number assigned to it by the FAA.

We propose to achieve an equivalent level of safety by including the word "EXPERIMENTAL" in the placard on the top of the aircraft, as shown above, where the PIC, VO and others in the vicinity of the aircraft while it is preparing for launch will be able to see the designation. Additionally, we feel that the permanent placard discussed in the previous paragraph will provide the aircraft's registration information at the ground station. Finally, we will display at the ground station a high contrast flag or banner that contains the words "Unmanned Aircraft Ground Station" in letters 3 inches high or greater. Since the aircraft will operate within 3/4 NM of the ground station, the banner should be visible to anyone that observes the aircraft and chooses to investigate its point of origin.

## 14 CFR 91.9 Civil aircraft flight manual, marking, and placard requirements.

This regulation provides that no person may operate an aircraft unless a current, approved flight manual is in the aircraft. We assume that the intent of this requirement is to ensure that flight manual information is available to the aircraft while operating the aircraft. We request an exemption to this requirement since the aircraft is not only too small to carry documentation, the documentation would not be available to the crew during flight operations.

To obtain an equivalent level of safety and meet the intent of 91.9, we propose that a current, approved UA Flight Manual (Appendix A) must be available to the crew at the ground station anytime the aircraft is in, or preparing for, flight.

# 14 CFR 61.113 Private pilot privileges and limitations: Pilot in Command and 61.133 Commercial pilot privileges and limitations.

The regulation provides that no person that holds a private pilot certificate may act as pilot in command of an aircraft for compensation or hire. Subparagraph (b) allows a private pilot to act as pilot in command of an aircraft in connection with any business or employment if: (1) The flight is only incidental to that business or employment; and (2) The aircraft does not carry passengers or property for compensation or hire.

Our proposed operations require that the PIC must either

- 1. Hold a Commercial Pilot Certificate issued by the FAA, and have logged 25 hours of flight experience in this type of UA, or
- 2. Meet the requirements of 8900.227 para 16(c)(2)(c) "Operations without a pilot certificate" in which the PIC is required to complete "FAA private pilot ground instruction" and pass "the FAA Private Pilot written examination." Since there are currently no means available for the pilot of a UAS to gain the experience in an equivalent category and class in order to apply for a commercial pilot's license, we propose to generate an equivalent level of safety by requiring our pilots to complete, at a minimum, FAA commercial pilot ground instruction and pass the FAA Commercial Pilot written examination in addition

to completing the private pilot requirements. Since the aircraft cannot carry passengers or property, we feel we meet the intent of 61.113 Subparagraph (b) even though the intent of this application is to conduct a business.

## 14 CFR 91.109 Flight Instruction; Simulated instrument flight and certain flight tests

The regulation states that "No person may operate a civil aircraft that is being used for flight instruction unless that aircraft has fully functioning dual controls."

The ME System ground-based control station consists of a small hand-held radio transmitter and while it does not offer a second set of "controls", both the student and instructor can, and will, operate the single set of controls simultaneously. With both student and instructor having "hands-on" the controls during flight, we feel that this technique meets the intent 91.109 and provides an equivalent level of safety.

## 14 CFR 91.119 Minimum safe altitudes: General.

The regulation states that over sparsely populated areas the aircraft cannot be operated closer than 500 feet to any person, vessel, vehicle, or structure. Since the aircraft will be operating at a maximum of 400 feet AGL, we cannot comply with this requirement.

In order to provide an equivalent level of safety we will only fly over private property with a size of at least two acres with the permission of the owner of the property flown over. The aircraft will not be operated over congested areas or over any open air assembly of persons. The property owner will be briefed on the expected route of flight and the associated risks to persons and property on the ground. The aircraft will be operated at a low altitude allowing, if a power unit fails, an emergency landing without undue hazard to persons or property on the surface. Therefore we maintain that due to the small size of the UA, the hazard to persons, vehicles and structures is minimal compared to manned aircraft, which should be considered in granting the exemption.

## 14 CFR 91.121 Altimeter settings.

The regulation requires that aircraft shall maintain cruising altitudes by reference to an altimeter setting available within 100 NM of the aircraft.

The UA will always fly below 400 feet AGL and will not need to maintain cruising altitudes in order to prevent conflict with other aircraft. An Above Ground Level altimeter measurement above the takeoff point is transmitted via radio from the UA on-board computer to the display screen held by the PIC, providing a constantly updated AGL readout.

## 14 CFR 91.151 Fuel requirements for flight in VFR conditions.

The regulation provides that no person may begin a flight in an airplane under day-VFR conditions unless there is enough fuel to fly to the first point of intended landing and to fly after that for at least 30 minutes. We feel the intention of this paragraph is to provide an energy reserve as a safety buffer for delays to landing. The UA is battery operated and the maximum duration of flight from a single battery charge is 18 minutes with a 20% reserve. Since the aircraft will never fly more than ¾ NM from the point of intended landing, a full battery charge at launch will ensure that we meet the reserve energy requirement of this paragraph. We request an exemption to the word "fuel" and ask for an equivalent interpretation with the word "energy".

## 14 CFR Subpart E (91.401 - 91.417) - Maintenance, Preventive Maintenance, Alterations

The regulation provides that the operator is primarily responsible for maintaining the aircraft in an airworthy condition, including compliance with part 39 and 43. Paragraphs 91.407 and 91.409 require that the aircraft be "approved for return to service by a person authorized under 43.7" after maintenance and inspection.

It is our intention that the PIC perform maintenance and inspection of the aircraft and "be authorized to approve the aircraft for return to service." As provided in the Pre-Flight Checklist in Appendix A, the PIC will ensure that the aircraft is in an airworthy condition prior to every flight and in addition conduct

detailed inspections after every two hours of flight. Maintenance performed by the PIC is limited to repairing small cracks, replacing a propeller, checking electrical connections and updating software and firmware for the on-board computer. All other maintenance will be performed by the manufacturer or their designated repair facility. The PIC will document work performed in accordance with 91.417. We feel that due to the size, construction, and simplicity of the aircraft, the PIC can ensure an equivalent level of safety.

## 8900.227 Paragraph 16(c)(4) PIC Medical. and Paragraph 16(e)(1) Observer Medical.

This policy provides that both the PIC and VO must have a valid FAA second-class medical certificate issued under part 67 in order to perform as a pilot or observer. The UA maximum gross weight is 6.5 pounds, it is constructed of carbon fiber and plastic and the PIC is not on board. Both the PIC and the VO are required to be in VLOS. Given the unlikely event that both the PIC and VO become medically incapacitated while the aircraft is in flight, the UA will return autonomously to the site of launching and land without crew intervention.

Therefore, requiring the PIC and VO to meet the same medical requirements as a commercial pilot carrying passengers in a large aircraft is an unnecessary burden.

We propose that the minimum medical requirements for the PIC and VO be vision corrected to 20/20 and a valid, state issued driver's license. The 20/20 vision requirement will ensure that the PIC and VO can see and avoid air traffic; a licensed driver is medically qualified to operate a much larger vehicle.

#### APPENDIX A - FLIGHT MANUAL

#### FLIGHT RESTRICTIONS

- a) No flight will be made with a UA Gross weight exceeding 55 pounds;
- b) All operations must occur in FAA Class G airspace at no more than 400' AGL, at an airspeed of no more than 50 knots and no further than 3/4 NM from the PIC;
- c) All operations must utilize a visual observer (VO). The VO and PIC must be able to communicate verbally at all times during a flight operation;
- d) Operations will be restricted to flights over property with the permission of the property owner;
- e) The PIC must have accumulated and logged, in a manner consistent with 14 CFR § 61.51 (b), a minimum of 100 flight cycles and 25 hours of total time as a UA rotorcraft pilot and at least ten hours logged as a UA pilot with a similar UA type;
- f) All required permits will be obtained from state and local government prior to operation;
- g) The ME System will not be operated over densely populated areas;
- h) The ME System will not be operated at air shows;
- i) The ME System will not be operated over any open-air assembly of people;
- j) The ME System will not be operated over heavily trafficked roads;
- k) The ME System will not be operated within 5 NM of an airport or heliport;
- l) Operations will be restricted to day only and weather conditions equivalent to VFR;
- m) The PIC will brief the VO and property owner about the operation and risk before the first flight at each new location;
- n) No flight may be made without a successful Pre-Flight Inspection by the PIC before each operation to ascertain that the UA is in a condition safe for flight.

## PREFLIGHT CHECKLIST

- 1. Remote controller, aircraft battery, and mobile device are fully charged.
- 2. Propellers are mounted correctly and firmly.
- 3. Micro-SD card has been inserted if necessary.
- 4. Gimbal is functioning as normal.
- 5. Motors can start and are functioning as normal.
- 6. DJI Pilot app connected to the aircraft.

#### TO REGAIN CONTROL AFTER LOST RADIO CONTACT

If radio contact is lost and not restored within 3 seconds, an automatic Return to Home feature is activated and will bring the UAV back to the PIC.