FAA HOLDOVER TIME GUIDELINES



WINTER 2024-2025 ORIGINAL ISSUE: AUGUST 6, 2024

The information contained in this document serves as the official FAA guidance, Holdover Times and Allowance Times for use during the 2024-2025 winter season.

Questions concerning FAA aircraft ground de/anti-icing requirements or Flight Standards policies should be addressed to timothy.mcclain@faa.gov or 703-999-6648.

Questions on the technical content of the holdover time tables or allowance time tables should be addressed to warren.underwood@faa.gov or 404-305-7267.

Questions regarding editorial content or web access issues should be addressed to sung.shin@faa.gov or 202-267-8086.

The Holdover Times Tables and related information can be found at the FAA's Aircraft Ground Deicing website.

To receive notifications on updates to the Holdover Times Tables and related information, subscribe to the Aircraft Ground Deicing website by clicking on this link.

This document is intended to be used in conjunction with the FAA Ground Deicing Program General Information Document, Winter 2024-2025, located on the FAA's Aircraft Ground Deicing website.

CHANGE CONTROL RECORDS

This page indicates any changes made to individual pages within the document. Changed pages have the appropriate revision date in the footer. Sidebars are shown to assist in identifying where significant changes have been made on these pages.

It is the responsibility of the end user to periodically check the following website for updates: https://www.faa.gov/other_visit/aviation_industry/airline_operators/airline_safety/deicing/.

REVISION	DATE	DESCRIPTION OF CHANGES	AFFECTED PAGES	AUTHOR

TABLE OF CONTENTS

Change Control Records	2
Table of Contents	3
How to Use This Document	5
Highlights and Changes for Winter 2024-2025	7
Active Frost Holdover Time (HOT) Guidelines Winter 2024-2025	
Table 1: Active Frost Holdover Times for SAE Type I, Type II, Type III, and Type IV Fluids	
HOT Guidelines for SAE Type I Fluids Winter 2024-2025	
Table 2: Holdover Times for SAE Type I Fluid on Critical Aircraft Surfaces Composed Predominantly of Aluminum	
Table 3: Holdover Times for SAE Type I Fluid on Critical Aircraft Surfaces Composed Predominantly of Composites	
HOT Guidelines for SAE Type II Fluids Winter 2024-2025	. 14
Table 4: Generic Holdover Times for SAE Type II Fluids	. 15
Table 5: Type II Holdover Times for ABAX ECOWING AD-2	
Table 6: Type II Holdover Times for Aviation Xi'an High-Tech Cleanwing II	
Table 7: Type II Holdover Times for Clariant Safewing MP II FLIGHT	
Table 9: Type II Holdover Times for Kilfrost ABC-K Plus	
Table 10: Type II Holdover Times for Kilfrost Ice Clear II	
Table 11: Type II Holdover Times for MKS DevO Chemicals COREICEPHOB Type II	
Table 12: Type II Holdover Times for Newave Aerochemical FCY-2	
Table 13: Type II Holdover Times for ROMCHIM ADD-PROTECT NG Type II	. 24
Table 14: Type II Holdover Times for ROMCHIM ADD-PROTECT Type II	
HOT Guidelines for SAE Type III Fluids Winter 2024-2025	
Table 15: Type III Holdover Times for AllClear AeroClear MAX Applied Unheated on Low Speed Aircraft	
Table 16: Type III Holdover Times for AllClear AeroClear MAX Applied Unheated on Middle Speed Aircraft	
Table 17: Type III Holdover Times for AllClear AeroClear MAX Applied Unheated on High Speed Aircraft	
HOT Guidelines for SAE Type IV Fluids Winter 2024-2025	
Table 18: Generic Holdover Times for SAE Type IV Fluids	
Table 20: Type IV Holdover Times for ALAB International PROFLIGHT EG4	
Table 21: Type IV Holdover Times for ALAB International PROFLIGHT PG4	. 34
Table 22: Type IV Holdover Times for AllClear ClearWing EG	
Table 23: Type IV Holdover Times for ASGlobal 4Flite EG	
Table 24: Type IV Holdover Times for ASGlobal 4Flite PG	
Table 25: Type IV Holdover Times for AVIAFLUID AVIAFLIBRA (AFFIGURE AVIAFLUID AVIAFLUI	
Table 26: Type IV Holdover Times for AVIAFLUID AVIAFlight PG	. 39
Table 28: Type IV Holdover Times for CHEMCO ChemR Nordik IV	. 4 0 ⊿1
Table 29: Type IV Holdover Times for Chongqing Joba Chemical Co., Ltd FW-IV	. 42
Table 30: Type IV Holdover Times for Clariant Safewing MP IV LAUNCH	
Table 31: Type IV Holdover Times for Clariant Safewing MP IV LAUNCH PLUS	
Table 32: Type IV Holdover Times for Cryotech Polar Guard® Advance	
Table 33: Type IV Holdover Times for Cryotech Polar Guard® Xtend	. 46
Table 34. Type IV Holdover Times for Dow Inc. UCAR Endurance ™ EG 106	
Table 36: Type IV Holdover Times for Inland Technologies ECO-SHIELD®	. 4 0
Table 37: Type IV Holdover Times for JSC RCP Nordix Defrost ECO 4	
Table 38: Type IV Holdover Times for JSC RCP Nordix Defrost NORTH 4	. 51
Table 39: Type IV Holdover Times for Kilfrost ABC-S Plus	. 52
Table 40: Type IV Holdover Times for MKS DevO Chemicals COREICEPHOB TYPE IV PG	
Table 41: Type IV Holdover Times for Newave Aerochemical FCY 9311	
Table 43: Type IV Holdover Times for Shaanxi Cleanway Cleansurface IV	
Allowance Times Tables for Winter 2024-2025	
Table 44: List of Fluids Validated for Use with Allowance Times	
Table 45: Allowance Times for SAE Type III Fluids	
Table 46: Allowance Times for SAE Type IV Ethylene Glycol (EG) Fluids	
Table 47: Allowance Times for SAE Type IV Propylene Glycol (PG) Fluids	
Supplemental Guidance for Winter 2024-2025	. 64
Table 48: Snowfall Intensities as a Function of Prevailing Visibility	

Table 49: Type I Fluids Tested for Anti-Icing Performance and Aerodynamic Acceptance	66
Table 50: Type II Fluids Tested for Anti-Icing Performance and Aerodynamic Acceptance	70
Table 51: Type III Fluids Tested for Anti-Icing Performance and Aerodynamic Acceptance	72
Table 52: Type IV Fluids Tested for Anti-Icing Performance and Aerodynamic Acceptance	73
Table 53: Viscosity Measurement Methods for Type II, III, and IV Fluids Tested for Anti-Icing Performance and A	Aerodynamic
Acceptance	78
Table 54: Guidelines for the Application of SAE Type I Fluid	79
Table 55: Guidelines for the Application of SAE Type II and IV Fluid	80
Table 56: Guidelines for the Application of Unheated SAE Type III Fluid	81
Appendix A: Adjusted Holdover Time (HOT) Guidelines	A- 1
Appendix B: Testing Laboratories	B-1
0: Type II Fluids Tested for Anti-Icing Performance and Aerodynamic Acceptance	

HOW TO USE THIS DOCUMENT

Complementary Documents

This document is designed to be used in conjunction with the FAA N 8900 series notice "Revised FAA-Approved Deicing Program Updates, Winter 2024-2025" and the FAA General Information Ground Deicing Program, Issue 2. These documents complement each other and should be used together for a thorough understanding of the subject matter.

Beginning in the winter of 2021-22, the FAA has published an annual database of degree-specific holdover times (DSHOTs) for snow and snow-related precipitation conditions (including snow, snow grains, and snow pellets). The DSHOT database contains an expanded set of snow precipitation HOTs for all undiluted Type II, III and IV anti-icing fluids listed in the FAA HOT Guidelines. This database can be found at the following website: https://www.faa.gov/other_visit/aviation_industry/airline_operators/airline_safety/deicing/.

Guidance and conditions on the use of DSHOT data can be found in the FAA General Information Ground Deicing Program document, Issue 2.

Applicability

A new version of this document is published for each winter operating season, typically in early August preceding the winter operating season. Updates to the winter's document may be published at any time after the Original Issue document is published. When a new document is published, either mid-season or each new season, the previous document becomes obsolete. It is the responsibility of the end user to periodically check for document updates on the following website:

https://www.faa.gov/other visit/aviation industry/airline operators/airline safety/deicing/.

Main Document Structure and Content

This document is divided into several sections.

- <u>Change Control Records</u>: Provides details of any changes made to the document in mid-season document updates.
- Table of Contents: Provides a list of sections, tables, and appendices in the document.
- How to Use This Document: Provides top-level guidance on how to use the document.
- Highlights and Changes for Winter 2024-2025: Describes key changes made to the document for the current winter operating season.
- Holdover Time Guidelines: Series of tables that provide estimated holdover times (in hh:mm). Fluids are divided by fluid type (Type I, II, III, and IV), aircraft construction materials (Type I only), fluid brand (Type II, III, IV), aircraft rotation speed (Type III only), and fluid application temperature (Type III only). Columns in the tables divide the information by precipitation type; rows in the tables divide the information by temperature and fluid dilution. Notes in the tables refer to additional information on the specific HOTs. Cautions that apply to all tables in a section are located on the flysheets before each section.
- Allowance Times Tables: Tables that provide allowance times (in minutes) for Type III and Type IV fluids.
 Rows in the tables divide the information by precipitation type; columns in the tables divide the information
 by temperature. Notes in the tables refer to additional information on the specific allowance times.
 Cautions that apply to all allowance times tables are located on the flysheet before the section. Use of
 these tables must be validated by first confirming that fluid being used is listed in the "List of Fluids
 Validated for Use with Allowance Times".
- <u>Supplementary Guidance</u>: Series of tables that provide supplementary information for using the holdover time guidelines and allowance times tables. Includes a table for estimating snowfall intensity from prevailing visibility, tables of fluid information (one table per fluid type), and tables of fluid application guidance (by fluid type).

Appendices

The appendices contain complementary content.

- <u>Appendix A</u>: Provides adjusted holdover time guidelines (holdover time guidelines and allowance times tables) for operations when flaps and slats are deployed prior to de/anti-icing.
- Appendix B: Provides information on laboratories involved in testing de/anti-icing fluids.
- <u>Appendix C</u>: Provides the latest de/anti-icing fluid manufacturer contact information at the time of publication.

HIGHLIGHTS AND CHANGES FOR WINTER 2024-2025

CHANGED FROM PREVIOUS YEAR

The principal changes from the previous year are briefly indicated herein.

How to Use this Document

 The allowance time tables section has been expanded to describe the purpose of the new list of fluids validated for use with allowance times table.

Holdover Time Tables

- Fluid specific HOT guidelines have been created for four new fluids: ALAB International PROFLIGHT PG4 (Type IV), Chongqing Joba Chemical Co., Ltd FW-IV (Type IV), MKS DevO Chemicals COREICEPHOB TYPE-IV PG (Type IV), and Shaanxi Cleanway Cleansurface IV (Type IV).
- Fluid specific HOT Guidelines have been adjusted for two existing fluids: MKS DevO Chemicals COREICEPHOB Type II (Type II) and ALAB International PROFLIGHT EG4.
- The HOT guidelines for Clariant Safewing MP II FLIGHT PLUS (Type II), JSC RCP Nordix Defrost PG 2
 (Type II), AllClear ClearWing ECO (Type IV), Clariant Max Flight AVIA (Type IV), Clariant Max Flight
 SNEG (Type IV), and Clariant Safewing EG IV NORTH (Type IV) have been removed.
- Increases have been made to the Type II generic holdover times in freezing drizzle and in light freezing rain at -3°C and above, as a result of the removed fluids.
- Increases have been made to the Type IV generic holdover times in snow and in freezing fog below -8 to -14°C as a result of removed fluids.
- Several decreases have been made to the Type IV generic holdover times in snow and in freezing fog as a result of the newly added fluids.
- A new "Snow mixed with Freezing Fog" column has been added to all Type I, II, III, and IV HOT tables with fluid specific values. The Generic "Snow mixed with Freezing Fog" table has been removed.
- A note was added in all Type I, II, III, and IV HOT tables indicating that the visibility table must be used in conditions of snow mixed with freezing fog in order to confirm the snowfall intensity.
- The Type I column in the Active Frost HOT table has been split into two to separate aluminum and composite HOTs.
- A caution relating to cold-soaked wing with the use of 50/50 fluids from the Type II/IV fluid application table was added to the Type II and IV fluid HOT table cautions.
- A caution relating to blowing snow that applies to all Type I, II, III, and IV HOT tables has been updated to include drifting snow.
- A caution was removed for all Type IV fluids indicating that the HOT tables are for use with aircraft conforming to the SAE AS5900 high speed aerodynamic test criterion.

Allowance Times Tables

- The table "List of Fluid Validated for Use with Allowance Times" was added indicating which Type III and IV fluids are validated for use with which allowance times.
- The condition Moderate Ice Pellets Mixed with Moderate Snow has been added to the Type IV allowance time tables.
- The condition Light Ice Pellets Mixed with Light Rain and Light Snow has been added to the Type IV allowance time tables.
- The condition Light Ice Pellets Mixed with Light Freezing Rain and Light Snow has been added to the Type IV allowance time tables.

- A new "Above 0°C" column was added to all allowance time tables and the tables were restructured accordingly. Notes limiting certain conditions to above 0°C have been removed
- The Light Ice Pellets and Moderate Ice Pellets allowance times for Type IV EG fluids have been expanded in temperature below -5 to -10°C.
- The precipitation type column and the METAR codes column have been merged into a single column.
- The small hail note was updated to provide clarity and the corresponding small hail METAR codes have been added to all conditions in the tables.
- The note regarding the 90 minute rule has been updated to add clarity and to include the new allowance time conditions.

Supplemental Guidance

• The list of fluids (Tables 49, 50, 51 and 52) has been updated to reflect the latest information available on all de/anti-icing fluids.

UNCHANGED FROM PREVIOUS YEAR

Supplemental Guidance

The fluid application tables are unchanged.

ACTIVE FROST HOLDOVER TIME (HOT) GUIDELINES WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

CAUTIONS

- The responsibility for the application of these data remains with the user.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.

TABLE 1: ACTIVE FROST HOLDOVER TIMES FOR SAE TYPE I, TYPE II, TYPE III, AND TYPE IV FLUIDS1

Transaction of the Control of the Co	•	
Outside Air Temperature ^{2,3,4}	Type I Aluminum	Type I Composite
-1 °C and above (30 °F and above)		
below -1 to -3 °C (below 30 to 27 °F)		
below -3 to -10 °C (below 27 to 14 °F)	0:45	0:35
below -10 to -14 °C (below 14 to 7 °F)		
below -14 to -21 °C (below 7 to -6 °F)		
below -21 to -25 °C (below -6 to -13 °F)		
below -25 °C to LOUT (below -13 °F to LOUT)		

Outside Air Temperature ^{3,4}	Concentration Fluid/Water By % Volume	Type II	Type III⁵	Type IV
	100/0	8:00	2:00	12:00
-1 °C and above (30 °F and above)	75/25	5:00	1:00	5:00
(oo i ana abovo)	50/50	2:00	0:30	3:00
	100/0	8:00	2:00	12:00
below -1 to -3 °C (below 30 to 27 °F)	75/25	5:00	1:00	5:00
(55,50,000,00,10,27,17)	50/50	1:30	0:30	3:00
below -3 to -10 °C	100/0	8:00	2:00	10:00
(below 27 to 14 °F)	75/25	4:00	1:00	5:00
below -10 to -14 °C	100/0	6:00	2:00	6:00
(below 14 to 7 °F)	75/25	1:00	1:00	1:00
below -14 to -21 °C (below 7 to -6 °F)	100/0	3:00	2:00	6:00
below -21 to -25 °C (below -6 to -13 °F)	100/0	2:00	2:00	4:00
below -25 °C (below -13 °F)	100/0	No Holdo	over Time Guideli	nes Exist

- 1 To use the HOTs in this table, ensure that the fluid and dilution being used is listed in the List of Qualified Fluids Tested for Anti-Icing Performance and Aerodynamic Acceptance table (Table 49 Table 52). Any restrictions on the use of the fluid have to be identified and applied.
- 2 Type I Fluid / Water Mixture must be selected so that the freezing point of the mixture is at least 10 °C (18 °F) below outside air temperature.
- 3 Ensure that the lowest operational use temperature (LOUT) is respected.
- 4 Changes in outside air temperature (OAT) over the course of longer frost events can be significant; the appropriate holdover time to use is the one provided for the coldest OAT that has occurred in the time between the de/anti-icing fluid application and takeoff.
- 5 To use the Type III fluid frost holdover times, the fluid brand being used must be known. AllClear AeroClear MAX must be applied unheated.

CAUTIONS

HOT GUIDELINES FOR SAE TYPE I FLUIDS WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

CAUTIONS

- The responsibility for the application of these data remains with the user.
- The time of protection will be shortened in heavy weather conditions. Heavy precipitation rates or high moisture content, high wind velocity jet blast, or blowing snow may reduce holdover time below the lowest time stated in the range.
 Holdover time may be reduced when aircraft skin temperature is lower than outside air temperature.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.

TABLE 2: HOLDOVER TIMES FOR SAE TYPE I FLUID ON CRITICAL AIRCRAFT SURFACES COMPOSED PREDOMINANTLY OF ALUMINUM

Outside Air Temperature ^{1,2}	Freezing Fog, Freezing Mist ³ , or Ice Crystals ⁴	Snow mixed with Freezing Fog ⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold- Soaked Wing ¹⁰	Other ¹¹
-3 °C and above (27 °F and above)	0:11 - 0:17	0:05 - 0:08	0:18 - 0:22	0:11 - 0:18	0:06 - 0:11	0:09 - 0:13	0:02 - 0:05	0:02 - 0:05	
below -3 to -6 °C (below 27 to 21 °F)	0:08 - 0:13	0:04 - 0:06	0:14 - 0:17	0:08 - 0:14	0:05 - 0:08	0:05 - 0:09	0:02 - 0:05		
below -6 to -10 °C (below 21 to 14 °F)	0:06 - 0:10	0:03 - 0:05	0:11 - 0:13	0:06 - 0:11	0:04 - 0:06	0:04 - 0:07	0:02 - 0:05	CAUTIOI No holdover guidelines e	time
below -10 °C (below 14 °F)	0:05 - 0:09	0:02 - 0:03	0:07 - 0:08	0:04 - 0:07	0:02 - 0:04				

NOTES

- 1 Type I fluid / water mixture must be selected so that the freezing point of the mixture is at least 10 °C (18 °F) below outside air temperature.
- 2 Ensure that the lowest operational use temperature (LOUT) is respected.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.

CAUTIONS

TABLE 3: HOLDOVER TIMES FOR SAE TYPE I FLUID ON CRITICAL AIRCRAFT SURFACES COMPOSED PREDOMINANTLY OF COMPOSITES

Outside Air Temperature ^{1,2}	Freezing Fog, Freezing Mist ³ , or Ice Crystals ⁴	Snow mixed with Freezing Fog ⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold- Soaked Wing ¹⁰	Other ¹¹
-3 °C and above (27 °F and above)	0:09 - 0:16	0:02 - 0:04	0:12 - 0:15	0:06 - 0:12	0:03 - 0:06	0:08 - 0:13	0:02 - 0:05	0:01 - 0:05	
below -3 to -6 °C (below 27 to 21 °F)	0:06 - 0:08	0:02 - 0:04	0:11 - 0:13	0:05 - 0:11	0:02 - 0:05	0:05 - 0:09	0:02 - 0:05		
below -6 to -10 °C (below 21 to 14 °F)	0:04 - 0:08	0:02 - 0:04	0:09 - 0:12	0:05 - 0:09	0:02 - 0:05	0:04 - 0:07	0:02 - 0:05	CAUTIOI No holdover guidelines e	time
below -10 °C (below 14 °F)	0:04 - 0:07	0:02 - 0:03	0:07 - 0:08	0:04 - 0:07	0:02 - 0:04				

NOTES

- 1 Type I fluid / water mixture must be selected so that the freezing point of the mixture is at least 10 °C (18 °F) below outside air temperature.
- 2 Ensure that the lowest operational use temperature (LOUT) is respected.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.

CAUTIONS

HOT GUIDELINES FOR SAE TYPE II FLUIDS WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

CAUTIONS

- The responsibility for the application of these data remains with the user.
- The time of protection will be shortened in heavy weather conditions. Heavy precipitation rates or high moisture content, high wind velocity jet blast, or blowing snow may reduce holdover time below the lowest time stated in the range.
 Holdover time may be reduced when aircraft skin temperature is lower than outside air temperature.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.
- Whenever frost or ice occurs on the lower surface of the wing in the area of the fuel tank, indicating a cold-soaked wing, the 50/50 dilutions of Type II or IV shall not be used for the anti-icing step because fluid freezing may occur.

TABLE 4: GENERIC HOLDOVER TIMES FOR SAE TYPE II FLUIDS1

Outside Air Temperature ²	Fluid Concentration Fluid/Water By % Volume	Freezing Fog, Freezing Mist ³ , or Ice Crystals ⁴	Snow mixed with Freezing Fog ⁵	Snow, Snow Grains or Snow Pellets ^{6,7,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold- Soaked Wing ¹⁰	Other ¹¹	
	100/0	0:55 - 1:50	0:20 - 0:40	0:30 - 0:55	0:35 - 1:05	0:25 - 0:35	0:07 - 0:45		
-3 °C and above (27 °F and above)	75/25	0:40 - 1:10	0:15 - 0:25	0:15 - 0:30	0:25 - 0:40	0:15 - 0:25	0:04 - 0:25		
(2	50/50	0:15 - 0:30	0:05 - 0:10	0:07 - 0:15	0:09 - 0:15	0:06 - 0:09			
below -3 to -8 °C	100/0	0:30 - 0:45	0:15 - 0:30	0:20 - 0:40	0:20 - 0:45	0:15 - 0:20			
(below 27 to 18 °F)	75/25	0:25 - 0:55	0:09 - 0:15	0:10 - 0:25	0:15 - 0:30	0:08 - 0:15			
below -8 to -14 °C	100/0	0:30 - 0:45	0:10 - 0:25	0:15 - 0:30	0:20 - 0:45 ¹²	0:15 - 0:20 ¹²	0.447		
(below 18 to 7 °F)	75/25	0:25 - 0:55	0:07 - 0:15	0:09 - 0:20	0:15 - 0:30 ¹²	0:08 - 0:15 ¹²	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:15 - 0:20	0:01 - 0:05	0:02 - 0:07			guidelines	exist	
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:15 - 0:20	0:00 - 0:02	0:01 - 0:03					
below -25 °C to LOUT ¹³ (below -13 °F to LOUT)	100/0	0:15 - 0:20	0:00 - 0:00	0:00 - 0:01					

- 1 To use the HOTs in this table, ensure that the fluid and dilution being used is listed in the Type II Fluids Tested for Anti-Icing Performance and Aerodynamic Acceptance table (Table 50). Any restrictions on the use of the fluid have to be identified and applied.
- 2 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 12 No holdover time guidelines exist for this condition below -10 °C (14 °F).
- 13 If the LOUT is unknown, no holdover time guidelines exist below -25 °C (-13 °F).

CAUTIONS

TARIES: TVD	TIMES EVD	ABAX ECOWING	$\Lambda \Pi 2$
IADLE 3. I I F C	LINES FUR	ADAX ECOVING	AU-Z

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:20 - 3:00	0:30 - 0:55	2:25 - 2:55	1:15 - 2:25	0:40 - 1:15	0:40 - 1:40	0:30 - 0:45	0:09 - 1:25	
-3 °C and above (27 °F and above)	75/25	1:15 - 1:25	0:20 - 0:40	1:45 - 2:10	0:55 - 1:45	0:25 - 0:55	0:35 - 1:05	0:20 - 0:30	0:04 - 0:50	
	50/50	0:15 - 0:30	0:05 - 0:10	0:35 - 0:40	0:15 - 0:35	0:07 - 0:15	0:09 - 0:15	0:06 - 0:09		
below -3 to -8 °C	100/0	0:45 - 2:30	0:25 - 0:45	2:00 - 2:25	1:00 - 2:00	0:30 - 1:00	0:25 - 1:10	0:20 - 0:30		
(below 27 to 18 °F)	75/25	0:35 - 1:55	0:20 - 0:35	1:40 - 2:05	0:50 - 1:40	0:25 - 0:50	0:15 - 0:55	0:20 - 0:35		
below -8 to -14 °C	100/0	0:45 - 2:30	0:20 - 0:40	1:45 - 2:05	0:55 - 1:45	0:30 - 0:55	0:25 - 1:10 ¹¹	0:20 - 0:3011	OALITIO	
(below 18 to 7 °F)	75/25	0:35 - 1:55	0:20 - 0:35	1:35 - 2:00	0:50 - 1:35	0:25 - 0:50	0:15 - 0:55 ¹¹	0:20 - 0:3511	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:15 - 0:40	0:01 - 0:05	0:20 - 0:30	0:07 - 0:20	0:02 - 0:07		guidelines exist		
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:15 - 0:40	0:00 - 0:02	0:09 - 0:15	0:03 - 0:09	0:01 - 0:03				
below -25 to -27 °C (below -13 to -17 °F)	100/0	0:15 - 0:40	0:00 - 0:00	0:05 - 0:07	0:01 - 0:05	0:00 - 0:01				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 6: TYPE II HOLDOVER TIMES FOR AVIATION XI'AN HIGH-TECH CLEANWING II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	0:55 - 1:50	0:20 - 0:40	1:35 - 1:55	0:55 - 1:35	0:30 - 0:55	0:35 - 1:05	0:25 - 0:35	0:10 - 0:55	
-3 °C and above (27 °F and above)	75/25	0:50 - 1:20	0:20 - 0:35	1:20 - 1:40	0:45 - 1:20	0:25 - 0:45	0:35 - 1:00	0:20 - 0:30	0:07 - 0:50	
(2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	50/50	0:35 - 1:00	0:10 - 0:20	0:50 - 1:05	0:25 - 0:50	0:15 - 0:25	0:20 - 0:40	0:10 - 0:20		
below -3 to -8 °C	100/0	0:45 - 1:50	0:15 - 0:30	1:20 - 1:35	0:40 - 1:20	0:25 - 0:40	0:30 - 0:55	0:20 - 0:25		
(below 27 to 18 °F)	75/25	0:40 - 1:45	0:20 - 0:35	1:20 - 1:35	0:45 - 1:20	0:25 - 0:45	0:35 - 0:40	0:20 - 0:25		
below -8 to -14 °C	100/0	0:45 - 1:50	0:15 - 0:25	1:05 - 1:20	0:35 - 1:05	0:20 - 0:35	0:30 - 0:55 ¹¹	0:20 - 0:2511	CAUTIO No holdove	
(below 18 to 7 °F)	75/25	0:40 - 1:45	0:20 - 0:35	1:20 - 1:35	0:45 - 1:20	0:25 - 0:45	0:35 - 0:4011	0:20 - 0:2511	guidelines	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:20 - 0:50	0:09 - 0:20	0:45 - 1:00	0:25 - 0:45	0:15 - 0:25			-	
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:20 - 0:50	0:05 - 0:10	0:30 - 0:35	0:15 - 0:30	0:07 - 0:15				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 7: TYPE II HOLDOVER TIMES FOR CLARIANT SAFEWING MP II FLIGHT

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰		
	100/0	3:30 - 4:00	0:45 - 1:10	2:35 - 3:00	1:35 - 2:35	1:00 - 1:35	1:20 - 2:00	0:45 - 1:25	0:10 - 1:30			
-3 °C and above (27 °F and above)	75/25	1:50 - 2:45	0:30 - 1:00	2:35 - 3:00	1:20 - 2:35	0:40 - 1:20	1:10 - 1:30	0:30 - 0:55	0:06 - 0:50			
(= 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	50/50	0:55 - 1:45	0:09 - 0:20	0:45 - 0:55	0:25 - 0:45	0:10 - 0:25	0:20 - 0:30	0:10 - 0:15				
below -3 to -8 °C	100/0	0:55 - 1:45	0:35 - 1:00	2:05 - 2:30	1:15 - 2:05	0:45 - 1:15	0:35 - 1:30	0:25 - 0:45				
(below 27 to 18 °F)	75/25	0:25 - 1:05	0:20 - 0:40	1:45 - 2:10	0:55 - 1:45	0:30 - 0:55	0:25 - 1:10	0:20 - 0:35				
below -8 to -14 °C	100/0	0:55 - 1:45	0:30 - 0:50	1:50 - 2:10	1:05 - 1:50	0:40 - 1:05	0:35 - 1:30 ¹¹	0:25 - 0:4511	0.44174.0			
(below 18 to 7 °F)	75/25	0:25 - 1:05	0:15 - 0:30	1:20 - 1:40	0:40 - 1:20	0:20 - 0:40	0:25 - 1:10 ¹¹	0:20 - 0:3511	CAUTIO No holdove			
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:30 - 0:50	0:06 - 0:20	1:10 - 1:40	0:25 - 1:10	0:08 - 0:25			guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:30 - 0:50	0:02 - 0:07	0:30 - 0:40	0:10 - 0:30	0:03 - 0:10						
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:30 - 0:50	0:01 - 0:05	0:20 - 0:30	0:07 - 0:20	0:02 - 0:07						

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 8: TYPE II HOLDOVER TIMES FOR CRYOTECH POLAR GUARD® II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:50 - 4:00	0:50 - 1:25	3:00 - 3:00	1:55 - 3:00	1:05 - 1:55	1:35 - 2:00	1:15 - 1:30	0:15 - 2:00	
-3 °C and above (27 °F and above)	75/25	2:30 - 4:00	0:30 - 1:05	3:00 - 3:00	1:25 - 3:00	0:40 - 1:25	1:40 - 2:00	0:40 - 1:10	0:09 - 1:40	
(= 1	50/50	0:50 - 1:25	0:07 - 0:20	1:10 - 1:35	0:25 - 1:10	0:10 - 0:25	0:20 - 0:45	0:09 - 0:20		
below -3 to -8 °C	100/0	0:55 - 2:30	0:35 - 1:05	2:25 - 2:50	1:25 - 2:25	0:50 - 1:25	0:35 - 1:35	0:35 - 0:45		
(below 27 to 18 °F)	75/25	0:40 - 1:30	0:25 - 0:50	2:20 - 3:00	1:05 - 2:20	0:30 - 1:05	0:25 - 1:05	0:35 - 0:45		
below -8 to -14 °C	100/0	0:55 - 2:30	0:30 - 0:50	2:00 - 2:20	1:10 - 2:00	0:40 - 1:10	0:35 - 1:35 ¹¹	0:35 - 0:45 ¹¹	CALITIO	
(below 18 to 7 °F)	75/25	0:40 - 1:30	0:20 - 0:45	2:00 - 2:30	0:55 - 2:00	0:25 - 0:55	0:25 - 1:05 ¹¹	0:35 - 0:45 ¹¹	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:25 - 0:50	0:08 - 0:25	1:35 - 2:15	0:35 - 1:35	0:10 - 0:35			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:25 - 0:50	0:03 - 0:10	0:40 - 0:55	0:15 - 0:40	0:04 - 0:15				
below -25 to -30.5 °C (below -13 to -23 °F)	100/0	0:25 - 0:50	0:02 - 0:05	0:25 - 0:30	0:07 - 0:25	0:02 - 0:07				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 9: TYPE II HOLDOVER TIMES FOR KILFROST ABC-K PLUS

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Freezing Fog, Freezing Mist ² , or Ice Crystals ³	Snow mixed with Freezing Fog ⁴	Snow, Snow Grains or Snow Pellets ^{5,6,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold- Soaked Wing ⁹	Other ¹⁰
	100/0	2:15 - 3:45	0:45 - 1:15	1:00 - 1:40	1:50 - 2:00	1:00 - 1:25	0:20 - 2:00	
-3 °C and above (27 °F and above)	75/25	1:40 - 2:30	0:25 - 0:50	0:35 - 1:10	1:25 - 2:00	0:50 - 1:10	0:15 - 2:00	
(=	50/50	0:35 - 1:05	0:05 - 0:10	0:07 - 0:15	0:20 - 0:30	0:10 - 0:15		
below -3 to -8 °C	100/0	0:30 - 1:05	0:40 - 1:10	0:55 - 1:30	0:25 - 1:00	0:15 - 0:35		
(below 27 to 18 °F)	75/25	0:25 - 1:25	0:25 - 0:50	0:35 - 1:05	0:20 - 0:55	0:09 - 0:30		
below -8 to -14 °C	100/0	0:30 - 1:05	0:40 - 1:05	0:50 - 1:25	0:25 - 1:00 ¹¹	0:15 - 0:35 ¹¹	0411710	
(below 18 to 7 °F)	75/25	0:25 - 1:25	0:25 - 0:50	0:35 - 1:05	0:20 - 0:55 ¹¹	0:09 - 0:30 ¹¹	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:30 - 0:55	0:01 - 0:05	0:02 - 0:07			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:30 - 0:55	0:00 - 0:02	0:01 - 0:03				
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:30 - 0:55	0:00 - 0:00	0:00 - 0:01				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TARIF 10	· TYPF II HOI	DOVER TIMES	FOR KILFRO	ST ICE CLEAR II
IADLE IV) FUN NILFNU	JOI ICE CLEAR II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:25 - 2:25	0:30 - 1:00	2:25 - 2:55	1:20 - 2:25	0:40 - 1:20	1:00 - 1:35	0:40 - 1:05	0:15 - 2:00	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(= 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	1:05 - 2:35	0:30 - 0:50	2:10 - 2:35	1:10 - 2:10	0:40 - 1:10	0:30 - 1:15	0:35 - 0:55		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	1:05 - 2:35	0:25 - 0:50	2:00 - 2:25	1:05 - 2:00	0:35 - 1:05	0:30 - 1:15 ¹¹	0:35 - 0:5511	0.411710	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:35 - 0:45	0:10 - 0:20	0:55 - 1:05	0:30 - 0:55	0:15 - 0:30			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:35 - 0:45	0:06 - 0:10	0:30 - 0:35	0:15 - 0:30	0:08 - 0:15				
below -25 to -28 °C (below -13 to -18 °F)	100/0	0:35 - 0:45	0:05 - 0:09	0:25 - 0:30	0:10 - 0:25	0:06 - 0:10				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 11: TYPE II HOLDOVER TIMES FOR MKS DEVO CHEMICALS COREICEPHOB TYPE II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:55 - 2:45	0:30 - 1:00	2:35 - 3:00	1:25 - 2:35	0:40 - 1:25	1:10 - 2:00	0:45 - 1:00	0:15 - 1:35	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(50/50	1:05 - 1:45	0:15 - 0:35	1:35 - 1:55	0:45 - 1:35	0:25 - 0:45	0:50 - 1:15	0:25 - 0:30		
below -3 to -8 °C	100/0	0:45 - 1:25	0:25 - 0:45	1:50 - 2:15	1:00 - 1:50	0:30 - 1:00	0:30 - 1:10	0:25 - 0:35		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:45 - 1:25	0:20 - 0:35	1:30 - 1:50	0:50 - 1:30	0:25 - 0:50	0:30 - 1:1011	0:25 - 0:3511		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:15 - 0:25	0:01 - 0:05	0:20 - 0:30	0:07 - 0:20	0:02 - 0:07			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:15 - 0:25	0:00 - 0:02	0:09 - 0:15	0:03 - 0:09	0:01 - 0:03				
below -25 to -27 °C (below -13 to -17 °F)	100/0	0:15 - 0:25	0:00 - 0:00	0:05 - 0:07	0:01 - 0:05	0:00 - 0:01				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- These holdover times are for use in -SNFZFG and SNFZFG below 0°C. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm that the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm that the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0°C (32°F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10°C (14°F).

CAUTIONS

TABLE 12: TYPE II HOLDOVER TIMES FOR NEWAVE AEROCHEMICAL FCY-2

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Freezing Fog, Freezing Mist ² , or Ice Crystals ³	Snow mixed with Freezing Fog ⁴	Snow, Snow Grains or Snow Pellets ^{5,6,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold- Soaked Wing ⁹	Other ¹⁰
	100/0	1:15 - 2:25	0:25 - 0:40	0:30 - 0:55	0:35 - 1:05	0:25 - 0:35	0:08 - 0:45	
-3 °C and above (27 °F and above)	75/25	0:50 - 1:30	0:15 - 0:30	0:20 - 0:40	0:25 - 0:45	0:15 - 0:25	0:05 - 0:25	
(======================================	50/50	0:25 - 0:35	0:09 - 0:20	0:15 - 0:25	0:10 - 0:20	0:07 - 0:10		
below -3 to -8 °C	100/0	0:45 - 1:30	0:15 - 0:30	0:20 - 0:40	0:20 - 0:45	0:15 - 0:20		
(below 27 to 18 °F)	75/25	0:30 - 1:05	0:10 - 0:20	0:15 - 0:25	0:15 - 0:30	0:08 - 0:15		
below -8 to -14 °C	100/0	0:45 - 1:30	0:10 - 0:25	0:15 - 0:30	0:20 - 0:45 ¹¹	0:15 - 0:20 ¹¹	0411710	
(below 18 to 7 °F)	75/25	0:30 - 1:05	0:08 - 0:15	0:10 - 0:20	0:15 - 0:30 ¹¹	0:08 - 0:15 ¹¹	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:25 - 0:35	0:01 - 0:05	0:02 - 0:07			guidelines	exist
below -18 to -25 °C ¹² (below 0 to -13 °F)	100/0	0:25 - 0:35	0:00 - 0:02	0:01 - 0:03				
below -25 to -28 °C (below -13 to -18 °F)	100/0	0:25 - 0:35	0:00 - 0:00	0:00 - 0:01				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 13: TYPE II HOLDOVER TIMES FOR ROMCHIM ADD-PROTECT NG TYPE II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:10 - 2:25	0:25 - 0:55	2:35 - 3:00	1:10 - 2:35	0:35 - 1:10	0:50 - 1:20	0:35 - 0:50	0:07 - 1:10	
-3 °C and above (27 °F and above)	75/25	1:00 - 1:50	0:20 - 0:40	1:55 - 2:25	0:55 - 1:55	0:25 - 0:55	0:40 - 1:15	0:25 - 0:40	0:07 - 0:55	
(2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	50/50	0:25 - 0:55	0:10 - 0:20	0:55 - 1:05	0:30 - 0:55	0:15 - 0:30	0:20 - 0:35	0:10 - 0:20		
below -3 to -8 °C	100/0	0:55 - 1:35	0:20 - 0:40	1:50 - 2:20	0:50 - 1:50	0:25 - 0:50	0:35 - 1:10	0:25 - 0:35		
(below 27 to 18 °F)	75/25	0:55 - 1:25	0:15 - 0:30	1:25 - 1:45	0:40 - 1:25	0:20 - 0:40	0:25 - 1:05	0:20 - 0:30		
below -8 to -14 °C	100/0	0:55 - 1:35	0:15 - 0:30	1:25 - 1:50	0:40 - 1:25	0:20 - 0:40	0:35 - 1:10 ¹¹	0:25 - 0:3511	CALITIO	NI.
(below 18 to 7 °F)	75/25	0:55 - 1:25	0:10 - 0:25	1:05 - 1:25	0:30 - 1:05	0:15 - 0:30	0:25 - 1:05 ¹¹	0:20 - 0:3011	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:15 - 0:20	0:01 - 0:05	0:20 - 0:30	0:07 - 0:20	0:02 - 0:07			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:15 - 0:20	0:00 - 0:02	0:09 - 0:15	0:03 - 0:09	0:01 - 0:03				
below -25 to -28 °C (below -13 to -18 °F)	100/0	0:15 - 0:20	0:00 - 0:00	0:05 - 0:07	0:01 - 0:05	0:00 - 0:01				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 14: TYPE II HOLDOVER TIMES FOR ROMCHIM ADD-PROTECT TYPE II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:40 - 3:30	0:20 - 0:45	1:55 - 2:25	1:00 - 1:55	0:30 - 1:00	0:40 - 1:35	0:25 - 0:45	0:09 - 0:50	
-3 °C and above (27 °F and above)	75/25	0:40 - 1:10	0:15 - 0:25	1:00 - 1:10	0:30 - 1:00	0:15 - 0:30	0:25 - 0:40	0:15 - 0:25	0:05 - 0:25	
(50/50	0:20 - 0:35	0:07 - 0:15	0:30 - 0:35	0:15 - 0:30	0:09 - 0:15	0:10 - 0:30	0:08 - 0:10		
below -3 to -8 °C	100/0	0:30 - 0:45	0:15 - 0:30	1:20 - 1:40	0:40 - 1:20	0:20 - 0:40	0:25 - 0:50	0:20 - 0:30		
(below 27 to 18 °F)	75/25	0:30 - 0:55	0:09 - 0:15	0:40 - 0:50	0:25 - 0:40	0:10 - 0:25	0:20 - 0:30	0:15 - 0:20		
below -8 to -14 °C	100/0	0:30 - 0:45	0:15 - 0:25	1:05 - 1:20	0:35 - 1:05	0:15 - 0:35	0:25 - 0:5011	0:20 - 0:3011	0.411710	
(below 18 to 7 °F)	75/25	0:30 - 0:55	0:07 - 0:15	0:35 - 0:40	0:20 - 0:35	0:09 - 0:20	0:20 - 0:3011	0:15 - 0:2011	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:15 - 0:25	0:01 - 0:05	0:20 - 0:30	0:07 - 0:20	0:02 - 0:07			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:15 - 0:25	0:00 - 0:02	0:09 - 0:15	0:03 - 0:09	0:01 - 0:03				
below -25 to -28 °C (below -13 to -18 °F)	100/0	0:15 - 0:25	0:00 - 0:00	0:05 - 0:07	0:01 - 0:05	0:00 - 0:01				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

HOT GUIDELINES FOR SAE TYPE III FLUIDS WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

CAUTIONS

- The responsibility for the application of these data remains with the user.
- The time of protection will be shortened in heavy weather conditions. Heavy precipitation rates or high moisture content, high wind velocity jet blast, or blowing snow may reduce holdover time below the lowest time stated in the range.
 Holdover time may be reduced when aircraft skin temperature is lower than outside air temperature.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.

TABLE 15: TYPE III HOLDOVER TIMES FOR ALLCLEAR AEROCLEAR MAX APPLIED UNHEATED ON LOW SPEED AIRCRAFT¹

Outside Air Temperature ²	Fluid Concentration Fluid/Water By % Volume	Mist ³ , or Ice	Snow mixed with Freezing Fog ⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold-Soaked Wing ¹⁰	Other ¹¹
	100/0	0:45 - 1:55	0:13 - 0:30	1:20 - 1:45	0:40 - 1:20	0:18 - 0:40	0:25 - 0:50	0:14 - 0:25	0:05 - 0:40	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(= 1	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		-
below -3 to -10 °C	100/0	0:50 - 1:40	0:13 - 0:30	1:20 - 1:45	0:40 - 1:20	0:18 - 0:40	0:25 - 0:45	0:15 - 0:25	CAUTIO	N:
(below 27 to 14 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	No holdover guidelines	
below -10 to -16 °C (below 14 to 3 °F)	100/0	0:40 - 1:45	0:13 - 0:30	1:20 - 1:45	0:40 - 1:20	0:18 - 0:40				

NOTES

- 1 These holdover times are for aircraft conforming to the SAE AS5900 low speed aerodynamic test criterion. Fluid must be applied unheated to use these holdover times. No holdover times exist for this fluid applied heated. If uncertain whether the aircraft conforms to the low, middle, or high speed aerodynamic test criterion, no holdover time guidelines exist below -16°C (3°F).
- 2 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type III fluid cannot be used.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.

CAUTIONS

TABLE 16: TYPE III HOLDOVER TIMES FOR ALLCLEAR AEROCLEAR MAX APPLIED UNHEATED ON MIDDLE SPEED AIRCRAFT¹

Outside Air Temperature ²	Fluid Concentration Fluid/Water By % Volume	Mist ³ , or Ice	Snow mixed with Freezing Fog ⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold-Soaked Wing ¹⁰	Other ¹¹
	100/0	0:45 - 1:55	0:13 - 0:30	1:20 - 1:45	0:40 - 1:20	0:18 - 0:40	0:25 - 0:50	0:14 - 0:25	0:05 - 0:40	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(= 1	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		-
below -3 to -10 °C	100/0	0:50 - 1:40	0:13 - 0:30	1:20 - 1:45	0:40 - 1:20	0:18 - 0:40	0:25 - 0:45	0:15 - 0:25	CAUTIO	N:
(below 27 to 14 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	No holdove	
below -10 to -20.5 °C (below 14 to -5 °F)	100/0	0:40 - 1:45	0:13 - 0:30	1:20 - 1:45	0:40 - 1:20	0:18 - 0:40			galaciiilee	O/IIOC

NOTES

- 1 These holdover times are for aircraft conforming to the SAE AS5900 middle speed aerodynamic test criterion. Fluid must be applied unheated to use these holdover times. No holdover times exist for this fluid applied heated. If uncertain whether the aircraft conforms to the low, middle, or high speed aerodynamic test criterion, no holdover time guidelines exist below -16°C (3°F).
- 2 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type III fluid cannot be used.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.

CAUTIONS

TABLE 17: TYPE III HOLDOVER TIMES FOR ALLCLEAR AEROCLEAR MAX APPLIED UNHEATED ON HIGH SPEED AIRCRAFT¹

Outside Air Temperature ²	Fluid Concentration Fluid/Water By % Volume	Mist ³ , or Ice	Snow mixed with Freezing Fog ⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold-Soaked Wing ¹⁰	Other ¹¹
	100/0	0:45 - 1:55	0:13 - 0:30	1:20 - 1:45	0:40 - 1:20	0:18 - 0:40	0:25 - 0:50	0:14 - 0:25	0:05 - 0:40	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(=: : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -10 °C	100/0	0:50 - 1:40	0:13 - 0:30	1:20 - 1:45	0:40 - 1:20	0:18 - 0:40	0:25 - 0:45	0:15 - 0:25		
(below 27 to 14 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -10 to -25 °C (below 14 to -13 °F)	100/0	0:40 - 1:45	0:13 - 0:30	1:20 - 1:45	0:40 - 1:20	0:18 - 0:40			guidelines	
below -25 to -35 °C (below -13 to -31 °F)	100/0	0:25 - 1:00	0:07 - 0:16	0:45 - 1:00	0:20 - 0:45	0:10 - 0:20				

NOTES

- 1 These holdover times are for aircraft conforming to the SAE AS5900 high speed aerodynamic test criterion. Fluid must be applied unheated to use these holdover times. No holdover times exist for this fluid applied heated. If uncertain whether the aircraft conforms to the low, middle, or high speed aerodynamic test criterion, no holdover time guidelines exist below -16°C (3°F).
- 2 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type III fluid cannot be used.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 45 provides allowance times for ice pellets and small hail for SAE Type III fluids, applied unheated).

CAUTIONS

HOT GUIDELINES FOR SAE TYPE IV FLUIDS WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend, or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

CAUTIONS

- The responsibility for the application of these data remains with the user.
- The time of protection will be shortened in heavy weather conditions. Heavy precipitation rates or high moisture content, high wind velocity jet blast, or blowing snow may reduce holdover time below the lowest time stated in the range.
 Holdover time may be reduced when aircraft skin temperature is lower than outside air temperature.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.
- Whenever frost or ice occurs on the lower surface of the wing in the area of the fuel tank, indicating a cold-soaked wing, the 50/50 dilutions of Type II or IV shall not be used for the anti-icing step because fluid freezing may occur.

TADIE 10.	GENERIC HOL	DOVED	TIMES EOD	CAE TVDE	IV EL LUDe1
TABLE 18:	GENERIC HOL	_DUVER	HIMES FOR	SAE ITPE	IN LUNDO.

Outside Air Temperature ²	Fluid Concentration Fluid/Water By % Volume	Mist ³ , or Ice	Snow mixed with Freezing Fog ⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold-Soaked Wing ¹⁰	Other ¹¹	
	100/0	1:15 - 2:15	0:25 - 0:45	1:55 - 2:20	1:00 - 1:55	0:30 - 1:00	0:40 - 1:10	0:20 - 0:35	0:08 - 1:05		
-3 °C and above (27 °F and above)	75/25	1:25 - 2:40	0:30 - 0:55	2:05 - 2:25	1:15 - 2:05	0:40 - 1:15	1:00 - 1:20	0:30 - 0:50	0:09 - 1:20		
(=: : : :::::::::::::::::::::::::::::::	50/50	0:30 - 0:55	0:07 - 0:20	1:00 - 1:10	0:25 - 1:00	0:10 - 0:25	0:15 - 0:40	0:09 - 0:20		_	
below -3 to -8 °C	100/0	0:15 - 0:35	0:20 - 0:40	1:45 - 2:05	0:55 - 1:45	0:25 - 0:55	0:25 - 1:10	0:20 - 0:25			
(below 27 to 18 °F)	75/25	0:40 - 1:20	0:25 - 0:50	1:50 - 2:10	1:05 - 1:50	0:30 - 1:05	0:20 - 1:05	0:15 - 0:25			
below -8 to -14 °C	100/0	0:15 - 0:35	0:15 - 0:35	1:30 - 1:50	0:45 - 1:30	0:20 - 0:45	0:25 - 1:10 ¹²	0:20 - 0:2512	OALITIO		
(below 18 to 7 °F)	75/25	0:40 - 1:20	0:20 - 0:45	1:45 - 2:00	0:55 - 1:45	0:25 - 0:55	0:20 - 1:0512	0:15 - 0:25 ¹²		CAUTION: No holdover time	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:15 - 0:30	0:01 - 0:06	0:30 - 0:45	0:09 - 0:30	0:02 - 0:09			guidelines exist		
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:15 - 0:30	0:00 - 0:02	0:10 - 0:20	0:03 - 0:10	0:01 - 0:03					
below -25 °C to LOUT ¹³ (below -13 °F to LOUT)	1 1()()/()	0:15 - 0:30	0:00 - 0:01	0:07 - 0:10	0:02 - 0:07	0:00 - 0:02					

- 1 To use the HOTs in this table, ensure that the fluid and dilution being used is listed in the Type IV Fluids Tested for Anti-Icing Performance and Aerodynamic Acceptance table (Table 52). Any restrictions on the use of the fluid have to be identified and applied.
- 2 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 46 provides allowance times for Type IV EG fluids and Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail. If the glycol type is unknown, the allowance times for SAE Type IV PG fluids should be used).
- 12 No holdover time guidelines exist for this condition below -10 °C (14 °F).
- 13 If the LOUT is unknown, no holdover time guidelines exist below -25.5 °C (-14 °F).

CAUTIONS

TARIF 19	· TYPE IV HO	DLDOVER TIMES FOR	ARAY FCOWING	ΔD-49
IADLE 13.		JEDUVER HIVIES FOR	ADAX ECUVVIIIG	AU-43

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	3:20 - 4:00	0:45 - 1:25	3:00 - 3:00	1:55 - 3:00	1:00 - 1:55	1:25 - 2:00	1:00 - 1:25	0:10 - 1:55		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(=:	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		•	
below -3 to -8 °C	100/0	0:20 - 1:35	0:35 - 1:05	2:55 - 3:00	1:30 - 2:55	0:45 - 1:30	0:25 - 1:25	0:20 - 0:25			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	0:20 - 1:35	0:30 - 0:55	2:25 - 3:00	1:15 - 2:25	0:40 - 1:15	0:25 - 1:2511	0:20 - 0:2511	CALITIO		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		CAUTION: No holdover time	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:25 - 0:40	0:01 - 0:06	0:30 - 0:45	0:09 - 0:30	0:02 - 0:09		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:25 - 0:40	0:00 - 0:02	0:10 - 0:20	0:03 - 0:10	0:01 - 0:03					
below -25 to -26 °C (below -13 to -15 °F)	100/0	0:25 - 0:40	0:00 - 0:01	0:07 - 0:10	0:02 - 0:07	0:00 - 0:02					

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 20: TYPE IV HOLDOVER TIMES FOR ALAB INTERNATIONAL PROFLIGHT EG4

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Freezing Fog, Freezing Mist ² , or Ice Crystals ³	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	3:05 - 4:00	0:45 - 1:25	3:00 - 3:00	1:50 - 3:00	1:00 - 1:50	1:25 - 2:00	0:40 - 1:00	0:10 - 2:00	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(=: -: =::= ::= ::= ;	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	2:30 - 3:55	0:45 - 1:25	3:00 - 3:00	1:50 - 3:00	1:00 - 1:50	1:05 - 2:00	0:50 - 1:35		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	2:30 - 3:55	0:45 - 1:25	3:00 - 3:00	1:50 - 3:00	1:00 - 1:50	1:05 - 2:0011	0:50 - 1:35 ¹¹	CALITIO	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:35 - 1:35	0:07 - 0:20	0:50 - 1:05	0:25 - 0:50	0:10 - 0:25		guidelines exist		
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:35 - 1:35	0:03 - 0:10	0:40 - 0:55	0:15 - 0:40	0:05 - 0:15				
below -25 to -26°C (below -13 to -15°F)	100/0	0:35 - 1:35	0:01 - 0:06	0:25 - 0:35	0:08 - 0:25	0:02 - 0:08				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 46 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 21: TYPE IV HOLDOVER TIMES FOR ALAB INTERNATIONAL PROFLIGHT PG4

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Freezing Fog, Freezing Mist ² , or Ice Crystals ³	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:25 - 2:15	0:30 - 1:00	2:40 - 3:00	1:20 - 2:40	0:40 - 1:20	1:05 - 1:25	0:40 - 0:50	0:15 - 1:20	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(=: -: =::= ::= ::= ;	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	1:05 - 2:20	0:25 - 0:50	2:20 - 2:55	1:10 - 2:20	0:35 - 1:10	0:45 - 1:10	0:35 - 0:45		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	1:05 - 2:20	0:20 - 0:45	2:05 - 2:35	1:00 - 2:05	0:30 - 1:00	0:45 - 1:10 ¹¹	0:35 - 0:4511	CALITIO	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:35 - 0:50	0:01 - 0:06	0:30 - 0:45	0:09 - 0:30	0:02 - 0:09		guidelines exist		
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:35 - 0:50	0:00 - 0:02	0:10 - 0:20	0:03 - 0:10	0:01 - 0:03				
below -25 to -29°C (below -13 to -20°F)	100/0	0:35 - 0:50	0:00 - 0:01	0:07 - 0:10	0:02 - 0:07	0:00 - 0:02				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TARI F 22. TYPF IV HO	I DOVER TIMES FOR	RALLCLEAR CLEARWING EG	ì
		ALLULLAN ULLANVINU LU	,

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	1:50 - 3:15	0:30 - 1:00	2:40 - 3:00	1:20 - 2:40	0:40 - 1:20	1:10 - 1:35	0:30 - 1:00	0:10 - 1:30		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		_	
below -3 to -8 °C	100/0	1:35 - 3:45	0:25 - 0:55	2:25 - 3:00	1:10 - 2:25	0:35 - 1:10	1:05 - 1:30	0:30 - 1:00			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	1:35 - 3:45	0:25 - 0:50	2:15 - 2:45	1:05 - 2:15	0:30 - 1:05	1:05 - 1:3011	0:30 - 1:0011	0.411710		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		CAUTION: No holdover time	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:55 - 2:00	0:15 - 0:35	1:35 - 2:05	0:45 - 1:35	0:20 - 0:45			guidelines exist		
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:55 - 2:00	0:09 - 0:20	0:55 - 1:10	0:25 - 0:55	0:15 - 0:25					
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:55 - 2:00	0:07 - 0:15	0:45 - 0:55	0:20 - 0:45	0:10 - 0:20					

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 46 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TARIF 23	· TYPF I\	/ HOLDOVER	TIMES FOR	ASGLOBAL	4FI ITF FG
IADLL 23.		/ IIOLDOVLI		AJGLUDAL	#1 L11 L LG

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	1:35 - 3:15	0:25 - 0:45	2:05 - 2:35	1:00 - 2:05	0:30 - 1:00	0:40 - 1:10	0:20 - 0:35	0:08 - 1:05		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(=:	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	1:25 - 2:45	0:20 - 0:40	1:50 - 2:15	0:55 - 1:50	0:25 - 0:55	0:40 - 1:10	0:20 - 0:35			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	1:25 - 2:45	0:20 - 0:35	1:35 - 2:00	0:50 - 1:35	0:25 - 0:50	0:40 - 1:10 ¹¹	0:20 - 0:3511	CALITIO		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		CAUTION: No holdover time	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:50 - 1:25	0:15 - 0:35	1:35 - 2:00	0:45 - 1:35	0:20 - 0:45		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:50 - 1:25	0:15 - 0:30	1:20 - 1:40	0:35 - 1:20	0:20 - 0:35					
below -25 to -30 °C (below -13 to -22 °F)	100/0	0:30 - 1:05	0:09 - 0:20	0:55 - 1:05	0:25 - 0:55	0:10 - 0:25					

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 24: TYPE IV HOLDOVER TIMES FOR ASGLOBAL 4FLITE PG

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰		
	100/0	1:50 - 3:15	0:40 - 1:10	2:50 - 3:00	1:35 - 2:50	0:50 - 1:35	1:10 - 1:35	0:45 - 1:05	0:15 - 1:20			
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		•		
below -3 to -8 °C	100/0	1:05 - 1:55	0:30 - 0:50	2:05 - 2:30	1:10 - 2:05	0:35 - 1:10	0:55 - 1:10	0:35 - 0:55				
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A				
below -8 to -14 °C	100/0	1:05 - 1:55	0:20 - 0:40	1:40 - 2:00	0:55 - 1:40	0:30 - 0:55	0:55 - 1:10 ¹¹	0:35 - 0:55 ¹¹	CALITIO			
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove			
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:30 - 0:45	0:15 - 0:25	1:05 - 1:20	0:35 - 1:05	0:15 - 0:35		guidelines exist				
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:30 - 0:45	0:07 - 0:15	0:35 - 0:45	0:20 - 0:35	0:09 - 0:20						
below -25 to -26 °C (below -13 to -15 °F)	100/0	0:30 - 0:45	0:06 - 0:15	0:35 - 0:45	0:20 - 0:35	0:08 - 0:20						

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 25: TYPE	IV HOLDOVED	TIMES FOD	V/IVEL LIID	AVIAELICHT EC
IADLE 20: ITPE	IV HULDUVER	LIMES FUR	AVIAFLUID	AVIACLIGHTEG

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:30 - 3:05	0:30 - 0:50	1:55 - 2:20	1:10 - 1:55	0:40 - 1:10	1:05 - 2:00	0:30 - 0:50	0:10 - 2:00	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(=: : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		-
below -3 to -8 °C	100/0	1:20 - 3:00	0:25 - 0:45	1:45 - 2:05	1:00 - 1:45	0:35 - 1:00	0:55 - 1:30	0:35 - 0:50		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	1:20 - 3:00	0:25 - 0:40	1:35 - 1:55	0:55 - 1:35	0:30 - 0:55	0:55 - 1:30 ¹¹	0:35 - 0:5011	0.411710	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:35 - 1:45	0:20 - 0:40	1:40 - 2:00	0:50 - 1:40	0:25 - 0:50			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:35 - 1:45	0:15 - 0:30	1:20 - 1:35	0:40 - 1:20	0:20 - 0:40				
below -25 to -31 °C (below -13 to -24 °F)	100/0	0:35 - 1:05	0:07 - 0:15	0:35 - 0:45	0:20 - 0:35	0:09 - 0:20				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 46 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 26: TYPE IV HOLDOVER TIMES FOR AVIAFLUID AVIAFLIGHT PG

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰			
	100/0	2:15 - 4:00	0:40 - 1:15	3:00 - 3:00	1:40 - 3:00	0:55 - 1:40	2:00 - 2:00	1:10 - 1:55	0:20 - 2:00				
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A				
(= 1 1 4.14 4.55 15)	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		•			
below -3 to -8 °C	100/0	1:05 - 2:10	0:25 - 0:50	2:00 - 2:25	1:05 - 2:00	0:35 - 1:05	0:35 - 1:55	0:45 - 1:05					
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A					
below -8 to -14 °C	100/0	1:05 - 2:10	0:20 - 0:35	1:30 - 1:50	0:50 - 1:30	0:25 - 0:50	0:35 - 1:55 ¹¹	0:45 - 1:05 ¹¹	0.411710				
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove				
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:20 - 0:35	0:10 - 0:20	0:50 - 1:00	0:25 - 0:50	0:15 - 0:25			guidelines exist				
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:20 - 0:35	0:05 - 0:09	0:25 - 0:30	0:15 - 0:25	0:06 - 0:15							
below -25 to -25.5 °C (below -13 to -14 °F)	100/0	0:20 - 0:35	0:05 - 0:09	0:25 - 0:30	0:10 - 0:25	0:06 - 0:10							

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TARIF 27:	TYPE IV	HOLDO/	/FR TIMES FO	R CHEMCO	CHEMR EG IV
IADLL 21.		HOLDON	ER HIVIES FU	IN CHEIVICO	CHEIVIN EG IV

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	2:05 - 3:35	0:25 - 1:00	3:00 - 3:00	1:15 - 3:00	0:35 - 1:15	0:45 - 1:40	0:25 - 0:40	0:09 - 1:45		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(= 1	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	1:25 - 3:40	0:25 - 1:00	3:00 - 3:00	1:15 - 3:00	0:35 - 1:15	1:00 - 1:35	0:35 - 0:50			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	1:25 - 3:40	0:25 - 1:00	3:00 - 3:00	1:15 - 3:00	0:35 - 1:15	1:00 - 1:35 ¹¹	0:35 - 0:5011	CALITIO		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:40 - 1:25	0:15 - 0:30	1:25 - 1:45	0:40 - 1:25	0:20 - 0:40		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:40 - 1:25	0:15 - 0:30	1:25 - 1:45	0:40 - 1:25	0:20 - 0:40					
below -25 to -27 °C (below -13 to -17 °F)	100/0	0:40 - 1:25	0:15 - 0:30	1:25 - 1:45	0:40 - 1:25	0:20 - 0:40					

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 46 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 28: TYPE IV HOLDOVER TIMES FOR CHEMCO CHEMR NORDIK IV

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	2:15 - 4:00	0:40 - 1:20	3:00 - 3:00	1:45 - 3:00	0:55 - 1:45	1:20 - 2:00	0:55 - 1:20	0:25 - 2:00		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		_	
below -3 to -8 °C	100/0	1:50 - 4:00	0:40 - 1:20	3:00 - 3:00	1:45 - 3:00	0:55 - 1:45	1:15 - 2:00	0:45 - 1:20			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	1:50 - 4:00	0:40 - 1:20	3:00 - 3:00	1:45 - 3:00	0:55 - 1:45	1:15 - 2:00 ¹¹	0:45 - 1:20 ¹¹	CALITIO		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:40 - 1:30	0:35 - 1:10	3:00 - 3:00	1:35 - 3:00	0:50 - 1:35		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:40 - 1:30	0:25 - 0:50	2:10 - 2:40	1:05 - 2:10	0:35 - 1:05					
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:40 - 1:30	0:20 - 0:40	1:50 - 2:15	0:55 - 1:50	0:30 - 0:55					

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 46 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 29: TYPE IV HOLDOVER TIMES FOR CHONGQING JOBA CHEMICAL CO., LTD FW-IV

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰		
	100/0	3:15 - 4:00	0:35 - 1:15	3:00 - 3:00	1:40 - 3:00	0:50 - 1:40	1:30 - 2:00	0:45 - 1:05	0:15 - 2:00			
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A				
below -3 to -8 °C	100/0	2:30 - 4:00	0:30 - 1:00	2:45 - 3:00	1:25 - 2:45	0:40 - 1:25	0:50 - 2:00	0:35 - 1:10				
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A				
below -8 to -14 °C	100/0	2:30 - 4:00	0:30 - 0:55	2:25 - 3:00	1:15 - 2:25	0:35 - 1:15	0:50 - 2:0011	0:35 - 1:10 ¹¹	CALITIO			
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove			
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:35 - 1:40	0:20 - 0:40	2:00 - 2:35	0:55 - 2:00	0:25 - 0:55		guidelines exist				
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:35 - 1:40	0:15 - 0:30	1:20 - 1:45	0:35 - 1:20	0:15 - 0:35						
below -25 to -29°C (below -13 to -20°F)	100/0	0:35 - 1:40	0:10 - 0:25	1:10 - 1:30	0:30 - 1:10	0:15 - 0:30						

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 46 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 30: TYPE IV HOLDOVER TIMES FOR CLARIANT SAFEWING MP IV LAUNCH

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	4:00 - 4:00	0:50 - 1:20	2:50 - 3:00	1:45 - 2:50	1:05 - 1:45	1:30 - 2:00	1:00 - 1:40	0:15 - 1:40		
-3 °C and above (27 °F and above)	75/25	3:40 - 4:00	0:45 - 1:20	3:00 - 3:00	1:45 - 3:00	1:00 - 1:45	1:40 - 2:00	0:45 - 1:15	0:10 - 1:45		
(50/50	1:25 - 2:45	0:20 - 0:35	1:25 - 1:40	0:45 - 1:25	0:25 - 0:45	0:30 - 0:50	0:20 - 0:25			
below -3 to -8 °C	100/0	1:00 - 1:55	0:40 - 1:05	2:25 - 2:50	1:30 - 2:25	0:55 - 1:30	0:35 - 1:40	0:25 - 0:45			
(below 27 to 18 °F)	75/25	0:40 - 1:20	0:40 - 1:10	2:40 - 3:00	1:30 - 2:40	0:50 - 1:30	0:25 - 1:10	0:25 - 0:45			
below -8 to -14 °C	100/0	1:00 - 1:55	0:35 - 1:00	2:10 - 2:30	1:20 - 2:10	0:50 - 1:20	0:35 - 1:4011	0:25 - 0:4511	CALITIO		
(below 18 to 7 °F)	75/25	0:40 - 1:20	0:35 - 1:00	2:25 - 2:55	1:25 - 2:25	0:45 - 1:25	0:25 - 1:10 ¹¹	0:25 - 0:4511	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:30 - 0:50	0:05 - 0:15	1:15 - 1:45	0:20 - 1:15	0:06 - 0:20		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:30 - 0:50	0:02 - 0:06	0:30 - 0:45	0:09 - 0:30	0:02 - 0:09					
below -25 to -28.5 °C (below -13 to -19 °F)	100/0	0:30 - 0:50	0:01 - 0:04	0:20 - 0:30	0:06 - 0:20	0:01 - 0:06					

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 31: TYPE IV HOLDOVER TIMES FOR CLARIANT SAFEWING MP IV LAUNCH PLUS

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	3:55 - 4:00	0:40 - 1:35	3:00 - 3:00	2:05 - 3:00	0:55 - 2:05	2:00 - 2:00	1:00 - 2:00	0:20 - 2:00		
-3 °C and above (27 °F and above)	75/25	3:55 - 4:00	0:35 - 1:25	3:00 - 3:00	1:55 - 3:00	0:50 - 1:55	2:00 - 2:00	1:20 - 1:25	0:20 - 1:50		
,	50/50	1:15 - 1:50	0:15 - 0:35	1:35 - 2:00	0:45 - 1:35	0:20 - 0:45	0:25 - 1:00	0:15 - 0:20			
below -3 to -8 °C	100/0	0:55 - 2:15	0:35 - 1:15	3:00 - 3:00	1:40 - 3:00	0:45 - 1:40	0:25 - 1:35	0:25 - 0:40			
(below 27 to 18 °F)	75/25	0:40 - 2:00	0:30 - 1:05	3:00 - 3:00	1:30 - 3:00	0:35 - 1:30	0:20 - 1:05	0:20 - 0:30			
below -8 to -14 °C	100/0	0:55 - 2:15	0:30 - 1:05	3:00 - 3:00	1:25 - 3:00	0:40 - 1:25	0:25 - 1:3511	0:25 - 0:4011	0.411710		
(below 18 to 7 °F)	75/25	0:40 - 2:00	0:25 - 0:55	2:55 - 3:00	1:15 - 2:55	0:30 - 1:15	0:20 - 1:0511	0:20 - 0:3011	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:25 - 0:50	0:05 - 0:20	1:15 - 1:50	0:25 - 1:15	0:07 - 0:25		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:25 - 0:50	0:02 - 0:07	0:30 - 0:45	0:09 - 0:30	0:03 - 0:09					
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:25 - 0:50	0:01 - 0:04	0:20 - 0:30	0:06 - 0:20	0:02 - 0:06					

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 32: TYPE IV HOLDOVER TIMES FOR CRYOTECH POLAR GUARD® ADVANCE

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:50 - 4:00	0:50 - 1:25	3:00 - 3:00	1:55 - 3:00	1:05 - 1:55	1:35 - 2:00	1:15 - 1:30	0:15 - 2:00	
-3 °C and above (27 °F and above)	75/25	2:30 - 4:00	0:30 - 1:05	3:00 - 3:00	1:25 - 3:00	0:40 - 1:25	1:40 - 2:00	0:40 - 1:10	0:09 - 1:40	
(50/50	0:50 - 1:25	0:07 - 0:20	1:10 - 1:35	0:25 - 1:10	0:10 - 0:25	0:20 - 0:45	0:09 - 0:20		
below -3 to -8 °C	100/0	0:55 - 2:30	0:35 - 1:05	2:25 - 2:50	1:25 - 2:25	0:50 - 1:25	0:35 - 1:35	0:35 - 0:45		
(below 27 to 18 °F)	75/25	0:40 - 1:30	0:25 - 0:50	2:20 - 3:00	1:05 - 2:20	0:30 - 1:05	0:25 - 1:05	0:35 - 0:45		
below -8 to -14 °C	100/0	0:55 - 2:30	0:30 - 0:50	2:00 - 2:20	1:10 - 2:00	0:40 - 1:10	0:35 - 1:35 ¹¹	0:35 - 0:45 ¹¹	CALITIO	NI.
(below 18 to 7 °F)	75/25	0:40 - 1:30	0:20 - 0:45	2:00 - 2:30	0:55 - 2:00	0:25 - 0:55	0:25 - 1:05 ¹¹	0:35 - 0:45 ¹¹	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:25 - 0:50	0:08 - 0:25	1:35 - 2:15	0:35 - 1:35	0:10 - 0:35			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:25 - 0:50	0:03 - 0:10	0:40 - 0:55	0:15 - 0:40	0:04 - 0:15				
below -25 to -30.5 °C (below -13 to -23 °F)	100/0	0:25 - 0:50	0:02 - 0:05	0:25 - 0:30	0:07 - 0:25	0:02 - 0:07				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 33: TYPE IV HOLDOVER TIMES FOR CRYOTECH POLAR GUARD® XTEND

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	2:30 - 4:00	0:50 - 1:30	3:00 - 3:00	2:00 - 3:00	1:05 - 2:00	2:00 - 2:00	1:00 - 1:50	0:20 - 1:45		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	1:00 - 1:50	0:40 - 1:10	2:50 - 3:00	1:35 - 2:50	0:50 - 1:35	0:35 - 1:40	0:50 - 0:55			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	1:00 - 1:50	0:35 - 1:00	2:25 - 2:55	1:20 - 2:25	0:45 - 1:20	0:35 - 1:40 ¹¹	0:50 - 0:55 ¹¹	CALITIO		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:25 - 0:40	0:15 - 0:30	1:20 - 1:40	0:40 - 1:20	0:20 - 0:40		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:25 - 0:40	0:05 - 0:10	0:30 - 0:40	0:15 - 0:30	0:06 - 0:15					
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:25 - 0:40	0:03 - 0:06	0:20 - 0:25	0:09 - 0:20	0:04 - 0:09					

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 34: TYPE IV HOLDOVER TIMES FOR DOW INC. UCAR ENDURANCE™ EG106

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:05 - 3:10	0:30 - 1:00	2:45 - 3:00	1:20 - 2:45	0:40 - 1:20	1:10 - 2:00	0:50 - 1:15	0:20 - 2:00	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		_
below -3 to -8 °C	100/0	1:50 - 3:20	0:25 - 0:50	2:25 - 3:00	1:10 - 2:25	0:35 - 1:10	0:55 - 1:50	0:45 - 1:10		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	1:50 - 3:20	0:25 - 0:45	2:10 - 2:45	1:05 - 2:10	0:30 - 1:05	0:55 - 1:50 ¹¹	0:45 - 1:10 ¹¹	CALITIO	.N.I.
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:30 - 1:05	0:15 - 0:35	1:45 - 2:15	0:50 - 1:45	0:25 - 0:50			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:30 - 1:05	0:15 - 0:30	1:30 - 1:55	0:40 - 1:30	0:20 - 0:40				
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:30 - 1:05	0:15 - 0:30	1:20 - 1:45	0:40 - 1:20	0:20 - 0:40				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 46 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 35: TYPE IV HOLDOVER TIMES FOR DOW INC. UCAR™ FLIGHTGUARD™ AD-49

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	3:20 - 4:00	0:45 - 1:25	3:00 - 3:00	1:55 - 3:00	1:00 - 1:55	1:25 - 2:00	1:00 - 1:25	0:10 - 1:55	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		_
below -3 to -8 °C	100/0	0:20 - 1:35	0:35 - 1:05	2:55 - 3:00	1:30 - 2:55	0:45 - 1:30	0:25 - 1:25	0:20 - 0:25		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:20 - 1:35	0:30 - 0:55	2:25 - 3:00	1:15 - 2:25	0:40 - 1:15	0:25 - 1:2511	0:20 - 0:2511		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:25 - 0:40	0:01 - 0:06	0:30 - 0:45	0:09 - 0:30	0:02 - 0:09			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:25 - 0:40	0:00 - 0:02	0:10 - 0:20	0:03 - 0:10	0:01 - 0:03				
below -25 to -26 °C (below -13 to -15 °F)	100/0	0:25 - 0:40	0:00 - 0:01	0:07 - 0:10	0:02 - 0:07	0:00 - 0:02				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 36: TYPE IV HOLDOVER TIMES FOR INLAND TECHNOLOGIES ECO-SHIELD®

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:15 - 2:40	0:35 - 1:00	2:25 - 2:50	1:20 - 2:25	0:45 - 1:20	0:40 - 1:30	0:35 - 0:40	0:15 - 1:35	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
,	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		_
below -3 to -8 °C	100/0	1:10 - 2:35	0:30 - 0:55	2:05 - 2:30	1:10 - 2:05	0:40 - 1:10	0:50 - 1:25	0:30 - 0:40		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	1:10 - 2:35	0:25 - 0:50	1:55 - 2:15	1:05 - 1:55	0:35 - 1:05	0:50 - 1:25 ¹¹	0:30 - 0:4011	CALITIO	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:30 - 1:00	0:01 - 0:06	0:30 - 0:45	0:09 - 0:30	0:02 - 0:09			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:30 - 1:00	0:00 - 0:02	0:10 - 0:20	0:03 - 0:10	0:01 - 0:03				
below -25 to -25.5 °C (below -13 to -14 °F)	100/0	0:30 - 1:00	0:00 - 0:01	0:07 - 0:10	0:02 - 0:07	0:00 - 0:02				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 37: TYPE IV HOLDOVER TIMES FOR JSC RCP NORDIX DEFROST ECO 4

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:30 - 2:40	0:30 - 0:55	2:30 - 3:00	1:15 - 2:30	0:35 - 1:15	1:05 - 1:30	0:40 - 1:05	0:15 - 1:10	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(= 1	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	0:55 - 2:35	0:25 - 0:50	2:15 - 2:45	1:05 - 2:15	0:35 - 1:05	0:50 - 1:20	0:35 - 0:50		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:55 - 2:35	0:25 - 0:45	2:05 - 2:35	1:00 - 2:05	0:30 - 1:00	0:50 - 1:2011	0:35 - 0:5011	CALITIO	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:30 - 0:50	0:01 - 0:06	0:30 - 0:45	0:09 - 0:30	0:02 - 0:09			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:30 - 0:50	0:00 - 0:02	0:10 - 0:20	0:03 - 0:10	0:01 - 0:03				
below -25 to -25.5 °C (below -13 to -14 °F)	100/0	0:30 - 0:50	0:00 - 0:01	0:07 - 0:10	0:02 - 0:07	0:00 - 0:02				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 38: TYPE IV HOLDOVER TIMES FOR JSC RCP NORDIX DEFROST NORTH 4

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:10 - 4:00	0:30 - 1:00	2:55 - 3:00	1:25 - 2:55	0:40 - 1:25	1:05 - 2:00	0:30 - 0:50	0:09 - 1:55	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		•
below -3 to -8 °C	100/0	2:40 - 4:00	0:30 - 1:00	2:55 - 3:00	1:25 - 2:55	0:40 - 1:25	1:05 - 2:00	0:40 - 1:00		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	2:40 - 4:00	0:30 - 1:00	2:55 - 3:00	1:25 - 2:55	0:40 - 1:25	1:05 - 2:0011	0:40 - 1:00 ¹¹	OALITIO	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:45 - 1:55	0:07 - 0:20	0:50 - 1:05	0:25 - 0:50	0:10 - 0:25			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:45 - 1:55	0:03 - 0:10	0:40 - 0:55	0:15 - 0:40	0:05 - 0:15				
below -25 to -26 °C (below -13 to -15 °F)	100/0	0:45 - 1:55	0:01 - 0:06	0:25 - 0:35	0:08 - 0:25	0:02 - 0:08				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 46 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 39: TYPE IV HOLDOVER TIMES FOR KILFROST ABC-S PLUS

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:10 - 4:00	0:55 - 1:35	3:00 - 3:00	2:05 - 3:00	1:15 - 2:05	1:50 - 2:00	1:05 - 2:00	0:25 - 2:00	
-3 °C and above (27 °F and above)	75/25	1:25 - 2:40	0:30 - 0:55	2:05 - 2:25	1:15 - 2:05	0:45 - 1:15	1:00 - 1:20	0:30 - 0:50	0:10 - 1:20	
,	50/50	0:30 - 0:55	0:15 - 0:25	1:00 - 1:10	0:30 - 1:00	0:15 - 0:30	0:15 - 0:40	0:15 - 0:20		
below -3 to -8 °C	100/0	0:55 - 3:30	0:50 - 1:25	3:00 - 3:00	1:50 - 3:00	1:05 - 1:50	0:25 - 1:35	0:20 - 0:30		
(below 27 to 18 °F)	75/25	0:45 - 1:50	0:30 - 0:50	1:50 - 2:10	1:05 - 1:50	0:40 - 1:05	0:20 - 1:10	0:15 - 0:25		
below -8 to -14 °C	100/0	0:55 - 3:30	0:45 - 1:15	2:55 - 3:00	1:45 - 2:55	1:00 - 1:45	0:25 - 1:35 ¹¹	0:20 - 0:3011	CALITIO	NI.
(below 18 to 7 °F)	75/25	0:45 - 1:50	0:25 - 0:45	1:45 - 2:00	1:00 - 1:45	0:35 - 1:00	0:20 - 1:10 ¹¹	0:15 - 0:25 ¹¹	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:40 - 1:00	0:01 - 0:06	0:30 - 0:45	0:09 - 0:30	0:02 - 0:09			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:40 - 1:00	0:00 - 0:02	0:10 - 0:20	0:03 - 0:10	0:01 - 0:03				
below -25 to -28 °C (below -13 to -18 °F)	100/0	0:40 - 1:00	0:00 - 0:01	0:07 - 0:10	0:02 - 0:07	0:00 - 0:02				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 40: TYPE IV HOLDOVER TIMES FOR MKS DEVO CHEMICALS COREICEPHOB TYPE IV PG

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:20 - 3:50	0:35 - 1:15	3:00 - 3:00	1:40 - 3:00	0:45 - 1:40	1:25 - 2:00	0:50 - 1:20	0:10 - 1:40	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(== : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		-
below -3 to -8 °C	100/0	0:15 - 0:35	0:25 - 0:55	2:35 - 3:00	1:10 - 2:35	0:35 - 1:10	0:40 - 1:30	0:20 - 0:35		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:15 - 0:35	0:20 - 0:45	2:05 - 2:40	0:55 - 2:05	0:25 - 0:55	0:40 - 1:3011	0:20 - 0:3511	0.441710	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:15 - 0:30	0:01 - 0:06	0:30 - 0:45	0:09 - 0:30	0:02 - 0:09			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:15 - 0:30	0:00 - 0:02	0:10 - 0:20	0:03 - 0:10	0:01 - 0:03				
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:15 - 0:30	0:00 - 0:01	0:07 - 0:10	0:02 - 0:07	0:00 - 0:02				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 41: TYPE IV HOLDOVER TIMES FOR NEWAVE AEROCHEMICAL FCY 9311

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:55 - 4:00	0:25 - 0:55	2:20 - 2:55	1:10 - 2:20	0:35 - 1:10	1:10 - 2:00	0:40 - 1:05	0:15 - 1:25	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	0:35 - 2:05	0:20 - 0:40	1:50 - 2:20	0:55 - 1:50	0:30 - 0:55	0:35 - 1:20	0:20 - 0:35		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:35 - 2:05	0:20 - 0:35	1:35 - 2:00	0:50 - 1:35	0:25 - 0:50	0:35 - 1:2011	0:20 - 0:3511	CALITIO	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:30 - 0:55	0:10 - 0:20	1:00 - 1:15	0:30 - 1:00	0:15 - 0:30			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:30 - 0:55	0:05 - 0:10	0:35 - 0:40	0:15 - 0:35	0:07 - 0:15				
below -25 to -29.5 °C (below -13 to -21 °F)	100/0	0:30 - 0:55	0:05 - 0:10	0:30 - 0:40	0:15 - 0:30	0:06 - 0:15				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 42: TYPE IV HOLDOVER TIMES FOR NEWAVE AEROCHEMICAL FCY-EGIV

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:35 - 4:00	0:25 - 0:55	2:35 - 3:00	1:10 - 2:35	0:35 - 1:10	1:20 - 2:00	0:40 - 1:05	0:15 - 2:00	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		•
below -3 to -8 °C	100/0	1:25 - 3:25	0:20 - 0:45	2:10 - 2:45	1:00 - 2:10	0:25 - 1:00	0:50 - 2:00	0:45 - 1:05		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	1:25 - 3:25	0:20 - 0:40	1:55 - 2:25	0:50 - 1:55	0:25 - 0:50	0:50 - 2:0011	0:45 - 1:05 ¹¹	CALITIO	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:35 - 1:55	0:15 - 0:30	1:35 - 2:05	0:40 - 1:35	0:15 - 0:40			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:35 - 1:55	0:09 - 0:20	1:10 - 1:35	0:30 - 1:10	0:15 - 0:30				
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:35 - 1:55	0:08 - 0:20	1:00 - 1:20	0:25 - 1:00	0:10 - 0:25				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 46 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE 43: TYPE IV HOLDOVER TIMES FOR SHAANXI CLEANWAY CLEANSURFACE IV

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:30 - 4:00	0:30 - 1:15	3:00 - 3:00	1:40 - 3:00	0:40 - 1:40	1:20 - 2:00	0:40 - 1:10	0:15 - 1:50	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(=: : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		•
below -3 to -8 °C	100/0	0:55 - 2:05	0:20 - 0:45	2:25 - 3:00	1:00 - 2:25	0:25 - 1:00	0:30 - 1:30	0:25 - 0:35		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:55 - 2:05	0:15 - 0:35	1:45 - 2:15	0:45 - 1:45	0:20 - 0:45	0:30 - 1:3011	0:25 - 0:3511	0.44174.0	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:25 - 0:35	0:10 - 0:20	1:05 - 1:20	0:30 - 1:05	0:15 - 0:30			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:25 - 0:35	0:05 - 0:10	0:35 - 0:45	0:15 - 0:35	0:07 - 0:15				
below -25 to -30 °C (below -13 to -22 °F)	100/0	0:20 - 0:30	0:04 - 0:09	0:30 - 0:35	0:15 - 0:30	0:06 - 0:15				

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm that the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm that the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table 47 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

ALLOWANCE TIMES TABLES FOR WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

CAUTIONS

- The responsibility for the application of these data remains with the user.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.
- Allowance time cannot be extended by an inspection of the aircraft critical surfaces.

TABLE 44: LIST OF FLUIDS VALIDATED FOR USE WITH ALLOWANCE TIMES1

Manufacturer	Fluid Name	Applicable Allowance Times (ATs)
	Type III Fluids	
AllClear Systems LLC	AeroClear MAX	ATs for Type III Fluids
	Type IV EG Fluids	
ALAB International	PROFLIGHT EG4	ATs for Type IV EG Fluids ³
AllClear Systems LLC	ClearWing EG	ATs for Type IV EG Fluids
ASGlobal	4Flite EG	Fluid has not been validated ²
AVIAFLUID International Ltd	AVIAFlight EG	ATs for Type IV EG Fluids
CHEMCO Inc.	ChemR EG IV	ATs for Type IV EG Fluids
CHEMCO Inc.	ChemR Nordik IV	ATs for Type IV EG Fluids
CHONGQING JOBA CHEMICAL CO,.LTD	FW-IV	ATs for Type IV EG Fluids ³
Dow Inc	UCAR ENDURANCE™ EG106 ADF/AAF	ATs for Type IV EG Fluids
JSC RCP Nordix	Defrost NORTH 4	ATs for Type IV EG Fluids
Newave Aerochemical Co. Ltd.	FCY-EGIV	ATs for Type IV EG Fluids
	Type IV PG Fluids	
ABAX Industries	ECOWING AD-49	ATs for Type IV PG Fluids
ALAB International	PROFLIGHT PG4	ATs for Type IV PG Fluids ³
ASGlobal	4Flite PG	ATs for Type IV PG Fluids
AVIAFLUID International Ltd	AVIAFlight PG	ATs for Type IV PG Fluids
Clariant Produkte (Deutschland) GmbH	Safewing MP IV LAUNCH	ATs for Type IV PG Fluids
Clariant Produkte (Deutschland) GmbH	Safewing MP IV LAUNCH PLUS	ATs for Type IV PG Fluids
Cryotech Deicing Technology	Polar Guard® Advance	ATs for Type IV PG Fluids
Cryotech Deicing Technology	Polar Guard® Xtend	ATs for Type IV PG Fluids
Dow Chemical Company	UCAR™ FLIGHTGUARD™ AD-49	ATs for Type IV PG Fluids
Inland Technologies Inc.	ECO-SHIELD®	ATs for Type IV PG Fluids
JSC RCP Nordix	Defrost ECO 4	ATs for Type IV PG Fluids
Kilfrost Limited	ABC-S Plus	ATs for Type IV PG Fluids
MKS DevO Chemicals	COREICEPHOB TYPE-IV PG	ATs for Type IV PG Fluids ³
Newave Aerochemical Co. Ltd.	FCY 9311	ATs for Type IV PG Fluids
Shaanxi Cleanway Aviation Chemical Co., Ltd.	Cleansurface IV	ATs for Type IV PG Fluids ³

- 1. Allowance times are for use with undiluted (100/0) Type III, Type IV EG, and Type IV PG fluids only. No allowance times exist for Type II fluids.
- 2. No allowance times exist for this fluid at the time of publication as the allowance times have not yet been validated.
- 3. Fluid is new to market and in the process of commercialization. The applicable allowance times can be used for a limited grace period of two testing opportunities that is made available to the manufacturer. The fluid must be validated within this time frame to continue the use of the allowance times.

TABLE 45: ALLOWANCE TIMES FOR SAE TYPE III FLUIDS^{1,2}

		Outside Air	Temperature	
Precipitation Types or Combinations and Applicable METAR Codes ⁴	Above 0 °C (32 °F and above)	0 to -5 °C (32 to 23 °F)	Below -5 to -10 °C (Below 23 to 14 °F)	Below -10 °C³ (Below 14 °F)
Light Ice Pellets -PL -GS	10 minutes	10 minutes	10 minutes	
Light Ice Pellets Mixed with Light Snow -PLSN, -SNPL, -GSSN, -SNGS	10 minutes	10 minutes	10 minutes	
Light Ice Pellets Mixed with Light or Moderate Freezing Drizzle -PLFZDZ, -FZDZPL, FZDZPL, -GSFZDZ, -FZDZGS, FZDZGS		7 minutes	5 minutes	Caution:
Light Ice Pellets Mixed with Light or Moderate Drizzle -PLDZ, -DZPL, DZPL, -GSDZ, -DZGS, DZGS	7 minutes			No allowance times currently exist
Light Ice Pellets Mixed with Light Freezing Rain -PLFZRA, -FZRAPL, -GSFZRA, -FZRAGS		7 minutes	5 minutes	
Light Ice Pellets Mixed with Light Rain -PLRA, -RAPL, -GSRA, -RAGS	7 minutes			
Moderate Ice Pellets (or Small Hail) PL, GS	5 minutes	5 minutes	5 minutes	

NOTES

- 1 These allowance times are for use with undiluted (100/0) fluids applied unheated on aircraft with rotation speeds of 100 knots or greater. To use the allowance times in this table, ensure the fluid being used is listed in the List of Fluids Validated for the Use of Allowance Times Table (Table 44).
- 2 Takeoff is allowed up to 90 minutes after start of fluid application if the precipitation stops at or before the allowance time expires and does not restart. Take is not permitted if the OAT decreases during the 90 minutes in conditions of light ice pellets mixed with either: light freezing drizzle, moderate freezing drizzle, light freezing rain, or light rain.
- 3 Ensure that the lowest operational use temperature (LOUT) is respected.
- 4 In the US, small hail is reported as GR with the remark "GR LESS THAN ¼". Outside of the US small hail is reported as GS. If the METAR does not report an intensity for small hail, use the "moderate ice pellets or small hail" allowance times. If the METAR reports an intensity with small hail, the condition with the equivalent intensity can be used. This also applies in mixed conditions.

CAUTIONS

TABLE 46: ALLOWANCE TIMES FOR SAE TYPE IV ETHYLENE GLYCOL (EG) FLUIDS^{1,2}

		Outsi	de Air Temperat	ure	
Precipitation Types or Combinations and Applicable METAR Codes ⁵	Above 0 °C³ (32 °F and above)	0 to -5 °C ³ (32 to 23 °F)	Below -5 to -10 °C ³ (Below 23 to 14 °F)	Below -10 to -16 °C ³ (Below 14 to 3 °F)	Below -16 to -22 °C ^{3,4} (Below 3 to -8 °F)
Light Ice Pellets -PL, -GS	70 minutes	70 minutes	70 minutes	50 minutes	30 minutes
Light Ice Pellets Mixed with Light Snow -PLSN, -SNPL, -GSSN, -SNGS	50 minutes	50 minutes	30 minutes	25 minutes	
Light Ice Pellets Mixed with Light or Moderate Freezing Drizzle -PLFZDZ, -FZDZPL, FZDZPL, -GSFZDZ, -FZDZGS, FZDZGS		40 minutes	30 minutes		
Light Ice Pellets Mixed with Light or Moderate Drizzle -PLDZ, -DZPL, DZPL, -GSDZ, -DZGS, DZGS	40 minutes			Cau No allowa	tion:
Light Ice Pellets Mixed with Light Freezing Rain -PLFZRA, -FZRAPL, -GSFZRA, -FZRAGS		40 minutes	30 minutes		ly exist
Light Ice Pellets Mixed with Light Rain -PLRA, -RAPL, -GSRA, -RAGS	40 minutes				
Light Ice Pellets Mixed with Light Rain and Light Snow -PLRASN, -PLSNRA, -RAPLSN, -RASNPL, -SNPLRA, -SNRAPL, -GSRASN, -GSSNRA, -RAGSSN, -RASNGS, -SNGSRA, -SNRAGS	20 minutes				
Light Ice Pellets Mixed with Light Freezing Rain and Light Snow -PLFZRASN, -PLSNFZRA, -FZRAPLSN, -FZRASNPL, -SNPLFZRA, -SNFZRAPL, -GSFZRASN, -GSSNFZRA, -FZRAGSSN, -FZRASNGS, -SNGSFZRA, -SNFZRAGS		20 minutes			
Moderate Ice Pellets (or Small Hail) PL, GS	35 minutes	35 minutes	35 minutes	15 minutes	10 minutes
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Snow PLSN, SNPL, GSSN, SNGS	25 minutes	15 minutes	10 minutes		
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Freezing Drizzle PLFZDZ, GSFZDZ		20 minutes	10 minutes		
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Drizzle PLDZ, GSDZ	20 minutes		Cautio		
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Rain PLRA, GSRA, RAPL, RAGS	15 minutes		exist		

NOTES

• The notes that apply to the allowance times in the table above can be found on page 61.

CAUTIONS

TABLE 46 (CONT'D): ALLOWANCE TIMES FOR SAE TYPE IV ETHYLENE GLYCOL (EG) FLUIDS

NOTES

- 1 These allowance times are for use with undiluted (100/0) EG based fluids. If the glycol type is unknown, the allowance times for SAE Type IV PG fluids should be used. To use the allowance times in this table, ensure the fluid being used is listed in the List of Fluids Validated for the Use of Allowance Times Table (Table 44).
- 2 Takeoff is allowed up to 90 minutes after start of fluid application if the precipitation stops at or before the allowance time expires and does not restart. Takeoff is not permitted if the OAT decreases during the 90 minutes in conditions of light ice pellets mixed with either: light or moderate freezing drizzle, light or moderate drizzle, light freezing rain, light rain, light rain and light snow, or light freezing rain and light snow.
- 3 No allowance times exist for EG based fluids when used on aircraft with rotation speeds less than 100 knots.
- 4 Ensure that the lowest operational use temperature (LOUT) is respected.
- 5 In the US, small hail is reported as GR with the remark "GR LESS THAN ¼". Outside of the US small hail is reported as GS. If the METAR does not report an intensity for small hail, use the "moderate ice pellets or small hail" allowance times. If the METAR reports an intensity with small hail, the ice pellet condition with the equivalent intensity can be used. This also applies in mixed conditions.

TABLE 47: ALLOWANCE TIMES FOR SAE TYPE IV PROPYLENE GLYCOL (PG) FLUIDS^{1,2}

		Out	side Air Temper	ature			
Precipitation Types or Combinations and Applicable METAR Codes ⁶	Above 0 °C ³ (32 °F and above)	0 to -5 °C ³ (32 to 23 °F)	Below -5 to -10 °C ³ (Below 23 to 14 °F)	Below -10 to -16 °C ⁴ (Below 14 to 3 °F)	Below -16 to -22 °C ^{4,5} (Below 3 to -8 °F)		
Light Ice Pellets -PL, -GS	50 minutes	50 minutes	30 minutes	30 minutes	20 minutes		
Light Ice Pellets Mixed with Light Snow -PLSN, -SNPL, -GSSN, -SNGS	40 minutes	40 minutes	15 minutes	15 minutes			
Light Ice Pellets Mixed with Light or Moderate Freezing Drizzle -PLFZDZ, -FZDZPL, FZDZPL, -GSFZDZ -FZDZGS, FZDZGS		25 minutes	10 minutes				
Light Ice Pellets Mixed with Light or Moderate Drizzle -PLDZ, -DZPL, DZPL, -GSDZ, -DZGS, DZGS	25 minutes						
Light Ice Pellets Mixed with Light Freezing Rain -PLFZRA, -FZRAPL, -GSFZRA, -FZRAGS		25 minutes	10 minutes	No allowa	tion: ince times ily exist		
Light Ice Pellets Mixed with Light Rain -PLRA, -RAPL, -GSRA, -RAGS	25 minutes						
Light Ice Pellets Mixed with Light Rain and Light Snow -PLRASN, -PLSNRA, -RAPLSN, -RASNPL, -SNPLRA, -SNRAPL, -GSRASN, -GSSNRA, -RAGSSN, -RASNGS, -SNGSRA, -SNRAGS	20 minutes						
Light Ice Pellets Mixed with Light Freezing Rain and Light Snow -PLFZRASN, -PLSNFZRA, -FZRAPLSN, -FZRASNPL, -SNPLFZRA, -SNFZRAPL, -GSFZRASN, -GSSNFZRA, -FZRAGSSN, -FZRASNGS, -SNGSFZRA, -SNFZRAGS		20 minutes					
Moderate Ice Pellets (or Small Hail) PL, GS	15 minutes	15 minutes	10 minutes	10 minutes			
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Snow PLSN, SNPL, GSSN, SNGS	15 minutes	5 minutes	5 minutes				
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Freezing Drizzle PLFZDZ, GSFZDZ		10 minutes	7 minutes				
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Drizzle PLDZ, GSDZ	10 minutes	Caution:					
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Rain PLRA, GSRA, RAPL, RAGS	10 minutes	No allowance times currently exist					

NOTES

• The notes that apply to the allowance times in the table above can be found on page 63.

CAUTIONS

TABLE 47 (CONT'D): ALLOWANCE TIMES FOR SAE TYPE IV PROPYLENE GLYCOL (PG) FLUIDS

NOTES

- 1 These allowance times are for use with undiluted (100/0) PG based fluids applied on aircraft with rotation speeds of 100 knots or greater. If the glycol type is unknown, the allowance times for SAE Type IV PG fluids should be used. To use the allowance times in this table, ensure the fluid being used is listed in the List of Fluids Validated for the Use of Allowance Times Table (Table 44).
- 2 Takeoff is allowed up to 90 minutes after start of fluid application if the precipitation stops at or before the allowance time expires and does not restart. Takeoff is not permitted if the OAT decreases during the 90 minutes in conditions of light ice pellets mixed with either: light or moderate freezing drizzle, light or moderate drizzle, light freezing rain, light rain, light rain and light snow, or light freezing rain and light snow..
- 3 No allowance times exist for PG based fluids when used on aircraft with rotation speeds less than 100 knots.
- 4 No allowance times exist for PG based fluids when used on aircraft with rotation speeds less than 115 knots.
- 5 Ensure that the lowest operational use temperature (LOUT) is respected.
- 6 In the US, small hail is reported as GR with the remark "GR LESS THAN ¼". Outside of the US, small hail is reported as GS. If the METAR does not report an intensity for small hail, use the "moderate ice pellets or small hail" allowance times. If the METAR reports an intensity with small hail, the ice pellet condition with the equivalent intensity can be used. This also applies in mixed conditions.

SUPPLEMENTAL GUIDANCE FOR WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

TABLE 48: SNOWFALL INTENSITIES AS A FUNCTION OF PREVAILING VISIBILITY

	Visil	bility		Da	ay	Nig	ght
Statu	ıte Miles		Meters	-1°C and below 30 °F and below	Above -1°C Above 30 °F	-1°C and Below 30 °F and below	Above -1°C Above 30 °F
≤1/4 (≤3/8	3)	≤400 (≤600)		Heavy	Heavy	Heavy	Heavy
1/2 (>3/8	3 to ≤5/8)	800 (>600 to ≤1000)		Moderate	Heavy	Heavy	Heavy
3/4 (>5/8	3 to ≤7/8)	1200	(>1000 to ≤1400)	Moderate	Moderate	Moderate	Heavy
1 (>7/8	3 to ≤1 1/8)	1600	(>1400 to ≤1800)	Light	Light	Moderate	Moderate
1 1/4 (>1 1	1/8 to ≤1 3/8)	2000 (>1800 to ≤2200)		(>1800 to ≤2200) Light Lig		Moderate	Moderate
1 ½ (>1 3	3/8 to ≤1 5/8)	2400	(>2200 to ≤2600)	Light	Light	Moderate	Moderate
1 ¾ (>1 5	5/8 to ≤1 7/8)	2800	(>2600 to ≤3000)	Very Light	Light	Light	Light
2 (>1 7	7/8 to ≤2 ½)	3200	(>3000 to ≤3600)	Very Light	Very Light	Light	Light
2 ½ (>2 ½	⁄₄ to ≤2 ¾)	4000	(>3600 to ≤4400)	Very Light	Very Light	Very Light	Very Light
3 (>2 ³ /	¼ to ≤3 ¼)	4800	(>4400 to ≤5200)	Very Light	Very Light	Very Light	Very Light
≥ 3 ½ (>3 ½	/4)	≥5600	(>5200)	Very Light	Very Light	Very Light	Very Light

- The METAR/SPECI reported visibility or flight crew observed visibility will be used with this visibility table to establish snowfall intensity for Type I, II, III and IV holdover time guidelines, during snow, snow grain, or snow pellet precipitation conditions. This visibility table will also be used when snow, snow grains, or snow pellets are accompanied by blowing or drifting snow, or when snow is mixed with ice crystals or freezing fog in the METAR/SPECI.
- The use of Runway Visual Range (RVR) is not permitted for determining visibility used with the holdover tables.
- Some METARs contain tower visibility as well as surface visibility. Whenever surface visibility is available from an official source, such as a METAR, in either the main body of the METAR or in the Remarks ("RMK") section, the preferred action is to use the surface visibility value.
- If the visibility is being reduced by snow along with form(s) of obscuration such as fog, haze, smoke, etc., use of the table above may overestimate the actual snowfall intensity. However, use of the snowfall intensity being reported by the weather observer or automated surface observing system (ASOS), from the FMH-1 Table, may underestimate the actual snowfall intensity as it does not directly correlate to the snowfall intensities used when determining holdover times. Use of the visibility table in all snow conditions with or without obscurations is recommended.

Example for how to read and use the table: CYVO 160200Z 15011G17KT 1SM -SN DRSN OVC009 M06/M08 A2948

In the above METAR the snowfall intensity is reported as light. However, based upon the "Snowfall Intensities as a Function of Prevailing Visibility" table, with a visibility of 1 statute mile, at night and a temperature of -6°C, the snowfall intensity is classified as moderate. The snowfall intensity of moderate - not the METAR reported intensity of light - will be used to determine which holdover time guideline value is appropriate for the fluid in use.

TABLE 49:

TYPE I FLUIDS TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE (see cautions and notes on pages 77 and 78)

	Tune			Low	est Operation	nal Use Tem	perature ³		
Fluid Name	Type of Glycol ¹	Expiry ² (y-m-d)	Dilution ^{4,5}		speed amic test ⁶	middle aerodyna	speed mic test ⁶	high s aerodyna	
	0.,00.		(fluid/water)	°C	°F	°C	°F	°C	°F
ABAX Industries						•			
DE-950	PG	26-06-01	71/29	-26	-15	Not te	sted ¹¹	-31	-24
ADDCON EUROPE GmbH ¹⁰									
IceFree I.80	PG	21-03-14 ⁹	70/30	-26	-15	Not te	sted ¹¹	-32	-26
Aéro Mag 2000									
DeiceX PG ADF Concentrate (Multiple Location)	PG	Y-M-D ¹²	65/35	-25	-13	Not te	sted11	-31.5	-25
ALAB Industries ¹⁰									
WDF 1	EG	22-03-02 ⁹	70/30	-40	-40	Not tested ¹¹		-45	-49
ALAB International						•			
PROFLIGHT EG1	EG	25-06-01	70/30	-43.5	-46	Not tested ¹¹		-44	-47
AllClear Systems LLC	<u> </u>			<u> </u>		'			
Lift-Off E-188	EG	26-06-01	70/30	-40	-40	Not te	sted ¹¹	-41.5	-43
Lift-Off P-88	PG	26-06-01	70/30	-24.5	-12	Not te	sted ¹¹	-29.5	-21
Arcton Ltd. ¹⁰						•			
Arctica DG ready-to-use	DEG	22-03-26 ⁹	as supplied	-26	-15	Not te	sted ¹¹	-26	-15
ASGlobal						•			
Sky-Go EG	EG	26-09-23	70/30	-31 ¹⁴	-24 ¹⁴	Not te	sted ¹¹	-44	-47
Sky-Go PG	PG	26-07-27	70/30	-21.5 ¹⁴	-7 ¹⁴	Not te	sted ¹¹	-30.5	-23
Sky-Go PG 80	PG	27-08-07	70/30	-25 ¹⁴	-13 ¹⁴	Not te	sted ¹¹	-31.5	-25
AVIAFLUID International Ltd	•			•		•			
AVIAFLO EG	EG	21-06-19 ⁹	70/30	-40.5	-41	Not te	sted ¹¹	-44	-47
AVIAFLO PG	PG	22-02-10 ⁹	70/30	Not to	ested ¹¹	Not te	sted ¹¹	-30	-22
Aviation Xi'an High-Tech Physical Chemical Co. Ltd.									
Cleanwing I	PG	27-06-08	75/25	Not to	ested ¹¹	Not te	sted ¹¹	-39.5	-39
Cleanwing E	EG	22-07-09 ¹³	75/25	-37	-35	Not te	sted ¹¹	-37	-35
Cleanwing S-92	EG	22-06-03 ¹³	75/25	-35	-31	Not te	sted ¹¹	-40	-40
KHF-1	PG	27-06-08	75/25	Not to	ested ¹¹	Not te	sted ¹¹	-38.5	-37

TABLE 49 (CONT'D): TYPE I FLUIDS TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE

	Typo			Lov	vest Operatio	nal Use Temperature ³		
Fluid Name	Type of Glycol ¹	Expiry ² (y-m-d)	Dilution ^{4,5}		speed amic test ⁶	middle speed aerodynamic test ⁶	high s	speed mic test ⁶
	Ciyooi		(fluid/water)	°C	°F	°C °F	°C	°F
Beijing Wangye Aviation Chemical Product Co Ltd. ¹⁰				<u> </u>			•	
KLA-1A	EG	22-05-22 ⁹	60/40	Not to	ested ¹¹	Not tested ¹¹	-32	-26
Beijing Yadilite Aviation Advanced Materials Corpora	ntion ¹⁰							
YD-101 Type I	PG	21-03-07 ⁹	60/40	Not to	ested ¹¹	Not tested ¹¹	-30	-22
YD-101A Type I	EG	25-02-26	70/30	Not to	ested ¹¹	Not tested ¹¹	-38	-36
CHEMCO Inc.							•	
CHEMR EG I	EG	28-06-01	70/30	-37	-35	Not tested ¹¹	-43	-45
CHEMR REG I	EG	26-06-01	75/25	-36.5	-34	Not tested ¹¹	-43.5	-46
Chongqing Joba Chemical Co., Ltd								
FW-I	EG	25-11-07	75/25	-43	-45	Not tested ¹¹	-46	-51
Clariant Produkte (Deutschland) GmbH								
Octaflo EF Concentrate	PG	22-03-28 ⁹	65/35	-25	-13	Not tested ¹¹	-33	-27
Safewing MP I 1938 ECO (80)	PG	24-06-23 ⁹	71/29	-25	-13	Not tested ¹¹	-32.5	-27
Safewing MP I ECO PLUS (80)	PG	27-06-01	71/29	-25	-13	Not tested ¹¹	-33	-27
Safewing MP I LFD 80	PG	25-04-15	71/29	-26	-15	Not tested ¹¹	-33	-27
Safewing MP I LFD 80 Pre-Mix 55%	PG	27-06-01	as supplied	Not to	ested ¹¹	Not tested ¹¹	-17	1
Safewing MP I LFD 88	PG	27-06-01	65/35	-26	-15	Not tested ¹¹	-33	-27
Safewing MP I LFD PLUS 88	PG	26-06-01	65/35	-25	-13	Not tested ¹¹	-34	-29
Cryotech Deicing Technology							•	
Polar Plus® LT	PG	28-06-01	63/37	-27	-17	Not tested ¹¹	-33	-27
Polar Plus® LT (80)	PG	28-06-01	70/30	-27	-17	Not tested ¹¹	-33	-27
Dow Inc.								
UCAR™ ADF Concentrate	EG	27-06-01	75/25	-36	-33	Not tested ¹¹	-45	-49
UCAR™ ADF XL54 ¹⁵	EG	27-06-01	as supplied	-33	-27	Not tested ¹¹	-33	-27
UCAR™ PG ADF Concentrate	PG	27-06-01	65/35	-25	-13	Not tested ¹¹	-32	-26
UCAR™ PG ADF Dilute 55/45 ¹⁶	PG	27-06-01	as supplied	-24	-11	Not tested ¹¹	-25	-13

TABLE 49 (CONT'D): TYPE I FLUIDS TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE

	Туре			Low	vest Operation	onal Use Te	mperature ³		
Fluid Name	of Glycol ¹	of (y-m-d) Dil		low s aerodyna	-	middle speed aerodynamic test ⁶		high s aerodyna	
			(fluid/water)	°C	°F	°C	°F	°C	°F
Heilongjiang Hangjie Aero-chemical Technology Co	o. Ltd. ¹⁰								
HJF-1	EG	21-06-14 ⁹	65/35	Not tested11		Not t	ested ¹¹	-42	-44
HOC Industries									
SafeTemp® ES Plus	PG	24-06-30 ¹³	65/35	-25.5	-14	Not t	ested ¹¹	-29	-20
Inland Technologies Inc.									
DuraGly-E Type I ADF Concentrate	EG	23-02-08 ¹³	60/40	-33	-27	Not t	ested ¹¹	-33	-27
Inland ADF Concentrate (Multiple Location)	EG	Y-M-D ¹⁷	75/25	-36	-33	Not tested ¹¹		-42.5	-45
SafeTemp® ES Plus (Multiple Location)	PG	Y-M-D ¹⁸	65/35	-25.5	-14	Not tested ¹¹		-31	-24
JSC RCP Nordix									
DEFROST EG 88.1	EG	25-04-13	70/30	-40.5	-41	Not t	ested ¹¹	-44.5	-48
DEFROST PG 1	PG	23-11-21 ⁹	70/30	-24.5	-12	Not t	ested ¹¹	-31.5	-25
Kilfrost Limited									•
Kilfrost DF Plus	PG	27-06-01	69/31	-25.5	-14	Not t	ested ¹¹	-32	-26
Kilfrost DF Plus (80)	PG	24-07-14 ⁹	69/31	-26	-15	Not t	ested ¹¹	-31.5	-25
Kilfrost DF Plus (88)	PG	23-06-05 ⁹	63/37	-25.5	-14	Not t	ested ¹¹	-32	-26
Kilfrost Ice Clear I	PG	27-06-01	70/30	-26	-15	Not t	ested ¹¹	-33	-27
LNT Solutions ¹⁰									
LNT E188	EG	25-08-13	70/30	-30.5	-23	Not t	ested ¹¹	-41	-42
LNT P180	PG	26-11-10	69/31	-26	-15	Not t	ested ¹¹	-32	-26
MKS DevO Chemicals									•
COREICEPHOB TYPE I	PG	26-06-01	71/29	Not te	sted ¹¹	Not t	ested ¹¹	-32.5	-27
Newave Aerochemical Co. Ltd.									
FCY-1A	EG	27-06-01	75/25	-4 0 ¹⁴	-40 ¹⁴	Not t	ested ¹¹	-40	-40
FCY-1Bio+	EG	25-06-22	75/25	-40.5	-41	Not to	ested ¹¹	-40.5	-41
FCY-1Bio+ (R)	EG	25-12-01	75/25	Not te	sted ¹¹	Not to	ested ¹¹	-46	-51

TABLE 49 (CONT'D): TYPE I FLUIDS TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE

	Туре			Lov	vest Operati	onal Use Te	mperature ³		
Fluid Name	of Glycol ¹	Expiry ² (y-m-d)	(y-m-d) Dilution ^{4,5}		peed mic test ⁶		e speed amic test ⁶	high speed aerodynamic test ⁶	
	0.,00.		(fluid/water)	°C	°F	°C	°F	°C	°F
ROMCHIM PROTECT SRL		•						•	
ADD-PROTECT NG Type I	EG	26-06-01	60/40	-22	-8	Not to	Not tested ¹¹		-8
ADD-PROTECT Type I	PG	27-06-01	70/30	-25.5	-14	Not to	ested ¹¹	-31	-24
Shaanxi Cleanway Aviation Chemical Co., Ltd				'					
Cleansurface I	EG	25-06-07	75/25	Not te	ested ¹¹	Not to	ested ¹¹	-40.5	-41
Cleansurface I-BIO	EG	22-05-02 ⁹	75/25	Not te	ested ¹¹	Not tested ¹¹		-37	-35
Topan LLP ¹⁰									
TOPAN TYPE I	EG	24-07-13 ⁹	75/25	-35.5	-32	Not to	ested ¹¹	-42	-44
Xinjiang Zhongtian Liyang Aviation Newmaterial Te	chnology C	o., Ltd. ¹⁰							
Clearice-I	EG	23-10-24 ⁹	60/40	Not te	Not tested ¹¹ Not tested ¹¹		-30	-22	
Clearice-IB	EG	24-08-04 ⁹	75/25	Not te	ested ¹¹	Not to	ested ¹¹	-43.5	-46

TABLE 50:
TYPE II FLUIDS TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE

				Lowe	st Operation	al Use Tempe	erature ³		AS 9968 Visc	osity ⁷ (mPa.s)	
	Type of	Expiry ²	Dilution	middle	speed	high	speed	Lowest On-V	Ving Viscosity ⁸	Highest On-V	Ving Viscosity ⁸
Fluid Name	Glycol ¹	(y-m-d)	(fluid/water)	aerodynamic test ⁶		_	namic test ⁶	Manufacturer Method	Alternate Method	Manufacturer Method	Alternate Method
				°C	°F	°C	°F	Metriou	Wethod	Metriod	Wethou
ABAX Industries											
			100/0	Not to	ested ¹¹	-27	-17	5 750 (a)	Not Available ¹⁹	17 200 (a)	14 000 (h)
ECOWING AD-2	PG	25-06-01	75/25	Not to	ested ¹¹	-15	5	12 000 (c)	Not Available ¹⁹	30 200 (c)	32 000 (h)
			50/50 ⁹	Not tested ¹¹		-3	27	7 500 (a)	Not Available ¹⁹	26 900 (c)	36 800 (h)
Aviation Xi'an High-Ted	ch Physic	cal Chemica	I Co. Ltd.								
			100/0	Not to	ested ¹¹	-25	-13	4 650 (e)	4 500 (a)	13 500 (a)	11 100 (i)
Cleanwing II	PG	25-07-06	75/25	Not to	ested ¹¹	-15	5	9 450 (e)	10 000 (a)	14 600 (i)	Not Available ¹⁹
			50/50	Not to	ested ¹¹	-4.5	24	10 150 (e)	10 200 (a)	12 900 (i)	Not Available ¹⁹
Clariant Produkte (Deu	tschland) GmbH									
			100/0	Not to	ested ¹¹	-29	-20	3 340 (a)	Not Available ¹⁹	20 500 (q)	20 500 (c)
Safewing MP II FLIGHT	PG	26-06-01	75/25	Not to	ested ¹¹	-14	7	12 900 (c)	Not Available ¹⁹	47 800 (q)	47 800 (c)
			50/50	Not to	ested ¹¹	-3.5	26	11 500 (a)	Not Available ¹⁹	63 000 (q)	63 000 (c)
Cryotech Deicing Tech	nology										
			100/0	Not to	ested ¹¹	-30.5	-23	4 400 (f)	4 050 (a)	17 000 (f)	16 200 (a)
Polar Guard® II	PG	25-06-01	75/25	Not to	ested ¹¹	-14	7	11 600 (f)	9 750 (a)	38 000 (c)	Not Available ¹⁹
			50/50	Not to	ested ¹¹	-3.5	26	80 (a) Not Available ¹⁹		48 000 (c)	Not Available ¹⁹
Kilfrost Limited											
			100/0	Not to	ested ¹¹	-29	-20	2 850 (e)	2 640 (a)	13 400 (a)	Not Available ¹⁹
ABC-K Plus	PG	25-06-01	75/25	Not to	ested ¹¹	-14.5	6	12 650 (e)	12 650 (c)	29 000 (c)	Not Available ¹⁹
			50/50	Not to	ested ¹¹	-3.5	26	4 200 (e)	5 260 (a)	15 000 (a)	Not Available ¹⁹
			100/0	Not to	ested ¹¹	-28	-18	4 100 (a)	18 000 (m)	26 000 (c)	Not Available ¹⁹
Ice Clear II	PG	26-06-01	75/25		Dilution No	ot Applicable			Dilution No	t Applicable	
			50/50		Dilution No	ot Applicable			Dilution No	t Applicable	
MKS DevO Chemicals											
COREICEPHOB			100/0	Not te		-27	-17	34 400 (i)	Not Available ¹⁹	50 200 (i)	Not Available ¹⁹
Type II	PG	26-06-01	75/25			t Applicable			Dilution Not		
.754			50/50	Not te	sted ¹¹	-3.5	26	20 700 (i)	Not Available ¹⁹	30 700 (i)	Not Available ¹⁹

TABLE 50 (CONT'D): TYPE II FLUIDS TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE

				Lowe	st Operationa	al Use Tempe	rature ³		AS 9968 Visc	osity ⁷ (mPa.s)	
	Type of Glycol ¹	Fyniry ²	xpiry ² Dilution /-m-d) (fluid/water)	middle	n annod	high	speed	Lowest On-W	ing Viscosity ⁸	Highest On-Wing Viscosity ⁸	
Fluid Name		(y-m-d)		middle speed aerodynamic test ⁶			amic test ⁶	Manufacturer Method	Alternate Method	Manufacturer	Alternate
				°C	°F	°C	°F	wethod	Wethod	Method	Method
Newave Aerochemical	Co. Ltd.						•				
			100/0	Not to	ested ¹¹	-28	-18	7 000 (e)	8 920 (a)	24 800 (c)	Not Available ¹⁹
FCY-2	PG	25-07-13	75/25	Not tested ¹¹		-14.5	6	18 550 (e)	18 550 (c)	31 300 (i)	Not Available ¹⁹
			50/50	Not to	ested ¹¹	-4.5	24	6 750 (e)	7 030 (a)	15 200 (i)	Not Available ¹⁹
ROMCHIM PROTECT S	SRL						•				
ADD DDOTECT			100/0	Not to	ested ¹¹	-28	-18	5 200 (a)	Not Available ¹⁹	12 400 (a)	Not Available ¹⁹
ADD-PROTECT NG Type II	PG	25-06-01	75/25	Not to	ested ¹¹	-14.5	6	8 250 (a)	Not Available ¹⁹	43 800 (i)	Not Available ¹⁹
ПО Туре п			50/50	Not to	ested ¹¹	-3	27	5 850 (a)	Not Available ¹⁹	38 900 (i)	Not Available ¹⁹
	100/0 Not tested ¹¹		ested ¹¹	-28	-18	4 000 (a)	Not Available ¹⁹	18 250 (a)	12 900 (i)		
ADD-PROTECT Type II	PG	25-06-01	75/25	Not to	ested ¹¹	-14	7	7 700 (a)	Not Available ¹⁹	23 300 (c)	23 200 (i)
			50/50	Not to	ested ¹¹	-3	27	14 500 (a)	Not Available ¹⁹	31 400 (c)	22 600 (i)

TABLE 51: TYPE III FLUIDS TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE

					Lowest	Operationa	I Use Temp	erature ³	AS 9968 Viscosity ⁷ (mPa.s)						
	Type of	Expiry ²	Dilution			الداداء				Lowest On-W	ing Viscosity ⁸	Highest On-Wing Viscosity ⁸			
Fluid Name	Glycol ¹	(y-m-d)	(fluid/water)	aerodyna	peed imic test ⁶		e speed amic test ⁶	_	high speed aerodynamic test ⁶				Alternate Method	Manufacturer Method	Alternate Method
				°C	°F	°C	°F	°C	°F	Method	Wiethou	Wethou	Wetriod		
AllClear Syste	ems LLC														
AcroCloss			100/0	-16	3	-20.5	-5	-35	-31	7 800 (o)	Not Available ¹⁹	15 000 (o)	Not Available ¹⁹		
MAX	AeroClear EG 24-03-08 ¹³ 75/2		75/25			Dilution No	t Applicable				Dilution No	ot Applicable			
IVIAX			50/50	·	•	Dilution No	t Applicable	•			Dilution No	ot Applicable			

TABLE 52:
TYPE IV FLUIDS TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE

				Lowe	st Operationa	ıl Use Tempe	rature ³		AS 9968 Viscosity ⁷ (mPa.s)				
	Type of	Expiry ²	Dilution	middle	e speed	high	speed	Lowest On-V	Ving Viscosity ⁸	Highest On-V	ing Viscosity ⁸		
Fluid Name	Glycol ¹	(y-m-d)	(fluid/water)	aerodynamic test ⁶		aerodynamic test ⁶		Manufacturer Method	Alternate Method	Manufacturer Method	Alternate Method		
				°C	°F	ů	°F	Metriod	Wethou	Wethou	Wethou		
ABAX Industries													
			100/0	Not tested ¹¹		-26	-15	12 150 (h)	11 000 (a)	22 400 (h)	25 900 (c)		
ECOWING AD-49	PG	26-06-01	75/25	Dilution Not Applicable					Dilution No	ot Applicable			
			50/50		Dilution Not				Dilution No	ot Applicable			
ALAB International													
			100/0	Not te	ested ¹¹	-26	-15	1 840 (a)	Not Available ¹⁹	6 180 (a)	Not Available ¹⁹		
PROFLIGHT EG4	PROFLIGHT EG4 EG 25-06-0 ⁻		75/25		Dilution No	t Applicable			Dilution No	ot Applicable			
			50/50		Dilution No	t Applicable			Dilution No	ot Applicable			
			100/0	Not to	ested ¹¹	-29	-20	10 600 (a)	Not Available ¹⁹	17 800 (h)	Not Available ¹⁹		
PROFLIGHT PG4 PG		26-06-01	75/25			t Applicable			Dilution No	ot Applicable			
			50/50	Dilution Not Applicable				Dilution No	ot Applicable				
AllClear Systems LL0													
			100/0	Not te	ested ¹¹	-29	-20	35 500 (n)	13 350 (a)	51 800 (k)	Not Available ¹⁹		
ClearWing EG	EG	25-06-01	75/25	Dilution Not Applicable			Dilution Not Applicable						
			50/50		Dilution No	t Applicable		Dilution Not Applicable					
ASGlobal													
			100/0	Not to	ested ¹¹	-30	-22	6 600 (a)	Not Available ¹⁹	17 300 (a)	Not Available ¹⁹		
4Flite EG	EG	24-07-15 ¹³	75/25		Dilution No	ot Applicable		Dilution Not Applicable					
			50/50		Dilution No	t Applicable		Dilution Not Applicable					
			100/0	Not te	ested ¹¹	-26	-15	26 100 (c)	Not Available ¹⁹	, ,	Not Available ¹⁹		
4Flite PG	PG	25-08-04	75/25		Dilution No	t Applicable				ot Applicable			
			50/50		Dilution No	t Applicable			Dilution No	ot Applicable			
AVIAFLUID Internation	nal Ltd												
	100/0		100/0	Not to	ested ¹¹	-31	-24	5 600 (a)	Not Available ¹⁹	12 800 (a)	11 200 (i)		
AVIAFlight EG	EG	22-04-28 ⁹	75/25			ot Applicable			Dilution N	ot Applicable			
			50/50			t Applicable		Dilution Not Applicable					
			100/0	Not to	ested ¹¹	-25.5	-14	28 600 (c) Not Available ¹⁹ 35 900 (c) 22 200 (i)					
AVIAFlight PG	PG	23-07-01 ⁹	75/25			ot Applicable				ot Applicable			
			50/50		Dilution No	ot Applicable			Dilution N	ot Applicable			

TABLE 52 (CONT'D): TYPE IV FLUIDS TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE

				Lowest	t Operationa	al Use Tempe	rature ³		AS 9968 Visc	osity ⁷ (mPa.s)	
	Type of	Expiry ²	Dilution (fluid/water)	م الداد است		la i aula		Lowest On-W	/ing Viscosity ⁸	Highest On-Wing Viscosity ⁸	
Fluid Name	Glycol ¹	(y-m-d)		middle speed high space aerodynamic test ⁶ aerodynam		speed amic test ⁶	Manufacturer Method	Alternate Method	Manufacturer Method	Alternate Method	
				°C	°F	°C	°F	Wiethod	Wethod	Wethou	Wethou
CHEMCO Inc.					•	•					
			100/0	Not tes	sted ¹¹	-27	-17	46 400 (m)	19 450 (c)	67 000 (m)	Not Available ¹⁹
ChemR EG IV	EG	23-04-07 ⁹	75/25		Dilution No	ot Applicable	•		Dilution No	t Applicable	•
			50/50		Dilution No	ot Applicable			Dilution No	t Applicable	
			100/0	Not tes	sted ¹¹	-29	-20	60 800 (n)	43 100 (c)	87 100 (n)	Not Available ¹⁹
ChemR Nordik IV	EG	25-06-01	75/25		Dilution No	t Applicable			Dilution No	t Applicable	
			50/50		Dilution No	t Applicable		Dilution Not Applicable			
Chongqing Joba Chen	nical Co.,	Ltd									
		25-11-01	100/0	Not tes	sted ¹¹	-29	-20	32 600 (j)	Not Available ¹⁹	66 200 (j)	Not Available ¹⁹
FW-IV	EG		75/25		Dilution No	t Applicable	<u> </u>		Dilution No	t Applicable	
			50/50		Dilution No	t Applicable			Dilution No	t Applicable	
Clariant Produkte (Deu	utschland	l) GmbH									
O (: MD I)/		26-06-01	100/0	Not tes	sted ¹¹	-28.5	-19	7 550 (a)	Not Available ¹⁹	20 500 (q)	20 500 (c)
Safewing MP IV LAUNCH	PG		75/25	Not tes	sted ¹¹	-14	7	18 000 (a)	Not Available ¹⁹	47 800 (q)	47 800 (c)
LAUNCH			50/50	Not tes	sted ¹¹	-3.5	26	17 800 (a)	Not Available ¹⁹	63 000 (q)	63 000 (c)
Cofession MD IV			100/0	Not tes	sted ¹¹	-29	-20	8 700 (p)	8 450 (a)	21 000 (q)	21 000 (c)
Safewing MP IV LAUNCH PLUS	PG	25-06-01	75/25	Not tes	sted ¹¹	-14	7	18 800 (q)	17 200 (c)	51 600 (q)	51 600 (c)
LAUNCHFLUS			50/50	Not tes	sted ¹¹	-3.5	26	9 700 (p)	12 150 (a)	65 700 (q)	65 700 (c)
Cryotech Deicing Tech	nnology										
			100/0	Not tes	sted ¹¹	-30.5	-23	4 400 (f)	4 050 (a)	17 000 (f)	16 200 (a)
Polar Guard® Advance	PG	25-06-01	75/25	Not tes	sted ¹¹	-14	7	11 600 (f)	9 750 (a)	38 000 (c)	Not Available ¹⁹
			50/50	Not tes	sted ¹¹	-3.5	26	80 (a)	Not Available ¹⁹	48 000 (c)	Not Available ¹⁹
			100/0	Not tes	sted ¹¹	-29	-20	6 000 (f)	6 350 (a)	23 500 (f)	23 200 (c)
Polar Guard® Xtend	PG	25-06-01	75/25	Dilution Not Applicable					Dilution No	t Applicable	
			50/50		Dilution No	t Applicable			Dilution No	t Applicable	

TABLE 52 (CONT'D): TYPE IV FLUIDS TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE

				Lowest	Operationa	al Use Tempe	rature ³		AS9968 Visco	osity ⁷ (mPa.s)	
	Type of	Expiry ² (y-m-d)	Dilution	middle s		hiah	speed	Lowest On-W	ing Viscosity ⁸	Highest On-V	Ving Viscosity ⁸
Fluid Name	Glycol ¹		(fluid/water)	aerodynamic test ⁶			aerodynamic test ⁶		Alternate Method	Manufacturer Method	Alternate Method
				°C	°F	°C	°F	Method	Metriod	Wethou	Wethod
Dow Inc.											
UCAR ENDURANCE™	ICAD ENDUDANCETM		100/0	Not tested ¹¹		-29	-20	24 850 (j)	2 230 (a)	47 800 (j)	5 900 (a)
EG106 ADF/AAF	EG	25-06-01	75/25	Dilution Not Applicable				Dilution No	t Applicable		
LG 100 ADI /AAI			50/50		Dilution No	t Applicable			Dilution No	t Applicable	
UCAR™			100/0	Not tes	ted ¹¹	-26	-15	12 150 (h)	11 000 (a)	22 400 (h)	25 900 (c)
FLIGHTGUARD™	PG	25-06-08	75/25		Dilution No	t Applicable			Dilution No	t Applicable	
AD-49			50/50		Dilution Not Applicable				Dilution No	t Applicable	
Inland Technologies In	ic.										
ECO-SHIELD®			100/0	Not tes	ted ¹¹	-25.5	-14	11 050 (a)	Not Available ¹⁹	25 800 (i)	34 500 (c)
	PG	24-10-28	75/25		Dilution No	t Applicable			Dilution No	t Applicable	
			50/50		Dilution No	t Applicable			Dilution No	t Applicable	
JSC RCP Nordix			-								
			100/0	Not tes	ted ¹¹	-25.5	-14	9 800 (h)	12 350 (a)	14 800 (i)	17 340 (a)
Defrost ECO 4	PG	23-08-129	75/25		Dilution No	ot Applicable	•	Dilution Not Applicable			
			50/50		Dilution No	ot Applicable	t Applicable		Dilution Not Applicable		
			100/0	Not tes	ted ¹¹	-26	-15	2 500 (a)	Not Available ¹⁹	5 350 (a)	Not Available ¹⁹
Defrost NORTH 4	EG	23-06-01 ⁹	75/25		Dilution No	ot Applicable			Dilution No	t Applicable	
			50/50		Dilution No	ot Applicable			Dilution No	t Applicable	
Kilfrost Limited											
			100/0	Not tes	ted ¹¹	-28	-18	17 900 (e)	17 900 (c)	43 800 (c)	Not Available ¹⁹
ABC-S Plus	PG	25-06-15	75/25	Not tes	ted ¹¹	-14.5	6	18 300 (e)	18 300 (c)	58 000 (c)	Not Available ¹⁹
			50/50	Not tes	ted ¹¹	-3.5	26	7 500 (e)	7 500 (a)	27 000 (c)	Not Available ¹⁹
MKS DevO Chemicals											
CODEICEDHOD			100/0	Not tes	ted ¹¹	-29	-20	50 200 (i)	Not Available ¹⁹	60 900 (i)	Not Available ¹⁹
COREICEPHOB TYPE-IV PG	PG	26-06-01	75/25		Dilution No	t Applicable	-		Dilution No	t Applicable	
FE- V FG			50/50		Dilution No	t Applicable			Dilution No	t Applicable	

TABLE 52 (CONT'D): TYPE IV FLUIDS TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE

		Expiry ² (y-m-d)		Lowest	Operationa	al Use Tempe	ature ³	AS9968 Viscosity ⁷ (mPa.s)				
	Type of		Dilution (fluid/water)	middle a	nood	high	high speed		ing Viscosity ⁸	Highest On-W	ling Viscosity ⁸	
Fluid Name	Glycol ¹			middle speed aerodynamic test ⁶		aerodynamic test ⁶		Manufacturer Method	Alternate Method	Manufacturer Method	Alternate Method	
				°C	°F	°C	°F	Wethod	Wethod	Wethou	WetHod	
Newave Aerochemical Co. Ltd.												
T			100/0	Not tested ¹¹		-29.5	-21	14 100 (c)	Not Available ¹⁹	27 600 (c)	25 700 (i)	
FCY 9311	PG	26-06-01	75/25	Dilution Not Applicable				Dilution Not Applicable				
			50/50	Dilution Not Applicable				Dilution No	t Applicable			
		26-06-01	100/0	Not test	ed ¹¹	-29	-20	24 800 (g)	6 300 (a)	43 700 (k)	78 000 (c)	
FCY-EGIV	EG		75/25	Dilution Not Applicable				Dilution Not Applicable				
			50/50		Dilution No	t Applicable		Dilution Not Applicable				
Shaanxi Cleanway Avi	ation Che	emical Co.,	Ltd									
		25-11-28	100/0	Not tested ¹¹		-30	-22	16 750 (a)	Not Available ¹⁹	29 700 (d)	Not Available ¹⁹	
Cleansurface IV	PG		75/25		Dilution No	t Applicable		Dilution Not Applicable				
			50/50		Dilution No	t Applicable		Dilution Not Applicable				

CAUTIONS AND NOTES FOR TABLES 49, 50, 51, 52

CAUTIONS

- These tables list fluids that have been tested with respect to endurance time performance (Holdover Times), anti-icing performance (Water Spray Endurance Testing/High Humidity Endurance Testing) and aerodynamic acceptance (Type I: SAE ARP6207 §3.4.1, AMS1424 §3.5.2 and §3.5.3; Type II/ III/ IV: SAE ARP5718 §FOREWARD, AMS1428 §3.2.4 and §3.2.5) only. These tests were conducted by APS Aviation Inc. (www.apsaviation.ca) and Anti-icing Materials International Laboratory (AMIL) (www.uqac.ca/amil). The end user is responsible for contacting the fluid manufacturer to confirm all other SAE AMS1424/1428 technical requirement tests, such as fluid stability, toxicity, materials compatibility, etc. have been conducted. These technical requirement tests are typically conducted by Scientific Material International (SMI) (www.smiinc.com) and AMIL, or any acceptable source.
- LOUT data provided in these tables is based strictly on the manufacturer's data; the end user is responsible for verifying the validity
 of this data.
- Type I fluids supplied in concentrated form must not be used in that form and must be diluted.

NOTES

- 1 PG = conventional glycol (propylene glycol); EG = conventional glycol (ethylene glycol); DEG = conventional glycol (diethylene glycol); NCG = non-conventional glycol (organic non-ionic diols and triols, e.g. 1,3-propanediol, glycerine) and mixtures of non-conventional glycol and conventional glycol; NG = non-glycol (e.g. organic salts) and mixtures of non-glycol and glycol.
- 2 Expiry date is the earlier expiry date of the Aerodynamic Test(s) or Water Spray Endurance Test. Fluids that are tested after the issuance of this list will appear in a later update.
- 3 The values in this table were determined using test results from pre-production fluid samples when available. In some cases, the fluid manufacturer requested the publication of a more conservative value than the pre-production test value. The lowest operational use temperature (LOUT) for a given fluid is the higher (warmer) of:
 - a) The lowest temperature at which the fluid meets the aerodynamic acceptance test for a given aircraft type; or
 - b) The actual freezing point of the fluid plus its freezing point buffer (Type I = 10 °C/18 °F; Type II/III/IV = 7 °C/13 °F).
 - Note: LOUTs are rounded to the nearest half degree Celsius and the values in degrees Fahrenheit are calculated to the nearest whole degree.
- 4 The LOUT for Type I fluids that are intended to be diluted is derived from a dilution that provides the lowest operational use temperature. For other Type I dilutions, determine the freezing point of the fluid and add a 10 °C freezing point buffer, as a dilution will usually yield a higher and more restrictive operational use temperature. Consult the fluid manufacturer or fluid documentation for further clarification and guidance on establishing the appropriate operational use temperature of a diluted fluid.
- 5 Type I concentrate fluids have also been tested at 50/50 (glycol/water) dilution.
- 6 If uncertain whether the aircraft to be treated conforms to the low speed, the middle speed, or the high speed aerodynamic test, consult the aircraft manufacturer. The aerodynamic test is defined in SAE AS5900 (latest version).
- The Alternate viscosity method should only be used for field verification and auditing purposes; when in doubt as to which method is appropriate, use the manufacturer method. Viscosity measurement methods are indicated as letters (in parentheses) beside each viscosity value. Details of each measurement method are shown in the table on the following page. The exact measurement method (spindle, container, fluid volume, temperature, speed, duration) must be used to compare the viscosity of a sample to a viscosity given in this table.
- 8 The lowest on-wing viscosity (LOWV), and highest on-wing viscosity (HOWV) values in this table are those of the fluids provided by the manufacturers for holdover time testing, and initial qualification aerodynamic testing. For the holdover times and lowest operation use temperature to be valid, the viscosity of the fluid on the wing shall not be lower than the LOWV value in this table and higher than the HOWV value in this table. The user should periodically ensure that the viscosity of a fluid sample taken from the wing surface complies with these limits.
- 9 Aerodynamic Performance and Anti-Icing Performance test data has expired; fluids listed in italics will be removed from this listing four years after expiry.
- 10 Manufacturer has not provided fluid information as required in SAE ARP5718B; fluid may be removed from this listing in subsequent revisions.
- 11 Manufacturer has indicated fluid was not tested.
- 12 Dow UCAR™ PG ADF Concentrate, sold under the product name DeiceX PG ADF Concentrate, qualified from 2023-06-15.
- 13 Currently in the test/re-test process. Contact the fluid manufacturer for latest information (see Appendix C for latest available contact information).
- 14 Fluid was not retested for low speed aerodynamics. This data will be removed four years after the expiry of the last low speed test.
- 15 For UCAR™ ADF XL54, refer to primary site qualification of UCAR™ ADF Concentrate.
- 16 For UCAR™ PG ADF Dilute 55/45, refer to primary site qualification of UCAR™ PG ADF Concentrate.
- 17 Dow UCAR™ ADF Concentrate, sold under the product name Inland ADF Concentrate, qualified from 2015-09-04.
- 18 Refer to preproduction qualification of SafeTemp® ES Plus submitted by HOC Industries, qualified from 2017-11-20.
- 19 Manufacturer has not provided an alternate method for measuring viscosity. Please use the Manufacturer Method.

TABLE 53:
VISCOSITY MEASUREMENT METHODS FOR TYPE II, III, AND IV FLUIDS
TESTED FOR ANTI-ICING PERFORMANCE AND AERODYNAMIC ACCEPTANCE

Method	Brookfield Spindle*	Container	Fluid Volume	Temp.**	Speed	Duration
а	LV1 (with guard leg)	600 mL low form (Griffin) beaker	575 mL***	20 °C	0.3 rpm	10.0 minutes
b	LV1 (with guard leg)	600 mL low form (Griffin) beaker	575 mL***	20 °C	0.3 rpm	33.3 minutes
С	LV2-disc (with guard leg)	600 mL low form (Griffin) beaker	425 mL***	20 °C	0.3 rpm	10.0 minutes
d	LV2-disc (with guard leg)	600 mL low form (Griffin) beaker	575 mL***	20 °C	0.3 rpm	10.0 minutes
е	LV2-disc (with guard leg)	150 mL tall form (Berzelius) beaker	135 mL***	20 °C	0.3 rpm	10.0 minutes
f	SC4-34/13R	small sample adapter	10 mL	20 °C	0.3 rpm	10.0 minutes
g	SC4-34/13R	small sample adapter	10 mL	0 ℃	0.3 rpm	30.0 minutes
h	SC4-31/13R	small sample adapter	10 mL	20 °C	0.3 rpm	10.0 minutes
i	SC4-31/13R	small sample adapter	10 mL	20 °C	0.3 rpm	30.0 minutes
j	SC4-31/13R	small sample adapter	10 mL	0 °C	0.3 rpm	10.0 minutes
k	SC4-31/13R	small sample adapter	10 mL	0 °C	0.3 rpm	30.0 minutes
I	SC4-31/13R	small sample adapter	9 mL	20 °C	0.3 rpm	15.0 minutes
m	SC4-31/13R	small sample adapter	9 mL	0 °C	0.3 rpm	10.0 minutes
n	SC4-31/13R	small sample adapter	9 mL	0 ℃	0.3 rpm	30.0 minutes
0	SC4-31/13R	small sample adapter	9 mL	0 °C	0.3 rpm	65.0 minutes
р	LV1	big sample adapter	55 mL	20 °C	0.3 rpm	10.0 minutes
q	LV2-disc	big sample adapter	60 mL	20 °C	0.3 rpm	10.0 minutes

^{*} Spindle must be attached to a Brookfield viscometer model equipped with an LV spring.

^{**} Sample temperature will affect readings; ensure sufficient time is allowed for sample to reach thermal equilibrium before starting test. Use of a cooling bath strongly recommended.

^{***} If necessary, adjust fluid volume to ensure fluid is level with notch on the spindle shaft.

TABLE 54: GUIDELINES FOR THE APPLICATION OF SAE TYPE I FLUID

Outside Air	One-Step Procedure	Two-Step Procedure				
Temperature (OAT) ¹	De/Anti-icing ²	First Step: Deicing	Second Step: Anti-icing ³			
0 °C (32 °F) and above	Fluid/water mixture heated to at least 60°C	Heated water or a heated fluid/water mixture	Fluid/water mixture heated to at least 60°C (140°F) at the			
Below 0 °C (32 °F) to LOUT	(140°F) at the nozzle with a freezing point of at least 10°C (18°F) below OAT	Heated fluid/water mixture with a freezing point at OAT or below	nozzle with a freezing point of at least 10°C (18°F) below OAT			

NOTES

- 1 Fluids must not be used at temperatures below their lowest operational use temperature (LOUT).
- When anti-icing using the one-step procedure, a minimum quantity of 1 liter/m² (~2 gal./100 sq. ft.) of Type I fluid mixture heated to at least 60°C (140°F) is required after all frozen contamination is removed. This is achieved using a continuous process. This application is necessary to heat the surfaces, as heat contributes significantly to the Type I fluid holdover times.
- 3 To be applied before first-step fluid freezes, typically within 3 minutes. This time may be higher than 3 minutes in some conditions, but potentially lower in heavy precipitation, colder temperatures, or for critical surfaces constructed of composite materials. If necessary, the second step shall be applied area by area (sectionally).

- This table is applicable for the use of Type I holdover time guidelines in all conditions, including active frost. If holdover
 times are not required, a temperature of 60 °C (140 °F) at the nozzle is desirable.
- If holdover times are required, the temperature of water or fluid/water mixtures shall be at least 60 °C (140 °F) at the nozzle. Upper temperature limit shall not exceed fluid and aircraft manufacturers' recommendations.
- To use Type I Holdover Times Guidelines in all conditions including active frost, an additional minimum of 1 liter/m² (~2 gal./100 sq. ft.) of heated Type I fluid mixture must be applied to the surfaces after all frozen contamination is removed. This application is necessary to heat the surfaces, as heat contributes significantly to the Type I fluid holdover times. The required protection can be provided using a 1-step method by applying more fluid than is strictly needed to just remove all of the frozen contamination (the same additional amount stated above is required).
- The lowest operational use temperature (LOUT) for a given Type I fluid is the higher (warmer) of:
 - a) The lowest temperature at which the fluid meets the aerodynamic acceptance test for a given aircraft type; or
 - b) The actual freezing point of the fluid plus a freezing point buffer of 10 °C (18 °F).
- Wing skin temperatures may be colder or warmer than the OAT. Causes can include: radiation cooling, cold-soaked wing, or hangar storage. Consult the appropriate guidance (HOT Tables and FAA Ground Deicing General Information Document, Winter 2024-2025") for the contaminant in question.
- When conducting aircraft deicing using a Type I fluid and not using the 10 °C/18 °F buffer, procedures must be developed and approved to ensure refreezing does not occur prior to takeoff.

TABLE 55: GUIDELINES FOR THE APPLICATION OF SAE TYPE II AND IV FLUID

(FLUID CONCENTRATIONS IN % VOLUME)

Outside Air Temperature	One-Step Procedure	Two-Step Procedure					
(OAT) ¹	De/Anti-icing	First Step: Deicing	Second Step: Anti-icing ²				
0 °C (32 °F) and above	100/0, 75/25 or 50/50 Heated ³ Type II or IV fluid/water mixture	Heated water or a heated Type I, II, III, or IV fluid/water mixture	100/0, 75/25 or 50/50 Heated or unheated Type II or IV fluid/water mixture				
Below 0 °C (32 °F) to -3 °C (27 °F)	100/0, 75/25 or 50/50 Heated ³ Type II or IV fluid/water mixture	Heated Type I, II, III, or IV fluid/water mixture with a freezing point at OAT or below	100/0, 75/25 or 50/50 Heated or unheated Type II or IV fluid/water mixture				
Below -3 °C (27 °F) to -14 °C (7 °F)	100/0 or 75/25 Heated ³ Type II or IV fluid/water mixture	Heated Type I, II, III, or IV fluid/water mixture with a freezing point at OAT or below	100/0 or 75/25 Heated or unheated Type II or IV fluid/water mixture				
Below -14 °C (7 °F) to LOUT	100/0 Heated ³ Type II or IV fluid	Heated Type I, II, III, or IV fluid/water mixture with a freezing point at OAT or below	100/0 Heated or unheated Type II or IV fluid				

NOTES

- 1 Fluids used for the anti-icing procedure must not be used at temperatures below their lowest operational use temperature (LOUT). First step fluids must not be used below their freezing points. Consideration should be given to the use of Type I/III fluid when Type II/IV fluid cannot be used due to LOUT limitations (see Tables 55 and 57). The LOUT for a given Type II/IV fluid is the higher (warmer) of:
 - a) The lowest temperature at which the fluid meets the aerodynamic acceptance test for a given aircraft type; or
 - b) The actual freezing point of the fluid plus its freezing point buffer of 7 °C (13 °F).

Although some LOUTs are lower than the temperatures stated in the HOT table, holdover times do not apply when anti-icing below the lowest temperature stated in the band.

- 2 To be applied before first step fluid freezes, typically within 3 minutes. Time may be longer than 3 minutes in some conditions, but potentially shorter in heavy precipitation, colder temperatures, or for critical surfaces constructed of composite materials. If necessary, the second step shall be applied area by area (sectionally).
- 3 Clean aircraft may be anti-iced with unheated fluid.

- For heated fluids, a fluid temperature not less than 60 °C (140 °F) at the nozzle is desirable.
- Upper temperature limit shall not exceed fluid and aircraft manufacturers' recommendations.
- Wing skin temperatures may be colder or warmer than the OAT. Causes can include: radiation cooling, cold-soaked wing, or hangar storage. Consult the appropriate guidance (HOT Tables and FAA Ground Deicing General Information Document, Winter 2024-2025") for the contaminant in question.
- Whenever frost or ice occurs on the lower surface of the wing in the area of the fuel tank, indicating a cold-soaked wing, the 50/50 dilutions of Type II or IV shall not be used for the anti-icing step because fluid freezing may occur.
- An insufficient amount of anti-icing fluid may cause a substantial loss of holdover time. This is particularly true when
 using a Type I fluid mixture for the first step in a two-step procedure.
- When conducting aircraft deicing using a Type I fluid and not using the 10 °C/18 °F buffer, procedures must be
 developed and approved to ensure refreezing does not occur prior to takeoff.

TABLE 56: GUIDELINES FOR THE APPLICATION OF UNHEATED SAE TYPE III FLUID

(FLUID CONCENTRATIONS IN % VOLUME)

Outside Air Temperature	Anti-icing Only⁴	Two-Step Procedure					
(OAT) ¹	7 title forming Griny	First Step: Deicing	Second Step: Anti-icing ²				
0 °C (32 °F) and above	100/0, 75/25 or 50/50 Unheated Type III fluid/water mixture	Heated ³ water or a heated ³ Type I, II, III, or IV fluid/water mixture	100/0, 75/25 or 50/50 Unheated Type III fluid/water mixture				
Below 0 °C (32 °F) to -3 °C (27 °F)	100/0, 75/25 or 50/50 Unheated Type III fluid/water mixture	Heated ³ Type I, II, III, or IV fluid/water mixture with a freezing point at OAT or below	100/0, 75/25 or 50/50 Unheated Type III fluid/water mixture				
Below -3 °C (27 °F) to -10 °C (14 °F)	100/0 or 75/25 Unheated Type III fluid/water mixture	Heated ³ Type I, II, III, or IV fluid/water mixture with a freezing point at OAT or below	100/0 or 75/25 Unheated Type III fluid/water mixture				
Below -10 °C (14 °F) to LOUT	100/0 Unheated Type III fluid	Heated ³ Type I, II, III, or IV fluid/water mixture with a freezing point at OAT or below	100/0 Unheated Type III fluid				

NOTES

- 1 Fluids used for the anti-icing procedure must not be used at temperatures below their lowest operational use temperature (LOUT). First step fluids must not be used below their freezing points. Consider the use of Type I when Type III fluid cannot be used (see Table 54). The LOUT for a given Type III fluid is the higher (warmer) of:
 - a) The lowest temperature at which the fluid meets the aerodynamic acceptance test for a given aircraft type; or
 - b) The actual freezing point of the fluid plus its freezing point buffer of 7 °C (13 °F).

Although the LOUTs may be lower than the temperatures stated in the HOT table, holdover times do not apply when anti-icing below the lowest temperature stated in the band.

- 2 To be applied before first step fluid freezes, typically within 3 minutes. This time may be longer than 3 minutes in some conditions, but potentially shorter in heavy precipitation, colder temperatures, or for critical surfaces constructed of composite materials. If necessary, the second step shall be applied area by area (sectionally).
- 3 For heated fluids, a fluid temperature not less than 60 °C (140 °F) at the nozzle is desirable.
- 4 Anti-icing only with unheated Type III fluid is only possible on a clean aircraft. If deicing is required, a two-step procedure must be used.

- Upper temperature limit shall not exceed fluid and aircraft manufacturers' recommendations.
- Wing skin temperatures may be colder or warmer than the OAT. Causes can include: radiation cooling, cold-soaked wing, or hangar storage. Consult the appropriate guidance (HOT Tables and FAA Ground Deicing General Information Document, Winter 2024-2025") for the contaminant in question.
- Whenever frost or ice occurs on the lower surface of the wing in the area of the fuel tank, indicating a cold-soaked wing, the 50/50 dilutions of Type III shall not be used for the anti-icing step because fluid freezing may occur.
- An insufficient amount of anti-icing fluid may cause a substantial loss of holdover time. This is particularly true when
 using a Type I fluid mixture for the first step in a two-step procedure.
- When conducting aircraft deicing using a Type I fluid and not using the 10 °C/18 °F buffer, procedures must be
 developed and approved to ensure refreezing does not occur prior to takeoff.

APPENDIX A: ADJUSTED HOLDOVER TIME (HOT) GUIDELINES

These tables are for use when flaps/slats are deployed prior to de/anti-icing. Holdover and allowance times have been adjusted to 76 percent of standard times. Standard holdover and allowance times can be used if flaps and slats are deployed as close to departure as safety allows.

Note: Industry data indicates the possibility of increased takeoff misconfigurations when the selection of takeoff flaps is delayed later in the taxi regime. If an air carrier chooses to select the flaps/slats to the takeoff configuration prior to beginning the anti-icing process, operators should have robust procedures in place to ensure that the aircraft is properly configured prior to takeoff. Air Carriers should follow the airframe manufacturer's recommended procedures regarding anti-icing operations and the configuration of flaps/slats while taxiing.

ADJUSTED HOLDOVER TIME (HOT) GUIDELINES FOR WINTER 2024-2025

Adjusted Active Frost HOT Guidelines Winter 2024-2025	
Table Adj-1: Adjusted Active Frost Holdover Times for SAE Type I, Type II, Type III, and Type IV Fluids	A-4
Adjusted HOT Guidelines for SAE Type I Fluids Winter 2024-2025	A-5
Table Adj-2: Adjusted Holdover Times for SAE Type I Fluid on Critical Aircraft Surfaces Composed Predomina Aluminum	
Table Adj-3: Adjusted Holdover Times for SAE Type I Fluid on Critical Aircraft Surfaces Composed Predomina Composites	ntly of
Adjusted HOT Guidelines for SAE Type II Fluids Winter 2024-2025	
Table Adj-4: Adjusted Generic Holdover Times for SAE Type II Fluids	
Table Adj-5: Adjusted Type II Holdover Times for ABAX ECOWING AD-2	A-10
Table Adj-6: Adjusted Type II Holdover Times for Aviation Xi'an High-Tech Cleanwing II	
Table Adj-7: Adjusted Type II Holdover Times for Clariant Safewing MP II FLIGHT	
Table Adj-8: Adjusted Type II Holdover Times for Cryotech Polar Guard® II	
Table Adj-9: Adjusted Type II Holdover Times for Kilfrost ABC-K Plus	
Table Adj-10: Adjusted Type II Holdover Times for Kilfrost Ice Clear II	A-15
Table Adj-11: Adjusted Type II Holdover Times for MKS DevO Chemicals COREICEPHOB Type II	
Table Adj-12: Adjusted Type II Holdover Times for Newave Aerochemical FCY-2	A-17 A 10
Table Adj-13: Adjusted Type II Holdover Times for ROMCHIM ADD-PROTECT NG Type II	
Adjusted HOT Guidelines for SAE Type III Fluids Winter 2024-2025	
Table Adj-15: Adjusted Type III Holdover Times for AllClear AeroClear MAX Applied Unheated on Low Speed A	A-21
Table Adj-16: Adjusted Type III Holdover Times for AllClear AeroClear MAX Applied Unheated on Middle Speed A	A-22
Table Adj-17: Adjusted Type III Holdover Times for AllClear AeroClear MAX Applied Unheated on High Speed A	
Adjusted HOT Guidelines for SAE Type IV Fluids Winter 2024-2025	A-24
Table Adj-18: Adjusted Generic Holdover Times for SAE Type IV Fluids	A-25
Table Adj-19: Adjusted Type IV Holdover Times for ABAX ECOWING AD-49	A-26
Table Adj-20: Adjusted Type IV Holdover Times for ALAB International PROFLIGHT EG4	A-27
Table Adj-21: Adjusted Type IV Holdover Times for ALAB International PROFLIGHT PG4	
Table Adj-22: Adjusted Type IV Holdover Times for AllClear ClearWing EG	A-29
Table Adj-23: Adjusted Type IV Holdover Times for ASGlobal 4Flite EG	
Table Adj-24: Adjusted Type IV Holdover Times for ASGlobal 4Flite PG	
Table Adj-25: Adjusted Type IV Holdover Times for AVIAFLUID AVIAFlight EG	
Table Adj-27: Adjusted Type IV Holdover Times for CHEMCO ChemR EG IV	
Table Adj-28: Adjusted Type IV Holdover Times for CHEMCO ChemR Nordik IV	Δ-35
Table Adj-29: Adjusted Type IV Holdover Times for Chongging Joba Chemical Co.,Ltd FW-IV	
Table Adj-30: Adjusted Type IV Holdover Times for Clariant Safewing MP IV LAUNCH	
Table Adj-31: Adjusted Type IV Holdover Times for Clariant Safewing MP IV LAUNCH PLUS	
Table Adj-32: Adjusted Type IV Holdover Times for Cryotech Polar Guard® Advance	
Table Adj-33: Adjusted Type IV Holdover Times for Cryotech Polar Guard® Xtend	A-40
Table Adj-34: Adjusted Type IV Holdover Times for Dow Inc. UCAR Endurance™ EG106	
Table Adj-35: Adjusted Type IV Holdover Times for Dow inc. UCAR™ FlightGuard™ AD-49	A-42
Table Adj-36: Adjusted Type IV Holdover Times for Inland Technologies ECO-SHIELD®	
Table Adj-37: Adjusted Type IV Holdover Times for JSC RCP Nordix Defrost ECO 4	
Table Adj-38: Adjusted Type IV Holdover Times for JSC RCP Nordix Defrost NORTH 4	
Table Adj-39: Adjusted Type IV Holdover Times for Kilfrost ABC-S Plus	
Table Adj-40: Adjusted Type IV Holdover Times for MKS DevO Chemicals COREICEPHOB TYPE IV PG	
Table Adj-41: Adjusted Type IV Holdover Times for Newave Aerochemical FCY-EGIV	
Table Adj-43: Adjusted Type IV Holdover Times for Shaanxi Cleanway Cleansurface IV	
Adjusted Allowance Times Tables for Winter 2024-2025	
Table Adj-44: Adjusted Allowance Times for SAE Type III Fluids	
Table Adj-45: Adjusted Allowance Times for SAE Type III Fittings	A-52 A-53
Table Adj-46: Adjusted Allowance Times for SAE Type IV Propylene Glycol (PG) Fluids	

ADJUSTED ACTIVE FROST HOT GUIDELINES WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

- The responsibility for the application of these data remains with the user.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.

TABLE ADJ-1: ADJUSTED ACTIVE FROST HOLDOVER TIMES FOR SAE TYPE II, TYPE III, AND TYPE IV FLUIDS¹

Outside Air Temperature ^{2,3,4}	Type I Aluminum	Type I Composite	
-1 °C and above (30 °F and above)			
below -1 to -3 °C (below 30 to 27 °F)			
below -3 to -10 °C (below 27 to 14 °F)	0:34	0:27	
below -10 to -14 °C (below 14 to 7 °F)			
below -14 to -21 °C (below 7 to -6 °F)			
below -21 to -25 °C (below -6 to -13 °F)			
below -25 °C to LOUT (below -13 °F to LOUT)			

Outside Air Temperature ^{3,4}	Concentration Fluid/Water By % Volume	Type II	Type III⁵	Type IV		
	100/0	6:05	1:31	9:07		
-1 °C and above (30 °F and above)	75/25	3:48	0:46	3:48		
(oo i ana abovo)	50/50	1:31	0:23	2:17		
	100/0	6:05	1:31	9:07		
below -1 to -3 °C (below 30 to 27 °F)	75/25	3:48	0:46	3:48		
(55,50,40,50,10,27,17)	50/50	1:08	0:23	2:17		
below -3 to -10 °C	100/0	6:05	1:31	7:36		
(below 27 to 14 °F)	75/25	3:02	0:46	3:48		
below -10 to -14 °C	100/0	4:34	1:31	4:34		
(below 14 to 7 °F)	75/25	0:46	0:46	0:46		
below -14 to -21 °C (below 7 to -6 °F)	100/0	2:17	1:31	4:34		
below -21 to -25 °C (below -6 to -13 °F)	100/0	1:31	1:31	3:02		
below -25 °C (below -13 °F)	100/0	No Holdo	No Holdover Time Guidelines Exist			

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 To use the HOTs in this table, ensure that the fluid and dilution being used is listed in the List of Qualified Fluids Tested for Anti-Icing Performance and Aerodynamic Acceptance table (Table 49 Table 52). Any restrictions on the use of the fluid have to be identified and applied.
- 2 Type I Fluid / Water Mixture must be selected so that the freezing point of the mixture is at least 10 °C (18 °F) below outside air temperature.
- 3 Ensure that the lowest operational use temperature (LOUT) is respected.
- 4 Changes in outside air temperature (OAT) over the course of longer frost events can be significant; the appropriate holdover time to use is the one provided for the coldest OAT that has occurred in the time between the de/anti-icing fluid application and takeoff.
- 5 To use the Type III fluid frost holdover times, the fluid brand being used must be known. AllClear AeroClear MAX must be applied unheated.

CAUTIONS

ADJUSTED HOT GUIDELINES FOR SAE TYPE I FLUIDS WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

- The responsibility for the application of these data remains with the user.
- The time of protection will be shortened in heavy weather conditions. Heavy precipitation rates or high moisture content, high wind velocity jet blast, or blowing snow may reduce holdover time below the lowest time stated in the range. Holdover time may be reduced when aircraft skin temperature is lower than outside air temperature.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.

TABLE ADJ-2: ADJUSTED HOLDOVER TIMES FOR SAE TYPE I FLUID ON CRITICAL AIRCRAFT SURFACES COMPOSED PREDOMINANTLY OF ALUMINUM

Outside Air Temperature ^{1,2}	Freezing Fog, Freezing Mist ³ , or Ice Crystals ⁴	Snow mixed with Freezing Fog ⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold- Soaked Wing ¹⁰	Other ¹¹
-3 °C and above (27 °F and above)	0:08 - 0:13	0:04 - 0:06	0:14 - 0:17	0:08 - 0:14	0:05 - 0:08	0:07 - 0:10	0:02 - 0:04	0:02 - 0:04	
below -3 to -6 °C (below 27 to 21 °F)	0:06 - 0:10	0:03 - 0:05	0:11 - 0:13	0:06 - 0:11	0:04 - 0:06	0:04 - 0:07	0:02 - 0:04		
below -6 to -10 °C (below 21 to 14 °F)	1 0.02 - 0.08	0:02 - 0:04	0:08 - 0:10	0:05 - 0:08	0:03 - 0:05	0:03 - 0:05	0:02 - 0:04	CAUTIOI No holdover guidelines e	time
below -10 °C (below 14 °F)	0:04 - 0:07	0:02 - 0:02	0:05 - 0:06	0:03 - 0:05	0:02 - 0:03				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Type I fluid / water mixture must be selected so that the freezing point of the mixture is at least 10 °C (18 °F) below outside air temperature.
- 2 Ensure that the lowest operational use temperature (LOUT) is respected.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.

CAUTIONS

TABLE ADJ-3: ADJUSTED HOLDOVER TIMES FOR SAE TYPE I FLUID ON CRITICAL AIRCRAFT SURFACES COMPOSED PREDOMINANTLY OF COMPOSITES

Outside Air Temperature ^{1,2}	Freezing Fog, Freezing Mist ³ , or Ice Crystals ⁴	Snow mixed with Freezing Fog ⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold- Soaked Wing ¹⁰	Other ¹¹
-3 °C and above (27 °F and above)	0:07 - 0:12	0:02 - 0:03	0:09 - 0:11	0:05 - 0:09	0:02 - 0:05	0:06 - 0:10	0:02 - 0:04	0:01 - 0:04	
below -3 to -6 °C (below 27 to 21 °F)	0:05 - 0:06	0:02 - 0:03	0:08 - 0:10	0:04 - 0:08	0:02 - 0:04	0:04 - 0:07	0:02 - 0:04		
below -6 to -10 °C (below 21 to 14 °F)	1 0.03 - 0.08	0:02 - 0:03	0:07 - 0:09	0:04 - 0:07	0:02 - 0:04	0:03 - 0:05	0:02 - 0:04	CAUTION No holdover guidelines e	time
below -10 °C (below 14 °F)	0:03 - 0:05	0:02 - 0:02	0:05 - 0:06	0:03 - 0:05	0:02 - 0:03				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Type I fluid / water mixture must be selected so that the freezing point of the mixture is at least 10 °C (18 °F) below outside air temperature.
- 2 Ensure that the lowest operational use temperature (LOUT) is respected.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.

CAUTIONS

ADJUSTED HOT GUIDELINES FOR SAE TYPE II FLUIDS WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

- The responsibility for the application of these data remains with the user.
- The time of protection will be shortened in heavy weather conditions. Heavy precipitation rates or high moisture content, high wind velocity jet blast, or blowing snow may reduce holdover time below the lowest time stated in the range.
 Holdover time may be reduced when aircraft skin temperature is lower than outside air temperature.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.
- Whenever frost or ice occurs on the lower surface of the wing in the area of the fuel tank, indicating a cold-soaked wing, the 50/50 dilutions of Type II or IV shall not be used for the anti-icing step because fluid freezing may occur.

TADIE ADIA.		ACMEDIA HA			E TYPE II FLUIDS ¹
$I \triangle RI \vdash \triangle III^{-/1}$	$\Delta \cap \cap \cap \cap \cap$		I	MEZECIE ZAF	- I V D E II EI I III 1 \
IAULL AUJ-7.	AUJUGILU	GENERAL OF		IVILO I OIX JAL	_

Outside Air Temperature ²	Fluid Concentration Fluid/Water By % Volume	Freezing Fog, Freezing Mist ³ , or Ice Crystals ⁴	Snow mixed with Freezing Fog ⁵	Snow, Snow Grains or Snow Pellets ^{6,7,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold- Soaked Wing ¹⁰	Other ¹¹
	100/0	0:42 - 1:24	0:15 - 0:30	0:23 - 0:42	0:27 - 0:49	0:19 - 0:27	0:05 - 0:34	
-3 °C and above (27 °F and above)	75/25	0:30 - 0:53	0:11 - 0:19	0:11 - 0:23	0:19 - 0:30	0:11 - 0:19	0:03 - 0:19	
(=: : :::::::::::::::::::::::::::::::::	50/50	0:11 - 0:23	0:04 - 0:08	0:05 - 0:11	0:07 - 0:11	0:05 - 0:07		
below -3 to -8 °C	100/0	0:23 - 0:34	0:11 - 0:23	0:15 - 0:30	0:15 - 0:34	0:11 - 0:15	-	
(below 27 to 18 °F)	75/25	0:19 - 0:42	0:07 - 0:11	0:08 - 0:19	0:11 - 0:23	0:06 - 0:11	-	
below -8 to -14 °C	100/0	0:23 - 0:34	0:08 - 0:19	0:11 - 0:23	0:15 - 0:34 ¹²	0:11 - 0:15 ¹²	0411710	
(below 18 to 7 °F)	75/25	0:19 - 0:42	0:05 - 0:11	0:07 - 0:15	0:11 - 0:23 ¹²	0:06 - 0:11 ¹²	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:11 - 0:15	0:01 - 0:04	0:02 - 0:05			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:11 - 0:15	0:00 - 0:02	0:01 - 0:02				
below -25 °C to LOUT ¹³ (below -13 °F to LOUT)	100/0	0:11 - 0:15	0:00 - 0:00	0:00 - 0:01				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT. NOTES

- 1 To use the HOTs in this table, ensure that the fluid and dilution being used is listed in the Type II Fluids Tested for Anti-Icing Performance and Aerodynamic Acceptance table (Table 50). Any restrictions on the use of the fluid have to be identified and applied.
- 2 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 12 No holdover time guidelines exist for this condition below -10 °C (14 °F).
- 13 If the LOUT is unknown, no holdover time guidelines exist below -25 °C (-13 °F).

CAUTIONS

TABLE ADJ-5: ADJUSTED TYPE II HOLDOVER TIMES FOR ABAX ECOWING AD-2

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:01 - 2:17	0:23 - 0:42	1:50 - 2:13	0:57 - 1:50	0:30 - 0:57	0:30 - 1:16	0:23 - 0:34	0:07 - 1:05	
-3 °C and above (27 °F and above)	75/25	0:57 - 1:05	0:15 - 0:30	1:20 - 1:39	0:42 - 1:20	0:19 - 0:42	0:27 - 0:49	0:15 - 0:23	0:03 - 0:38	
(== : : :::::::::::::::::::::::::::::::	50/50	0:11 - 0:23	0:04 - 0:08	0:27 - 0:30	0:11 - 0:27	0:05 - 0:11	0:07 - 0:11	0:05 - 0:07		•
below -3 to -8 °C	100/0	0:34 - 1:54	0:19 - 0:34	1:31 - 1:50	0:46 - 1:31	0:23 - 0:46	0:19 - 0:53	0:15 - 0:23		
(below 27 to 18 °F)	75/25	0:27 - 1:27	0:15 - 0:27	1:16 - 1:35	0:38 - 1:16	0:19 - 0:38	0:11 - 0:42	0:15 - 0:27		
below -8 to -14 °C	100/0	0:34 - 1:54	0:15 - 0:30	1:20 - 1:35	0:42 - 1:20	0:23 - 0:42	0:19 - 0:53 ¹¹	0:15 - 0:23 ¹¹	CALITIO	
(below 18 to 7 °F)	75/25	0:27 - 1:27	0:15 - 0:27	1:12 - 1:31	0:38 - 1:12	0:19 - 0:38	0:11 - 0:4211	0:15 - 0:27 ¹¹	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:11 - 0:30	0:01 - 0:04	0:15 - 0:23	0:05 - 0:15	0:02 - 0:05			exist	
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:11 - 0:30	0:00 - 0:02	0:07 - 0:11	0:02 - 0:07	0:01 - 0:02				
below -25 to -27 °C (below -13 to -17 °F)	100/0	0:11 - 0:30	0:00 - 0:00	0:04 - 0:05	0:01 - 0:04	0:00 - 0:01				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-6: ADJUSTED TYPE II HOLDOVER TIMES FOR AVIATION XI'AN HIGH-TECH CLEANWING II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	0:42 - 1:24	0:15 - 0:30	1:12 - 1:27	0:42 - 1:12	0:23 - 0:42	0:27 - 0:49	0:19 - 0:27	0:08 - 0:42	
-3 °C and above (27 °F and above)	75/25	0:38 - 1:01	0:15 - 0:27	1:01 - 1:16	0:34 - 1:01	0:19 - 0:34	0:27 - 0:46	0:15 - 0:23	0:05 - 0:38	
(=: : :::::::::::::::::::::::::::::::::	50/50	0:27 - 0:46	0:08 - 0:15	0:38 - 0:49	0:19 - 0:38	0:11 - 0:19	0:15 - 0:30	0:08 - 0:15		•
below -3 to -8 °C	100/0	0:34 - 1:24	0:11 - 0:23	1:01 - 1:12	0:30 - 1:01	0:19 - 0:30	0:23 - 0:42	0:15 - 0:19		
(below 27 to 18 °F)	75/25	0:30 - 1:20	0:15 - 0:27	1:01 - 1:12	0:34 - 1:01	0:19 - 0:34	0:27 - 0:30	0:15 - 0:19		
below -8 to -14 °C	100/0	0:34 - 1:24	0:11 - 0:19	0:49 - 1:01	0:27 - 0:49	0:15 - 0:27	0:23 - 0:4211	0:15 - 0:19 ¹¹	CAUTIO No holdove	
(below 18 to 7 °F)	75/25	0:30 - 1:20	0:15 - 0:27	1:01 - 1:12	0:34 - 1:01	0:19 - 0:34	0:27 - 0:3011	0:15 - 0:19 ¹¹	guidelines	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:15 - 0:38	0:07 - 0:15	0:34 - 0:46	0:19 - 0:34	0:11 - 0:19				
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:15 - 0:38	0:04 - 0:08	0:23 - 0:27	0:11 - 0:23	0:05 - 0:11				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-7: ADJUSTED TYPE II HOLDOVER TIMES FOR CLARIANT SAFEWING MP II FLIGHT

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:40 - 3:02	0:34 - 0:53	1:58 - 2:21	1:12 - 1:58	0:46 - 1:12	1:01 - 1:31	0:34 - 1:05	0:08 - 1:08	
-3 °C and above (27 °F and above)	75/25	1:24 - 2:05	0:23 - 0:46	1:58 - 2:24	1:01 - 1:58	0:30 - 1:01	0:53 - 1:08	0:23 - 0:42	0:05 - 0:38	
(=: : : :::::::::::::::::::::::::::::::	50/50	0:42 - 1:20	0:07 - 0:15	0:34 - 0:42	0:19 - 0:34	0:08 - 0:19	0:15 - 0:23	0:08 - 0:11		
below -3 to -8 °C	100/0	0:42 - 1:20	0:27 - 0:46	1:35 - 1:54	0:57 - 1:35	0:34 - 0:57	0:27 - 1:08	0:19 - 0:34		
(below 27 to 18 °F)	75/25	0:19 - 0:49	0:15 - 0:30	1:20 - 1:39	0:42 - 1:20	0:23 - 0:42	0:19 - 0:53	0:15 - 0:27		
below -8 to -14 °C	100/0	0:42 - 1:20	0:23 - 0:38	1:24 - 1:39	0:49 - 1:24	0:30 - 0:49	0:27 - 1:0811	0:19 - 0:34 ¹¹	CALITIO	
(below 18 to 7 °F)	75/25	0:19 - 0:49	0:11 - 0:23	1:01 - 1:16	0:30 - 1:01	0:15 - 0:30	0:19 - 0:53 ¹¹	0:15 - 0:27 ¹¹	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:23 - 0:38	0:05 - 0:15	0:53 - 1:16	0:19 - 0:53	0:06 - 0:19			exist	
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:23 - 0:38	0:02 - 0:05	0:23 - 0:30	0:08 - 0:23	0:02 - 0:08				
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:23 - 0:38	0:01 - 0:04	0:15 - 0:23	0:05 - 0:15	0:02 - 0:05				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-8: ADJUSTED TYPE II HOLDOVER TIMES FOR CRYOTECH POLAR GUARD® II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:09 - 3:02	0:38 - 1:05	2:28 - 2:59	1:27 - 2:28	0:49 - 1:27	1:12 - 1:31	0:57 - 1:08	0:11 - 1:31	
-3 °C and above (27 °F and above)	75/25	1:54 - 3:02	0:23 - 0:49	2:17 - 2:55	1:05 - 2:17	0:30 - 1:05	1:16 - 1:31	0:30 - 0:53	0:07 - 1:16	
(=: : :::::::::::::::::::::::::::::::::	50/50	0:38 - 1:05	0:05 - 0:15	0:53 - 1:12	0:19 - 0:53	0:08 - 0:19	0:15 - 0:34	0:07 - 0:15		
below -3 to -8 °C	100/0	0:42 - 1:54	0:27 - 0:49	1:50 - 2:09	1:05 - 1:50	0:38 - 1:05	0:27 - 1:12	0:27 - 0:34		
(below 27 to 18 °F)	75/25	0:30 - 1:08	0:19 - 0:38	1:46 - 2:17	0:49 - 1:46	0:23 - 0:49	0:19 - 0:49	0:27 - 0:34		
below -8 to -14 °C	100/0	0:42 - 1:54	0:23 - 0:38	1:31 - 1:46	0:53 - 1:31	0:30 - 0:53	0:27 - 1:1211	0:27 - 0:3411	OALITIO	
(below 18 to 7 °F)	75/25	0:30 - 1:08	0:15 - 0:34	1:31 - 1:54	0:42 - 1:31	0:19 - 0:42	0:19 - 0:4911	0:27 - 0:3411	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:19 - 0:38	0:06 - 0:19	1:12 - 1:43	0:27 - 1:12	0:08 - 0:27			exist	
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:19 - 0:38	0:02 - 0:08	0:30 - 0:42	0:11 - 0:30	0:03 - 0:11				
below -25 to -30.5 °C (below -13 to -23 °F)	100/0	0:19 - 0:38	0:02 - 0:04	0:19 - 0:23	0:05 - 0:19	0:02 - 0:05				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-9: ADJUSTED TYPE II HOLDOVER TIMES FOR KILFROST ABC-K PLUS

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Freezing Fog, Freezing Mist ² , or Ice Crystals ³	Snow mixed with Freezing Fog ⁴	Snow, Snow Grains or Snow Pellets ^{5,6,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold- Soaked Wing ⁹	Other ¹⁰
	100/0	1:43 - 2:51	0:34 - 0:57	0:46 - 1:16	1:24 - 1:31	0:46 - 1:05	0:15 - 1:31	
-3 °C and above (27 °F and above)	75/25	1:16 - 1:54	0:19 - 0:38	0:27 - 0:53	1:05 - 1:31	0:38 - 0:53	0:11 - 1:31	
(=	50/50	0:27 - 0:49	0:04 - 0:08	0:05 - 0:11	0:15 - 0:23	0:08 - 0:11		
below -3 to -8 °C	100/0	0:23 - 0:49	0:30 - 0:53	0:42 - 1:08	0:19 - 0:46	0:11 - 0:27		
(below 27 to 18 °F)	75/25	0:19 - 1:05	0:19 - 0:38	0:27 - 0:49	0:15 - 0:42	0:07 - 0:23		
below -8 to -14 °C	100/0	0:23 - 0:49	0:30 - 0:49	0:38 - 1:05	0:19 - 0:46 ¹¹	0:11 - 0:27 ¹¹	0.447	
(below 18 to 7 °F)	75/25	0:19 - 1:05	0:19 - 0:38	0:27 - 0:49	0:15 - 0:42 ¹¹	0:07 - 0:2311	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:23 - 0:42	0:01 - 0:04	0:02 - 0:05			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:23 - 0:42	0:00 - 0:02	0:01 - 0:02				
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:23 - 0:42	0:00 - 0:00	0:00 - 0:01				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-10: ADJUSTED TYPE II HOLDOVER TIMES FOR KILFROST ICE CLEAR II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	1:05 - 1:50	0:23 - 0:46	1:50 - 2:13	1:01 - 1:50	0:30 - 1:01	0:46 - 1:12	0:30 - 0:49	0:11 - 1:31		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(== : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	0:49 - 1:58	0:23 - 0:38	1:39 - 1:58	0:53 - 1:39	0:30 - 0:53	0:23 - 0:57	0:27 - 0:42			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	0:49 - 1:58	0:19 - 0:38	1:31 - 1:50	0:49 - 1:31	0:27 - 0:49	0:23 - 0:5711	0:27 - 0:4211	0.441710		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:27 - 0:34	0:08 - 0:15	0:42 - 0:49	0:23 - 0:42	0:11 - 0:23		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:27 - 0:34	0:05 - 0:08	0:23 - 0:27	0:11 - 0:23	0:06 - 0:11					
below -25 to -28 °C (below -13 to -18 °F)	100/0	0:27 - 0:34	0:04 - 0:07	0:19 - 0:23	0:08 - 0:19	0:05 - 0:08					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-11: ADJUSTED TYPE II HOLDOVER TIMES FOR MKS DEVO CHEMICALS COREICEPHOB TYPE II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	1:27 - 2:05	0:23 - 0:46	1:58 - 2:24	1:05 - 1:58	0:30 - 1:05	0:53 - 1:31	0:34 - 0:46	0:11 - 1:12		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(=: : :::::::::::::::::::::::::::::::::	50/50	0:49 - 1:20	0:11 - 0:27	1:12 - 1:27	0:34 - 1:12	0:19 - 0:34	0:38 - 0:57	0:19 - 0:23			
below -3 to -8 °C	100/0	0:34 - 1:05	0:19 - 0:34	1:24 - 1:43	0:46 - 1:24	0:23 - 0:46	0:23 - 0:53	0:19 - 0:27			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	0:34 - 1:05	0:15 - 0:27	1:08 - 1:24	0:38 - 1:08	0:19 - 0:38	0:23 - 0:5311	0:19 - 0:2711	OALITIO		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:11 - 0:19	0:01 - 0:04	0:15 - 0:23	0:05 - 0:15	0:02 - 0:05		guidelines exis			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:11 - 0:19	0:00 - 0:02	0:07 - 0:11	0:02 - 0:07	0:01 - 0:02					
below -25 to -27 °C (below -13 to -17 °F)	100/0	0:11 - 0:19	0:00 - 0:00	0:04 - 0:05	0:01 - 0:04	0:00 - 0:01					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-12: ADJUSTED TYPE II HOLDOVER TIMES FOR NEWAVE AEROCHEMICAL FCY-2

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Freezing Fog, Freezing Mist ² , or Ice Crystals ³	Snow mixed with Freezing Fog⁴	Snow, Snow Grains or Snow Pellets ^{5,6,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold- Soaked Wing ⁹	Other ¹⁰
	100/0	0:57 - 1:50	0:19 - 0:30	0:23 - 0:42	0:27 - 0:49	0:19 - 0:27	0:06 - 0:34	
-3 °C and above (27 °F and above)	75/25	0:38 - 1:08	0:11 - 0:23	0:15 - 0:30	0:19 - 0:34	0:11 - 0:19	0:04 - 0:19	
(=: : aa assis)	50/50	0:19 - 0:27	0:07 - 0:15	0:11 - 0:19	0:08 - 0:15	0:05 - 0:08		
below -3 to -8 °C	100/0	0:34 - 1:08	0:11 - 0:23	0:15 - 0:30	0:15 - 0:34	0:11 - 0:15		
(below 27 to 18 °F)	75/25	0:23 - 0:49	0:08 - 0:15	0:11 - 0:19	0:11 - 0:23	0:06 - 0:11		
below -8 to -14 °C	100/0	0:34 - 1:08	0:08 - 0:19	0:11 - 0:23	0:15 - 0:34 ¹¹	0:11 - 0:15 ¹¹	0.447	
(below 18 to 7 °F)	75/25	0:23 - 0:49	0:06 - 0:11	0:08 - 0:15	0:11 - 0:23 ¹¹	0:06 - 0:11 ¹¹	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:19 - 0:27	0:01 - 0:04	0:02 - 0:05			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:19 - 0:27	0:00 - 0:02	0:01 - 0:02				
below -25 to -28 °C (below -13 to -18 °F)	100/0	0:19 - 0:27	0:00 - 0:00	0:00 - 0:01				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-13: ADJUSTED TYPE II HOLDOVER TIMES FOR ROMCHIM ADD-PROTECT NG TYPE II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	0:53 - 1:50	0:19 - 0:42	1:58 - 2:28	0:53 - 1:58	0:27 - 0:53	0:38 - 1:01	0:27 - 0:38	0:05 - 0:53	
-3 °C and above (27 °F and above)	75/25	0:46 - 1:24	0:15 - 0:30	1:27 - 1:50	0:42 - 1:27	0:19 - 0:42	0:30 - 0:57	0:19 - 0:30	0:05 - 0:42	
(=: : : :::::::::::::::::::::::::::::::	50/50	0:19 - 0:42	0:08 - 0:15	0:42 - 0:49	0:23 - 0:42	0:11 - 0:23	0:15 - 0:27	0:08 - 0:15		
below -3 to -8 °C	100/0	0:42 - 1:12	0:15 - 0:30	1:24 - 1:46	0:38 - 1:24	0:19 - 0:38	0:27 - 0:53	0:19 - 0:27		
(below 27 to 18 °F)	75/25	0:42 - 1:05	0:11 - 0:23	1:05 - 1:20	0:30 - 1:05	0:15 - 0:30	0:19 - 0:49	0:15 - 0:23		
below -8 to -14 °C	100/0	0:42 - 1:12	0:11 - 0:23	1:05 - 1:24	0:30 - 1:05	0:15 - 0:30	0:27 - 0:5311	0:19 - 0:2711	CALITIO	NI.
(below 18 to 7 °F)	75/25	0:42 - 1:05	0:08 - 0:19	0:49 - 1:05	0:23 - 0:49	0:11 - 0:23	0:19 - 0:49 ¹¹	0:15 - 0:23 ¹¹	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:11 - 0:15	0:01 - 0:04	0:15 - 0:23	0:05 - 0:15	0:02 - 0:05			exist	
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:11 - 0:15	0:00 - 0:02	0:07 - 0:11	0:02 - 0:07	0:01 - 0:02				
below -25 to -28 °C (below -13 to -18 °F)	100/0	0:11 - 0:15	0:00 - 0:00	0:04 - 0:05	0:01 - 0:04	0:00 - 0:01				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-14: ADJUSTED TYPE II HOLDOVER TIMES FOR ROMCHIM ADD-PROTECT TYPE II

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:16 - 2:40	0:15 - 0:34	1:27 - 1:50	0:46 - 1:27	0:23 - 0:46	0:30 - 1:12	0:19 - 0:34	0:07 - 0:38	
-3 °C and above (27 °F and above)	75/25	0:30 - 0:53	0:11 - 0:19	0:46 - 0:53	0:23 - 0:46	0:11 - 0:23	0:19 - 0:30	0:11 - 0:19	0:04 - 0:19	
(=: -: -: -: -: -: -: -: -: -: -: -: -: -:	50/50	0:15 - 0:27	0:05 - 0:11	0:23 - 0:27	0:11 - 0:23	0:07 - 0:11	0:08 - 0:23	0:06 - 0:08		•
below -3 to -8 °C	100/0	0:23 - 0:34	0:11 - 0:23	1:01 - 1:16	0:30 - 1:01	0:15 - 0:30	0:19 - 0:38	0:15 - 0:23		
(below 27 to 18 °F)	75/25	0:23 - 0:42	0:07 - 0:11	0:30 - 0:38	0:19 - 0:30	0:08 - 0:19	0:15 - 0:23	0:11 - 0:15		
below -8 to -14 °C	100/0	0:23 - 0:34	0:11 - 0:19	0:49 - 1:01	0:27 - 0:49	0:11 - 0:27	0:19 - 0:3811	0:15 - 0:23 ¹¹	OALITIO	
(below 18 to 7 °F)	75/25	0:23 - 0:42	0:05 - 0:11	0:27 - 0:30	0:15 - 0:27	0:07 - 0:15	0:15 - 0:23 ¹¹	0:11 - 0:15 ¹¹	CAUTION: No holdover time	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:11 - 0:19	0:01 - 0:04	0:15 - 0:23	0:05 - 0:15	0:02 - 0:05	guidelines exis			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:11 - 0:19	0:00 - 0:02	0:07 - 0:11	0:02 - 0:07	0:01 - 0:02				
below -25 to -28 °C (below -13 to -18 °F)	100/0	0:11 - 0:19	0:00 - 0:00	0:04 - 0:05	0:01 - 0:04	0:00 - 0:01				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type II fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

ADJUSTED HOT GUIDELINES FOR SAE TYPE III FLUIDS WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

- The responsibility for the application of these data remains with the user.
- The time of protection will be shortened in heavy weather conditions. Heavy precipitation rates or high moisture content, high wind velocity jet blast, or blowing snow may reduce holdover time below the lowest time stated in the range.
 Holdover time may be reduced when aircraft skin temperature is lower than outside air temperature.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.

TABLE ADJ-15: ADJUSTED TYPE III HOLDOVER TIMES FOR ALLCLEAR AEROCLEAR MAX APPLIED UNHEATED ON LOW SPEED AIRCRAFT¹

Outside Air Temperature ²	Fluid Concentration Fluid/Water By % Volume	Mist ³ , or Ice	Snow mixed with Freezing Fog⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold-Soaked Wing ¹⁰	Other ¹¹
	100/0	0:34 - 1:27	0:10 - 0:23	1:01 - 1:20	0:30 - 1:01	0:14 - 0:30	0:19 - 0:38	0:11 - 0:19	0:04 - 0:30	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		-
below -3 to -10 °C	100/0	0:38 - 1:16	0:10 - 0:23	1:01 - 1:20	0:30 - 1:01	0:14 - 0:30	0:19 - 0:34	0:11 - 0:19	CAUTIO	N:
(below 27 to 14 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	No holdover time guidelines exist	
below -10 to -16 °C (below 14 to 3 °F)	100/0	0:30 - 1:20	0:10 - 0:23	1:01 - 1:20	0:30 - 1:01	0:14 - 0:30				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 These holdover times are for aircraft conforming to the SAE AS5900 low speed aerodynamic test criterion. Fluid must be applied unheated to use these holdover times. No holdover times exist for this fluid applied heated. If uncertain whether the aircraft conforms to the low, middle, or high speed aerodynamic test criterion, no holdover time guidelines exist below -16°C (3°F).
- 2 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type III fluid cannot be used.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.

CAUTIONS

TABLE ADJ-16: ADJUSTED TYPE III HOLDOVER TIMES FOR ALLCLEAR AEROCLEAR MAX APPLIED UNHEATED ON MIDDLE SPEED AIRCRAFT¹

Outside Air Temperature ²	Fluid Concentration Fluid/Water By % Volume	Mist ³ , or Ice	Snow mixed with Freezing Fog⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold-Soaked Wing ¹⁰	Other ¹¹
	100/0	0:34 - 1:27	0:10 - 0:23	1:01 - 1:20	0:30 - 1:01	0:14 - 0:30	0:19 - 0:38	0:11 - 0:19	0:04 - 0:30	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(=: : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		•
below -3 to -10 °C	100/0	0:38 - 1:16	0:10 - 0:23	1:01 - 1:20	0:30 - 1:01	0:14 - 0:30	0:19 - 0:34	0:11 - 0:19	CAUTIO	N:
(below 27 to 14 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	No holdover time guidelines exist	
below -10 to -20.5 °C (below 14 to -5 °F)	100/0	0:30 - 1:20	0:10 - 0:23	1:01 - 1:20	0:30 - 1:01	0:14 - 0:30			. ga.ac	

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 These holdover times are for aircraft conforming to the SAE AS5900 middle speed aerodynamic test criterion. Fluid must be applied unheated to use these holdover times. No holdover times exist for this fluid applied heated. If uncertain whether the aircraft conforms to the low, middle, or high speed aerodynamic test criterion, no holdover time guidelines exist below -16°C (3°F).
- 2 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type III fluid cannot be used.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.

CAUTIONS

TABLE ADJ-17: ADJUSTED TYPE III HOLDOVER TIMES FOR ALLCLEAR AEROCLEAR MAX APPLIED UNHEATED ON HIGH SPEED AIRCRAFT¹

Outside Air Temperature ²	Fluid Concentration Fluid/Water By % Volume	Mist ³ , or Ice	Snow mixed with Freezing Fog⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold-Soaked Wing ¹⁰	Other ¹¹
	100/0	0:34 - 1:27	0:10 - 0:23	1:01 - 1:20	0:30 - 1:01	0:14 - 0:30	0:19 - 0:38	0:11 - 0:19	0:04 - 0:30	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(== : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		•
below -3 to -10 °C	100/0	0:38 - 1:16	0:10 - 0:23	1:01 - 1:20	0:30 - 1:01	0:14 - 0:30	0:19 - 0:34	0:11 - 0:19		
(below 27 to 14 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTION:	
below -10 to -25 °C (below 14 to -13 °F)	100/0	0:30 - 1:20	0:10 - 0:23	1:01 - 1:20	0:30 - 1:01	0:14 - 0:30			No holdover time guidelines exist	
below -25 to -35 °C (below -13 to -31 °F)	100/0	0:19 - 0:46	0:05 - 0:12	0:34 - 0:46	0:15 - 0:34	0:08 - 0:15				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 These holdover times are for aircraft conforming to the SAE AS5900 high speed aerodynamic test criterion. Fluid must be applied unheated to use these holdover times. No holdover times exist for this fluid applied heated. If uncertain whether the aircraft conforms to the low, middle, or high speed aerodynamic test criterion, no holdover time guidelines exist below -16°C (3°F).
- 2 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type III fluid cannot be used.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-44 provides allowance times for ice pellets and small hail for SAE Type III fluids, applied unheated).

CAUTIONS

ADJUSTED HOT GUIDELINES FOR SAE TYPE IV FLUIDS WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

- The responsibility for the application of these data remains with the user.
- The time of protection will be shortened in heavy weather conditions. Heavy precipitation rates or high moisture content, high wind velocity jet blast, or blowing snow may reduce holdover time below the lowest time stated in the range.
 Holdover time may be reduced when aircraft skin temperature is lower than outside air temperature.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.
- Whenever frost or ice occurs on the lower surface of the wing in the area of the fuel tank, indicating a cold-soaked wing, the 50/50 dilutions of Type II or IV shall not be used for the anti-icing step because fluid freezing may occur.

TABLE ADJ-18: ADJUSTED GENERIC HOLDOVER TIMES FOR SAE TYPE IV FLUIDS1

Outside Air Temperature ²	Fluid Concentration Fluid/Water By % Volume	Mint3 or loo	Snow mixed with Freezing Fog ⁵	Very Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Light Snow, Snow Grains or Snow Pellets ^{6,7,8}	Moderate Snow, Snow Grains or Snow Pellets ^{6,8}	Freezing Drizzle ⁹	Light Freezing Rain	Rain on Cold-Soaked Wing ¹⁰	Other ¹¹	
	100/0	0:57 - 1:43	0:19 - 0:34	1:27 - 1:46	0:46 - 1:27	0:23 - 0:46	0:30 - 0:53	0:15 - 0:27	0:06 - 0:49		
-3 °C and above (27 °F and above)	75/25	1:05 - 2:02	0:23 - 0:42	1:35 - 1:50	0:57 - 1:35	0:30 - 0:57	0:46 - 1:01	0:23 - 0:38	0:07 - 1:01		
(=:	50/50	0:23 - 0:42	0:05 - 0:15	0:46 - 0:53	0:19 - 0:46	0:08 - 0:19	0:11 - 0:30	0:07 - 0:15			
below -3 to -8 °C	100/0	0:11 - 0:27	0:15 - 0:30	1:20 - 1:35	0:42 - 1:20	0:19 - 0:42	0:19 - 0:53	0:15 - 0:19			
(below 27 to 18 °F)	75/25	0:30 - 1:01	0:19 - 0:38	1:24 - 1:39	0:49 - 1:24	0:23 - 0:49	0:15 - 0:49	0:11 - 0:19			
below -8 to -14 °C	100/0	0:11 - 0:27	0:11 - 0:27	1:08 - 1:24	0:34 - 1:08	0:15 - 0:34	0:19 - 0:5312	0:15 - 0:19 ¹²	0.44174.0		
(below 18 to 7 °F)	75/25	0:30 - 1:01	0:15 - 0:34	1:20 - 1:31	0:42 - 1:20	0:19 - 0:42	0:15 - 0:4912	0:11 - 0:19 ¹²	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:11 - 0:23	0:01 - 0:05	0:23 - 0:34	0:07 - 0:23	0:02 - 0:07		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:11 - 0:23	0:00 - 0:02	0:08 - 0:15	0:02 - 0:08	0:01 - 0:02					
below -25 °C to LOUT ¹³ (below -13 °F to LOUT)	1 (1(1/(1	0:11 - 0:23	0:00 - 0:01	0:05 - 0:08	0:02 - 0:05	0:00 - 0:02					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT. NOTES

- 1 To use the HOTs in this table, ensure that the fluid and dilution being used is listed in the Type IV Fluids Tested for Anti-Icing Performance and Aerodynamic Acceptance table (Table 52). Any restrictions on the use of the fluid have to be identified and applied.
- 2 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 3 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 4 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 5 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 6 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 7 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 8 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 9 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 10 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 11 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-45 provides allowance times for Type IV EG fluids and Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail. If the glycol type is unknown, the allowance times for SAE Type IV PG fluids should be used).
- 12 No holdover time guidelines exist for this condition below -10 °C (14 °F).
- 13 If the LOUT is unknown, no holdover time guidelines exist below -25.5 °C (-14 °F).

CAUTIONS

TARIF AD I-10.	· AD IIISTED I	ADE IN HUI D	OVER TIMES F	OR ABAX ECOWIN	AC VD-40
IADLE ADJ-13.	. ADJUJIED I	IFE IV HOLD	OVER HIMES I	ON ADAX ECUVVII	1G AD-43

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	2:32 - 3:02	0:34 - 1:05	2:47 - 3:00	1:27 - 2:47	0:46 - 1:27	1:05 - 1:31	0:46 - 1:05	0:08 - 1:27		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(2. 1 and above)	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	0:15 - 1:12	0:27 - 0:49	2:13 - 2:40	1:08 - 2:13	0:34 - 1:08	0:19 - 1:05	0:15 - 0:19			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	0:15 - 1:12	0:23 - 0:42	1:50 - 2:17	0:57 - 1:50	0:30 - 0:57	0:19 - 1:05 ¹¹	0:15 - 0:19 ¹¹	0.441710		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:19 - 0:30	0:01 - 0:05	0:23 - 0:34	0:07 - 0:23	0:02 - 0:07		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:19 - 0:30	0:00 - 0:02	0:08 - 0:15	0:02 - 0:08	0:01 - 0:02					
below -25 to -26 °C (below -13 to -15 °F)	100/0	0:19 - 0:30	0:00 - 0:01	0:05 - 0:08	0:02 - 0:05	0:00 - 0:02					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-20: ADJUSTED TYPE IV HOLDOVER TIMES FOR ALAB INTERNATIONAL PROFLIGHT EG4

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	2:21 - 3:02	0:34 - 1:05	2:43 - 3:00	1:24 - 2:43	0:46 - 1:24	1:05 - 1:31	0:30 - 0:46	0:08 - 1:31		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(2. 1 and above)	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	1:54 - 2:59	0:34 - 1:05	2:43 - 3:00	1:24 - 2:43	0:46 - 1:24	0:49 - 1:31	0:38 - 1:12			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	1:54 - 2:59	0:34 - 1:05	2:43 - 3:00	1:24 - 2:43	0:46 - 1:24	0:49 - 1:3111	0:38 - 1:1211	0.411710		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:27 - 1:12	0:05 - 0:15	0:38 - 0:49	0:19 - 0:38	0:08 - 0:19		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:27 - 1:12	0:02 - 0:08	0:30 - 0:42	0:11 - 0:30	0:04 - 0:11					
below -25 to -26 °C (below -13 to -15 °F)	100/0	0:27 - 1:12	0:01 - 0:05	0:19 - 0:27	0:06 - 0:19	0:02 - 0:06					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-45 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-21: ADJUSTED TYPE IV HOLDOVER TIMES FOR ALAB INTERNATIONAL PROFLIGHT PG4

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	1:05 - 1:43	0:23 - 0:46	2:02 - 2:32	1:01 - 2:02	0:30 - 1:01	0:49 - 1:05	0:30 - 0:38	0:11 - 1:01		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(== : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	0:49 - 1:46	0:19 - 0:38	1:46 - 2:13	0:53 - 1:46	0:27 - 0:53	0:34 - 0:53	0:27 - 0:34			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	0:49 - 1:46	0:15 - 0:34	1:35 - 1:58	0:46 - 1:35	0:23 - 0:46	0:34 - 0:5311	0:27 - 0:3411	0.441710		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:27 - 0:38	0:01 - 0:05	0:23 - 0:34	0:07 - 0:23	0:02 - 0:07		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:27 - 0:38	0:00 - 0:02	0:08 - 0:15	0:02 - 0:08	0:01 - 0:02					
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:27 - 0:38	0:00 - 0:01	0:05 - 0:08	0:02 - 0:05	0:00 - 0:02					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

	_		
TADIE ADIAM.	AD HIGHED TVDE		S FOR ALLCLEAR CLEARWING EG
		· IV H() I)()V E	. E()
IADLL ADJ-22.	ADJUSILD LIFL	. IV HOLDOVLK HIVILS) I ON ALLCLEAN CLEANWING LG

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	1:24 - 2:28	0:23 - 0:46	2:02 - 2:32	1:01 - 2:02	0:30 - 1:01	0:53 - 1:12	0:23 - 0:46	0:08 - 1:08		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(=: : :::::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	1:12 - 2:51	0:19 - 0:42	1:50 - 2:17	0:53 - 1:50	0:27 - 0:53	0:49 - 1:08	0:23 - 0:46			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	1:12 - 2:51	0:19 - 0:38	1:43 - 2:05	0:49 - 1:43	0:23 - 0:49	0:49 - 1:0811	0:23 - 0:4611	0.441710		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:42 - 1:31	0:11 - 0:27	1:12 - 1:35	0:34 - 1:12	0:15 - 0:34		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:42 - 1:31	0:07 - 0:15	0:42 - 0:53	0:19 - 0:42	0:11 - 0:19					
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:42 - 1:31	0:05 - 0:11	0:34 - 0:42	0:15 - 0:34	0:08 - 0:15					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-45 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-23: ADJUSTED TYPE IV HOLDOVER TIMES FOR ASGLOBAL 4FLITE EG

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	1:12 - 2:28	0:19 - 0:34	1:35 - 1:58	0:46 - 1:35	0:23 - 0:46	0:30 - 0:53	0:15 - 0:27	0:06 - 0:49		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(=: : :::::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	1:05 - 2:05	0:15 - 0:30	1:24 - 1:43	0:42 - 1:24	0:19 - 0:42	0:30 - 0:53	0:15 - 0:27			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	1:05 - 2:05	0:15 - 0:27	1:12 - 1:31	0:38 - 1:12	0:19 - 0:38	0:30 - 0:5311	0:15 - 0:27 ¹¹	0.441710		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:38 - 1:05	0:11 - 0:27	1:12 - 1:31	0:34 - 1:12	0:15 - 0:34		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:38 - 1:05	0:11 - 0:23	1:01 - 1:16	0:27 - 1:01	0:15 - 0:27					
below -25 to -30 °C (below -13 to -22 °F)	100/0	0:23 - 0:49	0:07 - 0:15	0:42 - 0:49	0:19 - 0:42	0:08 - 0:19					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-24: ADJUSTED TYPE IV HOLDOVER TIMES FOR ASGLOBAL 4FLITE PG

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	1:24 - 2:28	0:30 - 0:53	2:09 - 2:36	1:12 - 2:09	0:38 - 1:12	0:53 - 1:12	0:34 - 0:49	0:11 - 1:01		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	0:49 - 1:27	0:23 - 0:38	1:35 - 1:54	0:53 - 1:35	0:27 - 0:53	0:42 - 0:53	0:27 - 0:42			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	0:49 - 1:27	0:15 - 0:30	1:16 - 1:31	0:42 - 1:16	0:23 - 0:42	0:42 - 0:5311	0:27 - 0:4211	0.441710		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:23 - 0:34	0:11 - 0:19	0:49 - 1:01	0:27 - 0:49	0:11 - 0:27		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:23 - 0:34	0:05 - 0:11	0:27 - 0:34	0:15 - 0:27	0:07 - 0:15					
below -25 to -26 °C (below -13 to -15 °F)	100/0	0:23 - 0:34	0:05 - 0:11	0:27 - 0:34	0:15 - 0:27	0:06 - 0:15					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-25: ADJUSTED TYPE IV HOLDOVER TIMES FOR AVIAFLUID AVIAFLIGHT EG

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	1:08 - 2:21	0:23 - 0:38	1:27 - 1:46	0:53 - 1:27	0:30 - 0:53	0:49 - 1:31	0:23 - 0:38	0:08 - 1:31		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(=: : :::::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	1:01 - 2:17	0:19 - 0:34	1:20 - 1:35	0:46 - 1:20	0:27 - 0:46	0:42 - 1:08	0:27 - 0:38			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	1:01 - 2:17	0:19 - 0:30	1:12 - 1:27	0:42 - 1:12	0:23 - 0:42	0:42 - 1:0811	0:27 - 0:3811	0.441710		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:27 - 1:20	0:15 - 0:30	1:16 - 1:31	0:38 - 1:16	0:19 - 0:38		guidelines exis			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:27 - 1:20	0:11 - 0:23	1:01 - 1:12	0:30 - 1:01	0:15 - 0:30					
below -25 to -31 °C (below -13 to -24 °F)	100/0	0:27 - 0:49	0:05 - 0:11	0:27 - 0:34	0:15 - 0:27	0:07 - 0:15					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-45 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-26: ADJUSTED TYPE IV HOLDOVER TIMES FOR AVIAFLUID AVIAFLIGHT PG

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰		
	100/0	1:43 - 3:02	0:30 - 0:57	2:17 - 2:47	1:16 - 2:17	0:42 - 1:16	1:31 - 1:31	0:53 - 1:27	0:15 - 1:31			
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		•		
below -3 to -8 °C	100/0	0:49 - 1:39	0:19 - 0:38	1:31 - 1:50	0:49 - 1:31	0:27 - 0:49	0:27 - 1:27	0:34 - 0:49				
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A				
below -8 to -14 °C	100/0	0:49 - 1:39	0:15 - 0:27	1:08 - 1:24	0:38 - 1:08	0:19 - 0:38	0:27 - 1:2711	0:34 - 0:4911	0.441710			
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove			
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:15 - 0:27	0:08 - 0:15	0:38 - 0:46	0:19 - 0:38	0:11 - 0:19		guidelines exist				
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:15 - 0:27	0:04 - 0:07	0:19 - 0:23	0:11 - 0:19	0:05 - 0:11						
below -25 to -25.5 °C (below -13 to -14 °F)	100/0	0:15 - 0:27	0:04 - 0:07	0:19 - 0:23	0:08 - 0:19	0:05 - 0:08						

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-27: ADJUSTED TYPE IV HOLDOVER TIMES FOR CHEMCO CHEMR EG IV

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	1:35 - 2:43	0:19 - 0:46	2:17 - 2:55	0:57 - 2:17	0:27 - 0:57	0:34 - 1:16	0:19 - 0:30	0:07 - 1:20		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(== : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	1:05 - 2:47	0:19 - 0:46	2:17 - 2:55	0:57 - 2:17	0:27 - 0:57	0:46 - 1:12	0:27 - 0:38			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	1:05 - 2:47	0:19 - 0:46	2:17 - 2:55	0:57 - 2:17	0:27 - 0:57	0:46 - 1:12 ¹¹	0:27 - 0:3811	0.441710		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:30 - 1:05	0:11 - 0:23	1:05 - 1:20	0:30 - 1:05	0:15 - 0:30		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:30 - 1:05	0:11 - 0:23	1:05 - 1:20	0:30 - 1:05	0:15 - 0:30					
below -25 to -27 °C (below -13 to -17 °F)	100/0	0:30 - 1:05	0:11 - 0:23	1:05 - 1:20	0:30 - 1:05	0:15 - 0:30					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-45 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ABLAS.	. AD IIIOTED '	TVDE			
					RICIDINIK IV
I ADLE ADJ-20.	. ADJUSIED	TYPE IV HOLDOVE	N HIVIES FUN	CHEINICO CHEININ	

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰		
	100/0	1:43 - 3:02	0:30 - 1:01	2:28 - 3:00	1:20 - 2:28	0:42 - 1:20	1:01 - 1:31	0:42 - 1:01	0:19 - 1:31			
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A				
below -3 to -8 °C	100/0	1:24 - 3:02	0:30 - 1:01	2:28 - 3:00	1:20 - 2:28	0:42 - 1:20	0:57 - 1:31	0:34 - 1:01				
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A				
below -8 to -14 °C	100/0	1:24 - 3:02	0:30 - 1:01	2:28 - 3:00	1:20 - 2:28	0:42 - 1:20	0:57 - 1:3111	0:34 - 1:01 ¹¹	CALITIO			
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove			
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:30 - 1:08	0:27 - 0:53	2:21 - 2:51	1:12 - 2:21	0:38 - 1:12		guidelines exis				
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:30 - 1:08	0:19 - 0:38	1:39 - 2:02	0:49 - 1:39	0:27 - 0:49						
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:30 - 1:08	0:15 - 0:30	1:24 - 1:43	0:42 - 1:24	0:23 - 0:42						

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-45 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-29: ADJUSTED TYPE IV HOLDOVER TIMES FOR CHONGQING JOBA CHEMICAL CO.,LTD FW-IV

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰	
	100/0	2:28 - 3:02	0:27 - 0:57	2:28 - 3:00	1:16 - 2:28	0:38 - 1:16	1:08 - 1:31	0:34 - 0:49	0:11 - 1:31		
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
(== : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -3 to -8 °C	100/0	1:54 - 3:02	0:23 - 0:46	2:05 - 2:36	1:05 - 2:05	0:30 - 1:05	0:38 - 1:31	0:27 - 0:53			
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
below -8 to -14 °C	100/0	1:54 - 3:02	0:23 - 0:42	1:50 - 2:17	0:57 - 1:50	0:27 - 0:57	0:38 - 1:3111	0:27 - 0:5311	0.441710		
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove		
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:27 - 1:16	0:15 - 0:30	1:31 - 1:58	0:42 - 1:31	0:19 - 0:42		guidelines exist			
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:27 - 1:16	0:11 - 0:23	1:01 - 1:20	0:27 - 1:01	0:11 - 0:27					
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:27 - 1:16	0:08 - 0:19	0:53 - 1:08	0:23 - 0:53	0:11 - 0:23					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-45 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-30: ADJUSTED TYPE IV HOLDOVER TIMES FOR CLARIANT SAFEWING MP IV LAUNCH

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	3:02 - 3:02	0:38 - 1:01	2:09 - 2:32	1:20 - 2:09	0:49 - 1:20	1:08 - 1:31	0:46 - 1:16	0:11 - 1:16	
-3 °C and above (27 °F and above)	75/25	2:47 - 3:02	0:34 - 1:01	2:21 - 2:47	1:20 - 2:21	0:46 - 1:20	1:16 - 1:31	0:34 - 0:57	0:08 - 1:20	
(= 1	50/50	1:05 - 2:05	0:15 - 0:27	1:05 - 1:16	0:34 - 1:05	0:19 - 0:34	0:23 - 0:38	0:15 - 0:19		
below -3 to -8 °C	100/0	0:46 - 1:27	0:30 - 0:49	1:50 - 2:09	1:08 - 1:50	0:42 - 1:08	0:27 - 1:16	0:19 - 0:34		
(below 27 to 18 °F)	75/25	0:30 - 1:01	0:30 - 0:53	2:02 - 2:28	1:08 - 2:02	0:38 - 1:08	0:19 - 0:53	0:19 - 0:34		
below -8 to -14 °C	100/0	0:46 - 1:27	0:27 - 0:46	1:39 - 1:54	1:01 - 1:39	0:38 - 1:01	0:27 - 1:16 ¹¹	0:19 - 0:34 ¹¹		
(below 18 to 7 °F)	75/25	0:30 - 1:01	0:27 - 0:46	1:50 - 2:13	1:05 - 1:50	0:34 - 1:05	0:19 - 0:53 ¹¹	0:19 - 0:34 ¹¹	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:23 - 0:38	0:04 - 0:11	0:57 - 1:20	0:15 - 0:57	0:05 - 0:15			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:23 - 0:38	0:02 - 0:05	0:23 - 0:34	0:07 - 0:23	0:02 - 0:07				
below -25 to -28.5 °C (below -13 to -19 °F)	100/0	0:23 - 0:38	0:01 - 0:03	0:15 - 0:23	0:05 - 0:15	0:01 - 0:05				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-31: ADJUSTED TYPE IV HOLDOVER TIMES FOR CLARIANT SAFEWING MP IV LAUNCH PLUS

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:59 - 3:02	0:30 - 1:12	3:00 - 3:00	1:35 - 3:00	0:42 - 1:35	1:31 - 1:31	0:46 - 1:31	0:15 - 1:31	
-3 °C and above (27 °F and above)	75/25	2:59 - 3:02	0:27 - 1:05	3:00 - 3:00	1:27 - 3:00	0:38 - 1:27	1:31 - 1:31	1:01 - 1:05	0:15 - 1:24	
(== : : :::::::::::::::::::::::::::::::	50/50	0:57 - 1:24	0:11 - 0:27	1:12 - 1:31	0:34 - 1:12	0:15 - 0:34	0:19 - 0:46	0:11 - 0:15		
below -3 to -8 °C	100/0	0:42 - 1:43	0:27 - 0:57	2:51 - 3:00	1:16 - 2:51	0:34 - 1:16	0:19 - 1:12	0:19 - 0:30		
(below 27 to 18 °F)	75/25	0:30 - 1:31	0:23 - 0:49	2:40 - 3:00	1:08 - 2:40	0:27 - 1:08	0:15 - 0:49	0:15 - 0:23		
below -8 to -14 °C	100/0	0:42 - 1:43	0:23 - 0:49	2:28 - 3:00	1:05 - 2:28	0:30 - 1:05	0:19 - 1:1211	0:19 - 0:30 ¹¹	0.441740	
(below 18 to 7 °F)	75/25	0:30 - 1:31	0:19 - 0:42	2:13 - 2:55	0:57 - 2:13	0:23 - 0:57	0:15 - 0:4911	0:15 - 0:2311	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:19 - 0:38	0:04 - 0:15	0:57 - 1:24	0:19 - 0:57	0:05 - 0:19		guidelines exis		
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:19 - 0:38	0:02 - 0:05	0:23 - 0:34	0:07 - 0:23	0:02 - 0:07				
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:19 - 0:38	0:01 - 0:03	0:15 - 0:23	0:05 - 0:15	0:02 - 0:05				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-32: ADJUSTED TYPE IV HOLDOVER TIMES FOR CRYOTECH POLAR GUARD® ADVANCE

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:09 - 3:02	0:38 - 1:05	2:28 - 2:59	1:27 - 2:28	0:49 - 1:27	1:12 - 1:31	0:57 - 1:08	0:11 - 1:31	
-3 °C and above (27 °F and above)	75/25	1:54 - 3:02	0:23 - 0:49	2:17 - 2:55	1:05 - 2:17	0:30 - 1:05	1:16 - 1:31	0:30 - 0:53	0:07 - 1:16	
(2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	50/50	0:38 - 1:05	0:05 - 0:15	0:53 - 1:12	0:19 - 0:53	0:08 - 0:19	0:15 - 0:34	0:07 - 0:15		
below -3 to -8 °C	100/0	0:42 - 1:54	0:27 - 0:49	1:50 - 2:09	1:05 - 1:50	0:38 - 1:05	0:27 - 1:12	0:27 - 0:34		
(below 27 to 18 °F)	75/25	0:30 - 1:08	0:19 - 0:38	1:46 - 2:17	0:49 - 1:46	0:23 - 0:49	0:19 - 0:49	0:27 - 0:34		
below -8 to -14 °C	100/0	0:42 - 1:54	0:23 - 0:38	1:31 - 1:46	0:53 - 1:31	0:30 - 0:53	0:27 - 1:1211	0:27 - 0:3411	OALITIO	
(below 18 to 7 °F)	75/25	0:30 - 1:08	0:15 - 0:34	1:31 - 1:54	0:42 - 1:31	0:19 - 0:42	0:19 - 0:4911	0:27 - 0:3411	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:19 - 0:38	0:06 - 0:19	1:12 - 1:43	0:27 - 1:12	0:08 - 0:27			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:19 - 0:38	0:02 - 0:08	0:30 - 0:42	0:11 - 0:30	0:03 - 0:11				
below -25 to -30.5 °C (below -13 to -23 °F)	100/0	0:19 - 0:38	0:02 - 0:04	0:19 - 0:23	0:05 - 0:19	0:02 - 0:05				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-33: ADJUSTED TYPE IV HOLDOVER TIMES FOR CRYOTECH POLAR GUARD® XTEND

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:54 - 3:02	0:38 - 1:08	2:43 - 3:00	1:31 - 2:43	0:49 - 1:31	1:31 - 1:31	0:46 - 1:24	0:15 - 1:20	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(=: : :::::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	0:46 - 1:24	0:30 - 0:53	2:09 - 2:36	1:12 - 2:09	0:38 - 1:12	0:27 - 1:16	0:38 - 0:42		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:46 - 1:24	0:27 - 0:46	1:50 - 2:13	1:01 - 1:50	0:34 - 1:01	0:27 - 1:1611	0:38 - 0:4211	0.441710	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:19 - 0:30	0:11 - 0:23	1:01 - 1:16	0:30 - 1:01	0:15 - 0:30			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:19 - 0:30	0:04 - 0:08	0:23 - 0:30	0:11 - 0:23	0:05 - 0:11				
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:19 - 0:30	0:02 - 0:05	0:15 - 0:19	0:07 - 0:15	0:03 - 0:07				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-34: ADJUSTED TYPE IV HOLDOVER TIMES FOR DOW INC. UCAR ENDURANCE™ EG106

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:35 - 2:24	0:23 - 0:46	2:05 - 2:40	1:01 - 2:05	0:30 - 1:01	0:53 - 1:31	0:38 - 0:57	0:15 - 1:31	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(=: : :::::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	1:24 - 2:32	0:19 - 0:38	1:50 - 2:17	0:53 - 1:50	0:27 - 0:53	0:42 - 1:24	0:34 - 0:53		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	1:24 - 2:32	0:19 - 0:34	1:39 - 2:05	0:49 - 1:39	0:23 - 0:49	0:42 - 1:2411	0:34 - 0:5311	0.441710	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:23 - 0:49	0:11 - 0:27	1:20 - 1:43	0:38 - 1:20	0:19 - 0:38			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:23 - 0:49	0:11 - 0:23	1:08 - 1:27	0:30 - 1:08	0:15 - 0:30				
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:23 - 0:49	0:11 - 0:23	1:01 - 1:20	0:30 - 1:01	0:15 - 0:30				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-45 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-35: ADJUSTED TYPE IV HOLDOVER TIMES FOR DOW INC. UCAR™ FLIGHTGUARD™ AD-49

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	2:32 - 3:02	0:34 - 1:05	2:47 - 3:00	1:27 - 2:47	0:46 - 1:27	1:05 - 1:31	0:46 - 1:05	0:08 - 1:27	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(== : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	0:15 - 1:12	0:27 - 0:49	2:13 - 2:40	1:08 - 2:13	0:34 - 1:08	0:19 - 1:05	0:15 - 0:19		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:15 - 1:12	0:23 - 0:42	1:50 - 2:17	0:57 - 1:50	0:30 - 0:57	0:19 - 1:05 ¹¹	0:15 - 0:19 ¹¹	OALITIO	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:19 - 0:30	0:01 - 0:05	0:23 - 0:34	0:07 - 0:23	0:02 - 0:07			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:19 - 0:30	0:00 - 0:02	0:08 - 0:15	0:02 - 0:08	0:01 - 0:02				
below -25 to -26 °C (below -13 to -15 °F)	100/0	0:19 - 0:30	0:00 - 0:01	0:05 - 0:08	0:02 - 0:05	0:00 - 0:02				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-36: ADJUSTED TYPE IV HOLDOVER TIMES FOR INLAND TECHNOLOGIES ECO-SHIELD®

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	0:57 - 2:02	0:27 - 0:46	1:50 - 2:09	1:01 - 1:50	0:34 - 1:01	0:30 - 1:08	0:27 - 0:30	0:11 - 1:12	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	0:53 - 1:58	0:23 - 0:42	1:35 - 1:54	0:53 - 1:35	0:30 - 0:53	0:38 - 1:05	0:23 - 0:30		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:53 - 1:58	0:19 - 0:38	1:27 - 1:43	0:49 - 1:27	0:27 - 0:49	0:38 - 1:05 ¹¹	0:23 - 0:3011	0.441710	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:23 - 0:46	0:01 - 0:05	0:23 - 0:34	0:07 - 0:23	0:02 - 0:07			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:23 - 0:46	0:00 - 0:02	0:08 - 0:15	0:02 - 0:08	0:01 - 0:02				
below -25 to -25.5 °C (below -13 to -14 °F)	100/0	0:23 - 0:46	0:00 - 0:01	0:05 - 0:08	0:02 - 0:05	0:00 - 0:02				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-37: ADJUSTED TYPE IV HOLDOVER TIMES FOR JSC RCP NORDIX DEFROST ECO 4

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:08 - 2:02	0:23 - 0:42	1:54 - 2:24	0:57 - 1:54	0:27 - 0:57	0:49 - 1:08	0:30 - 0:49	0:11 - 0:53	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	0:42 - 1:58	0:19 - 0:38	1:43 - 2:05	0:49 - 1:43	0:27 - 0:49	0:38 - 1:01	0:27 - 0:38		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:42 - 1:58	0:19 - 0:34	1:35 - 1:58	0:46 - 1:35	0:23 - 0:46	0:38 - 1:0111	0:27 - 0:3811	0.441710	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:23 - 0:38	0:01 - 0:05	0:23 - 0:34	0:07 - 0:23	0:02 - 0:07			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:23 - 0:38	0:00 - 0:02	0:08 - 0:15	0:02 - 0:08	0:01 - 0:02				
below -25 to -25.5 °C (below -13 to -14 °F)	100/0	0:23 - 0:38	0:00 - 0:01	0:05 - 0:08	0:02 - 0:05	0:00 - 0:02				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-38: ADJUSTED TYPE IV HOLDOVER TIMES FOR JSC RCP NORDIX DEFROST NORTH 4

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:39 - 3:02	0:23 - 0:46	2:13 - 2:51	1:05 - 2:13	0:30 - 1:05	0:49 - 1:31	0:23 - 0:38	0:07 - 1:27	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(= 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	2:02 - 3:02	0:23 - 0:46	2:13 - 2:51	1:05 - 2:13	0:30 - 1:05	0:49 - 1:31	0:30 - 0:46		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	2:02 - 3:02	0:23 - 0:46	2:13 - 2:51	1:05 - 2:13	0:30 - 1:05	0:49 - 1:31 ¹¹	0:30 - 0:4611	OALITIO	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:34 - 1:27	0:05 - 0:15	0:38 - 0:49	0:19 - 0:38	0:08 - 0:19			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:34 - 1:27	0:02 - 0:08	0:30 - 0:42	0:11 - 0:30	0:04 - 0:11				
below -25 to -26 °C (below -13 to -15 °F)	100/0	0:34 - 1:27	0:01 - 0:05	0:19 - 0:27	0:06 - 0:19	0:02 - 0:06				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-45 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-39: ADJUSTED TYPE IV HOLDOVER TIMES FOR KILFROST ABC-S PLUS

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog ⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:39 - 3:02	0:42 - 1:12	2:43 - 3:00	1:35 - 2:43	0:57 - 1:35	1:24 - 1:31	0:49 - 1:31	0:19 - 1:31	
-3 °C and above (27 °F and above)	75/25	1:05 - 2:02	0:23 - 0:42	1:35 - 1:50	0:57 - 1:35	0:34 - 0:57	0:46 - 1:01	0:23 - 0:38	0:08 - 1:01	
(=: : : :::::::::::::::::::::::::::::::	50/50	0:23 - 0:42	0:11 - 0:19	0:46 - 0:53	0:23 - 0:46	0:11 - 0:23	0:11 - 0:30	0:11 - 0:15		
below -3 to -8 °C	100/0	0:42 - 2:40	0:38 - 1:05	2:24 - 2:51	1:24 - 2:24	0:49 - 1:24	0:19 - 1:12	0:15 - 0:23		
(below 27 to 18 °F)	75/25	0:34 - 1:24	0:23 - 0:38	1:24 - 1:39	0:49 - 1:24	0:30 - 0:49	0:15 - 0:53	0:11 - 0:19		
below -8 to -14 °C	100/0	0:42 - 2:40	0:34 - 0:57	2:13 - 2:40	1:20 - 2:13	0:46 - 1:20	0:19 - 1:12 ¹¹	0:15 - 0:23 ¹¹		
(below 18 to 7 °F)	75/25	0:34 - 1:24	0:19 - 0:34	1:20 - 1:31	0:46 - 1:20	0:27 - 0:46	0:15 - 0:53 ¹¹	0:11 - 0:19 ¹¹	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:30 - 0:46	0:01 - 0:05	0:23 - 0:34	0:07 - 0:23	0:02 - 0:07			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:30 - 0:46	0:00 - 0:02	0:08 - 0:15	0:02 - 0:08	0:01 - 0:02				
below -25 to -28 °C (below -13 to -18 °F)	100/0	0:30 - 0:46	0:00 - 0:01	0:05 - 0:08	0:02 - 0:05	0:00 - 0:02				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-40: ADJUSTED TYPE IV HOLDOVER TIMES FOR MKS DEVO CHEMICALS COREICEPHOB TYPE IV PG

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:46 - 2:55	0:27 - 0:57	2:47 - 3:00	1:16 - 2:47	0:34 - 1:16	1:05 - 1:31	0:38 - 1:01	0:08 - 1:16	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(=: : :::::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	0:11 - 0:27	0:19 - 0:42	1:58 - 2:32	0:53 - 1:58	0:27 - 0:53	0:30 - 1:08	0:15 - 0:27		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:11 - 0:27	0:15 - 0:34	1:35 - 2:02	0:42 - 1:35	0:19 - 0:42	0:30 - 1:0811	0:15 - 0:27 ¹¹	OALITIO	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:11 - 0:23	0:01 - 0:05	0:23 - 0:34	0:07 - 0:23	0:02 - 0:07			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:11 - 0:23	0:00 - 0:02	0:08 - 0:15	0:02 - 0:08	0:01 - 0:02				
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:11 - 0:23	0:00 - 0:01	0:05 - 0:08	0:02 - 0:05	0:00 - 0:02				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-41: ADJUSTED TYPE IV HOLDOVER TIMES FOR NEWAVE AEROCHEMICAL FCY 9311

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:27 - 3:02	0:19 - 0:42	1:46 - 2:13	0:53 - 1:46	0:27 - 0:53	0:53 - 1:31	0:30 - 0:49	0:11 - 1:05	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	0:27 - 1:35	0:15 - 0:30	1:24 - 1:46	0:42 - 1:24	0:23 - 0:42	0:27 - 1:01	0:15 - 0:27		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:27 - 1:35	0:15 - 0:27	1:12 - 1:31	0:38 - 1:12	0:19 - 0:38	0:27 - 1:0111	0:15 - 0:27 ¹¹	0.441710	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:23 - 0:42	0:08 - 0:15	0:46 - 0:57	0:23 - 0:46	0:11 - 0:23			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:23 - 0:42	0:04 - 0:08	0:27 - 0:30	0:11 - 0:27	0:05 - 0:11				
below -25 to -29.5 °C (below -13 to -21 °F)	100/0	0:23 - 0:42	0:04 - 0:08	0:23 - 0:30	0:11 - 0:23	0:05 - 0:11				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-42: ADJUSTED TYPE IV HOLDOVER TIMES FOR NEWAVE AEROCHEMICAL FCY-EGIV

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:58 - 3:02	0:19 - 0:42	1:58 - 2:32	0:53 - 1:58	0:27 - 0:53	1:01 - 1:31	0:30 - 0:49	0:11 - 1:31	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	1:05 - 2:36	0:15 - 0:34	1:39 - 2:05	0:46 - 1:39	0:19 - 0:46	0:38 - 1:31	0:34 - 0:49		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	1:05 - 2:36	0:15 - 0:30	1:27 - 1:50	0:38 - 1:27	0:19 - 0:38	0:38 - 1:3111	0:34 - 0:4911	0.411710	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:27 - 1:27	0:11 - 0:23	1:12 - 1:35	0:30 - 1:12	0:11 - 0:30			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:27 - 1:27	0:07 - 0:15	0:53 - 1:12	0:23 - 0:53	0:11 - 0:23				
below -25 to -29 °C (below -13 to -20 °F)	100/0	0:27 - 1:27	0:06 - 0:15	0:46 - 1:01	0:19 - 0:46	0:08 - 0:19				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-45 provides allowance times for Type IV EG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

TABLE ADJ-43: ADJUSTED TYPE IV HOLDOVER TIMES FOR SHAANXI CLEANWAY CLEANSURFACE IV

Outside Air Temperature ¹	Fluid Concentration Fluid/Water By % Volume	Mist ² , or Ice	Snow mixed with Freezing Fog⁴	Very Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Light Snow, Snow Grains or Snow Pellets ^{5,6,7}	Moderate Snow, Snow Grains or Snow Pellets ^{5,7}	Freezing Drizzle ⁸	Light Freezing Rain	Rain on Cold-Soaked Wing ⁹	Other ¹⁰
	100/0	1:54 - 3:02	0:23 - 0:57	2:51 - 3:00	1:16 - 2:51	0:30 - 1:16	1:01 - 1:31	0:30 - 0:53	0:11 - 1:24	
-3 °C and above (27 °F and above)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
(== : : :::::::::::::::::::::::::::::::	50/50	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -3 to -8 °C	100/0	0:42 - 1:35	0:15 - 0:34	1:50 - 2:21	0:46 - 1:50	0:19 - 0:46	0:23 - 1:08	0:19 - 0:27		
(below 27 to 18 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A		
below -8 to -14 °C	100/0	0:42 - 1:35	0:11 - 0:27	1:20 - 1:43	0:34 - 1:20	0:15 - 0:34	0:23 - 1:0811	0:19 - 0:2711	0.441710	
(below 18 to 7 °F)	75/25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	CAUTIO No holdove	
below -14 to -18 °C (below 7 to 0 °F)	100/0	0:19 - 0:27	0:08 - 0:15	0:49 - 1:01	0:23 - 0:49	0:11 - 0:23			guidelines	exist
below -18 to -25 °C (below 0 to -13 °F)	100/0	0:19 - 0:27	0:04 - 0:08	0:27 - 0:34	0:11 - 0:27	0:05 - 0:11				
below -25 to -30 °C (below -13 to -22 °F)	100/0	0:15 - 0:23	0:03 - 0:07	0:23 - 0:27	0:11 - 0:23	0:05 - 0:11				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. HOLDOVER TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I fluid when Type IV fluid cannot be used.
- 2 Freezing mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0 °C (32 °F) and below.
- 3 Use freezing fog holdover times in conditions of ice crystals mixed with freezing fog or mist.
- 4 These holdover times are for use in -SNFZFG and SNFZFG. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "moderate". No holdover times exist if the reported visibility correlates to a "heavy" precipitation intensity.
- 5 To determine snowfall intensity, the Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required.
- 6 Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. The Snowfall Intensities as a Function of Prevailing Visibility table (Table 48) is required to confirm the precipitation intensity is no greater than "light". No holdover times exist if the reported visibility correlates to a "moderate" or "heavy" precipitation intensity.
- 7 Use snow holdover times in conditions of very light, light, or moderate snow mixed with ice crystals.
- 8 Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.
- 9 No holdover time guidelines exist for this condition for 0 °C (32 °F) and below.
- 10 Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail (Table Adj-46 provides allowance times for Type IV PG fluids in ice pellets and small hail).
- 11 No holdover time guidelines exist for this condition below -10 °C (14 °F).

CAUTIONS

ADJUSTED ALLOWANCE TIMES TABLES FOR WINTER 2024-2025

The HOT Guidelines are provided for information and guidance purposes. The HOT Guidelines on their own do not change, create, amend or permit deviations from regulatory requirements.

The HOT Guidelines may use mandatory terms such as "must", "shall" and "is/are required" so as to convey the intent of meeting regulatory requirements and SAE Standards, where applicable. The term "should" is to be understood, unless an alternative method of achieving safety is implemented that would meet or exceed the intent of the recommendation.

CAUTIONS

- The responsibility for the application of these data remains with the user.
- Fluids used during ground de/anti-icing do not provide in-flight icing protection.
- This table is for departure planning only and should be used in conjunction with pretakeoff check procedures.
- Allowance time cannot be extended by an inspection of the aircraft critical surfaces.

TABLE ADJ-44: ADJUSTED ALLOWANCE TIMES FOR SAE TYPE III FLUIDS^{1,2}

	Outside Air Temperature					
Precipitation Types or Combinations and Applicable METAR Codes ⁴	Above 0 °C (32 °F and above)	0 to -5 °C (32 to 23 °F)	Below -5 to -10 °C (Below 23 to 14 °F)	Below -10 °C³ (Below 14 °F)		
Light Ice Pellets -PL, -GS	8 minutes	8 minutes	8 minutes			
Light Ice Pellets Mixed with Light Snow -PLSN, -SNPL, -GSSN, -SNGS	8 minutes	8 minutes	8 minutes			
Light Ice Pellets Mixed with Light or Moderate Freezing Drizzle -PLFZDZ, -FZDZPL, FZDZPL, -GSFZDZ, -FZDZGS, FZDZGS		5 minutes	4 minutes	Caution:		
Light Ice Pellets Mixed with Light or Moderate Drizzle -PLDZ, -DZPL, DZPL, -GSDZ, -DZGS, DZGS	5 minutes			No allowance times currently exist		
Light Ice Pellets Mixed with Light Freezing Rain -PLFZRA, -FZRAPL, -GSFZRA, -FZRAGS		5 minutes	4 minutes			
Light Ice Pellets Mixed with Light Rain -PLRA, -RAPL, -GSRA, -RAGS	5 minutes					
Moderate Ice Pellets (or Small Hail) PL, GS	4 minutes	4 minutes	4 minutes			

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. ALLOWANCE TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

- 1 These allowance times are for use with undiluted (100/0) fluids applied unheated on aircraft with rotation speeds of 100 knots or greater. To use the allowance times in this table, ensure the fluid being used is listed in the List of Fluids Validated for the Use of Allowance Times Table (Table 44).
- 2 Takeoff is allowed up to 90 minutes after start of fluid application if the precipitation stops at or before the allowance time expires and does not restart. Take is not permitted if the OAT decreases during the 90 minutes in conditions of light ice pellets mixed with either: light or moderate freezing drizzle, light or moderate drizzle, light freezing rain, or light rain.
- 3 Ensure that the lowest operational use temperature (LOUT) is respected.
- 4 In the US, small hail is reported as GR with the remark "GR LESS THAN ¼". Outside of the US small hail is reported as GS. If the METAR does not report an intensity for small hail, use the "moderate ice pellets or small hail" allowance times. If the METAR reports an intensity with small hail, the condition with the equivalent intensity can be used. This also applies in mixed conditions.

CAUTIONS

TABLE ADJ-45: ADJUSTED ALLOWANCE TIMES FOR SAE TYPE IV ETHYLENE GLYCOL (EG) FLUIDS^{1,2}

	Outside Air Temperature					
Precipitation Types or Combinations and Applicable METAR Codes ⁵	Above 0 °C³ (32 °F and above)	0 to -5 °C ³ (32 to 23 °F)	Below -5 to -10 °C ³ (Below 23 to 14 °F)	Below -10 to -16 °C ³ (Below 14 to 3 °F)	Below -16 to -22 °C ^{3,4} (Below 3 to -8 °F)	
Light Ice Pellets -PL, -GS	53 minutes	53 minutes	53 minutes	38 minutes	23 minutes	
Light Ice Pellets Mixed with Light Snow -PLSN, -SNPL, -GSSN, -SNGS	38 minutes	38 minutes	23 minutes	19 minutes		
Light Ice Pellets Mixed with Light or Moderate Freezing Drizzle -PLFZDZ, -FZDZPL, FZDZPL, -GSFZDZ, -FZDZGS, FZDZGS		30 minutes	23 minutes			
Light Ice Pellets Mixed with Light or Moderate Drizzle -PLDZ, -DZPL, DZPL, -GSDZ, -DZGS, DZGS	30 minutes					
Light Ice Pellets Mixed with Light Freezing Rain -PLFZRA, -FZRAPL, -GSFZRA, -FZRAGS		30 minutes	23 minutes			
Light Ice Pellets Mixed with Light Rain -PLRA, -RAPL, -GSRA, -RAGS	30 minutes			Caut No allowa current	nce times	
Light Ice Pellets Mixed with Light Rain and Light Snow -PLRASN, -PLSNRA, -RAPLSN, -RASNPL, -SNPLRA, -SNRAPL, -GSRASN, -GSSNRA, -RAGSSN, -RASNGS, -SNGSRA, -SNRAGS	15 minutes			ourron	, y CAIG.	
Light Ice Pellets Mixed with Light Freezing Rain and Light Snow -PLFZRASN, -PLSNFZRA, -FZRAPLSN, -FZRASNPL, -SNPLFZRA, -SNFZRAPL, -GSFZRASN, -GSSNFZRA, -FZRAGSSN, -FZRASNGS, -SNGSFZRA, -SNFZRAGS		15 minutes				
Moderate Ice Pellets (or Small Hail) PL, GS	27 minutes	27 minutes	27 minutes	11 minutes	8 minutes	
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Snow PLSN, SNPL, GSSN, SNGS	19 minutes	11 minutes	8 minutes			
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Freezing Drizzle PLFZDZ, GSFZDZ		15 minutes	8 minutes			
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Drizzle PLDZ, GSDZ	15 minutes	Caution: No allowance times currently exist				
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Rain PLRA, GSRA, RAPL, RAGS	11 minutes					

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. ALLOWANCE TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

• The notes that apply to the allowance times in the table above can be found on page A-54.

CAUTIONS

TABLE 45 (CONT'D): ALLOWANCE TIMES FOR SAE TYPE IV ETHYLENE GLYCOL (EG) FLUIDS

NOTES

- 1 These allowance times are for use with undiluted (100/0) EG based fluids. If the glycol type is unknown, the allowance times for SAE Type IV PG fluids should be used. To use the allowance times in this table, ensure the fluid being used is listed in the List of Fluids Validated for the Use of Allowance Times Table (Table 44).
- 2 Takeoff is allowed up to 90 minutes after start of fluid application if the precipitation stops at or before the allowance time expires and does not restart. Takeoff is not permitted if the OAT decreases during the 90 minutes in conditions of light ice pellets mixed with either: light freezing drizzle, moderate freezing drizzle, light freezing rain, or light rain.
- 3 No allowance times exist for EG based fluids when used on aircraft with rotation speeds less than 100 knots.
- 4 Ensure that the lowest operational use temperature (LOUT) is respected.
- 5 In the US, small hail is reported as GR with the remark "GR LESS THAN ¼". Outside of the US small hail is reported as GS. If the METAR does not report an intensity for small hail, use the "moderate ice pellets or small hail" allowance times. If the METAR reports an intensity with small hail, the ice pellet condition with the equivalent intensity can be used. This also applies in mixed conditions.

TABLE ADJ-46: ADJUSTED ALLOWANCE TIMES FOR SAE TYPE IV PROPYLENE GLYCOL (PG) FLUIDS^{1,2}

	Outside Air Temperature					
Precipitation Types or Combinations and Applicable METAR Codes ⁶	Above 0 °C³ (32 °F and above)	0 to -5 °C ³ (32 to 23 °F)	Below -5 to -10 °C ³ (Below 23 to 14 °F)	Below -10 to -16 °C ⁴ (Below 14 to 3 °F)	Below -16 to -22 °C ^{4,5} (Below 3 to -8 °F)	
Light Ice Pellets -PL, -GS	38 minutes	38 minutes	23 minutes	23 minutes	15 minutes	
Light Ice Pellets Mixed with Light Snow -PLSN, -SNPL, -GSSN, -SNGS	30 minutes	30 minutes	11 minutes	11 minutes		
Light Ice Pellets Mixed with Light or Moderate Freezing Drizzle -PLFZDZ, -FZDZPL, FZDZPL, -GSFZDZ, -FZDZGS, FZDZGS		19 minutes	8 minutes			
Light Ice Pellets Mixed with Light or Moderate Drizzle -PLDZ, -DZPL, DZPL, -GSDZ, -DZGS, DZGS	19 minutes					
Light Ice Pellets Mixed with Light Freezing Rain -PLFZRA, -FZRAPL, -GSFZRA, -FZRAGS		19 minutes	8 minutes	No allowa	tion: ince times ily exist	
Light Ice Pellets Mixed with Light Rain -PLRA, -RAPL, -GSRA, -RAGS	19 minutes				.,	
Light Ice Pellets Mixed with Light Rain and Light Snow -PLRASN, -PLSNRA, -RAPLSN, -RASNPL, -SNPLRA, -SNRAPL, -GSRASN, -GSSNRA, -RAGSSN, -RASNGS, -SNGSRA, -SNRAGS	15 minutes					
Light Ice Pellets Mixed with Light Freezing Rain and Light Snow -PLFZRASN, -PLSNFZRA, -FZRAPLSN, -FZRASNPL, -SNPLFZRA, -SNFZRAPL, -GSFZRASN, -GSSNFZRA, -FZRAGSSN, -FZRASNGS, -SNGSFZRA, -SNFZRAGS		15 minutes			1	
Moderate Ice Pellets (or Small Hail) PL, GS	11 minutes	11 minutes	8 minutes	8 minutes		
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Snow PLSN, SNPL, GSSN, SNGS	11 minutes	4 minutes	4 minutes			
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Freezing Drizzle PLFZDZ, GSFZDZ		8 minutes	5 minutes			
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Drizzle PLDZ, GSDZ	8 minutes	Caution:				
Moderate Ice Pellets (or Small Hail) Mixed with Moderate Rain PLRA, GSRA, RAPL, RAGS	8 minutes	No allowance times currently exist				

THIS TABLE IS FOR USE WHEN FLAPS/SLATS ARE DEPLOYED PRIOR TO DE/ANTI-ICING. ALLOWANCE TIMES HAVE BEEN ADJUSTED TO 76 PERCENT.

NOTES

• The notes that apply to the allowance times in the table above can be found on page A-56.

CAUTIONS

TABLE 46 (CONT'D): ALLOWANCE TIMES FOR SAE TYPE IV PROPYLENE GLYCOL (PG) FLUIDS

NOTES

- 1 These allowance times are for use with undiluted (100/0) PG based fluids applied on aircraft with rotation speeds of 100 knots or greater. If the glycol type is unknown, the allowance times for SAE Type IV PG fluids should be used. To use the allowance times in this table, ensure the fluid being used is listed in the List of Fluids Validated for the Use of Allowance Times Table (Table 44).
- 2 Takeoff is allowed up to 90 minutes after start of fluid application if the precipitation stops at or before the allowance time expires and does not restart. Takeoff is not permitted if the OAT decreases during the 90 minutes in conditions of light ice pellets mixed with either: light freezing drizzle, moderate freezing drizzle, light freezing rain, or light rain.
- 3 No allowance times exist for PG based fluids when used on aircraft with rotation speeds less than 100 knots.
- 4 No allowance times exist for PG based fluids when used on aircraft with rotation speeds less than 115 knots.
- 5 Ensure that the lowest operational use temperature (LOUT) is respected.
- 6 In the US, small hail is reported as GR with the remark "GR LESS THAN 1/4". Outside of the US, small hail is reported as GS. If the METAR does not report an intensity for small hail, use the "moderate ice pellets or small hail" allowance times. If the METAR reports an intensity with small hail, the ice pellet condition with the equivalent intensity can be used. This also applies in mixed conditions.

APPENDIX B: TESTING LABORATORIES

TESTING LABORATORIES

The following laboratories are known to provide testing for de/anti-icing fluids given they verifiably adhere to internationally accepted standards and recommended practices that are associated with the holdover times published by the FAA.

Please enquire directly with the laboratories for a full list of testing available.

- Anti-icing Materials International Laboratory (AMIL): 555, boulevard de l'Université, Chicoutimi, Québec, G7H 2B1, Canada, 418-545-5011 ext. 2406, www.amillaboratory.ca. Provides testing for anti-icing performance (described in AMS1424, AMS1428, and AS5901), aerodynamic acceptance (described in AMS1424, AMS1428 and AS5900), physical properties including fluid stability (described in AMS1424 and AMS1428), environmental information (described in AMS1424 and AMS1428) and most of tests to evaluate materials compatibility (described in AMS1424 and AMS1428).
- APS Aviation Inc.: 6700, chemin de la Côte-de-Liesse, Suite 102, Saint-Laurent, Quebec, H4T 2B5, Canada, 514-878-4388 www.apsaviation.ca. Provides endurance time testing (described in ARP5485B and ARP5945A).
- Scientific Material International (SMI): 12219 SW 131st Avenue, Miami, Florida, USA 33186-6401; 305-971-7047, www.smiinc.com. Provides testing for physical properties including fluid stability (described in AMS1424 and AMS1428), environmental information (described in AMS1424 and AMS1428) and most of tests to evaluate materials compatibility (described in AMS1424 and AMS1428).

APPENDIX C: AIRCRAFT DEICING FLUID (ADF)/AIRCRAFT ANTI-ICING FLUID (AAF) MANUFACTURERS

TABLE C-1: ADF/AAF MANUFACTURERS CONTACT INFORMATION*

Fluid Manufacturer	Primary contact	Email Address
ABAX Industries	Cristina Poupet	c.poupet@abax.eu
ADDCON EUROPE GmbH	Norman Kilian	norman.kilian@addcon.com
Aero Mag 2000 SYR LLC	Mark Vilcek	m.vilcek@aeromag2000.com
ALAB Industries	Marat Zhazbek	info@alab.kz
Alab International	Kuanyshbay Bissenov	deicing@alab.kz
AllClear Systems LLC	Steve Szafara	SSzafara@allclearsys.com
Arcton Ltd.	Bulat Hamitov	bulathamitov@yandex.ru
ASGlobal	Paulo de Oliveira	paulo@asglobal.biz
AVIAFLUID International Ltd	Igor Derbasov	iderbasov@aviafluid.ru
Aviation Xi'an High-Tech Physical Chemical Co. Ltd.	Arella	xiangaokelihua@163.com
Beijing Wangye Aviation Chemical Product Co Ltd.	Sina Gong	hswgyh@sina.com
Beijing Yadilite Aviation Advanced Materials Corporation	Kewei Wang	wangkewei@yadilite.com
CHEMCO Inc.	Claude Grenon	claude.grenon@chemco-inc.com
Chongqing Joba Chemical Co,.Ltd.	Cherry Wang	info@changfengchem.com
Clariant Produkte (Deutschland) GmbH	Andreas Brueck	andreas.brueck@clariant.com
Cryotech Deicing Technology	Melissa Copeland	melissa.copeland@cryotech.com
Dow Inc.	Sarah Venckeleer	fdeicer@dow.com.
Heilongjiang Hangjie Aero-chemical Technology Co. Ltd.	Wang Dawen	dawen_hrb@163.com
HOC Industries	Jeremy Wilcoxson	jwilcoxson@hocindustries.com
Inland Technologies Inc.	Alex McLeod	amcleod@inlandgroup.ca
JSC RCP Nordix	Ruslan Ukraintsev	defrost@nordway.ru
Kilfrost Limited	Lee Stokes	lee.stokes@kilfrost.com
LNT Solutions	Philip Newton	philip.newton@Intsolutions.com
MKS DevO Chemicals	Efe Dikergil	efe.dikergil@mksdevo.com
Newave Aerochemical Co. Ltd.	Peng Aiqun	lwgs@newave.cn
ROMCHIM PROTECT SRL	Eugenia Hongu	contact@romchimprotect.ro
Shaanxi Cleanway Aviation Chemical Co., Ltd	Arella	xiangaokelihua@163.com
Topan LLC	Almat Kurmanov	almat.kurmanov@topan.kz
Xinjiang Zhongtian Liyang Chemical Technology Co., Ltd	Huang Liang	heima.54@foxmail.com

^{*}Contact information provided above is the latest information as of the time of publication, August 6, 2024.