

U.S. DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

CERTIFICATE OF WAIVER

ISSUED TO

Enhanced Patrol LLC
Responsible Person: Jonathan Frith
Waiver Number: 107W-2025-04534

ADDRESS –

**4937 Saint Ives Dr
Murfreesboro, TN 37128**

This certificate is issued for the operations specifically described hereinafter. No person shall conduct any operation pursuant to the authority of this certificate except in accordance with the provisions contained in this certificate.

OPERATIONS AUTHORIZED

Small unmanned aircraft system (sUAS) operations beyond the visual line of sight of the remote pilot in command (PIC); Acting as a remote pilot in command (PIC) or visual observer (VO) in the operation of more than one small unmanned aircraft (sUA) at the same time; Small unmanned aircraft system (sUAS) operations over human beings; Small unmanned aircraft system (sUAS) operations over a moving vehicle.

LIST OF WAIVED REGULATIONS BY SECTION AND TITLE

**14 CFR §§ 107.31—Visual line of sight aircraft operation,
107.35—Operation of multiple small unmanned aircraft systems,
107.39—Operation over human beings, and
107.145—Operations over moving vehicles**

STANDARD PROVISIONS

1. A copy of the application made for this certificate shall be attached to and become a part hereof.
2. This certificate shall be presented for inspection upon the request of any authorized representative of the Administrator of the Federal Aviation Administration, or of any State or municipal official charged with the duty of enforcing local laws or regulations.
3. The holder of this certificate shall be responsible for the strict observance of the terms and provisions contained herein.
4. This certificate is nontransferable.

NOTE—This certificate constitutes a waiver of those Federal rules or regulations specifically referred to above. It does not constitute a waiver of any State law or local ordinance.

SPECIAL PROVISIONS

Special Provisions Nos. 1 to 45, inclusive, are set forth on the attached pages.

This Certificate of Waiver is effective from January 14, 2026, to January 31, 2030, and is subject to cancellation at any time upon notice by the Administrator or an authorized representative.

BY DIRECTION OF THE ADMINISTRATOR

Emerging Technologies Division, AFS-700

SPECIAL PROVISIONS ISSUED TO
Enhanced Patrol LLC

General.

The FAA's Flight Standards Service has reviewed your application to ensure compliance with the requirements of 14 CFR § 107.200 and § 107.205. Pursuant to these authorities, the Administrator finds that the proposed small unmanned aircraft (sUA) operation can be conducted safely under the provisions of this Certificate of Waiver (Waiver) as listed below because you have established adequate mitigations for risks involved with operating your sUA in the manner you described. Adherence to the provisions of this Waiver establishes the required level of safety within the national airspace system.

The Administrator may cancel this Waiver at any time. As a general rule, this Waiver may be canceled when it is no longer required, there is an abuse of its provisions, or when unforeseen safety factors develop. Failure to comply with any provision listed below is a violation of the terms of this Waiver and will serve as justification for cancellation.

List of Regulations Waived by Section and Title. The following regulations are waived:

14 CFR § 107.31, Visual line of sight aircraft operation, is waived to allow operation of the small unmanned aircraft (sUA) beyond the direct visual line of sight of the remote pilot in command (PIC);

14 CFR § 107.35, Operation of multiple small unmanned aircraft systems, is waived to allow a person to act as the remote Pilot in Command (PIC) or visual observer (VO) to operate multiple small UAS simultaneously;

14 CFR § 107.39, Operations over human beings, is waived to allow sUA operations over human beings who are not direct participants, necessary for the safe operation of the small unmanned aircraft;

14 CFR § 107.145, Operations over moving vehicles, is waived to allow sUA operations over a moving vehicle.

No part of this waiver will function as an airspace authorization under 14 CFR § 107.41. The FAA's Air Traffic Organization responds directly to requests for such authorizations.

Common Special Provisions. The Responsible Person is directly responsible for safety of operations conducted under this Waiver and will ensure the Remote Pilot in Command (remote PIC), manipulator of the controls, and visual observer(s) (VO)¹ comply with all provisions of this Waiver.

1. The Responsible Person listed on the Waiver is responsible to the FAA for the safe conduct of the operations. Prior to conducting operations that are the subject of this Waiver, the Responsible Person:
 - a. Must ensure the remote PIC, manipulators of the controls, and VO(s) are informed of the terms and provisions of this Waiver and strictly observe the terms and provisions herein;
 - b. Must ensure the remote PIC, manipulators of the controls, and VO(s) are informed and familiar with part 107 regulations; and

¹ Title 14 CFR § 107.3 defines the term "visual observer." Any VO participating in operations conducted under this Waiver must meet the requirements listed in § 107.33 throughout the duration of flight operations.

- c. Evidence of the above (a and b) must be documented and must be presented for inspection upon request from the Administrator or an authorized representative;
- 2. This Waiver may not be combined with any other waiver(s), authorizations(s), or exemption(s) without specific authorization from the FAA;
- 3. The FAA has the authority to cancel or delay any or all flight operations if the safety of persons or property on the ground or in the air are in jeopardy or there is a violation of the terms of this Waiver;
- 4. A copy of this Waiver must be accessible and available to the remote PIC at the ground control station during sUA operations that are the subject of this Waiver;
- 5. The Responsible Person listed on this Waiver must maintain a current list of pilots by name and remote pilot certificate number used in operations under this Waiver. This list must be presented for inspection upon request from the Administrator or an authorized representative;
- 6. The Responsible Person listed on this Waiver must maintain a current list of sUA by registration number(s) used in operations under this Waiver. This list must be presented for inspection upon request from the Administrator or an authorized representative;
- 7. For the purposes of this Waiver, direct participants are the remote PICs, persons manipulating the controls, VOs, and any persons whose involvement is necessary for safety of the sUA operation. All other persons are considered non-participants;
- 8. If a discrepancy exists between the provisions in this Waiver and the waiver application, the Waiver takes precedence and must be followed;

Visual Line of Sight Operations Special Provisions The remote PIC may conduct sUAS operations without the ability to see the unmanned aircraft throughout the entire flight, provided:

- 9. Remote ID: The sUA must be a standard remote identification unmanned aircraft listed on the FAA-accepted declaration of compliance list (found here: <https://uasdoc.faa.gov/>), unless otherwise authorized by the Administrator in writing;
- 10. The Flight Crew for operations under this Waiver must consist of the personnel specified in the Waiver application and supporting documentation, in the number and crew specialties as specified;
- 11. The remote PIC (RPIC) and Electronic Observer (EO) must be co-located in the same operations center which must be located within the continental United States;
- 12. Non-Shielded Operations: using VO(s) and or DAA
 - a. The sUA must not exceed 400 feet AGL;
 - b. The Detect and Avoid (DAA) Systems specified in the Waiver application must be active and under observation by the remote PIC or Electronic Observer, as applicable during all operations as described in the Waiver application. If the sUA is operated into areas where the effectiveness or coverage of the DAA system is compromised the maximum altitude must not exceed 200 feet AGL; or
 - c. May use sufficient VO(s), defined as the minimum number of VO(s) required to continuously observe at least a 2 statute mile radius of airspace surrounding the sUA in flight, are:
 - 1) Used to identify any non-participating aircraft prior to their entry into the planned

- operational area;
 - 2) Physically located such that the remote PIC receives sufficient notice to ensure the UA remains well clear of all other aircraft;
 - 3) Physically located to notify the remote PIC of any moving vehicle or human presence that may pose a hazard to the operation;
 - d. Communication between the remote PIC and VO must occur to facilitate, when necessary, for the remote PIC taking action to maneuver the sUA with sufficient time to;
 - 1) Give way to all other aircraft in accordance with § 107.37;
 - 2) React to any unforeseen operational or mechanical failure without creating a hazard to other people, other aircraft, or property in the event of a loss of control of the sUA; and
 - 3) Maintain compliance with this Waiver and un-waived provisions of part 107;
 - e. If communication between the VO and the remote PIC will occur by electronic device:
 - 1) The device must be continuous full-duplex;
 - 2) The remote PIC must be able to use the device hands-free; and
 - 3) There must be a reliable back-up communication method;
 - f. All VO(s) must receive documented training for their duties and responsibilities to include;
 - 1) Scanning of the Operational Volume for Air and Ground based intruders;
 - 2) Communications procedures and phraseology; and
 - 3) Overall operations conducted under this Waiver;
13. Standard Shielding: The sUA must not exceed:
- a. 100 feet above ground level (AGL) (200 feet if DAA is used); or
 - b. 100 feet above the height of any object (200 feet if DAA is used), obstacle (natural or man-made),
 - c. Must remain within the confines of the defined operational area detailed in the Site Selection Performance procedures as stated in the CONOPs; and
 - d. Flight operations will be limited to a distance of 1 SM from takeoff location unless Visual Observers are in place to continuously observe the airspace 2 SM around the position of the UAS;
14. Critical Infrastructure Shielding - for structures as defined in subsection (e) of the Critical Infrastructure Protection Act of 2001 (42 U.S.C. 5195c(e)): The sUA must not exceed:
- a. 200 feet above ground level (AGL); or
 - b. 200 feet above the height of any object, obstacle (natural or man-made), within a 200 foot radius of the sUA; not to exceed 400 feet AGL; and
 - c. Must remain within the confines of the defined operational area detailed in the Site Selection Performance procedures as stated in the CONOPS; and
 - d. Notwithstanding the requirement of paragraph (c) transition flights may be made between assets that may not provide shielding along the total route as long as the transition corridor is operated;
 - 1) At 100 feet above ground level (AGL); and
 - 2) The area is sparsely populated with no operations over non company personnel or non company vehicles;

15. Long Range Linear Infrastructure Shielding Operational Parameters:

- a. 100 feet above ground level (AGL); or
- b. 100 feet above the height of any object, obstacle (natural or man-made) within a 200 foot radius of the sUA perpendicular to the sUA's direction of flight (lateral separation); and
- c. 100 feet above the height of any object, obstacle (natural or man-made) within a 500 foot radius of the sUA along the sUA's direction of flight (vertical separation);

15. Detect and Avoid Technology (when used):

- a. No changes may be made to the Detect and Avoid system described in the Waiver application. Any change to the technology or manner in which Detect and Avoid is accomplished that differs from that specified in the Waiver application or supporting documentation must be made by a requested Waiver Amendment;
- b. The Detect and Avoid Systems specified in the Waiver application must be active and under observation by the remote PIC or Electronic Observer, as applicable during all operations as described in the Waiver application. If the sUA is operated into areas where the effectiveness or coverage of the DAA system is compromised the maximum altitude must not exceed 200 feet AGL;

16. The maximum takeoff weight of the sUA and all attachments such as shielding for rotating components (i.e., prop guards), remote ID module, camera, anti-collision lights, and/or payload **must not exceed 0.88 pounds**;

SPECIAL PROVISIONS APPLICABLE TO sUA GREATER THAN 0.88 POUNDS;

17. Multiple UAS Operations: AGGREGATED C2 SYSTEM

- a. The remote PIC may conduct operations of up to 6 sUA of the make/model defined in the Waiver application controlled and monitored using an aggregated solution, equipped with redundant flight control and transmission systems, and must ensure adequate simultaneous control of the sUA so they remain inside the area of operation, as described in the waiver application;
- b. sUA operations are limited to a maximum altitude of 400 feet AGL;
- c. The remote PIC must ensure that an individual system failure must not interfere with the operation of any other sUA or cause incidents, accidents, or loss of control involving any other sUA that are subject to this Waiver;
- d. Each sUA must be equipped with an independent Flight Termination System that will allow a safe maneuver for recovery inside the defined operational area if the command and control system fails;
- e. The flight termination and Geo-fencing systems must be verified operational prior to each flight;

18. The remote PIC (RPIC) must ensure:

- a. Prior to conducting operations under this Waiver, the RPIC must perform a documented site survey to:
 - 1) Identify flight operational area obstacles and boundaries so as to avoid collision with, or damage to property;
 - 2) Validate C2 signal strength is sufficient for control through the entire route;
 - 3) Validate suitable launch/recovery site(s); and
 - 4) Complete and document a Flight Risk Assessment;
- b. Routes are preplanned (using waypoints) prior to flight and aircraft are programmed to automatically follow the route. Manual flights are allowed as necessary;
- c. Geofencing is used to confine the Operational Volume. (defined as the property lines of the assets or perimeter boundaries of the controlled access area or right of way specified in the Waiver application + maximum allowed altitude);
- d. Return to Home/Return to Land feature must not allow the sUA to deviate from the defined operational volume;
- e. Launch or recovery areas are pre-designated and monitored to keep any human being who is not directly participating in the operation out of the areas prior to, during, and immediately following flight operations;
- f. Non-participant persons inside the operational area are notified of sUA operations; and
- g. Individuals directly participating in the operation of the sUAS must be easily identifiable visually (e.g., apparel, safety vests);

19. The Responsible Person must ensure:

- a. A copy of the Waiver application and Waiver is available to the remote PIC and all other direct participants prior to and during sUAS operations that are the subject of this Waiver;
- b. A copy of the current operations manual required by this Waiver is available to the remote PIC and all other direct participants prior to and during sUAS operations that are the subject of this Waiver;
- c. All operations conducted under this Waiver follow the procedures outlined in the current operations manual. If a discrepancy exists between the provisions in this Waiver and the procedures outlined in the operations manual, the provisions of this Waiver take precedence and must be followed;
- d. A documented notification from the operator(s) of the sUA to any airport, heliport, known agricultural aerial application operation or aerial military installation within a 3 mile radius of the operating area; and
- e. Each remote PIC who will conduct operations under this Waiver is trained in a manner that addresses the items listed in § 107.49(a) and in a manner that is consistent with how the sUAS will be operated under this Waiver. All training and demonstration for all remote PICs and VO(s) must be documented and made available upon request by the Administrator or an authorized representative. Training operations may only be conducted under the standard requirements of part 107 (without waiver).

The training must include:

- 1) sUA limitations;
- 2) sUA programming;
- 3) sUA operational procedures;
- 4) Abnormal procedures;
- 5) Air traffic avoidance procedures;
- 6) Crew Resource Management;

- 7) sUA flight training; and
 - 8) Demonstration of sUA ground and flight skills;
20. The maximum takeoff weight of the sUA and all attachments such as shielding for rotating components (i.e. prop guards), remote ID module, camera, anti-collision light, parachute recovery system, and/or payload **must not exceed 3.5 pounds (3 pounds, 8 ounces)**;
21. Operations Manual: The Responsible Person must update or revise the operations manual (aka CONOPs) submitted with the Waiver application for changes in the operation. The Responsible Person must track such revisions and present revised documents to the Administrator or an authorized representative upon request. The Responsible Person must also present revised documents when applying for extension of or amendment to this Waiver. If any revision to the manual would be contrary to the information provided in the waiver application or obviate a condition or limitation of this waiver, then the Responsible Person must apply for an amendment to this Waiver;
22. Operations subject to this waiver must cease as soon as possible in a manner that does not jeopardize the safety of human beings, property or other aircraft, if, at any time:
- a. Safety of human beings or property on the ground or in the air is in jeopardy;
 - b. Any failure to comply with the provisions of this Waiver exists;
 - c. Full-duplex communications cannot be maintained between the remote PIC and any VO participating in the operation;
23. The sUA must be equipped and operated with a Parachute Recovery System (PRS) conforming to the ASTM F3322-18 (or newer) standard.
- a. The PRS must be maintained per the manufacturers recommended procedures, and safety checked prior to flight;
 - b. The operation over human beings and moving vehicles occupied by people must immediately terminate if the PRS experiences an inflight failure or fails a safety check per the operator's manual;
 - c. The sUA must be operated at or above the minimum altitude specified in the PRS operator's manual when the sUA is over human beings and moving vehicles occupied by people; and
 - d. The RPIC must have the most recent version of the PRS operator's manual for the PRS being used in their possession, and readily accessible, during the operation. A digital copy of this manual is acceptable for this purpose;

SPECIAL PROVISIONS APPLICABLE TO ALL sUAS;

24. Lost Link Procedures: If the remote PIC loses command or control link with the sUA, the sUA must follow a predetermined route to immediately reestablish command and control link. If command and control link is not immediately reestablished and the remote PIC no longer has the ability to direct the sUAS to ensure compliance with applicable provisions of part 107, the sUA must follow the loss of command and control procedure as described in the waiver application;
25. The sUAS must be equipped and operated with a mechanism to shield or prevent rotating parts from causing lacerations to human skin (e.g., prop guards);

26. Transient operations over moving vehicles occupied by people are prohibited unless:
 - a. The sUA remains within a closed- or restricted-access site and all non-participants in the sUA operation are on notice of the sUAS operation prior to takeoff, or
 - b. For other than closed set operations, sUA operations shall be operated in a manner that minimizes risk to moving vehicles;
 - c. sUA up to and including 0.88 pounds must be operated no lower than fifty feet above ground level (AGL); and
 - d. sUA greater than 0.88 pounds must be operated at or above the minimum altitude specified in the PRS manufacturer's operator's manual;
27. Safety Review: Prior to operations under this Waiver the remote PIC must perform a safety review that addresses, at minimum, the following items as applicable:
 - a. Designated positions, physical locations, responsibilities, and Crew Resource Management;
 - b. Planned flight operating area;
 - c. Designated launch and recovery areas;
 - d. Verification of geo-fence boundaries;
 - e. Verification of return home and land flight profile, and course;
 - f. Procedures for avoidance of other aircraft and obstacles;
 - g. Procedures for operating under this waiver;
 - h. Land vehicle speed;
 - i. Intended flight path;
 - j. Abnormal procedures; and
 - k. Emergency procedures;
28. Sustained operations over moving vehicles occupied by people are prohibited unless the sUA operation remains within a closed- or restricted-access site and all non-participants in the sUA operation are on notice of the sUAS operation prior to takeoff;
29. Operations over people attending sporting events, concerts, crowds, political events, races, controlled access events, and other open-air assemblies of people is prohibited, unless, prior to sUAS operations conducted under this Waiver, the responsible person coordinates the sUAS operations with the event's security planner or venue's designee. For this Waiver, "coordinates" means contacting the venue designee or event's security planner and
 - a. Providing a copy of this Waiver,
 - b. Providing a schedule of planned sUAS operation(s) times,
 - c. Providing the location the remote PIC will be operating the sUAS from,
 - d. Providing the remote PIC's phone number where they can be contacted during sUAS operations, and
 - e. Receiving written confirmation from the event security planner or venue's designee that the above information has been provided to him/her;
30. The route of flight must be planned and flown to minimize the time the sUA is over people and moving vehicles occupied by people;

31. Prior to each flight a checklist must be used to aid in identifying potential ground and air hazards along the route of flight and in the immediate vicinity, completed by the RPIC, and briefed to the VO(s) and the person flying the drone. The checklist must cover the following items at a minimum:
- Identify areas or routes of low-level helicopter and airplane operations such as helipads, grass airstrips, airports, military operations areas below 500 feet above ground level (AGL), tour operator flights, and farmland suitable for agricultural aircraft operations, within one statute mile of the intended operating area or route;
 - Identify locations of expected pedestrian and vehicular traffic in the immediate vicinity of the operating area or route of flight; and
 - Identify the highest obstacle or obstruction in the operating area that may be encountered between the takeoff/home location and anywhere along the planned route of flight should a pre-programmed return-to-home (RTH) flight be initiated;
32. Prior to takeoff, the sUAS must be programmed to execute a pre-programmed RTH command if the signal is lost or disrupted for more than 5 seconds. The RPIC must program a RTH altitude that avoids any obstructions along the RTH route, limited to no higher than 400 feet AGL;
33. At least one VO is required for each operation over people and moving vehicles occupied by people. The VO(s) must understand the general concept of the operation and their specific duties.
- The VO(s) must be positioned where they can immediately alert the RPIC of collision hazards. If the VO(s) is(are) not collocated with the Remote Pilot in Command, the VO(s) must have direct voice communication with the RPIC at all times during the flight.
 - If voice communication is lost between the VO(s) and the RPIC, the operation must cease until the communication issue is resolved;
34. Operations conducted under this waiver are limited to location(s) that meet the performance-based criteria contained in the waiver application;
35. Unmanned Aircraft Systems (UAS): NON-SPECIFIC without a Dock System
- Operations conducted under this Waiver may only occur with the make and model sUAS as described in the Waiver application;
 - Additional UAS may be added to the operation as long as:
 - The operational parameters and procedures will remain as described in the Waiver application and supporting documentation. Any changes to the procedures required to incorporate the new UAS will require an Amendment request;
 - The new system can be operated under the Operational and Environmental Special Provisions as stated in the Waiver;
 - The technical ability of the UAS to comply with the Waiver Special Provisions must remain unchanged. All UAS used under this waiver must be in compliance with the GCS, C2, ADS-b, Anti-collision lighting, Emitter, Geofencing, Maintenance, and any DAA requirements stated in the Waiver Special Provisions;
 - If the UAS will be utilized with a remote Docking Station the Dock must be evaluated and found in compliance with the requirements of §107.15 and §107.49 for the ability of the RPIC to determine the UA is in a condition safe for flight from the remote piloting location. The docking station must present the RPIC the ability to clear the immediate flight area and assess weather conditions at the dock location;
 - The Responsible Person maintains a list of UAS eligible for use under this Waiver that includes the make and model of the UAS, date added to the list, and name of the person who affirms compliance with the stipulations of this provision. This list must be made available to the Administrator on request;

36. Unmanned Aircraft System: Dock Ops when used
 - a. Operations conducted under this Waiver may only occur with the make and model sUAS described in the waiver application. This includes the Docking Station specified in the CONOPS. Proposed operations of any other manufacturer, make or model of sUAS or Docking Station will require a new waiver application or a request to amend this Waiver; and
 - b. The sUA Docking Station must be equipped or provided with sufficient lighting to ensure the ability to determine the satisfactory condition of the sUA prior to flight for all operations and ensure the immediate takeoff and landing area is clear;
37. ADS-B out (1090/978 MHz) may not be transmitted from the sUAS when operating pursuant to this Waiver. An ADS-B in Receiver (other than a cell phone or third party internet services) must be operational and monitored during all operations pursuant to this Waiver;
38. The area of operation must be sufficiently illuminated to allow both the remote PIC and VO (when used) to identify people or obstacles on the ground, or a daytime site assessment must be performed prior to conducting operations that are the subject of this Waiver, noting any hazards or obstructions;
39. Anti-Collision Lighting: The sUA must be equipped with anti-collision lighting compliant with §107.29 to appropriately increase the conspicuity of the sUA. The anti-collision lighting system must be operational at all times;
40. Ground Control Station, Control and Communications (C2) System:
 - a. Telemetry: The sUAS ground control station must display in real-time the sUA altitude, position, direction of flight, ground speed, C2 signal strength, GPS or navigation system signal condition, battery condition, and sUA distance from the control station as described in the Waiver application;
 - b. Alerting: The remote PIC must ensure the GCS is configured to audibly and/or visually alert the remote PIC of degraded system performance, geofence loss of containment, loss of Control link with the sUA, and intrusion alerts as described in the Waiver application;
 - c. Emergency Profiles: The remote PIC must ensure the GCS is configured for automated emergency actions (e.g. RTL/RTH, altitude descend, position hold etc.) as described in the Waiver application; and
 - d. Sensors: the remote PIC must ensure any installed collision/obstacle avoidance sensors are operational;
41. Prior to conducting operations, simulation-based testing will be conducted as described in the waiver application;
42. As described in the waiver application, prior to operations subject to this waiver, a geo fence must be set to contain all sUA within the planned operational area;

43. UAS Maintenance: All sUAS operations conducted in accordance with this Waiver must comply with all manufacturer recommendations and limitations for the sUAS:

- a. The Responsible Person must maintain each sUAS and its components in accordance with manufacturer's instructions and recommendations. sUAS maintenance includes scheduled and unscheduled overhaul, repair, inspection, modification, replacement, and system software upgrades of the sUAS and its components necessary for flight;
- b. A log of all maintenance performed must be kept for each aircraft operated under this waiver. This log must be available to the remote PIC for review prior to conducting operations that are the subject of this waiver. Each sUAS maintenance log must be presented to the Administrator when requested. The log must contain the following information for each maintenance activity:
 - 1) A description (or reference data acceptable to the Administrator) of work performed;
 - 2) The date of completion of the work performed;
 - 3) The name of the person who performed the work; and
 - 4) The signature of the person who performed the work;
- c. Any sUAS that has undergone maintenance must undergo a functional test flight prior to conducting operations under this Waiver. The functional test flight may only be conducted under the standard requirements of part 107 (without waiver). A log entry must be made for each functional test flight.

The log entry must contain at minimum the:

- 1) Calendar date;
- 2) sUA registration number;
- 3) Remote PIC who performed the functional test flight;
- 4) Duration of the flight; and
- 5) The result of the functional flight test;

44. All emitters used in sUAS must be compliant with all applicable FCC regulations provisions of the FCC authorization granted for the emitter. A FCC Experimental authorization may not be used for sUAS operations under this Waiver; and

45. Operations conducted under this Waiver are limited to the locations meeting the site selection performance procedures as stated in the Waiver application.