

## Memorandum

Subject:

**ACTION:** Interim Guidance for Evaluating Area

- -

JUN 1 7 2004

Navigation (RNAV) Holding Patterns

From: Manager, Flight Technologies and Procedures

Division, AFS-400

Reply to Attn. of:

Date:

To: Program Director, Aviation System Standards, AVN-1

<u>PURPOSE</u>: This memorandum establishes interim guidance for evaluation of RNAV holding patterns.

BACKGROUND: Representative of the aviation industry expressed concerns regarding containment sufficiency of the RNAV holding patterns described in FAA Order 7130.3A, Holding Pattern Criteria, chapter 6. A Flight Procedure Standards Branch, AFS-420, limited mathematical analysis concluded the holding pattern dimensions may be inadequate in some entry leg scenarios with crosswind conditions that result in excessive wind drift while dead reckoning.

<u>POLICY</u>: Develop holding patterns on original RNAV procedures and perform biennial reviews using FAA Order 7130.3A, chapter 2, Conventional Holding Criteria. Use pattern sizes listed in Table 2 under the Fix-to-Navigational Aid Distance column for 15-29.9 nautical miles. For helicopter RNAV procedures, use pattern template size #4.

Please address questions concerning this policy to Don Pate, AFS-420, (405) 954-4164.

Original Signed By:

S John W. McGraw

cc:

AFS-400 (sus: 20041588-0) AFS-405/410/420/430/440