

Federal Aviation Administration

DOT/FAA/AM-05/16 Office of Aerospace Medicine Washington, DC 20591

Relationship of the Aircraft Mix Index With Performance and Objective Workload Evaluation Research Measures and Controllers' Subjective Complexity Ratings

Elaine M. Pfleiderer Civil Aerospace Medical Institute Federal Aviation Administration Oklahoma City, OK 73125

August 2005

Final Report

NOTICE

This document is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The United States Government assumes no liability for the contents thereof.

Technical Report Documentation Page

1. Report No. DOT/FAA/AM-05/16	2. Government Accession No		3. Recipient's Catalog No	
4. Title and Subtitle Relationship of the Aircraft Mix II	ndex With Performance and	d Objective	5. Report Date August 2005	
Workload Évaluation Research (P Subjective Complexity Ratings	OWER) Measures and Con	ntrollers'	6. Performing Organizatio	ın Code
7. Author(s)			8. Performing Organization	on Report No.
Pfleiderer EM				
9. Performing Organization Name and Addres	S		10. Work Unit No. (TRAIS	3)
FAA Civil Aerospace Medical Inst		11 Contract or Grant No		
P.O. Box 25082 Oklahoma City, OK 73125				
Oklaholila City, OK 75125				
12. Sponsoring Agency name and Address			13. Type of Report and P	eriod Covered
Office of Aerospace Medicine				
Federal Aviation Administration				
Washington DC 20591			14. Sponsoring Agency C	Code
washington, DC 20991				
15. Supplemental Notes				
Work was accomplished under ap	proved task AM-B05-HRR	-522.		
Aircraft mix (i.e., the mix of aircraft cited as a complexity factor in entropy fac	ft with different performant oute air traffic control. Ho ionship. The present study idity of aircraft mix as a co- ling data were collected fro oad Evaluation Research (1 l in 6-minute intervals for o produced four component Mix Index was most closely sociated with traffic comple- e "Complexity" ratings in r ft Mix Index failed to cont 47) and high-altitude (<i>R</i> =.5 ft mix appears to be associa- tors in the en route environ	ce characteristi- wever, scant att is the third in a ntributor to tra- m the Fort Wo POWER) meas each of the 36 s s with eigenval- y associated with exity. These var nultiple regress ribute significa- 57; R^2 =.33) sect ated with traffic ument.	cs in a sector) has been tention has been direct a series of investigation ffic complexity. Eightor th and Atlanta en rou ures and the Aircraft M amples. Principal Cor ues >1 accounting for h Component 1, whice iables were used as pre- ion analyses of low- ar ntly to the explained w or models. In the aggre complexity, it may no	a repeatedly red to a as designed to een 30-minute ite centers. Mix Index approximately th was edictors against ad high- rariance in the regate, the ot be as
17. Key Words Aircraft Mix, Air Traffic Control, Workload	Airspace Complexity,	18. Distribution Statement Document is available to the public through the Defense Technical Information Center, Ft. Belvior, VA 22060; and the National Technical Information Service, Springfield, VA 22161		
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified		21. No. of Pages	22. Price

Form DOT F 1700.7 (8-72)

Reproduction of completed page authorized

Relationship of the Aircraft Mix Index With Performance and Objective Workload Evaluation Research Measures and Controllers' Subjective Complexity Ratings

Aircraft mix has been proposed as one of the traffic characteristics contributing to sector complexity in en route air traffic control (e.g., Christien & Benkouar, 2003; Federal Aviation Administration [FAA], 1984; FAA, 1999; Grossberg, 1989; Histon, Aigoin, Delahaye, Hansman, & Puechmorel, 2001; Mogford, Murphy, Roske-Hofstrand, Yastrop, & Guttman, 1994; Robertson, Grossberg, & Richards, 1979). However, its reputation has primarily been based on anecdotal evidence with little attention focused on examining this relationship statistically. The present study is the third in a series of investigations designed to define, quantify, and assess the validity of aircraft mix as a contributor to traffic complexity in en route air traffic control.

First in the series was an investigation of the salient features of aircraft mix as it relates to aircraft performance characteristics (Pfleiderer, 2000). For this analysis, 30 Certified Professional Controllers (CPCs) from several en route centers across the United States provided average speed, climb, and descent rate estimates for a sample of 30 distinct aircraft types. A matrix of squared Euclidean distances was derived from summary estimates (i.e., means of speed, climb, and descent rates) and used to construct a multidimensional scaling (MDS) model of controllers' perceptions of the aircraft performance characteristics of the aircraft. Interpretation of the two-dimensional MDS model suggested that Dimension 1 was related to engine type, and Dimension 2 was associated with weight class. The results were interpreted as evidence of performancebased prototypes (for further explanation, see Pfleiderer, 2000). However, it was also evident from the position of the elements (i.e., aircraft types) in the derived stimulus space that it might be possible to develop a measure of aircraft mix using these two easily obtained variables.

Pfleiderer (2003a) continued that line of investigation in a study designed to determine whether controllers' perceptions of aircraft performance were comparable to the actual recorded performance of aircraft in a sample of live air traffic data. In general, controllers' perceptions of aircraft performance characteristics were similar to the actual performance of the aircraft in the recorded data. However, weight class was far less salient as a separate dimension in the model derived from the matrix of System Analysis Recording (SAR) data than in the model based on controller estimates. The relationship between weight class and engine type in the SAR data model was a clear reminder that weight class is a correlate of engine type (i.e., most piston-driven aircraft are Small, most turboprops are Large, all Heavy aircraft are jets). This result led to the conclusion that engine type alone was an appropriate and sufficient dimension upon which to base the calculation of the Aircraft Mix Index. (For a complete description of Aircraft Mix Index calculations, see Appendix A.)

Based on the apparent success of the first phase of the investigation, a second phase was initiated that focused on testing the Aircraft Mix Index for its ability to discriminate between altitude strata. After all, if the index had sufficient variability and precision, it should be able to discriminate between high- and low-altitude sectors. This was based on the assumption that high-altitude sectors should have a lower incidence of aircraft mix due to the relatively low service ceilings of some aircraft, whereas low-altitude sectors should have a much higher incidence of aircraft mix because all aircraft must climb and descend through low-altitude airspace at some point in their flight. For this analysis, the Aircraft Mix Index was calculated in 15-minute intervals for all active sectors within a 1-hour sample of air traffic data recorded at the Kansas City en route center (15 high-altitude and 13 low-altitude sectors). As anticipated, values of the Aircraft Mix Index tended to be higher in low-altitude sectors than in high-altitude sectors. A comparison of the two groups using the distribution-free Mann-Whitney U statistic (Mann & Whitney, 1947) revealed that the Aircraft Mix Index was reliably different between highand low-altitude sectors.

Because the Aircraft Mix Index was able to discriminate between sector strata, it passed the "minimum test" to be considered as a possible addition to the suite of Performance and Objective Workload Evaluation Research (POWER) variables. POWER refers to a set of measures developed for quantifying en route air traffic controller activity and task load (for a detailed description of POWER measures and methodology, see Mills, Pfleiderer, & Manning, 2002). In the first phase of the present study, I conducted an evaluation of the relationship between the Aircraft Mix Index and existing POWER measures using Principal Components Analysis (PCA). PCA is a statistical technique often used to reveal patterns of correlations among variables. Values in the component loading matrix produced by PCA represent the correlation of individual variables with the underlying dimension the component describes. If the Aircraft Mix Index was redundant with traffic volume (as opposed to describing some aspect of the complexity associated with that traffic) it should load onto the same component as the total number of controlled aircraft. On the other hand, if the Aircraft Mix Index provided information about the complexity associated with the presence of aircraft with different performance characteristics then it should load onto a component with others that relate to traffic complexity. Moreover, its loading should be of sufficient magnitude to suggest that this is a reliable relationship.

Though PCA offers insight into the relationship of the Aircraft Mix Index relative to the other POWER variables, it cannot tell us whether the information it provides is unique. More importantly, it does not address the larger question regarding the relative contribution of aircraft mix to traffic complexity. Therefore, contingent upon the results of the PCA, a multiple regression analysis was conducted using a subjective criterion of "Complexity" provided by controllers from the each of the en route centers sampled. The predictor variable set consisted of those variables identified by the PCA as being most closely related to the "Complexity" dimension/construct. The results of the multiple regression analysis should tell us whether aircraft mix (as measured by the Aircraft Mix Index) contributes a significant amount of unique information to the prediction of controllers' perceptions of sector complexity.

METHOD

System Analysis Recording data and subjective complexity ratings were generously provided by researchers associated with the Dynamic Density project (e.g., Kopardekar & Magyarits, 2003). Traffic samples selected for the analyses were collected at the Fort Worth and Atlanta en route centers. The Fort Worth data consisted of samples from six high-altitude and three low-altitude sectors. The Atlanta data were from five high-altitude and four low-altitude sectors. Two 30-minute samples were collected from each of the selected sectors (a total of 36 samples). Traffic sample descriptions and sector maps are provided in Appendix B.

Three controllers individually viewed Systematic Air Traffic Operations Research Initiative (SATORI; Rodgers & Duke, 1993) re-creations and rated the complexity of the traffic situation on a scale from one to seven (lowest to highest) at 2-minute intervals throughout the 30-minute sample time frame. For the current study, means of the individual controller ratings were averaged over 6-minute intervals to create a total of 180 observations.

POWER measures were computed in 6-minute intervals for each of the traffic samples, producing a total of 180 observations for each POWER measure. Variables selected for the PCA (shown in Table 1) consisted of five POWER measures that have consistently demonstrated a relationship with controller activity and task load (e.g., Manning, Mills, Fox, Pfleiderer, & Mogilka, 2001; Mills, Pfleiderer, & Manning, 2002), and five thought to relate to traffic complexity. The selected Traffic Complexity/ Proximity variables are relatively new additions to the

POWER Variable	
Number of Controlled Aircraft	
Number of R-side Entries	
Number of R-side Entry Errors	Controller Activity/Task load
Number of RA-side Entries	
Number of RA-side Entry Errors	
Aircraft Mix Index	
Mean Lateral Distance	
Mean Vertical Distance	Traffic Complexity/Proximity
Number of Altitude Changes	
Number of Heading Changes	

Table 1. POWER Variables Selected for Principle Components Analysis (PCA)

POWER suite of measures. (Consequently, this analysis also represents a serendipitous opportunity to examine whether or not these variables do, in fact, appear to describe a separate dimension.) The reasons for including the Aircraft Mix Index have already been described in some detail, but the rationale behind the other variables in this group deserves some explanation.

There is little doubt that the number of aircraft within a sector affects controller workload. It is also doubtful that this measure alone sufficiently captures all aspects of the complexity associated with that traffic (Hilburn & Flynn, 2004; Mogford et al., 1994). One of the traffic complexity issues that should be addressed is the relative position of the aircraft. For the suite of POWER measures, we have opted to incorporate summary measures of aircraft proximity (i.e., Mean Lateral Distance, Mean Vertical Distance). Though not as elegant as some measures (e.g., clustering techniques developed by Delahaye & Puechmorel, 2000), they do have the advantage of reflecting the dimensions controllers use to evaluate aircraft separation.

The number of climbing and descending aircraft is well established as a contributor to traffic complexity (e.g., Christien & Benkouar, 2003; Histon et al., 2001; EUROCONTROL, 2002b, as cited in EUROCON-TROL, 2004; Grossberg, 1989; Robertson, Grossberg, & Richards, 1979; Stein, 1985). The number of altitude changes provides more information than a count of the number of aircraft in transition. Altitude changes have been shown to correspond well with the number of altitude clearances and may provide some indication of the amount of workload associated with monitoring the response to and the effectiveness of the issued clearance (Pfleiderer, 2003b). As shown in Figure 1, heading changes have the potential to profoundly impact the complexity of an air traffic situation, whether they occur as part of the scheduled flight plan or in response to a clearance. It is not surprising, therefore, that heading changes have been shown to contribute significantly to sector complexity (e.g., Laudeman, Sheldon, Branstrom, & Brasil, 1998). It should be noted that POWER only counts heading changes greater than or equal to 10° that persist for a minimum of 36 seconds. These computer-detected heading changes have been shown to correspond well with the number of issued heading clearances (Pfleiderer, 2003b).

RESULTS AND DISCUSSION

Principal Components Analysis

Descriptive Statistics

As shown in Table 2, the distributions of most of the variables selected for the PCA approximated normality. However, distributions of the Aircraft Mix Index, R-side Entry Errors, and Radar Associate Entry Errors deviated significantly. Although assumptions regarding normality are not generally in effect when PCA is used descriptively, in this particular application it is important to remember that PCA is sensitive to the sizes of correlations. To the extent that normality fails, the solution may be degraded and this should be considered when interpreting the results of the analysis (Tabachnik & Fidell, 1989).

Preliminary Comparative PCA

Because the data were sampled from different populations (i.e., en route centers), preliminary comparative analyses were conducted to determine whether the two data sets were similar enough to justify combining them.



Figure 1. Potential Effect of Heading Changes on the Complexity of Traffic Patterns (Adapted from Hilburn & Flynn, 2004 after van Gent, Hoekstra, & Ruigrok, 1997)

Variable	Mean	S.D.	Skew. ¹	Kurtosis ²
Aircraft Mix Index	10.85	14.78	2.23	6.62
Mean Lateral Distance (nm)	48.65	13.84	.25	48
Mean Vertical Distance (ft/100)	54.59	17.77	.74	.53
Number of Altitude Changes	6.86	3.71	.37	13
Number of Heading Changes	4.41	3.03	.71	14
Number of Controlled Aircraft	14.82	4.02	.25	.41
Number of R-side Entries	33.99	11.74	.31	46
Number of R-side Entry Errors	2.23	2.35	1.78	4.13
Number of RA-side Entries	6.64	5.97	.98	.41
Number of RA-side Entry Errors	.66	1.21	3.04	12.31

 Table 2. Principal Components Analysis Descriptive Statistics (N = 180)

¹S.E. Skew. = .181; ²S.E. Kurt. = .360

This was necessary because the number of observations available from the individual facility data sets is somewhat small for a successful PCA. Indeed, according to Comrey's (1973) guidelines for sample size in PCA, a sample size of 90 (i.e., that seen if the sites were analyzed separately) would fall somewhere between "poor" and "very poor." Though it is certainly undesirable to overanalyze any set of data, the best (and possibly the only) way to determine whether or not two data sets are similar enough for a combined analysis is to conduct separate PCAs and compare the extracted components. For these analyses, a maximum of two components (i.e., the hypothesized number of dimensions in the selected variables) was chosen as the criterion for component extraction. This decision was based on the fact that we were only interested in the similarities between the two data sets and not in the subtle differences that might exist between them. In other words, we simply needed to know if *comparable* analyses would yield *comparable* results. Specifying the maximum number of components that might be extracted ensured that the analyses were comparable.

In the Fort Worth sample, the two extracted components accounted for approximately 54% of the variance. Component 1 had an eigenvalue of 3.00 and accounted for approximately 30% of the variance, whereas Component 2 had an eigenvalue of 2.40 and accounted for approximately 24% of the total variance.

In the sample of data from the Atlanta en route center, the two extracted components accounted for approximately 48% of the variance. Component 1 had an eigenvalue of 2.68 and accounted for approximately 27%, whereas Component 2 had an eigenvalue of 2.10 and accounted for approximately 21% of the total variance.

Though the two samples did not produce identical results, the extracted components were reasonably similar. As shown in Table 3, the first extracted component in the Fort Worth sample (ZFW-1) was comparable to the second extracted component in the Atlanta sample (ZTL-2). Component ZFW-2 was similar to ZTL-1 except for lateral and vertical distances. (Please note that the order of extraction is somewhat irrelevant. Varimax rotation tends to reapportion variance among components so they become relatively equal in importance.) The recommended procedure for statistically comparing the pattern and magnitude of component loadings is the Pearson product-moment correlation. The correlation of ZFW-1 and ZTL-2 yielded a coefficient of r = .79. The correlation of ZFW-2 and ZTL-1 produced an r= .83. Both correlations were significant at the <.01 level, indicating that the data were similar enough for a pooled analysis.

Pooled Sample PCA

Principal components analysis is generally used in the exploratory stages of research when the exact number and nature of the dimensions are not known. Although the selected variables were hypothesized to represent elements of two dimensions, extraction of one or more additional components would not be entirely unexpected. Therefore, a minimum eigenvalue of 1.00 (as opposed to a specified number of components) was selected as the criterion for component extraction, thus allowing for true exploration of the data.

Varimax rotation was selected for the analysis because it increases the interpretability of the solution. As the name suggests, varimax (*vari*ance *max*imizing procedure) simplifies components by maximizing the variance of

Variable	Component		Comp	oonent
	ZFW-1	ZFW-2	ZTL-1	ZTL-2
Aircraft Mix Index	.78	.14	34	.75
Lateral Distance (nm)	73	.29	.54	44
Vertical Distance (ft/100)	.73	28	66	.24
Altitude Changes	.86	.06	.19	.75
Heading Changes	.58	.15	.33	.74
Number of Aircraft	05	.68	.73	.30
R-side Entries	35	.63	.71	.25
R-side Entry Errors	.15	.73	.39	02
RA-side Entries	14	.68	.60	.12
RA-side Entry Errors	.23	.57	.39	.00

Table 3. Preliminary Comparative PCA – Rotated Component Matrices*

* Varimax rotation converged in 3 iterations for both analyses.

the loadings within components. Simply stated, varimax makes small loadings smaller and large loadings larger. This simplifies interpretation of the components by making it more obvious which variables are associated with them (Tabachnik & Fidell, 1989).

Table 4 contains a correlation matrix of the variables selected for analysis. It is clear that many of the variables are related, though the magnitudes are moderate. Nevertheless, it is encouraging that the Aircraft Mix Index appears to be more closely associated with the "Complexity/Proximity" variables than with others in the matrix.

PCA with varimax rotation converged in eight iterations and produced four components with eigenvalues > 1. These components accounted for approximately 71% of the variance in the data set. As shown in the rotated component matrix in Table 5, all variables loaded onto at least one component with a loading of .40 or greater.

Component 1 had an eigenvalue of 2.40 and accounted for approximately 24% of the variance in the data set. Without exception, the variables associated with this component were selected to represent various aspects of traffic complexity. Values in the loading matrix describe the correlation of each variable with the underlying dimension the component represents. Notice that the Aircraft Mix Index has one of the highest loadings on this component.

Component 2 had an eigenvalue of 2.06 and accounted for about 21% of the variance. The two variables with the highest loadings, the number of controlled aircraft and the number of Radar controller computer entries, are straightforward activity measures. Radar controller entry errors tend to increase as controller activity increases. Therefore, a conservative loading of .54 on this component makes sense within the context of the other variables.

Component 3 had an eigenvalue of 1.35 and accounted for approximately 13% of the variance in the data set. Generally, components described by only two variables are considered to be unreliable and are not interpreted. However, this component has emerged in a number of analyses (e.g., Mills, Pfleiderer, & Manning, 2002) suggesting that it is, in fact, reliable. The extraction of "Radar Associate Activity" as a separate component may reflect the unique relationship that Radar Associate Entries and Errors share with other activity measures. When activity is relatively low, a Radar controller working alone has time to make entries on the Radar Associate's console (because some entries can only be made from that console). As the traffic situation becomes more demanding, the Radar controller no longer has time to make entries from the RA-side console. During peak hours, a Radar Associate controller is assigned to the sector and entries made from the RA-side console become more frequent. It is probably the distinctive "J-shaped" distribution of RA-Entries and their relationship to RA-Entry Errors that distinguishes these variables as a separate component. Therefore, Component 3 might be viewed as a subset of general activity.

Component 4 had an eigenvalue of 1.27 and accounted for approximately 13% of the variance. The same caveat regarding two-variable components applies to Component 4, only in this case it may be more justified. Components defined by only two variables may be reliable if the variables are highly correlated with one another (i.e., r > .70) and are relatively uncorrelated with others in the variable set. These variables fail to meet the first criterion in that

Table 4. Correlation Mé	atrix (N -= 180)								
	Aircraft Mix Index	Lateral Distance	Vertical Distance	Altitude Changes	Heading Changes	Controlled Aircraft	R-side Entries	R-side Entry	RA-side Entries
Lateral Distance	34**								
Vertical Distance	.41**	40**							
Altitude Changes	.38**	42**	.34**						
Heading Changes	.31**	24**	.07	.48**					
Controlled Aircraft	04	.35**	14	.16*	.30**				
R-side Entries	17*	.25**	33**	.08	60 [.]	.54**			
R-side Entry Errors	05	90.	07	.12	.04	.40**	.39**		
R-side Entries	90'-	.17*	26**	01	.15	.26**	.14	.05	
RA-side Entry Errors	.05	04	01	.11	.04	.08	.15*	.35**	.39**
** <i>p</i> < .01; * <i>p</i> <05									

6

	Component			
Variable	1	2	3	4
Aircraft Mix Index	.71			
Mean Lateral Distance (nm)	67			
Mean Vertical Distance (ft/100)	.61			
Number of Altitude Changes	.80			
Number of Heading Changes	.64			
Number of Controlled Aircraft		.85		
Number of R-side Entries		.79		
Number of R-side Entry Errors		.54		.69
Number of RA-side Entries			.89	
Number of RA-side Entry Errors			.47	.79

Table 5. Principal Components Analysis Rotated Component Matrix

* Component loadings < .40 not shown.

the bivariate correlation between them (r = .35) is less than .70. As shown in the matrix in Table 4, bivariate comparisons between each of these variables with others in the set resulted in a considerable number of significant correlations. Consequently, this component fails to meet criteria that would indicate it might be reliable. It is also important to note that the distributions of both these variables are severely positively skewed and leptokurtotic. Therefore, it is likely that the communality described by this component reflects a similarity of distribution rather than of meaning. On the other hand, data entry errors tend to increase with the number of entries. As such, Component 4 might also be viewed as a subset or correlate of general activity.

The results of the PCA demonstrate that the Aircraft Mix Index was consistently associated with other variables thought to relate to traffic complexity. Moreover, the magnitude of its loading (.71) suggests that this is a reliable relationship. This leads us to the next phase of the experiment: Multiple regression analysis using the variables associated with the "Complexity" dimension (Aircraft Mix Index, Mean Lateral Distance, Mean Vertical Distance, Number of Altitude Changes, and Number of Heading Changes) to predict controllers' subjective "Complexity" ratings.

Multiple Regression Analysis

Perhaps the most important assumption of a regression analysis is that the observations are sampled from the same population. Although the preliminary comparative PCA indicated that the data from the two facilities were similar enough to justify pooling, the results of comparisons of the Aircraft Mix Index in high- and low-altitude sectors in a previous study (i.e., Pfleiderer, 2003b) suggested that high- and low-altitude sectors might constitute heterogeneous samples. Therefore, initial data screening was conducted by visually examining scatterplots of each predictor variable against the criterion with observations color-coded according to altitude strata. It was immediately apparent that highand low-altitude sectors should be analyzed separately. Unfortunately, splitting the sample resulted in a sample size of 70 for the low-altitude sectors (i.e., a 14:1 case to independent variable ratio). Ideally, we would want a ratio of 20 cases for every predictor to ensure sufficient statistical power to detect small effect sizes and to accommodate measurement error. Nevertheless, a 14:1 ratio exceeds the absolute minimum requirement of five cases for every predictor (Tabachnik & Fidell, 1989).¹

Descriptive Statistics

Descriptive analyses were conducted separately for the high- and low-altitude samples. The criterion variable (i.e., Complexity ratings provided by controllers) originally consisted of discrete values representing anchor points along an underlying continuum of the controllers' perceptions of traffic complexity. However, the Complexity ratings used in this analysis represent the means of ratings taken every 2 minutes, summarized over 6-minute intervals. As such, these ratings were normally distributed in both sample sets (see Table 6).

¹ Please note that splitting the sample into high- and low-altitude sectors was *not* an option for the principal components analysis. Simply stated, if N=90 was insufficient for PCA then N=70 was even more so.

 Table 6. Multiple Regression Analysis Descriptive Statistics

 Low-Altitude Sample (N = 70)

Variable	Mean	S.D.	Skew. ¹	Kurtosis ²
Low Altitude Sample (N = 70)				
Complexity Ratings	2.65	1.05	.35	93
Aircraft Mix Index	22.91	17.53	1.43	2.95
Square Root Aircraft Mix Index	4.44	1.79	.35	02
Mean Horizontal Distance (nm)	36.23	7.54	.20	57
Mean Vertical Distance (ft/100)	66.46	17.99	.37	.25
Number of Altitude Changes	8.83	3.79	.05	05
Number of Heading Changes	5.10	3.10	.55	29
High-Altitude Sample (<i>N</i> = 110)				
Complexity Ratings	3.84	1.07	.13	26
Aircraft Mix Index	8.63	3.88	16	21
Mean Horizontal Distance (nm)	56.55	10.80	.28	.06
Mean Vertical Distance (ft/100)	47.04	12.88	.59	.37
Number of Altitude Changes	5.60	3.07	.26	47
Number of Heading Changes	3.97	2.91	.83	.10

¹Low-Altitude: S.E. Skew. = .287; High-Altitude: S.E. Skew. = .230

² Low-Altitude: S.E. Kurt. = .566; High-Altitude: S.E. Kurt. = .457

In the low-altitude sector sample, the distribution of the Aircraft Mix Index deviated by as much as five standard deviations in both skewness and kurtosis. Square root transformation of the Aircraft Mix Index in this sample reduced deviations to less than one standard deviation from normal. In the high-altitude sector sample, transformation of the Aircraft Mix Index was contraindicated because transformation would create unacceptable deviations in a distribution that was acceptable in its natural state. (Indeed, all the selected variables were normally distributed in the high-altitude sample.)

Correlations. Tables 7 and 8 contain matrices of Pearson's product-moment correlations for all variable pairs in each of the sub-samples. In the low-altitude sample (Table 7), the Aircraft Mix Index exhibits a significant relationship with both the criterion and several of the predictors. However, the Aircraft Mix Index failed to demonstrate a significant bivariate association with any of the other variables in the high-altitude sector sample (Table 8).

Tests of Assumptions

Multicollinearity. Multicollinearity refers to a very strong linear relationship between sets of predictor variables that renders the regression coefficients unstable (Fox, 1991; Tabachnik & Fidell, 1989). It is important to note that it is not the bivariate correlations among the predictors that creates multicollinearity, but rather the multiple correlation of the regression of a particular predictor on the others. Therefore, the best way to test for multicollinearity in the predictor set is to conduct a series of regressions with each of the predictors taking turns as the criterion and examining the squared multiple correlations for perfect or near perfect values (which would indicate multicollinearity). The results of these tests when conducted on the selected set of independent variables revealed no indication of multicollinearity in either the high- or low-altitude samples.

Outliers. No univariate outliers (i.e., cases with values greater than three standard deviations from the mean) were detected in either the low-altitude or high-altitude sector samples. Mahalanobis distances using p < .001 failed to uncover any multivariate outliers (i.e., cases with an unusual pattern of values) in either data set.

Table 7. Correlation Matrix: Low-Altitude (N = 70)

	Complexity Ratings	Aircraft Mix Index (Transformed)	Mean Lateral Distance	Mean Vertical Distance	Altitude Changes
Aircraft Mix Index (Transformed)	.34**				
Mean Lateral Distance	04	.35*			
Mean Vertical Distance	06	.30*	.1		
			1		
Altitude Changes	.45**	.29*	_**	.02	
			.3		
			2		
Heading Changes	.67**	.48**	_	11	.54**
			.0		
			4		

** *p* = < .01; * *p* < .05

Table 8. Correlation Matrix: High-Altitude Sample (N = 110)

	Complexity Ratings	Aircraft Mix Index	Mean Lateral Distance	Mean Vertical Distance	Altitude Changes
Aircraft Mix Index	01				
Mean Lateral Distance	28**	.09			
Mean Vertical Distance	23*	08	10		
Altitude Changes	.26**	04	13	.29**	
Heading Changes	.48**	07	22*	.04	.39**

** *p* = < .01; * *p* < .05

Table 9. Regression of POWER Complexity Variables on ATC Complexity Ratings:Low-Altitude Sample

Model Summary	R	R ²	Adj. R ²	S.E. Est.
	.68**	.47	.42	.79
Variable	b	S.E.	ß	sr ²
Transformed Aircraft Mix Index	.003	.072	.005	.00
Mean Lateral Distance (nm)	.001	.015	.009	.00
Mean Vertical Distance (ft/100)	.001	.006	.024	.00
Number of Altitude Changes	.032	.033	.113	.01
Number of Heading Changes	.216	.042	.620	.22**

Significance levels derived from *t*-tests: ** p < .01; * p < .05

Linearity and equality of variance. The assumption of linearity and the assumption of constant variance of Y for all values of X can be easily tested by visually examining a plot of residuals against predicted values. If both assumptions are met, there will be no systematic pattern in the plots. Studentized residuals against the predicted values were randomly distributed in a horizontal band around zero, indicating that the assumptions were met.

Normal distribution of errors. One of the simplest ways to test whether errors of prediction are normally distributed is by visual examination of a cumulative probability plot of the observed distribution of residuals against that expected of a normal distribution. If the two distributions are identical, a straight line results. Cumulative probability plots demonstrated that the assumption of normally distributed errors was met.

Independence of errors. Because the scenario data were collected sequentially, they were screened to determine whether the time series had produced systematic variance in errors. Unfortunately, statistical procedures for testing sequential correlation of adjacent error terms (e.g., the Durbin-Watson) were not designed to test discrete groups of sequential data. Therefore, Studentized residuals were plotted against the sequence variable and visually examined. Non-independence of prediction errors in these data would manifest itself in "zigzag" or "herringbone" patterns. That is, each sequential group of five observations would have a discernable pattern of increasing or decreasing error. No patterns were detected, thus indicating that the assumption of independence of errors had been met.

Regression Model: Low-Altitude Sample

Standard multiple regression analysis of the low-altitude sector sample produced a multiple R=.69 which was significantly different from zero, F(5,62) = 10.97, p<.01. As shown in Table 9, the regression model derived from the selected variables accounted for approximately 47% of the variance in Complexity ratings. Table 9 also contains unstandardized regression coefficients (*b*), their standard errors (*S.E.*), standardized regression coefficients (*B*), and squared semipartial correlations (sr^2) for each of the predictors. In standard multiple regression, sr^2 represents the unique contribution of a predictor to the total variance explained. It is clear that the Number of Heading Changes was the only variable that accounted for a significant amount of unique variance (22%). The difference between R^2 and the sum of sr^2 for all predictors in the variable set represents shared variance. Thus, 23% of the variance described by R^2 was unique whereas 24% was shared.

Regression Model: High-Altitude Sample

Because the value of the Aircraft Mix Index is set to "system missing" in the absence of any aircraft with differing performance characteristics within a given sector, there were a considerable number of missing values in the high-altitude data set. Nevertheless, standard multiple regression analysis produced a multiple R=.57, which was significantly different from zero, F(5,40) = 3.94, p <.01. As shown in Table 10, the only variable to account for a significant amount of unique variance in this data set was Mean Vertical Distance (16%). The Number of Altitude Changes (7%), the Number of Heading Changes (5%), and Mean Lateral Distance (3%) added to the total 31% unique variance explained, but these contributions were not statistically significant. Again, the Aircraft Mix Index failed to contribute any unique information to the prediction of controllers' Complexity ratings.

CONCLUSIONS

It is important to note that the list of predictors included in the regression analyses was not intended to be exhaustive. It is certainly possible, even probable, that other measures might account for additional variance in

Table 10. Regression of POWER Complexity Variables on ATC Complexity Ratings:

 High-Altitude Sample

Model Summary	R	R ²	Adj. R ²	S.E. Est.
	.57**	.33	.25	.80
Variable	b	S.E.	ß	sr ²
Aircraft Mix Index	.000	.031	002	.00
Mean Lateral Distance (nm)	017	.013	175	.03
Mean Vertical Distance (ft/100)	034	.011	502	.16**
Number of Altitude Changes	.123	.063	.321	.07
Number of Heading Changes	.108	.061	.250	.05

Significance levels derived from *t*-tests: ** p < .01; * p < .05

controllers' complexity ratings. Therefore, the results should not be interpreted as evidence that a single variable is sufficient to describe complexity in the en route environment. The focus of the analyses was simply to assess the relative contribution of aircraft mix to sector complexity. The fact that the Aircraft Mix Index failed to explain a significant amount of unique variance in controllers' Complexity ratings was disappointing, particularly with respect to the low-altitude sample, but not entirely unanticipated. Historically, the evidence supporting aircraft mix as a complexity factor has been anecdotal rather than statistical, no doubt because aircraft mix was considered to be "non-quantifiable" (e.g., FAA, 1984). Certainly controllers' verbal representations/reports constitute a valuable heuristic, but with such evidence comes the risk of misattribution. For example, a specific factor might be particularly salient to the controller during periods of perceived increases in "workload" or "complexity" and yet be a mere correlate of the factor that is actually driving their subjective experience. Thus, it is particularly important to make every attempt to quantify and assess each proposed complexity factor to determine its relative influence and relationship with other factors.

This is not to say that aircraft mix should be automatically discounted based on the results of a single analysis. It is entirely possible that aircraft mix does not, in fact, share a linear relationship with complexity and therefore cannot be captured using a linear regression analysis. Hilburn and Flynn (2004) have proposed that linear regression is ill suited for the study of air traffic complexity because "complexity factors combine in a non-linear way. Though the constellation of factors might well apply across contexts, the relative importance of each differs by context" (p. 200).

Another potential reason that aircraft mix failed to describe a significant amount of variance in controllers' complexity ratings is that it might only be a relevant factor in a few sectors, but in those sectors it is a major contributor to traffic complexity. Every sector is unique. This presents a challenge when attempting to build models that will generalize. It is, therefore, vital to investigate the potential of aircraft mix and other prospective complexity factors using data collected at multiple facilities with a number of different statistical strategies before drawing any firm conclusions.

In that same vein, as gratifying as it may be that all the variables selected to represent "Traffic Complexity/ Proximity" in the principal components analysis formed a single dimension, there is no guarantee that this would be the case in all data sets. Neither do these variables represent a comprehensive list of factors that might relate to sector complexity. A considerable amount of work has been done in this area (for an excellent review of the literature, see EUROCONTROL, 2004) and many of the proposed measures will be considered as possible additions to the POWER variables. Each candidate will be tested with the same rigor as the Aircraft Mix Index using similar methodology (i.e., examining the validity of each measure individually, testing its performance within the framework of the POWER variable suite, then examining its contribution relative to an external criterion). Each iteration of this process brings us closer to developing a set of measures that might comprehensively describe the sector environment to better understand the nature of sector complexity and its effects on controller workload and performance.

REFERENCES

- Christien, R., & Benkouar, A. (2003, June). Air traffic complexity indicators and ATC sectors classification. Paper presented at the 5th USA/Europe Air Traffic Management R&D Seminar, Budapest, Hungary.
- Comrey, A.L. (1973). *A first course in factor analysis.* New York: Academic Press.
- Delahaye, D. & Puechmorel, S. (2000). *Air traffic complexity: Towards intrinsic metrics.* Paper presented at the 3rd USA/Europe Air Traffic Management R&D Seminar, Napoli, Italy.
- EUROCONTROL (2004, March). *Cognitive complexity in air traffic control: A literature review.* EEC Note No. 04/04. Brétigny-sur-Orge, France: Author.
- Federal Aviation Administration (1984). *Establishment* and validation of en route sectors. (FAA Order No. 7210.46). Washington, DC: Author.
- Federal Aviation Administration (1999). Position classification standard for air traffic control: Series ATC – 2152 terminal and en route. Washington, DC: Author.
- Fox, J. (1991). *Regression diagnostics: An introduction*. Sage University Paper series on Quantitative Applications in the Social Sciences, 07-079). Newbury Park, CA: Sage.
- Grossberg, M. (1989, April). Relation of sector complexity to operational errors. *Quarterly report of the Federal Aviation Administration's Office of Air Traffic Evaluations and Analysis.* Washington, DC: Federal Aviation Administration.

- Hilburn, B., & Flynn, G. (2004, March). *Toward a non-linear approach to modeling air traffic complexity.*Paper presented at the 2nd Human Performance Situation Awareness and Automation Conference, Daytona Beach, FL.
- Histon, J.M., Aigoin, G., Delahaye, D., Hansman, R.J., & Puechmorel, S. (2001, December). *Introducing* structural considerations into complexity metrics. Paper presented at the 4th USA/Europe Air Traffic Management R&D Seminar, Santa Fe, NM.
- Kopardekar, P., & Magyarits, S. (2003, June). Measurement and prediction of dynamic density. Paper presented at the 5th USA/Europe Air Traffic Management R&D Seminar, Budapest, Hungary.
- Laudeman, I.V., Sheldon, S.G., Branstrom, R., & Brasil, C.L. (1998). Dynamic density: An air traffic management metric. (NASA/TM-1998-112226). Washington, DC: National Aeronautics and Space Administration.
- Mann, H.B., & Whitney, D.R. (1947). On a test of whether one of two random variables is stochastically larger than the other. *Annals of Mathematical Statistics*, 18, p. 50-60.
- Manning, C.A., Mills, S.H., Fox, C., Pfleiderer, E.M., & Mogilka, H. (2001, May). The relationship between air traffic control communications events and measures of controller taskload and workload. Paper presented at the 72nd Annual Scientific Meeting of the Aerospace Medical Association, Reno, NV.
- Mills, S.H., Pfleiderer, E.M., & Manning, C.A. (2002). POWER: Objective activity and taskload assessment in en route air traffic control. (Report No. DOT/ FAA/AM-02/02). Washington, DC: Office of Aerospace Medicine.²
- Mogford, R.H., Murphy, E.D., Roske-Hofstrand, R.J., Yastrop, G. & Guttman, J.A. (1994). Application of research techniques for documenting cognitive processes in air traffic control: Sector complexity and decision making. (Report No. DOT/FAA/ CD-TN94/3). Atlantic City, NJ: Federal Aviation Administration Technical Center.

- Pfleiderer, E.M. (2003a). Development of an empiricallybased index of aircraft mix. (Report No. DOT/FAA/ AM-03/8). Washington, DC: Office of Aviation Medicine.²
- Pfleiderer, E.M. (2003b, May). Relationship between computer-detected altitude, heading, and speed changes with controller clearances in en route air traffic control. Paper presented at the 74th Annual Scientific Meeting of the Aerospace Medical Association, San Antonio, TX.
- Robertson, A., Grossberg, M., & Richards, J. (1979). Validation of air traffic controller workload models. (Report No. DOT/FAA/RD-79/83). Cambridge, MA: U.S. Department of Transportation Research and Special Programs Administration – Volpe National Transportation System Center.
- Rodgers, M.D., Duke D.D. (1993). SATORI: Situation assessment through the re-creation of incidents. (Report No. DOT/FAA/AM-92/12). Washington, DC: Office of Aviation Medicine.²
- Stein, E.S. (1985). Air traffic controller workload: An examination of workload probe. (Report No. DOT/ FAA/CT-TN84/24). Atlantic City, NJ: Federal Aviation Administration Technical Center.
- Tabachnik, B. G., & Fidell, L. S. (1989). Using multivariate statistics (2nd ed.). New York: HarperCollins.
- van Gent, R., Hoekstra, J.M., & Ruigrok, R.C.J. (1997). Free flight with airborne separation assurance. In: Proceedings of the Confederation of European Aerospace Societies (CEAS) 10th European Aerospace Conference, 20-21, October 1997, Amsterdam, The Netherlands.

Pfleiderer, E.M. (2000). Multidimensional scaling analysis of controllers' perceptions of aircraft performance characteristics. (Report No. DOT/FAA/ AM-00/24). Washington, DC: Office of Aviation Medicine.²

²This publication and all Office of Aerospace Medicine technical reports are available in full-text from the Civil Aerospace Medical Institute's publications Web site: http://www.faa.gov/library/reports/ medical/oamtechreports/

APPENDIX A

Calculation of the Aircraft Mix Index

The first step in calculating the Aircraft Mix Index is assigning aircraft type codes, which have values ranging from one to four. Piston-driven aircraft are assigned a code value of 1, turboprops a value of 2, jet aircraft a value of 3, and high-performance jet aircraft a value of 4. The next step is creating a half matrix of aircraft type differences for all pairs of aircraft within a given sector. Table A1 lists aircraft type differences for the sample of aircraft in Figure A1. For instance, DAL589 is a commercial jet and has been assigned an aircraft mix code of 3. N149RJ is a turboprop with an aircraft mix code of 2. The aircraft mix difference between N149RJ and DAL589 is 1. The final step in the computation of the index involves summing all items in the half matrix. For example, the Aircraft Mix Index for the group of aircraft in Figure A1 is 17.00 (see Table A1). For each minute of data, the Aircraft Mix Index is calculated for all aircraft pairs at approximately 12-second intervals and stored in an array. At the end of each minute, the mean of these values is calculated and sent to an array. These stored values are used to calculate the average Aircraft Mix Index for whatever processing interval (e.g., 15-minutes, 30-minutes, etc.) has been selected.



Figure A1. Sample Sector With Aircraft Mix Codes

Table A1. Aircraft Mix Index

	DAL589	AAL123	N149RJ	UAL556	BLADE76
AAL123	0				
N149RJ	1	1			
UAL556	0	0	1		
BLADE76	1	1	2	1	
N456CP	2	2	1	1	3
Index = 17	4	4	4	2	3

APPENDIX B



Traffic Sample Descriptions and Sector Maps

5-0105
5-1845
0-1550
5-1535
0-1620
5-1625
3-1253
5-2305
5-1535
5-1855
5-1315
5-1925
e (local)
0-1310
5-1915
5-1625
5-2305
5-1325
5-1355

* Low/Intermediate SFC to FL230