# SPATIAL DISORIENTATION IN GENERAL AVIATION ACCIDENTS

William R. Kirkham, M.D., Ph.D. William E. Collins, Ph.D. Paula M. Grape James M. Simpson Terry F. Wallace Civil Aeromedical Institute Federal Aviation Administration Oklahoma City, Oklahoma



## **March 1978**

Document is available to the public through the National Technical Information Service, Springfield, Virginia 22161

Prepared for U.S. DEPARTMENT OF TRANSPORTATION Federal Aviation Administration Office of Aviation Medicine Washington, D.C. 20591

Technical Report Documentation Page

		and the second se		
1. Report No.	2. Government Acces	sion No. 3.	Recipient's Catalog	No.
FAA-AM-78-13				
4. Title and Subtitle		5.	Report Date	
Spatial Disorientation in (	operal Aviatio	6.	Performing Organiza	tion Code
spatial Disorientation in G	seneral Aviacio	a Accidents	Parforming Organizat	ion Report No
7. Author(s) William R. Kirkham	, William E. C	ollins,	errorming organizat	
9. Performing Organization Name and Addre	ess	10.	Work Unit No. (TRA	IIS)
FAA Civil Aeromedical Insti	tute	11.	Contract or Grant N	0.
Oklahoma City Oklahoma 73	125		-	
Oklanoma City, Oklanoma 75	125	13.	Type of Report and	Period Covered
Office of Aviation Medicine				
Federal Aviation Administra	tion			
Wachington D.C. 20501	w.	14.	Sponsoring Agency	Code
Washington, D.C. 20091				
This research was conducted 16. Abstract Spatial disorien attitude or motion of the p paper defines elements of S Accident reports made by th period were reviewed. Stat dents. SD was involved in and fatal. However, SD ran aircraft accidents and is c VFR flight into adverse wea fatal accidents. When SD w of the time that accident i 12,500 1b) accounted for 97	under Tasks Al tation (SD) rei ilot and his an D problems as a se National Tran istical computa 2.5 percent of ked as the thin losely related ther." SD was as ascribed as nvolved fatalit .3 percent of a	M-B-77-TOX-23 and fers to an incorre- incraft with respe- encountered in ger asportation Safety ations were made r all general aviat d highest "cause" to the second hig a cause or factor a cause or factor ties. Small fixed all SD accidents.	AM-B-78-TOX- ect self-appr ect to the ea eral civil a Board for a elating SD t ion accident in fatal sm hest "cause, in 16 perce in an accid -wing aircra	23. aisal of the rth. This viation. recent 6-year o fatal acci- s, nonfatal all fixed-wing " "continued nt of all
Inclement weather was assoc cause or factor in 35.6 per	iated with 42 p cent of these of	ercent of all fat ases. Flight was	al accidents initiated i	ft (under , and SD was a nto and
Inclement weather was assoc cause or factor in 35.6 per continued into adverse weat related fatal accidents. F prevalent adverse weather c 84.7 percent of SD weather- importance of this psychoph are made of ways to improve	iated with 42 p cent of these of her in 19.7 and og (56.8 percer onditions. Nor involved accide ysiological phe pilots' awaren	percent of all fat cases. Flight was a 68.7 percent, re- at) and rain (41.8 m-instrument-rated ents. These and o enomenon (SD) in f mess and understan	al accidents initiated i spectively, percent) we pilots were ther data at light safety ding of this	<pre>ent, 90 percent ft (under , and SD was a nto and of SD weather- re the most involved in test to the . Suggestions problem.</pre>
Inclement weather was assoc cause or factor in 35.6 per continued into adverse weat related fatal accidents. F prevalent adverse weather c 84.7 percent of SD weather- importance of this psychoph are made of ways to improve 17. Key Words	iated with 42 p cent of these of her in 19.7 and og (56.8 percer onditions. Nor involved accide ysiological phe pilots' awarer	bercent of all fat cases. Flight was 1 68.7 percent, re- nt) and rain (41.8 n-instrument-rated ents. These and o enomenon (SD) in f ness and understan 18. Distribution Statement	al accidents initiated i spectively, percent) we pilots were ther data at light safety ding of this	ft (under , and SD was a nto and of SD weather- re the most involved in test to the . Suggestions problem.
Inclement weather was assoc cause or factor in 35.6 per continued into adverse weat related fatal accidents. F prevalent adverse weather c 84.7 percent of SD weather- importance of this psychoph are made of ways to improve 17. Key Words Spatial disorientation Fatal accidents Weather accidents	iated with 42 p cent of these of her in 19.7 and og (56.8 percer onditions. Nor involved accide ysiological phe pilots' awarer	bercent of all fat cases. Flight was 1 68.7 percent, re- nt) and rain (41.8 n-instrument-rated ents. These and o enomenon (SD) in f ness and understan 18. Distribution Statement Document is avai through the Nati Service, Springf	al accidents initiated i spectively, percent) we pilots were ther data at light safety ding of this lable to the onal Technic ield, Virgin	<pre>ent, 90 percent ft (under , and SD was a nto and of SD weather- re the most involved in test to the . Suggestions problem. U.S. public al Information ia 22161.</pre>
Inclement weather was assoc cause or factor in 35.6 per continued into adverse weat related fatal accidents. F prevalent adverse weather c 84.7 percent of SD weather- importance of this psychoph are made of ways to improve 17. Key Words Spatial disorientation Fatal accidents Weather accidents 19. Security Classif. (of this report)	iated with 42 p cent of these of her in 19.7 and og (56.8 percer onditions. Nor involved accide ysiological phe pilots' awarer	percent of all fat cases. Flight was 1 68.7 percent, re- nt) and rain (41.8 n-instrument-rated ents. These and o enomenon (SD) in f mess and understan 18. Distribution Statement Document is avait through the Nati Service, Springf if. (of this pege)	al accidents initiated i spectively, percent) we pilots were ther data at light safety ding of this lable to the onal Technic ield, Virgin	<pre>ent, 90 percent ft (under , and SD was a nto and of SD weather- re the most involved in test to the . Suggestions problem. U.S. public al Information ia 22161. 22. Price</pre>
Inclement weather was assoc cause or factor in 35.6 per continued into adverse weat related fatal accidents. F prevalent adverse weather c 84.7 percent of SD weather- importance of this psychoph are made of ways to improve 17. Key Words Spatial disorientation Fatal accidents Weather accidents 19. Security Classif. (of this report)	iated with 42 p cent of these of her in 19.7 and og (56.8 percer onditions. Nor involved accide ysiological phe pilots' awarer	percent of all fat cases. Flight was 1 68.7 percent, re- nt) and rain (41.8 n-instrument-rated ents. These and o enomenon (SD) in f ness and understan 18. Distribution Statement Document is avait through the Nati Service, Springf	al accidents initiated i spectively, percent) we pilots were ther data at light safety ding of this lable to the onal Technic ield, Virgin	ent, 90 percent ft (under , and SD was a nto and of SD weather- re the most involved in test to the . Suggestions problem. U.S. public al Information ia 22161.

Reproduction of completed page authorized

#### SPATIAL DISORIENTATION IN GENERAL AVIATION ACCIDENTS

#### I. Introduction.

In aviation, spatial disorientation refers to an incorrect selfappraisal of the attitude or motion of the pilot and his plane with respect to the earth (7). On some occasions, disorientation in the air consists of true vertigo (sensations that the world or the pilot is spinning) and/or dizziness (sensations of unsteadiness with a feeling of movement within the head). Indeed, the three terms "disorientation," "vertigo," and "dizziness" are usually (if inaccurately) used interchangeably to describe a variety of symptoms, such as false sensations (i) of turning, (ii) of linear velocity, or (iii) of tilt. When mentioned by pilots, "vertigo" almost always means their awareness of any of the various forms of disorientation. Thus, "pilot vertigo" and the more technical term "spatial disorientation" are virtually identical in the language of pilots (9). In fact, the Flight Instructor's Handbook issued by the Federal Aviation Administration (FAA) from 1969-1977 defined vertigo as "a disorientation in space" (10).

Most of the "disorientation" difficulties encountered by pilots in aircraft are due to inadequate and unreliable sensory information (3,4,6,7, 12,14,15,18,20). In this regard, the visual (seeing) and the vestibular (position and motion detecting) systems are of critical importance. As terrestrial beings, we use our vision in almost all situations to maintain stability and orientation with our surroundings. However, when we leave our firm base on the ground for the platform of an aircraft that can roll, pitch, and yaw simultaneously and at various rates, we may exceed the capability of our senses to keep us properly oriented in space. In "good weather" flight a pilot relies heavily on external visual cues provided by the horizon or terrain to maintain orientation. If these external cues are lost, as at night or in adverse weather, the pilot is left with secondary orientation modalities (vestibular organs, proprioceptor systems) which can fail to perceive changes in attitude and motion or can give false cues of attitude and motion. If proper orientation is not quickly regained, the pilot may inadvertently maneuver the aircraft violently, thereby overstressing it, or lose control of the aircraft and impact with the ground. The rationale for visual flight rules, therefore, is to keep inexperienced (non-instrumentrated) pilots out of weather conditions that are highly conducive to the production of spatial disorientation. In fact, the early impetus for developing aircraft flight instrumentation (as compared with engine instrumentation) was to provide instruments that would indicate the true attitude of the aircraft and thus allow the pilot to perceive accurately his orientation in conditions under which vision was obscured and in spite of his own erroneous vestibular sensations of orientation.

How serious is the problem of spatial disorientation in aviation? The greatest attention has been given to this problem in connection with military

aviation where high-performance aircraft are involved. The role of spatial disorientation in United States Air Force (USAF) accidents has been analyzed in a number of studies covering the years 1954-56 (19), 1964-67 (16), 1958-68 (2), 1969-71 (1), and 1968-72 (13). Spatial disorientation was a significant factor in 4-6 percent of all accidents (1,13), in 4-9 percent of major accidents (2,16,19), and in 10-26 percent of fatal accidents (1,2,16,19). Barnum and Bonner (2) describe the average USAF pilot involved in a spatial disorientation accident as a 30-year-old fighter pilot with 10 years of flight experience, 1,500 hours of first pilot/instructor pilot time, and with 25 flights in the 3-month period prior to the accident.

If approximately 15 percent of fatal accidents in military aircraft flown by highly trained and instrument-rated pilots have spatial disorientation as a cause, what role has spatial disorientation in general aviation accidents? There are obvious differences between military and general aviation flying. Military aircraft are, for the most part, high-performance aircraft that subject pilots to greater levels of angular and linear accelerations in the air. Military pilots have considerable experience with instruments and can fly their aircraft well in conditions in which vision is obscured. They also receive a considerable amount of physiological training and attend regular refresher courses. On the other hand, general aviation aircraft are slower and their pilots are not subjected to the highacceleration maneuvers of military planes. In addition, many general aviation pilots are not qualified for instrument flying. Furthermore, general aviation pilots, in contrast to military pilots, are not, by and large, familiar with the unreliability of the human vestibular organs in flight and lack indoctrination or awareness of the potential for spatial disorientation. For the most part, civilian pilots do not appreciate that one of the greatest dangers of weather conditions to the safety of flight is not in the chance of getting lost or of encountering severe turbulence but in the obscuration of vision leading to spatial disorientation and subsequent loss of control of the aircraft.

This report was undertaken to document the incidence of spatial disorientation in civil aviation accidents and to define the conditions in which spatial disorientation has occurred as revealed by accident statistics. It is hoped that such data may be a useful part of the total information employed to educate general aviation pilots concerning this hazard to flight safety.

### II. Materials and Methods.

The National Transportation Safety Board (NTSB) investigates all fatal aviation accidents primarily to determine their cause. Usually, nonfatal general aviation accidents in aircraft of less than 12,500 lb are investigated by the FAA (under an agreement with the NTSB) and its reports are then made to the NTSB. The NTSB determines, codes, and enters into computer files a variety of data relating to pertinent causes, factors, and conditions that prevailed in each accident. Brief reports and tabular summaries of these causes, factors, and conditions in accidents are compiled in various formats. Data taken from NTSB reports were compiled into the tables used in this report. In addition, several computer retrievals were made on special request to the NTSB for data that had not yet become available in printed form or that otherwise had not been isolated from the bulk of the accident data. Some of the data in this report were compiled and tabulated by individually reviewing all briefs of accidents for the periods reported. In some instances only current and the most readily available data were used. The tables in this report reflect only accidents from three categories of aircraft: large fixed-wing, small fixed-wing, and rotorcraft. Such accidents represent 97.6 percent of general aviation accidents in the period from 1968 through 1975, and the data used were considered representative of general aviation accidents. In most instances in which spatial disorientation was determined to have occurred in the accident, it was listed by the NTSB as a cause. In some accidents it was listed only as a factor. In this report "cause" and "factor" are combined and shown as "cause/factor," except in a few instances.

#### III. Results.

A. <u>Overall Incidence of Spatial Disorientation in General Aviation</u> <u>Accidents</u>. The number of general aviation accidents, the number of accidents in which spatial disorientation was recorded as a cause/factor, and the incidence as a percentage of total accidents for the period 1968-75 are presented in Table 1. These figures do not include the relatively few air carrier accidents. The yearly incidence ranged from 1.8 to 3.0 percent with a mean of 2.5 percent. Unfortunately, these data obscure the significance of spatial disorientation in flight safety. It is in <u>fatal</u> accidents that spatial disorientation assumes a clearly important cause/factor role.

	2	Spat	ial Disorientatio	n		
Year	Total Accidents	Cause	Factor	Total Cause/Factor	Percentag Cause/Facto of All Accide	ents
1968	4,812	89	0	89	1.8	
1969	4.647	102	0	102	2.2	
1970	4,592	109	1	110	2.4	
1971	4,520	127	1	128	2.8	
1972	4,127	114	1	115	2.7	
1973	4,119	123	0	123	3.0	
1974	4,294	110	2	112	2.6	
1975	4,071	109	0	109	2.7	
Tota	18 35,182	883	5	888	2.5	

TABLE 1. Spatial Disorientation as a Cause/Factor in General Aviation Accidents\*

\*Accidents in large fixed-wing aircraft, small fixed-wing aircraft, and rotorcraft in which cause/factors were assigned. B. Spatial Disorientation in Fatal Accidents. Table 2 shows the yearly incidence of all fatal and nonfatal accidents for which spatial disorientation was assigned as a cause or factor during 1970 through 1975. On the average, <u>90 percent of the time</u>, when spatial disorientation is ascribed to an accident, that accident involved fatalities. In addition, there appears to be a trend toward fewer nonfatal disorientation accidents.

TABLE 2.	Severity of A	ccidents in	Which Spat	ial Disorient	tation	
	Was a Cause/	Factor-U.S	3. General A	viation		
	With Spati	al Disorier	itation	Percentage o	of Total	
Year	Total Accidents	Nonfatal Accidents	Fatal Accidents	Nonfatal Accidents	Fatal Accidents	

Year	Accidents	Accidents	Accidents	Accidents	Accidents
1970	110	16	94	14.5	85.5
1971	128	19	109	14.8	85.2
1972	115	10	105	8.7	91.3
1973	123	_ 11	112	8.9	91.1
1974	112	1045 1	108	3.6 999	96.4
1975	109	10	99	9.2	90.8
Total	697	70	627 Mea	an 10.0	90.0

Table 3 provides a different perspective. In this table, the annual frequency with which spatial disorientation was identified as a cause/ factor in fatal accidents is presented for the years 1970 through 1975. The data indicate that spatial disorientation was involved in 16 percent of all fatal accidents.

TABLE 3. Frequency of Fatal General Aviation Accidents in Which

Spatial Disorientation Was a Cause/Factor

		Spatial Disorientation	as a Cause/Factor
Year	All Fatal* Accidents	Number of Fatal Accidents	Percentage of All Fatal Accidents
1970	632	94	14.9
1971	638	109	17.1
1972	674	105	15.6
1973	700	112	16.0
1974	712	108	15.2
1975	656	99	15.1
Totals	4,012	627	15.6

\*In large fixed-wing aircraft, small fixed-wing aircraft, and rotorcraft only.

C. <u>Spatial Disorientation Accidents by Aircraft Type</u>. Table 4 gives the distribution of accidents, fatal accidents, and spatial disorientation accidents by the three major aircraft types in general aviation for 6 years, 1970 through 1975. In this period there were 697 spatial disorientation accidents, 678 in small fixed-wing aircraft, 18 in rotorcraft, and only 1 in large fixed-wing aircraft. No instances of spatial disorientation were recorded in other categories of aircraft. The following data can be derived: 90.1 percent of all accidents in all types of aircraft including gliders, balloons, etc., 91.1 percent of all fatal accidents, and <u>97.3 percent of all</u> spatial disorientation accidents occurred in small fixed-wing aircraft.

> TABLE 4. Spatial Disorientation as a Cause/Factor in U.S. General Aviation Accidents by Aircraft Types

	Large 1	ixed-Wing A	ircraft	Small	Fixed-Wing.	Aircraft	-	Rotorcraft	
Year	Accidents	Fatal Accidents	Spatial Disorient. Accidents	Accidente	Fatal Accidente	Spatial Disorient. Accidents	Accidents	Fetal Accidents	Spatial Disoriant. Accidents
1970	40	14	1	4,290	587	105	262	22	4
1971	38	7	0	4,243	605	123	239	26	5
1972	28	6	0	3,858	632	114	241	36	1
1973	42	13	0	3,802	660	119	275	27	4
1974	34	18	0	3,975	647	109	285	47	3
1975	31	9	<u>o</u>	3,738	624	108	302	_23	_1
Totals	213	67	1 '	23,906	3,755	678	1,604	181	18

D. <u>Spatial Disorientation and the Pilot</u>. During the years 1970 through 1975, 87.5 percent of fatal accidents involving small fixed-wing aircraft were categorized by the NTSB as due to (cited as "cause") an action or condition of the pilot in command (as opposed to a condition of the aircraft power plant, the airframe, instruments, weather, etc.). In this regard, the role of spatial disorientation takes on additional significance. For all fatal accidents in small fixed-wing aircraft from 1970 through 1975 the actions or conditions of the pilot that were most frequently cited as a cause can be described as follows:

- (i) failed to obtain/maintain flying speed (26.3 percent).
- (ii) continued VFR flight into adverse weather (22.2 percent).
- (iii) spatial disorientation (16.4 percent).

No other action or condition from the lengthy list reported by the NTSB reached 8 percent. (The list includes conditions such as misjudgment of altitude, failure to follow procedures, etc.) Thus, <u>spatial disorientation</u> ranks as the third highest cause in fatal, <u>small</u>, <u>fixed-wing aircraft</u> accidents.

Given the significance of spatial disorientation in fatal accidents attributed to a condition of the pilot, are there any salient features of this cause/factor which might be related to pilot age or experience? Table 5 gives the age distribution of pilots involved in fatal weather-related spatial disorientation accidents; the greatest incidence is in the fifth decade (ages 40-49). In total hours of flying experience, 60.8 percent of the pilots had 500 or less and 39.2 percent had more than 500 hours. In those with less than 500 hours, the greatest incidence, 18.6 percent, involved pilots with 100-200 hours; an almost identical proportion, 19.2 percent, involved pilots with 1,000-5,000 hours of flying experience. In terms of certification, 70.3 percent had private pilot certificates, 10.1 percent had student certificates, 16.3 percent had commercial pilot certificates, and 2.2 percent of the pilots were listed as having no license.

The greatest accident rate, 29.8 percent, occurred in pilots with 50 or less hours in aircraft type. The incidence declined with experience in type of aircraft.

TABLE 5. Age and Experience of Pilots in Fatal Weather-Related Accidents With Spatial Disorientation as a Cause/Factor

	1970	1971	1972	1973	1974	1975	Total	Percent
Age of pilot								
< 20	2	1	1	4	2	3	13	2.3
20-29	8	9	17	13	20	11	78	14.1
30-39	28	33	23	34	26	23	167	30.2
40-49	25	28	30	23	38	35	179	32.4
50-59	13	15	17	20	12	17	94	17.0
60-69	2	4	. 5	5	0	4	20	3.6
70-79	0	1	0	0	0	0	1	0.2
80-89	0	0	0	0	1	0	1	0.2
Total flight hours								
< 100	14	20	18	11	13	11	87	15.7
100-199	20	15	16	19	14	19	103	18.6
200-299	11	13	6	9	16	10	65	11.8
300-399	4	7	5	9	8	5	38	6.9
400-499	0	2	9	7	5	2	25	4.5
500-999	14	9	8	16	12	22	81	14.6
1,000-4,999	8	17	20	23	24	14	106	19.2
5,000-9,999	4	1	2	1	1	2	11	2.0
- or > 10,000	0	0	1	3	1	2	7	1.3
Unknown	3	7	8	1	5	6	30	5.4
Type of license	10.11	1.11						
Student	8	18	8	9	7	6	56	10.1
Private	58	59	68	68	73	63	389	70.3
Commercial	10	11	12	19	16	22	90	16.3
Transport	1	0	2	2	0	0	5	0.9
Unknown	0	0	1	0	0	0	1	0.2
None	1	3	2	1	3	2	12	2.2
Hours in type airci	raft							
< or = 50	27	26	35	26	25	26	165	29.8
51-200	23	24	18	23	33	21	142	25.7
201-500	6	11	- 9	18	5	13	62	11.2
501-999	5	0	- 1	4	1	6	17	3.1
= or > 1,000	4	1	4	3	2	0	14	2.5
the second se						-		

di nd la disciplita i une

E. Weather and Spatial Disorientation Accidents. A significant percentage of fatal general aviation accidents occur in inclement weather (17). Although weather itself is rarely listed as the sole, direct cause of an accident, it is often cited as a contributing factor. Thus, during the 6-year period from 1970 through 1975, weather was the sole cause in only 3.8 percent of fatal accidents in small fixed-wing aircraft as compared to its role as a contributing factor in 38.4 percent of fatal accidents. Inclement weather, then, was associated with over 42 percent of the fatal accidents during that 6-year period. Because inclement weather plays a major role, as noted earlier, in causing spatial disorientation, the incidence of disorientation in weatherand non-weather-related general aviation accidents was tabulated for the years 1970 through 1975. During that 6-year period, spatial disorientation was a cause/factor (i) in 10.3 percent of all weather-related accidents (fatal and nonfatal in all aircraft types) and (ii) most significantly, in 35.6 percent of all weather-involved fatal accidents in small fixed-wing aircraft.

Inclement weather and spatial disorientation thus interact in a significant fashion to produce fatal accidents. To examine this interaction more clearly, various features of fatal accidents that occurred during the most recent 6-year period for which data are available and in which spatial disorientation and weather were a cause/factor are summarized in Table 6. Flight was initiated into adverse weather in 19.7 percent of these accidents; flight was continued into adverse weather in 68.7 percent. By far the greatest number of accidents, 78.5 percent, occurred during inflight descent, but inflight breakup occurred in 12.8 percent. The most prevalent weather condition involved fog (56.8 percent) with rain the next in prevalency (41.8 percent); turbulence (12.7 percent) and thunderstorms (13.9 percent) were also prominent. At the time of accidents, VFR weather conditions existed 29.2 percent and IFR conditions 67.8 percent of the time (4 percent unknown or not given); 67.5 percent of the accidents occurred during daylight hours, 25.7 percent at night (6.9 percent unknown or not given). No flight plan was filed in 64.7 percent of the fatal flights; IFR flight plans were filed in 12.9 percent; only 15.7 percent of the pilots were instrument rated.

	-	Tear	and nu	mber, c	f fats	1 acci	dents	
	1970	1971	1972	1973	1974	1975	Total	SV
Cheracteristics Cited	_78	91	93	.99	99	93		Fercentage
Flight into adverse								
weather:								
Initiated	18	10	15	28	25	13	109	19.7
Continued	53	60	65	71	61	70	380	68.7
Unknown/not listed	7	21	13	0	13	10	64	11.6
Heather conditions:*								
Snow	13	10	18	11	19	13	84	15.2
Rain	23	40	44	37	44	43	231	41.8
Fog	43	50	52	64	49	56	314	56.8
Thunderstorm	7	7	19	12	20	12	77	13.9
Turbulence	10	13	15	11	12	9	70	12.7
Ceiling < or = 500	29	31	32	46	30	24	192	34.7
Ceiling > 500	29	43	47	42	42	39	252	47.9
Ceiling unknown/not given	20	17	14	11	27	30	119	21.5
Weather type:								
VFR	33	36	26	23	27	- 11	156	28.2
IFR	38	51	63	75	69	79	375	67.8
Unknown/not given	7	4	4	1	3	3	22	4.0
Type of flight plan:								
lines	53	65	57	62	65	56	358	66.7
VPR	16	16	26	19	22	23	122	22.1
LFR	7	8	10	18	12	14	69	12.5
Unknown/not given	2	2	0	0	0	0	4	0.7
instrument-rated pilots	9	11	14	19	14	20	87	15.7
ime of accident:								
6 8. m. to 8 p.m.	49	64	66	75	64	55	373	67.5
8 p.m. to 6 4.m.	24	20	18	16	32	32	142	25.7
Unknown/not given	5	7	9	8	3	6	38	6.9
hase of flight:*								
Takeoff climb	1	0	2	8	10	6	27	4.9
Inflight	7	0	5	3	3	4	22	4.0
Inflight descent	66	81	81	76	67	63	434	78.5
Landing	5	10	4	7	4	6	56	6.5
Other	3	- 1	7	13	15	14	53	9.6
was of accident :*								
Collision w/ground or								
Water	67	89	83	73	72	78	667	84.4
Colligion w/structures	1	4	4	4	2	3	18	3.2
Inflight breakup	10	5	10	19	16	33	71	12.8
Onben Di onton	0	0	1	2	4			1.4

7

In this same 6-year period there were 71 accidents involving inflight breakup of aircraft structure in which both weather and spatial disorientation were listed as a cause/factor (Table 6); although thunderstorms and/or turbulence were listed as a cause/factor in 31 percent of these accidents, more than twice as many (69 percent) did not involve thunderstorms or turbulence as a cause/factor. These latter figures suggest that spatial disorientation may lead to loss of control of the aircraft in relatively nonturbulent air while flying through clouds, causing the pilot to overstress the airplane in attempting to correct attitude and direction.

### IV. Discussion.

Because spatial disorientation is a cause/factor in only 2.5 percent of all types of general aviation accidents combined, its significance may be underestimated by the aviation community. It is in the category of <u>fatal</u> accidents that the significance of this psychophysiological phenomenon is clearly highlighted. As we have seen, spatial disorientation is the third leading cause in all fatal accidents (16 percent) and is also closely associated with the second leading cause (continuing VFR flight into adverse weather); it is a cause or factor in 35.6 percent of all weather-involved fatal accidents. Moreover, when spatial disorientation is associated with an accident, it is a fatal accident 90 percent of the time.

Is the incidence of spatial disorientation truly this high in aircraft accidents, or is spatial disorientation just a convenient "wastebasket" cause used to explain "unexplainable" events in weather accidents? In 10 percent of spatial disorientation accidents that prove nonfatal, the pilot is frequently able to describe the problem in orientation. Also, in some fatal accidents there have been radio communications prior to impact that indicated the pilot was disoriented. In the majority of accidents, however, spatial disorientation can be surmised after thoughtful and objective evaluation of the evidence at hand; thus potential criticism of the citation of the accident cause as a subjective or judgmental matter can usually be dispelled. However, the difficulty of determining without question if spatial disorientation was a cause in an accident is possibly the reason little mention is made of the subject in discussing civil aviation accident statistics. On the other hand, spatial disorientation may be underestimated as a cause/factor on similar grounds. Because the judgment of spatial disorientation is somewhat subjective or is sometimes based on circumstantial evidence, investigators may tend to avoid listing it as the cause of an accident. In any case, the accident data and the testimonies of numerous pilots who have had nonfatal brushes with spatial disorientation signify unequivocally that this phenomenon continues to be a serious problem in aviation.

Although the problem of spatial disorientation is as old as aviation itself, its significance in flight safety is clearly underplayed. For example, in flight training and throughout general aviation a great deal of attention is given to weather and the movement of weather fronts. But little or no mention is made about the connection between weather and spatial disorientation. In the "Pilot's Handbook of Aeronautical Knowledge" (11) the student pilot can obtain a wealth of information on weather. text also notes: "Despite the development of many ingenious devices, improvement in aircraft design, power plants, radio aids and navigational techniques, safety in flight is still subject to conditions of limited visibility, turbulence and icing." Although a half-page discussion of "vertigo" appears elsewhere in the Handbook (11) under medical facts for pilots, in the entire section on weather (almost 50 pages) the relationship of restricted visibility to spatial disorientation is not mentioned. As another example, an NTSB study of fatal weather-involved general aviation accidents (17) does not discuss spatial disorientation as such; yet, the tabular information in the report shows spatial disorientation as a frequent cause of weather-involved accidents, second only to continued VFR flight into adverse weather. While there is no discussion in the NTSB study of the significance of spatial disorientation in accident causation, the report does quote from a 1969 NTSB weather briefing guide, as follows: "Too many of the fatal, weather-involved, general aviation accidents are caused, in part at least, by the pilot's mistaken idea of his ability to cope with certain weather situations." Similarly, the FAA's recently issued "Aviation Instructor's Handbook" (9) discusses the desirability of "integrated flight instruction" from the first time each maneuver is introduced. When this training technique is used, instruction in the control of an airplane by outside visual references is "integrated" with instruction in the use of flight instrument indications for the same maneuver. This handbook states that such instruction "provides the student with the ability to control an airplane in flight for limited periods if outside references are lost. This ability could save the pilot's life or those of the passengers in an actual emergency." While the authors strongly support this teaching approach, the real hazard of loss of visual references, i.e., spatial disorientation, is not specifically identified and such identification, in our view, is important if both pilots and flight instructors are to more successfully deal with this flight hazard.

The lack of emphasis on spatial disorientation as a significant factor in general aviation safety is not limited to textbooks and reports. In a recent survey of disorientation training in FAA-certified flight and ground schools, Collins, Hasbrook, Lennon, and Gay (8) reported that more than one-third of over 600 respondent schools evaluated their disorientation training program as inadequate and defined the inadequacy most often as a lack of appropriate instructional materials, aids, and information. The report (8) also suggested methods that could be used to provide flight training students and private pilots with a greater awareness of the dangers of spatial disorientation. In this regard, it was suggested that during early training greater emphasis should be placed on (i) the seriousness of spatial disorientation problem in fatal aviation accidents, (ii) causes of disorientation, (iii) disorientation-induced dangers associated with flying in poor visibility and/or IFR conditions, (iv) the need to acknowledge to oneself when an orientation problem exists, and (v) ways to overcome disorientation in flight. Combinations of appropriate lectures, films, and demonstrations were suggested to accomplish this objective with emphasis both on the dangers of disorientation and on how to deal with it in flight. The latter, the authors noted, involves proficient use of appropriate flight instruments.

The need for the ability to control an aircraft solely by response to its instruments cannot be understated. The data indicate that 85 percent of all fatal accidents involving spatial disorientation also involve noninstrument-rated pilots. On the other hand, the fact that 15 percent of these accidents (about the same percentage as that for military pilots) involved instrument-rated pilots attests to the importance of proficiency and recency in the use of the flight instruments and to the need for good judgment about flying conditions irrespective of ratings or skill.

All pilots must be made aware of the significance of spatial disorientation in fatal accidents. We agree with the previously expressed approach (8), based on data from flight and ground schools, to accomplish this goal. That approach includes:

- (i) improved flight school lectures relative to spatial disorientation.
- (ii) ground-based demonstrations of disorientation with appropriate briefings (7).
- (iii) inflight demonstrations on two or more occasions during student pilot training. Appropriate briefings and lecture material must accompany these experiences.
- (iv) specifically encouraging pilots always to obtain preflight weather briefings.
- (v) specifically encouraging pilots not to take off or fly in poor visibility or at night unless they are highly proficient in the use of flight instruments.
- (vi) requiring flight test examiners to assure themselves that pilot applicants have a basic understanding of spatial disorientation and giving applicants an opportunity to demonstrate their ability to cope with such conditions during the flight test.

We would add to these three additional recommendations. First, student pilot manuals and training handbooks should be revised to include information on the contribution of spatial disorientation to fatal accidents. Second, emphasis on spatial disorientation should be made in chapters and sections dealing with weather problems in flight. Third, written tests for all pilot applicants should include questions which require responses based on an awareness and understanding of the fatal hazards associated with spatial disorientation and the importance of avoiding weather conditions that may produce it. Pilots should have a built-in association between adverse weather, disorientation, and fatal accidents.

A former FAA administrator has stated: "The skies are more crowded today, but the real hazards to safe flight are precisely what Wilbur Wright warned against--carelessness and overconfidence on the part of some pilots, such as inadequate preflighting, risky weather decisions, and lack of visual alertness for other aircraft" (5). Relative to "risky weather decisions," it should be the understanding of all pilots that unless they are thoroughly trained and experienced in instrument flying techniques, they are basically incapable of safely coping with weather situations that obscure vision. The accident statistics attest to this. Unless understanding is brought to the consciousness of every pilot, no substantial reduction in fatal weather accidents is likely to be achieved in the foreseeable future.

# References

- Barnum, F.: Spatial Disorientation Aircraft Accidents, 1 Jan 1969-31 Dec 1971. Presented at the 44th Annual Scientific Meeting of the Aerospace Medical Association, Las Vegas, Nevada, May 1973.
- Barnum, F., and R. Bonner: Epidemiology of USAF Spatial Disorientation Aircraft Accidents, 1 Jan 1958-31 Dec 1968. AEROSPACE MEDICINE 42:896, 1971.
- Benson, A. J.: Spatial Disorientation in Flight. In J. A. Gilles (Ed.), A Textbook of Aviation Physiology, Pergamon, New York, 1965.
- Bonner, R. H.: Spatial Disorientation--Current Concepts and Aeromedical Implications. USAFSAM AEROMEDICAL REVIEW, No. 7-63, Brooks AFB, Texas, 1963.
- Butterfield, Alexander: A Lesson From History. FAA WORLD, <u>3</u> (Dec):2, 1973.
- Clark, B., and M. A. Nicholson: Aviator's Vertigo: A Cause of Pilot Error in Naval Aviation Students. JOURNAL OF AVIATION MEDICINE, 25: 171, 1954.
- Collins, W. E.: Effective Approaches to Disorientation Familiarization for Aviation Personnel. FAA Office of Aviation Medicine Report No. AM-70-17, 1970.
- Collins, W. E., A. H. Hasbrook, A. O. Lennon, and D. J. Gay: Disorientation Training in FAA-Certified Flight and Ground Schools: A Survey. FAA Office of Aviation Medicine Report No. AM-77-24, 1977.
- 9. Federal Aviation Administration: Aviation Instructor's Handbook. FAA Advisory Circular AC-60-14, 1977.
- Federal Aviation Administration: Flight Instructor's Handbook. FAA Advisory Circular AC-61-16A, 1969.
- 11. Federal Aviation Administration: Pilot's Handbook of Aeronautical Knowledge. FAA Advisory Circular AC-61-23A, 1971.
- Gillingham, K. K.: A Primer of Vestibular Function, Spatial Disorientation, and Motion Sickness. USAFSAM AERONAUTICAL REVIEWS, No. 4-66, Brooks AFB, Texas, 1966.

12

- Kellogg, R.: Appendix A: USAF Spatial Disorientation Accidents During the Period 1968-1972. In Staff Study Report on Spatial Orientation Training. Aerospace Medical Division, Brooks AFB, Texas, December 1974.
- Melvill Jones, G.: Disorientation in Flight. In Th. von Karman (Ed. Chmn.), <u>Advances in Aeronautical Sciences</u>, Pergamon, New York, 1959.
- 15. Melvill Jones, G.: Vestibulo-ocular Disorganization in the Aerodynamic Spin. AEROSPACE MEDICINE, 36:976, 1965.
- 16. Moser, R.: Spatial Disorientation as a Factor in Accidents in an Operational Command. AEROSPACE MEDICINE, 40:174, 1969.
- National Transportation Safety Board: Special Study of Fatal Weather-Involved General Aviation Accidents. NTSB Report No. AAS-74-2, 1974.
- Neely, S. E.: Patterns of Interference With the Ability of Pilots to Control Their Aircraft. In A. B. Barbour and H. E. Wittingham (Eds.), <u>Human Problems of Supersonic and Hypersonic</u> Flight, Pergamon, New York, 1962.
- Nuttall, J. B., and W. G. Sanford: Spatial Disorientation in Operational Flying. Publication M-27-56, U.S. Air Force Directorate of Flight Safety Research, September 1956.
- 20. Vinacke, W. E.: Illusions Experienced by Aircraft Pilots While Flying. JOURNAL OF AVIATION MEDICINE, 18:308, 1947.

TU.S. GOVERNMENT PRINTING OFFICE: 1994 - 560-063/00047