

1. Report No. FAA-AM-78-17	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle COMPARATIVE READABILITY OF ENROUTE LOW ALTITUDE CHARTS WITH AND WITHOUT TERRAIN DEPICTION		5. Report Date April 1978	
		6. Performing Organization Code	
		8. Performing Organization Report No.	
7. Author(s) Paul G. Rasmussen, Kenneth W. Welsh, and John A. Vaughan		10. Work Unit No. (TRAIS)	
9. Performing Organization Name and Address FAA Civil Aeromedical Institute P. O. Box 25082 Oklahoma City, Oklahoma 73125		11. Contract or Grant No.	
		13. Type of Report and Period Covered	
12. Sponsoring Agency Name and Address Office of Aviation Medicine Federal Aviation Administration 800 Independence Avenue, S.W. Washington, D.C. 20591		14. Sponsoring Agency Code	
15. Supplementary Notes  Work was performed under Task AM-A-78-PHY-95.			
16. Abstract  The U.S. National Ocean Survey has issued an experimental copy of Enroute Low Altitude Chart L-3/4 dated April 21, 1977, as part of a program to explore the feasibility of introducing terrain depiction on the charts. The FAA's Air Traffic Service (AAT-1) requested the Office of Aviation Medicine to determine what derogatory effects such a change might have on the usability of the charts.  It was found in the study that shaded terrain depiction reduces readability of alphanumeric data as measured by increases in reading errors and reading time. Losses are attributed to the low figure-to-ground contrast ratios between the chart legends and the terrain background. Losses are most pronounced for alphanumeric data printed in small character sizes and with light inking densities. Losses are also evident for some large character sizes and heavy inking densities where mountainous terrain is depicted by heavy inking densities. Losses are particularly evident under low luminance levels but also occur to a lesser extent at elevated luminance levels. Differences between the experimental and standard versions of the charts are least pronounced when the terrain depiction introduced only a moderate reduction in figure-to-ground contrast level and the items were viewed at elevated luminance levels.			
17. Key Words  Chart Readability Contrast Effects Terrain Depiction		18. Distribution Statement  Document is available to the public through the National Technical Information Service, Springfield, Virginia 22161.	
19. Security Classif. (of this report)  Unclassified	20. Security Classif. (of this page)  Unclassified	21. No. of Pages  13	22. Price



# COMPARATIVE READABILITY OF ENROUTE LOW ALTITUDE CHARTS WITH AND WITHOUT TERRAIN DEPICTION

## I. Introduction.

The U.S. National Ocean Survey has issued an experimental copy of Enroute Low Altitude Chart L-3/4 dated April 21, 1977, that depicts terrain features in shaded relief and, additionally, provides Maximum Elevation Figures (MEF). In addition to soliciting user comments, the FAA Air Traffic Service (AAT-1) requested the Office of Aviation Medicine to conduct a study to determine how introduction of terrain depiction might affect usability of the charts.

The most obvious effect of shaded relief terrain depiction might be to impair readability of alphanumeric data on the charts. Where mountainous terrain is depicted as background to such data, the contrast ratio is considerably reduced from ratios found on standard charts.

A limited study of the comparative readability of selected categories of data appearing on the charts was conducted by the Vision Research Unit of the FAA Civil Aeromedical Institute's Aviation Physiology Laboratory (AAC-115). The study was restricted to consideration of simple readability as a discrimination task and did not address such factors as search time for specific information or the ability to use the charts in flight.

## II. Methods.

Five categories of information appearing on the experimental terrain depiction versions of Enroute Low Altitude Charts L-3 and L-4 were selected as being representative of the alphanumeric content of the charts. The five categories are as follows: (i) UHF/VHF Airway and Route Data, (ii) Aerodromes Without Published Instrument Approach Procedures, (iii) Air/Ground Communication Boxes, (iv) ARTCC Remoted Site Boxes, and (v) Maximum Elevation Figures.

Six samples of each of the first four categories were selected from the experimental charts. Three samples in each category were chosen as representative of a dense terrain background (low terrain contrast) and three as representative of an intermediate terrain background (moderate terrain contrast). In addition, 12 MEF figures

were selected from the terrain depiction chart to provide four samples at each of three relative contrast ratios (high, medium, and low). No attempt was made to quantify the contrast ratios or equate them within categories on other than a subjective basis. A listing of the test items (samples) is given in Table 1.

The selected test items were cut from the experimental versions of the charts in rectangular sections. Corresponding samples, except for MEF numerals, were cut from standard issues of the charts. Extraneous data appearing on the 60 test items were deleted to minimize confusion with the data to be evaluated. The items were then mounted in four random sequences on a display drum. Items were presented singly through a 2.4- by 3.0-cm (0.9- by 1.2-in) viewing aperture in a neutral-gray occluder plate.

The viewing aperture and the surrounding area were illuminated by a 60-W incandescent bulb (General Electric Daylight Blue) mounted in a stainless steel reflector. Luminance levels of 0.25, 1.00, and 4.00 fL were achieved by regulating the voltage applied to the bulb. Luminance in the aperture was measured by a Pritchard Spectra Photometer from a white oxide diffuser plaque immediately behind the aperture.

Test subjects were 11 male and 7 female non-pilot volunteers. Non-pilot subjects were used in order to avoid the confounding factor of variable experience levels found in the pilot population. All subjects had 20/20 near visual acuity corrected by reading glasses or bifocal lenses when necessary. Subjects' ages ranged from 27 to 58 years with a mean age of 45 years. The subjects viewed the display from a distance of 40 cm (15.7 in) as measured from the apex of the cornea to the center of the aperture.

The subjects were read the instructions and shown a representative sample of each category of test items. It was emphasized that they should respond as quickly as was consistent with accuracy and completeness and should not spend undue time on difficult items. The display illumination was adjusted to the level specified for the first trial and the room lights were extinguished. A 2-minute adaptation period preceded the beginning of the first series of test items. The 60 items were presented with a short interruption after every 15th presentation to reposition the drum for the next list. When subjects had completed the last item, the illumination was adjusted to the next level and the procedure repeated. A third trial

TABLE 1. Test Items With Chart Locations

<u>TEST ITEM</u>	<u>CHART REFERENCE</u>	
<u>UHF/VHF Airway and Route Data</u>		
Moderate Terrain Contrast		
V-280	105°00' W	33°00' N
V-25	120°00' W	34°40' N
V-197	118°30' W	35°00' N
Low Terrain Contrast		
V-105-257	112°15' W	34°15' N
V-190	110°15' W	34°00' N
V-237	114°30' W	35°10' N
<u>Aerodome Legends</u>		
Moderate Terrain Contrast		
Conchas State Park	104°15' W	35°20' N
Grants-Milan	108°00' W	35°15' N
Diamond A. Ranch	105°10' W	33°20' N
Low Terrain Contrast		
Transwestern	109°15' W	35°30' N
St. Johns	109°30' W	34°30' N
Bagdad	113°10' W	34°40' N
<u>Air/Ground Communication</u>		
Moderate Terrain Contrast		
Thermal	116°25' W	33°35' N
Santa Barbara	119°35' W	34°35' N
San Luis Obispo	120°30' W	35°15' N
Low Terrain Contrast		
St. Johns	109°20' W	34°15' N
Santa Fe	106°30' W	35°45' N
Zuni	109°15' W	35°20' N

TABLE 2. Comparative Error and Time Score for UHF/VHF Airway and Route Data at Two Contrast Levels and Three Luminance Levels

	0.25 fL			1.00 fL		4.00 fL	
	Original Terrain			Original Terrain		Original Terrain	
MODERATE CONTRAST	ERROR SCORE	Misreading	2	6	0	1	0
		Major Omission	0	0	0	0	0
		No Response	0	0	0	0	0
		Total Errors	2	6	0	1	0
		Error Rate (%)	4	11	0	2	0
MODERATE CONTRAST	TIME SCORE	Recognition Time (sec)	1.66	1.94	1.29	1.31	1.14
		Percent Increase	--	17	--	2	--
		Reading Time (sec)	6.01	7.38	5.23	5.13	5.23
		Percent Increase	--	23	--	(2)	--
							(1)
LOW CONTRAST	ERROR SCORE	Misreading	0	19	0	11	0
		Major Omission	0	6	0	0	0
		No Response	0	2	0	0	0
		Total Errors	0	27	0	11	0
		Error Rate (%)	0	50	0	20	0
LOW CONTRAST	TIME SCORE	Recognition Time (sec)	1.59	3.36	1.26	1.71	1.26
		Percent Increase	--	111	--	36	--
		Reading Time (sec)	7.67	13.76	6.79	8.40	6.87
		Percent Increase	--	79	--	24	--
							8

TABLE 3. Comparative Error and Time Score for Aerodromes Without Published Instrument Approach Procedures at Two Contrast Levels and Three Luminance Levels

		0.25 fL			1.00 fL			4.00 fL		
		Original Terrain			Original Terrain			Original Terrain		
		Original	Terrain		Original	Terrain		Original	Terrain	
MODERATE CONTRAST	ERROR SCORE	Misreading	2	4	0	1	1	1	0	0
		Major Omission	0	3	0	0	0	0	0	0
		No Response	0	0	0	0	0	0	0	0
		Total Errors	2	7	0	1	1	1	0	0
		Error Rate (%)	4	13	0	2	2	2	0	0
MODERATE CONTRAST	TIME SCORE	Recognition Time (sec)	1.95	2.60	1.45	1.58	1.20	1.34		
		Percent Increase	--	33	--	9	--	12		
		Reading Time(sec)	7.44	9.82	5.63	6.34	5.34	5.85		
		Percent Increase	--	32	--	13	--	10		
		Misreading	5	15	0	12	0	13		
LOW CONTRAST	ERROR SCORE	Major Omission	1	7	0	7	0	1		
		No Response	0	20	0	3	0	0		
		Total Errors	6	42	0	22	0	14		
		Error Rate (%)	11	78	0	41	0	26		
		Recognition Time (sec)	2.00	8.35	1.37	4.39	1.06	2.50		
LOW CONTRAST	TIME SCORE	Percent Increase	--	318	--	220	--	136		
		Reading Time (sec)	7.90	20.30	6.01	13.10	5.37	9.01		
		Percent Increase	--	157	--	118	--	68		

TABLE 4. Comparative Error and Time Score for Air/Ground Communication Boxes at Two Contrast Levels and Three Luminance Levels

	0.25 fL		1.00 fL		4.00 fL	
	Original	Terrain	Original	Terrain	Original	Terrain
MODERATE CONTRAST	ERROR SCORE					
	Misreading	1	5	0	0	0
	Major Omission	0	0	0	0	0
	No Response	0	0	0	0	0
	Total Errors	1	5	0	0	0
MODERATE CONTRAST	TIME SCORE					
	Recognition Time (sec)	1.29	1.33	1.02	1.02	1.11
	Percent Increase	--	3	--	--	9
	Reading Time (sec)	7.02	7.82	5.96	6.00	6.10
	Percent Increase	--	11	--	--	2
LOW CONTRAST	ERROR SCORE					
	Misreading	2	3	0	0	0
	Major Omission	1	5	0	0	0
	No Response	0	0	0	0	0
	Total Errors	3	8	0	0	0
LOW CONTRAST	TIME SCORE					
	Recognition Time (sec)	1.20	1.76	0.96	0.94	1.02
	Percent Increase	--	47	--	--	9
	Reading Time (sec)	6.70	9.97	5.69	5.70	5.86
	Percent Increase	--	49	--	--	3



TABLE 5. Comparative Error and Time Score for ARTCC Remoted Site Boxes at Two Contrast Levels and Three Luminance Levels

	0.25 fL			1.00 fL		4.00 fL	
	Original Terrain		Terrain	Original Terrain		Original Terrain	
MODERATE CONTRAST	ERROR SCORE						
	Misreading		9	17	0	7	2
	Major Omission		5	15	0	4	0
	No Response		0	6	0	0	0
	Total Errors		14	38	0	11	2
MODERATE CONTRAST	Error Rate (%)		26	70	0	20	4
	Recognition Time (sec)		1.53	3.55	1.05	1.68	0.99
	Percent Increase		--	132	--	60	--
	Reading Time (sec)		10.47	15.16	6.21	9.20	5.92
	Percent Increase		--	45	--	48	--
LOW CONTRAST	ERROR SCORE		10	8	0	12	16
	Misreading		11	13	0	10	8
	Major Omission		1	31	0	12	2
	No Response		22	52	0	34	26
	Total Errors		41	96	0	63	48
LOW CONTRAST	Error Rate (%)		2.19	10.17	1.17	5.26	0.98
	Recognition Time (sec)		--	364	--	350	--
	Percent Increase		13.26	24.87	7.16	17.17	6.18
	Reading Time (sec)		--	88	--	140	--
	Percent Increase						

slightly longer than times required by the slowest reader. If a "Major Omission" error was scored for the item, the actual reading time was doubled, subject to the 30-second maximum value. "Percent Increase" values are the increases in time required to respond to the terrain concept items compared to the standard version of the same items. The two values in parentheses in Table 2 indicate decreases in reading times. All percentage values have been rounded to the nearest full percentage point.

The data for the MEFs are presented in Table 6. The error definitions are the same as for the other categories of information except that the "Major Omission" category is not included because of the limited numeric content of these test items. Time scores for the MEFs follow the criteria for the other categories of test items except that "Recognition Time" was limited to a maximum of 10 seconds and "Reading Time" to a maximum of 20 seconds in order to avoid excessive distortion of time scores for items that normally have a very short reading time. Percent increase values for the medium and low contrast items are based on comparison with the high contrast level items.

#### IV. Discussion.

An effective terrain depiction format appears to depend on establishment of acceptable contrast ratios between the alphanumeric information and the terrain background. Such ratios must not only provide for adequate readability of the alphanumeric information, but also must accommodate a wide enough range in terrain printing densities to effectively depict the terrain background.

If terrain densities are equal to or less than the intermediate values used in this study, only minimal changes in character size or density will be necessary to assure adequate readability of the charts. If terrain printing densities causing low contrast are utilized, it will be necessary to consider increasing the size of the alphanumeric characters. Contrast enhancement by use of selected color combinations, alternate symbology, and reduction of terrain printing densities behind alphanumeric data (blocking) might also be considered.

Specific recommendations for providing maximum readability of a given format must be developed on the basis of the criteria governing the purpose of the chart. There is abundant

literature addressed to the general problem of readability of the printed word and graphic material. A good summary of map and chart design for aviation has been issued by the Australian Department of Civil Aviation that also includes an extensive reference section providing coverage of the pertinent literature (1).

All subjects in this study had good vision and were viewing the chart elements under ideal laboratory conditions. Common in-flight factors such as degraded visual acuity, vibration, turbulence, distraction and stress would logically be expected to reduce chart readability below the levels found in this study.

TABLE 6. Error and Time Score for Maximum Elevation Figures (MEF)  
at Three Contrast Levels and Three Luminance Levels

	0.25 fL			1.00 fL			4.00 fL			
	High	Medium	Low	High	Medium	Low	High	Medium	Low	
ERROR SCORE	Misreading	0	3	9	0	2	14	0	0	13
	No Response	0	0	26	0	0	16	0	0	6
	Total Errors	0	3	35	0	2	30	0	0	19
	Error Rate (%)	0	4	49	0	3	42	0	0	26
TIME SCORE	Recognition Time (sec)	0.99	1.28	5.42	0.94	1.05	4.23	0.94	1.06	2.78
	Percent Increase	--	29	447	--	12	350	--	13	196
	Reading Time (sec)	1.56	2.03	10.18	1.50	1.65	7.49	1.48	1.67	4.74
	Percent Increase	--	30	553	--	10	399	--	13	220

#### REFERENCE

1. Watkins, R. D.: The Presentation of Printed Information to Aircraft Pilots, Aviation Medical Branch, Department of Civil Aviation, Aviation Medicine Memorandum No. 27, Melbourne, Australia, 1970.

