

8/10/2021

CAX - Commercial Pilot Airplane

The following sample questions for Commercial Pilot-Airplane (CAX) are suitable study material for the Commercial Pilot-Airplane Rating. These questions are a representation of questions that can be found on all Commercial Pilot-Airplane Rating tests. The applicant must realize that these questions are to be used as a study guide, and are not necessarily actual test questions. The full CAX test contains 100 questions. The Application Identification, Information Verification, and Authorization Requirements Matrix lists all FAA exams. It is available at

www.faa.gov/training_testing/testing/media/testing_matrix.pdf

The FAA testing system is supported by a series of supplement publications. These publications include the graphics, legends, and maps that are needed to successfully respond to certain test questions. FAA-CT-8080-1E, Airman Knowledge Testing Supplement for Commercial Pilot is available at

www.faa.gov/training_testing/testing/supplements/media/commercial_akts.pdf

The questions presented here have an associated Airman Certification Standards (ACS) code. The ACS Codes link the individual question to a Task Element within the Commercial Pilot-Airplane (CAX) ACS document. The CAX ACS is available at

www.faa.gov/training_testing/testing/acs/media/commercial_airplane_acs_change_1.pdf

The online Commercial Pilot Airplane (CAX) practice test is available on the PSI website at <https://faa.psiexams.com/FAA/login>

NOTE: Some questions in the PSI Practice Test may contain the reference "Refer to FAA-CT-8080 . ." You may access the referred to supplement by opening the following link in a separate window while taking the test.

www.faa.gov/training_testing/testing/supplements/media/commercial_akts.pdf

1. When in the vicinity of a VOR which is being used for navigation on VFR flights, it is important to
- A. make 90° left and right turns to scan for other traffic.
 - B. exercise sustained vigilance to avoid aircraft that may be converging on the VOR from other directions.
 - C. pass the VOR on the right side of the radial to allow room for aircraft flying in the opposite direction on the same radial.

Metadata: ACS_CA_Code : CA.VI.A.R1

2. An airplane is converging with a helicopter. Which aircraft has the right-of-way?
- A. The aircraft on the left.
 - B. The aircraft on the right.
 - C. The faster of the two aircraft.

Metadata: ACS_CA_Code : CA.III.B.K3

3. Your VFR flight will be conducted above 10,000 MSL in Class E airspace. What is the minimum flight visibility?
- A. 3 NM.
 - B. 5 SM.
 - C. 1 SM.

Metadata: ACS_CA_Code : CA.I.E.K1

4. You are pilot-in-command of a VFR flight that you think will be within the fuel range of your aircraft. As part of your preflight planning you must
- A. be familiar with all instrument approaches at the destination airport.
 - B. list an alternate airport on the flight plan, and confirm adequate takeoff and landing performance at the destination airport.
 - C. obtain weather reports, forecasts, and fuel requirements for the flight.

Metadata: ACS_CA_Code : CA.I.C.K3

5. What are the characteristics of an unstable atmosphere?

- A. A cool, dry air mass.**
- B. A warm, humid air mass.**
- C. Descending air in the northern hemisphere.**

Metadata: ACS_CA_Code : CA.I.C.K3a

6. (Refer to FAA-CT-8080-1E, Figure 38.) Given the following information, does the weight of the aircraft and center of gravity fall within allowable limits?

Empty Weight (oil is included) = 1,275 lb

Empty Weight moment (in-lb/1,000) = 102.05

Pilot and copilot = 390 lb

Rear seat passenger = 145 lb

Cargo = 95 lb

Fuel = 35 gallons

- A. Yes, the weight and center of gravity is within allowable limits.**
- B. No, the weight exceeds the maximum allowable.**
- C. No, the weight is acceptable, but the center of gravity is aft of the allowable limits.**

Metadata: ACS_CA_Code : CA.I.F.K2f

7. (Refer to FAA-CT-8080-1E, Figure 52, Area 8.) The traffic pattern altitude at the Auburn (AUN) airport is 1,000 feet AGL. May you practice landings under VFR when the AWOS is reporting a ground visibility of 2 miles?

- A. Yes, you will be operating in a combination of Class E and G airspace.**
- B. No, the reported ground visibility must be at least 3 miles.**
- C. No, the Class E airspace extends to the airport surface.**

Metadata: ACS_CA_Code : CA.I.E.K1

8. Which is true regarding the use of airborne weather-avoidance radar for the recognition of certain weather conditions?

- A. The radar scope provides no assurance of avoiding instrument weather conditions.**
- B. The avoidance of hail is assured when flying between and just clear of the most intense echoes.**
- C. The clear area between intense echoes indicates that visual sighting of storms can be maintained when flying between the echoes.**

Metadata: ACS_CA_Code : CA.I.C.K4

9. Your aircraft has an exhaust manifold type heating system. The exhaust manifold is periodically inspected to avoid
- A. carbon monoxide poisoning.
 - B. overheating in the cockpit.
 - C. extremely cold temperatures in the cabin.

Metadata: ACS_CA_Code : CA.I.G.K1i

10. When departing from a runway that is covered with snow or slush, what could a pilot do to prevent damage to the landing gear due to the conditions?
- A. Do not retract the landing gear immediately to allow the gear to air-dry.
 - B. Immediately retract the landing gear so it can be heated in the gear wells.
 - C. Fly at a speed above the green arc of the airspeed indicator to remove the snow and slush.

Metadata: ACS_CA_Code : CA.I.G.K1d

11. (Refer to FAA-CT-8080-1E, Figure 11.) What would be the approximate true airspeed and fuel consumption per hour at an altitude of 7,500 feet, using 52 percent power?
- A. 103 MPH TAS, 6.3 GPH.
 - B. 105 MPH TAS, 6.2 GPH.
 - C. 105 MPH TAS, 6.6 GPH.

Metadata: ACS_CA_Code : CA.I.D.K3a

12. What should be expected when making a downwind landing? The likelihood of
- A. undershooting the intended landing spot and a faster airspeed at touchdown.
 - B. overshooting the intended landing spot and a faster groundspeed at touchdown.
 - C. undershooting the intended landing spot and a faster groundspeed at touchdown.

Metadata: ACS_CA_Code : CA.IV.B.K2

13. When transitioning from straight-and-level flight to a constant airspeed climb, the angle of attack and lift
- A. are increased and remain at a higher lift-to-weight ratio to maintain the climb.
 - B. remain the same and maintain a steady state lift-to-weight ratio during the climb.
 - C. are momentarily increased and lift returns to a steady state during the climb.

Metadata: ACS_CA_Code : CA.I.F.K3

14. If you experience an engine failure in a single-engine aircraft after takeoff, you should
- A. establish the proper glide attitude.
 - B. turn into the wind.
 - C. adjust the pitch to maintain V_Y .

Metadata: ACS_CA_Code : CA.IV.A.R3b

15. You are acting as a commercial pilot, but are not operating under the regulations of 14 CFR part 119. Which of these operations are you authorized to conduct?
- A. On-demand, passenger carrying flights of nine persons or less.
 - B. Aerial application and aerial photography.
 - C. On-demand cargo flights.

Metadata: ACS_CA_Code : CA.I.A.K2

16. (Refer to FAA-CT-8080-1E, Figure 61.) Ground control has instructed you to taxi Alpha to Foxtrot to the active runway. According to the sign in the figure, which direction would you turn at this intersection to comply with ATC?
- A. No turn is required.
 - B. The turn will be made to the right.
 - C. The turn will be made to the left.

Metadata: ACS_CA_Code : CA.II.D.K3

17. While executing a 60° level turn, your aircraft is at a load factor of 2.0. What does this mean?
- A. The total load on the aircraft's structure is two times its weight.
 - B. The load factor is over the load limit.
 - C. The gust factor is two times the total load limit.

Metadata: ACS_CA_Code : CA.I.F.K3

18. What could be one result of exceeding critical Mach number?
- A. Propeller stall.
 - B. Reduction in drag.
 - C. Aircraft control difficulties.

Metadata: ACS_CA_Code : CA.I.F.K3

19. What should you expect when you are told that LAHSO operations are in effect at your destination airport?

- A. All aircraft must operate on an IFR clearance due to high traffic volume.**
- B. ATC may offer a clearance to land and hold short of a specified point on the runway.**
- C. Delays due to low IFR conditions and high traffic volume.**

Metadata: ACS_CA_Code : CA.IV.B.R3b

20. You attended a party last night and you consumed several glasses of wine. You are planning to fly your aircraft home and have been careful to make sure 8 hours have passed since your last alcoholic drink. You can make the flight now only if you are not under the influence of alcohol and your blood alcohol level is

- A. below .04%.**
- B. below .08%.**
- C. 0.0%.**

Metadata: ACS_CA_Code : CA.I.H.K2

21. You are conducting your preflight of an aircraft and notice that the last inspection of the emergency locator transmitter was 11 calendar months ago. You may

- A. depart if you get a special flight permit.**
- B. depart because the ELT is within the inspection requirements.**
- C. not depart until a new inspection is conducted.**

Metadata: ACS_CA_Code : CA.I.B.K1b

22. What significant cloud coverage is reported by this pilot report?

KMOB UA/OV 15NW MOB 1340Z/SK 025 OVC 045/075 OVC 080/090 OVC

- A. Three (3) separate overcast layers exist with bases at 2,500, 7,500 and 9,000 feet.**
- B. The top of the lower overcast is 2,500 feet; base and top of second overcast layer are 4,500 and 9,000 feet, respectively.**
- C. The base of the second overcast layer is 2,500 feet; top of second overcast layer is 7,500 feet; base of third layer is 9,000 feet.**

Metadata: ACS_CA_Code : CA.I.C.K2

23. Given the following METAR: KHOB 151250Z 17006KT 4SM BKN025 OVC040 13/11 A2998, what is the maximum altitude to maintain VFR below the ceiling in Class E airspace below 10,000 feet MSL?

- A. 2,000 feet AGL.
- B. 3,500 feet AGL.
- C. 3,900 feet AGL.

Metadata: ACS_CA_Code : CA.I.C.K2

24. You would like to enter Class B airspace and contact the approach controller. The controller responds to your initial radio call with "N125HF standby." May you enter the Class B airspace?

- A. You must remain outside Class B airspace until controller gives you a specific clearance.
- B. You may continue into the Class B airspace and wait for further instructions.
- C. You may continue into the Class B airspace without a specific clearance, if the aircraft is ADS-B equipped.

Metadata: ACS_CA_Code : CA.I.E.K1

25. You are avoiding a thunderstorm that is in your flightpath. You are over 20 miles from the cell however, you are under the anvil of the cell. Is this a hazard?

- A. No, you are at a safe distance from the cell.
- B. Yes, hail can be discharged from the anvil.
- C. Yes, this is still in the area of dissipation.

Metadata: ACS_CA_Code : CA.I.C.K3h

26. (Refer to FAA-CT-8080-1E, Figure 32.) What is the total takeoff distance required to clear a 50-foot obstacle with the following conditions.

Temperature: 50 °F

Pressure altitude: 4,000 feet

Weight: 3,200 lbs.

Headwind: 15 kts.

- A. 1,200 feet.
- B. 880 feet.
- C. 700 feet.

Metadata: ACS_CA_Code : CA.I.F.K1

27. You are preflight planning in the morning before an afternoon flight. Where would you find information regarding an "Airport surface hot spot?"

- A. Call the Automated Flight Service Station.**
- B. In the Chart Supplements U.S.**
- C. In the NOTAMs during your preflight briefing.**

Metadata: ACS_CA_Code : CA.II.D.K1

28. (Refer to FAA-CT-8080-1E, Figure 53, Area 4.) You plan to depart on a day VFR flight from the Firebaugh (F34) airport. What is the floor of controlled airspace above this airport?

- A. 1,200 feet above the airport.**
- B. 700 feet above the airport.**
- C. 1,500 feet above the airport.**

Metadata: ACS_CA_Code : CA.I.E.K1

29. You are most likely to experience somatogravic illusion during

- A. a rapid descent.**
- B. deceleration upon landing.**
- C. rapid acceleration on takeoff.**

Metadata: ACS_CA_Code : CA.I.H.K1d

30. What must a pilot do or be aware of when transitioning an Alert Area?

- A. All pilots must contact the controlling agency to ensure aircraft separation.**
- B. Non-participating aircraft may transit the area as long as they operate in accordance with their waiver.**
- C. Be aware that the area may contain unusual aeronautical activity or high volume of pilot training.**

Metadata: ACS_CA_Code : CA.I.E.K3

31. (Refer to FAA-CT-8080-1E, Figure 53, Area 2.) What is indicated by the star next to the "L" in the airport information box for the MADERA (MAE) airport north of area 2?

- A. Special VFR is prohibited.**
- B. There is a rotating beacon at the field.**
- C. Lighting limitations exist.**

Metadata: ACS_CA_Code : CA.I.E.K2

- 32. (Refer to FAA-CT-8080-1E, Figure 54, Area 3.) What is the significance of R-2531? This is a restricted area**
- A. for IFR aircraft.**
 - B. where aircraft may never operate.**
 - C. where often invisible hazards exist.**

Metadata: ACS_CA_Code : CA.I.E.K3

- 33. (Refer to FAA-CT-8080-1E, Figure 53.) You are planning a VFR west bound flight departing the FRESNO CHANDLER EXECUTIVE (FCH) airport and you will be passing through the active Lemoore C and A MOAs. What action should you take?**
- A. Exercise extreme caution while in the boundaries of the MOA.**
 - B. Avoid the MOA, VFR, and IFR flights are prohibited during day light hours.**
 - C. Contact the aircraft operating in the MOA on the Guard frequency of 121.5.**

Metadata: ACS_CA_Code : CA.I.E.K3

- 34. As a commercial pilot, you decide to start a small business flying non-stop tours to look at Christmas lights during the holiday season. What authorizations, if any, are required to conduct Christmas light tours?**
- A. No authorizations or approvals are required if you hold the appropriate category and class rating for the aircraft that will be flown.**
 - B. You must apply for and receive a Letter of Authorization from a Flight Standards District Office.**
 - C. You must apply to the FAA to receive an exemption to carry passengers at night within a 50 mile radius of your departure airport.**

Metadata: ACS_CA_Code : CA.I.A.K2

- 35. You are PIC of a flight and determine that the aircraft you planned to fly has an overdue Airworthiness Directive (AD). Which of the following is an appropriate decision?**
- A. No maintenance is available so you wait until after the trip to comply with the AD.**
 - B. You make the flight because you can overfly an AD by 10 hours.**
 - C. You cancel the flight and have the aircraft scheduled for maintenance.**

Metadata: ACS_CA_Code : CA.I.B.K1c

- 36. Your flight takes you in the path of a large aircraft. In order to avoid the vortices you should fly**
- A. at the same altitude as the large aircraft.**
 - B. below the altitude of the large aircraft.**
 - C. above the flight path of the large aircraft.**

Metadata: ACS_CA_Code : CA.IV.A.R2d

- 37. To act as PIC of a high performance airplane, which training or experience would meet the additional requirements?**
- A. Logged at least five hours as SIC in a high performance or turbine-powered airplane in the last 12 calendar months.**
 - B. Received and logged ground and flight training in an airplane with retractable landing gear, flaps, and controllable-pitch propeller.**
 - C. Received and logged ground and flight training in a high performance airplane and a received a logbook endorsement.**

Metadata: ACS_CA_Code : CA.I.A.K1

- 38. You have accomplished 25 takeoffs and landings in multi-engine land airplanes in the previous 45 days. For a flight you plan to conduct today, this meets the PIC recency of experience requirements to carry passengers in which airplanes?**
- A. Multi or single-engine land.**
 - B. Single-engine land airplane.**
 - C. Multi-engine land airplane.**

Metadata: ACS_CA_Code : CA.I.A.K1

- 39. There is a high pressure system that is located south of your planned route in the Northern Hemisphere on a west to east cross-country flight. To take advantage of favorable winds, you would plan your route**
- A. on the north side of the high pressure area.**
 - B. on the south side of the high pressure area.**
 - C. through the middle of the high pressure area.**

Metadata: ACS_CA_Code : CA.I.D.K2

40. In the following METAR/TAF for HOU, what is the ceiling and visibility forecast on the 7th day of the month at 0600Z?

**KHOU 061734Z 0618/0718 16014G22KT P6SM VCSH BKN018 BKN035
FM070100 17010KT P6SM BKN015 OVC025
FM070500 17008KT 4SM BR SCT008 OVC012
FM071000 18005KT 3SM BR OVC007
FM071500 23008KT 5SM BR VCSH SCT008 OVC015**

- A. Visibility 6 miles with a broken ceiling at 15,000 feet MSL.**
- B. 4 nautical miles of visibility and an overcast ceiling at 700 feet MSL.**
- C. 4 statute miles visibility and an overcast ceiling at 1,200 feet AGL.**

Metadata: ACS_CA_Code : CA.I.C.K2

41. You have delayed your flight to allow a fast moving cold front to clear your destination airport before your arrival. What type of flying conditions would you expect after the front has passed?

- A. A fast moving squall line with high winds and thunderstorms.**
- B. Clear skies with gusty, turbulent winds and cooler temperatures.**
- C. Low clouds, reduced visibility and showery, misty conditions.**

Metadata: ACS_CA_Code : CA.I.C.K3e

42. What is a consideration when using a hand-held GPS for VFR navigation?

- A. Position accuracy may degrade without notification.**
- B. RAIM capability will be maintained for entire flight.**
- C. Waypoints will still be accurate even if database is not current.**

Metadata: ACS_CA_Code : CA.VI.B.K2

43. What procedure could a pilot use to navigate under VFR from one point to another when ground references are not visible?

- A. Dead reckoning.**
- B. Pilotage.**
- C. VFR is not allowed in these circumstances.**

Metadata: ACS_CA_Code : CA.VI.A.K1

44. (Refer to FAA-CT-8080-1E, Figure 52, Area 2.) When departing the RIO LINDA (L36) airport to the northwest at an altitude of 1,000 feet, AGL, you

- A. must make contact with MC CLELLAN (MCC) control tower as soon as practical after takeoff.**
- B. are not required to contact any ATC facilities if you do not enter the Class C Airspace**
- C. must make contact with the SACRAMENTO INTL (SMF) control tower immediately after takeoff.**

Metadata: ACS_CA_Code : CA.I.E.K1

45. You are flying an aircraft equipped with an electronic flight display and the air data computer fails. What instrument is affected?

- A. ADS-B in capability.**
- B. Airspeed indicator.**
- C. Attitude indicator.**

Metadata: ACS_CA_Code : CA.IX.C.K2d

46. When conducting a go-around, the pilot must be aware that

- A. radio communications are key to alerting other aircraft in the pattern that a go-around maneuver is being conducted.**
- B. the airplane is trimmed for a power-off condition, and application of takeoff power will cause the nose to rise rapidly.**
- C. flaps should be raised as quickly as possible to reduce drag and increase airspeed for a successful go-around.**

Metadata: ACS_CA_Code : CA.IV.B.R3a

47. On a post flight inspection of your aircraft after an aborted takeoff due to an elevator malfunction, you find that the elevator control cable has broken. According to NTSB 830, you

- A. must immediately notify the nearest NTSB office.**
- B. should notify the NTSB within 10 days.**
- C. must file a NASA report immediately.**

Metadata: ACS_CA_Code : CA.III.A.K8

48. Structural damage or failure is more likely to occur in smooth air at speeds above

- A. V_{NO} .**
- B. V_A .**
- C. V_{NE} .**

Metadata: ACS_CA_Code : CA.I.F.R2

49. As air temperature increases, density altitude will

- A. decrease.**
- B. increase.**
- C. remain the same.**

Metadata: ACS_CA_Code : CA.I.C.K3c

50. Unless otherwise authorized by ATC, which airspace requires the appropriate Automatic Dependent Surveillance-Broadcast (ADS-B) Out equipment installed?

- A. Within Class E airspace below the upper shelf of Class C Airspace.**
- B. Above the ceiling and within the lateral boundaries of Class D airspace up to 10,000 feet MSL.**
- C. Within Class G airspace 25 nautical miles from a Class B airport.**

Metadata: ACS_CA_Code : CA.I.E.K1