

LINK	ANTENNA	RANGE
MHX910	Whip	
MHX910	Omni	
MHX910	Yagi	
MHX320	Whip	9km (LOS)
MHX320	Omni	31km (LOS)
MHX320	Yagi	
Iridium SATCOMM	N/A	Unlimited

2

GCS Limitations

Stage Box Electrical System Limitations (Suitcase Type)

AC Input	90-240 VAC / 50-60 Hz
DC Input	10-16 VDC
System Voltage Displayed (nominal)	14.8 V
Battery Back-up Fail	<9 V

Stage Box Electrical System Limitations (Benchtop Type)

DC Input (Main)	16 VDC
DC Input (Auxillary)	11-14 VDC
DC Transformer	Input: 100-250 VAC / 50-60 Hz Output: 16VDC / 2.8A
System Voltage Displayed (nominal)	13.3 V
Battery Back-up Fail	<9 V

Stage Box Environmental Limitations

Min Ambient Operating Temp	-40°C
Max Ambient Operating Temp	80°C

Uplink/Downlink Frequency

Microhard MHX320	340 – 390 MHz (user selectable)
Microhard MHX910	900 MHz Spread Spectrum Frequency Hopping
Iridium SATCOMM	1616 – 1626.5 MHz (TDMA/FDMA)

Uplink/Downlink Power

Microhard MHX320	1 W
Microhard MHX910	1 W
Iridium SATCOMM	0.6W

Communications Systems Datalink Ranges (km)

LIN K	ANTENNA	RANGE
MHX910	Whip	
MHX910	Omni	
MHX910	Yagi	
MHX320	Whip	9km (LOS)
MHX320	Omni	31km (LOS)
MHX320	Yagi	
Refer to payload documentation for any payload specific environmental limitations		
Iridium SATCOMM	N/A	Unlimited

