

DRAFT ENVIRONMENTAL IMPACT STATEMENT

SPACEX STARSHIP-SUPER HEAVY LAUNCH VEHICLE AT LAUNCH COMPLEX 39A

at the Kennedy Space Center, Merritt Island, Florida

Volume II, Appendix C.2, Part 2

August 2025



**Federal Aviation
Administration**

THIS PAGE INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

Appendix C	Resource Area Supporting Information	C-1
C.1	Noise Assessment and Noise Assessment Appendix.....	C-1
C.1.1	Noise Assessment	C-1
C.1.2	Noise Assessment Appendix.....	C-2
C.2	Air Quality Assessment.....	C-3
C.2.1	Engine Emissions Analysis	C-3
C.2.2	ACAM Construction Analysis	C-6
C.3	Biological Resources Supplemental Information.....	C-143
C.3.1	State-Listed Species	C-143
C.3.2	Migratory Bird Species	C-145
C.3.3	Marine Mammal Species in the Study Area	C-148

THIS PAGE INTENTIONALLY LEFT BLANK.

8.4.1 Architectural Coatings Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
Start Quarter: 1
Start Year: 2026

- Phase Duration

Number of Month: 3
Number of Days: 0

8.4.2 Architectural Coatings Phase Assumptions

- General Architectural Coatings Information

Building Category: Non-Residential
Total Square Footage (ft²): 16836
Number of Units: N/A

- Architectural Coatings Default Settings

Default Settings Used: Yes
Average Day(s) worked per week: 5 (default)

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

8.4.3 Architectural Coatings Phase Emission Factor(s)

- Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

8.4.4 Architectural Coatings Phase Formula(s)

- Worker Trips Emissions per Phase

$$VMT_{WT} = (1 * WT * PA) / 800$$

VM_{WT} : Worker Trips Vehicle Miles Travel (miles)
 1: Conversion Factor man days to trips (1 trip / 1 man * day)
 WT : Average Worker Round Trip Commute (mile)
 PA : Paint Area (ft^2)
 800: Conversion Factor square feet to man days (1 ft^2 / 1 man * day)

$$V_{POL} = (VM_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VM_{WT} : Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_{AC} = (AB * 2.0 * 0.0116) / 2000.0$$

VOC_{AC} : Architectural Coating VOC Emissions (TONs)
 AB : Area of Building (ft^2)
 2.0: Conversion Factor total area to coated area (2.0 ft^2 coated area / total area)
 0.0116: Emission Factor (lb/ ft^2)
 2000: Conversion Factor pounds to tons

9. Construction / Demolition

9.1 General Information & Timeline Assumptions

- Activity Location

County: Brevard
Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Water Farm

- Activity Description:

A new water tank farm area would be constructed at LC-39A near the launch mount.

- Activity Start Date

Start Month: 1
Start Month: 2026

- Activity End Date

Indefinite: False
End Month: 3
End Month: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.220036
SO _x	0.001180
NO _x	0.597701
CO	0.804101

Pollutant	Total Emissions (TONs)
PM 10	0.797502
PM 2.5	0.023403
Pb	0.000000
NH ₃	0.001254

- Activity Emissions of GHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.005296
N ₂ O	0.001674

Pollutant	Total Emissions (TONs)
CO ₂	134.335448
CO ₂ e	134.966512

- Global Scale Activity Emissions for SCGHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.005294
N ₂ O	0.001673

Pollutant	Total Emissions (TONs)
CO ₂	134.293509
CO ₂ e	134.924338

9.1 Site Grading Phase**9.1.1 Site Grading Phase Timeline Assumptions****- Phase Start Date**

Start Month: 1
Start Quarter: 1
Start Year: 2026

- Phase Duration

Number of Month: 3
Number of Days: 0

9.1.2 Site Grading Phase Assumptions**- General Site Grading Information**

Area of Site to be Graded (ft²): 12935
Amount of Material to be Hauled On-Site (yd³): 0
Amount of Material to be Hauled Off-Site (yd³): 0

- Site Grading Default Settings

Default Settings Used: Yes
Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Graders Composite	1	6
Other Construction Equipment Composite	1	8
Rubber Tired Dozers Composite	1	6
Tractors/Loaders/Backhoes Composite	1	7

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)
Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
--	------	------	------	------	------	------	----

POVs	50.00	50.00	0	0	0	0	0
------	-------	-------	---	---	---	---	---

9.1.3 Site Grading Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Graders Composite [HP: 148] [LF: 0.41]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.31292	0.00490	2.52757	3.39734	0.14041	0.12918
Other Construction Equipment Composite [HP: 82] [LF: 0.42]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.28160	0.00487	2.73375	3.50416	0.15811	0.14546
Rubber Tired Dozers Composite [HP: 367] [LF: 0.4]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.35280	0.00491	3.22260	2.72624	0.14205	0.13069
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gases Pollutant Emission Factors (g/hp-hour) (default)

Graders Composite [HP: 148] [LF: 0.41]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02153	0.00431	530.81500	532.63663
Other Construction Equipment Composite [HP: 82] [LF: 0.42]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02140	0.00428	527.54121	529.35159
Rubber Tired Dozers Composite [HP: 367] [LF: 0.4]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02160	0.00432	532.54993	534.37751
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gases Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

9.1.4 Site Grading Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)
 20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)
 ACRE: Total acres (acres)
 WD: Number of Total Work Days (days)
 2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)
 NE: Number of Equipment
 WD: Number of Total Work Days (days)
 H: Hours Worked per Day (hours)
 HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL}: Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
 HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
 HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
 HC: Average Hauling Truck Capacity (yd³)
 (1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Vehicle Exhaust On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 WD: Number of Total Work Days (days)
 WT: Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

9.2 Trenching/Excavating Phase

9.2.1 Trenching / Excavating Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
Start Quarter: 1
Start Year: 2026

- Phase Duration

Number of Month: 3
Number of Days: 0

9.2.2 Trenching / Excavating Phase Assumptions

- General Trenching/Excavating Information

Area of Site to be Trenched/Excavated (ft²): 12935
Amount of Material to be Hauled On-Site (yd³): 0
Amount of Material to be Hauled Off-Site (yd³): 0

- Trenching Default Settings

Default Settings Used: Yes
Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Excavators Composite	2	8
Other General Industrial Equipmen Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)
Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

9.2.3 Trenching / Excavating Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.39317	0.00542	3.40690	4.22083	0.09860	0.09071
Other General Industrial Equipmen Composite [HP: 35] [LF: 0.34]						

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.45335	0.00542	3.58824	4.59368	0.11309	0.10404
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gasses Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02381	0.00476	587.02896	589.04350
Other General Industrial Equipment Composite [HP: 35] [LF: 0.34]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02385	0.00477	587.87714	589.89459
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

9.2.4 Trenching / Excavating Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM_{10FD} = (20 * ACRE * WD) / 2000$$

PM_{10FD}: Fugitive Dust PM 10 Emissions (TONs)
 20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)
 ACRE: Total acres (acres)
 WD: Number of Total Work Days (days)
 2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)
 NE: Number of Equipment
 WD: Number of Total Work Days (days)
 H: Hours Worked per Day (hours)

HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL} : Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 HA_{OnSite} : Amount of Material to be Hauled On-Site (yd³)
 $HA_{OffSite}$: Amount of Material to be Hauled Off-Site (yd³)
 HC: Average Hauling Truck Capacity (yd³)
 (1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM: Vehicle Exhaust On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 WD: Number of Total Work Days (days)
 WT: Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

9.3 Building Construction Phase

9.3.1 Building Construction Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration

Number of Month: 3
 Number of Days: 0

9.3.2 Building Construction Phase Assumptions

- General Building Construction Information

Building Category: Office or Industrial
Area of Building (ft²): 12935
Height of Building (ft): 15
Number of Units: N/A

- Building Construction Default Settings

Default Settings Used: Yes
Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Cranes Composite	1	4
Forklifts Composite	2	6
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

- Vendor Trips

Average Vendor Round Trip Commute (mile): 40 (default)

- Vendor Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

9.3.3 Building Construction Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Cranes Composite [HP: 367] [LF: 0.29]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.19758	0.00487	1.83652	1.63713	0.07527	0.06925
Forklifts Composite [HP: 82] [LF: 0.2]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.24594	0.00487	2.34179	3.57902	0.11182	0.10287
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gasses Pollutant Emission Factors (g/hp-hour) (default)

Cranes Composite [HP: 367] [LF: 0.29]						
---------------------------------------	--	--	--	--	--	--

	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02140	0.00428	527.46069	529.27080
Forklifts Composite [HP: 82] [LF: 0.2]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02138	0.00428	527.09717	528.90603
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

9.3.4 Building Construction Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

HP: Equipment Horsepower

LF: Equipment Load Factor

EF_{POL}: Emission Factor for Pollutant (g/hp-hour)

0.002205: Conversion Factor grams to pounds

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = BA * BH * (0.42 / 1000) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

BA: Area of Building (ft²)

BH: Height of Building (ft)

(0.42 / 1000): Conversion Factor ft³ to trips (0.42 trip / 1000 ft³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VM_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 WD : Number of Total Work Days (days)
 WT : Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE : Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Vender Trips Emissions per Phase

$$VMT_{VT} = BA * BH * (0.38 / 1000) * HT$$

VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
 BA : Area of Building (ft^2)
 BH : Height of Building (ft)
 (0.38 / 1000): Conversion Factor ft^2 to trips (0.38 trip / 1000 ft^2)
 HT : Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

9.4 Architectural Coatings Phase

9.4.1 Architectural Coatings Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration

Number of Month: 3
 Number of Days: 0

9.4.2 Architectural Coatings Phase Assumptions

- General Architectural Coatings Information

Building Category: Non-Residential
 Total Square Footage (ft²): 12935
 Number of Units: N/A

- Architectural Coatings Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

9.4.3 Architectural Coatings Phase Emission Factor(s)

- Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO _{2e}
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

9.4.4 Architectural Coatings Phase Formula(s)

- Worker Trips Emissions per Phase

$$VMT_{WT} = (1 * WT * PA) / 800$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 1: Conversion Factor man days to trips (1 trip / 1 man * day)
 WT: Average Worker Round Trip Commute (mile)
 PA: Paint Area (ft²)
 800: Conversion Factor square feet to man days (1 ft² / 1 man * day)

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_{AC} = (AB * 2.0 * 0.0116) / 2000.0$$

VOC_{AC}: Architectural Coating VOC Emissions (TONs)
 BA: Area of Building (ft²)
 2.0: Conversion Factor total area to coated area (2.0 ft² coated area / total area)
 0.0116: Emission Factor (lb/ft²)
 2000: Conversion Factor pounds to tons

10. Construction / Demolition

10.1 General Information & Timeline Assumptions

- Activity Location

County: Brevard
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Vaporization Farm

- Activity Description:

The ASU would be cooled by a typical evaporative cooling tower requiring approximately 75 cubic meters per hour of water and producing approximately 7 cubic meters per hour of wastewater. The ASU would be up to approximately 180 feet tall with supporting infrastructure up to approximately 60 feet tall. An onsite ASU reduces the need to transport nitrogen and oxygen to LC-39A from off-site via trucks.

- Activity Start Date

Start Month: 1
 Start Month: 2026

- Activity End Date

Indefinite: False
 End Month: 3
 End Month: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.182443
SO _x	0.001185
NO _x	0.600762
CO	0.805372

Pollutant	Total Emissions (TONs)
PM 10	0.603639
PM 2.5	0.023460
Pb	0.000000
NH ₃	0.001332

- Activity Emissions of GHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.005319
N ₂ O	0.001886

Pollutant	Total Emissions (TONs)
CO ₂	135.905945
CO ₂ e	136.600829

- Global Scale Activity Emissions for SCGHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.005318

Pollutant	Total Emissions (TONs)
CO ₂	135.889169

N ₂ O	0.001886	CO ₂ e	136.583960
------------------	----------	-------------------	------------

10.1 Site Grading Phase

10.1.1 Site Grading Phase Timeline Assumptions

- Phase Start Date
 Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration
 Number of Month: 3
 Number of Days: 0

10.1.2 Site Grading Phase Assumptions

- General Site Grading Information
 Area of Site to be Graded (ft²): 9686
 Amount of Material to be Hauled On-Site (yd³): 0
 Amount of Material to be Hauled Off-Site (yd³): 0

- Site Grading Default Settings
 Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Graders Composite	1	6
Other Construction Equipment Composite	1	8
Rubber Tired Dozers Composite	1	6
Tractors/Loaders/Backhoes Composite	1	7

- Vehicle Exhaust
 Average Hauling Truck Capacity (yd³): 20 (default)
 Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips
 Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

10.1.3 Site Grading Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Graders Composite [HP: 148] [LF: 0.41]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.31292	0.00490	2.52757	3.39734	0.14041	0.12918

Other Construction Equipment Composite [HP: 82] [LF: 0.42]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.28160	0.00487	2.73375	3.50416	0.15811	0.14546
Rubber Tired Dozers Composite [HP: 367] [LF: 0.4]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.35280	0.00491	3.22260	2.72624	0.14205	0.13069
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gasses Pollutant Emission Factors (g/hp-hour) (default)

Graders Composite [HP: 148] [LF: 0.41]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02153	0.00431	530.81500	532.63663
Other Construction Equipment Composite [HP: 82] [LF: 0.42]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02140	0.00428	527.54121	529.35159
Rubber Tired Dozers Composite [HP: 367] [LF: 0.4]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02160	0.00432	532.54993	534.37751
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96834

10.1.4 Site Grading Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM_{10fd} = (20 * ACRE * WD) / 2000$$

PM_{10fd}: Fugitive Dust PM 10 Emissions (TONs)

20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)

ACRE: Total acres (acres)

WD: Number of Total Work Days (days)

2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)
 NE: Number of Equipment
 WD: Number of Total Work Days (days)
 H: Hours Worked per Day (hours)
 HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL}: Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
 HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
 HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
 HC: Average Hauling Truck Capacity (yd³)
 (1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Vehicle Exhaust On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 WD: Number of Total Work Days (days)
 WT: Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

10.2 Trenching/Excavating Phase**10.2.1 Trenching / Excavating Phase Timeline Assumptions****- Phase Start Date**

Start Month: 1

Start Quarter: 1
Start Year: 2026

- Phase Duration
Number of Month: 3
Number of Days: 0

10.2.2 Trenching / Excavating Phase Assumptions

- General Trenching/Excavating Information
Area of Site to be Trenched/Excavated (ft²): 9686
Amount of Material to be Hauled On-Site (yd³): 0
Amount of Material to be Hauled Off-Site (yd³): 0

- Trenching Default Settings
Default Settings Used: Yes
Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Excavators Composite	2	8
Other General Industrial Equipmen Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust
Average Hauling Truck Capacity (yd³): 20 (default)
Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips
Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

10.2.3 Trenching / Excavating Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.39317	0.00542	3.40690	4.22083	0.09860	0.09071
Other General Industrial Equipmen Composite [HP: 35] [LF: 0.34]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.45335	0.00542	3.58824	4.59368	0.11309	0.10404
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gasses Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]						
--	--	--	--	--	--	--

	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02381	0.00476	587.02896	589.04350
Other General Industrial Equipment Composite [HP: 35] [LF: 0.34]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02385	0.00477	587.87714	589.89459
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

10.2.4 Trenching / Excavating Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)
 20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)
 ACRE: Total acres (acres)
 WD: Number of Total Work Days (days)
 2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)
 NE: Number of Equipment
 WD: Number of Total Work Days (days)
 H: Hours Worked per Day (hours)
 HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL}: Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 HA_{OnSite} : Amount of Material to be Hauled On-Site (yd³)
 $HA_{OffSite}$: Amount of Material to be Hauled Off-Site (yd³)
 HC : Average Hauling Truck Capacity (yd³)
 $(1 / HC)$: Conversion Factor cubic yards to trips (1 trip / HC yd³)
 HT : Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205 : Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Vehicle Exhaust On Road Vehicle Mixture (%)
 2000 : Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 WD : Number of Total Work Days (days)
 WT : Average Worker Round Trip Commute (mile)
 1.25 : Conversion Factor Number of Construction Equipment to Number of Works
 NE : Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VE} : Worker Trips Vehicle Miles Travel (miles)
 0.002205 : Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Worker Trips On Road Vehicle Mixture (%)
 2000 : Conversion Factor pounds to tons

10.3 Building Construction Phase

10.3.1 Building Construction Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration

Number of Month: 3
 Number of Days: 0

10.3.2 Building Construction Phase Assumptions

- General Building Construction Information

Building Category: Commercial or Retail
 Area of Building (ft²): 9686
 Height of Building (ft): 60
 Number of Units: N/A

- Building Construction Default Settings

Default Settings Used: Yes
Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Cranes Composite	1	4
Forklifts Composite	2	6
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDBGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDBGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

- Vendor Trips

Average Vendor Round Trip Commute (mile): 40 (default)

- Vendor Trips Vehicle Mixture (%)

	LDGV	LDGT	HDBGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

10.3.3 Building Construction Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Cranes Composite [HP: 367] [LF: 0.29]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.19758	0.00487	1.83652	1.63713	0.07527	0.06925
Forklifts Composite [HP: 82] [LF: 0.2]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.24594	0.00487	2.34179	3.57902	0.11182	0.10287
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gases Pollutant Emission Factors (g/hp-hour) (default)

Cranes Composite [HP: 367] [LF: 0.29]			
	CH ₄	N ₂ O	CO ₂
Emission Factors	0.02140	0.00428	527.46069
Forklifts Composite [HP: 82] [LF: 0.2]			
	CH ₄	N ₂ O	CO ₂
Emission Factors	0.02138	0.00428	527.09717
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]			
	CH ₄	N ₂ O	CO ₂
Emission Factors	0.02149	0.00430	529.70686

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

10.3.4 Building Construction Phase Formula(s)**- Construction Exhaust Emissions per Phase**

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

HP: Equipment Horsepower

LF: Equipment Load Factor

EF_{POL}: Emission Factor for Pollutant (g/hp-hour)

0.002205: Conversion Factor grams to pounds

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = BA * BH * (0.32 / 1000) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

BA: Area of Building (ft²)

BH: Height of Building (ft)

(0.32 / 1000): Conversion Factor ft³ to trips (0.32 trip / 1000 ft³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 WD: Number of Total Work Days (days)
 WT: Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Vender Trips Emissions per Phase

$$VMT_{VT} = BA * BH * (0.05 / 1000) * HT$$

VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
 BA: Area of Building (ft²)
 BH: Height of Building (ft)
 (0.05 / 1000): Conversion Factor ft³ to trips (0.05 trip / 1000 ft³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

10.4 Architectural Coatings Phase

10.4.1 Architectural Coatings Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration

Number of Month: 3
 Number of Days: 0

10.4.2 Architectural Coatings Phase Assumptions

- General Architectural Coatings Information

Building Category: Non-Residential
 Total Square Footage (ft²): 9686
 Number of Units: N/A

- Architectural Coatings Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Worker Trips
 Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

10.4.3 Architectural Coatings Phase Emission Factor(s)

- Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

10.4.4 Architectural Coatings Phase Formula(s)

- Worker Trips Emissions per Phase

$$VMT_{WT} = (1 * WT * PA) / 800$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 1: Conversion Factor man days to trips (1 trip / 1 man * day)
 WT: Average Worker Round Trip Commute (mile)
 PA: Paint Area (ft²)
 800: Conversion Factor square feet to man days (1 ft² / 1 man * day)

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_{AC} = (AB * 2.0 * 0.0116) / 2000.0$$

VOC_{AC}: Architectural Coating VOC Emissions (TONs)
 BA: Area of Building (ft²)
 2.0: Conversion Factor total area to coated area (2.0 ft² coated area / total area)
 0.0116: Emission Factor (lb/ft²)
 2000: Conversion Factor pounds to tons

A.1.1.1

AIR CONFORMITY APPLICABILITY MODEL REPORT GREENHOUSE GAS (GHG) EMISSIONS

1. General Information: The Air Force's Air Conformity Applicability Model (ACAM) was used to perform an analysis to estimate GHG emissions and assess the theoretical Social Cost of Greenhouse Gases (SC GHG) associated with the action. The analysis was performed in accordance with the Air Force Manual 32-7002, Environmental Compliance and Pollution Prevention; the Environmental Impact Analysis Process (EIAP, 32 CFR 989); and the USAF Air Quality Environmental Impact Analysis Process (EIAP) Guide. This report provides a summary of GHG emissions and SC GHG analysis.

Report generated with ACAM version: 5.0.23a

a. Action Location:

Base: CAPE CANAVERAL AFS
State: Florida
County(s): Brevard
Regulatory Area(s): NOT IN A REGULATORY AREA

b. Action Title: SpaceX Starship-Heavy Launch Vehicle at Launch Complex 39A at the Kennedy Space Center, Cape Canaveral, Florida

c. Project Number/s (if applicable): N/A

d. Projected Action Start Date: 1 / 2026

e. Action Description:

SpaceX's proposed operations include construction of a SpaceX starship-super heavy launch/landing pad and other launch support infrastructure at LC-39A, launches at LC-39A, landings at LC-39A, and landings in the ocean.

f. Point of Contact:

Name: Allison Williams
Title: Environmental Scientist
Organization: Leidos Corporation
Email: allison.williams@leidos.com
Phone Number: 719-470-9579

2. Analysis: Total combined direct and indirect GHG emissions associated with the action were estimated through ACAM on a calendar-year basis from the action start through the expected life cycle of the action. The life cycle for Air Force actions with "steady state" emissions (SS, net gain/loss in emission stabilized and the action is fully implemented) is assumed to be 10 years beyond the SS emissions year or 20 years beyond SS emissions year for aircraft operations related actions.

GHG Emissions Analysis Summary:

GHGs produced by fossil-fuel combustion are primarily carbon dioxide (CO₂), methane (CH₄), and nitrous oxide (NO₂). These three GHGs represent more than 97 percent of all U.S. GHG emissions. Emissions of GHGs are typically quantified and regulated in units of CO₂ equivalents (CO₂e). The CO₂e takes into account the global warming potential (GWP) of each GHG. The GWP is the measure of a particular GHG's ability to absorb solar radiation as well as its residence time within the atmosphere. The GWP allows comparison of global warming impacts between different gases; the higher the GWP, the more that gas contributes to climate change in comparison to CO₂. All GHG emissions estimates were derived from various emission sources using the methods, algorithms, emission factors, and GWPs from the most current Air Emissions Guide for Air Force Stationary Sources, Air Emissions Guide for Air Force Mobile Sources, and/or Air Emissions Guide for Air Force Transitory Sources.

The Air Force has adopted the Prevention of Significant Deterioration (PSD) threshold for GHG of 75,000 ton per year (ton/yr) of CO₂e (or 68,039 metric ton per year, mton/yr) as an indicator or "threshold of insignificance" for NEPA air quality impacts in all areas. This indicator does not define a significant impact; however, it provides a threshold to identify actions that are insignificant (de minimis, too trivial or minor to merit consideration). Actions with a net change in GHG (CO₂e) emissions below the insignificance indicator (threshold) are considered too insignificant on a global scale to warrant any further analysis. Note that actions with a net change in GHG (CO₂e) emissions above the insignificance indicator (threshold) are only considered potentially significant and require further assessment to determine if the action poses a significant impact. For further detail on insignificance indicators see Level II, Air Quality Quantitative Assessment, Insignificance Indicators (April 2023).

The following table summarizes the action-related GHG emissions on a calendar-year basis through the projected life cycle of the action.

Action-Related Annual GHG Emissions (mton/yr)						
YEAR	CO ₂	CH ₄	N ₂ O	CO ₂ e	Threshold	Exceedance
2026	1,896	0.05516654	0.11989608	1,933	68,039	No
2027 [SS Year]	0	0	0	0	68,039	No

The following U.S. and State's GHG emissions estimates (next two tables) are based on a five-year average (2016 through 2020) of individual state-reported GHG emissions (Reference: State Climate Summaries 2022, NOAA National Centers for Environmental Information, National Oceanic and Atmospheric Administration. <https://statesummaries.noaa.gov/downloads/>).

State's Annual GHG Emissions (mton/yr)				
YEAR	CO ₂	CH ₄	N ₂ O	CO ₂ e
2026	227,404,647	552,428	58,049	228,015,124
2027 [SS Year]	0	0	0	0

U.S. Annual GHG Emissions (mton/yr)				
YEAR	CO ₂	CH ₄	N ₂ O	CO ₂ e
2026	5,136,454,179	25,626,912	1,500,708	5,163,581,798
2027 [SS Year]	0	0	0	0

GHG Relative Significance Assessment:

A Relative Significance Assessment uses the rule of reason and the concept of proportionality along with the consideration of the affected area (yGba.e., global, national, and regional) and the degree (intensity) of the proposed action's effects. The Relative Significance Assessment provides real-world context and allows for a reasoned choice against alternatives through a relative comparison analysis. The analysis weighs each alternative's annual net change in GHG emissions proportionally against (or relative to) global, national, and regional emissions.

The action's surroundings, circumstances, environment, and background (context associated with an action) provide the setting for evaluating the GHG intensity (impact significance). From an air quality perspective, context of an action is the local area's ambient air quality relative to meeting the NAAQSs, expressed as attainment, nonattainment, or maintenance areas (this designation is considered the attainment status). GHGs are non-hazardous

to health at normal ambient concentrations and, at a cumulative global scale, action-related GHG emissions can only potentially cause warming of the climatic system. Therefore, the action-related GHGs generally have an insignificant impact to local air quality.

However, the affected area (context) of GHG/climate change is global. Therefore, the intensity or degree of the proposed action's GHG/climate change effects are gauged through the quantity of GHG associated with the action as compared to a baseline of the state, U.S., and global GHG inventories. Each action (or alternative) has significance, based on their annual net change in GHG emissions, in relation to or proportionally to the global, national, and regional annual GHG emissions.

To provide real-world context to the GHG and climate change effects on a global scale, an action's net change in GHG emissions is compared relative to the state (where action will occur) and U.S. annual emissions. The following table provides a relative comparison of an action's net change in GHG emissions vs. state and U.S. projected GHG emissions for the same time period.

Total GHG Relative Significance (mton)					
		CO2	CH4	N2O	CO2e
2026-2037	State Total	227,404,647	552,428	58,049	228,015,124
2026-2037	U.S. Total	5,136,454,179	25,626,912	1,500,708	5,163,581,798
2026-2037	Action	1,896	0.055167	0.119896	1,933
Percent of State Totals		0.00083363%	0.00000999%	0.00020654%	0.00084767%
Percent of U.S. Totals		0.00003691%	0.00000022%	0.00000799%	0.00003743%

From a global context, the action's total GHG percentage of total global GHG for the same time period is: 0.00000502%.*

* Global value based on the U.S. emits 13.4% of all global GHG annual emissions (2018 Emissions Data, Center for Climate and Energy Solutions, accessed 7-6-2023, <https://www.c2es.org/content/international-emissions>).

Climate Change Assessment (as SC GHG):

On a global scale, the potential climate change effects of an action are indirectly addressed and put into context through providing the theoretical SC GHG associated with an action. The SC GHG is an administrative and theoretical tool intended to provide additional context to a GHG's potential impacts through approximating the long-term monetary damage that may result from GHG emissions affect on climate change. It is important to note that the SC GHG is a monetary quantification, in 2020 U.S. dollars, of the theoretical economic damages that could result from emitting GHGs into the atmosphere.

The SC GHG estimates are derived using the methodology and discount factors in the "Technical Support Document: Social Cost of Carbon, Methane, and Nitrous Oxide Interim Estimates under Executive Order 13990," released by the Interagency Working Group on Social Cost of Greenhouse Gases (IWG SC GHGs) in February 2021.

The speciated IWG Annual SC GHG Emission associated with an action (or alternative) are first estimated as annual unit cost (cost per metric ton, \$/mton). Results of the annual IWG Annual SC GHG Emission Assessments are tabulated in the IWG Annual SC GHG Cost per Metric Ton Table below:

IWG SC GHG Discount Factor: 2.5%

IWG Annual SC GHG Cost per Metric Ton (\$/mton [In 2020 \$])			
YEAR	CO2	CH4	N2O
2026	\$84.00	\$2,300.00	\$30,000.00
2027 [SS Year]	\$86.00	\$2,300.00	\$31,000.00

Action-related SC GHG were estimated by calendar-year for the projected action's lifecycle. Annual estimates were found by multiplying the annual emission for a given year by the corresponding IWG Annual SC GHG Emission value (see table above).

Action-Related Annual SC GHG (\$K/yr [In 2020 \$])				
YEAR	CO2	CH4	N2O	GHG
2026	\$159.24	\$0.13	\$3.60	\$162.96
2027 [SS Year]	\$0.00	\$0.00	\$0.00	\$0.00

The following two tables summarize the U.S. and State's Annual SC GHG by calendar-year. The U.S. and State's Annual SC GHG are in 2020 dollars and were estimated by each year for the projected action lifecycle. Annual SC GHG estimates were found by multiplying the U.S. and State's annual five-year average GHG emissions for a given year by the corresponding IWG Annual SC GHG Cost per Metric Ton value.

State's Annual SC GHG (\$K/yr [In 2020 \$])				
YEAR	CO2	CH4	N2O	GHG
2026	\$19,101,990.35	\$1,270,583.74	\$1,741,465.95	\$22,114,040.04
2027 [SS Year]	\$0.00	\$0.00	\$0.00	\$0.00

U.S. Annual SC GHG (\$K/yr [In 2020 \$])				
YEAR	CO2	CH4	N2O	GHG
2026	\$431,462,151.04	\$58,941,896.86	\$45,021,229.08	\$535,425,276.98
2027 [SS Year]	\$0.00	\$0.00	\$0.00	\$0.00

Relative Comparison of SC GHG:

To provide additional real-world context to the potential climate change impact associated with an action, a Relative Comparison of SC GHG Assessment is also performed. While the SC GHG estimates capture an indirect approximation of global climate damages, the Relative Comparison of SC GHG Assessment provides a better perspective from a regional and global scale.

The Relative Comparison of SC GHG Assessment uses the rule of reason and the concept of proportionality along with the consideration of the affected area (yGba.e., global, national, and regional) and the SC GHG as the degree (intensity) of the proposed action's effects. The Relative Comparison Assessment provides real-world context and allows for a reasoned choice among alternatives through a relative contrast analysis which weighs each alternative's SC GHG proportionally against (or relative to) existing global, national, and regional SC GHG. The below table provides a relative comparison between an action's SC GHG vs. state and U.S. projected SC GHG for the same time period.

Total SC-GHG (\$K [In 2020 \$])					
		CO2	CH4	N2O	GHG
2026-2037	State Total	\$19,101,990.35	\$1,270,583.74	\$1,741,465.95	\$22,114,040.04
2026-2037	U.S. Total	\$431,462,151.04	\$58,941,896.86	\$45,021,229.08	\$535,425,276.98
2026-2037	Action	\$159.24	\$0.13	\$3.60	\$162.96
Percent of State Totals		0.00083363%	0.00000999%	0.00020654%	0.00073692%
Percent of U.S. Totals		0.00003691%	0.00000022%	0.00000799%	0.00003044%

From a global context, the action's total SC GHG percentage of total global SC GHG for the same time period is: 0.00000408%.*

* Global value based on the U.S. emits 13.4% of all global GHG annual emissions (2018 Emissions Data, Center for Climate and Energy Solutions, accessed 7-6-2023, <https://www.c2es.org/content/international-emissions>).

Allison Williams, Environmental Scientist
Name, Title

Jul 26 2024
Date

A.1.2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1. General Information

- Action Location

Base: CAPE CANAVERAL AFS
State: Florida
County(s): Brevard
Regulatory Area(s): NOT IN A REGULATORY AREA

- Action Title: SpaceX Starship-Heavy Launch Vehicle at Launch Complex 39A at the Kennedy Space Center, Cape Canaveral, Florida

- Project Number/s (if applicable): N/A

- Projected Action Start Date: 1 / 2026

- Action Purpose and Need:

To increase operational efficiency, capabilities, and cost effectiveness of the Starship-Super Heavy program.

- Action Description:

SpaceX's proposed operations include construction of a SpaceX starship-super heavy launch/landing pad and other launch support infrastructure at LC-39A, launches at LC-39A, landings at LC-39A, and landings in the ocean.

- Point of Contact

Name: Allison Williams
Title: Environmental Scientist
Organization: Leidos Corporation
Email: allison.williams@leidos.com
Phone Number: 719-470-9579

Report generated with ACAM version: 5.0.23a

- Activity List:

Activity Type		Activity Title
2.	Construction / Demolition	Super Heavy Catch Tower
3.	Construction / Demolition	Air Separation Unit
4.	Construction / Demolition	Stormwater/Deluge Ponds
5.	Construction / Demolition	Methane Liquefier

Emission factors and air emission estimating methods come from the United States Air Force's Air Emissions Guide for Air Force Stationary Sources, Air Emissions Guide for Air Force Mobile Sources, and Air Emissions Guide for Air Force Transitory Sources.

2. Construction / Demolition

2.1 General Information & Timeline Assumptions

- Activity Location

County: Brevard

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Super Heavy Catch Tower

- Activity Description:

SpaceX would construct an additional tower within the LC-39A fence line to support landing operations. While the integration tower used for launch could support Super Heavy landings, an additional landing tower would reduce launch pad refurbishment needed between each launch, providing a shorter turnaround period between launches and increase the efficiency of launch operations. The catch tower would be approximately 480 feet tall and be similar in appearance to the existing integration tower.

- Activity Start Date

Start Month: 1

Start Month: 2026

- Activity End Date

Indefinite: False

End Month: 3

End Month: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.135746
SO _x	0.001353
NO _x	0.694364
CO	0.869198

Pollutant	Total Emissions (TONs)
PM 10	0.342790
PM 2.5	0.025205
Pb	0.000000
NH ₃	0.003958

- Activity Emissions of GHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.006097
N ₂ O	0.008361

Pollutant	Total Emissions (TONs)
CO ₂	185.812364
CO ₂ e	188.455647

- Global Scale Activity Emissions for SCGHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.006097
N ₂ O	0.008361

Pollutant	Total Emissions (TONs)
CO ₂	185.801181
CO ₂ e	188.444400

2.1 Site Grading Phase

2.1.1 Site Grading Phase Timeline Assumptions

- Phase Start Date

Start Month: 1

Start Quarter: 1

Start Year: 2026

- Phase Duration

Number of Month: 3

Number of Days: 0

2.1.2 Site Grading Phase Assumptions

- General Site Grading Information

Area of Site to be Graded (ft²): 5284
 Amount of Material to be Hauled On-Site (yd³): 0
 Amount of Material to be Hauled Off-Site (yd³): 0

- Site Grading Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Graders Composite	1	6
Other Construction Equipment Composite	1	8
Rubber Tired Dozers Composite	1	6
Tractors/Loaders/Backhoes Composite	1	7

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)
 Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

2.1.3 Site Grading Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Graders Composite [HP: 148] [LF: 0.41]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.31292	0.00490	2.52757	3.39734	0.14041	0.12918
Other Construction Equipment Composite [HP: 82] [LF: 0.42]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.28160	0.00487	2.73375	3.50416	0.15811	0.14546
Rubber Tired Dozers Composite [HP: 367] [LF: 0.4]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.35280	0.00491	3.22260	2.72624	0.14205	0.13069
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gases Pollutant Emission Factors (g/hp-hour) (default)

Graders Composite [HP: 148] [LF: 0.41]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02153	0.00431	530.81500	532.63663

Other Construction Equipment Composite [HP: 82] [LF: 0.42]				
	CH₄	N₂O	CO₂	CO₂e
Emission Factors	0.02140	0.00428	527.54121	529.35159
Rubber Tired Dozers Composite [HP: 367] [LF: 0.4]				
	CH₄	N₂O	CO₂	CO₂e
Emission Factors	0.02160	0.00432	532.54993	534.37751
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH₄	N₂O	CO₂	CO₂e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO_x	NO_x	CO	PM 10	PM 2.5	NH₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH₄	N₂O	CO₂	CO₂e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

2.1.4 Site Grading Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)
 20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)
 ACRE: Total acres (acres)
 WD: Number of Total Work Days (days)
 2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)
 NE: Number of Equipment
 WD: Number of Total Work Days (days)
 H: Hours Worked per Day (hours)
 HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL}: Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 HA_{OnSite} : Amount of Material to be Hauled On-Site (yd³)
 $HA_{OffSite}$: Amount of Material to be Hauled Off-Site (yd³)
 HC : Average Hauling Truck Capacity (yd³)
 $(1 / HC)$: Conversion Factor cubic yards to trips (1 trip / HC yd³)
 HT : Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Vehicle Exhaust On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 WD : Number of Total Work Days (days)
 WT : Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE : Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

2.2 Trenching/Excavating Phase

2.2.1 Trenching / Excavating Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration

Number of Month: 3
 Number of Days: 0

2.2.2 Trenching / Excavating Phase Assumptions

- General Trenching/Excavating Information

Area of Site to be Trenched/Excavated (ft²): 5284
 Amount of Material to be Hauled On-Site (yd³): 0
 Amount of Material to be Hauled Off-Site (yd³): 0

- Trenching Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Excavators Composite	2	8
Other General Industrial Equipmen Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)
 Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LBDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LBDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

2.2.3 Trenching / Excavating Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.39317	0.00542	3.40690	4.22083	0.09860	0.09071
Other General Industrial Equipmen Composite [HP: 35] [LF: 0.34]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.45335	0.00542	3.58824	4.59368	0.11309	0.10404
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gasses Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02381	0.00476	587.02896	589.04350
Other General Industrial Equipmen Composite [HP: 35] [LF: 0.34]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02385	0.00477	587.87714	589.89459
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480

LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

2.2.4 Trenching / Excavating Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)
 20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)
 ACRE: Total acres (acres)
 WD: Number of Total Work Days (days)
 2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)
 NE: Number of Equipment
 WD: Number of Total Work Days (days)
 H: Hours Worked per Day (hours)
 HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL}: Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
 HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
 HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
 HC: Average Hauling Truck Capacity (yd³)
 (1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Vehicle Exhaust On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 WD: Number of Total Work Days (days)
 WT: Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{VE}: Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

2.3 Building Construction Phase

2.3.1 Building Construction Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration

Number of Month: 3
 Number of Days: 0

2.3.2 Building Construction Phase Assumptions

- General Building Construction Information

Building Category: Office or Industrial
 Area of Building (ft²): 5284
 Height of Building (ft): 480
 Number of Units: N/A

- Building Construction Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Cranes Composite	1	4
Forklifts Composite	2	6
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

- Vendor Trips

Average Vendor Round Trip Commute (mile): 40 (default)

- Vendor Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

2.3.3 Building Construction Phase Emission Factor(s)**- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)**

Cranes Composite [HP: 367] [LF: 0.29]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.19758	0.00487	1.83652	1.63713	0.07527	0.06925
Forklifts Composite [HP: 82] [LF: 0.2]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.24594	0.00487	2.34179	3.57902	0.11182	0.10287
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gasses Pollutant Emission Factors (g/hp-hour) (default)

Cranes Composite [HP: 367] [LF: 0.29]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02140	0.00428	527.46069	529.27080
Forklifts Composite [HP: 82] [LF: 0.2]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02138	0.00428	527.09717	528.90603
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
--	-----------------	------------------	-----------------	-------------------

LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

2.3.4 Building Construction Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL} : Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

HP: Equipment Horsepower

LF: Equipment Load Factor

EF_{POL} : Emission Factor for Pollutant (g/hp-hour)

0.002205: Conversion Factor grams to pounds

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = BA * BH * (0.42 / 1000) * HT$$

VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)

BA: Area of Building (ft²)

BH: Height of Building (ft)

(0.42 / 1000): Conversion Factor ft³ to trips (0.42 trip / 1000 ft³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)

VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL} : Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

1.25: Conversion Factor Number of Construction Equipment to Number of Works

NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL} : Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Vender Trips Emissions per Phase

$$VMT_{VT} = BA * BH * (0.38 / 1000) * HT$$

VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
 BA: Area of Building (ft²)
 BH: Height of Building (ft)
 (0.38 / 1000): Conversion Factor ft³ to trips (0.38 trip / 1000 ft³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

2.4 Architectural Coatings Phase

2.4.1 Architectural Coatings Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration

Number of Month: 3
 Number of Days: 0

2.4.2 Architectural Coatings Phase Assumptions

- General Architectural Coatings Information

Building Category: Non-Residential
 Total Square Footage (ft²): 5284
 Number of Units: N/A

- Architectural Coatings Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

2.4.3 Architectural Coatings Phase Emission Factor(s)

- Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

2.4.4 Architectural Coatings Phase Formula(s)

- Worker Trips Emissions per Phase

$$VMT_{WT} = (1 * WT * PA) / 800$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

1: Conversion Factor man days to trips (1 trip / 1 man * day)

WT: Average Worker Round Trip Commute (mile)

PA: Paint Area (ft²)

800: Conversion Factor square feet to man days (1 ft² / 1 man * day)

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_{AC} = (BA * 2.0 * 0.0116) / 2000.0$$

VOC_{AC}: Architectural Coating VOC Emissions (TONs)

BA: Area of Building (ft²)

2.0: Conversion Factor total area to coated area (2.0 ft² coated area / total area)

0.0116: Emission Factor (lb/ft²)

2000: Conversion Factor pounds to tons

3. Construction / Demolition

3.1 General Information & Timeline Assumptions

- Activity Location

County: Brevard

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Air Separation Unit

- Activity Description:

SpaceX proposes to construct an air separation unit (ASU) within the LC-39A fence line to generate liquid nitrogen and liquid oxygen to support launch activities.

- Activity Start Date

Start Month: 1

Start Month: 2026

- Activity End Date

Indefinite: False

End Month: 3

End Month: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	2.557821
SO _x	0.004516
NO _x	2.414730
CO	2.220838

Pollutant	Total Emissions (TONs)
PM 10	12.308043
PM 2.5	0.061614
Pb	0.000000
NH ₃	0.044231

- Activity Emissions of GHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.020291
N ₂ O	0.107033

Pollutant	Total Emissions (TONs)
CO ₂	1001.867488
CO ₂ e	1034.263027

- Global Scale Activity Emissions for SCGHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.020290
N ₂ O	0.107032

Pollutant	Total Emissions (TONs)
CO ₂	1001.853508
CO ₂ e	1034.248969

3.1 Site Grading Phase

3.1.1 Site Grading Phase Timeline Assumptions

- Phase Start Date

Start Month: 1

Start Quarter: 1

Start Year: 2026

- Phase Duration

Number of Month: 3

Number of Days: 0

3.1.2 Site Grading Phase Assumptions

- General Site Grading Information

Area of Site to be Graded (ft²): 205085

Amount of Material to be Hauled On-Site (yd³): 0

Amount of Material to be Hauled Off-Site (yd³): 0

- Site Grading Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Graders Composite	1	8
Other Construction Equipment Composite	1	8
Rubber Tired Dozers Composite	1	8
Tractors/Loaders/Backhoes Composite	2	7

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)
 Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

3.1.3 Site Grading Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Graders Composite [HP: 148] [LF: 0.41]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.31292	0.00490	2.52757	3.39734	0.14041	0.12918
Other Construction Equipment Composite [HP: 82] [LF: 0.42]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.28160	0.00487	2.73375	3.50416	0.15811	0.14546
Rubber Tired Dozers Composite [HP: 367] [LF: 0.4]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.35280	0.00491	3.22260	2.72624	0.14205	0.13069
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gases Pollutant Emission Factors (g/hp-hour) (default)

Graders Composite [HP: 148] [LF: 0.41]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02153	0.00431	530.81500	532.63663
Other Construction Equipment Composite [HP: 82] [LF: 0.42]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02140	0.00428	527.54121	529.35159
Rubber Tired Dozers Composite [HP: 367] [LF: 0.4]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02160	0.00432	532.54993	534.37751
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

3.1.4 Site Grading Phase Formula(s)**- Fugitive Dust Emissions per Phase**

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)
 20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)
 ACRE: Total acres (acres)
 WD: Number of Total Work Days (days)
 2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)
 NE: Number of Equipment
 WD: Number of Total Work Days (days)
 H: Hours Worked per Day (hours)
 HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL}: Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle-Exhaust Vehicle Miles Travel (miles)
 HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
 HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
 HC: Average Hauling Truck Capacity (yd³)
 (1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Vehicle Exhaust On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 WD : Number of Total Work Days (days)
 WT : Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE : Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

3.2 Trenching/Excavating Phase

3.2.1 Trenching / Excavating Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration

Number of Month: 3
 Number of Days: 0

3.2.2 Trenching / Excavating Phase Assumptions

- General Trenching/Excavating Information

Area of Site to be Trenched/Excavated (ft²): 205085
 Amount of Material to be Hauled On-Site (yd³): 0
 Amount of Material to be Hauled Off-Site (yd³): 0

- Trenching Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Excavators Composite	2	8

Other General Industrial Equipmen Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

3.2.3 Trenching / Excavating Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.39317	0.00542	3.40690	4.22083	0.09860	0.09071
Other General Industrial Equipmen Composite [HP: 35] [LF: 0.34]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.45335	0.00542	3.58824	4.59368	0.11309	0.10404
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gasses Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02381	0.00476	587.02896	589.04350
Other General Industrial Equipmen Composite [HP: 35] [LF: 0.34]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02385	0.00477	587.87714	589.89459
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490

LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

3.2.4 Trenching / Excavating Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM_{10FD} = (20 * ACRE * WD) / 2000$$

PM_{10FD} : Fugitive Dust PM 10 Emissions (TONs)
 20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)
 ACRE: Total acres (acres)
 WD: Number of Total Work Days (days)
 2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL} : Construction Exhaust Emissions (TONs)
 NE: Number of Equipment
 WD: Number of Total Work Days (days)
 H: Hours Worked per Day (hours)
 HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL} : Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 HA_{OnSite} : Amount of Material to be Hauled On-Site (yd³)
 $HA_{OffSite}$: Amount of Material to be Hauled Off-Site (yd³)
 HC: Average Hauling Truck Capacity (yd³)
 (1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM: Vehicle Exhaust On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 WD: Number of Total Work Days (days)
 WT: Average Worker Round Trip Commute (mile)

1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

3.3 Building Construction Phase

3.3.1 Building Construction Phase Timeline Assumptions

- Phase Start Date
 Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration
 Number of Month: 3
 Number of Days: 0

3.3.2 Building Construction Phase Assumptions

- General Building Construction Information
 Building Category: Office or Industrial
 Area of Building (ft²): 205085
 Height of Building (ft): 180
 Number of Units: N/A

- Building Construction Default Settings
 Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Cranes Composite	1	6
Forklifts Composite	2	6
Generator Sets Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8
Welders Composite	3	8

- Vehicle Exhaust
 Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips
 Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

- Vendor Trips

Average Vendor Round Trip Commute (mile): 40 (default)

- Vendor Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

3.3.3 Building Construction Phase Emission Factor(s)**- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)**

Cranes Composite [HP: 367] [LF: 0.29]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.19758	0.00487	1.83652	1.63713	0.07527	0.06925
Forklifts Composite [HP: 82] [LF: 0.2]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.24594	0.00487	2.34179	3.57902	0.11182	0.10287
Generator Sets Composite [HP: 14] [LF: 0.74]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.53947	0.00793	4.32399	2.85973	0.17412	0.16019
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839
Welders Composite [HP: 46] [LF: 0.45]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.46472	0.00735	3.57020	4.49314	0.09550	0.08786

- Construction Exhaust Greenhouse Gases Pollutant Emission Factors (g/hp-hour) (default)

Cranes Composite [HP: 367] [LF: 0.29]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02140	0.00428	527.46069	529.27080
Forklifts Composite [HP: 82] [LF: 0.2]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02138	0.00428	527.09717	528.90603
Generator Sets Composite [HP: 14] [LF: 0.74]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02305	0.00461	568.32694	570.27730
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468
Welders Composite [HP: 46] [LF: 0.45]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02305	0.00461	568.29068	570.24091

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751

HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

3.3.4 Building Construction Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

HP: Equipment Horsepower

LF: Equipment Load Factor

EF_{POL}: Emission Factor for Pollutant (g/hp-hour)

0.002205: Conversion Factor grams to pounds

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = BA * BH * (0.42 / 1000) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

BA: Area of Building (ft²)

BH: Height of Building (ft)

(0.42 / 1000): Conversion Factor ft³ to trips (0.42 trip / 1000 ft³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

1.25: Conversion Factor Number of Construction Equipment to Number of Works

NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Vender Trips Emissions per Phase

$$VMT_{VT} = BA * BH * (0.38 / 1000) * HT$$

VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
 BA : Area of Building (ft²)
 BH : Height of Building (ft)
 (0.38 / 1000): Conversion Factor ft³ to trips (0.38 trip / 1000 ft³)
 HT : Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

3.4 Architectural Coatings Phase

3.4.1 Architectural Coatings Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration

Number of Month: 3
 Number of Days: 0

3.4.2 Architectural Coatings Phase Assumptions

- General Architectural Coatings Information

Building Category: Non-Residential
 Total Square Footage (ft²): 205085
 Number of Units: N/A

- Architectural Coatings Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
--	------	------	------	------	------	------	----

POVs	50.00	50.00	0	0	0	0	0
------	-------	-------	---	---	---	---	---

3.4.3 Architectural Coatings Phase Emission Factor(s)

- Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

3.4.4 Architectural Coatings Phase Formula(s)

- Worker Trips Emissions per Phase

$$VMT_{WT} = (I * WT * PA) / 800$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 I : Conversion Factor man days to trips (1 trip / 1 man * day)
 WT : Average Worker Round Trip Commute (mile)
 PA : Paint Area (ft²)
 800 : Conversion Factor square feet to man days (1 ft² / 1 man * day)

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 0.002205 : Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Worker Trips On Road Vehicle Mixture (%)
 2000 : Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_{AC} = (AB * 2.0 * 0.0116) / 2000.0$$

VOC_{AC} : Architectural Coating VOC Emissions (TONs)
 AB : Area of Building (ft²)
 2.0 : Conversion Factor total area to coated area (2.0 ft² coated area / total area)
 0.0116 : Emission Factor (lb/ft²)
 2000 : Conversion Factor pounds to tons

4. Construction / Demolition

4.1 General Information & Timeline Assumptions

- Activity Location

County: Brevard

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Stormwater/Deluge Ponds

- Activity Description:

SpaceX proposes to construct additional stormwater/deluge ponds, if needed, to manage water associated with deluge and stormwater within LC-39A

- Activity Start Date

Start Month: 1

Start Month: 2026

- Activity End Date

Indefinite: False

End Month: 1

End Month: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.004092
SO _x	0.000121
NO _x	0.066187
CO	0.057681

Pollutant	Total Emissions (TONs)
PM 10	0.412026
PM 2.5	0.001355
Pb	0.000000
NH ₃	0.001549

- Activity Emissions of GHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.000560
N ₂ O	0.003748

Pollutant	Total Emissions (TONs)
CO ₂	31.498878
CO ₂ e	32.629627

- Global Scale Activity Emissions for SCGHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.000560
N ₂ O	0.003748

Pollutant	Total Emissions (TONs)
CO ₂	31.498878
CO ₂ e	32.629627

4.1 Trenching/Excavating Phase

4.1.1 Trenching / Excavating Phase Timeline Assumptions

- Phase Start Date

Start Month: 1

Start Quarter: 1

Start Year: 2026

- Phase Duration

Number of Month: 0

Number of Days: 10

4.1.2 Trenching / Excavating Phase Assumptions

- General Trenching/Excavating Information

Area of Site to be Trenched/Excavated (ft²): 125186
 Amount of Material to be Hauled On-Site (yd³): 0
 Amount of Material to be Hauled Off-Site (yd³): 20864

- Trenching Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Excavators Composite	2	8
Other General Industrial Equipmen Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)
 Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

4.1.3 Trenching / Excavating Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.39317	0.00542	3.40690	4.22083	0.09860	0.09071
Other General Industrial Equipmen Composite [HP: 35] [LF: 0.34]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.45335	0.00542	3.58824	4.59368	0.11309	0.10404
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gasses Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02381	0.00476	587.02896	589.04350
Other General Industrial Equipmen Composite [HP: 35] [LF: 0.34]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02385	0.00477	587.87714	589.89459
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

4.1.4 Trenching / Excavating Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM_{10FD} = (20 * ACRE * WD) / 2000$$

PM_{10FD}: Fugitive Dust PM 10 Emissions (TONs)
 20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)
 ACRE: Total acres (acres)
 WD: Number of Total Work Days (days)
 2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)
 NE: Number of Equipment
 WD: Number of Total Work Days (days)
 H: Hours Worked per Day (hours)
 HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL}: Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
 HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
 HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
 HC: Average Hauling Truck Capacity (yd³)
 (1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Vehicle Exhaust On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 WD : Number of Total Work Days (days)
 WT : Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE : Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VE} : Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM : Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

5. Construction / Demolition

5.1 General Information & Timeline Assumptions

- Activity Location

County: Brevard
Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Methane Liquefier

- Activity Description:

As part of the liquefaction process, SpaceX proposes to construct a methane liquefier to supercool pretreated natural gas into a liquid state for storage and transportation to the launch vehicle. The natural gas pretreatment and liquefier together would be up to three acres in area and comprised of several structures each up to 65 feet tall.

- Activity Start Date

Start Month: 1
Start Month: 2026

- Activity End Date

Indefinite: False
End Month: 3
End Month: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.649986
SO ₂	0.001791

Pollutant	Total Emissions (TONs)
PM 10	2.862310
PM 2.5	0.030786

NO _x	0.898651
CO	1.119628

Pb	0.000000
NH ₃	0.004958

- Activity Emissions of GHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.007672
N ₂ O	0.010219

Pollutant	Total Emissions (TONs)
CO ₂	232.427126
CO ₂ e	235.663415

- Global Scale Activity Emissions for SCGHG:

Pollutant	Total Emissions (TONs)
CH ₄	0.007669
N ₂ O	0.010218

Pollutant	Total Emissions (TONs)
CO ₂	232.332063
CO ₂ e	235.567820

5.1 Site Grading Phase

5.1.1 Site Grading Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
Start Quarter: 1
Start Year: 2026

- Phase Duration

Number of Month: 3
Number of Days: 0

5.1.2 Site Grading Phase Assumptions

- General Site Grading Information

Area of Site to be Graded (ft²): 47394
Amount of Material to be Hauled On-Site (yd³): 0
Amount of Material to be Hauled Off-Site (yd³): 0

- Site Grading Default Settings

Default Settings Used: Yes
Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Graders Composite	1	6
Other Construction Equipment Composite	1	8
Rubber Tired Dozers Composite	1	6
Tractors/Loaders/Backhoes Composite	1	7

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)
Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

5.1.3 Site Grading Phase Emission Factor(s)**- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)**

Graders Composite [HP: 148] [LF: 0.41]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.31292	0.00490	2.52757	3.39734	0.14041	0.12918
Other Construction Equipment Composite [HP: 82] [LF: 0.42]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.28160	0.00487	2.73375	3.50416	0.15811	0.14546
Rubber Tired Dozers Composite [HP: 367] [LF: 0.4]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.35280	0.00491	3.22260	2.72624	0.14205	0.13069
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gasses Pollutant Emission Factors (g/hp-hour) (default)

Graders Composite [HP: 148] [LF: 0.41]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02153	0.00431	530.81500	532.63663
Other Construction Equipment Composite [HP: 82] [LF: 0.42]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02140	0.00428	527.54121	529.35159
Rubber Tired Dozers Composite [HP: 367] [LF: 0.4]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02160	0.00432	532.54993	534.37751
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

5.1.4 Site Grading Phase Formula(s)**- Fugitive Dust Emissions per Phase**

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)
 20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)
 ACRE: Total acres (acres)
 WD: Number of Total Work Days (days)
 2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)
 NE: Number of Equipment
 WD: Number of Total Work Days (days)
 H: Hours Worked per Day (hours)
 HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL}: Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
 HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
 HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
 HC: Average Hauling Truck Capacity (yd³)
 (1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Vehicle Exhaust On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 WD: Number of Total Work Days (days)
 WT: Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

5.2 Trenching/Excavating Phase

5.2.1 Trenching / Excavating Phase Timeline Assumptions

- Phase Start Date
 Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration
 Number of Month: 3
 Number of Days: 0

5.2.2 Trenching / Excavating Phase Assumptions

- General Trenching/Excavating Information
 Area of Site to be Trenched/Excavated (ft²): 47394
 Amount of Material to be Hauled On-Site (yd³): 0
 Amount of Material to be Hauled Off-Site (yd³): 0

- Trenching Default Settings
 Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Excavators Composite	2	8
Other General Industrial Equipmen Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust
 Average Hauling Truck Capacity (yd³): 20 (default)
 Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips
 Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

5.2.3 Trenching / Excavating Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.39317	0.00542	3.40690	4.22083	0.09860	0.09071
Other General Industrial Equipment Composite [HP: 35] [LF: 0.34]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.45335	0.00542	3.58824	4.59368	0.11309	0.10404
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839

- Construction Exhaust Greenhouse Gasses Pollutant Emission Factors (g/hp-hour) (default)

Excavators Composite [HP: 36] [LF: 0.38]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02381	0.00476	587.02896	589.04350
Other General Industrial Equipment Composite [HP: 35] [LF: 0.34]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02385	0.00477	587.87714	589.89459
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

5.2.4 Trenching / Excavating Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM_{10_{FD}} = (20 * ACRE * WD) / 2000$$

PM_{10_{FD}}: Fugitive Dust PM 10 Emissions (TONs)

20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)

ACRE: Total acres (acres)

WD: Number of Total Work Days (days)

2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * HP * LF * EF_{POL} * 0.002205) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment
 WD: Number of Total Work Days (days)
 H: Hours Worked per Day (hours)
 HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL}: Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
 HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
 HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
 HC: Average Hauling Truck Capacity (yd³)
 (1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Vehicle Exhaust On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 WD: Number of Total Work Days (days)
 WT: Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

5.3 Building Construction Phase

5.3.1 Building Construction Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration

Number of Month: 3
 Number of Days: 0

5.3.2 Building Construction Phase Assumptions

- General Building Construction Information

Building Category: Office or Industrial
 Area of Building (ft²): 47394
 Height of Building (ft): 65
 Number of Units: N/A

- Building Construction Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Cranes Composite	1	6
Forklifts Composite	2	6
Generator Sets Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8
Welders Composite	3	8

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

- Vendor Trips

Average Vendor Round Trip Commute (mile): 40 (default)

- Vendor Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

5.3.3 Building Construction Phase Emission Factor(s)

- Construction Exhaust Criteria Pollutant Emission Factors (g/hp-hour) (default)

Cranes Composite [HP: 367] [LF: 0.29]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.19758	0.00487	1.83652	1.63713	0.07527	0.06925
Forklifts Composite [HP: 82] [LF: 0.2]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.24594	0.00487	2.34179	3.57902	0.11182	0.10287
Generator Sets Composite [HP: 14] [LF: 0.74]						

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.53947	0.00793	4.32399	2.85973	0.17412	0.16019
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.18406	0.00489	1.88476	3.48102	0.06347	0.05839
Welders Composite [HP: 46] [LF: 0.45]						
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5
Emission Factors	0.46472	0.00735	3.57020	4.49314	0.09550	0.08786

- Construction Exhaust Greenhouse Gasses Pollutant Emission Factors (g/hp-hour) (default)

Cranes Composite [HP: 367] [LF: 0.29]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02140	0.00428	527.46069	529.27080
Forklifts Composite [HP: 82] [LF: 0.2]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02138	0.00428	527.09717	528.90603
Generator Sets Composite [HP: 14] [LF: 0.74]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02305	0.00461	568.32694	570.27730
Tractors/Loaders/Backhoes Composite [HP: 84] [LF: 0.37]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02149	0.00430	529.70686	531.52468
Welders Composite [HP: 46] [LF: 0.45]				
	CH ₄	N ₂ O	CO ₂	CO ₂ e
Emission Factors	0.02305	0.00461	568.29068	570.24091

- Vehicle Exhaust & Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Vehicle Exhaust & Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517
MC	0.11230	0.00331	391.17366	394.96854

5.3.4 Building Construction Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{\text{EOL}} = (NE * WD * H * HP * LF * EF_{\text{EOL}} * 0.002205) / 2000$$

CEE_{EOL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

HP: Equipment Horsepower
 LF: Equipment Load Factor
 EF_{POL} : Emission Factor for Pollutant (g/hp-hour)
 0.002205: Conversion Factor grams to pounds
 2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = BA * BH * (0.42 / 1000) * HT$$

VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 BA: Area of Building (ft²)
 BH: Height of Building (ft)
 (0.42 / 1000): Conversion Factor ft³ to trips (0.42 trip / 1000 ft³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VE} : Vehicle Exhaust Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 WD: Number of Total Work Days (days)
 WT: Average Worker Round Trip Commute (mile)
 1.25: Conversion Factor Number of Construction Equipment to Number of Works
 NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Vender Trips Emissions per Phase

$$VMT_{VT} = BA * BH * (0.38 / 1000) * HT$$

VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
 BA: Area of Building (ft²)
 BH: Height of Building (ft)
 (0.38 / 1000): Conversion Factor ft³ to trips (0.38 trip / 1000 ft³)
 HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds

EF_{poll}: Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

5.4 Architectural Coatings Phase

5.4.1 Architectural Coatings Phase Timeline Assumptions

- Phase Start Date
 Start Month: 1
 Start Quarter: 1
 Start Year: 2026

- Phase Duration
 Number of Month: 3
 Number of Days: 0

5.4.2 Architectural Coatings Phase Assumptions

- General Architectural Coatings Information
 Building Category: Non-Residential
 Total Square Footage (ft²): 47394
 Number of Units: N/A

- Architectural Coatings Default Settings
 Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Worker Trips
 Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

5.4.3 Architectural Coatings Phase Emission Factor(s)

- Worker Trips Criteria Pollutant Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	NH ₃
LDGV	0.26860	0.00172	0.11494	4.59156	0.00364	0.00322	0.05129
LDGT	0.22958	0.00212	0.14451	3.87645	0.00408	0.00361	0.04304
HDGV	0.88395	0.00483	0.59039	11.06281	0.01969	0.01741	0.09480
LDDV	0.08708	0.00132	0.14749	6.56557	0.00364	0.00335	0.01705
LDDT	0.15078	0.00150	0.41118	5.60763	0.00583	0.00536	0.01751
HDDV	0.10944	0.00419	2.34024	1.60034	0.04742	0.04363	0.06571
MC	3.20770	0.00193	0.54558	12.49470	0.02291	0.02026	0.05171

- Worker Trips Greenhouse Gasses Emission Factors (grams/mile)

	CH ₄	N ₂ O	CO ₂	CO ₂ e
LDGV	0.01351	0.00495	340.96759	342.77490
LDGT	0.01304	0.00715	419.83935	422.29139
HDGV	0.05499	0.02808	955.36623	965.09057
LDDV	0.04285	0.00073	393.05215	394.34113
LDDT	0.03067	0.00109	441.62237	442.71351
HDDV	0.01948	0.16187	1248.10200	1296.81517

MC	0.11230	0.00331	391.17366	394.96854
----	---------	---------	-----------	-----------

5.4.4 Architectural Coatings Phase Formula(s)

- Worker Trips Emissions per Phase

$$VMT_{WT} = (1 * WT * PA) / 800$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 1: Conversion Factor man days to trips (1 trip / 1 man * day)
 WT: Average Worker Round Trip Commute (mile)
 PA: Paint Area (ft²)
 800: Conversion Factor square feet to man days (1 ft² / 1 man * day)

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_{AC} = (AB * 2.0 * 0.0116) / 2000.0$$

VOC_{AC} : Architectural Coating VOC Emissions (TONs)
 AB: Area of Building (ft²)
 2.0: Conversion Factor total area to coated area (2.0 ft² coated area / total area)
 0.0116: Emission Factor (lb/ft²)
 2000: Conversion Factor pounds to tons

A.1.2.1

AIR CONFORMITY APPLICABILITY MODEL REPORT GREENHOUSE GAS (GHG) EMISSIONS

1. General Information: The Air Force's Air Conformity Applicability Model (ACAM) was used to perform an analysis to estimate GHG emissions and assess the theoretical Social Cost of Greenhouse Gases (SC GHG) associated with the action. The analysis was performed in accordance with the Air Force Manual 32-7002, Environmental Compliance and Pollution Prevention; the Environmental Impact Analysis Process (EIAP, 32 CFR 989); and the USAF Air Quality Environmental Impact Analysis Process (EIAP) Guide. This report provides a summary of GHG emissions and SC GHG analysis.

Report generated with ACAM version: 5.0.23a

a. Action Location:

Base: CAPE CANAVERAL AFS
State: Florida
County(s): Brevard
Regulatory Area(s): NOT IN A REGULATORY AREA

b. Action Title: SpaceX Starship-Heavy Launch Vehicle at Launch Complex 39A at the Kennedy Space Center, Cape Canaveral, Florida

c. Project Number/s (if applicable): N/A

d. Projected Action Start Date: 1 / 2026**e. Action Description:**

SpaceX's proposed operations include construction of a SpaceX starship-super heavy launch/landing pad and other launch support infrastructure at LC-39A, launches at LC-39A, landings at LC-39A, and landings in the ocean.

f. Point of Contact:

Name: Allison Williams
Title: Environmental Scientist
Organization: Leidos Corporation
Email: allison.williams@leidos.com
Phone Number: 719-470-9579

2. Analysis: Total combined direct and indirect GHG emissions associated with the action were estimated through ACAM on a calendar-year basis from the action start through the expected life cycle of the action. The life cycle for Air Force actions with "steady state" emissions (SS, net gain/loss in emission stabilized and the action is fully implemented) is assumed to be 10 years beyond the SS emissions year or 20 years beyond SS emissions year for aircraft operations related actions.

GHG Emissions Analysis Summary:

GHGs produced by fossil-fuel combustion are primarily carbon dioxide (CO₂), methane (CH₄), and nitrous oxide (NO₂). These three GHGs represent more than 97 percent of all U.S. GHG emissions. Emissions of GHGs are typically quantified and regulated in units of CO₂ equivalents (CO₂e). The CO₂e takes into account the global warming potential (GWP) of each GHG. The GWP is the measure of a particular GHG's ability to absorb solar radiation as well as its residence time within the atmosphere. The GWP allows comparison of global warming impacts between different gases; the higher the GWP, the more that gas contributes to climate change in comparison to CO₂. All GHG emissions estimates were derived from various emission sources using the methods, algorithms, emission factors, and GWPs from the most current Air Emissions Guide for Air Force Stationary Sources, Air Emissions Guide for Air Force Mobile Sources, and/or Air Emissions Guide for Air Force Transitory Sources.

The Air Force has adopted the Prevention of Significant Deterioration (PSD) threshold for GHG of 75,000 ton per year (ton/yr) of CO₂e (or 68,039 metric ton per year, mton/yr) as an indicator or "threshold of insignificance" for NEPA air quality impacts in all areas. This indicator does not define a significant impact; however, it provides a threshold to identify actions that are insignificant (de minimis, too trivial or minor to merit consideration). Actions with a net change in GHG (CO₂e) emissions below the insignificance indicator (threshold) are considered too insignificant on a global scale to warrant any further analysis. Note that actions with a net change in GHG (CO₂e) emissions above the insignificance indicator (threshold) are only considered potentially significant and require further assessment to determine if the action poses a significant impact. For further detail on insignificance indicators see Level II, Air Quality Quantitative Assessment, Insignificance Indicators (April 2023).

The following table summarizes the action-related GHG emissions on a calendar-year basis through the projected life cycle of the action.

Action-Related Annual GHG Emissions (mton/yr)						
YEAR	CO ₂	CH ₄	N ₂ O	CO ₂ e	Threshold	Exceedance
2026	1,317	0.03140643	0.11735438	1,353	68,039	No
2027 [SS Year]	0	0	0	0	68,039	No

The following U.S. and State's GHG emissions estimates (next two tables) are based on a five-year average (2016 through 2020) of individual state-reported GHG emissions (Reference: State Climate Summaries 2022, NOAA).

National Centers for Environmental Information, National Oceanic and Atmospheric Administration.
<https://statesummaries.ncics.org/downloads/>

State's Annual GHG Emissions (mton/yr)				
YEAR	CO ₂	CH ₄	N ₂ O	CO ₂ e
2026	227,404,647	552,428	58,049	228,015,124
2027 [SS Year]	0	0	0	0

U.S. Annual GHG Emissions (mton/yr)				
YEAR	CO ₂	CH ₄	N ₂ O	CO ₂ e
2026	5,136,454,179	25,626,912	1,500,708	5,163,581,798
2027 [SS Year]	0	0	0	0

GHG Relative Significance Assessment:

A Relative Significance Assessment uses the rule of reason and the concept of proportionality along with the consideration of the affected area (yGba.e., global, national, and regional) and the degree (intensity) of the proposed action's effects. The Relative Significance Assessment provides real-world context and allows for a reasoned choice against alternatives through a relative comparison analysis. The analysis weighs each alternative's annual net change in GHG emissions proportionally against (or relative to) global, national, and regional emissions.

The action's surroundings, circumstances, environment, and background (context associated with an action) provide the setting for evaluating the GHG intensity (impact significance). From an air quality perspective, context of an action is the local area's ambient air quality relative to meeting the NAAQSs, expressed as attainment, nonattainment, or maintenance areas (this designation is considered the attainment status). GHGs are non-hazardous to health at normal ambient concentrations and, at a cumulative global scale, action-related GHG emissions can only potentially cause warming of the climatic system. Therefore, the action-related GHGs generally have an insignificant impact to local air quality.

However, the affected area (context) of GHG/climate change is global. Therefore, the intensity or degree of the proposed action's GHG/climate change effects are gauged through the quantity of GHG associated with the action as compared to a baseline of the state, U.S., and global GHG inventories. Each action (or alternative) has significance, based on their annual net change in GHG emissions, in relation to or proportionally to the global, national, and regional annual GHG emissions.

To provide real-world context to the GHG and climate change effects on a global scale, an action's net change in GHG emissions is compared relative to the state (where action will occur) and U.S. annual emissions. The following table provides a relative comparison of an action's net change in GHG emissions vs. state and U.S. projected GHG emissions for the same time period.

Total GHG Relative Significance (mton)					
		CO ₂	CH ₄	N ₂ O	CO ₂ e
2026-2037	State Total	227,404,647	552,428	58,049	228,015,124
2026-2037	U.S. Total	5,136,454,179	25,626,912	1,500,708	5,163,581,798
2026-2037	Action	1,317	0.031406	0.117354	1,353
Percent of State Totals		0.00057909%	0.00000569%	0.00020216%	0.00059322%
Percent of U.S. Totals		0.00002564%	0.00000012%	0.00000782%	0.00002620%

From a global context, the action's total GHG percentage of total global GHG for the same time period is: 0.00000351% *

* Global value based on the U.S. emits 13.4% of all global GHG annual emissions (2018 Emissions Data, Center for Climate and Energy Solutions, accessed 7-6-2023, <https://www.c2es.org/content/international-emissions>).