

Date effective: June 11, 2018

The following sample questions for Private Pilot-Glider (PGL) are suitable study material for the Private Pilot-Glider Rating. These questions are a representation of questions that can be found on all Private Pilot-Glider Rating tests. The applicant must realize that these questions are to be used as a study guide, and are not necessarily actual test questions. The full PGL test contains 60 questions. The Application Identification, Information Verification, and Authorization Requirements Matrix lists all FAA exams. It is available at http://www.faa.gov/training_testing/testing/media/testing_matrix.pdf.

The FAA testing system is supported by a series of supplement publications. These publications include the graphics, legends, and maps that are needed to successfully respond to certain test questions. FAA-CT-8080-2H, Airman Knowledge Testing Supplement for Sport Pilot, Recreational Pilot, Remote Pilot, and Private Pilot is available at http://www.faa.gov/training_testing/testing/supplements/media/sport_rec_private_akts.pdf.

The Learning Statement Reference Guide for Airman Knowledge Testing contains listings of learning statements with their associated codes. Matching the learning statement codes with the codes listed on your Airman Knowledge Test Report assists in the evaluation of knowledge areas missed on your exam. It is available at http://www.faa.gov/training_testing/testing/media/LearningStatementReferenceGuide.pdf.

PGL Sample Questions:

1 . PLT245

A sailplane pilot can differentiate between a spin and a spiral dive because in a spiral dive,

- A) the speed remains constant.
- B) the G loads increase.
- C) there is a small loss of altitude in each rotation.

2 . PLT025

Which statement relates to Bernoulli's principle?

- A) For every action there is an equal and opposite reaction.
- B) An additional upward force is generated as the lower surface of the wing deflects air downward.
- C) Air traveling faster over the curved upper surface of an airfoil causes lower pressure on the top surface.

3 . PLT168

The term `angle of attack` is defined as the angle between the

- A) chord line of the wing and the relative wind.
- B) airplane's longitudinal axis and that of the air striking the airfoil.
- C) airplane's center line and the relative wind.

4 . PLT124

(Refer to FAA-CT-8080-2H, Figure 8.) What is the effect of a temperature increase from 35 to 50°F on the density altitude if the pressure altitude remains at 3,000 feet MSL?

- A) 1,000-foot increase.
- B) 1,100-foot decrease.
- C) 1,300-foot increase.

5 . PLT088

(Refer to FAA-CT-8080-2H, Figure 4.) Which color identifies the normal flap operating range?

- A) The yellow arc.
- B) The green arc.
- C) The white arc.

6 . PLT497

Unless otherwise authorized, if flying a transponder equipped aircraft, a pilot should squawk which VFR code?

- A) 1200.
- B) 7600.
- C) 7700.

7 . PLT215

In the Northern Hemisphere, if a glider is accelerated or decelerated, the magnetic compass will normally indicate

- A) a turn toward north while decelerating on an east heading.
- B) correctly only when on a north or south heading.
- C) a turn toward south while accelerating on a west heading.

8 . PLT088

(Refer to FAA-CT-8080-2H, Figure 4.) Which marking identifies the never-exceed speed?

- A) Upper limit of the green arc.
- B) Upper limit of the white arc.
- C) The red radial line.

9 . PLT215

Deviation error of the magnetic compass is caused by

- A) a northerly turning error.
- B) certain metals and electrical systems within the aircraft.
- C) the difference in location of true north and magnetic north.

10 . PLT088

(Refer to FAA-CT-8080-2H, Figure 4.) What is the caution range of the glider?

- A) 0 to 60 KTS.
- B) 100 to 165 KTS.
- C) 165 to 208 KTS.

11 . PLT497

When making routine transponder code changes, pilots should avoid inadvertent selection of which code?

- A) 7200.
- B) 7000.
- C) 7500.

12 . PLT077

(Refer to FAA-CT-8080-2H Figure 48.) The portion of the runway identified by the letter A may be used for

- A) landing.
- B) taxiing and takeoff.
- C) taxiing and landing.

13 . PLT141

(Refer to FAA-CT-8080-2H, Figure 64.) Which marking indicates a vehicle lane?

- A) A.
- B) C.
- C) E.

14 . PLT141

The `yellow demarcation bar` marking indicates

- A) a runway with a displaced threshold that precedes the runway.
- B) a hold line from a taxiway to a runway.
- C) the beginning of available runway for landing on the approach side.

15 . PLT141

This sign is a visual clue that

- A) confirms the aircraft's location to be on taxiway "B."
- B) warns the pilot of approaching taxiway "B."
- C) indicates "B" holding area is ahead.



16 . PLT141

This sign confirms your position on

- A) runway 22.
- B) routing to runway 22.
- C) taxiway 22.



17 . PLT141

From the cockpit, this marking confirms the aircraft to be

- A) on a taxiway, about to enter runway zone.
- B) on a runway, about to clear.
- C) near an instrument approach clearance zone.

18 . PLT393

What action should a pilot take when operating under VFR in a Military Operations Area (MOA)?

- A) Obtain a clearance from the controlling agency prior to entering the MOA.
- B) Operate only on the airways that transverse the MOA.
- C) Exercise extreme caution when military activity is being conducted.

19 . PLT161

The radius of the procedural outer area of Class C airspace is normally

- A) 10 NM.
- B) 20 NM.
- C) 30 NM.

20 . PLT204

(Refer to FAA-CT-80802H, Figure 75, west of Area 6.) During preflight planning, your course is plotted to fly through R-2305.

Where would you find additional information regarding this airspace?

- A) In the Aeronautical Information Manual.
- B) In the Chart Supplements U.S.
- C) On the Sectional Chart in the Special Use Airspace area.

21 . PLT161

The correct method of stating 5,500 feet MSL to ATC is

- A) 'FIVE POINT FIVE.'
- B) 'FIFTY-FIVE HUNDRED FEET MSL.'
- C) 'FIVE THOUSAND FIVE HUNDRED.'

22 . PLT161

If you are operating a glider equipped with a 4096 code radar beacon transponder and not in contact with an ATC facility, what is the transponder code you should be operating on (squawking)?

- A) 1202.
- B) 1200.
- C) 7700.

23 . PLT219

A pilot unintentionally enters a steep diving spiral to the left. What is the proper way to recover from this attitude without overstressing the glider?

- A) Apply up-elevator pressure to raise the nose.
- B) Apply more up-elevator pressure and then use right aileron pressure to control the overbanking tendency.
- C) Relax the back pressure and shallow the bank; then apply up-elevator pressure until the nose has been raised to the desired position.

24 . PLT221

The sailplane has become airborne and the towplane loses power before leaving the ground. The sailplane should release immediately,

- A) and maneuver to the right side of the runway.
- B) extend the spoilers, and land straight ahead.
- C) and maneuver to the left of the towplane.

25 . PLT221

What would be a proper action or procedure to use if the pilot is getting too low on a cross-country flight in a sailplane?

- A) Continue on course until descending to 1,000 feet above the ground and then plan the landing approach.
- B) Fly directly into the wind and make a straight-in approach at the end of the glide.
- C) Have a suitable landing area selected upon reaching 2,000 feet AGL, and a specific field chosen upon reaching 1,500 feet AGL.

26 . PLT006

A sailplane has a best glide ratio of 23:1. How many feet will the glider lose in 8 nautical miles?

- A) 1,840 feet.
- B) 2,100 feet.
- C) 2,750 feet.

27 . PLT103

What antidotal phrase can help reverse the hazardous attitude of impulsivity?

- A) Do it quickly to get it over with.
- B) It could happen to me.
- C) Not so fast, think first.

28 . PLT334

A lack of orientation with regard to the position, attitude, or movement of the aircraft in space is defined as

- A) spatial disorientation.
- B) hyperventilation.
- C) hypoxia.

29 . PLT332

A pilot experiencing the effects of hyperventilation should be able to restore the proper carbon dioxide level in the body by

- A) slowing the breathing rate, breathing into a paper bag, or talking aloud.
- B) breathing spontaneously and deeply or gaining mental control of the situation.
- C) increasing the breathing rate in order to increase lung ventilation.

30 . PLT099

Eye movements during daytime collision avoidance scanning should

- A) not exceed 10 degrees and view each sector at least 1 second.
- B) be 30 degrees and view each sector at least 3 seconds.
- C) use peripheral vision by scanning small sectors and utilizing off-center viewing.

31 . PLT012

How far will an aircraft travel in 7.5 minutes with a ground speed of 114 knots?

- A) 14.25 NM.
- B) 15.00 NM.
- C) 14.50 NM.

32 . PLT064

(Refer to FAA-CT-8080-2H, Figure 26, Area 2.) The day VFR visibility and cloud clearance requirements to operate over the town of Cooperstown, after departing and climbing out of the Cooperstown Airport at or below 700 feet AGL are

- A) 1 mile and clear of clouds.
- B) 1 mile and 1,000 feet above, 500 feet below, and 2,000 feet horizontally from clouds.
- C) 3 miles and clear of clouds.

33 . PLT078

(Refer to FAA-CT-8080-2H, Figure 52.) Where is Loup City Municipal located in relation to the city?

- A) Northeast approximately 3 miles.
- B) Northwest approximately 1 mile.
- C) East approximately 7 miles.

34 . PLT078

(Refer to FAA-CT-8080-2H, Figure 52.) When approaching Lincoln Municipal from the west at noon for the purpose of landing, initial communications should be with

- A) Lincoln Approach Control on 124.0 MHz.
- B) Minneapolis Center on 128.75 MHz.
- C) Lincoln Tower on 118.5 MHz.

35 . PLT101

(Refer to FAA-CT-8080-2H, Figure 25, Area 5.) The navigation facility at Dallas-Ft. Worth International (DFW) is a

- A) VOR.
- B) VORTAC.
- C) VOR/DME.

36 . PLT064

(Refer to FAA-CT-8080-2H, Figure 20, Area 1.) The NALF Fentress (NFE) Airport is in what type of airspace?

- A) Class C.
- B) Class E.
- C) Class G.

37 . PLT323

What information is contained in the Notices to Airmen Publication (NTAP)?

- A) Current NOTAM (D) and FDC NOTAMs.
- B) All current NOTAMs.
- C) Current Airport/Facility Directory information and FDC NOTAMs.

38 . PLT372

A 100-hour inspection was due at 3302.5 hours. The 100-hour inspection was actually done at 3309.5 hours. When is the next 100-hour inspection due?

- A) 3312.5 hours.
- B) 3395.5 hours.
- C) 3402.5 hours.

39 . PLT384

Pre-takeoff briefing of passengers about the use of seat belts for a flight is the responsibility of

- A) all passengers.
- B) the pilot in command.
- C) the right seat pilot.

40 . PLT371

With respect to the certification of airmen, which are categories of aircraft?

- A) Gyroplane, helicopter, airship, free balloon.
- B) Airplane, rotorcraft, glider, lighter-than-air.
- C) Single-engine land and sea, multiengine land and sea.

41 . PLT434

Two-way radio communication must be established with the Air Traffic Control facility having jurisdiction over the area prior to entering which class airspace?

- A) Class C.
- B) Class E.
- C) Class G.

42 . PLT502

A flashing white light signal from the control tower to a taxiing aircraft is an indication to

- A) taxi at a faster speed.
- B) taxi only on taxiways and not cross runways.
- C) return to the starting point on the airport.

43 . PLT496

The minimum allowable strength of a towline used for an aerotow of a glider having a certificated gross weight of 700 pounds is

- A) 560 pounds.
- B) 700 pounds.
- C) 1,000 pounds.

44 . PLT496

When using a towline having a breaking strength more than twice the maximum certificated operating weight of the glider, an approved safety link must be installed at what point(s)?

- A) Only the point where the towline is attached to the glider.
- B) The point where the towline is attached to the glider and the point of attachment of the towline to the towplane.
- C) Only the point where the towline is attached to the towplane.

45 . PLT163

During operations outside controlled airspace at altitudes of more than 1,200 feet AGL, but less than 10,000 feet MSL, the minimum flight visibility for day VFR flight is

- A) 1 mile.
- B) 3 miles.
- C) 5 miles.

46 . PLT496

The minimum allowable strength of a towline used for an aerotow of a glider having a certificated gross weight of 1,040 pounds is

- A) 502 pounds.
- B) 832 pounds.
- C) 1,040 pounds.

47 . PLT369

In which class of airspace is aerobatic flight prohibited?

- A) Class E airspace not designated for federal airways above 1,500 feet AGL.
- B) Class E airspace below 1,500 feet AGL.
- C) Class G airspace above 1,500 feet AGL.

48 . PLT411

Your cousin wants you to take him flying. You must have made at least three takeoffs and three landings in your aircraft within the preceding

- A) 90 days.
- B) 60 days.
- C) 30 days.

49 . PLT399

Each person who holds a pilot certificate or a medical certificate shall present it for inspection upon the request of any

- A) authorized representative of the Department of Transportation.
- B) person in a position of authority.
- C) local law enforcement officer.

50 . PLT366

The pilot of an aircraft that has been involved in an accident is required to file an NTSB accident report within how many days?

- A) 5.
- B) 7.
- C) 10.

51 . PLT163

During operations outside controlled airspace at altitudes of more than 1,200 feet AGL, but less than 10,000 feet MSL, the minimum distance below clouds requirement for VFR flight at night is

- A) 500 feet.
- B) 1,000 feet.
- C) 1,500 feet.

52 . PLT496

For the aerotow of a glider that weighs 700 pounds, which towrope tensile strength would require the use of safety links at each end of the rope?

- A) 850 pounds.
- B) 1,040 pounds.
- C) 1,450 pounds.

53 . PLT511

One weather phenomenon which will always occur when flying across a front is a change in the

- A) stability of the air mass.
- B) type of precipitation.
- C) wind direction.

54 . PLT192

When warm, moist, stable air flows upslope, it

- A) produces stratus type clouds.
- B) causes showers and thunderstorms.
- C) develops convective turbulence.

55 . PLT516

The wind at 5,000 feet AGL is southwesterly while the surface wind is southerly. This difference in direction is primarily due to

- A) stronger pressure gradient at higher altitudes.
- B) friction between the wind and the surface.
- C) stronger Coriolis force at the surface.

56 . PLT076

(Refer to FAA-CT-8080-2H, Figure 17.) What wind is forecast for STL at 12,000 feet?

- A) 230° true at 56 knots.
- B) 230° true at 39 knots.
- C) 230° magnetic at 56 knots.

57 . PLT514

In addition to the standard briefing, what additional information should be asked of the weather briefer in order to evaluate soaring conditions?

- A) The upper soundings to determine the thermal index at all soaring levels.
- B) Dry adiabatic rate of cooling to determine the height of cloud bases.
- C) Moist adiabatic rate of cooling to determine the height of cloud tops.

58 . PLT128

Why is frost considered hazardous to flight?

- A) Frost changes the basic aerodynamic shape of the airfoils, thereby increasing lift.
- B) Frost slows the airflow over the airfoils, thereby increasing control effectiveness.
- C) Frost spoils the smooth flow of air over the wings, thereby decreasing lifting capability.

59 . PLT021

(Refer to FAA-CT-8080-2H, Figure 53.) What is the CG of the glider if the pilot and passenger each weigh 215 pounds?

- A) 74.69 inches aft of datum - out of limits forward.
- B) 81.08 inches aft of datum - within limits.
- C) 81.08 inches aft of datum - over maximum gross weight.

60 . PLT256

(Refer to FAA-CT-8080-2H, Figure 53.) How is the CG affected if radio and oxygen equipment weighing 35 pounds is added at station 43.8? The glider weighs 945 pounds with a moment of 78,000.2 pound-inches prior to adding the equipment.

- A) CG shifts forward 0.79 inch - out of limits forward.
- B) CG shifts forward 1.38 inches - within limits.
- C) CG shifts aft 1.38 inches - out of limits aft.